

*** USER ACCOUNTS ***

* GUEST ACCOUNTS have very limited permissions, usually only accessing the intranet (if there is one), company directories, or online help.

- * EMPLOYEE ACCOUNTS grant permissions over anything in the employee's job description.

> thrusters from their terminal.

company sensitive information and files.

- personel, or officers on a ship.

- other connected Networks.

```
> data... everything.
```

go wild, they've earned it.

ways. For example:

- only be hacked manually.


- Networks unreachable through other means.

Think of Your Accounts as Assets to Manage

*** EQUIPMENT ***

- * Retrieves a map of all Nodes on a Network.

| mothershiprpg.com · Edited by JARRETT CRADER |



SCI-FI · HORROR · RPG

```
+-----=[ version 1.0 ]-----
```

sensitive information.

the door is opened. Easy.

```
a **NETWORK**.
```

#####

MRPG-A1

*** NETWORKS ***

A NETWORK is an interconnected system made up of a series of NODES. Networks can be big and sprawling with dozens of Nodes, or they can be small and simple, with only a couple of Nodes of note.

-- [Example: Jump-1 Research Vessel NOAH-IV] ---
This ship has 2 Networks (made of 6 Nodes each) connected via the Captain's Encrypted Terminal.

X===== [crew.net] =====X

INTRANET	INTRANET.HUB
UNSECURE	SECURE
DATABANK	ROUTER
NULL RESPONSE	+1 RESPONSE
GUEST.PC	
UNSECURED	
TERMINAL	
NULL RESPONSE	
EMPLOYEE1.PC	
BROKEN	
TERMINAL	
NULL RESPONSE	
CAPTAIN.PC	
ENCRYPTED	
TERMINAL	
+3 RESPONSE	
SUPER USER:	CAPTAIN.PDA
command.net	SECURE
	MOBILE TERMINAL
	+1 RESPONSE
	+Capt.'s PEK

X===== [command.net] =====X

FACILITIES.HUB	LIFE-SUP.CTRL
SECURE	HARDENED
ROUTER	INFRASTRUCTURE
+2 RESPONSE	+5 RESPONSE
	ENGINE.CTRL
	HARDENED
	INFRASTRUCTURE
	+4 RESPONSE
	JUMPNV.COMP
	HARDENED
	INFRASTRUCTURE
	+2 RESPONSE
COMMS.TERM	CORP.LINK
SECURE	ENCRYPTED
TERMINAL	UPLINK
+1 RESPONSE	NULL RESPONSE

*** NODES ***

A Node can represent a modems, hub, printer, computer, personal digital assistant, electronically controlled utility, or any other virtual software or connected device.

Each Node is defined by its FUNCTION, SECURITY, and RESPONSE.

-- [Function] -----

A Node's FUNCTION is a simple description of what the Node does. Several examples include:

- * ACCESS POINT: Grants entry to the Network.
- * DATA STORAGE: Contains valuable information (e.g. mission paydata, facility maps, storage manifests, user lists, camera recordings, etc.).
- * ROUTER: Allows communication to pass through this Node to other Modes connected to it. From a hacking perspective controlling such a node could allow a hacker to reconfigure Network paths to avoid more secure Nodes in a Network.
- * FIREWALL: A high Security and/or high Response Node designed to hinder hacking attempts.
- * INFRASTRUCTURE/HARDPOINT CONTROL: Grants control of connected location's infrastructure (e.g. airlocks, ventilation, doors, lights, cameras, engines, reactor, life support, weapons, etc.).
- * UPLINK/RELAY/BRIDGE: Connects one Network to one (or more) separate Networks.
- * TERMINAL: Physical interface (e.g. a personal computer) which allows the user to access its own contents and connect to the Network.

-- [Security] -----

A Node's SECURITY represents how difficult the Node's defenses are to penetrate. There are four levels:

- * UNSECURED NODES are open for anyone to use. They have no password protection or security of any kind.
- * SECURED NODES require a Hacking check to gain access to their contents.
- * HARDENED NODES are heavily fortified and require a *Hacking* [-] check to defeat.
- * ENCRYPTED NODES cannot be hacked with a *Hacking* check. Instead they require the PRIVATE ENCRYPTION KEY (PEK) of a user who has access to the network. PEKs can be acquired through theft, interrogation, social engineering, or hacking a lower security Node (like the target's personal computer) which contains the PEK.

These four levels allow you to quickly establish how hard the hack will be and communicate that to the hacker so they know what they're up against.

-- [Response] -----

A Network's RESPONSE measures how severe the reaction is from any network admins, operators, automated security features, overseer AIs, etc. safeguarding the network. A network's response is rated from Null (no roll required) to +5 (a rapid and severe response).

Whenever a hacker fails their *Hacking* check, roll on the RESPONSE TABLE and add the Network's Response.

+----- [RESPONSE TABLE] -----+

D10	RESPONSE
00	Warning message. Network's RESPONSE +1
01	Device is remotely powered off.
02	USER ACCOUNT locked out for 1d10 hours.
03	Security member dispatched to investigate. Arrives in 1d10 rounds.
04	Network creates "dummy" directories for the Hacker to search while a security team is sent to investigate.
05	The network and all linked networks are locked down for 1d10 hours.
06	This network and all linked networks increase security level by 1.
07	All linked networks increase RESPONSE +1
08	Facility blackout. All non-essential electronics powered down.
09+	TACTICAL RESPONSE TEAM deployed on Seek & Destroy mission. Arrives, heavily armed in 1d5 rounds.

Other examples of Responses include:

- * DENIAL OF SERVICE: NetSec blocks connections from the hacker's connected hardware by flooding the connection with garbage making future hacking attempts slower.
- * BACK HACK: NetSec attempts to control/destroy the terminal/deck/etc. being used in the attack.
- * MALWARE ATTACK: NetSec uses a virus to disable the hacker's hardware for some time.
- * POWER OVERLOAD: NetSec pushes excessive voltage to the hacker's hardware.
- * IDENTITY TRACE: NetSec attempts to obtain identifying information about the hacker.
- * NETWORK TRACE: NetSec attempts to locate the physical location hacker.