

Meteory Dry Chemical Powder Fire Extinguishers Stored Pressure



Application

- Meteory Dry Chemical Powder Fire Extinguisher Stored Pressure is effective in Classes (A, B & C).
- Model : M1,M3,M6,M9,&M12

Agent Specifications

- The cylinder is packed with Dry Chemical Powder which is a non-toxic material.
- Has the required extinguishing ability without any change in mechanical properties as flow, solidification, moisture effect.

Capacities

Meteory Dry Chemical Powder Fire Extinguishers' Stored Pressure Capacities are (1, 3, 6, 9 & 12) Kg.

Coating

Electrostatic Painted (RAL 3000).

Quality

- Designed, Manufactured, and Tested according to Egyptian Standard Specifications No: 8442/2021.
- ISO 9001 certified.
- Egyptian Quality Mark Certified

Warranty

- 2 years warranty against material failure and production defects.

visit us



Meteory®

Fire Extinguishers

Features

- Meteory Dry Chemical Powder Fire Extinguishers Stored Pressure is suitable for protecting warehouses, residential buildings, and vehicles.
- Designed as welded cylinders for all capacities.
- Designed with a body thickness of 2 mm
- Top and bottom thickness of 2.5 mm.
- Equipped with a Brass valve.
- Equipped with a plastic nozzle for 1, 3 kg.
- Equipped with a high-pressure hose and a plastic nozzle for 6, 9 & 12 Kg.
- Equipped with a plastic hand for 1 kg.
- Equipped with a metal hand for 3, 6, 9 & 12Kg.
- Delivered with its special bracket.
- Applicable for class E up to 1000 V.
- Brass head with operating lever maximizes performance
- Allows intermittent and repeated operation.
- Ease of operation and handling.
- High-quality coating.



Technical Specification

Capacity	1, 3, 6, 9, & 12 Kg.
Model	M1,M3,M6,M9,&M12
Extinguishing Agent	Multipurpose Powder
Working Temperature Range	-20 °C to 70 °C
Cylinder Material	Cold drawn steel
Working Pressure	17.5 bar
Testing Pressure	35 bar
Bursting Pressure Min	70bar
Valve Material	Brass valve
Discharge Fitting	(50:60) cm long high pressure reinforced rubber hose.
Paint Outside	Electrostatic Painted (RAL 3000)
Period of Warranty	2 Years



Fire Rating

Capacities	A	B
1 Kg	5&8	21&34
3 Kg	13&21	55&70
6 Kg	27,34&43	113&144&183
9 Kg	34,43&55	144&183
12 Kg	43&55	183&233

