

Meteory Co2 Fire Extinguishers



Application

- Meteory Carbon Dioxide fire extinguisher is effective in Classes (B, C & E).
- Model : Co2 2, Co2 3, Co2 6, Co2 10, Co2 (2*6), Co2 (2*10) & Co2 45.

Agent Specifications

- The cylinder is packed with carbon dioxide that leaves no trace after the extinguishing process.

Capacities

- Meteory Co2 fire Extinguishers' Capacities are (2, 3, 6, 10, (2*6), (2*10) & 45) Kg.

Coating

- Electrostatic Painted (RAL 3000) on the outside.

Quality

- Designed, Manufactured, and Tested according to Egyptian Standard Specifications No, 735 /2015 for (2-3-6) Kg capacities.
- Designed, Manufactured, and Tested according to Egyptian Standard Specifications No, 6115/2007 for (10 & 45) Kg capacities.
- ISO 9001 certified.

Warranty

- 2 years warranty Against material failure or production defects.

visit us



Features

- Designed as seamless cylinder for all capacities.
- Designed as a portable fire extinguisher for 2, 3 & 6 kg.
- Designed as a trolley fire extinguisher for 10, (2*10) & 45 kg.
- Equipped with a brass valve.
- Equipped with a plastic nozzle for 2 & 3 kg.
- Equipped with a high-pressure hose and a plastic nozzle for 6, 10, (2*10) & 45 kg.
- Allows intermittent and repeated operation.
- Ease of operation and handling.
- High-Quality electrostatic coating.



Technical Specification

Capacity	2,3,6, 10, (2*6), (2*10) & 45 kg.
Model	Co2 2, Co2 3, Co2 6, Co2 10, Co2 (2*6), Co2 (2*10) & Co2 45
Extinguishing Agent	CO2
Working Temperature Range	-20 °C to 70 °C
Cylinder Material	Seamless steel cylinder
Working Pressure	100 bar
Testing Pressure	200 bar
Bursting Pressure Min.	400 bar
Valve Material	Brass valve with overpressure safety valve
Paint Finish Surface	Electro-static painted
Period of Warranty	2 Years
Coverage of the Warranty	Against material failure or production defects

visit us

