

Meteory Automatic Dry Chemical Fire Extinguishers



Application

- Meteory Automatic Dry Chemical Powder Fire Extinguisher is effective in Classes (A, B & C).
- Model: MAtuto 6, MAuto 9, MAuto 12.

Agent Specifications

- The cylinder is packed with a Dry Chemical Powder which is a non-toxic material.
- Has the required extinguishing ability without any change in mechanical properties as flow, solidification, and moisture effect.

Capacities

- Meteory Automatic Dry Chemical Powder Fire Extinguishers' Capacities are (6, 9 & 12) Kg.

Coating

- Corrosion-resistant treated and coated on the inside.
- Electrostatic Painted (RAL 3000) on the outside.

Quality

- Designed, Manufactured and Tested according to Egyptian Standard Specifications No: 5680/2013.
- ISO 9001 certified

Warranty

- 2 years warranty against material failure and production defects.

visit us



Features

- Meteory Automatic Dry Chemical Powder Fire Extinguishers are suitable for protecting warehouses, residential buildings & vehicles.
- Equipped with a sensitive heat-bulb that works automatically when the temperature reaches 68 degrees celsius and without any human interference, The control valve is completely closed and does not allow air moisture to leak into the agent inside the cylinder.
- The cylinder can be fixed securely to the ceiling with a special mounting bracket.
- The cylinder does not have any openings other than the head hole.
- The cylinder body thickness not less than 2 mm top and bottom thickness 2.5 mm.
- Ease of operation.
- High-quality coating.



Technical Specification

Capacity	6, 9 & 12 kg
Model	MAtuto 6, MAuto 9, MAuto 12.
Extinguishing Agent	Multipurpose Powder
Working Temperature Range	-20°C to +68 °C, Do not use outside the specified temperature range
Cylinder Material	Cold drawn steel
Working Pressure	17.5 bar
Testing Pressure	35 bar
Bursting Pressure Min	70 bar
Head Material	Brass head
Paint On The Inside	Corrosion-resistant treated and coated on the inside.
Paint On The Outside	Electrostatic Painted (RAL 3000) on the outside.
Period of Warranty	2 Years
Coverage of the Warranty	Against material failure or production defects



Fire Rating

Capacities	A	B
6 Kg	27,34&43	113&144
9 Kg	34,43&55	144&183
12 Kg	43&55	183&233

Immersion space

weight	Ceiling height	Immersion space
6 kg	(Max) 3m	6 m ²
9 kg	(Max) 4m	9 m ²
12 kg	(Max) 5m	12 m ²

