

Meteory Trolley Dry Chemical Powder Fire Extinguishers with External Cartridge



Application

- Meteory Trolley Dry Chemical Powder Fire Extinguishers with External Cartridge is effective in Classes (A, B & C).
- Model: MET 30, MET 50, MET 75 & MET 100.

Agent Specifications

- The cylinder is packed with a Dry Chemical Powder which is a non-toxic material.
- Has the required extinguishing ability without any change in mechanical properties as flow, solidification, and moisture effect.

Capacities

- Meteory Trolley Dry Chemical Powder Fire Extinguishers with External Cartridge Capacities are (30, 50 ,75 & 100) Kg.

Coating

- Corrosion-resistant treated and coated on the inside.
- Electrostatic Painted (RAL 3000) on the outside.

Quality

- Designed, Manufactured and Tested according to Egyptian Standard Specifications No: 1494/2007.
- ISO 9001 certified

Warranty

- 2 years warranty against material failure and production defects.

visit us



Features

- Thickness Body 3 mm top and bottom 3.5 mm for 30 kg.
- Thickness Body 5 mm top and bottom 6 mm for 50 & 70 kg.
- Thickness Body 8 mm top and bottom 9 mm for 100 kg.
- Equipped with a Safety Release Valve.
- Equipped with a Manometer to determine the operating pressure.
- Equipped with a rubber hose.
- Equipped with a high-pressure Nitrogen external cartridge with a burst pressure of 600 bar.
- Equipped with 3 wheels to be easily moved.
- Allows intermittent and repeated operation.
- Ease of operation and handling.
- High-Quality coating.



Technical Specification

Capacity	30, 50, 75 & 100 kg
Model	MET 30, MET 50, MET 75 & MET 100
Extinguishing Agent	Multipurpose Powder
Working Temperature Range	-20°C to +70 °C
Cylinder Material	Cold drawn steel
Working Pressure	17.5 bar
Testing Pressure	35 bar
Bursting Pressure Min	70 bar
Valve Material	Brass valve
Discharge Fitting	long high pressure reinforced rubber hose
Paint On The Inside	Corrosion-resistant treated and coated
Paint On The Outside	Electrostatic Painted (RAL 3000)
Period of Warranty	2 Years
Coverage of the Warranty	Against material failure or production defects

Fire Rating

Capacities	A	B
1 Kg	5&8	21&34
3 Kg	13&21	55&70
6 Kg	27,34&43	113&144&183
9 Kg	34,43&55	144&183
12 Kg	43&55	183&233

