

Meteory Foam Fire Extinguishers



Application

- Meteory Foam Fire Extinguisher is effective in Classes (B & C).
- Model: F 9, F 30, F 50, F 75 & F 100.

Agent Specifications

- Using AFFF 1 : 6 % .

Capacities

- Meteory Foam Fire Extinguishers' Capacities are (9, 30, 50, 75 & 100) liter.

Coating

- Corrosion-resistant treated and coated from inside.
- Polyester painted from outside.

Quality

- Designed, Manufactured and Tested according to Egyptian Standard Specifications No, 4105 /2007 (9) Liter.
- Designed, Manufactured and Tested according to Egyptian Standard Specifications No, 1686 /2007 (30-50-75-100) Liter capacities.
- ISO 9001 certified

Warranty

- 2 years warranty against material failure and production defects.

visit us



Features

- Meteory Foam fire extinguisher is effective in fighting flammable and combustible liquids and gases.
- The body of the device is made of cold-drawn steel with a thickness of at least 2 mm for the face.
- Equipped with a safety release valve for safe operation.
- Equipped with Manometer to determine operating pressure.
- Equipped with high-pressure hose assembly with foam gun and nozzles for long through.
- Equipped with a high-pressure external cartridge filled with Nitrogen with burst pressure 600 bar.
- An AFFF 1: 6 % charge is enclosed in a separate cartridge, that instantly mixes with the water only at operation.
- Equipped with 3 wheels to easily move.
- Allows intermittent and repeated operation.
- Easy operation and handling.
- High-Quality Coating.



Technical Specification

Capacity	9, 30, 50, 75 & 100 liter.
Model	F 9, F 30, F 50, F 75 & F 100
Extinguishing Agent	AFFF 1 : 6 % .
Working Temperature Range	-20 °C to 70 °C
Cylinder Material	Cold drawn steel
Working Pressure	17.5 bar
Testing Pressure	35 bar
Bursting Pressure Min	70 bar
Valve Material	Brass valve
Paint On The Inside	Corrosion-resistant treated and coated
Paint On The Outside	Polyester Painted
Period of Warranty	2 Years
Coverage of the Warranty	Against material failure or production defects

