

GLT API

Adrián Castelló 03/07/16

GLT (Generic Lightweight Threads)

- GLT != Specification
- MassiveThreads, Qthreads and Argobots
- Two parts
 - CORE: Functionality supported by all the libraries
 - Extended: All the functionality allowed by each library
- Two implementations
 - Static library
 - Better performance expected
 - Needs recompilation
 - Dynamic library
 - Does not need recompilation

CORE

Module	Number of functions
Init & Finalize	2
Work unit management*	18
Mutex	5
Barrier	3
Condition	5
Timer	6
Helper functions	2
Query functions+	27

* Tasklets and ULTs (If a library does not allow the use of tasklets, a ULT is used)

+ One for each module of the extended implementation

Extended modules

MassiveThreads	Qthreads	Argobots
WS API	Basic	Event
Profiling	Atomic	Future
Log	FEB	Promise
Seralize	Reduction (Sinc)	Extended mutex
Key (TLS)*	Loop	Key (TLS)*
Felock	Util	Self
Extended Work units	Data Structures	Pools
	Syscall	Scheduler
	Extended Runtime	Threads
	Memory	Extended Tasklets
		Extended ULTs

*Same functionality but it can not be implemented with Qthreads primitives

Programming Model I

- By default one thread per logical CPU is created
- GLT_NUM_THREADS environment variable can change the number
- MassiveThreads
 - MYTH_WORKER_NUM can be used if the first one is not set
- Qthreads
 - QTHREADS_NUM_SHEPHERDS can be used if the first one is not set
 - GLT_NUM_WORKERS_PER_THREAD or QTHREAD_NUM_WORKERS_PER_SHEPHERD defines the number of workers managed by each thread (1 by default)
- Argobots
 - GLT_NUM_POOLS defines the total number of pools (1 for each threads by default)
 - If less pools than threads are created, they are shared and assigned using a round-robin mechanism
 - In the extended version, programmers can create as many threads and pools (and schedulers) as they need but the management will be controlled by them

Programming Model II

- Thread AFFINITY is enabled by default
- Qthreads
 - If just one thread (Shepherd) and more than one worker are created, the thread is bounded to a node and the workers to a cores.
 - If more than one thread is created, it is bounded to a core