Options

key	...pow	Origin	...Gall	Name	...erati	Year	...in_lt	...linde	...eme
0	130	USA	18	chevro...	12	1970-0...	3504	8	307
1	165	USA	15	buick s...	11.5	1970-0...	3693	8	350
2	150	USA	18	plymo...	11	1970-0...	3436	8	
3	150	USA	16	amc re...	12	1970-0...	3433	8	
4	140	USA	17	ford to...	10.5	1970-0...	3449	8	
5	198	USA	15	ford ga...	10	1970-0...	4341	8	
6	220	USA	14	chevro...	9	1970-0...	4354	8	454
7	215	USA	14	plymo...	8.5	1970-0...	4312	8	440
	225	USA	14	pontia...	10	1970-0...	4425	8	455
	190	USA	15	amc a...	8.5	1970-0...	3850	8	390
	115	Europe	*NaN*	citroen...	17.5	1970-0...	3090	4	133
	165	USA	*NaN*	chevro...	11.5	1970-0...	4142	8	350
12	153	USA	*NaN*	ford to...	11	1970-0...	4034	8	351
13	175	USA	*NaN*	plymo...	10.5	1970-0...	4166	8	383

1

2

Search: remove missing values

3

dropna 0.55 dropna Copy

```
Return a new Series with missing values removed.

        See the :ref:`User Guide <missing_data>` for more on which values are
        considered missing, and how to work with missing data.

        Parameters
        ----------
        axis : {0 or 'index'}
            Unused. Parameter needed for compatibility with DataFrame.
        inplace : bool, default False
            If True, do operation inplace and return None.
        how : str, optional
            Not in use. Kept for compatibility.
```

notna 0.49 notna Copy

```
Detect existing (non-missing) values.
```

isna 0.47 isna Copy

```
Detect missing values.
```

pad 0.45 pad Copy

```
Synonym for :meth:`DataFrame.fillna` with ``method='ffill'``.
```

backfill 0.45 backfill Copy

```
Synonym for :meth:`DataFrame.fillna` with ``method='bfill'``.
```

ne 0.44 ne Copy

```
Return Not equal to of series and other, element-wise (binary operator `ne`).
```