



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Neural Networks

K. Breininger, F. Denzinger, F. Thamm, Z. Yang, N. Maul, F. Meister, C. Liu, S. Jaganathan, L. Folle,
M. Vornehm, A. Popp, B. Geissler, S. Mehlretter, N. Patel, V. Bacher, K. Fischer
Pattern Recognition Lab, Friedrich-Alexander University of Erlangen-Nürnberg
November 8, 2020



Flexibility vs. Abstraction

Low level

High level



- Linear Algebra operations
- Bare metal





- Compiles graphs of Tensor operations
- High flexibility



- Stacks together elementary layers
- Reduced flexibility

Artificial Neural Networks



$$y = f\left(\sum_i^N w_i x_i\right)$$



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Neural Network



Neural Network

In layer-oriented frameworks we typically have a neural network object which:

Neural Network

In layer-oriented frameworks we typically have a neural network object which:

- is responsible for holding a **graph of layers**, whereas a "layer" represents a function (e.g. ReLU) or operation (e.g. convolution)
 - we allow only extremely simple graphs
 - with a list of layers
 - and only one data source
 - and one loss function

Neural Network

In layer-oriented frameworks we typically have a neural network object which:

- is responsible for holding a **graph of layers**, whereas a "layer" represents a function (e.g. ReLU) or operation (e.g. convolution)
 - we allow only extremely simple graphs
 - with a list of layers
 - and only one data source
 - and one loss function
- is responsible to hold **access to data**

Neural Network

In layer-oriented frameworks we typically have a neural network object which:

- is responsible for holding a **graph of layers**, whereas a "layer" represents a function (e.g. ReLU) or operation (e.g. convolution)
 - we allow only extremely simple graphs
 - with a list of layers
 - and only one data source
 - and one loss function
- is responsible to hold **access to data**
- has **no explicit knowledge** about the graph of layers it contains

Neural Network

In layer-oriented frameworks we typically have a neural network object which:

- is responsible for holding a **graph of layers**, whereas a "layer" represents a function (e.g. ReLU) or operation (e.g. convolution)
 - we allow only extremely simple graphs
 - with a list of layers
 - and only one data source
 - and one loss function
- is responsible to hold **access to data**
- has **no explicit knowledge** about the graph of layers it contains
- **recursively calls forward** on its layers passing the input-data
- **recursively calls backward** on its layers passing the error

Neural Network

In layer-oriented frameworks we typically have a neural network object which:

- is responsible for holding a **graph of layers**, whereas a "layer" represents a function (e.g. ReLU) or operation (e.g. convolution)
 - we allow only extremely simple graphs
 - with a list of layers
 - and only one data source
 - and one loss function
- is responsible to hold **access to data**
- has **no explicit knowledge** about the graph of layers it contains
- **recursively calls forward** on its layers passing the input-data
- **recursively calls backward** on its layers passing the error
- in our case stores the loss over iterations, while in other frameworks this is commonly separated into an optimizer class




FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING


Fully Connected Layer



Forward




Forward



$$\begin{pmatrix} w_1 \\ \vdots \\ w_n \end{pmatrix}^T \begin{pmatrix} x_1 \\ \vdots \\ x_n \end{pmatrix} + w_{n+1} = \hat{y}$$

$$\mathbf{w}^T \mathbf{x} = \hat{y}$$


Forward




$$\begin{pmatrix} w_1 \\ \vdots \\ w_n \\ w_{n+1} \end{pmatrix}^T \begin{pmatrix} x_1 \\ \vdots \\ x_n \\ 1 \end{pmatrix} = \hat{y}$$

$$\mathbf{w}^T \mathbf{x} = \hat{y}$$

Forward




Forward



$$\begin{pmatrix} w_{1,1} & \dots & w_{1,m} \\ \vdots & \ddots & \vdots \\ w_{n,1} & \dots & w_{n,m} \\ w_{n+1,1} & \dots & w_{n+1,m} \end{pmatrix}^T \begin{pmatrix} x_1 \\ \vdots \\ x_n \\ 1 \end{pmatrix} = \begin{pmatrix} \hat{y}_1 \\ \vdots \\ \hat{y}_m \end{pmatrix}$$

$$\mathbf{W}\mathbf{x} = \hat{\mathbf{y}}$$

Forward



$$\begin{pmatrix} w_{1,1} & \dots & w_{1,m} \\ \vdots & \ddots & \vdots \\ w_{n,1} & \dots & w_{n,m} \\ w_{n+1,1} & \dots & w_{n+1,m} \end{pmatrix}^T \begin{pmatrix} x_{1,1} & \dots & x_{1,b} \\ \vdots & \ddots & \vdots \\ x_{n,1} & \dots & x_{n,b} \\ 1 & \dots & 1 \end{pmatrix}$$

$$\mathbf{WX} = \hat{\mathbf{Y}} \quad (1)$$

Backward

- Return gradient with respect to **X**:

Backward

- Return gradient with respect to **X**:

$$\mathbf{E}_{n-1} = \mathbf{W}^T \mathbf{E}_n \quad (2)$$

- **E_n**: **error_tensor** passed downward

Backward

- Return gradient with respect to **X**:

$$\mathbf{E}_{n-1} = \mathbf{W}^T \mathbf{E}_n \quad (2)$$

- Update **W** using gradient with respect to **W**:

- **E_n**: **error_tensor** passed downward

Backward

- Return gradient with respect to \mathbf{X} :

$$\mathbf{E}_{n-1} = \mathbf{W}^T \mathbf{E}_n \quad (2)$$

- Update \mathbf{W} using gradient with respect to \mathbf{W} :


$$\mathbf{W}^{t+1} = \mathbf{W}^t - \eta \cdot \mathbf{E}_n \mathbf{X}^T \quad (3)$$

Note: Dynamic programming part of Backpropagation


- \mathbf{E}_n : **error_tensor** passed downward
- η : learning rate

Memory Layout

- Numpy uses C ordering by default
- Wrong ordering will cause strided data access
- We want the batch size to be the outermost loop
→ We have to adjust our formulas for the implementation



Forward - Our Memory Layout



$$\begin{pmatrix} x_{1,1} & \dots & x_{1,b} \\ \vdots & \ddots & \vdots \\ x_{n,1} & \dots & x_{n,b} \\ 1 & \dots & 1 \end{pmatrix}^T \begin{pmatrix} w_{1,1} & \dots & w_{1,m} \\ \vdots & \ddots & \vdots \\ w_{n,1} & \dots & w_{n,m} \\ w_{n+1,1} & \dots & w_{n+1,m} \end{pmatrix}$$

$$\mathbf{x}'\mathbf{w}' = \hat{\mathbf{y}}' \quad (4)$$

with

$$\mathbf{x}' = \mathbf{x}^T, \mathbf{w}' = \mathbf{w}^T, \hat{\mathbf{y}}' = \hat{\mathbf{y}}^T \quad (5)$$

$$\hat{\mathbf{y}}^T = (\mathbf{w}\mathbf{x})^T = \mathbf{x}^T\mathbf{w}^T \quad (6)$$

Backward - Our Memory Layout

- Return gradient with respect to \mathbf{X} :

$$\mathbf{E}'_{n-1} = \mathbf{E}'_n \mathbf{W}'^T \quad (7)$$

- Update \mathbf{W}' using gradient with respect to \mathbf{W}' :

$$\mathbf{W}'^{t+1} = \mathbf{W}'^t - \eta \cdot \mathbf{X}'^T \mathbf{E}'_n \quad (8)$$

Note: Dynamic programming part of Backpropagation

- \mathbf{E}'_n : **error_tensor** passed downward
- η : learning rate



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Basic Optimization



SGD

- In order to perform the aforementioned weight update we make use of a dedicated optimizer.
- In the first exercise we implement the Stochastic Gradient Descent Algorithm

$$\mathbf{w}^{(k+1)} = \mathbf{w}^{(k)} - \eta \underbrace{\nabla L(\mathbf{w}^{(k)})}_{\text{Gradient}}$$

where η denotes the learning rate.




FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

ReLU Activation Function



Forward



Backward

ReLU is not continuously differentiable!

Backward

ReLU is not continuously differentiable!

$$e_{n-1} = \begin{cases} 0 & \text{if } x \leq 0 \\ e_n & \text{else} \end{cases} \quad (9)$$

Note: DP part of Backpropagation yet again

Backward

ReLU is not continuously differentiable!

$$e_{n-1} = \begin{cases} 0 & \text{if } x \leq 0 \\ e_n & \text{else} \end{cases} \quad (9)$$

Note: DP part of Backpropagation yet again

- The scalar e is because activation functions operate elementwise on \mathbf{E}

Backward

ReLU is not continuously differentiable!

$$e_{n-1} = \begin{cases} 0 & \text{if } x \leq 0 \\ e_n & \text{else} \end{cases} \quad (9)$$

Note: DP part of Backpropagation yet again

- The scalar e is because activation functions operate elementwise on \mathbf{E}

- If you wonder about e_n instead of 1 consider that this is $\underbrace{\frac{\partial L}{\partial \hat{\mathbf{y}}}}_{\mathbf{E}} \cdot \underbrace{\frac{\partial \hat{\mathbf{y}}}{\partial \mathbf{x}}}_{\text{ReLU}}$



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

SoftMax Activation Function



Forward

Labels as N -dimensional **one hot** vector \mathbf{y} :

$$\begin{pmatrix} \vdots \\ 1 \\ \vdots \end{pmatrix}$$

Forward

Labels as N -dimensional **one hot** vector \mathbf{y} :

$$\begin{pmatrix} \vdots \\ 1 \\ \vdots \end{pmatrix}$$

- Activation(Prediction) $\hat{\mathbf{y}}$ for every element of the batch of size B :

$$\hat{y}_k = \frac{\exp(x_k)}{\sum_{j=1}^N \exp(x_j)} \quad (10)$$

Numeric

- If $x_k > 0 \rightarrow e^{x_k}$ might become very large
- To increase numerical stability x_k can be shifted
- $\tilde{x}_k = x_k - \max(\mathbf{x})$
- This leaves the scores unchanged!

$$\frac{\exp(\tilde{x}_k)}{\sum_j \exp(\tilde{x}_j)} = \frac{\exp(x_k) \cdot \cancel{\exp(-x_{\max})}}{\sum_j \exp(x_j) \cdot \cancel{\exp(-x_{\max})}} \quad \checkmark$$

Backward

- Compute for every element of the batch:

$$\mathbf{E}_{n-1} = \hat{y} \left(\mathbf{E}_n - \sum_{j=1}^N \mathbf{E}_{n,j} \hat{y}_j \right) \quad (11)$$

Backward

- Compute for every element of the batch:

$$\mathbf{E}_{n-1} = \hat{y} \left(\mathbf{E}_n - \sum_{j=1}^N \mathbf{E}_{n,j} \hat{y}_j \right) \quad (11)$$

- All operations are element-wise

Backward

- Compute for every element of the batch:

$$\mathbf{E}_{n-1} = \hat{y} \left(\mathbf{E}_n - \sum_{j=1}^N \mathbf{E}_{n,j} \hat{y}_j \right) \quad \checkmark \quad (11)$$

- All operations are element-wise
- Notice the similarity to the sigmoid gradient $\hat{y}(1 - \hat{y})$



FRIEDRICH-ALEXANDER-
UNIVERSITÄT
ERLANGEN-NÜRNBERG
SCHOOL OF ENGINEERING

Cross Entropy Loss



Forward

$$loss = \sum_{b=1}^B -\ln(\hat{y}_k + \epsilon) \text{ where } y_k = 1 \quad (12)$$

- ϵ represents the smallest representable number. Take a look into *np.finfo.eps*
- ϵ increases stability for very wrong predictions to prevent values close to $\log(0)$

Forward

$$loss = \sum_{b=1}^B -\ln(\hat{y}_k + \epsilon) \text{ where } y_k = 1 \quad (12)$$

- ϵ represents the smallest representable number. Take a look into *np.finfo.eps*
- ϵ increases stability for very wrong predictions to prevent values close to $\log(0)$
- Notice: the Cross Entropy Loss requires predictions to be greater than 0,
- thus the Cross Entropy Loss works most stable with SoftMax predictions.

Backward

$$\mathbf{E}_n = -\frac{y}{\hat{y}} \quad (13)$$

- ϵ cancels out due to derivation. An additional ϵ would distort the gradient dramatically!
- The gradient prohibits predictions of 0 as well.

Backward

$$\mathbf{E}_n = -\frac{y}{\hat{y}} \quad (13)$$

- ϵ cancels out due to derivation. An additional ϵ would distort the gradient dramatically!
- The gradient prohibits predictions of 0 as well.
- Notice that this does **not** depend on an error \mathbf{E} .
→ it's the starting point of the recursive computation of gradients.



Thanks for listening.
Any questions?