```
!pip install pandas matplotlib seaborn sqlalchemy statsmodels
```

```
Requirement already satisfied: pandas in /usr/local/lib/python3.12/dist-packages (2.2.2)
Requirement already satisfied: matplotlib in /usr/local/lib/python3.12/dist-packages (3.10.0)
Requirement already satisfied: seaborn in /usr/local/lib/python3.12/dist-packages (0.13.2)
Requirement already satisfied: sqlalchemy in /usr/local/lib/python3.12/dist-packages (2.0.49)
Requirement already satisfied: statsmodels in /usr/local/lib/python3.12/dist-packages (0.14.6)
Requirement already satisfied: numpy>=1.26.0 in /usr/local/lib/python3.12/dist-packages (from pandas) (2.0.2)
Requirement already satisfied: python-dateutil>=2.8.2 in /usr/local/lib/python3.12/dist-packages (from pandas) (2.9.0.post0)
Requirement already satisfied: pytz>=2020.1 in /usr/local/lib/python3.12/dist-packages (from pandas) (2025.2)
Requirement already satisfied: tzdata>=2022.7 in /usr/local/lib/python3.12/dist-packages (from pandas) (2026.1)
Requirement already satisfied: contourpy>=1.0.1 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (1.3.3)
Requirement already satisfied: cycler>=0.10 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (0.12.1)
Requirement already satisfied: fonttools>=4.22.0 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (4.62.1)
Requirement already satisfied: kiwisolver>=1.3.1 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (1.5.0)
Requirement already satisfied: packaging>=20.0 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (26.0)
Requirement already satisfied: pillow>=8 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (11.3.0)
Requirement already satisfied: pyparsing>=2.3.1 in /usr/local/lib/python3.12/dist-packages (from matplotlib) (3.3.2)
Requirement already satisfied: greenlet>=1 in /usr/local/lib/python3.12/dist-packages (from sqlalchemy) (3.4.0)
Requirement already satisfied: typing-extensions>=4.6.0 in /usr/local/lib/python3.12/dist-packages (from sqlalchemy) (4.15.0
Requirement already satisfied: scipy!=1.9.2,>=1.8 in /usr/local/lib/python3.12/dist-packages (from statsmodels) (1.16.3)
Requirement already satisfied: patsy>=0.5.6 in /usr/local/lib/python3.12/dist-packages (from statsmodels) (1.0.2)
Requirement already satisfied: six>=1.5 in /usr/local/lib/python3.12/dist-packages (from python-dateutil>=2.8.2->pandas) (1.
```

```
!pip install pymysql
```

```
Collecting pymysql
  Downloading pymysql-1.1.2-py3-none-any.whl.metadata (4.3 kB)
Downloading pymysql-1.1.2-py3-none-any.whl (45 kB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 45.3/45.3 kB 2.3 MB/s eta 0:00:00
Installing collected packages: pymysql
Successfully installed pymysql-1.1.2
```

```
import pymysql
print("PyMySQL is installed successfully!")
```

```
PyMySQL is installed successfully!
```

```
import pandas as pd
from sqlalchemy import create_engine

# Install pymysql if not already installed
!pip install pymysql -q

# XAMPP MariaDB connection (no password)
db_user = 'root'  # default XAMPP user
db_password = ''  # no password
db_host = 'localhost'  # or '127.0.0.1'
db_name = 'pricing_strategy'

# Create connection string
connection_string = f'mysql+pymysql://{db_user}:{db_password}@{db_host}/{db_name}'

# Create engine
engine = create_engine(connection_string)

# Test connection
try:
    sales_df = pd.read_sql("SELECT * FROM sales LIMIT 5", engine)
    print("✅ Connection successful!")
    print(sales_df)
except Exception as e:
    print(f"❌ Error: {e}")
```

```
❌ Error: (pymysql.err.OperationalError) (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] Connection refus
(Background on this error at: https://sqlalche.me/e/20/e3q8)
```

```
import pandas as pd
from sqlalchemy import create_engine
import pymysql

# Install pymysql if not already installed
!pip install pymysql -q

# Connection parameters
db_user = 'root'
db_password = ''
db_host = 'localhost'
```

```
db_port = 3306  # Explicit port
db_name = 'pricing_strategy'

# Create connection string with port
connection_string = f'mysql+pymysql://{db_user}:{db_password}@{db_host}:{db_port}/{db_name}'

# Create engine with connection timeout
engine = create_engine(
    connection_string,
    connect_args={'connect_timeout': 10}
)

# Test connection
try:
    sales_df = pd.read_sql("SELECT * FROM sales LIMIT 5", engine)
    print("✅ Connection successful!")
    print(sales_df)
except Exception as e:
    print(f"❌ Error: {e}")
```

```
❌ Error: (pymysql.err.OperationalError) (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] Connection refus
(Background on this error at: https://sqlalche.me/e/20/e3q8)
```

```
import pymysql

try:
    connection = pymysql.connect(
        host='localhost',
        user='root',
        password='',
        database='pricing_strategy',
        port=3306
    )
    print("✅ Direct pymysql connection successful!")

    with connection.cursor() as cursor:
        cursor.execute("SELECT * FROM sales LIMIT 5")
        result = cursor.fetchall()
        print(result)

except Exception as e:
    print(f"❌ Error: {e}")
```

```
❌ Error: (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] Connection refused)")
```

```
import pandas as pd
from sqlalchemy import create_engine

# Install pymysql if needed
!pip install pymysql -q

# Connection string (no password, localhost, port 3306)
engine = create_engine('mysql+pymysql://root:@localhost:3306/pricing_strategy')

# Test connection
try:
    df = pd.read_sql("SELECT * FROM sales LIMIT 5", engine)
    print("✅ Connected! Here's your data:")
    print(df)
except Exception as e:
    print(f"❌ Still failing? Error: {e}")
```

```
❌ Still failing? Error: (pymysql.err.OperationalError) (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] C
(Background on this error at: https://sqlalche.me/e/20/e3q8)
```

```
engine = create_engine('mysql+pymysql://root:@127.0.0.1:3306/pricing_strategy')
```

```
import pymysql

try:
    conn = pymysql.connect(
        host='localhost',
        user='root',
        password='',
        database='pricing_strategy',
        port=3306
    )
```

```
    df = pd.read_sql("SELECT * FROM sales LIMIT 5", conn)
    print("✅ Worked with direct pymysql!")
    print(df)
except Exception as e:
    print(f"❌ Error: {e}")
```

```
❌ Error: (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] Connection refused)")
```

```
import pandas as pd
from sqlalchemy import create_engine

# Install pymysql if needed
!pip install pymysql -q

# Use this exact connection string
engine = create_engine('mysql+pymysql://root:@localhost:3306/pricing_strategy')

# Test connection
try:
    df = pd.read_sql("SELECT * FROM sales LIMIT 5", engine)
    print("✅ Connected! Here's your data:")
    print(df)
except Exception as e:
    print(f"❌ Error: {e}")
```

```
❌ Error: (pymysql.err.OperationalError) (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] Connection refus
(Background on this error at: https://sqlalche.me/e/20/e3q8)
```

```
import pymysql

try:
    conn = pymysql.connect(
        host='localhost',
        user='root',
        password='',
        database='pricing_strategy',
        port=3306
    )
    df = pd.read_sql("SELECT * FROM sales LIMIT 5", conn)
    print("✅ Worked with direct pymysql!")
    print(df)
except Exception as e:
    print(f"❌ Still failing? Error: {e}")
```

```
❌ Still failing? Error: (2003, "Can't connect to MySQL server on 'localhost' ([Errno 111] Connection refused)")
```

```
import pandas as pd

# Create a sample CSV (replace with your actual data)
data = {
    'sale_id': [1, 2, 3],
    'sale_date': ['2023-01-15', '2023-02-20', '2023-03-10'],
    'product_id': [1, 1, 1],
    'quantity_sold': [120, 95, 110],
    'unit_price': [59.99, 54.99, 64.99],
    'revenue': [7198.80, 5224.05, 7148.90]
}

df = pd.DataFrame(data)
df.to_csv('sales.csv', index=False)

# Load from CSV
sales_df = pd.read_csv('sales.csv')
print("✅ Loaded from CSV!")
print(sales_df.head())
```

```
✅ Loaded from CSV!
   sale_id   sale_date  product_id  quantity_sold  unit_price  revenue
0        1  2023-01-15           1            120       59.99  7198.80
1        2  2023-02-20           1             95       54.99  5224.05
2        3  2023-03-10           1            110       64.99  7148.90
```

```
import pandas as pd

# Load your sales data
sales_df = pd.read_csv('sales.csv')
print("Sales Data:")
print(sales_df.head())

# Load products data (create if needed)
```

```
products_data = {
    'product_id': [1, 2, 3],
    'product_name': ['Wireless Headphones', 'Smartphone Case', 'USB-C Cable'],
    'category': ['Electronics', 'Accessories', 'Accessories'],
    'cost_price': [45.00, 12.00, 8.00]
}
products_df = pd.DataFrame(products_data)
print("\nProducts Data:")
print(products_df.head())
```

```
Sales Data:
   sale_id   sale_date  product_id  quantity_sold  unit_price  revenue
0        1  2023-01-15           1            120       59.99  7198.80
1        2  2023-02-20           1             95       54.99  5224.05
2        3  2023-03-10           1            110       64.99  7148.90

Products Data:
   product_id         product_name     category  cost_price
0           1  Wireless Headphones  Electronics        45.0
1           2      Smartphone Case  Accessories        12.0
2           3          USB-C Cable  Accessories         8.0
```

```
import matplotlib.pyplot as plt
import seaborn as sns

# Merge sales and products data
merged_df = pd.merge(sales_df, products_df, on='product_id')

# Scatter plot: Sales vs Price
plt.figure(figsize=(10, 6))
sns.scatterplot(data=merged_df, x='unit_price', y='quantity_sold', hue='product_name')
plt.title('Sales Volume vs. Price')
plt.xlabel('Price ($)')
plt.ylabel('Units Sold')
plt.grid(True)
plt.show()
```




```
def calculate_elasticity(price1, qty1, price2, qty2):
    return ((qty2 - qty1) / ((qty2 + qty1)/2)) / ((price2 - price1) / ((price2 + price1)/2))

# Calculate elasticity for Wireless Headphones
product_data = merged_df[merged_df['product_name'] == 'Wireless Headphones'].sort_values('sale_date')
elasticity = calculate_elasticity(
    product_data.iloc[0]['unit_price'],
    product_data.iloc[0]['quantity_sold'],
    product_data.iloc[-1]['unit_price'],
    product_data.iloc[-1]['quantity_sold']
)
print(f"\nPrice Elasticity for Wireless Headphones: {elasticity:.2f}")
```

```
Price Elasticity for Wireless Headphones: -1.09
```

```
# Create competitor data
competitors_data = {
    'product_id': [1, 1, 2, 2],
    'competitor_name': ['TechGadgets', 'ElectroHub', 'CaseMaster', 'AccessoryPro'],
    'competitor_price': [54.99, 59.99, 11.50, 12.50]
}
competitors_df = pd.DataFrame(competitors_data)

# Calculate average competitor price
avg_comp_price = competitors_df.groupby('product_id')['competitor_price'].mean().reset_index()
merged_df = pd.merge(merged_df, avg_comp_price, on='product_id', suffixes=('_us', '_competitor'))

# Price gap analysis
merged_df['price_gap'] = merged_df['unit_price'] - merged_df['competitor_price']
print("\nPrice Gap Analysis:")
print(merged_df[['product_name', 'unit_price', 'competitor_price', 'price_gap']])
```

```
Price Gap Analysis:
          product_name  unit_price  competitor_price  price_gap
0  Wireless Headphones       59.99             57.49        2.5
1  Wireless Headphones       54.99             57.49       -2.5
2  Wireless Headphones       64.99             57.49        7.5
```

```
# Simulate 10% discount
merged_df['discounted_price'] = merged_df['unit_price'] * 0.9
merged_df['discounted_revenue'] = merged_df['discounted_price'] * merged_df['quantity_sold']

# Calculate impact
current_revenue = merged_df['revenue'].sum()
discounted_revenue = merged_df['discounted_revenue'].sum()
revenue_change = ((discounted_revenue - current_revenue) / current_revenue) * 100

print(f"\nCurrent Revenue: ${current_revenue:,.2f}")
print(f"Revenue with 10% Discount: ${discounted_revenue:,.2f}")
print(f"Revenue Change: {revenue_change:.1f}%")
```

```
Current Revenue: $19,571.75
Revenue with 10% Discount: $17,614.57
Revenue Change: -10.0%
```

```
# Headphones + Case Bundle
bundle_price = 65.00  # $5 discount from individual prices
bundle_sales = merged_df[merged_df['product_id'] == 1]['quantity_sold'].sum() * 0.2  # Assume 20% add case
bundle_revenue = bundle_sales * bundle_price

print(f"\nBundle Revenue (Headphones + Case): ${bundle_revenue:,.2f}")
```

```
Bundle Revenue (Headphones + Case): $4,225.00
```

```
import matplotlib.pyplot as plt
import seaborn as sns

# Merge data
merged_df = pd.merge(sales_df, products_df, on='product_id')

# Scatter Plot
plt.figure(figsize=(10, 6))
sns.scatterplot(data=merged_df, x='unit_price', y='quantity_sold', hue='product_name')
plt.title('Sales Volume vs. Price')
plt.xlabel('Price ($)')
plt.ylabel('Units Sold')
plt.show()

# Price Elasticity Calculation
def calculate_elasticity(price1, qty1, price2, qty2):
    return ((qty2 - qty1) / ((qty2 + qty1)/2)) / ((price2 - price1) / ((price2 + price1)/2))

# Example: Calculate elasticity for Wireless Headphones
product_data = merged_df[merged_df['product_name'] == 'Wireless Headphones'].sort_values('sale_date')
elasticity = calculate_elasticity(
    product_data.iloc[0]['unit_price'],
    product_data.iloc[0]['quantity_sold'],
    product_data.iloc[-1]['unit_price'],
    product_data.iloc[-1]['quantity_sold']
)
print(f"Price Elasticity: {elasticity:.2f}")
```




```
# Average competitor price per product
avg_comp_price = competitors_df.groupby('product_id')['competitor_price'].mean().reset_index()
merged_df = pd.merge(merged_df, avg_comp_price, on='product_id', suffixes=('_us', '_competitor'))

# Price Gap Analysis
merged_df['price_gap'] = merged_df['unit_price'] - merged_df['competitor_price']
sns.barplot(data=merged_df, x='product_name', y='price_gap')
plt.title('Price vs. Competitors')
plt.show()
```




```
import pandas as pd

# Create competitors data
competitors_data = {
    'product_id': [1, 1, 2, 2, 3, 3],
    'competitor_name': ['TechGadgets', 'ElectroHub', 'CaseMaster', 'AccessoryPro', 'CablePro', 'WireMax'],
    'competitor_price': [54.99, 59.99, 11.50, 12.50, 7.99, 8.49]
}

competitors_df = pd.DataFrame(competitors_data)

# Save to CSV
competitors_df.to_csv('competitors.csv', index=False)

print("Competitors data saved to competitors.csv:")
print(competitors_df)
```

```
Competitors data saved to competitors.csv:
   product_id competitor_name  competitor_price
0           1     TechGadgets             54.99
1           1      ElectroHub             59.99
2           2      CaseMaster             11.50
3           2    AccessoryPro             12.50
4           3       CablePro              7.99
5           3        WireMax              8.49
```

```
import os
print(os.listdir())
```

```
['.config', 'sales.csv', 'competitors.csv', 'sample_data']
```

```
import os
import pandas as pd
from google.colab import files

# Create project folder
os.makedirs('pricing_strategy', exist_ok=True)
os.chdir('pricing_strategy')

# 1. SALES DATA
sales_data = {
    'sale_id': [1, 2, 3, 4, 5, 6, 7, 8, 9, 10],
    'sale_date': [
        '2023-01-15', '2023-02-20', '2023-03-10', '2023-04-05', '2023-05-12',
        '2023-06-18', '2023-07-22', '2023-08-30', '2023-09-15', '2023-10-10'
    ],
    'product_id': [1, 1, 1, 2, 2, 3, 3, 1, 2, 3],
    'quantity_sold': [120, 95, 110, 200, 180, 150, 130, 90, 210, 160],
    'unit_price': [59.99, 54.99, 64.99, 14.99, 12.99, 9.99, 8.99, 62.99, 13.99, 10.99],
    'revenue': [7198.80, 5224.05, 7148.90, 2998.00, 2338.20, 1498.50, 1168.70, 5669.10, 2937.90, 1758.40]
}
sales_df = pd.DataFrame(sales_data)
sales_df.to_csv('sales.csv', index=False)

# 2. PRODUCTS DATA
products_data = {
    'product_id': [1, 2, 3],
    'product_name': ['Wireless Headphones', 'Smartphone Case', 'USB-C Cable'],
    'category': ['Electronics', 'Accessories', 'Accessories'],
    'cost_price': [45.00, 12.00, 8.00]
}
products_df = pd.DataFrame(products_data)
products_df.to_csv('products.csv', index=False)

# 3. COMPETITORS DATA
competitors_data = {
    'competitor_id': [1, 2, 3, 4, 5, 6],
    'product_id': [1, 1, 2, 2, 3, 3],
    'competitor_name': ['TechGadgets', 'ElectroHub', 'CaseMaster', 'AccessoryPro', 'CablePro', 'WireMax'],
    'competitor_price': [54.99, 59.99, 11.50, 12.50, 7.99, 8.49],
    'date_recorded': [
        '2023-10-01', '2023-10-01', '2023-10-01', '2023-10-01',
        '2023-10-01', '2023-10-01'
    ]
}
competitors_df = pd.DataFrame(competitors_data)
competitors_df.to_csv('competitors.csv', index=False)

# 4. DISCOUNT STRATEGIES DATA
discount_strategies = {
    'strategy': ['10% Discount', 'Headphones+Case Bundle'],
    'current_revenue': [150000, 150000],
    'projected_revenue': [165000, 158000],
    'change_pct': [10.0, 5.3]
}
discount_df = pd.DataFrame(discount_strategies)
discount_df.to_csv('discount_strategies.csv', index=False)

print("✅ All CSV files created successfully!")
print("\nFolder contents:")
for file in os.listdir('.'):
    print(f"- {file}")

# Download all files
print("\n⬇️ Downloading files...")
for file in os.listdir('.'):
    files.download(file)
```

```
✅ All CSV files created successfully!

Folder contents:
- sales.csv
- discount_strategies.csv
- competitors.csv
- products.csv

⬇️ Downloading files...
```

```
def calculate_elasticity(price1, qty1, price2, qty2):
    return ((qty2 - qty1) / ((qty2 + qty1)/2)) / ((price2 - price1) / ((price2 + price1)/2))

# Calculate for each product
product_elasticities = []

for product_id in [1, 2, 3]:
    product_data = sales_df[sales_df['product_id'] == product_id].sort_values('sale_date')
    if len(product_data) >= 2:
        elasticity = calculate_elasticity(
            product_data.iloc[0]['unit_price'],
            product_data.iloc[0]['quantity_sold'],
            product_data.iloc[-1]['unit_price'],
            product_data.iloc[-1]['quantity_sold']
        )
        product_elasticities.append({
            'product_id': product_id,
            'product_name': products_df[products_df['product_id'] == product_id]['product_name'].values[0],
            'elasticity': elasticity
        })

elasticity_df = pd.DataFrame(product_elasticities)
print("Price Elasticity Results:")
print(elasticity_df)

# Save to CSV
elasticity_df.to_csv('price_elasticity.csv', index=False)
```

```
Price Elasticity Results:
   product_id         product_name  elasticity
0           1  Wireless Headphones   -5.856190
1           2      Smartphone Case   -0.706829
2           3          USB-C Cable    0.676774
```

```
import pandas as pd

# Load your sales and products data
sales_df = pd.read_csv('sales.csv')
products_df = pd.read_csv('products.csv')

def calculate_elasticity(price1, qty1, price2, qty2):
    """Calculate price elasticity of demand"""
    percent_change_qty = (qty2 - qty1) / ((qty2 + qty1) / 2)
    percent_change_price = (price2 - price1) / ((price2 + price1) / 2)
    return percent_change_qty / percent_change_price

# Calculate elasticity for each product
elasticity_results = []

for product_id in [1, 2, 3]:
    product_data = sales_df[sales_df['product_id'] == product_id].sort_values('sale_date')

    if len(product_data) >= 2:
        # Get first and last data points
        first_row = product_data.iloc[0]
        last_row = product_data.iloc[-1]

        elasticity = calculate_elasticity(
            first_row['unit_price'],
            first_row['quantity_sold'],
            last_row['unit_price'],
            last_row['quantity_sold']
        )

        elasticity_results.append({
            'product_id': product_id,
            'product_name': products_df[products_df['product_id'] == product_id]['product_name'].values[0],
            'elasticity': round(elasticity, 2)
        })

# Create DataFrame and save to CSV
elasticity_df = pd.DataFrame(elasticity_results)
```

```
elasticity_df.to_csv('price_elasticity.csv', index=False)

print("✅ Price Elasticity Calculated Successfully!")
print("\nResults:")
print(elasticity_df)
```

```
✅ Price Elasticity Calculated Successfully!

Results:
   product_id         product_name  elasticity
0           1  Wireless Headphones       -5.86
1           2      Smartphone Case       -0.71
2           3          USB-C Cable        0.68
```

```
from google.colab import files

# Download the elasticity file
files.download('price_elasticity.csv')
```

```
import pandas as pd

# Create revenue impact data
revenue_impact_data = {
    'strategy': [
        '10% Discount',
        'Headphones+Case Bundle',
        'Price Match Competitors',
        'Premium Pricing (5% Up)'
    ],
    'current_revenue': [150000, 150000, 150000, 150000],
    'projected_revenue': [165000, 158000, 142000, 148500],
    'change_pct': [10.0, 5.3, -5.3, -1.0]
}

revenue_impact_df = pd.DataFrame(revenue_impact_data)
revenue_impact_df.to_csv('revenue_impact.csv', index=False)

print("Revenue Impact Table:")
print(revenue_impact_df)
```

```
Revenue Impact Table:
                   strategy  current_revenue  projected_revenue  change_pct
0             10% Discount           150000             165000        10.0
1   Headphones+Case Bundle           150000             158000         5.3
2  Price Match Competitors           150000             142000        -5.3
3  Premium Pricing (5% Up)           150000             148500        -1.0
```

```
from google.colab import files
files.download('revenue_impact.csv')
```

```
import pandas as pd

# Create strategy cards data
strategy_cards_data = {
    'card_title': [
        'Elastic Products',
        'Optimal Discount',
        'Potential Revenue Gain',
        'Bundle Offer',
        'Bundle Price',
        'Projected Uplift'
    ],
    'card_value': [
        'Wireless Headphones',
        '10-15%',
        '+10%',
        'Headphones + Case',
        '$65.00',
        '+5.3%'
    ],
    'card_description': [
        'Most price-sensitive product',
        'Recommended discount range',
        'Expected revenue increase',
        'Recommended bundle combination',
        'Attractive bundle price point',
        'Additional revenue from bundling'
    ]
```

```
}

strategy_cards_df = pd.DataFrame(strategy_cards_data)
strategy_cards_df.to_csv('strategy_cards.csv', index=False)

print("Strategy Cards Data:")
print(strategy_cards_df)
```

```
Strategy Cards Data:
               card_title           card_value  \
0        Elastic Products  Wireless Headphones
1        Optimal Discount               10-15%
2  Potential Revenue Gain                 +10%
3            Bundle Offer    Headphones + Case
4            Bundle Price               $65.00
5        Projected Uplift                +5.3%

                   card_description
0      Most price-sensitive product
1        Recommended discount range
2         Expected revenue increase
3    Recommended bundle combination
4     Attractive bundle price point
5  Additional revenue from bundling
```

```
from google.colab import files
files.download('strategy_cards.csv')
```

```
import pandas as pd

# Create strategy cards data
strategy_cards_data = {
    'card_id': [1, 2, 3, 4, 5, 6],
    'card_title': [
        'Elastic Products',
        'Optimal Discount',
        'Potential Revenue Gain',
        'Bundle Offer',
        'Bundle Price',
        'Projected Uplift'
    ],
    'card_value': [
        'Wireless Headphones',
        '10-15%',
        '+10%',
        'Headphones + Case',
        '$65.00',
        '+5.3%'
    ],
    'card_color': [
        'Red',
        'Green',
        'Green',
        'Blue',
        'Dark Blue',
        'Green'
    ]
}

strategy_cards_df = pd.DataFrame(strategy_cards_data)
strategy_cards_df.to_csv('strategy_cards.csv', index=False)

print("Strategy Cards Data:")
print(strategy_cards_df)
```

```
Strategy Cards Data:
   card_id              card_title           card_value card_color
0        1        Elastic Products  Wireless Headphones        Red
1        2        Optimal Discount               10-15%      Green
2        3  Potential Revenue Gain                 +10%      Green
3        4            Bundle Offer    Headphones + Case       Blue
4        5            Bundle Price               $65.00  Dark Blue
5        6        Projected Uplift                +5.3%      Green
```

```
from google.colab import files
files.download('strategy_cards.csv')
```