
scRNA-seq Integration & Batch correction

Multi-sample/batch harmonization

Aditya Singh

2026-11-12

Integration vs Batch Correction



- Batch correction is a type of integration; vice versa is not true
- In practice, integration = batch correction + dataset merging
- If batch correction is needed, it’s done along with the integration of samples
- Multiple samples integration is always performed
- Batch correction is added to it only when needed

Closer look




Image adapted from **Argelaguet et al. (2021)**.

- **Panel "a"**: Same type of data (scRNAseq)

- Integration & batch-correction (BC)
- 3 samples same run: Without BC
- 3 samples 2 batches: With BC

Overview: Why Integration?


The Challenge:

- **Panel "b"**: Multi-omics Integration
- Same samples, multiple platforms
- Example: RNAseq + ATACseq
- Beyond scope here
- Good to know and not to confuse!

- Comparing cells across individuals/conditions
- Multiple scRNA-seq experiments from different batches
- Technical variations overshadow biological signals
- Need unified analysis across samples

Batch Effects Include:

- Multiple seq runs
- Library preparation protocols
- Platform variations
- Sample handling differences
- And (sadly) many more!



Orthogonal Assumption

✅ Better Design

Balanced Batches

Sample	Condition	Batch
Patient A	Control	1
Patient B	Control	2
Patient C	Control	3
Patient D	Treated	1
Patient E	Treated	2
Patient F	Treated	3

Key challenge: Distinguish biological variation from batch effects

Key Assumption: Batches are uncorrelated (orthogonal) to the variable of interest.

❌ Bad Design

Confounded Batches

Sample	Condition	Batch
Patient A	Control	1

Sample	Condition	Batch
Patient B	Control	1
Patient C	Control	1
Patient D	Treated	2
Patient E	Treated	2
Patient F	Treated	2

Overview of Integration Methods

Method	Algorithm	Language	Library	Ref
CCA	Canonical Correlation Analysis	R	Seurat	**Cell 2019**
MNN	Mutual Nearest Neighbors correction	R / Python	batchelor / Scanpy	**Nat. Biotech 2018**
Conos	Graph-based joint kNN alignment	R	conos	**Nat. Methods 2019**
Harmony	Iterative PC correction (soft-clustering)	R / Python	harmony/ harmonypy	**Nat. Methods 2019**
bbknn	Batch-balanced kNN graph (graph-level integration)	Python	scanpy / bbknn	**Bioinformatics 2020**
Scanorama	Manifold alignment + SVD-based merging	Python	scanorama	**Nat. Biotech 2019**

Note: This is not an exhaustive list, just a selection of popular methods that we'll cover in the exercises

Classic Batch Correction Methods

Method	Algorithm	Language	Library	Ref
ComBat	Empirical Bayes location/scale adjustment	R	sva	**Biostatistics 2007**
ComBat-seq	Negative binomial ComBat for counts	R	svaseq	**NAR Genomics 2020**
limma	Linear models with empirical Bayes	R	limma	**NAR 2015**
RUV	Remove unwanted variation (control genes/factor-based)	R	RUVSeq	**Nat. Biotechnol 2014**
SVA	Surrogate variable analysis	R	sva	**PLoS Genetics 2007**


Note: These methods were developed for bulk data and usually not perform well on scRNA-seq due to sparsity and zero-inflation. They are included here for context

AI/Deep Learning Integration Methods

Method	Algorithm	Language	Library	Ref
scVI	Variational autoencoder	Python	scvi-tools	**Nat Methods 2018**
scANVI	Semi-supervised (label-aware) extension of scVI	Python	scvi-tools	**Mol Syst Biol 2021**
scARCHS / scArches	Reference mapping: query cells placed onto an atlas embedding	Python	scvi-tools	**Nat. Biotechnol 2024**
scGen	Causal VAE for perturbation modeling	Python	scvi-tools (scgen)	**Nat Methods 2019**

Note: scvi-tools ships in the course Scanpy container, so you can try these outside the tutorial hours. Deep-learning methods trade setup effort and compute for flexibility

CCA: Canonical Correlation Analysis




CCA: finding shared correlated components across batches.

- Finds correlated features between batches
- Creates canonical variates capturing shared variation
- Projects cells into aligned latent space
- Linear approach - computationally efficient for large datasets

Mutual Nearest Neighbors (MNN) Integration

- **Core concept**: Identifies pairs of cells that are each other's nearest neighbors across batches in high-dimensional gene expression space
- Assumes shared cell types exist between batches
- Doesn't require identical population composition
- **No predefined populations needed**: Works without cell type annotations
- **How it works**:
- Computes kNN graphs in PCA space
- Finds mutual nearest neighbor pairs across batches
- Applies linear batch-effect corrections using correction vectors
- **Minimal biological artifacts**: Conservative approach, reducing risk of removing biological differences

Visualizing MNN Correction



MNN integration example

Harmony: Iterative PC Correction




Image from **Korsunsky et al. (2019)**.

Harmony iteratively adjusts cell embeddings so that each cluster contains a balanced mix of batches

Scanorama: Manifold Alignment + SVD





Image from **Hie et al. (2019)**.

- Builds manifold alignment between pairs of datasets

- Uses Singular Value Decomposition (SVD) for efficient merging
- Iteratively corrects and merges multiple datasets

Conos: Graph-Based Alignment




Conos **Barkas et al. (2019)**.

- Builds separate k-NN graphs for each sample
- Constructs joint graph by adding cross-sample edges between similar cells
- Preserves per-sample structure while enabling global analysis

- Particularly useful for many-sample studies with distinct biological states

Comparison



Credit: Nikolay Oskolov

Comparison Matrix

Aspect	CCA	MNN	bbknn	Harmony	Scanorama	Conos
Speed	Fast	Slow	Fast	Fast	Medium	Slow
Scalability	~10k	~50k	100k+	125k+	~50k	~30k
Batch Correction	Good	Excellent	Good	Good	Excellent	Very Good
Biology Preservation	Medium	Excellent	Good	Excellent	Good	Excellent
Rare Type Detection	Poor	Excellent	Good	Good	Medium	Good
Learning Curve	Low	Medium	Low	Low	Medium	High
Language	R	R/Python	Python	R/Python	Python	R
Graph-Based	No	No	Yes	No	No	Yes

What the benchmarks say

Claim	Source	Key Finding
Speed: Harmony and graph-based methods scale best at large cell numbers	**Tran et al. (2020)**	Harmony substantially faster than MNN at high cell counts
Scalability: Harmony (125k+) > MNN/Scanorama (~50k) > CCA (~10k)	**Korsunsky et al. (2019)**	Harmony designed for atlas-scale integration
Batch mixing vs biology preservation is a trade-off, method- and dataset-dependent	**Luecken et al. (2022)**	Atlas-level scIB benchmark; no method wins on all datasets and metrics
Strong local correction (MNN/Scanorama) preserves rare populations well	**Luecken et al. (2022)**	Rare cell types recover best after methods that correct locally
Feature selection changes integration results, including query mapping and rare-type recovery	**Zappia et al. (2025)**	Registered benchmark: the gene-selection strategy matters almost as much as the method

Best Practices

- **QC first:** Remove low-quality cells before integration
- **Feature selection:** Use highly variable genes (2000-3000) before integration, ideally selected per batch and combined (benchmarks show the gene set changes results almost as much as the method, **Zappia et al. 2025**)
- **Batch awareness:** Always specify batch variable during integration
- **Metrics matter:** Assess both batch mixing and biological preservation
- **Visualize results:** Check UMAP, violin plots by batch, cell type distribution
- **Validate:** Confirm known biology is preserved in integrated data
- **Don’t fix something unbroken:** Make sure there are batch effects before *“fixing”*

How do I know the integration worked?

Two goals that pull against each other (**Luecken et al. 2022**):

Batch mixing - Same cell type should overlap across batches - Check: color UMAP by batch; do clusters contain all batches? - Formal scores: kBET, LISI/graph connectivity (scIB toolkit)

Biology preservation - Distinct cell types should stay distinct - Check: marker genes still mark one population, not everything - Check: known rare cell type still recoverable after integration - Formal scores: cluster purity (NMI/ARI), isolated labels

> **Tip**
>
> Practical minimum for a small study: UMAP colored by batch + marker panels + one expected rare population. Benchmarks formalize what your eyes already check.

Common Pitfalls

⚠ Overcorrection

- Removing real biological signal
- Check with known marker genes

⚠ Batch structure ignored

- Not specifying batch variable correctly
- Can lead to suboptimal integration

⚠ Incompatible preprocessing

- Different normalization or scaling across batches
- Standardize preprocessing pipeline first

⚠ Confounded design

- Batch perfectly correlated with condition (eg. all controls in batch 1, all treated in batch 2)

- Integration cannot disentangle technical vs biological variation

Integration in 2026: where the field moved

*For context only, these are **not** part of the hands-on tutorials.*

- **Benchmarks matured.** Large registered benchmarks (**Luecken et al. 2022**; **Zappia et al. 2025**) confirm: no single best method; performance depends on dataset scale, design, and the gene set you feed the method.
- **From "integrate everything" to "map to a reference".** Instead of integrating every new dataset with every other, new data is *mapped* onto a curated atlas, then compared to the atlas. Implemented as MapQuery (Seurat v5), scARCHS/scArches (**Hao et al. 2024**), and Symphony. Concept and caveats: **Lotfollahi, Hao, Theis & Satija 2024**, **Hrovatin et al. 2025**.
- **Reference mapping caveat:** mapped query cells inherit atlas labels, so a cell type *missing* from the reference gets forced onto the nearest atlas label. Expect unseen populations to be mislabeled, always check marker expression.
- **Cross-species integration** exists now (SATURN, **Rosen et al. 2024**), but only for homologous genes and it is far from routine.
- **Multimodal integration** (RNA + ATAC + protein) has its own registered benchmarks (**Liu et al. 2025**); MOFA-style multi-omics is beyond this course.

Q&A

Key takeaway: Integration balances batch removal with biology preservation
Summary slides for revision follow

Summary: Integration goals

ⓘ Q1. What is the main goal of scRNA-seq integration?

A: To align cells so they group by biological signal (for example, cell type) rather than technical or sample-specific differences.

ⓘ Q2. Why can integration be needed even with one sequencing batch?

A: Different samples in the same run can still differ in preparation, dissociation, or depth, making cells cluster by sample instead of cell type.

ⓘ Q3. What pattern in a UMAP suggests batch effect problems?

A: Clusters separate mainly by batch label even though the same cell type exists in all batches.

Summary: CCA / Seurat anchors

ⓘ Q4. Conceptually, what does CCA do for integration?

A: It finds shared low-dimensional “correlated directions” across datasets where similar cell states align.

ⓘ Q5. What are “anchors” in Seurat’s CCA-based integration?

A: Pairs or small groups of cells from different datasets that represent the same biological state and are used as reference points for alignment.

ⓘ Q6. Simple example

A: Take T cells from patient A and B that look similar, treat them as anchors, and warp both datasets so T cells from A and B overlap in the joint space.

Summary: Harmony

ⓘ Q7. What is the core idea behind Harmony?

A: Start in PCA space, then iteratively shift cell embeddings so each cluster has similar contributions from each batch, reducing batch-driven structure.

ⓘ Q8. Why is Harmony often practical for large datasets?

A: It operates on PCs, is relatively fast, and fits into a simple PCA → Harmony → UMAP workflow.

ⓘ Q9. Metaphor for Harmony's adjustment

A: You have groups of similar cells on a map; Harmony gently nudges cells from overrepresented batches so each group has a fair mix of batches.

Summary: MNN & Scanorama

ⓘ Q10. What is a mutual nearest neighbors (MNN) pair?

A: A pair of cells, one from each dataset, where each is among the nearest neighbors of the other in expression space.

ⓘ Q11. How does MNN-based integration use these pairs?

A: It assumes MNN pairs represent the same cell state and computes local correction vectors to align the datasets around those pairs.

ⓘ Q12. Intuitive example for MNN in lecture

A: If a T cell in dataset A and a T cell in dataset B are each other's closest match, link them and use that link to locally shift one dataset towards the other.

ⓘ Q13. What is the main idea behind Scanorama?

A: It uses MNN-like matches across many datasets and stitches them together like a panorama to build a unified embedding.

Summary: Conos

ⓘ Q14. Why is Scanorama useful for many-dataset studies?

ⓘ Q15. What is Conos' high-level approach to integration?

A: It can integrate multiple experiments at once by finding shared cell populations and merging them into a common space.

A: It builds a graph for each sample, then constructs a joint graph across samples using cross-sample neighbors, and analyzes this global graph for clustering and alignment.

ⓘ Q16. When is Conos particularly attractive?

A: When you have many samples and want to keep per-sample identity while still obtaining joint clustering from the combined graph.

ⓘ Q17. Simple metaphor for Conos

A: Each sample is its own social network; Conos adds edges between similar people across networks and then analyzes the big merged social graph.

Summary: Over- vs under-integration & choice

ⓘ Q18. How can you spot “over-integration” ?

A: UMAP: If biologically distinct groups are **integrated** (eg. disease and control where separation is expected)

ⓘ Q19. How can you spot “under-integration”?

A: UMAP: If technically distinct groups are **not-integrated** (eg. sequencing run 1 and 2)

ⓘ Q20. Simple rule-of-thumb when choosing an integration method

A: Use anchor/CCA or Harmony for typical multi-sample datasets; consider MNN/Scanorama for more local alignment or many datasets; use Conos for graph-based integration across many samples while preserving sample identity.

ⓘ Q21. What are the two axes to judge an integration by?

A: Batch mixing (same cell type from different batches overlaps) and biology preservation (distinct types stay distinct, rare types survive). Improving one often costs the other, so both must be reported.

ⓘ Q22. What is reference mapping, and what is its main pitfall?

A. New data is aligned to a curated atlas (MapQuery, scArches, Symphony) instead of re-integrating everything. Pitfall: query cells without atlas labels (e.g. cell types absent from the reference) are forced onto the wrong label.

Resources & Further reading

- Luecken, M.D., Büttner, M., Chaichoompu, K. et al. Benchmarking atlas-level data integration in single-cell genomics. Nat Methods 19, 41–50 (2022). https://doi.org/10.1038/s41592-021-01336-8
- Zappia, L., Richter, S., Ramírez-Suástegui, C. et al. Feature selection methods affect the performance of scRNA-seq data integration and querying. Nat Methods 22, 834–844 (2025). https://doi.org/10.1038/s41592-025-02624-3
- Korsunsky, I., Millard, N., Fan, J. et al. Fast, sensitive and accurate integration of single-cell data with Harmony. Nat Methods 16, 1289–1296 (2019). https://doi.org/10.1038/s41592-019-0619-0
- Hie, B., Bryson, B. & Berger, B. Efficient integration of heterogeneous single-cell transcriptomes using Scanorama. Nat Biotechnol 37, 685–691 (2019). https://doi.org/10.1038/s41587-019-0113-3
- Haghverdi, L., Lun, A.T.L., Morgan, M.D. & Marioni, J.C. Batch effects in single-cell RNA-sequencing data are corrected by matching mutual nearest neighbors. Nat Biotechnol 36, 421–427 (2018). https://doi.org/10.1038/nbt.4091
- Polański, S., Mäder, T., Langer, S.B., Hemberg, M. & Moody, J. BBKNN: fast batch alignment of single cell transcriptomes. Bioinformatics 36, 964–965 (2020). https://doi.org/10.1093/bioinformatics/btz625
- Hao, Y., Stuart, J., Kowalski, M.H. et al. Dictionary learning for integrative, multimodal and scalable single-cell analysis. Nat Biotechnol 42, 293–304 (2024). https://doi.org/10.1038/s41587-023-01767-y

- Lotfollahi, M., Hao, Y., Theis, F.J. & Satija, R. The future of rapid and automated single-cell data analysis using reference mapping. Cell 187, 2343–2358 (2024). https://doi.org/10.1016/j.cell.2024.03.009
- Hrovatin, K., Sikkema, L., Shitov, V.A. et al. Considerations for building and using integrated single-cell atlases. Nat Methods 22, 41–57 (2025). https://doi.org/10.1038/s41592-024-02532-y
- Argelaguet, R., Velten, B., Arnol,D, S. et al. Multi-omics factor analysis—a framework for unsupervised integration of multi-omics data sets. Mol Syst Biol 14, e8124 (2018). https://doi.org/10.15252/msb.20178124
- Barkas N., Petukhov V., Nikolaeva D., Lozinsky Y., Demharter S., Khodosevich K., & Kharchenko P.V. Joint analysis of heterogeneous single-cell RNA-seq dataset collections. Nature Methods, (2019). https://doi.org/10.1038/s41592-019-0466-z