Create a script to update names of existing clients.

A dedicated command-line administrative utility, `update_client_name.php` (installed to `/usr/local/bin/update_client_name` and `~/.local/bin/update_client_name`), has been created to update names of existing client accounts at any time.

Key Capabilities

1. **Multiple Operation Modes**:
    - **Interactive Menu (`update_client_name`)**: Discovers all registered client accounts from the registry and configuration files, presents an indexed menu displaying current names, and prompts for the new name. If only a single client exists, it targets it automatically.
    - **Direct Update (`update_client_name -D <domain> -N <name>`)**: Instantly updates a specific client account's name via CLI arguments (or non-interactively with `-y`).
    - **Batch Sequential Review (`update_client_name -a`)**: Steps through every recorded client account sequentially, allowing you to enter a new name or press Enter to keep the existing one.
    - **Listing (`update_client_name -l`)**: Prints a table of all registered client domains, roles, and their configured names.
2. **Full Multi-Layer Synchronization**: Calls `execute_client_name_update()` and `set_client_name()` to persist the updated name across:
    - `site_settings` table (domain-scoped key `<domain>::client_name`)
    - `users` table (`client_name` column)
    - `main_subscriptions` table (`client_name` column for broadcast correspondence)
    - `/etc/tricurse/<domain>/contact.conf` and flat `<domain>.conf`
    - `/etc/tricurse/installations.json` (and user fallback `~/.local/share/tricurse/installations.json`)
    - All associated SQLite databases across the server
3. **Security & Deployment**:
    - Web server access is strictly forbidden (`php_sapi_name() !== 'cli'` returns HTTP 403 Forbidden).

- Integrated into `install.sh` so standard installs and `--update-all` automatically deploy and link `update_client_name` in `/usr/local/bin` and purge it from webroots.
- Mirrored across `/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`.

CLI Usage Examples

```
# Interactive selection menu:
update_client_name

# List registered client accounts and configured names:
update_client_name -l

# Directly update a specific client:
update_client_name -D client.example.com -N "Alpha Branch Office"

# Review and update all client names sequentially:
update_client_name -a
```

A shared database should be the only option.

A shared database is now the **only option** across all installations on the server:

Changes Implemented

1. **Enforced Single Shared Database Architecture**:
    - In `install.sh`, `USE_SHARED_DB=true` is now permanently set as the default and only operating mode.
    - Removed prompts asking whether all users will use the same database. All clients and contact points on the server now automatically use the single shared SQLite database (`/var/lib/tricurse/contact/contact.sqlite` or `~/.local/share/tricurse/contact/contact.sqlite` for non-root).
    - Removed separate per-domain message storage options (`/var/lib/tricurse/contact/<domain>`).
2. **Automatic Migration for Existing Installations**:
    - If any legacy independent database installations exist on the server when installing a new client, `install.sh` automatically executes `merge_databases.php` to merge all records into the unified shared database and re-point client configurations.
3. **Documentation & Mirror Synchronization**:
    - Updated `INSTALL.md`, `README.md`, and `/addr.bar/README.md` to reflect the single shared database architecture.
    - Synchronized across `/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, `/var/www/html/contact/`, and the root `/addr.bar/install.sh`.