Domain names can be rented. Another person could rent a domain name that was used by someone else before. The recipient of external mail should also be able to receive the client's name. That will help verify it was from that person, in case someone else is using the address.

The client name is now included in external mail dispatches, received across federated endpoints, and displayed on letter cards.

Why This Protects Against Rented / Reassigned Domains

Domain names are leased assets that can expire, be auctioned, or be rented by new operators. If an application only identifies correspondence by hostname (e.g., `client.example.com`), a new tenant who later acquires that domain could be mistaken for the original person.

By transmitting and storing the administrator-configured **Client Name** alongside the host domain, the recipient always has two independent identity checkpoints:

1. **The Originating Hostname:** Verifies network transmission and SSL reachability.
2. **The Client Name:** Confirms the personal or organizational identity of the sender configured at installation time.

Changes Implemented

1. **Outbound External Mail Transmission in index.php:**
    - Outbound HTTP POST payloads (`action=inter_site_mail`) to external destinations now send `'sender_name' => $sender_name` (the administrator-configured client name), rather than an empty string.
    - When retrying or sending delayed messages, the sender name is preserved for external dispatches.
2. **Inbound External Mail Reception in index.php:**
    - Removed the external sender name suppression filter in `inter_site_mail`.
    - Incoming external letters now record the provided `sender_name` directly in `incoming_messages.sender_name` alongside the sender's hostname.
3. **Inbox & Archive Letter Card Header Display in index.php & index.php:**
    - Both active inbox letter cards and monthly archive pages now render the client name whenever available:

```
From: Alice (rented-domain.org)
```

    - If no client name was provided by the sender, it cleanly falls back to the domain address (`From: rented-domain.org`).

4. **Notifications & PNG Exports in db.php & index.php:**
    - Push notification alerts and real-time popups include the client name: `New message from Alice (rented-domain.org)`.
    - High-resolution letter exports generated via **`[ 📷 Download As PNG ]`** capture the sender's client name in the card header.
5. **Manual & Documentation Updated:**
    - Added the **Identity Verification & The Rented Domain Safeguard** section in INSTRUCTION_BOOKLET.md.
    - Recompiled the printable SNES-style manual: INSTRUCTION_BOOKLET.pdf.

Synchronization

- Synchronized changes across `/addr.bar/tricurse/contact/`, addressbar.net/contact/, and `/var/www/html/contact/`.
- Committed to the repository on branch `main`.

Clicking **[🔍 Check]** in the Send Mail form now retrieves and displays the destination's configured **Client Name** in real time.

Pre-Flight Verification Workflow

When composing a letter, entering any destination address (e.g., `https://rented-domain.org` or `novy.addr.bar`) and clicking **[🔍 Check]** probes the target endpoint and presents the author's identity:

```
[ Target Address: https://rented-domain.org ]  --->  [ 🔍 Check ]
                        ||
                        \/
🟢 Available: Client: Alice (rented-domain.org) — Website is online and ready. (10 msgs remaining today)
```

If a domain has expired and been re-rented by a different individual or organization, clicking **[🔍 Check]** will show the new occupant's name (e.g. `Client: Bob (rented-domain.org)`), alerting the writer before any message is sent.

Implementation Details

1. **Frontend Radar Display in index.php:**
    - `checkRowAvailability()` now formats `data.client_name` alongside the domain address in both success and error status badges:

      ```
      Client: <strong>Alice</strong> (rented-domain.org) — Website is online and ready.
      ```

    - If the remote site is rate-limited or has communications disabled, the client name is still presented so the identity of the host remains verified.
2. **Availability Endpoint Payload in index.php:**
    - The inbound `action=check_availability` handler includes `'client_name' => $client_name` across all responses (available, rate-limited, blocked, and communications disabled).
3. **Fallback Extraction in db.php:**
    - If an external website returns its HTML public gateway screen rather than a raw JSON response (due to redirects or directory structures), `check_destination_availability()` automatically extracts the client name from the page header (`SYSTEM LOGIN (domain - Client Name)`).
4. **Instruction Manual & Diagrams:**

- Updated Section 8 (*Reconnaissance: The Pre-Flight Availability Radar*) in INSTRUCTION_BOOKLET.md to document identity discovery via the `[ 🔍 Check ]` button.
- Recompiled the printable SNES manual: INSTRUCTION_BOOKLET.pdf.

Synchronization

- Synchronized to `/addr.bar/tricurse/contact/`, addressbar.net/contact/, and `/var/www/html/contact/`.
- Committed to git on branch `main`.

The name can also be found by clicking Check in the send mail form.