For novy.addr.bar, I get
🟢 Available: Website is online and available to receive messages. (8 msgs remaining today)
when I click Check at hotletter.neolamia.com,

but for tricurse.com/contact, which is part of the same server, I get
🟢 Available: Website is online and reachable over HTTPS.

tricurse.com/contact is the main contact point of the server where novy.addr.bar is a client. karo.addr.bar is a client there as well, and the rate limit applies per-server apparently because after sending a message, the rate is the same for the two client accounts. It was reduced by one after sending a message.

The main contact point doesn't include information about the remaining messages.

1. Why `tricurse.com/contact` Did Not Include Remaining Messages

The reason `novy.addr.bar` returned the remaining messages message while `tricurse.com/contact` returned only generic reachability was due to an **HTTP 301 trailing-slash redirect**:

1. **Root vs. Subdirectory**:
   - `novy.addr.bar` has `index.php` installed at the website root (`/`). When probed, the web server directly answered the `POST action=check_availability` request and returned the JSON API response containing `rate_limit_remaining`.
   - `tricurse.com` has its contact suite inside the `/contact/` subdirectory. When querying `https://tricurse.com/contact` (without the trailing slash), Nginx responded with an HTTP `301 Moved Permanently` directing to `https://tricurse.com/contact/`.
2. **Loss of POST Data During Redirect**:
   - When PHP's stream context automatically followed the 301 redirect, it converted the HTTP method from **POST** to **GET** and dropped the POST payload (`action=check_availability`).
   - `https://tricurse.com/contact/` therefore received a standard GET request and returned the full HTML webpage instead of the JSON API response.
   - Because the response was HTML rather than JSON, the checker fell back to displaying: 🟢 `Available: Website is online and reachable over HTTPS.`

Solution Applied:

In `db.php`:

- `check_destination_availability()` now includes directory candidate variations (both `/contact` and `/contact/`).

- It captures 301/302 redirects and preserves the POST request and payload across the redirect to the target URL.
- Probing `tricurse.com/contact` now returns the complete status including remaining messages:

```
Array
(
    [success] => 1
    [available] => 1
    [domain] => tricurse.com
    [client_name] => Tricurse
    [role] => main
    [rate_limit_remaining] => 100
    [message] => Website is online and available to receive messages.
)
```

---

2. Why the Rate Limit Reduced for Both Clients on the Server

Your observation is completely accurate:

1. **Shared Database Architecture**:
   `novy.addr.bar` and `karo.addr.bar` are both client accounts on the same server, sharing the central server database (`contact.sqlite`).
2. **Sender-Based Quota**:
   The rate limiter on the receiving server counts how many messages have arrived from a particular sender domain (`hotletter.neolamia.com`) in the last 24 hours:

   ```
   SELECT COUNT(*) FROM incoming_messages
   WHERE sender_host = ? AND is_sent_copy = 0
     AND received_at >= datetime('now', '-24 hours')
   ```

3. Because all incoming messages received by any client on that server reside in that shared database, a message sent from `hotletter.neolamia.com` to `novy.addr.bar` counts against `hotletter.neolamia.com`'s daily allowance for that server.
   When checking either client (`novy.addr.bar` or `karo.addr.bar`), the receiving server calculates remaining messages based on how many messages `hotletter.neolamia.com` has delivered to the server in that 24-hour window, which is why both counts decreased by one.