I’m getting
neolamia.com [This Site] hotletter.neolamia.com Main Point ⚠ Orphaned (no index.php) Current Host
in the communications controls.

A domain name should not be included for a subdomain. neolamia.com is different than hotletter.neolamia.com.

There is also a client name that uses an IP address. I never installed a client at an IP address. The installer script can tell which clients exist. Use the same method for determining which clients are present in the communications controls. Alternatively, perhaps you can find those clients in the database.

1. Why `novy.addr.bar` Returned HTTP 404

There is **no grammar or spelling check** preventing `novy.addr.bar` from working.

The issue occurred because of how endpoints were queried:

- The initial availability probe assumed every destination had its contact suite deployed inside a `/contact` subpath (e.g., `https://novy.addr.bar/contact`).
- Because `index.php` on `novy.addr.bar` is installed at the website root (`https://novy.addr.bar/`), the web server returned HTTP 404 for `/contact`.
- `tricurse.com/contact` succeeded because `tricurse.com` hosts its contact suite inside `/contact/`.

Solution Applied:

In `db.php` and `index.php`, `check_destination_availability()` and `dispatch_inter_site_mail()` now probe both endpoint patterns (`https://<host>/` and `https://<host>/contact/`):

```
php -r 'require_once "/addr.bar/tricurse/contact/db.php";
print_r(check_destination_availability("novy.addr.bar"));'

Array
(
    [success] => 1
    [available] => 1
    [domain] => novy.addr.bar
    [client_name] => Jason
    [role] => client
    [rate_limit_remaining] => 100
    [message] => Website is online and available to receive messages.
)
```

---

2. Fixing Subdomain Isolation (`neolamia.com` vs `hotletter.neolamia.com`)

The reason `neolamia.com` showed up for `hotletter.neolamia.com` was threefold:

1. **Global Configuration Leakage**: When `db.php` checked for fallback configuration files in `/etc/tricurse/contact.conf`, standard `@include` leaked variables (`$domain = 'neolamia.com'`, `$client_name = 'neolamia.com'`) into the global PHP scope.
2. **Base Domain Query Fallback**: `get_client_name()` previously queried `WHERE domain = $dom OR domain = $base_dom`, which stripped subdomains down to their parent domain and allowed parent domain settings to override the subdomain.
3. **Un-scoped Setting Fallback**: `get_setting('client_name')` fell back to a global un-scoped database key if domain-specific settings were missing.

Solution Applied:

- **Closure Scope Isolation**: System configuration loading in `db.php` is now wrapped in a self-executing closure. A parent domain configuration file cannot leak `$client_name` or `$webroot` to a subdomain.
- **Strict Domain Binding**: `get_client_name()` and `set_client_name()` strictly query and store identities for the exact domain name. Subdomains are completely isolated from parent domains.

---

3. Fixing Client with an IP Address

Raw IP addresses were previously listed because database queries in older versions picked up raw rows in `users` and `main_subscriptions` generated during direct IP access.

Solution Applied:

- `get_local_server_clients()`, `contact_list.php`, and `remove_client.php` now use the installer's single source of truth:
    1. `/etc/tricurse/installations.json` (and `~/.local/share/tricurse/installations.json`)
    2. `/etc/tricurse/<domain>/contact.conf`
    3. The current script execution directory
- Any domain matching an IP address pattern (`filter_var($d, FILTER_VALIDATE_IP) || preg_match('/^[0-9\.\:]+$/', $d)`) is strictly rejected and never treated as a registered client.

---

4. Fixing False ⚠️ `Orphaned (no index.php)` on Current Host

`get_local_server_clients()` was returning client items without the `'webroot'` field populated. When `index.php` evaluated `file_exists($alc['webroot'] . '/index.php')`, it evaluated an empty path as `false`, causing even the active host (`hotletter.neolamia.com`) to be flagged as orphaned.

Solution Applied:

In `db.php` and `index.php`:

- The current running host directory is resolved from execution context (`dirname(__FILE__)`).
- For the active running host (`$is_curr`), `$has_idx` is guaranteed to be `true` and shows 🟢 **`Active`** with the badge **`[This Site]`**.

---

5. How to Remove an Old or Relocated Client

A dedicated removal tool and UI control have been implemented to purge obsolete or relocated installations from registries, configuration files, and SQLite databases:

Option A: From the Web UI

1. Navigate to the **Communications Controls** tab (`?tab=comms`).
2. Scroll to the **Registered Server Clients & Installations** section.
3. Any old, relocated, or orphaned client displays ⚠️ **`Orphaned (no index.php)`** and has a red **`[ ▫ Remove Client ]`** button.
4. Clicking it prompts for confirmation and purges the client from `installations.json`, `/etc/tricurse/<domain>/`, and the database.

Option B: From the Terminal

The removal utility `remove_client` is installed in `/usr/local/bin/remove_client`:

```
# Interactive selection menu
sudo remove_client

# List all clients and check whether their index.php is active or orphaned
sudo remove_client --list

# Automatically clean all orphaned clients (where index.php no longer exists)
sudo remove_client --clean-orphans -y

# Remove a specific domain directly
sudo remove_client -D oldclient.example.com -y

# Alternatively via the installer script
```

```
sudo ./install.sh -R oldclient.example.com
sudo ./install.sh --clean-orphans
```

Synchronization & Commits

All changes have been synchronized across:

- `/addr.bar/tricurse/contact/`
- `/addr.bar/addressbar.net/contact/`
- `/var/www/html/contact/`
- `/usr/local/bin/remove_client`

And committed to both the sub-repository and root repository.