I’m getting a

Unavailable: Contact endpoint not found on destination website (HTTP 404).

when I try to contact novy.addr.bar

Is it because of the spelling? I can reach tricurse.com/contact. Is there some grammar check that prevents it from working?

It looks like the contact directory might be required, according to your feedback from the last request. However, I have installed the index.php page as the main page of the website, novy.addr.bar.

Implement a way to remove a client from the installation. In a previous installation, I changed the location for the installation. I want to remove the old client. There’s no longer an index.php there for them.

1. Why `novy.addr.bar` returned HTTP 404 (and why `tricurse.com/contact` worked)

There was **no grammar check or spelling issue**.

Here is what occurred:

- On `tricurse.com`, `index.php` was installed into a subfolder (`https://tricurse.com/contact/`).
- On `novy.addr.bar`, `index.php` was installed as the **main page at the root** of the website (`https://novy.addr.bar/`).
- In the original probe helper, any destination entered without a `.php` filename had `/contact` unconditionally appended to it. Probing `https://novy.addr.bar/contact` returned **HTTP 404 Not Found** because `novy.addr.bar` has no `/contact` directory.

The Fix

`check_destination_availability()` in `db.php` and `dispatch_inter_site_mail()` in `index.php` now automatically test both root and subfolder candidate endpoints:

1. If you enter an explicit subpath (e.g. `tricurse.com/contact`), it checks that exact path.
2. If you enter just a domain or hostname (e.g. `novy.addr.bar` or `tricurse.com`), it probes `https://<domain>/` (root) and `https://<domain>/contact/`.

- On `novy.addr.bar`, the root endpoint answers immediately with: `{"success":true,"available":true,"domain":"novy.addr.bar","client_name":"Jason","role":"client",...}`
- On `tricurse.com`, it seamlessly resolves to the `/contact/` endpoint.

---

2. Client Removal & Relocation Cleanup

A client removal and orphan cleanup feature has been implemented to handle instances where an installation directory was changed or where `index.php` is no longer present.

A. Dedicated CLI Utility: `remove_client`

Installed globally to `/usr/local/bin/remove_client`:

```
# 1. Interactive selection menu showing all clients and their live status:
sudo remove_client

# 2. One-command cleanup of all orphaned installations (where webroot has no
index.php):
sudo remove_client --clean-orphans

# 3. Direct removal by domain:
sudo remove_client -D oldclient.example.com -y

# 4. List all registered installations and active/orphan status:
remove_client -l
```

B. Installer Flags in `install.sh`

```
# Clean orphaned installations:
sudo ./install.sh --clean-orphans

# Remove a specific client:
sudo ./install.sh --remove oldclient.example.com
```

C. Automatic Relocation Detection

When installing or moving an installation to a new directory, `install.sh` and `is_client_domain_unique()` check if the old registered location still has `index.php`. If `index.php` is missing at the old location, the script detects that you relocated the client, removes the stale record from `/etc/tricurse/installations.json`, and completes the new installation without blocking you.

D. Web Interface Removal

Under **Communication Controls** (`tab=comms`), a **Registered Server Clients & Installations** section now displays all local clients with their directory and status (🟢 `Active` or ⚠️ `Orphaned`

(no index.php)), with a **[× Remove Client]** button next to each entry to purge stale clients with a single click.

What Gets Cleaned When a Client is Removed

1. **Installation Registries**: Removed from `/etc/tricurse/installations.json` and `~/.local/share/tricurse/installations.json`.
2. **Configuration Files**: Purged from `/etc/tricurse/<domain>/` and `/etc/tricurse/<domain>.conf`.
3. **Database Records**: Purged from `users`, `main_subscriptions`, `site_settings`, `login_attempts`, `push_subscriptions`, and `push_disabled_sources` in `contact.sqlite`.
4. **Hosts File**: Cleans the `127.0.0.1 <domain>` loopback entry from `/etc/hosts` if no other client uses it.