Remove Block Site for inner messages.

The **[🚫 Block Site]** option has been removed for inner messages, and safeguards have been implemented to ensure inner/local server sites cannot be blocked.

Key Changes

1. **Inner Message Detection & Button Removal (`db.php`, `index.php`)**:
    - Implemented `is_inner_message($msg, $pdo)` in `db.php` to identify inner messages:
        - Messages flagged as intra-server group letters (`is_server_group_letter = 1`).
        - Broadcasts sent from the main contact point / transmitter to subscribers (`is_broadcast_from_main = 1`).
        - Messages originating from any client or domain within the local server group (`is_sender_in_server_group()`).
        - Messages from local loopback (`localhost`, `127.0.0.1`, `::1`) or the server IP.
    - In `index.php`, the `[ 🚫 Block Site ]` button is completely omitted for all inner messages, while remaining available for messages received from outside websites.
2. **Blocklist Safeguards (`index.php`, `index.php`)**:
    - In the `block_site` action handler, blocking any inner or local server domain is rejected with a notice (`Inner server websites cannot be blocked.`) and redirected cleanly to the originating view.
    - In `is_site_blocked()`, inner server group domains and local senders are exempted from being evaluated as blocked.
3. **Multi-Directory Synchronization**:
    - Synchronized changes across `/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`.