When installed as an app, the visitor must be logged in before push notifications can be activated.

The requirement has been implemented across the client interface and server endpoint:

1. Client-Side Enforcement (`index.php`)

- **Installed App Detection**: Added `isInstalledApp()` to detect standalone, fullscreen, and minimal-ui PWA containers.
- **Login Requirement on Push Actions**:
  - `enablePushDirectly()`, `performPushSubscribe()`, and `togglePushSubscription()` now verify whether the visitor is authenticated (`isClientLoggedIn`) when running inside an installed app container.
  - If unauthenticated, push registration is blocked, an alert notifies the visitor that sign-in is required before push notifications can be activated, and the view smoothly scrolls and focuses the host password login input (`#loginPassword`).
- **Dynamic First-Launch Banner (`pwaFirstLaunchPushBanner`)**:
  - When opened as an installed app by an unauthenticated visitor, the banner displays:

    > *"Push notifications were deactivated for this newly installed standalone app container.* ***When installed as an app, the visitor must be logged in before push notifications can be activated.*** *Please sign in below to activate notifications."*

  - The primary action button displays `[ 🔐 Sign In to Activate Push ]` and scrolls directly to the login field.
  - Once the user logs in, the banner switches to `[ 🔔 Reactivate Push Notifications ]` (or the post-login prompt banner `#pushSignInPromptBanner` displays `[ 🔔 Enable Push Notifications ]`).
- **Header & Settings Status**: When viewed in standalone mode without logging in, the push button displays `[ 🔔 Push: Login Required ]` and the settings button displays `[ 🔒 Sign In to Enable Push ]`.

---

2. Server-Side Protection (`index.php`)

- The `save_push_subscription` endpoint checks whether the request originates from an installed app container (`is_standalone` in payload or `X-Installed-App` / `X-Standalone` request headers).

- If the visitor is not logged in (`!is_logged_in()`), the server immediately rejects the request with **HTTP 403 Forbidden**:

```
{
  "success": false,
  "error": "When installed as an app, the visitor must be logged in before
push notifications can be activated."
}
```

- Subscriptions are never inserted into the database unless authenticated.

---

3. Verification & Documentation

- **Automated Tests**: Tested unauthenticated requests from installed app containers via both JSON payload (`is_standalone: 1`) and `X-Installed-App` headers; verified both return HTTP 403 Forbidden and make zero insertions into `push_subscriptions`. Verified authenticated requests succeed (HTTP 200) and save subscriptions properly.
- **Documentation Updated**: Updated `INSTALL.md` and `README.md` to document the login requirement for installed app containers.
- **Targets Synchronized**: Changes deployed to `/addr.bar/addressbar.net/contact/` and `/var/www/html/contact/` and committed to git.