When sending messages to an external contact point, optionally include all destinations in the message information. Any messages delivered internally include the full recipient list. Change the option to Include all 'To' destinations in messages arriving to external sources. Those messages exclude internal recipients.

The destination distribution logic and form options have been updated to cleanly separate internal and external recipients:

Key Changes

1. **Send Mail Form Checkbox Option (`index.php`)**:
    - Updated the checkbox label in the federated mail form to: **`Include all 'To' destinations in messages arriving to external sources`**
2. **Internal Deliveries Full Recipient List (`index.php`, `index.php`)**:
    - Any message delivered internally (sent copy in sender outbox `sent_messages`, sender inbox `incoming_messages`, local server group deliveries, and central transmitter broadcasts) always includes the **full recipient list** (`all_recipients_full`), regardless of whether the external distribution checkbox is checked.
3. **External Contact Point Filtering (`db.php`, `index.php`)**:
    - Implemented `is_internal_destination($destination, $pdo)` in `db.php` to distinguish internal server group/loopback clients from remote external websites.
    - When dispatching to external contact points:
        - If the option is **checked**: `all_recipients` contains only external destinations, strictly **excluding all internal recipients**.
        - If the option is **unchecked**: `all_recipients` is omitted (`''`).
4. **Delayed Message Resend Consistency (`index.php`)**:
    - When re-sending delayed messages, external contact points similarly have internal recipients stripped from the visible distribution list.
5. **Documentation & Synchronization**:
    - Synchronized changes and documentation across `README.md`, `/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`.

Any message delivered to another client is already included in the inboxes of all other clients—is that correct? So, if a message is sent to an external source and includes one recipient on the server, all clients on the server will also receive a copy. Is that correct?

Yes, that is correct. Here is exactly how the system handles both scenarios:

---

1. "Any message delivered to another client is already included in the inboxes of all other clients—is that correct?"

- **Intra-Server Group Messages (YES):** Any letter sent from within the server group to another client (or to the main contact point/transmitter) is automatically received in the inboxes of **all** clients in the server group as a group letter. Each client maintains their own independent read receipt and archive status.
- **External Mail Exception (NO):** If an individual client receives mail directly from an **external website** outside the server, only that specific client receives it in their inbox—other clients on the server do not receive copies of external mail addressed solely to that peer.

---

2. "So, if a message is sent to an external source and includes one recipient on the server, all clients on the server will also receive a copy. Is that correct?"

- **YES, absolutely.**
- Because the sender is on the server and at least one destination is a client on the server:
    1. The letter delivered to the local client constitutes an **intra-server group communication** (both sender and target are within the server group).
    2. In the shared SQLite database, that letter is automatically accessible to **all clients on the server** in their inboxes.
    3. All clients on the server will see the **full recipient list** on their copy.
    4. The external source receives its own transmission, which **excludes the internal server recipients** from the visible distribution list.