Use preset names for destinations within the local server. Implement a drop down to select a name of a client on the local server in the Send Mail form. Mail from an external server shouldn't include a name.

The requested changes have been implemented, verified, and synchronized across all deployment directories:

Key Enhancements

1. **Preset Names for Destinations Within Local Server**:
    - Added `get_local_server_clients()` in `db.php` to retrieve all client accounts on the local server and their administrator-configured preset names across `installations.json`, `contact.conf`, `main_subscriptions`, and `users`.
    - Added `get_preset_name_for_destination()` and `format_destination_display()` to render local destinations using their preset client names (while formatting external destinations cleanly without `https://` or `index.php`).
    - Added `resolve_client_destination()` to automatically resolve a destination specified by preset name into its endpoint URL.
2. **Local Server Client Drop-Down in Send Mail Form**:
    - Added `<select id="localClientSelect">` and HTML5 `<datalist id="localClientsDatalist">` in the Send Mail form of `index.php`.
    - Selecting a client from the drop-down immediately populates an open destination row or appends a new destination row with that client's preset name.
    - Input rows are autocomplete-connected to the datalist so typing matching client names is suggested.
3. **External Mail Name Suppression**:
    - In incoming mail handling (`action === 'inter_site_mail'`), `is_sender_in_server_group()` checks if the sender is part of the local server group. For external senders, `sender_name` is suppressed and stored as `NULL` in the database.
    - In inbox message cards, sent messages, and push notification payloads, messages from external servers strictly omit any sender name and display only the clean sender host/domain (without `https://` or `index.php`).
    - In the inbox reply button, replying to an external sender addresses their clean domain, whereas replying to a local client uses their preset name.

Verification & Synchronization

- Unit tests verified preset name lookup, resolution, clean destination formatting, and external sender name suppression.
- Synchronized updated `db.php` and `index.php` to:
  - `/addr.bar/addressbar.net/contact/`
  - `/var/www/html/contact/`
- Committed changes to git repositories in `/addr.bar/tricurse/contact` and `/addr.bar`.