In new installations, set the default website endpoint URL in the send mail form to the main contact point.

The default website endpoint URL in the send mail form has been updated to automatically target the **Main Contact Point** on new installations.

Changes Implemented

1. **Endpoint Resolution Logic (`db.php`)**:
    - Added `get_main_contact_point_url($domain)` to dynamically resolve the active Main Contact Point endpoint URL by checking:
        1. Domain-scoped `subscribed_to_main_url` / `subscribed_to_main_domain` in `site_settings`.
        2. Client subscription entries in `main_subscriptions`.
        3. Global server installation registries (`/etc/tricurse/installations.json`, `~/.local/share/tricurse/installations.json`).
        4. Existing configuration files in `/etc/tricurse/`.
        5. The server's own endpoint when running with the `main` role (`https://<main-domain>/contact`).
    - Added `get_default_mail_destinations($domain)` which returns saved custom destinations if configured, and falls back to `[['url' => get_main_contact_point_url($domain), 'user' => '']]` on clean installations.
2. **Automated Setup in Installer (`install.sh`)**:
    - In Step 4 of installation, automatically determines the Main Contact Point endpoint URL for clients (`$SUBSCRIBE_TO` or `$DETECTED_MAIN`) or main recipient servers (`https://$DOMAIN/contact`).
    - Initializes `site_settings` with `subscribed_to_main_url` and populates `default_mail_destinations` with the Main Contact Point endpoint.
3. **Dynamic Frontend & Form Defaults (`index.php`)**:
    - Replaced static fallback instances with the dynamic `$primary_default_endpoint`.
    - Exposes `defaultEndpointUrl` to the browser runtime:
        1. Pre-fills empty destination rows with the Main Contact Point endpoint.

2. Dynamic placeholders in the Send Mail form, Distribution List Editor, and help modals now display the resolved Main Contact Point URL rather than hardcoded URLs.

4. **Schema Clean Seeding (`schema.sql`)**:
    - Set the default database seed for `default_mail_destinations` to empty (`''`), allowing dynamic resolution to take effect seamlessly on any fresh database initializations.
5. **Synchronization & Verification**:
    - Verified functionality across client and main contact point setups.
    - Synchronized all updated files to **`/addr.bar/addressbar.net/contact/`** and **`/var/www/html/contact/`** and committed to git.