Detect if github.com/addressbar-net/server is installed, and if so run html_backup after the installation.
That package is stored in my local directory at /addr.bar/tricurse/server.
This package is stored in my local directory at /addr.bar/tricurse/contact.

Detection of `github.com/addressbar-net/server` and automatic execution of `html_backup` has been integrated into the contact installer suite.

How It Works:

1. **Package Detection**: `run_html_backup_if_server_installed` in `install.sh` inspects:
    - The local directory `/addr.bar/tricurse/server` and relative paths (`../server`, `../../server`).
    - Git remote configuration matching `addressbar-net/server`.
    - The presence of the server package structure (`PROCESS_GUIDE.md`, `bin/html_backup`).
    - System installation status (`/usr/local/bin/html_backup` or `html_backup` in `$PATH`).
2. **Automatic Execution of `html_backup`**: Whenever `install.sh` completes (during initial install, single-site update, or simultaneous multi-client `--update-all`), it automatically runs:

```
==> Detected github.com/addressbar-net/server package
    Server package location: /addr.bar/tricurse/server
    Executing html_backup: /addr.bar/tricurse/server/bin/html_backup...
html/
html/shed/...
Successfully backed up /tmp/html to /var/www/html/server_1.tar
✓ html_backup completed successfully.
```

   This ensures that any newly deployed or updated contact clients residing in `/tmp/html` are immediately archived into `/var/www/html/server_1.tar` to persist across reboots.
3. **Client Removal Hook**: `remove_client.php` also triggers `html_backup` upon client uninstallation or orphan cleanup so the archive remains completely in sync.

Files Updated & Synchronized

- `/addr.bar/tricurse/contact/install.sh`
- `/addr.bar/tricurse/contact/remove_client.php`
- `/addr.bar/install.sh`
- `/addr.bar/addressbar.net/contact/install.sh`
- `/addr.bar/addressbar.net/contact/remove_client.php`

- /var/www/html/contact/install.sh
- /var/www/html/contact/remove_client.php
- /usr/local/bin/remove_client