Enable all letters within the server group to be received in the inbox of all clients.

You can mail the transmitter if there's no specific contact point. The main contact point serves that function. It can broadcast to the group. If an individual client receives mail from another website, it isn't received in the inbox of other clients.

The implementation is complete.

Key Changes Implemented

1. **Intra-Server Group Letter Delivery (`db.php`)**:
    - Added `get_server_group_domains()` and `is_sender_in_server_group()` to discover and normalize all member domains in the group (main contact points, subscribed clients, registered user domains, and local installations).
    - In `get_inbox_messages_for_domain()`, added query resolution for intra-server group correspondence: any letter sent by a server group member to another group member is retrieved and presented across the inboxes of all clients in the group with the badge 👥 `Server Group Letter`.
2. **Transmitter Broadcast Function (`db.php` & `index.php`)**:
    - When any sender (including outside websites without a specific contact point) mails the transmitter (the main contact point), the letter broadcasts to the group, appearing in the inboxes of all subscribed clients with the badge 📢 `Transmitter Broadcast (domain)`.
3. **External Mail Isolation for Individual Clients (`db.php`)**:
    - When an external website sends mail directly to an individual client, the message is delivered strictly to that specific client's inbox (`target_domain = ?`).
    - Because the sender is outside the server group and the target is an individual client (not the transmitter), other clients cannot query or view the message.
4. **Independent Read Status & Deletion Isolation (`db.php` & `index.php`)**:
    - Each client tracks read status independently via `message_reads`. When one client marks a shared letter as read, it remains unread for other group members.
    - Deletion of shared letters uses `message_deletions` per client domain. Deleting a shared letter from one client's inbox removes it only for that client, keeping the database record intact for other clients.
5. **Local Delivery Fallback (`index.php`)**:

- When letters are dispatched within the server group, if loopback HTTP is unavailable, messages are delivered directly to the local recipient domain in the database.

All mirror directories (`/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`) have been updated and synchronized.