Allow <a> elements to be used in text. When they're displayed in the message, they're shown as hyperlinks.

`<a>` elements are now supported in message text and displayed as clickable hyperlinks in both the inbox and archive.

Summary of Implementation

1. **Hyperlink Rendering Helper (`format_message_body_html`)**:
    - Added in `db.php`.
    - Parses `<a>` elements in the message text (e.g., `<a href="https://example.com">Example Site</a>`, `<a href="mailto:...">...</a>`, or domain addresses without scheme like `<a href="example.com">...</a>`).
    - Renders them as clickable links with `target="_blank"` and `rel="noopener noreferrer"`.
    - Inherits the terminal interface styling (`color: var(--hot-letter-orange); text-decoration: underline; font-weight: bold;` with hover effects).
2. **Security & Sanitization**:
    - **XSS Protection**: All non-anchor HTML tags (such as `<script>`, `<iframe>`, `<object>`, `<style>`, etc.) are escaped with `htmlspecialchars`.
    - **Safe Protocols Only**: Only safe URL schemes (`http://`, `https://`, `mailto:`, `ftp://`, or relative paths) are allowed. Dangerous protocols such as `javascript:`, `data:`, and `vbscript:` are blocked, rendering only the safe inner text.
    - **Attribute Whitelist**: Dangerous DOM event attributes (like `onclick`, `onmouseover`, etc.) are stripped, preserving only sanitized `href` and optional `title`.
    - **Link Text Escaping**: HTML inside the link text itself is escaped to prevent tag injection within anchor tags.
3. **Display & Compose UI Updates**:
    - **Inbox & Archive**: Updated in `index.php` to render message bodies through `format_message_body_html()` with `overflow-wrap: anywhere; word-break: break-word` to ensure long URLs never overflow the container.
    - **Compose Form**: Added a hint below the message textarea informing senders that `<a>` elements are supported.

All changes have been tested and synchronized across `/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`.