If a client on the server implements a block does it apply for the others too?

Yes, currently it applies to all clients on the server.

Why It Applies Server-Wide:

1. **Shared Database Table**:
   All clients on the same server share the unified database (`contact.sqlite`). The `blocked_sites` table stores entries globally:

```
CREATE TABLE blocked_sites (
    id INTEGER PRIMARY KEY AUTOINCREMENT,
    domain_or_url TEXT NOT NULL UNIQUE,
    ip_address TEXT DEFAULT NULL,
    reason TEXT DEFAULT NULL,
    is_blocked INTEGER DEFAULT 1,
    created_at TEXT DEFAULT (datetime('now'))
);
```

2. **Server-Level Gateway Enforcement**:
   When any client adds a domain to the blocklist (via the **Block Site** button in the Inbox or under **Communications Controls**), it inserts a row into `blocked_sites`.

3. **Global Rejection**:
   When incoming messages or availability checks arrive at the server from that blocked domain, `is_site_blocked()` queries `SELECT * FROM blocked_sites WHERE is_blocked = 1` across the database. The server rejects communications from that sender for **all local clients**, and the entry appears in the blocklist table across all accounts on that server.

> [!NOTE] If you would like blocks to be **individual per client** (so client A can block a sender without affecting client B's ability to receive messages from them), or if site blocking should be restricted to the **Main Contact Point**, let me know and we can add a domain-scoping column to `blocked_sites`.