Implement a feature that enables a client to see if another website is available for a message before writing one. Require every client to have the index.php page at a unique domain. It could be a domain or subdomain. It might be needed for SSL to verify the sender and adhere to the limits.

The **Pre-Message Website Availability Check** and the **Mandatory Unique Domain/Subdomain Requirement for Clients** have been implemented.

Summary of Implementation

1. Pre-Message Website Availability Check

- **Destination Verification Engine** (`db.php`):
  - Added `check_destination_availability($destination, $sender_url, $pdo)`:
    - **Local Server Clients**: Resolves preset client names and domain aliases against local group registrations. Checks whether incoming communications are enabled (`allow_incoming_communications`) and whether the client has reached its daily message rate limit (`rate_limit_inside_per_day`).
    - **External Websites**: Dispatches a lightweight non-blocking HTTPS probe (`stream_context_create()` with a 4-second timeout) to `https://<domain>/contact` with `action=check_availability`. Returns live availability, daily quotas, or reason codes (`communications_disabled`, `rate_limited`, `blocked`, or `unreachable`).
- **AJAX Endpoints** (`index.php`):
  - `action=check_availability`: Inbound federated endpoint returning JSON indicating if this site is available, accepting mail, sender block status, and remaining quota.
  - `action=check_peer_availability`: Local AJAX proxy endpoint enabling browser checks without CORS restrictions.
- **Compose Mail Interface UI** (`index.php`, L4558-L4605):
  - Added `[ 🔍 Check Availability ]` toolbar button above the `To:` field to check all destination rows at once.
  - Added `[ 🔍 Check ]` button on each individual destination row.
  - When selecting a client name from the **Local Server Client** dropdown, it automatically inserts the client and initiates a check.
  - Real-time status badges displayed beneath the destination field:

- 🟢 `[ 🟢 Available ]`: Site is online and ready (with daily message allowance).
- ⏳ `[ ⏳ Rate Limited ]`: Destination has hit its 24-hour rate limit.
- 🚫 `[ 🚫 Communications Disabled ]`: Incoming communications turned off on the target site.
- 🚫 `[ 🚫 Blocked ]`: Sender website is blocked by target host.
- 🔴 `[ 🔴 Unavailable / Unreachable ]`: Network timeout, SSL failure, or 404 contact endpoint not found.

2. Unique Domain or Subdomain Enforcement Per Client

- **Why It Is Required**:
  - **SSL/TLS Certificates**: SSL SNI certificates and HTTPS validation operate strictly on hostnames (domains or subdomains), not directory paths.
  - **Inter-Site Sender Verification**: Federated trust and reverse verification look up `sender_host` (e.g., `client1.example.com`).
  - **Rate Limit Isolation**: Daily rate limits in SQLite are enforced per host (`WHERE sender_host = ?`). Shared domains would cause separate clients to exhaust each other's sending quotas.
- **Installer Enforcement** (`install.sh`, L709-L747):
  - Updates prompt to require a unique domain or subdomain (e.g. `client1.example.com`).
  - Checks `/etc/tricurse/installations.json` and rejects attempts to deploy multiple clients under the same domain name at different directories.
- **PHP Domain Validator** (`db.php`):
  - Added `is_client_domain_unique($domain, $exclude_webroot, $pdo)`.

3. Documentation & Synchronization

- Documented in `README.md` and `INSTALL.md`.
- Synchronized across `/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`.