When an update to contact is available it should be able to be installed for all clients on a server simultaneously. When an update is installed, try to maintain push notifications that were already present. When a client signs in, if push notifications aren't enabled, prompt them to. When the app is installed and opened for the first time, deactivate and prompt the user to reactivate push notifications.

All requested features have been implemented and verified:

1. Simultaneous Multi-Client Server Updater

- **CLI Utility & Option**: Added `--update-all` (`-A`) to `install.sh` and installed the global CLI tool `contact_update_all` (backed by `contact_update_all.php`).
- **Simultaneous Execution**: Reads the server installation registry (`/etc/tricurse/installations.json` and `/etc/tricurse/*/contact.conf`), pulls git changes once, and updates all registered client domains and folders simultaneously without touching their sovereign databases or settings.

2. Push Notification & VAPID Key Preservation During Updates

- Both single update (`--update`) and multi-client update (`--update-all`) explicitly verify and preserve existing `push_subscriptions` and `site_settings` VAPID key pairs.
- Schema updates apply safe additive migrations (`CREATE TABLE IF NOT EXISTS` and `INSERT OR IGNORE`), ensuring browser/device endpoints are never dropped, reset, or broken during server upgrades.

3. Prompt to Enable Push Notifications Upon Sign-In

- In `index.php`, when a host signs in (`is_logged_in()`), the app checks whether Web Push is active in the current browser.
- If push notifications are not enabled, a dismissible banner (`pushSignInPromptBanner`) prompts the user to activate notifications with a direct one-click `[ 🔔 Enable Push Notifications ]` action.

4. PWA First-Launch Push Deactivation & Reactivation Prompt

- In `index.php`, standalone app launches are detected via `(display-mode: standalone)` and `localStorage.getItem('pwa_app_opened_first_time')`.
- On the first standalone launch, any stale subscriptions from prior browser sessions are unsubscribed and removed from the server, and a banner (`pwaFirstLaunchPushBanner`) welcomes the user and prompts them to click `[ 🔔 Reactivate Push Notifications ]` for the dedicated app container.

5. Documentation & Sync

- Updated `README.md` and `INSTALL.md` with `contact_update_all`, multi-client updates, push preservation, and PWA first-launch reactivation instructions.
- Synchronized all assets to `/addr.bar/install.sh`, `/addr.bar/addressbar.net/contact/`, `/var/www/html/contact/`, and `/usr/local/bin/`.