Do the recipients at the server see they're both in the destination currently?

Yes, they do—provided the external sender included the recipient list in the message (which is enabled by default via the *"Include all 'To' destinations in messages arriving to external sources"* option on the sending server).

Here is how it works depending on what the external sender provided:

---

1. When the External Sender Includes All Destinations (Standard)

- The external server delivers the message with the `all_recipients` field containing both endpoints.
- When **either recipient** opens their inbox (or archive), a distribution bar is displayed right above the message body:

```
To: [Client A's Preset Name]; [Client B's Preset Name]
```

- Because `format_destination_display()` automatically checks the local server's database, both local addresses are translated into their recognizable **preset names**.
- **Result:** Both recipients can clearly see that both of them were addressed in the message.

---

2. When the External Sender Omits Destinations (BCC / Unchecked Option)

- If the external sender unchecked the *"Include all 'To' destinations..."* checkbox or sent via an external script that only supplied `sender_url` and `message`:
  - The `all_recipients` field is blank.
  - The incoming message only displays `From: [External Sender]`.
- **Result:** Neither recipient sees the other's address, acting like a private or blind carbon copy.

When a message is received by a server with multiple local recipients, those recipients must AT LEAST be in the recipients list. That can be detected at the local server. The recipients don't have to be included by the sending server.

You are absolutely right. Because all client accounts on the local server share the underlying server environment and database, the local server already receives the delivery for each local client and therefore **knows exactly which local recipients were addressed**. We do not have to rely on the sending server to supply an `all_recipients` header.

What Was Implemented

1. **Automatic Local Recipient Detection (`sync_incoming_local_recipients`)**:
    - Added in `db.php` and hooked into both incoming POST processing and inbox/archive rendering in `index.php`.
    - When an external message arrives, the server checks for matching incoming records (same sender, identical message body, received in the same window) addressed to different local target domains on this server.
    - When multiple local recipients are detected, the system ensures that **all local recipients are AT LEAST included** in the `all_recipients` (`To:`) list across all matching message records.
    - If the sending server also included third-party external recipients in `all_recipients`, those external recipients are preserved and merged with the detected local recipients.
2. **Friendly Preset Name Resolution**:
    - The detected local recipients are resolved to their administrator-configured **preset names** (or clean domain addresses if no name is set).
    - In the inbox and archive of **every local recipient**, the metadata bar directly displays:

```
To: [Client A's Preset Name]; [Client B's Preset Name]
```

    - Both recipients can immediately see that both of them were included.
3. **Reply Banner Context**:
    - In `index.php`, when either recipient clicks `[ ↩️ Reply ]`, the reply notice banner displays the detected `Original To:` distribution list alongside the sender and subject, reminding the user who was originally addressed before they send their reply.

Verification

We tested this with two incoming messages from an external sender arriving for two different local domains without any `all_recipients` provided by the sender:

- Upon the arrival of the second message, the local server detected both local recipients and updated both records to `all_recipients = "Client A; Client B"`.
- We also tested with an external recipient already present (`external-friend.org/contact`); the system merged the list so that `all_recipients` became `external-friend.org/contact; Client A; Client B`.
- Changes have been tested and synchronized across all installations (`/addr.bar/tricurse/contact/`, `/addr.bar/addressbar.net/contact/`, and `/var/www/html/contact/`).