When Archive All Messages is clicked, some of the messages are left behind in the inbox.

Cause of Messages Left Behind in the Inbox

When **Archive All Messages** was clicked, messages remained in the inbox due to how message retrieval and deduplication interacted with the archive function:

1. **Deduplication Signature Skipping**:
    - In federated correspondence, multiple representations of a message can exist in `incoming_messages` with identical signatures (e.g., sent copy + main broadcast copy, intra-server group deliveries, multiple local recipients, or retry deliveries).
    - In db.php, `get_inbox_messages_for_domain()` calculates a signature `md5(sender || subject || body || time_window)` and skips duplicate rows to show only one card per message in the inbox.
    - When `archive_all_messages_for_domain()` previously called `get_inbox_messages_for_domain()`, it only received the deduplicated list. Consequently, it only inserted the ID of the **first** copy into `message_archives` and `message_deletions`.
    - The duplicate database row(s) were never archived. Upon reloading the inbox, the first copy was excluded by `id NOT IN (SELECT message_id FROM message_archives ...)`, leaving the second copy unexcluded and no longer considered a duplicate—causing it to immediately surface in the inbox.
2. **Single Message Archiving**:
    - Similarly, clicking `[ 📦 Archive ]` on an individual message only archived that specific row ID, leaving any sibling duplicate rows unarchived to appear on the next page refresh.
3. **Archive List Presentation**:
    - In the Archive tab, `get_archived_messages_for_domain()` did not deduplicate by signature, which could display multiple duplicate entries if sibling records were archived.

Changes Implemented

1. **Comprehensive Inbox Archiving (`archive_all_messages_for_domain`)**:
    - Updated in db.php: `archive_all_messages_for_domain()` now queries all eligible inbox message IDs for the domain directly in SQL (without deduplication skipping) and looks up any duplicate rows sharing those message signatures within the 24-hour delivery window.
    - All matching IDs are archived and deleted for both the domain and its base host, ensuring **zero** messages or sibling copies are left behind in the inbox.
    - Accurate distinct count is reported back to the session feedback.
2. **Signature-Aware Single Archiving & Unarchiving (`archive_message_for_domain` & `unarchive_message_for_domain`)**:
    - In db.php, archiving a single message now finds all duplicate rows matching that message's signature and archives them together.
    - Unarchiving restores all related copies back to the inbox.
3. **Archive View & Count Deduplication**:
    - In db.php, updated `get_archived_messages_for_domain()`, `count_archived_messages_for_domain()`, and `get_archive_periods_for_domain()` to deduplicate archived messages by signature, ensuring clean single entries and matching monthly counts.
4. **Inbox Limit**:
    - Raised default display limit in index.php from 50 to 200 to match the Archive view limit.
5. **Deployment & Verification**:
    - Tested all archiving, unarchiving, and deduplication workflows with automated tests.
    - Synchronized across `/addr.bar/tricurse/contact`, `/addr.bar/addressbar.net/contact`, and `/var/www/html/contact`.
    - Committed changes in both repositories (`21b3d37` in `tricurse/contact`, `3a6ffe3` in `/addr.bar`).