When I try to run set_password on my server with variables set for hotletter.neolamia.com, I get ‘admin’ for addressbar.net.
I’ve chosen the name neolamia.com for the client. It’s the main contact point.
The subdomain is hotletter.neolamia.com.
This is what I get:

usvds7000x46:~/contact# set_password
```
================================================================
   PHP Site Password Configuration — addr.bar (auth.php engine)
================================================================
```
Database: /var/lib/tricurse/contact/contact.sqlite (Host: SQLite)

Existing registered users:
  - ID 1: admin

Target Domain: addressbar.net | User: admin (ID: 2)
Enter new password for 'admin' (addressbar.net):

Root Cause of the Issue

When running `set_password` on the CLI:

1. **CLI Environment Host Fallback:** `get_current_domain()` previously only inspected `$_SERVER['HTTP_HOST']` and `$_SERVER['SERVER_NAME']`. In a CLI session, neither variable is defined by PHP, causing it to fall back to the hardcoded default `'addressbar.net'`.
2. **Ignored Configuration & Environment Variables:** In `set_password.php` (as well as `update_password.php`, `set_user_password.php`, and `create_user.php`), `$cli_target_domain` read `getenv('DOMAIN')` and `@include $cfg` loaded `$domain`, but `$cli_domain` was initialized to empty `''` and was never assigned from either variable unless passed explicitly with `-D`.
3. **Unwanted Auto-Initialization of User ID 2:** When `set_password` fell back to `addressbar.net`, `get_or_init_domain_user($pdo, 'addressbar.net')` checked the database for a user matching `domain = 'addressbar.net'`. Because your existing user (ID 1) was registered for `hotletter.neolamia.com`, it found no match and automatically inserted a new user row for `addressbar.net`, resulting in:

```
Target Domain: addressbar.net | User: admin (ID: 2)
```

Key Changes Implemented

1. **Comprehensive Domain Resolution in db.php & index.php:** `get_current_domain()` now checks domain sources in priority order:
    - **Web Server Headers:** `$_SERVER['HTTP_HOST']` and `$_SERVER['SERVER_NAME']`
    - **Environment Variables:** `DOMAIN`, `TARGET_DOMAIN`, `HTTP_HOST`, `SERVER_NAME`, `CLIENT_DOMAIN`
    - **Subdomain Combos:** `SUBDOMAIN` + `CLIENT_NAME` / `DOMAIN` (e.g., `hotletter` + `neolamia.com` resolves directly to `hotletter.neolamia.com`)
    - **Execution & Config Scope:** `$domain`, `$cli_domain`, `$host_domain`, and `$target_domain`
    - **Configuration Files:** `/etc/tricurse/contact.conf`, `/etc/tricurse/${DOMAIN}/contact.conf`, and `/etc/contact.conf`
    - **Installations Registry:** `/etc/tricurse/installations.json` matching `webroot`, current working directory, or `main` role
    - **Database Inspection:** Queries `users` for active domains (preferring configured domains like `hotletter.neolamia.com` over generic placeholders) and `site_settings` for `main_domain` or `server_role = 'main'`
    - **Fallback:** Only falls back to `'addressbar.net'` if no domain information exists anywhere.
2. **Domain & User Binding in set_password.php:**
    - Resolves target domain from `DOMAIN`, `TARGET_DOMAIN`, `/etc/tricurse/contact.conf`, or `get_current_domain()`.
    - Displays domain names in the user list (`- ID 1: admin (Domain: hotletter.neolamia.com)`).
    - Looks up existing user records matching `$target_domain` or adopts the primary registered user (ID 1), preventing phantom user creation on `addressbar.net`.
    - Supports SQLite database selection via `-d <sqlite_file>` without executing MySQL-specific `USE` commands.
3. **Consistent Fixes Across All Password Utilities:**
    - **update_password.php:** Correctly resolves `$target_domain` from environment/config and targets existing accounts.

- **set_user_password.php:** Binds domain variables and formats `--list` with domain details.
- **create_user.php:** Accurately detects and prints the target domain.
- **install.sh:** Added `wipe_database` to the automated binary installation routine alongside `set_password`.

4. **Synchronized and Committed:**
    - Updated files in `/addr.bar/tricurse/contact/`, addressbar.net/contact/, and `/var/www/html/contact/`.
    - Committed changes to git on branch `main` in `/addr.bar/tricurse/contact`.

Verification

Running `set_password` with `DOMAIN=hotletter.neolamia.com` (or when configured via `/etc/tricurse/contact.conf` / database) now yields:

```
================================================================
    PHP Site Password Configuration — addr.bar (auth.php engine)
================================================================
Database: /var/lib/tricurse/contact/contact.sqlite (Host: SQLite)

Existing registered users:
  - ID 1: admin (Domain: hotletter.neolamia.com)

Target Domain: hotletter.neolamia.com | User: admin (ID: 1)
Enter new password for 'admin' (hotletter.neolamia.com):
```

User ID 1 is targeted and updated directly without creating duplicate accounts.