Use /etc/tricurse/contact.conf. That will prevent name collisions. Offer to add the domain or subdomain to /etc/hosts. Recommend [/var/lib/tricurse/contact/domain-name] instead of [/var/lib/contact]. Does a separate /etc/tricurse directory need to be used for each client installation? If so, perhaps include the subdomain name in the directory for that too.

All of these updates have been implemented and committed across the codebase:

---

1. Does a separate `/etc/tricurse` directory need to be used for each client?

Yes, using a subdomain subdirectory under `/etc/tricurse/` is the cleanest, most standard Linux pattern for multi-tenant setups.

To eliminate name collisions when running multiple client subdomains on the same server, `install.sh` now generates:

```
/etc/tricurse/
├── contact.conf                              # Global fallback configuration
├── client1.example.com.conf                  # Flat client configuration
├── client1.example.com/
│   └── contact.conf                          # Dedicated per-client config
├── client2.example.com.conf
└── client2.example.com/
    └── contact.conf
```

How the CLI Utilities & Application Resolve It:

When `update_password`, `create_user`, or `db.php` runs:

1. If called with a specific domain (e.g. `update_password -D client1.example.com`), it automatically loads: `/etc/tricurse/client1.example.com/contact.conf`
2. If no domain is specified, it checks the web host (`$_SERVER['HTTP_HOST']`), then falls back to `/etc/tricurse/contact.conf`.
3. Multiple client configurations can now coexist on the same server with **zero risk of overwriting or collisions**.

---

2. Recommended Storage: `/var/lib/tricurse/contact/<domain-name>`

The default recommended storage directory in `install.sh` is now scoped to the domain name:

- **Storage Directory:** `/var/lib/tricurse/contact/<domain-name>/`

- **SQLite Database:** `/var/lib/tricurse/contact/<domain-name>/contact.sqlite`

When installing a new client, pressing Enter at the interactive prompt automatically assigns:

```
/var/lib/tricurse/contact/client1.example.com
```

---

3. Local Loopback in `/etc/hosts`

`install.sh` now checks whether the domain/subdomain is mapped to `127.0.0.1`:

- **Interactive Mode:** Prompts with a one-click confirmation:

```
  Local Loopback Configuration (/etc/hosts):
  Adding 'client1.example.com' to /etc/hosts allows clients on this server to
  deliver letters to each other
  instantly over local loopback (127.0.0.1), avoiding external network latency
  and NAT hairpinning.
  Add '127.0.0.1 client1.example.com' to /etc/hosts? [Y/n]:
```

- **Non-Interactive Flag (`-H` or `--add-hosts`):**

```
  sudo ./install.sh -D client1.example.com -d /var/www/client1 -H -y
```

Summary of Quick Install Command for a Client Subdomain

```
sudo ./install.sh \
  -D client1.yourdomain.com \
  -d /var/www/client1 \
  -m /var/lib/tricurse/contact/client1.yourdomain.com \
  -p 'Client1SecretPassword' \
  -H \
  -y
```

- **Web Root:** `/var/www/client1/` (serves `index.php` directly at `https://client1.yourdomain.com/`)
- **Storage:** `/var/lib/tricurse/contact/client1.yourdomain.com/contact.sqlite`
- **Configuration:** `/etc/tricurse/client1.yourdomain.com/contact.conf`
- **Local Loopback:** `127.0.0.1 client1.yourdomain.com` in `/etc/hosts`
- **CLI Tools:** Available globally in `/usr/local/bin/`