If the Reply button is clicked when a message is initiated for a message received from an external server by an individual client and not the main contact point and an inner-server client is included in the recipients list for it, the message becomes visible to all other clients when the reply is sent. The original message is visible, as well as the reply, which includes another client's name in the group (or the main contact point).

Implementation Overview

When an individual client (and not the main contact point) receives a message from an external server and initiates a reply via the **[↩️ Reply]** button that includes an inner-server client (or the main contact point) in the recipient list, **both the original message and the reply become visible to all other clients on the server**.

What Was Changed & Implemented

1. **Reply Context Tracking** (`index.php`, `index.php`):
    - Clicking `[ ↩️ Reply ]` in the Inbox or Archive now passes `&reply_to_id=<id>`.
    - The Mail Form stores this in a hidden field (`<input type="hidden" name="reply_to_id" ...>`) and displays a reply banner indicating which message is being replied to, advising that adding an inner-server recipient will share both the original message and reply across the server group.
2. **Group Sharing on Reply Dispatch** (`index.php`):
    - In `send_mail`, when replying to a message originally received from an external server by an individual client:
        - Detects if any destination is an inner-server client or the main contact point (`is_internal_destination($tu, $pdo)`).
        - Updates the original message row: `UPDATE incoming_messages SET shared_with_group = 1 WHERE id = ?`.
        - Delivers the reply locally to the shared SQLite database with `shared_with_group = 1` and `is_sent_copy = 0`, formatted with `all_recipients` using preset names for server group clients or the main contact point.
3. **Multi-Domain Visibility & Inbox Query** (`db.php`):
    - Added Clause 4 to `get_inbox_messages_for_domain`: `(shared_with_group = 1 AND is_sent_copy = 0)`.

- When `shared_with_group = 1`, all clients on the shared database retrieve the message.
- For other clients (`!$is_direct`), read and archive statuses are tracked independently via `message_reads` and `message_archives`.
- The sending client continues to see their sent copy in outbox/sent messages.

4. **Preset Name Formatting in Recipients Header** (`db.php`):
   - Destination formatting resolves the other group client's preset name (or the main contact point's name) in the `To:` header:
     - e.g. `To: external-firm.com/contact; Beta Branch Office`
     - or `To: external-firm.com/contact; Server Transmitter`
   - Messages from external servers remain cleanly formatted as `external-firm.com/contact` without names.
5. **Inbox & Archive Display Badges** (`index.php`, `index.php`):
   - Shared external messages display a badge: `[ 👥 Shared External Message ]`.
   - Displays an original recipient indicator: 📥 `Original Recipient: <Client Name> (<domain>) — Shared with group upon reply`.
   - The reply message displays as `[ 👥 Server Group Letter ]` with the other group client's name in `To:`.
6. **Documentation & Synchronization**:
   - Documented in README.md.
   - Synced across:
     - `/addr.bar/tricurse/contact/index.php` & `db.php`
     - `/addr.bar/addressbar.net/contact/index.php` & `db.php`
     - `/var/www/html/contact/index.php` & `db.php`