The Readme has installation of two packages—one right after another. If server/ is installed first, when the next git command is run in that directory, will it install contact into it and interfere with the server/ installation?

No, they will not interfere with each other on the server, but you should not clone `contact` inside `server/`.

Here is a breakdown of why and how:

---

1. Directory Navigation (Keep Git Repositories Side-by-Side)

If you remain inside `server/` after running the first script and run `git clone ... contact.git`, Git will clone the contact repository into a nested folder (`server/contact/`).

To keep the repositories cleanly organized and independent, run **`cd ..`** before cloning the second package so they sit side-by-side in your home or root directory:

```
# Step 1: Provision the Server Environment
git clone https://github.com/addressbar-net/server.git
cd server
sudo ./install.sh <your-domain.com>
cd ..                                       # <--- Return to parent directory

# Step 2: Deploy the Contact Package
git clone https://github.com/addressbar-net/contact.git
cd contact
sudo ./install.sh -D <your-domain.com> -d /tmp/html/<your-domain.com> -m
/var/lib/tricurse/contact -p 'YourSecretPassword' -H -y
```

> [!NOTE] The README.md has been updated to explicitly include the `cd ..` step.

---

2. Why the System Installations Do Not Interfere

Neither package depends on keeping runtime files in the Git clone directory. Both installers deploy their assets to designated system locations with zero overlap:

Component	`server` Package	`contact` Package	Any Conflict?
System Packages	Installs `nginx`, `snapd`, `certbot`, `php-fpm`, `sqlite3`	Uses the pre-installed packages	**None** (Complementary)
Web Root	Prepares `/tmp/html/<domain>` and writes Nginx config	Deploys `index.php`, `auth.php`, and PWA files into `/tmp/html/<domain>`	**None** (`contact` fills the web root created by `server`)

Component	`server` Package	`contact` Package	Any Conflict?
Database Storage	None (pure runtime)	`/var/lib/tricurse/contact/contact.sqlite`	**None**
CLI Binaries (`/usr/local/bin`)	`Tar`, `html_backup`, `initiate_remote_server`, `tmp_shed`	`update_password`, `set_user_password`, `create_user`, `contact_list`, `contact_update_all`	**None** (Completely different utility names)
Timezone	Configures `date.timezone = America/New_York` across `php.ini`	Inherits the configured timezone cleanly without warnings	**None**