Remove install_mysql_php_fpm.sh and install_mariadb_php_fpm.sh

from the installation procedure

in /addr.bar/tricurse/server.

Remove any automated configuration for fail2ban.

Is there a timezone setting? I'm getting an error in one of my scripts.

It says

PHP Warning: PHP Startup: Invalid date.timezone value 'America/New York', using 'UTC' instead of Unknown on line 0.

If there is an automated setting for adjusting the timezone, make sure it uses the proper syntax. My timezone is EDT.

I'm setting up a subdomain. hotletter.neolamia.com will forward to the server, where I'll install the https://hotletter.band package.

neolamia.com will forward to github.com/addressbar-net/server. That's where I'll host this package.

I want this package to work for the setup of the hotletter.band package, which is located in /addr.bar/tricurse/contact.

By installing this package first, on a fresh server, the next installation will work, which is that package.

Summary of Changes & Answers

---

1. Removal of MySQL / MariaDB Installation Scripts

- **Removed files**: Deleted `install_mysql_php_fpm.sh` and `install_mariadb_php_fpm.sh` from `/addr.bar/tricurse/server`.
- **Removed from installation procedure**: In install.sh, the MariaDB server installation step has been replaced with a lightweight PHP runtime setup (`php-fpm`, `php-cli`, `php-sqlite3`, `sqlite3`, `curl`, `unzip`), matching the pure SQLite direct-file storage architecture of `contact` (hotletter.band).
- **Updated Guide**: PROCESS_GUIDE.md was updated to document the SQLite architecture and the streamlined 6-step installation flow.

---

2. Removal of Automated Configuration for Fail2ban

- **Removed Fail2ban configuration**: In install.sh, removed `fail2ban` from package installation and deleted the SSH jail configuration step.
- **Deleted obsolete files**: Removed `sshd_rules.txt` and `jail.conf` from `/addr.bar/tricurse/server`.
- **Updated Contact installer**: Removed `fail2ban` from package dependency checks in contact/install.sh and `/addr.bar/install.sh`.

---

3. PHP Timezone Error Explanation & Automated Fix

Why the Error Occurred

The warning:

```
PHP Warning: PHP Startup: Invalid date.timezone value 'America/New York', using 'UTC' instead of Unknown on line 0.
```

- In PHP, `date.timezone` strictly requires an IANA/Olson Time Zone Database identifier.
- **Spaces are invalid**: `America/New York` contains a space, which causes PHP to fail at startup (`line 0`) before executing any code and fall back to `UTC`.
- **Abbreviations like `EDT` are invalid**: Three-letter daylight-saving abbreviations (e.g. `EDT`, `EST`) are not accepted as `date.timezone` directives in PHP.

The Proper Syntax

For the EDT / US Eastern timezone, the valid IANA identifier is **`America/New_York`** (with an underscore, no spaces):

```
date.timezone = America/New_York
```

Automated Configuration in `install.sh`

The automated timezone setting is integrated into **Step 4** of install.sh:

1. Detects the active PHP version (e.g. 8.2, 8.4, 8.5) and writes php_version.txt.
2. Sets the system timezone: `timedatectl set-timezone America/New_York`.
3. Scans all `php.ini` files (`fpm` and `cli`) under `/etc/php/` and replaces any commented, missing, or malformed/spaced timezone settings with:

   ```
   date.timezone = America/New_York
   ```

4. Enables and restarts the `php${PHP_VERSION}-fpm` service to apply changes cleanly.

---

4. Fresh Server Setup Workflow: `server` & `hotletter.band` Subdomain

Installing this package (`tricurse/server`) first on a fresh server creates the exact environment needed by the `hotletter.band` package (/addr.bar/tricurse/contact):

```
Fresh Server (Debian/Ubuntu)
  │
  ├─ 1. Run /addr.bar/tricurse/server/install.sh hotletter.neolamia.com
  │      ├─ Installs Nginx, Snapd, Certbot, PHP-FPM, PHP-SQLite3, SQLite3
  │      ├─ Configures PHP date.timezone = America/New_York
  │      ├─ Sets up document root: /tmp/html/hotletter.neolamia.com
  │      ├─ Configures Nginx default site (prioritizing index.php + PHP-FPM socket)
  │      └─ Issues SSL certificate via Certbot for hotletter.neolamia.com
  │
  └─ 2. Run /addr.bar/tricurse/contact/install.sh
         ├─ Automatically detects pre-configured document root in Nginx
         ├─ Finds all PHP & SQLite prerequisites already satisfied
         ├─ Initializes persistent SQLite storage
(/var/lib/tricurse/contact/contact.sqlite)
         └─ Deploys index.php, auth.php, PWA assets, and CLI tools seamlessly
```

Key Updates in `setup_nginx_certbot.sh`:

- In setup_nginx_certbot.sh and default, updated `index` order to `index index.php index.html;` so that once `contact` installs its `index.php`, Nginx immediately serves `index.php` rather than placeholder HTML.
- Added location security rules preventing public HTTP access to SQLite database files (`.sqlite`, `.db`, `.sql`) and dotfiles.