After the installation, run html_backup in case the server is restarted. That should restore the files to /tmp/html from /var/www/html/server_1.tar. Make sure that works.

Done. The Backup & Reboot Restore Workflow is Now Fully Configured and Verified

---

What Was Updated:

1. **`html_backup` Automatically Runs After Installation**:
    - Added **Step 8** to the end of install.sh to automatically execute `html_backup` once setup completes.
    - Archives `/tmp/html` directly to `/var/www/html/server_1.tar` (and keeps `server_1_HTML.tar` / `html.tar` for backwards compatibility).
    - Sets `chmod 644` on the backup archive so it is readable by the restoration scripts.
2. **Reboot Restoration from `/var/www/html/server_1.tar`**:
    - Updated install_temporary_directories.sh (which is triggered on system reboot via `@reboot` crontab):
        - Checks for `/var/www/html/server_1.tar` (with fallback to `server_1_HTML.tar` / `html.tar`).
        - Extracts the archive directly onto `/tmp` using `tar --overwrite -xpf` so all files and subdirectories are reconstructed under `/tmp/html/`.
        - Automatically applies `chmod 755` and sets ownership to `www-data:www-data` across `/tmp/html` and `/tmp/log/nginx`.
    - Updated initiate_remote_server to use the same logic when manually restoring from `/var/www/html/server_1.tar`.
3. **Portability & Reliability Enhancements**:
    - Removed `--atime-preserve` from html_backup and Tar to prevent `utime: Operation not permitted` failures across non-root execution or restrictive file systems.
    - Synced the updated helper scripts to `/usr/local/bin/`.

Verification:

The backup and restoration cycle was tested end-to-end:

1. Created web files in `/tmp/html/<domain>/`.
2. Executed `html_backup` successfully produced `/var/www/html/server_1.tar`.
3. Emulated a system reboot by wiping `/tmp/html`.
4. Executed `install_temporary_directories.sh` automatically detected `/var/www/html/server_1.tar` and restored all files to `/tmp/html/` with correct `755` and `www-data:www-data` permissions.

All changes have been committed to the repository's `main` branch.