

Preferential attachment.

The preferential attachment effect can be observed ~~globally~~ ^{directly} over the global network, or ~~locally~~ ^{indirectly} on ~~each~~ ^{local} level classes.

X.1 Global preferential attachment

~~these models~~ Stochastic block models lead to the ~~same~~ following generative process for links:

- For each node i , $1 \leq i \leq N$:
- For each node j , $1 \leq j \leq N$: generate a link between i and j with probability $P_{ij} = 1/N$

where N is either M or M_g .

The above process, for any given node i , considers all nodes j in turn, from node 1 to node N . The indexing, i.e. the mapping between nodes and integers in $[1..N]$, is however arbitrary and the results that follow are stated for all possible indexings.

For a given node i , at step p of the above process, p nodes, from node 1 to node p , have been considered and links from these nodes to node i generated or not. We will denote by $d_i^{(p)}$ the degree of node i , i.e. the number of links of node i , at the p th step of this generative definition:

$$d_i^{(p)} = \sum_{j=1}^p y_{ij}$$

For simplicity in the notation, we consider that nodes can be linked to themselves. Excluding such links does not pose particular problems.

The following definition comes from a model M (as defined above) behaves with global preferential attachment.

Definition (global preferential attachment): Let M be a model as defined above.

~~we say that~~ We say that M satisfies the global preferential attachment effect

if, for any node v , $1 \leq i \leq n$, $\forall (n, p) \in \mathbb{N} \times \mathbb{R}^+$ such that $1 \leq p < n$,

$$p(d_i^{(n)} > n+1 | d_i = n, M) \text{ increases with } n, \quad 1 \leq n < p.$$

If $p(d_i^{(n)} > n+1 | d_i \leq n, M)$ is independent of n , the model is said

to be neutral w.r. the global preferential attachment effect.

~~Include text on~~

This definition directly translates the fact that the more links

a node has at some point in the process, the more likely

a new link will be created with that node. This is

exactly the preferential attachment effect.

~~It also includes a note that~~ For both IFT and ITHS, in model M ,

the generation of links are independent of each other. The fact that n links have been created after p steps has no impact on the future

links in a given node. In M_g , as ~~the~~ one first needs to generate

Φ and ϕ prior to generate all the links, a similar behavior is

likely to be observed. Intuitively thus, both IFT and ITHS

are neutral w.r. the global preferential attachment effect. The following property formalizes this intuition.

Prop 1: Both self and others, for both we add $1/g$, we neutral w/ the global preferential attachment effect.

Proof: We first consider model M_c . For any index i , a node j , $1 \leq j \leq N$, and a step t , $1 \leq t \leq N$. One has $\forall n, 1 \leq n \leq t$:

$$P(d_i^{(n)} \geq n+1 | d_i = n, M_c) = 1 - P(d_i^{(n)} = n | d_i = n, M_c)$$

$$= 1 - P(y_{i,n} = 0, \dots, y_{i,n} = 0 | M_c) = 1 - \prod_{j=1}^n P(y_{i,j} = 0 | M_c)$$

where the last equality comes from the fact that, in M_c , links are independently generated.

Similarly:

$$P(d_i^{(n)} \geq n+2 | d_i = n, M_c) = 1 - \frac{n}{N} P(y_{i,n} = 0 | M_c) = P(d_i^{(n)} \geq n+1 | d_i = n, M_c)$$

This completes the proof for M_c .

For M_g , it suffices to observe that the above result is true for any F, ϕ and that:

$$P(d_i^{(n)} \geq n+1 | d_i = n, M_g) = \int \int_{F, \phi} P(d_i^{(n)} \geq n+1 | d_i = n, F, \phi) P(F | M_g) P(\phi | M_g) dF d\phi$$

$$\text{As } P(d_i^{(n)} \geq n+2 | d_i = n, F, \phi) = P(d_i^{(n)} \geq n+1 | d_i = n+1, F, \phi), \text{ we have:}$$

$$P(d_i^{(n)} \geq n+2 | d_i = n, M_g) = P(d_i^{(n)} \geq n+1 | d_i = n, M_g).$$

We now turn to local preferential attachment, as specified in eq

→ [PEF TO LET KEEPER SHOULD BE ADDED]

X.2. Local preferential attachment.

(4)

X.2.1 ILFM

For ILFM, the situation w.r.t to local preferential attachment is very similar to the one for global preferential attachment. This is due to the fact that, ~~in~~ ⁱⁿ M_k (i.e. given F and ϕ), a local degree can be defined in the same way as the global degree above.

Considering the same generative process as before, for M_k^p , the local degree in class k , $1 \leq k \leq K$, for a node i such that $f_{ik} = 1$ is defined by:

$$d_{i,k}^{(n)} = \sum_{j=1, f_{jk}=1}^p y_{ij}$$

Note that if $f_{ik} = 0$, $d_{i,k}^{(n)} = 0$ for all p .

This then leads to the following definition of the local preferential attachment for ILFM.

Definition (ILFM - local preferential attachment): ~~Let M_k be a model $(M_k \text{ or } M_k)$ associated to ILFM. We say that $\forall M_k$ satisfies the~~ ^{ILFM in ~~not ILFM~~} local preferential attachment effect iff for any indexing, for any node i ($1 \leq i \leq N$), for any step p ($1 \leq p \leq N$):

$$P(d_{i,k}^{(n)} \geq n+1 \mid d_{i,k}^{(n)} = n; M_k) \text{ increases with } n, \quad 1 \leq n < p.$$

If $P(d_{i,k}^{(n)} \geq n+1 \mid d_{i,k}^{(n)} = n; M_k)$ is independent of n , we say that the model is said to be ~~inde~~ neutral w.r.t to the local preferential attachment effect.

* such that $f_{ik} = 1$

As before, we have the following property:

(5)

Property 2. ILFM, for Π_e , is neutral w.r.t. the local preferential attachment effect.

Proof: The proof is identical to the first part of the proof for Property 1.

The definition of the local degree we have used does not directly translate to Π_g as it is based on the knowledge of Φ . One can nevertheless define an expected local degree for Π_g as follows:

$$\begin{aligned} \text{gd}_{i,e}^{(n)} &= \mathbb{E}_{\Phi, \phi} [\text{di}_{i,e}^{(n)}] \\ &= \int_{\Phi, \phi} P(\Pi | \Pi_g) P(\Phi | \Pi_g) \text{di}_{i,e}^{(n)} d\Phi d\phi \end{aligned}$$

A notion of local preferential attachment for Π_g can then be defined on the basis of this expected local degree.

Definition (ILFM - local preferential attachment; Π_g) We say that ILFM in Π_g satisfies the local preferential attachment effect iff for any indexing, for any node i ($1 \leq i \leq N$), for any step p ($1 \leq p \leq N$), $\exists \varepsilon \in]0, 1[$ s.t. $P(\text{gd}_{i,e}^{(n)} \geq x + \varepsilon | \text{gd}_{i,e}^{(n)} \geq x; \Pi_g)$ increases with x , $x \in]0, N[$.

[INCLUDE A ~~NEW~~ § ON LINK TO CONTINUOUS BUSINESS]

~~As a consequence~~

~~By definition, for any $\varepsilon \in]0, 1[$, $x \in]0, N[$:~~

$$\begin{aligned} P(\text{gd}_{i,e}^{(n)} \geq x + \varepsilon | \text{gd}_{i,e}^{(n)} \geq x; \Pi_g) &= 1 - P(\text{gd}_{i,e}^{(n)} = x | \text{gd}_{i,e}^{(n)} \geq x; \Pi_g) \\ &= 1 - P(y_{i,p} = 0, \dots, y_{i,n} = 0 | \Pi_g) \end{aligned}$$

where the last equation derives from the definition of $g_{i,j,k}^{(p)}$ ($g_{i,j,k}^{(p)} = g_{i,j,k}^{(p)}$ iff $y_{i,j,k} = \dots = y_{i,j,k} = 0$).

This last quantity is independent of x , leading to:

Property 3. IEFM with ρ_g is neutral wrt to the local preferential attachment effect.

X.2.2. IMMSB

For IMMSB in M_c , ~~we~~ the situation is similar to the one of IEFM in M_g , as we do not have ~~access~~ a direct access to classes, encoded in the z variables.

One can nevertheless define ~~the random variables~~ ~~the random variables~~ as local random variables $y_{i,j,k}$. Here $y_{i,j,k} = 1$ if a link is generated between ^{nodes} i and j using class k and 0 otherwise. One has:

$$P(y_{i,j,k} = 1 | M_c) = P(y_{i,j,k} = 1 | z_{i \rightarrow j} = k, z_{j \rightarrow i} = k, \Phi) P(z_{i \rightarrow j} = k | F) P(z_{j \rightarrow i} = k | F) \\ = f_{i,j,k} \Phi_{i,j,k}$$

The local degree $d_{i,k}^{(p)}$ can then be defined as the expectation over the nodes $1, \dots, p$ of $y_{i,j,k}$:

$$d_{i,k}^{(p)} = \sum_{j=1}^p P(y_{i,j,k} = 1 | M_c) = \sum_{j=1}^p f_{i,j,k} \Phi_{i,j,k}$$

→ THEN DEFINITION OF LOCAL PREF. ATT., PROPERTY AND PROOF AS IN ~~DSAA~~ DSAA

→ ~~THE~~ DEVELOPMENT FOR ρ_g TO BE DONE (soon)