## Nonlinear State Estimation with an Extended FMI 2.0 Co-Simulation Interface

Jonathan Brembeck<sup>1</sup>, Andreas Pfeiffer<sup>1</sup>, Michael Fleps-Dezasse<sup>1</sup>, Martin Otter<sup>1</sup>, Karl Wernersson<sup>2</sup>, Hilding Elmqvist<sup>2</sup>

<sup>1</sup>German Aerospace Center (DLR), Institute of System Dynamics and Control, 82234 Weßling, Germany

<sup>2</sup>Dassault Systèmes AB, Ideon Science Park, 22370 Lund, Sweden Jonathan.Brembeck@dlr.de, Andreas.Pfeiffer@dlr.de, Michael.Fleps-Dezasse@dlr.de, Martin.Otter@dlr.de, Karl.Wernersson@3ds.com, Hilding.Elmqvist@3ds.com

## **Abstract**

In this paper we propose a method how to automatically utilize continuous-time *Modelica* models directly in nonlinear state estimators (Figure 1). The approach is based on an extended *FMI 2.0 Co-Simulation Interface* that interacts with the state estimation algorithms implemented in a *Modelica* library (Figure 2). Besides a short introduction to *Kalman Filter* based state estimation, we give details on a generic interface to cooperate with FMUs in *Modelica*, an implementation of nonlinear state estimation based on this interface, and the *Dymola* prototype used for the evaluation. Finally we show first results in a tire load estimation application (Figure 4) for DLR's robotic electric research platform *ROMO* (Figure 3).

Keywords: FMI 2.0 Co-Simulation, FMU, Event Handling, Inline Integration, Kalman Filter, State Estimation, Moving Horizon Estimation, Tire Load Estimation




Figure 1: Principle of Kalman Filter based Estimation




Figure 2:Process flow to generate a state estimator based on an FMU



Figure 3: ROMO on the four post test rig




Figure 4:left: the "Wheel Robot" concept, right: nonlinear two mass system