

Grinding

GWS 9.115/125
Power and handling - redefined
Part No: 0601395505
Part No: 06013860K7

Specification	
Rated input power	900 W
No-load speed	11000 rpm
Disc diameter	115/125 mm
Grinding spindle thread	M 14
Why use this tool	New motor platform - high power and high torque

GWS 750-115
Power and handling - redefined
Part No: 06013940K2

Specification	
Rated input power	750 W
No-load speed	11000 rpm
Disc diameter	115 mm
Grinding spindle thread	M 14
Why use this tool	New motor platform - high power and high torque

GWS 700
Outstanding overload capacity fit for tough jobs
Part No: 06013A30K0

Specification	
Disc diameter	115 mm
No-load speed	12.000 – 12.000 rpm
Grinding spindle thread	M 14
Why use this tool	Compact and slim design for easy handling



GWS 17-125
Maximum productivity and the best use protection
Part No: 060179H002

Specification	
Rated input power	1700 W
No-load speed	2800 - 11500 rpm
Power output	1010 W
Grinding spindle thread	M 14 x 1.5
Why use this tool	6-stage speed preselection for different materials

GWS 2200
Performance that meets reliability, and your budget.
Part No: 06018C10K0

Specification	
Rated input power	2200 W
No-load speed	6500 - 6500 rpm
Disc diameter	230 mm
Grinding spindle thread	M 14
Why use this tool	Outstanding user protection thanks to the anti-rotation protective guard - stands firm, even if the disc breaks

GWS 14-125
The handy powerhouse
Part No: 0601513000

Specification	
Rated input power	1400 W
No-load speed	11500 rpm
Power output	450 W
Grinding spindle thread	M 14
Why use this tool	Powerful 1400 watt motor

GWS 30-230
Top performance with Vibration Control
Part No: 06018G1000

Specification	
Rated input power	2800 W
No-load speed	6500 rpm
Disc diameter	230 mm
Grinding spindle thread	M 14
Why use this tool	Double-sealed ball bearings and the especially sturdy gearing guarantee a long lifetime

GPO 14 CE
The handy tool for highly polished results
Part No: 0601389003

Specification	
Rated input power	1400 W
No-load speed	750 - 3000 rpm
Power output	800 W
Grinding spindle thread	M 14
Why use this tool	6-stage speed preselection for working on a wide variety of materials

GGG 28 C
The handy tool for universal grinding work
Part No: 0601220000

Specification	
Rated input power	650 W
No-load speed	30000 rpm
Power output	350 W
Tool holder	collects up to 8 mm diameter
Why use this tool	Little servicing required due to significantly improved carbon brushes

GBR 15 CA
The compact, lightweight solution for powerful
Part No: 0601776000

Specification	
Rated input power	1500 W
No-load speed	9300 rpm
Grinding head diameter	125 mm
Grinding spindle thread	M 14
Why use this tool	Special seal system protects gearbox and motor against abrasive concrete dust to provide a long lifetime

GNF 35 CA
The durable tool with Constant Electronic
Part No: 0601621703

Specification	
Rated input power	1400 W
No-load speed	9300 rpm
Power output	820 W
Disc diameter	150 mm
Cutting with	3 - 29 mm
Why use this tool	Optimum handling due to low weight

GWS 27-230 PR
Sustained high performance in all application levels
Part No: 06018C50K0

Specification	
Rated input power	2700 W
No-load speed	6.500 - 6.500 rpm
Disc diameter	30 mm
Power output	2700 W
Grinding spindle thread	M 14
Why use this tool	Greater efficiency on heavy-duty tasks and longer lifetime thanks to powerful 2,700W motor



Grinding, Drilling & Demolition

GGG 30LS
Best handling for perfect structure
Part No: 06012B50P0

Specification	
Rated input power	750 W
No-load speed	33000 rpm
Max. outer diameter of accessory	8 mm
Max. width of accessory	2
Why use this tool	Versatile applications due to comprehensive accessories

GBM 1600 RE
The most powerful model with 1500 watts
Part No: 0601130203

Specification	
Rated input power	1500 W
No-load speed	210 / 330 / 470 / 740 rpm
Rated speed	120 / 185 / 265 / 420 rpm
Rated torque	80.0 / 52.0 / 36.0 / 32.0 Nm
Why use this tool	Auxiliary handle for better grip

GBW 2000
Power and speed in a compact combination
Part No: 061125A4K6

Specification	
Rated input power	800 W
Impact energy	3.1 - 3.5 J
Impact rate at rated speed	0 - 4600 bpm
Rated speed	0 - 1400 rpm
Why use this tool	Powerful 600 W motor for enhanced performance

GBH 3-28 DFR
Top performance with 20% less vibration
Part No: 061124A000

Specification	
Rated input power	8500 W
Impact energy	3.2 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Why use this tool	Balanced weight distribution due to L-shaped design for more comfortable working

GBH 12-52 DV
The most powerful rotary hammer from Bosch - with Vibration Control
Part No: 0611266000

Specification	
Rated input power	1700W
Impact energy	19 J
Impact rate at rated speed	1750 - 2150 bpm
Rated speed	0 - 1200 rpm
Why use this tool	Overload clutch to protect the user and the machine

GSH 27 VC
The most powerful electric breaker from Bosch
Part No: 061130A000

Specification	
Rated input power	2000 W
Impact energy	62 J
Impact rate at rated speed	1000 bpm
Weight	29.5 kg
Why use this tool	Optimum handling: ergonomic handles with soft grip and low centre of gravity for optimum handling

GCO 220
An excellent investment on productivity
Part No: 0601B373L0

Specification	
Rated input power	2000 W
No-load speed	3600 rpm
Weight	15 kg
Cutting capacity at L-profile Ø	130 x 130 mm
Why use this tool	Variable speed dial wheel for easy flow speed adjustment

GMB 50-2
Good holding power for safe working
Part No: 0601193003

Specification	
Rated input power	95 W
No-load speed	65 mm
Power output	25kW
Grinding spindle thread	223 mm
Why use this tool	Connection belt between GBM 52-8 Professional and drill stand enables precise drilling with core cutters

GBH 2-24
The new standard in concrete drilling
Part No: 06112730K0

Specification	
Rated input power	730 W
Impact energy	2,7 J
Impact rate at rated speed	0 - 4200 bpm
Rated speed	0 - 930 rpm
Why use this tool	Spare parts interchangeability and easy maintenance because of smart design

GBH 4-32 DFR
The fastest multi-hammer in the 4kg class
Part No: 0611332100

Specification	
Rated input power	900 W
Impact energy	4.2 J
Impact rate at rated speed	0 - 3600 bpm
Rated speed	0 - 800 rpm
Why use this tool	Extremely robust thanks to aluminium gearbox

GSH 5-40
Longest lifetime in class with power that impresses
Part No: 0611339000

Specification	
Rated input power	1100W
Impact energy	7.5 J
Rated speed	2850 rpm
Weight	5.6 kg
Why use this tool	Soft grip for comfortable and fatigue free use



For full category model, please ask us

GBG 60-20
The powerful and sturdy tool for toughest applications
Part No: 060127A400

Specification	
Rated input power	600 W
No-load speed	3600 rpm
Grinding wheel diameter	200 mm
Grinding wheel bore	32 mm
Why use this tool	Large and easily adjustable spark protection glasses for safe and precise work

GRW 12 E
The compact tool for mixing various materials up to 50 kg
Part No: 06011A7000

Specification	
Rated input power	1200 W
No-load speed	1000 rpm
Weight	5.3 kg
Why use this tool	For stirrer buckets up to 140 mm in diameter

GBH 2-28 F
Top performance with Intelligent KickBack Control
Part No: 0611267600

Specification	
Rated input power	880 W
Impact energy	3.2 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Why use this tool	Magnesium gear housing for improved robustness

GBH 5-40 DCE
The fast all-rounder with Vibration Control
Part No: 0611264000

Specification	
Rated input power	1150 W
Impact energy	8.8 J
Impact rate at rated speed	1500 - 3050 bpm
Rated speed	170 - 340 rpm
Why use this tool	Automatic switch lock for the best competence in continuous chiselling applications

GSH 16-28
The most powerful electric breaker from Bosch
Part No: 061135000

Specification	
Rated input power	2000 W
Impact energy	62 J
Impact rate at rated speed	1000 bpm
Weight	29.5 kg
Why use this tool	Optimum handling: ergonomic handles with soft grip and low centre of gravity for optimum handling

GVC 22 EX
Best relation between weight and power in class
Part No: 06012B31K1

Specification	
Rated input power	2200 W
Electric Frequency	50, 60 Hz
Nominal frequency vibrations	15,000 rpm
Amplitude	4.3 mm
Why use this tool	User-friendly: Easy click system for hose exchanging and portable design

Impact /Diamond Drilling

GSB 162
Powerful and Reliable power tool
Part No: 060118B000

Specification	
Rated input power	1500 W
No-load speed	0 - 1800 rpm
Impact rate at no-load speed	1 - 10 bpm
Drilling diameter in aluminium	3-16 mm
Why use this tool	Easy slide switch for forward/ reverse rotation

GSB 13 RE + ACC
The handiest tool in its class
Part No: 0601217192

Specification	
Rated input power	600 W
No-load speed	0 - 2800 rpm
Power output	301 W
Rated torque	1.6 kg
Why use this tool	Electronic control for exact pilot drilling

GSB 20-2 RE
The most powerful tool in its class – for the toughest applications
Part No: 0601182A21L0

Specification	
Rated input power	1,100 W
No-load speed	0 - 900 / 3000 rpm
Chuck capacity, min/max.	1.5 - 13 mm
Rated torque	5.2 / 2.0 Nm
Why use this tool	Rotating brush shaft for equal power in reverse and forward rotation



Robert Bosch Nig. Ltd.
2, Soji Adepegba Close,
Off Allen Avenue
Ikeja, Lagos
Tel: +234 (908) 744 0259
www.bosch-professional.com/ng/en

For full category model, please ask us

GSB 600
Powerful and Reliable power tool
Part No: 06011A03F0

Specification	
Rated input power	600 W
No-load speed	0 - 3000 rpm
Impact rate at no-load speed	0 - 48000 bpm
Chuck capacity,min./max	1.5-13 mm
Why use this tool	Forward/reverse rotation for screw-driving applications

GSB 16 RE
Compact and powerful
Part No: 0601218191

Specification	
Rated input power	701 W
No-load speed	0 - 3000 rpm
Power output	351 W
Chuck capacity, min./max	13 mm
Why use this tool	Speed preselection with setting wheel

GCR 350
Suitable for GDB 350 WE diamond drill
Part No: 0601513000

Specification	
Drilling diameter	350 mm
Working length, Z-axis	550 mm
Column length	955 mm
Drill stroke	580 mm
Why use this tool	Robust construction for precise drilling



BOSCH

ONE BATTERY
FITS ALL!
Bosch Professional

PROFESSIONAL
18V
SYSTEM

1 YEAR
WARRANTY



Quick Reference Guide

www.bosch-professional.com/ng

Cordless

Bosch Go + ace

The only smart screwdriver - A simple push. A perfect finish
Part No: 06019H20K1

Specification	
Torque, max (hard/soft)	5 / 2.5 Nm
Max. drilling diameter in steel	5 mm
Max. screw diameter	5 mm
Battery voltage	3.6 V
Why use this tool	4 times more powerful than any existing screw driver in size and form



GBH 18V-18X

More Power. More Robust.
Part No: 06011927110

Specification	
Torque, max (hard/soft)	54 / 21 Nm
No-load speed (1st gear / 2nd gear)	0-900 rpm
Battery voltage	18 V
Torque settings	20+1
Why use this tool	Changeable Carbon Brushes. Extends the lifetime of the motor



GSB 18 V-90C

The versatile tool for powerful screw driving
Part No: 06019K1606

Specification	
Torque, max (hard/soft)	26/54 Nm
No-load speed (1st gear / 2nd gear)	0-630 / 0-2,100 rpm
Battery voltage	18 V
Torque settings	21
Why use this tool	Electronic Motor Protection (ECP) protects the motor against overload and ensures a long lifetime



GST 185-LI

The compact and powerful cordless jigsaw
Part No: 06015B3021

Specification	
Stroke rate	0-3,500 spm
Length rate	26mm
Battery voltage	18 V
Mitre cuts	45-45 °
Why use this tool	Powerful battery system for cutting even in thicker or harder materials



GWS 18 V-8

The most powerful 18-volt angle grinder
Part No: 06019G30A

Specification	
No-load speed	9000 rpm
Battery Voltage	18 V
Grinding/cutting disc diameter	125mm
Rubber backing pad, diameter	125mm
Why use this tool	Innovative COOLPACK batteries ensure optimum heat dissipation and therefore increase lifetime by up to 100%



GBA 18V 2.0Ah M-B

The lightweight 18 volt Compact battery with 2.0 Ah and COOLPACK technology
Part No: 1600200036

Specification	
Rated input power	18 V
No-load speed	350 g
Current charge	4 A
Why use this tool	Extremely robust thanks to aluminum gearbox



GSB 120-LI

Use your drill driver more flexibly - drive screws and drill in wood, steel and masonry!
Part No: 06019F3000

Specification	
Torque, max (hard/soft)	28 / 11 Nm
No-load speed (1st gear / 2nd gear)	0-400 / 0-1,300 rpm
Battery voltage	12 V
Torque settings	20
Why use this tool	Bosch Electronic Cell Protection (ECP) protects the battery against overload, overheating and deep discharge



GSB 183-LI

More Power. More Robust.
Part No: 06019K9110

Specification	
Torque, max (hard/soft)	21/56/60 Nm
No-load speed (1st gear / 2nd gear)	0-440 / 0-1,650 rpm
Battery voltage	18 V
Torque settings	20
Why use this tool	Changeable Carbon Brushes. Extends the lifetime of the motor



GBH 187

The cordless rotary hammer with SDS plus
Part No: 0611923110

Specification	
Rated speed	0-4,359 rpm
Max. impact energy	24 J
Drilling diameter, concrete, hammer drill bits	4-4.24 mm
Why use this tool	Vibration Control for low user fatigue



GKS 185

The most powerful circular saw in its class!
Part No: 06016C1223

Specification	
No-load speed	5000 rpm
Saw blade diameter	165 mm
Saw blade bore diameter	20 mm
weight	2.8 kg
Why use this tool	Unique Bosch Premium lithium-ion technology for longer lifetime and unbeatable battery runtime



GAL 12V-40

The quick charger for all Li-ion batteries from 10.8 to 12 volts
Part No: 1600A019R4

Specification	
Battery charging Voltage	10.8-12 V
Weight	400 g
Current charge	4 A
Why use this tool	Quick charger with the shortest charging times



For full category model, please ask us

GDR 18V-285

The new 18 V Impact driver/wrench with the right power for a variety of applications
Part No: 06019N2122

Specification	
Torque	285 Nm
No-load speed (1st level / 2nd level)	0-1300 / 2600 rpm
Battery voltage	18 V
Rated impact rate	2800 - 3400 bpm
Why use this tool	Always the right power for a variety of applications with 2-level power control



GSB 18 V-65C

The robust, powerful tool
Part No: 061900300

Specification	
Torque, max (hard/soft)	7/85/110 Nm
No-load speed (1st gear / 2nd gear)	0-440 / 0-1,650 rpm
Battery voltage	18 V
Torque settings	20
Why use this tool	Changeable Carbon Brushes. Extends the lifetime of the motor



GBH 185-LI

The handy powerhouse
Part No: 060119240L1

Specification	
Rated speed	0-100 bpm
Tool holder	SDS plus
Impact rate at rated speed	0-4,675
Why use this tool	Enhance safety against accidental jank thanks to KickBack Control



GSA 18V-24

Cordless Rivet Gun
Part No: 06019G4201

Specification	
Cutting depth in wood	230 mm
Cutting depth in metal profiles and metal pipes	175 mm
Stroke length	24 mm
Stroke rate (1st gear / 2nd gear)	0-2,500 spm
Why use this tool	SDS for easy, safe saw blade changing even when wearing protective gloves



GDX 18V-200

The most universal impact driver in its class - with even longer lifetime
Part No: 06019B9103

Specification	
Torque, max (hard/soft)	200 Nm
No-load speed (1st gear / 2nd gear)	0-3,400 rpm
Battery voltage	18 V
Screw diameter	M 6 - M 16
Why use this tool	Special bit holder combines 1/2" square and 1/4" hexagon - for even more applications



GAL 18V-40

The multi-volt quick charger for all Li-ion batteries from 14.4 to 36 volts
Part No: 1600A019R3

Specification	
Battery charging Voltage	14.4-18 V
Weight	0.55 kg
Current charge	4A
Why use this tool	Convenient cord wrap and very compact



Measuring / Leveling

GLM 25

A highly accurate and easy-to-use measuring tool for a variety of applications
Part No: 0601072800

Specification	
Measurement Range	0.15 - 40.00
Measurement Accuracy	± 0.0mm
Power Supply	Alkaline (2 x AAA)
Weight, approx.	0.1 kg
Why use this tool	GLM 25 is always to hand for fast and accurate measurements and IP54 class protection.



GLM 50-27 C

Direct digital transfer of measuring results
Part No: 0601072T00

Specification	
Measurement Range	0.05 - 50.00
Measurement Accuracy	± 1.5 mm
Laser diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Fast documentation and rapid data transfer with Bluetooth connectivity and the Bosch MeasureOn



GLL 12-22

The compact cross line laser for professionals
Part No: 0601065220

Specification	
Working Range	10 m
Accuracy	± 0.3 mm/m
Laser diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Good visibility: max. 10 m (depending on ambient brightness)



GLL 50-15 XG

For easy decorative interior fitting applications
Part No: 0601063N00


Specification	
Working Range	15m
Accuracy	± 0.2 mm/m
Working range with receiver	50m
Laser class	2
Why use this tool	Projection of two vertical 90° lines and one horizontal line



GLL 12V-100-33CG

The world's first floor surface laser
Part No: 0601065401

Specification	
Working range	10 m
Accuracy	± 0.3 mm/m
Laser diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Ideal for site managers, surveyors and all flooring trades



GRL 600 CHV

Smart functions for maximum productivity
Part No: 0601065F00

Specification	
Working range	20 m
Accuracy	50m
Laser diode	635-650 nm
Laser class	2
Why use this tool	Horizontal and vertical laser lines and two centred plumb points with optimal visibility



For full category model, please ask us

GLM 40

All relevant functions in a compact design
Part No: 0601072900

Specification	
Measurement Range	0.15 - 40.00
Measurement Accuracy	± 1.5 mm
Laser Diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Robust, shockproof housing with IP54 protection class (splash and dust protection)



GLM 100-25 C

Direct digital transfer of measuring results
Part No: 0601072Y00

Specification	
Measurement Range	0.08 - 100.00
Measurement Accuracy	± 1.5 mm
Laser diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Robust for use on the construction site due to dust and splash protection of IP65



GLL 12-22G

Compact 3-line laser: The versatile solution for indoor jobs
Part No: 0601063CJ0

Specification	
Working Range	15 m
Accuracy	± 0.5 mm/m
Laser diode	635 nm, < 1 mW
Laser class	2
Why use this tool	compact, modern and robust design for great mobility and durability



GLL 2-20G

The compact Multi Line Laser for all indoor applications
Part No: 0601065000


Specification	
Working Range	40 m
Working range with receiver	80m
Laser diode	640 nm, < 1 mW
Laser class	2
Why use this tool	Compact, easy-to-handle and extremely robust (IP54)



GLL 18V-120-33 CG

The easy solution for all leveling and transfer jobs over short distances
Part No: 0601065170

Specification	
Self Leveling Range	± 4°
Leveling time	4 s
Laser diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Robust instrument for jobsite use with IP54



For full category model, please ask us

GLM 50-22

The smart solution for measuring and documenting
Part No: 0601072500

Specification	
Measurement Range	0.05 - 50.00
Measurement Accuracy	± 1.5 mm
Laser Diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Robust and reliable with ISO certification and protection class IP65



GLM 150-27 C

The laser measure with the longest range
Part No: 0601072Z00

Specification	
Measurement Range	0.08 - 150.00
Measurement Accuracy	± 1.5 mm
Laser Diode	635 nm, < 1 mW
Laser class	2
Why use this tool	Robust, shockproof housing with IP54 protection class (splash and dust protection)



GLL 3X

For easy decorative interior fitting applications
Part No: 0601063CJ0

Specification	
Working Range	15m
Accuracy	± 0.5 mm/m
Laser Diode	635 nm, < 1 mW
Laser class	2
Why use this tool	compact, modern and robust design for great mobility and durability



GLL 88-33 G

Fast tile laying due to additional line at 45°
Part No: 0601065500

Specification	
Working Range	30 m
Angular accuracy (between 0 - 90° angle)	± 0.3 mm/m
Laser Diode	500 - 540 nm, < 10 mW
Laser class	2
Why use this tool	Alignment plate for better stability when working on uneven ground and for fixing to the wall



GRL 300 HV

Easy handling with horizontal and vertical self-leveling
Part No: 0601061505

Specification	
Working range	60 m
Working range with receiver	300 m (diameter)
Laser diode	635 nm, < 5 mW
Laser class	3
Why use this tool	Point, line and rotation modes for optimum visibility



Leveling / Detecting / Measuring

GOL 20 D

Robust and versatile - Ideal for outdoor use
Part No: 0601068402

Specification	
Unit of measure	360 degrees
Magnification	20x
Accuracy	3 mm at 30 m
Working range	up to 60 m
Why use this tool	Target collimator for rough alignment



GMS 120-7

Our bestseller, even more efficient
Part No: 0601081700

Specification	
Detection depth max	120 mm
Magnetic metals	200 mm
Non-Magnetic metals	80 mm
Live wire	50 mm
Wooden structure	30 mm
Length x width x height	186x86 mm
Weight	0,27 kg



GDM 600-15

Accurate measurement and easy recording of temperature and moisture levels
Part No: 0601077300

Specification	
Measurement Range	50 kHz ACV / 2 kHz ACA
IP-Protection	IP65
Resolution	0.01 Hz
Why use this tool	Handles tough jobsites with an IP65 rating for durability and impact resistance



GMC 600-15

The large inverted LCD display provides clear visibility, while True RMS measurement ensures precision.
Part No: 0601077600

Specification	
Continuity resolution	0.1 Ohm
Continuity accuracy	± 1.0 % + 50 A
IP-Protection	IP64
Display type	LED
Safety class	CAT IV 1000 V
Why use this tool	Handles tough jobsites with an IP65 rating for durability and impact resistance



GR 240

Precise digital inclinometer
Part No: 0601094100

Specification	
Length	60 m
Measurement range	0 - 360° (4 x 90°)
Electronics measurement accuracy 0°/90°	± 0.05° +
Electronics measuring accuracy at 1 - 89°	± 0.2° +
Why use this tool	Audible signal at 0° and 90°



GOL 26 D

Robust and versatile - Ideal for outdoor use
Part No: 0601068402

Specification	
Unit of measure	360 degrees
Magnification	20x
Accuracy	3 mm at 30 m
Working range	up to 60 m
Why use this tool	Target collimator for rough alignment



D-Tect 200 C

The specialist for finding objects with difficult conditions
Part No: 0601081600

Specification	
Detection depth max	120 mm
Magnetic metals	200 mm
Non-Magnetic metals	200 mm
Live wire	80 mm
Wooden structure	38 mm
Auto deactivation	0-30 min
Length x width x height	104x51x204 mm
Weight (batteries)	0.64 kg



BT 150

Absolutely secure stance on any floor
Part No: 0601096800

Specification	
Work height	55 - 157 cm
Weight, approx	1.3 kg
Tripod thread	1/4"
Why use this tool	1/4" tripod thread



GVD 1000-17

Reliable performance with automatic self-test before each use
Part No: 0601077000

Specification	
AC voltage measuring (RMS max)	1000V
IP-Protection	IP67
Display type	LED
Safety class	CAT IV 1000 V
Why use this tool	Robust design with IP67 rating for exceptional protection against dust and water on the toughest jobsites