'	ļ				1
	MC14001UBDR2G UB-suffix series CMOS gates: quad 2-input NOR Gate	CD40109BPWR CMOS quad low-to-high voltage level shifter (20V rating)	MC14011UBDG UB-suffix series CMOS gates: quad 2-input NAND Gate	CD4012BM96 CMOS dual 4-input NAND gate	MC14014BDG 8-Bit static shift register: synchronous parallel input/serial output 16-Lead SOIC, 3.9 mm 10
	CD4023BM96 CMOS triple 3-input NAND gate	CD4048BPW CMOS multifunction expandable 8-input gate	MC14585BDG 4-Bit magnitude comparator	M74HC133M1R 13-Input NAND gate	SN74HC157DR Quadruple 2-line to 1-line data selectors/multiplexers
	74HC175D Quad D-type flip-flop with reset; positive-edge trigger	74HC191D Presettable synchronous 4-bit binary up/down counter	CD74HC283ME4 High-speed CMOS logic 4-bit binary full adder with fast carry	CD74HC4067M96 High-speed CMOS logic 16-channel analog multi- plexer/demultiplexer	MM74HCT00M Quad 2-input NAND gate
	16-Lead SOIC, 3.9 mm 10	16-Lead SOIC, 3.9 mm 10	16-Lead SOIC, 3.9 mm 10	24-Lead SOIC, 7.5 mm 20	14-Lead SOIC, 3.9 mm 20
	SN74LVC07AD Hex buffer and driver with open-drain outputs	SN74LVC07APWR Hex buffer and driver with open-drain outputs	SN74LVC1G00DBVR Single 2-input positive-NAND gate	SN74LVC1G14DBVR Single Schmitt-trigger inverter	SN74LVC1G17DBVR Single Schmitt-trigger buffer
	SN74LVC1G32DBVR Single 2-input positive-OR gate 5-Lead SOT-23, 1.6 mm 20	SN74LVC1G86DBVR Single 2-input exclusive-OR gate 5-Lead SOT-23, 1.6 mm 20	SN74LVC2G07DBVR Dual buffer and driver with open-drain outputs 6-Lead SOT-23, 1.6 mm 20	SN74LVC32AD Quadruple 2-input positive- OR gates	SN74LVC32APWR Quadruple 2-input positive- OR gates
	SN74LVC4245APWR Octal bus transceiver and 3.3-V to 5-V shifter with 3-state outputs	74VHC00MTC Quad 2-input NAND gate	74VHC32MTCX Quad 2-input OR gate	74VHC595MTC 8-Bit shift register with output latches	74VHC86MTCX Quad 2-input exclusive-OR gate

14-Lead TSSOP, 4.4 mm

16-Lead TSSOP, 4.4 mm

14-Lead TSSOP, 4.4 mm

24-Lead TSSOP, 4.4 mm

14-Lead TSSOP, 4.4 mm