DELPHIX CONTINUOUS COMPLIANCE · DISCOVERY POLICY

Belize — Data Protection Act, 2021

Discovery and masking of Belizean personal data: identity numbers and names, quasi-identifiers, the sensitive personal data of section 2 — including financial record or position and criminal proceedings — and health records.

72	126	84
DATA CLASSES	CLASSIFIERS	ALGORITHMS

Discovery policy `BZ – Data Protection Act 2021 – v4`

Version 4 of October 12, 2026 · Assignment threshold 60%

Contents

The first sections explain what the policy is for and how it works. The data class chapters then describe every data class: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the policy contains.

1	**About this discovery policy**	
2	**The Data Protection Act, 2021 at a glance**	
3	**How sensitive data is discovered**	
4	**How data is masked**	
5	**Essential and extended packs**	
6	**Data classes at a glance**	

PART 7 · DIRECT IDENTIFIERS

7.1	**Social security number**	BZ_L1_SOCIAL_SECURITY_NUMBER
7.2	**Taxpayer identification number**	BZ_L1_TIN
7.3	**Passport**	BZ_L1_PASSPORT
7.4	**Voter ID**	BZ_L1_VOTER_ID
7.5	**Driver's licence**	BZ_L1_DRIVERS_LICENCE
7.6	**Immigration document**	BZ_L1_IMMIGRATION_DOCUMENT
7.7	**Civil registry entry**	BZ_L1_VITAL_RECORD
7.8	**Given names**	BZ_L1_GIVEN_NAME
7.9	**Surnames**	BZ_L1_SURNAME
7.10	**Full name**	BZ_L1_FULL_NAME
7.11	**E-mail**	BZ_L1_EMAIL
7.12	**Phone**	BZ_L1_PHONE
7.13	**Address**	BZ_L1_ADDRESS
7.14	**Address detail**	BZ_L1_ADDRESS_DETAIL
7.15	**Bank account**	BZ_L1_BANK_ACCOUNT
7.16	**Payment card**	BZ_L1_PAYMENT_CARD
7.17	**IP address**	BZ_L1_IP_ADDRESS
7.18	**Device identifier**	BZ_L1_DEVICE_ID
7.19	**Licence plate**	BZ_L1_LICENCE_PLATE
7.20	**Vehicle identification number**	BZ_L1_VIN
7.21	**Land parcel**	BZ_L1_LAND_PARCEL
7.22	**Contract or customer number**	BZ_L1_CONTRACT_NUMBER
7.23	**User name or social media**	BZ_L1_USERNAME
7.24	**Credential**	BZ_L1_CREDENTIAL
7.25	**Geolocation**	BZ_L1_GEOLOCATION

7.26	Free text	BZ_L1_FREE_TEXT

PART 8 · QUASI-IDENTIFIERS

8.1	Birth date	BZ_L2_BIRTH_DATE
8.2	Birth year	BZ_L2_BIRTH_YEAR
8.3	Age	BZ_L2_AGE
8.4	Life event dates	BZ_L2_EVENT_DATE
8.5	Sex	BZ_L2_SEX
8.6	Town or village	BZ_L2_TOWN_VILLAGE
8.7	Neighbourhood	BZ_L2_NEIGHBOURHOOD
8.8	Nationality	BZ_L2_NATIONALITY
8.9	Marital status	BZ_L2_MARITAL_STATUS
8.10	Occupation	BZ_L2_OCCUPATION
8.11	Employer	BZ_L2_EMPLOYER
8.12	Education	BZ_L2_EDUCATION
8.13	School	BZ_L2_SCHOOL
8.14	Children and dependants	BZ_L2_DEPENDANTS

PART 9 · SENSITIVE PERSONAL DATA

9.1	Ethnic origin	BZ_L3_ETHNICITY
9.2	Language	BZ_L3_LANGUAGE
9.3	Religion	BZ_L3_RELIGION
9.4	Beliefs of a similar nature	BZ_L3_BELIEF
9.5	Political opinion	BZ_L3_POLITICAL_OPINION
9.6	Membership of a political body	BZ_L3_POLITICAL_MEMBERSHIP
9.7	Trade union membership	BZ_L3_TRADE_UNION
9.8	Genetic data	BZ_L3_GENETIC
9.9	Biometric data	BZ_L3_BIOMETRIC
9.10	Sexual orientation	BZ_L3_SEXUAL_ORIENTATION
9.11	Sexual life	BZ_L3_SEXUAL_LIFE
9.12	Gender identity	BZ_L3_GENDER_IDENTITY

PART 10 · HEALTH RECORDS

10.1	Health identifier	BZ_HEALTH_ID
10.2	Diagnosis	BZ_HEALTH_DIAGNOSIS
10.3	Medication	BZ_HEALTH_MEDICATION
10.4	Clinical text	BZ_HEALTH_CLINICAL_TEXT
10.5	Test result	BZ_HEALTH_TEST_RESULT

10.6	Blood group	BZ_HEALTH_BLOOD_GROUP
10.7	Disability	BZ_HEALTH_DISABILITY
10.8	Sexual and reproductive health	BZ_HEALTH_REPRODUCTIVE
10.9	Mental health and addiction	BZ_HEALTH_MENTAL

PART 11 · FINANCIAL RECORD OR POSITION

11.1	Credit reference	BZ_FIN_CREDIT_REFERENCE
11.2	Debt amount	BZ_FIN_DEBT
11.3	Salary and income	BZ_FIN_INCOME
11.4	Assets	BZ_FIN_ASSETS
11.5	Pension	BZ_FIN_PENSION
11.6	Social security benefit	BZ_FIN_SSB_BENEFIT
11.7	Social programme	BZ_FIN_SOCIAL_PROGRAMME
11.8	Poverty and socioeconomic status	BZ_FIN_POVERTY
11.9	Housing tenure	BZ_FIN_HOUSING

PART 12 · CRIMINAL RECORD AND PROCEEDINGS

12.1	Criminal record and proceedings	BZ_PENAL_CRIMINAL_RECORD
12.2	Case number	BZ_PENAL_CASE_NUMBER
13	Where people live: towns and villages	
14	Limits	
15	Verification	
16	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Discovery policy and classifiers	

1

About this discovery policy

This discovery policy finds the personal data in a Belizean database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and social security numbers does not get there: a birth date, a sex and a village of a few hundred people are enough to point at one person. The policy works on the layers where the risk is:

- **Direct identifiers** — social security number, TIN, passport, voter ID, driver's licence, immigration permits, civil registry entries, names, contact, accounts and cards, land parcels, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, town or village, neighbourhood, nationality, marital status, occupation, employer, education.
- **Sensitive personal data** — the categories of section 2: racial or ethnic origin, political opinions, religious and similar beliefs, membership of a political body, trade union membership, genetic and biometric data, sexual orientation and sexual life — and, beyond the list, gender identity.
- **Health records** — health identifiers, diagnoses, medications, clinical notes, test results, disability, reproductive and mental health.
- **Financial record or position** — credit references, debt, income, assets, pensions, social security benefits, social programmes, poverty and housing tenure. Section 2 makes them sensitive.
- **Criminal record and proceedings** — records, charges, outcomes and case numbers, also sensitive under section 2.

In Data Control Tower the policy is one discovery policy with its classifiers, the data classes they vote for, the algorithms those data classes name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — `NAME`, `RESULT`, `CITY` — needs the values to agree. A column with a meaningless name (`FIELD1`, `REMARKS`) is still found when its values have a recognizable shape or vocabulary: a social security number, a Belizean phone number, a plate, a village.

Column names are recognized in English, in the abbreviations of Belizean systems (`SSN`, `SSB_NO`, `TIN`, `BHIS_NO`, `NHI_NO`, `DOB`) and in Spanish, which a large part of the country speaks.

> Before masking, inventory the binary columns (BLOBs, images, PDFs). Onboarding processes often store a scan of the social security card or passport: the number is still readable in the image. Report those columns as residual risk.

2

The Data Protection Act, 2021 at a glance

The Data Protection Act, 2021 — Act No. 45 of 2021 — was assented to on 29 November 2021 and gazetted on 30 November 2021. It regulates the collection, keeping, use and dissemination of personal data and protects the privacy of individuals in relation to it.

Commencement. The Act comes into force on a day appointed by the Minister by Order published in the Gazette, and different days may be appointed for different provisions (s. 97). In the public sources consulted in September 2026 no commencement Order was found, and secondary sources disagree on whether and when the Act took effect. Confirm the status with the Ministry before relying on a date; the design of the policy does not depend on it.

What matters for a copy of production data:

- **Personal data** is data which relates to an individual who can be identified from that data, or from that data together with other information which is in the possession of, or is likely to come into the possession of, the data controller (s. 2). Data from which no individual can be identified, even with that other information, is not personal data.
- **Sensitive personal data** is information on a data subject's racial or ethnic origin; political opinions; religious beliefs or other beliefs of a similar nature; membership of a political body; membership of a trade union; genetic data; biometric data; sexual orientation or sexual life; **financial record or position**; criminal record; and proceedings for any offence committed or alleged to have been committed, their disposal or sentence (s. 2). Health is not on the list; genetic and biometric data are, and the Act defines both.
- **Processing of sensitive personal data is prohibited** unless one of the conditions of section 10 applies — consent, employment obligations, vital interests, legal proceedings, public functions, medical purposes under a duty of confidentiality, among others. Data relating to criminal convictions and offences is processed only under the control of an official authority or as an enactment authorises (s. 10(2)).
- **Principles.** Personal data is collected for specified, explicit and legitimate purposes and not further processed in a manner incompatible with them; it is adequate, relevant and limited to what is necessary; kept in identifiable form no longer than necessary; and processed with appropriate security (s. 4). A controller who fails to comply commits an offence punishable by a fine of five hundred thousand dollars, imprisonment for three years, or both (s. 5(7)).
- **Security.** Technical and organisational measures appropriate to the risk, including pseudonymisation and encryption (s. 60), and data protection by design and by default (s. 55).
- **Breaches.** The Commissioner is notified without undue delay and, where feasible, within seventy-two hours (s. 61). Data subjects are told when the breach is likely to result in a high risk — unless the data affected had been rendered unintelligible to anyone not authorised to access it (s. 62).
- **Children.** A child is a person under 16. Processing a child's data is lawful only with the consent of a parent or guardian, or of the child when over thirteen (s. 9).
- **Scope.** Small businesses, with an annual turnover of $3,000,000 or less, are exempt — except those providing health services, credit reporting bodies, reporting entities under the anti-money-laundering law and others listed in section 3(3).
- **Research and statistics.** Processing only for research, statistical or historical purposes is compatible with the original purpose when results are not made available in a form which identifies data subjects (s. 36).
- **Supervision.** The Data Protection Commissioner, a public officer in the Ministry responsible for digital transformation and e-governance who acts independently, administers the Act (s. 68); appeals go to the Data Protection Tribunal (s. 88).

A test environment with production data is processing for purposes the data was not collected for, and it holds sensitive data — financial and criminal data among them — outside the controls built for it. A copy from which individuals can no longer be identified is not personal data: that is what the policy is for.

The list of sensitive data in section 2 is closed, but the policy goes further where the risk is the same: it treats health records, gender identity and the language a person speaks — which reveals Maya, Garifuna or Mennonite origin — with the same care.

> The definition of personal data counts what the controller holds or is likely to hold. Masking is deterministic for the engine key, so whoever has both the production data and the key can link a masked row back to its source. Keep the key, and access to production, away from the people who use the masked copy. Whether a copy counts as anonymised is a legal assessment of the whole environment, not of the discovery policy alone.

How sensitive data is discovered

A discovery job looks at every column of its rule set and asks each classifier of the discovery policy how confident it is that the column belongs to its data class. The policy uses the four classifier frameworks of Delphix:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the data class out. It never assigns a data class on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per data class, and the column is assigned to the data class with the highest confidence when it reaches the assignment threshold of the discovery policy — **60%** here. Values that do not match a format or a list count against their data class by the classifier's reject strength.

These are the names Data Control Tower gives the objects: data classes, classifiers and a discovery policy, run by a discovery job. A Continuous Compliance Engine used on its own calls the same objects domains, classifiers and a profile set, run by a profiling job; everything in this document applies to both.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. Discovery tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Discovery proposes; it does not decide. Review the data classes assigned in the rule set before running a masking job, and look for columns the policy left unassigned.

4

How data is masked

Each data class names one algorithm, which a masking job applies to every column the rule set assigns to the data class. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each data class shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine and compliance node uses the same keys.

Where an algorithm that comes with Delphix already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the policy names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name, the one an engine uses; Data Control Tower lists them without the

prefix (`CM Numeric` , `CreditCard` , `BloodType SL`). They are on every engine and in every Data Control Tower, and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. With other keys the masked values differ; their shape does not.

5

Essential and extended packs

The policy can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create just its data classes, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the discovery policy.

PACK	DATA CLASSES	CLASSIFIERS	ALGORITHMS	FILES
Essential	11	22	10	5
Extended	72	126	84	50

The essential pack holds these data classes, marked **Essential** in the tables and chapters:

- Social security number — `BZ_L1_SOCIAL_SECURITY_NUMBER`
- Taxpayer identification number — `BZ_L1_TIN`
- Passport — `BZ_L1_PASSPORT`
- Given names — `BZ_L1_GIVEN_NAME`
- Surnames — `BZ_L1_SURNAME`
- Full name — `BZ_L1_FULL_NAME`
- E-mail — `BZ_L1_EMAIL`
- Phone — `BZ_L1_PHONE`
- Address — `BZ_L1_ADDRESS`
- Address detail — `BZ_L1_ADDRESS_DETAIL`
- Birth date — `BZ_L2_BIRTH_DATE`

> With fewer data classes competing, a column that a data class of the extended pack would claim by its name can be proposed for an essential data class instead — a numeric code, for instance, can look like a telephone number. Review the discovery result.

6

Data classes at a glance

Every data class of the policy, how it is found and the algorithm that masks it.

DATA CLASS	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Social security number ESSENTIAL BZ_L1_SOCIAL_SECURITY_NUMBER	COLUMN NAME · VALUE FORMAT	BZ_CM_ALNUM
Taxpayer identification number ESSENTIAL BZ_L1_TIN	COLUMN NAME	BZ_CM_ALNUM
Passport ESSENTIAL BZ_L1_PASSPORT	COLUMN NAME · VALUE FORMAT	BZ_CM_ALNUM
Voter ID BZ_L1_VOTER_ID	COLUMN NAME	BZ_CM_ALNUM
Driver's licence BZ_L1_DRIVERS_LICENCE	COLUMN NAME	BZ_CM_ALNUM
Immigration document BZ_L1_IMMIGRATION_DOCUMENT	COLUMN NAME	BZ_CM_ALNUM
Civil registry entry BZ_L1_VITAL_RECORD	COLUMN NAME	BZ_CM_ALNUM
Given names ESSENTIAL BZ_L1_GIVEN_NAME	COLUMN NAME · KNOWN VALUES	BZ_GIVEN_NAMES
Surnames ESSENTIAL BZ_L1_SURNAME	COLUMN NAME · KNOWN VALUES	BZ_SURNAMES
Full name ESSENTIAL BZ_L1_FULL_NAME	COLUMN NAME · KNOWN VALUES	BZ_FULL_NAME
E-mail ESSENTIAL BZ_L1_EMAIL	COLUMN NAME · DATA TYPE · VALUE FORMAT	BZ_EMAIL
Phone ESSENTIAL BZ_L1_PHONE	COLUMN NAME · VALUE FORMAT	BZ_PHONE
Address ESSENTIAL BZ_L1_ADDRESS	COLUMN NAME · DATA TYPE · VALUE FORMAT	BZ_ADDRESS
Address detail ESSENTIAL BZ_L1_ADDRESS_DETAIL	COLUMN NAME	BZ_CM_ALNUM
Bank account BZ_L1_BANK_ACCOUNT	COLUMN NAME	BZ_CM_ALNUM
Payment card BZ_L1_PAYMENT_CARD	COLUMN NAME · VALUE FORMAT	BZ_CARD
IP address BZ_L1_IP_ADDRESS	COLUMN NAME · VALUE FORMAT	BZ_IP
Device identifier BZ_L1_DEVICE_ID	COLUMN NAME · VALUE FORMAT	BZ_CM_HEX
Licence plate BZ_L1_LICENCE_PLATE	COLUMN NAME · VALUE FORMAT	BZ_PLATE

DATA CLASS	FOUND BY	ALGORITHM
Vehicle identification number `BZ_L1_VIN`	COLUMN NAME · VALUE FORMAT	`BZ_CM_ALNUM`
Land parcel `BZ_L1_LAND_PARCEL`	COLUMN NAME · VALUE FORMAT	`BZ_PARCEL`
Contract or customer number `BZ_L1_CONTRACT_NUMBER`	COLUMN NAME	`BZ_CM_ALNUM`
User name or social media `BZ_L1_USERNAME`	COLUMN NAME	`BZ_CM_ALNUM`
Credential `BZ_L1_CREDENTIAL`	COLUMN NAME · VALUE FORMAT	`BZ_REDACT`
Geolocation `BZ_L1_GEOLOCATION`	COLUMN NAME · VALUE FORMAT	`BZ_COORDINATE`
Free text `BZ_L1_FREE_TEXT`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`BZ_FREE_TEXT`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `BZ_L2_BIRTH_DATE`	COLUMN NAME · DATA TYPE	`BZ_BIRTH_DATE`
Birth year `BZ_L2_BIRTH_YEAR`	COLUMN NAME · DATA TYPE	`BZ_YEAR`
Age `BZ_L2_AGE`	COLUMN NAME · DATA TYPE	`BZ_AGE`
Life event dates `BZ_L2_EVENT_DATE`	COLUMN NAME · DATA TYPE	`BZ_EVENT_DATE`
Sex `BZ_L2_SEX`	COLUMN NAME · KNOWN VALUES	`BZ_SEX`
Town or village `BZ_L2_TOWN_VILLAGE`	COLUMN NAME · VALUE FORMAT	`BZ_TOWN_VILLAGE`
Neighbourhood `BZ_L2_NEIGHBOURHOOD`	COLUMN NAME	`BZ_NEIGHBOURHOOD`
Nationality `BZ_L2_NATIONALITY`	COLUMN NAME · VALUE FORMAT	`BZ_NATIONALITY`
Marital status `BZ_L2_MARITAL_STATUS`	COLUMN NAME · VALUE FORMAT	`BZ_MARITAL_STATUS`
Occupation `BZ_L2_OCCUPATION`	COLUMN NAME	`BZ_OCCUPATION`
Employer `BZ_L2_EMPLOYER`	COLUMN NAME	`BZ_EMPLOYER`
Education `BZ_L2_EDUCATION`	COLUMN NAME · VALUE FORMAT	`BZ_EDUCATION`
School `BZ_L2_SCHOOL`	COLUMN NAME	`BZ_SCHOOL`
Children and dependants `BZ_L2_DEPENDANTS`	COLUMN NAME · DATA TYPE	`BZ_CAPPED_COUNT`
SENSITIVE PERSONAL DATA		

DATA CLASS	FOUND BY	ALGORITHM
Ethnic origin BZ_L3_ETHNICITY	COLUMN NAME VALUE FORMAT	BZ_ETHNICITY
Language BZ_L3_LANGUAGE	COLUMN NAME VALUE FORMAT	BZ_LANGUAGE
Religion BZ_L3_RELIGION	COLUMN NAME VALUE FORMAT	BZ_RELIGION
Beliefs of a similar nature BZ_L3_BELIEF	COLUMN NAME	BZ_SUPPRESSED_CATEGORY
Political opinion BZ_L3_POLITICAL_OPINION	COLUMN NAME VALUE FORMAT	BZ_POLITICAL_OPINION
Membership of a political body BZ_L3_POLITICAL_MEMBERSHIP	COLUMN NAME VALUE FORMAT	BZ_POLITICAL_PARTY
Trade union membership BZ_L3_TRADE_UNION	COLUMN NAME VALUE FORMAT	BZ_SUPPRESSED_CATEGORY
Genetic data BZ_L3_GENETIC	COLUMN NAME VALUE FORMAT	BZ_REDACT
Biometric data BZ_L3_BIOMETRIC	COLUMN NAME DATA TYPE	BZ_REDACT
Sexual orientation BZ_L3_SEXUAL_ORIENTATION	COLUMN NAME VALUE FORMAT	BZ_SEXUAL_ORIENTATION
Sexual life BZ_L3_SEXUAL_LIFE	COLUMN NAME	BZ_SUPPRESSED_CATEGORY
Gender identity BZ_L3_GENDER_IDENTITY	COLUMN NAME VALUE FORMAT	BZ_GENDER_IDENTITY
HEALTH RECORDS		
Health identifier BZ_HEALTH_ID	COLUMN NAME	BZ_CM_ALNUM
Diagnosis BZ_HEALTH_DIAGNOSIS	COLUMN NAME VALUE FORMAT	BZ_DIAGNOSIS
Medication BZ_HEALTH_MEDICATION	COLUMN NAME VALUE FORMAT	BZ_MEDICATION
Clinical text BZ_HEALTH_CLINICAL_TEXT	COLUMN NAME DATA TYPE	BZ_FREE_TEXT
Test result BZ_HEALTH_TEST_RESULT	COLUMN NAME	BZ_CM_ALNUM
Blood group BZ_HEALTH_BLOOD_GROUP	COLUMN NAME VALUE FORMAT	dlpx-core:BloodType SL
Disability BZ_HEALTH_DISABILITY	COLUMN NAME VALUE FORMAT	BZ_DISABILITY
Sexual and reproductive health BZ_HEALTH_REPRODUCTIVE	COLUMN NAME	BZ_SUPPRESSED_CATEGORY
Mental health and addiction BZ_HEALTH_MENTAL	COLUMN NAME	BZ_SUPPRESSED_CATEGORY
FINANCIAL RECORD OR POSITION		

DATA CLASS	FOUND BY	ALGORITHM
Credit reference `BZ_FIN_CREDIT_REFERENCE`	COLUMN NAME	`BZ_CREDIT`
Debt amount `BZ_FIN_DEBT`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Salary and income `BZ_FIN_INCOME`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Assets `BZ_FIN_ASSETS`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Pension `BZ_FIN_PENSION`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Social security benefit `BZ_FIN_SSB_BENEFIT`	COLUMN NAME VALUE FORMAT	`BZ_SSB_BENEFIT`
Social programme `BZ_FIN_SOCIAL_PROGRAMME`	COLUMN NAME VALUE FORMAT	`BZ_SOCIAL_PROGRAMME`
Poverty and socioeconomic status `BZ_FIN_POVERTY`	COLUMN NAME VALUE FORMAT	`BZ_POVERTY`
Housing tenure `BZ_FIN_HOUSING`	COLUMN NAME VALUE FORMAT	`BZ_HOUSING`
CRIMINAL RECORD AND PROCEEDINGS		
Criminal record and proceedings `BZ_PENAL_CRIMINAL_RECORD`	COLUMN NAME	`BZ_CRIMINAL_RECORD`
Case number `BZ_PENAL_CASE_NUMBER`	COLUMN NAME VALUE FORMAT	`BZ_CM_ALNUM`

PART 7

Direct identifiers

Data that identifies a person on its own. Belize has no national identity card for its citizens: the Social Security Board card is the everyday identification, asked for by employers, banks, the credit bureau and public hospitals, so its number is the key of most records. It is masked the same way everywhere, keeping its nine digits.

7.1 Social security number

BZ_L1_SOCIAL_SECURITY_NUMBER

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The nine-digit number of the Social Security Board, printed on the card every worker must have from age 14. It is issued in sequence and has no public check digit. Without a national identity card, it is the identifier employers, banks, credit unions, the credit bureau and public hospitals ask for.

HOW IT IS FOUND

COLUMN NAME BZ_L1_SOCIAL_SECURITY_NUMBER — Path

90% `ssn` `ss_?(no|num|number|nbr)` `social_?security(_?(no|num|number|nbr|card|id))?` `soc_?sec(_?(no|num|number))?` `ssb_?(no|num|number|id|card)` `social_?sec_?card` `insured_?(person_?)?(no|num|number)` `n(o|um|ro|umero)_?(de_?)?seguro_?social` `seguro_?social`

VALUE FORMAT BZ_L1_SOCIAL_SECURITY_NUMBER — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{3}[\s\-]\d{3}[\s\-]\d{3})`	70%	
`0*(?:\d{9})`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each digit is mapped to another digit, keeping the length and any separators (`123–456–789`). The mapping is one-to-one: a social security number used as a key does not collide, and the same number masks the same way in every table.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
000123456	→	**000904292**
123–456–789	→	**110–858–568**

7.2 Taxpayer identification number

BZ_L1_TIN

ESSENTIAL · COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The TIN of the Belize Tax Service, used for income tax, GST, customs and excise: six digits and a check digit that is not shown to the taxpayer. Individuals, sole proprietors, partnerships and companies all have one.

HOW IT IS FOUND

COLUMN NAME BZ_L1_TIN — Path

90% `tin` `tin_?(no|num|number)` `tax_?(id|identification)(_?(no|num|number))?` `tax_?payer_?(id|no|num|number)` `taxpayer_?(id|no|num|number)` `bts_?(no|id|tin|number)` `gst_?(no|number|reg|registration)(_?no)?` `n(o|um|ro)_?contribuyente` `nit`

HOW IT IS MASKED

Digit by digit, keeping the length. A company's TIN cannot be told apart from a person's and is masked too; the mapping is deterministic, so joins with supplier tables still work.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456	→	**904292**

7.3 Passport

BZ_L1_PASSPORT

ESSENTIAL COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

Belizean and foreign passport numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_PASSPORT — Path

85% `passport[a-z_]*` `pass_?port_?(no|num|number)` `pp_?(no|num|number)` `travel_?document(_?(no|num|number))?` `pasaporte[a-z_]*`

VALUE FORMAT BZ_L1_PASSPORT — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{1,2}\d{6,8}`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
P0123456	→	**M1295864**

7.4 Voter ID

BZ_L1_VOTER_ID

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The ID number and the registration number of the voter identification card of the Elections and Boundaries Department — one of the photo IDs accepted across public services.

HOW IT IS FOUND

> COLUMN NAME BZ_L1_VOTER_ID — Path
>
> 85% `voter_?(id|card|reg|registration)(_?(no|num|number|card))?` `voters_?(id|card|reg|registration)(_?(no|num|number))?` `elector(al)?_?(id|no|num|number|card|reg|registration)(_?(no|num|number))?` `ebd_?(no|id|reg|number)` `registration_?(no|num|number)_?(voter|elector)` `elector_?reg_?no`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456	→	**904292**

7.5 Driver's licence

BZ_L1_DRIVERS_LICENCE

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The number of the driver's licence issued by the Department of Transport or a town council.

HOW IT IS FOUND

> COLUMN NAME BZ_L1_DRIVERS_LICENCE — Path
>
> 85% `drivers?_?licen[cs]e(_?(no|num|number))?` `driving_?licen[cs]e(_?(no|num|number))?` `dl_?(no|num|number)` `licen[cs]e_?(no|num|number)` *(except when followed by* `plate`, `vehicle`, `business`, `trade`, `liquor`, `professional`*)* `licencia_?(de_?)?conducir`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BZ-012345	→	**CT-763680**

7.6 Immigration document

BZ_L1_IMMIGRATION_DOCUMENT

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Permanent residence cards, temporary employment (work) permits, visas, nationality and naturalization certificates, refugee and asylum identification, Qualified Retired Persons cards. In a country where 11.5% of the population was born abroad, they are common in employment and banking records.

HOW IT IS FOUND

COLUMN NAME — BZ_L1_IMMIGRATION_DOCUMENT — Path

85% `permanent_?residen(ce|cy|t)(_?(permit|card|no|num|number|id))?` `pr_?(card|permit)(_?(no|number))?` `work_?permit(_?(no|num|number))?` `temporary_?employment_?permit` `tep_?(no|num|number)` `immigration_?(permit|document|card|file|status_?no|no|num|number)` `visa_?(no|num|number)` `residen(ce|cy)_?permit(_?(no|number))?` `nationality_?certificate(_?(no|number))?` `naturali[sz]ation_?(certificate|cert|no|number)` `refugee_?(id|card|no|number)` `asylum_?(id|no|number)` `qrp_?(id|no|number|card)` `carne_?migratorio` `permiso_?(de_?)?(residencia|trabajo)`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PR 12345	→	XY 20897

7.7 Civil registry entry

BZ_L1_VITAL_RECORD

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Birth, death and marriage certificate or registry entry numbers of the Vital Statistics Unit.

HOW IT IS FOUND

COLUMN NAME — BZ_L1_VITAL_RECORD — Path

85% `birth_?cert(ificate)?(_?(no|num|number|entry))?` `death_?cert(ificate)?(_?(no|num|number))?` `marriage_?cert(ificate)?(_?(no|num|number))?` `registry_?entry(_?(no|number))?` `vital_?(record|statistics)_?(no|num|number)` `certificado_?(de_?)?(nacimiento|defuncion|matrimonio)` `acta_?(de_?)?(nacimiento|defuncion|matrimonio)`

55% `entry_?(no|number)`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1234/1985	→	**1092/4201**

7.8 Given names

BZ_L1_GIVEN_NAME

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

First and middle names (`FIRST_NAME` , `MIDDLE_NAME`), including two given names in one column such as `Maria Isabel` .

HOW IT IS FOUND

COLUMN NAME BZ_L1_GIVEN_NAME — Path

85%	`first_?names?` `given_?names?` `fore_?names?` `christian_?name` `fname` `name_?first` `middle_?names?` `mname` `name_?middle` `nombres?_?(de_?)?pila` `primer_?nombre` `segundo_?nombre` `nombres` *(except when followed by list E1)*
50%	`name` *(except when followed by list E2)* `nombre` *(except when followed by list E3)*

KNOWN VALUES BZ_L1_GIVEN_NAME — List

LIST	VALUES	STRENGTH	FIRST VALUES
`bz-detect-given-names.txt`	208	70%	Maria, Jose, Juan, Carlos, Luis, Francisco

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word is replaced by a name from a list of 208 names used in Belize, keeping the number of words and the case. More than three words are masked character by character.

`BZ_GIVEN_NAMES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .

`BZ_GIVEN_NAME` NAME

Replaces the name with one of the 208 names in `bz-given-names.txt` .

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Kenrick	→	**Yvette**
MARIA ISABEL	→	**NELSON CANDELARIA**

7.9 Surnames

BZ_L1_SURNAME

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

Surnames and maiden names, one or two per column, and hyphenated surnames: `Gillett` , `Gomez Cal` , `Young-Flowers` .

HOW IT IS FOUND

COLUMN NAME BZ_L1_SURNAME – Path

85% `last_?names?` `surnames?` `family_?names?` `lname` `name_?last` `maiden_?name` `mothers?_?maiden_?name` `maiden` `second_?surname` `married_?name` `apellidos?` `apellido_?(paterno|materno)` `primer_?apellido` `segundo_?apellido`

KNOWN VALUES BZ_L1_SURNAME – List

LIST	VALUES	STRENGTH	FIRST VALUES
`bz-detect-surnames.txt`	225	70%	Martinez, Garcia, Castillo, Lopez, Williams, Perez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each surname is replaced by one from a list of 225 surnames frequent in Belize — Mestizo, Creole, Maya, Garifuna and Mennonite, led by Martinez, Garcia, Castillo, Lopez and Williams —, keeping the number of words, the hyphen and the case.

`BZ_SURNAMES` **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .

`BZ_SURNAME` **NAME**

Replaces the name with one of the 225 names in `bz-surnames.txt` .

`BZ_CM_ALNUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Gillett`	→	**`Munoz`**
`Young-Flowers`	→	**`McKenzie-Ramirez`**

7.10 Full name

BZ_L1_FULL_NAME

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column, in the English order used by the civil registry — given name, middle name, surname — with a middle initial or a second surname in Hispanic families, or written as `SURNAME, GIVEN NAMES` . Also the name of an account holder, beneficiary, guardian or next of kin.

HOW IT IS FOUND

COLUMN NAME `BZ_L1_FULL_NAME – Path`

90% `full_?name` `fullname` `complete_?name` `person_?name` `name_?of_?(customer|cust|client|patient|employee|emp|staff|worker|member|student|pupil|insured|beneficiary|holder|account_?holder|policy_?holder|mother|father|parent|guardian|spouse|partner|next_?of_?kin|doctor|physician|nurse|contact|emergency_?contact|guarantor|debtor|borrower|applicant|signatory|witness|representative|owner|tenant|landlord|victim|complainant|accused|defendant|donor|heir|person|driver|agent|citizen|elector|voter|taxpayer|child|dependant|dependent|relative|officer|teacher|cliente|paciente|empleado|beneficiario|titular|madre|padre|conyuge|persona)` `(customer|cust|client|patient|employee|emp|staff|worker|member|student|pupil|insured|beneficiary|holder|account_?holder|policy_?holder|mother|father|parent|guardian|spouse|partner|next_?of_?kin|doctor|physician|nurse|contact|emergency_?contact|guarantor|debtor|borrower|applicant|signatory|witness|representative|owner|tenant|landlord|victim|complainant|accused|defendant|donor|heir|person|driver|agent|citizen|elector|voter|taxpayer|child|dependant|dependent|relative|officer|teacher|cliente|paciente|empleado|beneficiario|titular|madre|padre|conyuge|persona)_?name` `nombre_?(completo|compl)` `nombres?_?y_?apellidos?`

60% `beneficiary` `guardian` `next_?of_?kin` `spouse` `emergency_?contact` `guarantor` `account_?holder` `policy_?holder` `legal_?representative` `attorney` `patient` `victim` `complainant` `accused` `defendant` `insured_?person` `titular` `beneficiario` `conyuge`

50% `name` *(except when followed by list E2)* `nombre` *(except when followed by list E3)*

KNOWN VALUES `BZ_L1_FULL_NAME – List`

LIST	VALUES	STRENGTH	FIRST VALUES
`bz-detect-given-names.txt`	208	65%	Maria, Jose, Juan, Carlos, Luis, Francisco
`bz-detect-surnames.txt`	225	65%	Martinez, Garcia, Castillo, Lopez, Williams, Perez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Given names become given names and surnames become surnames, by position: one word is a given name; two, a given name and a surname; three, two given names and a surname; four, two of each. A middle initial stays an initial (`Kenrick A. Gillett`), and a comma separates surnames from given names.

`BZ_FULL_NAME` **REGEX DECOMPOSE**

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .

> `BZ_SURNAMES` **REGEX DECOMPOSE**
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .
>
> > `BZ_SURNAME` **NAME**
> >
> > Replaces the name with one of the 225 names in `bz-surnames.txt` .
> >
> > `BZ_CM_ALNUM` **CHARACTER MAPPING**
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_GIVEN_NAMES` **REGEX DECOMPOSE**
>
> Tries 3 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .
>
> > `BZ_GIVEN_NAME` **NAME**

> Replaces the name with one of the 208 names in `bz-given-names.txt`.

EXAMPLES

VALUE		MASKED
Kenrick A. Gillett	→	**Yvette A. Munoz**
Jose Luis Martinez Cal	→	**Sylvia Cesar Contreras Requena**
CAYETANO, SHANICE	→	**ZETINA, OSCAR**

7.11 E-mail

BZ_L1_EMAIL

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

> **COLUMN NAME** BZ_L1_EMAIL — Path
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `email_?address` `correo(_?electronico)?[a-z0-9_]*`

> **DATA TYPE** BZ_L1_EMAIL — Type
>
> Accepts text (length 5 or more); any other type rules the data class out.

> **VALUE FORMAT** BZ_L1_EMAIL — Regex
>
PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	
>
> A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes `.test`, reserved for testing: a masked address never receives mail.

`BZ_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
kenrick.gillett@gmail.com	→	**hasyinl.gajzezk@pgoeb.test**

7.12 Phone

BZ_L1_PHONE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Seven-digit numbers, with or without `+501`: mobiles start with 6 (`622-4567`) and landlines with the digit of their district — 2 Belize, 3 Orange Walk, 4 Corozal, 5 Stann Creek, 7 Toledo, 8 Cayo.

HOW IT IS FOUND

COLUMN NAME BZ_L1_PHONE — Path

85% `tel` `telephone[a-z0-9_]*` `tel_?(no|num|number|home|work|mobile|cell)` `phone[a-z0-9_]*` `ph_?(no|num|number)` `mobile[a-z0-9_]*` `cell` `cell_?(phone|no|number)` `cellphone` `cellular` `contact_?(no|num|number)` `fax` `whatsapp` `telefono[a-z0-9_]*` `celular` `movil` `n(o|um|ro)_?tel(efono)?`

VALUE FORMAT BZ_L1_PHONE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(\+?\(?501\)?[\s\-]?)6\d{2}[\s\-]?\d{4})`	100%	
`0*(?:6\d{2}[\s\-]?\d{4})`	80%	
`0*(?:(\+?\(?501\)?[\s\-]?)?[2-578]\d{2}[\s\-]?\d{4})`	70%	
`0*(?:\+?\d[\d\s()\-]{6,15})`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

`+501` , the separators and the first digit — mobile, or the district of a landline — stay; the other six digits are masked. A number not shaped like a Belizean number is masked whole.

`BZ_PHONE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+501 622-4567	→	**+501 690-9910**
822-1234	→	**890-9707**

7.13 Address

BZ_L1_ADDRESS

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT SECURE LOOKUP

WHAT IT IS

The address line as written in Belize, where there are no postal codes: a house number and street, a mile marker on a highway, or a lot in a neighbourhood, followed by the town.

HOW IT IS FOUND

COLUMN NAME BZ_L1_ADDRESS — Path

80% `address[a-z0-9_]*` *(except when preceded by* `mac` , `ip` , `e_?mail` , `web` , `url` *; except when followed by list E4)* `addr(ess)?_?(line|1|2)?[a-z0-9_]*` *(except when preceded by* `mac` , `ip` , `e_?mail` , `web` , `url` *)* `street(_?(address|name))?` `residential_?address` `home_?address` `mailing_?address` `postal_?address` `physical_?address` `residence` `place_?of_?residence` `domicile` `direccion[a-z_]*` *(except when followed by* `ip` , `mac` , `correo` , `electronica` *)* `domicilio[a-z_]*`

DATA TYPE BZ_L1_ADDRESS — Type

Accepts text (length 6 or more); any other type rules the data class out.

VALUE FORMAT BZ_L1_ADDRESS — Regex

PATTERN	STRENGTH	NOTES
`(?i)#?\s*\d+[A-Z]?\s+.*\b(street|st\.?|avenue|ave\.?|road|rd\.?|drive|dr\.?|lane|boulevard|blvd\.?|highway|hwy)\b.*`	80%	
`(?i).*\bmile\s+\d+.*\b(highway|road|hwy)\b.*`	90%	
`(?i).*\blot\s*(no\.?\s*|#\s*)?\d+\s*,.+`	60%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

It is replaced by one of 3,000 fictitious Belizean addresses — streets of Belize City and the towns, mile markers on the Philip Goldson, George Price, Hummingbird and Southern highways, lots in real neighbourhoods.

`BZ_ADDRESS` SECURE LOOKUP

Replaces the value with one of the 3,000 values in `bz-addresses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`#24 Cleghorn Street, Belize City`	→	**`Mile 60 Philip Goldson Highway, Corozal Town`**

7.14 Address detail

BZ_L1_ADDRESS_DETAIL

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

House, apartment, unit, floor or lot numbers in columns of their own.

HOW IT IS FOUND

COLUMN NAME BZ_L1_ADDRESS_DETAIL — Path

70% `house_?(no|num|number)` `apt(_?(no|number))?` `apartment(_?(no|number))?` `unit_?(no|num|number)` `flat_?(no|number)` `lot_?(no|num|number)` `floor_?(no|number)?` `suite(_?no)?` `building_?(no|number)` `num_?casa` `n(o|um|ro)_?casa` `apto`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Apt. 4B`	→	**`Adv. 9W`**

7.15 Bank account

BZ_L1_BANK_ACCOUNT

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Savings, chequing and share account numbers of banks and credit unions.

HOW IT IS FOUND

COLUMN NAME BZ_L1_BANK_ACCOUNT — Path

85% `account_?(no|num|number|nbr)` `acct_?(no|num|number|nbr)?` `acc_?(no|num|number)` `bank_?(account|acct)(_?(no|num|number))?` `savings_?(account|acct)(_?(no|number))?` `checking_?(account|acct)(_?(no|number))?` `chequing_?(account|acct)(_?(no|number))?` `share_?account(_?no)?` `iban` `cuenta_?(bancaria|ahorros?|corriente)` `n(o|um|ro)_?(de_?)?cuenta`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`010-123456-7`	→	**`047-799554-8`**

7.16 Payment card

BZ_L1_PAYMENT_CARD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit, debit and prepaid card numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_PAYMENT_CARD — Path

85% `card_?(no|num|number)` `credit_?card(_?(no|num|number))?` `debit_?card(_?(no|num|number))?` `cc_?(no|num|number)` `pan` `card_?pan` `masked_?pan` `tarjeta(_?(credito|debito))?` `n(o|um|ro)_?tarjeta`

VALUE FORMAT BZ_L1_PAYMENT_CARD — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1-9]\d{12,13}|[1-9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Credit Card, which comes with Delphix: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`BZ_CARD` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with Delphix and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
`4916 3131 2345 6780`	→	**`4916 3196 4606 3896`**

7.17 IP address

BZ_L1_IP_ADDRESS

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses of users and devices.

HOW IT IS FOUND

COLUMN NAME BZ_L1_IP_ADDRESS — Path

85% `ip` `ip_?(address|addr|origin|source|destination|client|user|remote|public|private|login)` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip` `source_?ip` `direccion_?ip`

VALUE FORMAT BZ_L1_IP_ADDRESS — Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each IPv4 octet is mapped to a number from 1 to 254; an IPv6 address is mapped as hexadecimal.

`BZ_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_HEX`.

> `BZ_OCTET` NUMERIC MAPPING
>
> Maps the number to another between 1 and 254.
>
> `BZ_CM_HEX` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`200.32.211.10`	→	**`146.25.143.16`**

7.18 Device identifier

BZ_L1_DEVICE_ID

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, advertising and session identifiers, handset serial numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_DEVICE_ID — Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `device_?(id|uuid|serial)` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `serial_?(no|number)_?(device|phone|handset)` `handset_?serial`

VALUE FORMAT BZ_L1_DEVICE_ID — Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Hex stays hex and digits stay digits, so the value keeps its format.

`BZ_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**

7.19 Licence plate

BZ_L1_LICENCE_PLATE

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Plates with a district or town code — `BZ`, `CY`, `CZL`, `OW`, `SC`, `TOL`, `BMP`, `SP` — a category letter for motorcycles, taxis and other public service vehicles, and a serial number: `CY C-12345`, `BZ 12345`.

HOW IT IS FOUND

COLUMN NAME BZ_L1_LICENCE_PLATE – Path

85% `licen[cs]e_?plates?(_?(no|num|number))?` `plates?(_?(no|num|number))?` `vehicle_?(reg|registration|plate|licen[cs]e)(_?(no|num|number))?` `registration_?plate` `number_?plate` `tag_?(no|number)` `placas?` `matricula`

VALUE FORMAT BZ_L1_LICENCE_PLATE – Regex

PATTERN	STRENGTH	NOTES
`(BMP|CZL|TOL|BZ|BC|CY|OW|SC|SP|SI|SE|PG|DG)[\s\-]?([A-Z][\s\-]?)?\d{3,5}`	80%	
`[A-Z][\s\-]\d{4,5}`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The code and the category letter stay, so a Cayo taxi is still a Cayo taxi; the serial digits are masked.

`BZ_PLATE` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
CY C-12345	→	**CY C-31564**
BZ 12345	→	**BZ 31564**

7.20 Vehicle identification number

BZ_L1_VIN

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The VIN, and engine and chassis numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_VIN — Path

80% `vin` `vin_?(no|number)` `vehicle_?identification_?(no|number)` `chassis(_?(no|number))?` `engine_?(no|number|serial)` `motor_?(no|number)` `serial_?(no|number)_?vehicle` `n(o|um|ro)_?(de_?)?(serie|chasis|motor)`

VALUE FORMAT BZ_L1_VIN — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1HGCM82633A004352	→	**1JTRL73362E132318**

7.21 Land parcel

BZ_L1_LAND_PARCEL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Registered land is identified by registration section, block and parcel (`Caribbean Shores, Block 16, Parcel 1234`); national land by lease, Minister's Fiat grant or title numbers. The Land Registry leads from a parcel to its proprietor.

HOW IT IS FOUND

COLUMN NAME BZ_L1_LAND_PARCEL — Path

85% `parcel(_?(no|num|number|id))?` `block_?(and_?)?parcel` `land_?(title|parcel|registry|register|certificate|lease)(_?(no|num|number))?` `title_?(deed_?)?(no|number)` `land_?certificate` `lease_?(no|number)` `minister_?s_?fiat(_?no)?` `fiat_?grant(_?no)?` `deed_?(no|number)` `cadastr[a-z_]*` `finca` `folio_?real`

VALUE FORMAT BZ_L1_LAND_PARCEL — Regex

PATTERN	STRENGTH	NOTES
`(?i).*block\s*(no\.?\s*)?\d+.*parcel\s*(no\.?\s*)?\d+.*`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The block and parcel numbers are masked digit by digit; the words and the registration section stay. Other formats are masked character by character.

`BZ_PARCEL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM` .

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Caribbean Shores, Block 16, Parcel 1234	→	**Caribbean Shores, Block 62, Parcel 9707**

7.22 Contract or customer number

BZ_L1_CONTRACT_NUMBER

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Contract, policy, loan, mortgage, membership, customer, employee, student or claim numbers, and electricity and water account numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_CONTRACT_NUMBER – Path

70% `contract_?(no|num|number)` `policy_?(no|num|number)` `loan_?(no|num|number|id)` `mortgage_?(no|number)` `member(ship)?_?(no|num|number|id)` `customer_?(no|num|number|id)` `client_?(no|num|number|id)` `cust_?(no|num|id)` `employee_?(no|num|number|id)` `emp_?(no|num|id)` `staff_?(no|num|number|id)` `payroll_?(no|number)` `claim_?(no|num|number)` `meter_?(no|number)` `bel_?account(_?no)?` `bws_?account(_?no)?` `student_?(no|num|number|id)` `n(o|um|ro)_?(de_?)?(contrato|poliza|cliente|empleado)`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
POL–123456	→	**MIF–194239**

7.23 User name or social media

BZ_L1_USERNAME

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

User names, aliases and social media handles.

HOW IT IS FOUND

COLUMN NAME BZ_L1_USERNAME – Path

70% `user_?name` `username` `login(_?(name|id))?` `user_?id_?login` `nick_?name` `nickname` `alias` `screen_?name` `handle` `facebook` `instagram` `twitter` `tiktok` `linkedin` `social_?media(_?(handle|account|profile))?` `telegram` `usuario`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@kenrick_g`	→	**`@ricposl_j`**

7.24 Credential

BZ_L1_CREDENTIAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Passwords, PINs, password hashes, security answers, tokens and API keys.

HOW IT IS FOUND

COLUMN NAME BZ_L1_CREDENTIAL — Path

90% `password` `passwd` `pwd` `pass_?word` `pass` `pin(_?(code|no|number))?` `passcode` `hash_?password` `password_?hash` `secret` `secret_?(answer|question)` `security_?(answer|question)` `access_?token` `refresh_?token` `api_?key` `otp` `contrasen[aã]` `contraseña` `clave` *(except when followed by* `producto`, `prod`, `articulo`, `postal` *)*

VALUE FORMAT BZ_L1_CREDENTIAL — Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character becomes `X`. A credential has no reason to look real in a test environment.

`BZ_REDACT` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Secret#2024`	→	**`XXXXXXXXXX`**

7.25 Geolocation

BZ_L1_GEOLOCATION

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns. Belize lies between 15.8° and 18.5° north and 87.4° and 89.3° west.

HOW IT IS FOUND

COLUMN NAME BZ_L1_GEOLOCATION — Path

85% `lat` `latitude` `lon` `lng` `longitude` `coordinates?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|location|position)` `geolocation` `gps(_?(location|position|coordinates))?` `latitud` `coordenadas?`

50% `long` `longitud`

VALUE FORMAT BZ_L1_GEOLOCATION — Regex

PATTERN	STRENGTH	NOTES
`0*(?:1[5–8]\.\d{3,}\s*,\s*–8[7–9]\.\d{3,})`	90%	
`0*(?:1[5–8]\.\d{3,})`	50%	
`–8[7–9]\.\d{3,}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved.

`BZ_COORDINATE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`17.251234,–88.759876`	→	**`17.257210,–88.778965`**

7.26 Free text

BZ_L1_FREE_TEXT

COLUMN NAME DATA TYPE VALUE FORMAT FREE TEXT REDACTION

WHAT IT IS

Remarks, comments, complaints, case notes and statements where personal data is written without structure.

HOW IT IS FOUND

COLUMN NAME BZ_L1_FREE_TEXT — Path

60% `remarks?` `comments?` `notes?` `observations?` `narrative` `free_?text` `memo` `messages?` *(except when followed by list E5)* `complaint(_?(text|details|description))?` `description_?(of_?)?(case|complaint|incident|request|issue|problem|events)` `incident_?(details|description|narrative)` `case_?(notes?|summary|details)` `statement` `details` `summary` `observaciones?` `comentarios?` `notas?`

DATA TYPE BZ_L1_FREE_TEXT — Type

Accepts text (length 30 or more); any other type rules the data class out.

VALUE FORMAT BZ_L1_FREE_TEXT – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{3}-?\d{3}-?\d{3})`	60%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:(\+?501\s?)?[2-8]\d{2}-\d{4})`	60%	anywhere in the value

A value that matches none does not count against the data class.

HOW IT IS MASKED

Free Text Redaction: social security numbers, e-mails, phone numbers, card numbers, plates and IPs become `[DATA]`, and the given names and surnames of the lists become `[NAME]`.

`BZ_FREE_TEXT` **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with `[DATA]`, and the 858 terms of `bz-text-names.txt` with `[NAME]`.

EXAMPLES

VALUE		MASKED
`Customer Gillett, SSN 000123456, email k.gillett@gmail.com, tel 622-4567.`	→	**`Customer [NAME], SSN [DATA], email [DATA], tel [DATA].`**

PART 8

Quasi-identifiers

Data that identifies no one on its own, but does in combination. Belize had 397,483 people in the 2022 census, spread over some two hundred villages and communities; 208 of the 221 places counted had fewer than 5,000 inhabitants, many fewer than 500. A birth date, a sex and one of those villages point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

8.1 Birth date

BZ_L2_BIRTH_DATE

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The birth date, in date, timestamp or text columns.

HOW IT IS FOUND

COLUMN NAME BZ_L2_BIRTH_DATE — Path

90% `dob` `d_?o_?b` `date_?of_?birth` `birth_?date` `birthdate` `birthday` `born_?(on|date)` `bdate` `fecha_?(de_?)?nac(imiento)?` `fec_?nac(imiento)?` `f_?nac(imiento)?` `nacimiento`

DATA TYPE BZ_L2_BIRTH_DATE — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 60 days back or forward: it breaks the link to the person and keeps ages and cohorts almost intact.

`BZ_BIRTH_DATE` DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

8.2 Birth year

BZ_L2_BIRTH_YEAR

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The birth year alone.

HOW IT IS FOUND

COLUMN NAME BZ_L2_BIRTH_YEAR — Path

90% `birth_?year` `year_?of_?birth` `yob` `yr_?of_?birth` `an(i)?o_?(de_?)?nac(imiento)?` `año_?(de_?)?nac(imiento)?`

DATA TYPE BZ_L2_BIRTH_YEAR — Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: 1985 becomes another year of the eighties.

`BZ_YEAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

8.3 Age

BZ_L2_AGE

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

Ages in years, whole or with decimals.

HOW IT IS FOUND

> COLUMN NAME BZ_L2_AGE – Path
>
> 85% `age(_?(years|yrs|in_?years|at_?(admission|death|entry|diagnosis|registration)|group|range|band|bracket|last_?birthday))?` `years_?old` `edad(_?(actual|anos|años))?`

> DATA TYPE BZ_L2_AGE – Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

HOW IT IS MASKED

The tens digit stays and the units digit is mapped (37 becomes 3x). From 100 on, 90: extreme ages identify on their own.

`BZ_AGE` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

8.4 Life event dates

BZ_L2_EVENT_DATE

COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

Dates of death, marriage, divorce, hiring and leaving a job, retirement, admission and discharge, diagnosis, arrest, conviction, naturalization and other personal events.

HOW IT IS FOUND

COLUMN NAME BZ_L2_EVENT_DATE — Path

80% `date_?of_?(death|marriage|divorce|hire|hiring|employment|engagement|termination|dismissal|resignation|retirement|admission|discharge|diagnosis|visit|consultation|delivery|arrest|conviction|sentence|sentencing|naturali[sz]ation|injury|surgery)` `(death|marriage|divorce|hire|hiring|employment|employment_?start|start_?of_?employment|termination|separation|resignation|retirement|admission|discharge|diagnosis|visit|delivery|arrest|conviction|sentencing|naturali[sz]ation|pension_?start|injury|vaccination|surgery|immigration)_?date` `dod` `fecha_?(de_?)?(defuncion|fallecimiento|matrimonio|divorcio|ingreso|egreso|contratacion|jubilacion|diagnostico)`

DATA TYPE BZ_L2_EVENT_DATE — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 30 days: less than the birth date, since they are often combined with it.

`BZ_EVENT_DATE` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

8.5 Sex

BZ_L2_SEX

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Registered sex in any notation: `F` / `M`, `Female` / `Male`, `Woman` / `Man`, and in Spanish.

HOW IT IS FOUND

COLUMN NAME BZ_L2_SEX — Path

85% `sex(_?(code|at_?birth|registered))?` `gender(_?code)?` *(except when followed by `identity`, `expression`)* `sexo` `genero` *(except when followed by `identidad`)*

KNOWN VALUES BZ_L2_SEX — List

LIST	VALUES	STRENGTH	FIRST VALUES
`bz-detect-sex.txt`	9	80%	female, male, woman, man, fem, mujer
`bz-detect-sex-letter.txt`	3	60%	f, m, h

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the data class.

HOW IT IS MASKED

Replaced within its own vocabulary: `F` / `M` stays `F` / `M`.

`BZ_SEX` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

> `BZ_SEX_FEMALE_MALE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `bz-sex-female-male.txt`, chosen by a keyed hash.
>
> `BZ_SEX_WOMAN_MAN` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `bz-sex-woman-man.txt`, chosen by a keyed hash.
>
> `BZ_SEX_SPANISH` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `bz-sex-spanish.txt`, chosen by a keyed hash.
>
> `BZ_SEX_MUJER_HOMBRE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `bz-sex-mujer-hombre.txt`, chosen by a keyed hash.
>
> `BZ_SEX_F_M` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `bz-sex-f-m.txt`, chosen by a keyed hash.
>
> `BZ_SEX_H_M` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `bz-sex-h-m.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
Male	→	**Female**

8.6 Town or village

BZ_L2_TOWN_VILLAGE

COLUMN NAME · VALUE FORMAT · DATA CLEANSING

WHAT IT IS

The city, town, village or community where a person lives or was born. The 2022 census counted Belize City, Belmopan, seven towns and some two hundred villages and communities; 208 of the 221 places had fewer than 5,000 inhabitants.

HOW IT IS FOUND

> COLUMN NAME BZ_L2_TOWN_VILLAGE — Path
>
85%	`town` `village` `town_?(or_?)?village` `city_?(town_?)?village` `ctv` `community` *(except when followed by* `service`, `group`, `organi[sz]ation`, `work`*)* `locality` `settlement` `home_?town` `hometown` `place_?of_?birth` `birth_?place` `birthplace` `place_?of_?residence_?(town|village)` `residence_?(town|village|community)` `town_?of_?residence` `village_?of_?residence` `aldea` `comunidad` `localidad` `lugar_?(de_?)?nacimiento`
50%	`city` `ciudad` `municipality` `pueblo`

> VALUE FORMAT BZ_L2_TOWN_VILLAGE — Values
>
PATTERN	STRENGTH	NOTES
One of 241 known values, ignoring case — Corozal Town, Altamira, Buena Vista, Calcutta, Caledonia, Carolina, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A place under 5,000 inhabitants becomes the nearest place of its district with at least 5,000; larger ones stay. See *Where people live*.

`BZ_TOWN_VILLAGE` DATA CLEANSING

Replaces each value found in `bz-town-village-generalized.txt` (489 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Crooked Tree	→	**Ladyville**
Hopkins	→	**Dangriga**
Belmopan	→	**Belmopan**

8.7 Neighbourhood

BZ_L2_NEIGHBOURHOOD

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Neighbourhoods, subdivisions, housing schemes and land registration sections within a town: `Lake Independence`, `Port Loyola`, `Salvapan`.

HOW IT IS FOUND

> COLUMN NAME BZ_L2_NEIGHBOURHOOD — Path
>
> 85% `neighbou?rhood` `subdivision` `barrio` `colonia` `residential_?area` `area_?of_?residence` `housing_?(area|scheme|estate)` `registration_?section` `reg_?section` `urbanizacion` `sector_?residencial`

HOW IT IS MASKED

Replaced by one of 30 neighbourhoods of Belize City and the towns.

`BZ_NEIGHBOURHOOD` SECURE LOOKUP

Replaces the value with one of the 30 values in `bz-neighbourhoods.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Yarborough	→	**DFC Area**

8.8 Nationality

BZ_L2_NATIONALITY

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

Nationality, citizenship or country of birth. In a Belizean database, an uncommon nationality identifies.

HOW IT IS FOUND

> COLUMN NAME BZ_L2_NATIONALITY — Path
>
> 80% `nationality` `citizenship` `country_?of_?(birth|origin|citizenship|nationality)` `birth_?country` `nacionalidad` `pais_?(de_?)?(nacimiento|origen)` `ciudadania`

VALUE FORMAT BZ_L2_NATIONALITY — Values

PATTERN	STRENGTH	NOTES
One of 46 known values, ignoring case — Belizean, Guatemalan, Salvadoran, Honduran, Mexican, American, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the 16 most common nationalities in Belize — Belizean, and then those of the largest foreign-born groups in the 2022 census: Guatemalan, Salvadoran, Honduran, American and Mexican.

`BZ_NATIONALITY` SECURE LOOKUP

Replaces the value with one of the 16 values in `bz-nationalities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Guatemalan	→	**Belizean**

8.9 Marital status

BZ_L2_MARITAL_STATUS

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

Marital and union status, in the 2022 census categories: never married, married, common-law union, visiting partner, divorced, widowed, legally separated.

HOW IT IS FOUND

COLUMN NAME BZ_L2_MARITAL_STATUS — Path

85% `marital_?status` `civil_?status` `union_?status` `marriage_?status` `relationship_?status` `estado_?civil` `edo_?civil`

VALUE FORMAT BZ_L2_MARITAL_STATUS — Values

PATTERN	STRENGTH	NOTES
One of 24 known values, ignoring case — Never married, Married, Common-law union, Visiting partner, Divorced, Widowed, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another of the seven categories.

`BZ_MARITAL_STATUS` SECURE LOOKUP

Replaces the value with one of the 7 values in `bz-marital-status.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Common-law union	→	**Married**

8.10 Occupation

BZ_L2_OCCUPATION

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Occupation, profession or job title. A rare title (`Regional Operations Manager, Toledo`) is unique in the database.

HOW IT IS FOUND

COLUMN NAME BZ_L2_OCCUPATION — Path

80% `occupation` `profession` `job_?title` `designation` `job_?description_?title` `post_?title` `position_?title` `ocupaci[oó]n` `profesi[oó]n` `puesto`

50% `job` `position` `post` `trade` *(except when followed by `name`, `mark`, `licen[cs]e`)* `cargo` *(except when followed by `fijo`, `monto`, `valor`)*

HOW IT IS MASKED

Replaced by one of 40 common occupations.

`BZ_OCCUPATION` SECURE LOOKUP

Replaces the value with one of the 40 values in `bz-occupations.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Regional Operations Manager, Toledo`	→	**`Graphic designer`**

8.11 Employer

BZ_L2_EMPLOYER

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The name of the employer or workplace. In a small economy, an employer and a job title together often point at one person.

HOW IT IS FOUND

COLUMN NAME BZ_L2_EMPLOYER — Path

80% `employer(_?name)?` `name_?of_?employer` `employer_?business_?name` `company_?of_?employment` `workplace` `work_?place` `place_?of_?(work|employment)` `employed_?(at|by|with)` `current_?employer` `patrono` `empleador` `lugar_?(de_?)?trabajo`

HOW IT IS MASKED

Replaced by one of 25 fictitious employers.

`BZ_EMPLOYER` SECURE LOOKUP

Replaces the value with one of the 25 values in `bz-employers.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Belize Electricity Limited`	→	**`Southern Distributors Ltd.`**

8.12 Education

BZ_L2_EDUCATION

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

The highest level of education, in the terms of the Belizean system: primary to Standard 6, secondary to Form 4, sixth form or junior college, vocational, associate, bachelor's, master's, doctorate.

HOW IT IS FOUND

COLUMN NAME BZ_L2_EDUCATION — Path

80% `education(_?(level|attainment|status|completed))?` `educational_?(level|attainment)` `highest_?(level_?(of_?)?)?(education|qualification|grade)` `level_?of_?education` `qualification` `schooling` `grade_?completed` `escolaridad` `nivel_?(educativo|de_?estudios)`

VALUE FORMAT BZ_L2_EDUCATION — Values

PATTERN	STRENGTH	NOTES
One of 29 known values, ignoring case — None, Preschool, Primary incomplete, Primary Standard 6, Secondary incomplete, Secondary Form 4, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another of the 12 levels.

`BZ_EDUCATION` SECURE LOOKUP

Replaces the value with one of the 12 values in `bz-education.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Sixth form / junior college`	→	**`Secondary (Form 4)`**

8.13 School

BZ_L2_SCHOOL

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The name of the primary or high school, sixth form, junior college or university.

HOW IT IS FOUND

COLUMN NAME BZ_L2_SCHOOL — Path

75% `school(_?name)?` `name_?of_?school` `high_?school` `primary_?school` `secondary_?school` `sixth_?form` `junior_?college` `college(_?name)?` `university(_?name)?` `institution_?attended` `alma_?mater` `escuela` `colegio` `universidad`

HOW IT IS MASKED

Replaced by one of 15 fictitious schools.

`BZ_SCHOOL` SECURE LOOKUP

Replaces the value with one of the 15 values in `bz-schools.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
St. John's College	→	**Maya Mountain Junior College**

8.14 Children and dependants

BZ_L2_DEPENDANTS

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of children, dependants or household members.

HOW IT IS FOUND

> COLUMN NAME BZ_L2_DEPENDANTS — Path
>
> 80% `dependants?` `dependents?` `no_?of_?(children|dependants|dependents|kids)` `num(ber)?_?(of_?)?(children|dependants|dependents|kids)` `children` `household_?(size|members)` `persons_?in_?household` `hijos` `n(o|um|ro)_?hijos` `dependientes`

> DATA TYPE BZ_L2_DEPENDANTS — Type
>
> Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

Capped at 5: large households are rare, and a rare count identifies.

`BZ_CAPPED_COUNT` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 9

Sensitive personal data

The categories of section 2 that are not health, financial or criminal data — which have groups of their own: racial or ethnic origin, political opinions, religious and similar beliefs, membership of a political body, trade union membership, genetic and biometric data, sexual orientation and sexual life — and, beyond the list, the language a person speaks and gender identity. Categorical columns keep their shape: a yes/no flag stays a flag, a numeric code gets other digits and any other value is replaced by one from its category's list. Where the values share no vocabulary, they are suppressed to `Not stated`.

9.1 Ethnic origin

BZ_L3_ETHNICITY

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Ethnic group in the terms of the 2022 census — Mestizo/Hispanic/Latino (51.7%), Creole (25.2%), Maya (Q'eqchi', Mopan, Yucatec; 9.8%), Garifuna (4.0%), East Indian, Mennonite, Chinese and others —, often as a yes/no flag for indigenous status.

HOW IT IS FOUND

COLUMN NAME — BZ_L3_ETHNICITY – Path

90% `ethnic(ity|_?group|_?origin|_?background|_?identity)?` `race` `racial_?(origin|group|background)` `indigenous(_?(status|group|people|peoples))?` `is_?indigenous` `maya_?(group|people)` `etnia` `grupo_?etnico` `origen_?etnico` `raza`

VALUE FORMAT — BZ_L3_ETHNICITY – Values

PATTERN	STRENGTH	NOTES
One of 42 known values, ignoring case — Mestizo Hispanic Latino, Creole, Maya Ketchi, Maya Mopan, Maya Yucatec, Garifuna, …	90%	
One of 8 known values, ignoring case — y, n, yes, no, s, sí, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A flag stays a flag in its vocabulary, a code gets other digits and any other value is replaced by one from the census list.

`BZ_ETHNICITY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_ETHNICITY_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_ETHNICITY_LIST` SECURE LOOKUP

Replaces the value with one of the 14 values in `bz-ethnic-groups.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Garinagu	→	**Not stated**
Y	→	**N**

9.2 Language

BZ_L3_LANGUAGE

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The language a person speaks or grew up with: English, Spanish, Kriol, Maya Q'eqchi', Mopan or Yucatec, Garifuna, German (Plautdietsch) and others. Not in the section 2 list, but it reveals ethnic origin as directly as the ethnic group column.

HOW IT IS FOUND

COLUMN NAME BZ_L3_LANGUAGE – Path

90%	`mother_?tongue` `first_?language` `native_?language` `home_?language` `language_?(spoken|at_?home|spoken_?at_?home|first|native|mother)` `languages_?spoken` `primary_?language` `lengua(_?materna)?` `idioma_?(materno|nativo)`
55%	`language` `idioma`

VALUE FORMAT BZ_L3_LANGUAGE – Values

PATTERN	STRENGTH	NOTES
One of 29 known values, ignoring case — English, Spanish, Kriol, Maya Q eqchi, Maya Mopan, Maya Yucatec, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Like ethnic origin: flags and codes keep their shape, names are replaced by another language of the census list.

`BZ_LANGUAGE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_LANGUAGE_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_LANGUAGE_LIST` SECURE LOOKUP

Replaces the value with one of the 11 values in `bz-languages.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Garifuna	→	**Other**

9.3 Religion

BZ_L3_RELIGION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Religion or denomination: Roman Catholic, Pentecostal, Seventh-day Adventist, Anglican, Mennonite, Baptist, Methodist, Nazarene, Jehovah's Witness, Hindu, Muslim, Bahá'í, Rastafarian, none.

HOW IT IS FOUND

COLUMN NAME BZ_L3_RELIGION — Path

95% `religion[a-z_]*` `religious_?(affiliation|denomination|belief|beliefs|preference|group)` `denomination` `faith` `church(_?(name|affiliation|member|membership|attended))?` `creed` `congregation` `religi[oó]n` `credo` `iglesia`

VALUE FORMAT BZ_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 48 known values, ignoring case — Roman Catholic, Pentecostal, Seventh-day Adventist, Anglican, Mennonite, Baptist, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`BZ_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_RELIGION_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_RELIGION_LIST` SECURE LOOKUP

Replaces the value with one of the 19 values in `bz-religions.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Salvation Army	→	**Church of God**

9.4 Beliefs of a similar nature

BZ_L3_BELIEF

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Philosophical or moral convictions, conscientious objection and other beliefs of a similar nature to religious ones.

HOW IT IS FOUND

COLUMN NAME BZ_L3_BELIEF – Path

90% `beliefs?` `philosophical_?(beliefs?|convictions?)` `conscientious_?objection` `conscientious_?objector` `moral_?(beliefs?|convictions?)` `personal_?convictions?` `worldview` `creencias?_?(filosoficas?|morales?|personales)` `convicci[oó]n(es)?` `objecion_?(de_?)?conciencia`

HOW IT IS MASKED

Suppressed to `Not stated`.

`BZ_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_SUPPRESS` SECURE LOOKUP

Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Refuses blood transfusions`	→	**`Not stated`**

9.5 Political opinion

`BZ_L3_POLITICAL_OPINION`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Ideology, voting intention, party preference in surveys.

HOW IT IS FOUND

COLUMN NAME `BZ_L3_POLITICAL_OPINION` — Path

90% `political_?(opinion|opinions|view|views|orientation|leaning|leanings|preference|ideology)` `ideology` `voting_?intention` `vote_?intention` `intended_?vote` `party_?preference` `preferred_?party` `swing_?voter` `opini[oó]n_?pol[ií]tica` `ideolog[ií]a` `intencion_?(de_?)?voto`

VALUE FORMAT `BZ_L3_POLITICAL_OPINION` — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Left, Centre-left, Centre, Centre-right, Right, No preference, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another position on a generic scale.

`BZ_POLITICAL_OPINION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_POLITICAL_OPINION_LIST`.

> `BZ_FLAG` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_POLITICAL_OPINION_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `bz-political-opinions.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Centre-right	→	**Right**

9.6 Membership of a political body

BZ_L3_POLITICAL_MEMBERSHIP

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The party or political body a person belongs to or supports — a category section 2 names on its own, apart from political opinions.

HOW IT IS FOUND

COLUMN NAME BZ_L3_POLITICAL_MEMBERSHIP – Path

95% `political_?(party|body|membership|affiliation|group)` `party_?(membership|member|affiliation|card|branch|division|supporter)` `member_?of_?(party|political_?(party|body))` `partido(_?pol[ií]tico)?` `afiliaci[oó]n_?pol[ií]tica` `militancia` `militante`

50% `party` *(except when followed by list E6)*

VALUE FORMAT BZ_L3_POLITICAL_MEMBERSHIP – Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — People s United Party, United Democratic Party, Belize Progressive Party, Belize Justice Movement, People s Democratic Movement, People s National Party, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the parties of the 2025 general election — People's United Party, United Democratic Party, Belize Progressive Party, Belize Justice Movement, People's Democratic Movement, People's National Party — or by independent or no party.

`BZ_POLITICAL_PARTY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_POLITICAL_PARTY_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_POLITICAL_PARTY_LIST` **SECURE LOOKUP**

Replaces the value with one of the 8 values in `bz-political-parties.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`United Democratic Party`	→	**`United Democratic Party`**

9.7 Trade union membership

`BZ_L3_TRADE_UNION`

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

Membership of a trade union or staff association, union dues, bargaining unit: BNTU, PSU, Christian Workers' Union and the other affiliates of the NTUCB.

HOW IT IS FOUND

COLUMN NAME `BZ_L3_TRADE_UNION — Path`

95% `trade_?union(_?(member|membership|name|dues))?` `union_?(member|membership|affiliation|name|dues|fees|code|branch|local|representative)` `unioni[sz]ed` `labou?r_?union` `bargaining_?unit` `collective_?(agreement|bargaining)` `staff_?association` `sindicato[a-z_]*` `sindical(izado)?` `afiliaci[oó]n_?sindical` `cuota_?sindical`

VALUE FORMAT `BZ_L3_TRADE_UNION — Values`

PATTERN	STRENGTH	NOTES
One of 23 known values, ignoring case — BNTU, PSU, NTUCB, CWU, BWU, BEWU, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Not stated`.

`BZ_SUPPRESSED_CATEGORY` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

`BZ_FLAG` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_SUPPRESS` SECURE LOOKUP

Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
BNTU	→	**Not stated**

9.8 Genetic data

BZ_L3_GENETIC

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Genetic profiles, sequences, mutations, karyotypes, paternity tests — in the Act's words, data on inherited or acquired genetic characteristics resulting from the analysis of a biological sample.

HOW IT IS FOUND

COLUMN NAME BZ_L3_GENETIC – Path

90% `dna` `genetic[a-z_]*` `genome` `genotyp[a-z_]*` `gene_?(test|result|marker|panel)` `genetic_?(test|marker|profile|result)` `mutation` `brca[12]?` `karyotype` `paternity_?test` `snp` `haplotype` `newborn_?screening` `adn` `gen[eé]tic[oa]`

VALUE FORMAT BZ_L3_GENETIC – Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character becomes `X`.

`BZ_REDACT` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positive	→	**XXXXXXXXXXXXXX**

9.9 Biometric data

BZ_L3_BIOMETRIC

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

Fingerprint, face, iris, palm or voice templates stored as text (hash, base64). The Social Security Board captures fingerprints and photographs when it issues a card.

HOW IT IS FOUND

COLUMN NAME BZ_L3_BIOMETRIC — Path

90% `fingerprints?` `finger_?prints?` `thumb_?prints?` `biometric[a-z_]*` `face_?(template|encoding|id|print|hash)` `facial_?(template|recognition|id|image_?hash)` `iris(_?(scan|template|code))?` `retina(_?scan)?` `voice_?(print|template)` `palm_?print` `signature_?(image|biometric|capture|pad)` `minutiae` `huellas?(_?dactilar(es)?)?` `biometri[a-z_]*`

DATA TYPE BZ_L3_BIOMETRIC — Type

Accepts text; any other type rules the data class out.

HOW IT IS MASKED

Every character becomes `X`. Binary columns are out of reach: see *Limits*.

`BZ_REDACT` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

9.10 Sexual orientation

BZ_L3_SEXUAL_ORIENTATION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Sexual orientation, which section 2 names explicitly.

HOW IT IS FOUND

COLUMN NAME BZ_L3_SEXUAL_ORIENTATION — Path

95% `sexual_?(orientation|preference)` `orientation_?sexual` `orient_?sexual` `orientaci[oó]n_?sexual` `preferencia_?sexual`

VALUE FORMAT BZ_L3_SEXUAL_ORIENTATION — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Heterosexual, Gay, Lesbian, Bisexual, Pansexual, Asexual, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`BZ_SEXUAL_ORIENTATION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SEXUAL_ORIENTATION_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_SEXUAL_ORIENTATION_LIST` SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-sexual-orientations.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Bisexual	→	**Other**

9.11 Sexual life

BZ_L3_SEXUAL_LIFE

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behaviour and history.

HOW IT IS FOUND

COLUMN NAME BZ_L3_SEXUAL_LIFE — Path

90% `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|history|partners?|practices?)` `sexually_?active` `number_?of_?sexual_?partners` `age_?(at_?)?first_?(sex|intercourse)` `vida_?sexual` `conducta_?sexual` `actividad_?sexual`

HOW IT IS MASKED

Suppressed to `Not stated`.

`BZ_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_SUPPRESS` SECURE LOOKUP

Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Active	→	**Not stated**

9.12 Gender identity

BZ_L3_GENDER_IDENTITY

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Gender identity and pronouns. Not in the section 2 list; treated as sensitive because it exposes people to the same discrimination.

HOW IT IS FOUND

COLUMN NAME BZ_L3_GENDER_IDENTITY — Path

95% `gender_?(identity|expression)` `preferred_?pronouns?` `pronouns?` `transgender` `trans_?status` `identidad_?(de_?)?g[eé]nero` `g[eé]nero_?autopercibido`

VALUE FORMAT BZ_L3_GENDER_IDENTITY — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Woman, Man, Trans woman, Trans man, Non-binary, Gender fluid, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`BZ_GENDER_IDENTITY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_GENDER_IDENTITY_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_GENDER_IDENTITY_LIST` SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-gender-identities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trans man	→	**Gender fluid**

PART 10

Health records

Section 2 does not list health among the sensitive data, but the Act gives health records a place of their own: a health record is information on a person's physical or mental condition made by a health care professional (s. 2), medical purposes are a condition of their own for processing sensitive data (s. 10), and a small business providing health services is never exempt (s. 3). A diagnosis, an antiretroviral or a pregnancy exposes a person at least as much as the listed categories, and the policy treats them the same way.

10.1 Health identifier

BZ_HEALTH_ID

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The number of the Belize Health Information System card required at public health facilities, National Health Insurance numbers, medical record, admission, prescription and sick-leave certificate numbers.

HOW IT IS FOUND

COLUMN NAME — BZ_HEALTH_ID – Path

85%

```
bhis(_?(no|num|number|id|card))?  nhi(_?(no|num|number|id|card|member_?(no|id)))?  medical_?record(_?(no|num|number))?  mrn  patient_?(id|no|num|number)  chart_?(no|num|number)  health_?(record|card|id)(_?(no|num|number))?  hospital_?(no|num|number)  admission_?(no|num|number)  prescription_?(no|num|number)  sick_?(note|leave|certificate)_?(no|num|number)  medical_?certificate_?(no|num|number)  expediente_?cl[ií]nico  historia_?cl[ií]nica
```

55%

```
chart  admission  episode
```

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BHIS–2024–00123	→	**BSED–7715–93610**

10.2 Diagnosis

BZ_HEALTH_DIAGNOSIS

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Diagnoses, as ICD-10 codes (`F32.9` , `B20`) or text, and medical history, allergies and chronic conditions.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_DIAGNOSIS – Path

85% `diagnos(is|es|tic)[a-z_]*` `dx` `icd_?(10|11)?(_?code)?` `medical_?(condition|history|problem|diagnosis)` `health_?(condition|problem)` `chronic_?(condition|disease|illness)` `illness(es)?` `disease[a-z_]*` `comorbidit(y|ies)` `allerg(y|ies)` `cause_?of_?(death|admission|illness|injury|sick_?leave)` `reason_?for_?(visit|admission|consultation|sick_?leave)` `presenting_?complaint` `chief_?complaint` `pre_?existing_?conditions?` `diagn[oó]stico[a-z_]*` `cie_?10` `enfermedad(es)?`

VALUE FORMAT BZ_HEALTH_DIAGNOSIS – Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

An ICD-10 code is replaced by another common code of the same format, with or without a decimal; text, by a common diagnosis. The real diagnosis does not survive.

`BZ_DIAGNOSIS` **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `BZ_DIAGNOSIS_TEXT`.

> `BZ_ICD10_DECIMAL` **SECURE LOOKUP**
>
> Replaces the value with one of the 33 values in `bz-icd10-decimal.txt`, chosen by a keyed hash.
>
> `BZ_ICD10` **SECURE LOOKUP**
>
> Replaces the value with one of the 37 values in `bz-icd10.txt`, chosen by a keyed hash.
>
> `BZ_FLAG` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_DIAGNOSIS_TEXT` **SECURE LOOKUP**
>
> Replaces the value with one of the 30 values in `bz-diagnoses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F32.9	→	**J02.9**
Major depression	→	**Obesity**

10.3 Medication

BZ_HEALTH_MEDICATION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Medications and active ingredients. Some reveal the diagnosis: an antiretroviral, an antipsychotic.

HOW IT IS FOUND

COLUMN NAME — BZ_HEALTH_MEDICATION — Path

85%

`medications?` `medicines?` `drugs?_?(name|prescribed)` `prescribed_?(drugs?|medications?)` `prescription_?(drug|medication|item)s?` `active_?ingredient` `dosage` `treatment_?(drug|medication)` `medicamentos?` `f[aá]rmacos?` `receta`

VALUE FORMAT — BZ_HEALTH_MEDICATION — Values

PATTERN	STRENGTH	NOTES
One of 51 known values, ignoring case — Paracetamol, Ibuprofen, Naproxen, Diclofenac, Metformin, Glibenclamide, …	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by one of 26 common medications.

`BZ_MEDICATION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_MEDICATION_LIST`.

> `BZ_FLAG` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_MEDICATION_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 26 values in `bz-medications.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Sertraline 50 mg`	→	**`Folic acid`**

10.4 Clinical text

BZ_HEALTH_CLINICAL_TEXT

COLUMN NAME | DATA TYPE | FREE TEXT REDACTION

WHAT IT IS

Progress notes, nursing notes, discharge summaries, triage notes and treatment plans.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_CLINICAL_TEXT – Path

85% `clinical_?notes?` `progress_?notes?` `nurs(e|ing)_?notes?` `doctors?_?notes?` `physician_?notes?` `medical_?notes?` `discharge_?(summary|notes?)` `clinical_?summary` `history_?of_?present(ing)?_?illness` `hpi` `physical_?exam(ination)?` `assessment_?(and_?)?plan` `treatment_?plan` `care_?plan` `triage_?notes?` `soap_?notes?` `anamnesis` `evoluci[oó]n(_?m[eé]dica)?` `nota_?m[eé]dica` `epicrisis`

DATA TYPE BZ_HEALTH_CLINICAL_TEXT – Type

Accepts text (length 30 or more); any other type rules the data class out.

HOW IT IS MASKED

Free Text Redaction, as for free text: identity numbers, contact details and names are redacted. The clinical content stays; if it must go too, assign the column to a suppression data class.

`BZ_FREE_TEXT` FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATA]`, and the 858 terms of `bz-text-names.txt` with `[NAME]`.

EXAMPLES

VALUE		MASKED
`Patient Gillett, SSN 000123456, seen for headache.`	→	**`Patient [NAME], SSN [DATA], seen for headache.`**

10.5 Test result

BZ_HEALTH_TEST_RESULT

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Laboratory and imaging results: HIV status, viral load, blood sugar, pregnancy or drug tests.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_TEST_RESULT – Path

80% `lab_?(result|test|value)s?` `test_?results?` `laboratory_?(result|test)s?` `hiv(_?(status|test|result))?` `viral_?load` `cd4(_?count)?` `blood_?(sugar|glucose|pressure)` `glucose` `hba1c` `cholesterol` `bmi` `pregnancy_?test` `drug_?(test|screen)` `covid_?(test|result)` `pcr_?result` `pap_?(smear|test)(_?result)?` `mammogram_?result` `x_?ray_?result` `resultado_?(examen|laboratorio|prueba)`

50% `result` `test`

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Reactive	→	**Muikyaya**

10.6 Blood group

BZ_HEALTH_BLOOD_GROUP

COLUMN NAME · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

ABO group and Rh factor.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_BLOOD_GROUP — Path

90% `blood_?(type|group)` `abo(_?rh)?` `rh_?factor` `rh` `grupo_?sangu[ií]neo` `tipo_?(de_?)?sangre`

VALUE FORMAT BZ_HEALTH_BLOOD_GROUP — Values

PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another of the eight groups.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with Delphix and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

10.7 Disability

BZ_HEALTH_DISABILITY

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Disability or functional limitation, in the data classes the 2022 census asks about: seeing, hearing, walking, remembering or concentrating, self-care, communicating.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_DISABILITY — Path

90% `disabilit(y|ies)[a-z_]*` `disabled` `impairments?` `handicap(ped)?` `special_?needs` `functional_?limitations?` `difficulty_?(seeing|hearing|walking|remembering|concentrating|self_?care|communicating)` `invalidity(_?(status|grade))?` `discapacidad[a-z_]*`

VALUE FORMAT BZ_HEALTH_DISABILITY — Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — Seeing, Hearing, Walking or climbing steps, Remembering or concentrating, Self-care, Communicating, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`BZ_DISABILITY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_DISABILITY_LIST`.

> `BZ_FLAG` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_DISABILITY_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `bz-disabilities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Severe psychosocial disability`	→	**`Communicating`**

10.8 Sexual and reproductive health

BZ_HEALTH_REPRODUCTIVE

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, weeks of gestation, miscarriages and abortions, contraception, fertility, antenatal care, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_REPRODUCTIVE – Path

90% `pregnan(t|cy)[a-z_]*` `gestation(al)?(_?age)?` `weeks_?(of_?)?(pregnancy|gestation)` `lmp` `last_?menstrual_?period` `abortions?` `miscarriages?` `contracepti(on|ve)[a-z_]*` `family_?planning(_?method)?` `fertility` `infertility` `ivf` `gravida` `antenatal` `prenatal` `postnatal` `postpartum` `sti` `sexually_?transmitted(_?infection)?` `embarazo` `aborto` `anticonceptivos?` `planificaci[oó]n_?familiar`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Not stated`.

`BZ_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

> `BZ_FLAG` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_SUPPRESS` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`12 weeks pregnant`	→	**`Not stated`**
`Y`	→	**`N`**

10.9 Mental health and addiction

BZ_HEALTH_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Mental disorders, suicide attempts and self-harm, substance use and rehabilitation.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_MENTAL — Path

90% `mental_?(health|illness|disorder|condition)` `psychiatr[a-z_]*` `psycholog[a-z_]*` `depression` `anxiety` `suicid[a-z_]*` `self_?harm` `substance_?(use|abuse|misuse)` `alcohol(ism|_?use|_?abuse|_?dependence)` `drug_?(use|abuse|addiction|dependence)` `addiction[a-z_]*` `rehab(ilitation)?_?(programme|program|centre|center|status)` `salud_?mental` `trastorno[a-z_]*` `adicci[oó]n(es)?`

HOW IT IS MASKED

Suppressed to `Not stated`.

`BZ_SUPPRESSED_CATEGORY` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

> `BZ_FLAG` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_SUPPRESS` **SECURE LOOKUP**
>
> Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Bipolar disorder`	→	**`Not stated`**

PART 11

Financial record or position

What makes the Belizean list unusual: a data subject's **financial record or position** is sensitive personal data (s. 2 (i)), with the same prohibition as religion or ethnic origin. It goes well beyond a bank account — a credit reference from the credit bureau the Central Bank licensed under the Credit Reporting Act, 2023, a loan in arrears, a salary, a social security benefit, a BOOST transfer or a poverty status. A template made for other laws treats most of these as ordinary data. Categories are replaced within their own notation; amounts are mapped into a plausible range unrelated to the real value.

11.1 Credit reference

BZ_FIN_CREDIT_REFERENCE

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Credit scores and reports, days past due, arrears, loan classification, written-off and non-performing loans. Belize's credit reporting system, run by a bureau the Central Bank licensed under the Credit Reporting Act, 2023, gathers them from banks and credit unions.

HOW IT IS FOUND

COLUMN NAME — BZ_FIN_CREDIT_REFERENCE – Path

90% `credit_?(score|rating|history|report|status|bureau|reference|risk|grade|standing)` `crif(_?(score|report|status))?` `delinquen(cy|t)(_?(status|days))?` `days_?(past_?due|in_?arrears|overdue)` `dpd` `arrears(_?(status|days))?` `past_?due(_?(days|status))?` `overdue_?(days|status)` `default_?(status|flag|indicator)` `defaulted` `written_?off` `write_?off(_?(status|flag))?` `collections?_?status` `bad_?debt` `loan_?(status|classification|grade)` `non_?performing` `npl` `morosidad` `score_?credit[oa]`

HOW IT IS MASKED

A score gets other digits, a flag stays a flag and any status is replaced by another credit status.

`BZ_CREDIT` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_CREDIT_STATUS`.

> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_FLAG` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CREDIT_STATUS` SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-credit-statuses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`90 days past due`	→	**`no credit history`**
`745`	→	**`471`**

11.2 Debt amount

`BZ_FIN_DEBT`

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Loan, mortgage and card balances, amounts in arrears, credit limits, instalments.

HOW IT IS FOUND

COLUMN NAME `BZ_FIN_DEBT – Path`

85% `loan_?(amount|balance|principal|outstanding)` `outstanding_?(balance|amount|debt|loan|principal)` `debt(_?(amount|total|balance))?` `amount_?(owed|due|outstanding|in_?arrears|overdue)` `balance_?(owed|outstanding|due)` `arrears_?amount` `credit_?limit` `mortgage_?(balance|amount)` `instal?lment(_?amount)?` `monthly_?(payment|repayment)` `saldo_?(deudor|prestamo|pr[eé]stamo)` `monto_?(deuda|prestamo)` `deuda`

DATA TYPE `BZ_FIN_DEBT – Type`

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
`8500`	→	**`5134`**

11.3 Salary and income

`BZ_FIN_INCOME`

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Salary and wages, insurable earnings, household income.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_INCOME – Path

85% `salary` `salaries` `wages?` `income[a-z_]*` `gross_?(pay|salary|income|earnings)` `net_?(pay|salary|income|earnings)` `(monthly|annual|weekly|fortnightly)_?(income|salary|earnings|pay|wage)` `earnings` `remuneration` `basic_?(pay|salary)` `insurable_?earnings` `household_?income` `take_?home_?pay` `salario` `sueldo` `ingresos?(_?[a-z]+)?`

DATA TYPE BZ_FIN_INCOME – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
2400	→	2459

11.4 Assets

BZ_FIN_ASSETS

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Property and land value, savings and account balances, fixed deposits, investments and credit union shares, net worth.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_ASSETS – Path

85% `net_?worth` `assets?_?(value|total)` `total_?assets` `property_?value` `land_?value` `market_?value` `appraised_?value` `valuation_?amount` `savings(_?balance)?` `account_?balance` `deposit_?balance` `fixed_?deposit(_?amount)?` `investment_?(balance|value|amount)` `share_?(balance|capital)` `patrimonio` `valor_?(catastral|propiedad|comercial)`

DATA TYPE BZ_FIN_ASSETS – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
185000	→	477515

11.5 Pension

BZ_FIN_PENSION

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

Retirement, invalidity and survivors' pension amounts, the non-contributory pension, gratuities and provident fund balances.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_PENSION – Path

90% `pension(_?(amount|payment|monthly|benefit_?amount|balance))?` `monthly_?pension` `retirement_?(pension|benefit|amount|balance)` `ncp_?(amount|payment)` `survivors?_?pension(_?amount)?` `invalidity_?pension(_?amount)?` `gratuity(_?amount)?` `provident_?fund(_?balance)?` `pensi[oó]n(_?monto)?` `jubilaci[oó]n(_?monto)?`

DATA TYPE BZ_FIN_PENSION – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
680	→	227

11.6 Social security benefit

BZ_FIN_SSB_BENEFIT

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The benefit a person claims or receives from the Social Security Board: sickness, maternity allowance or grant, employment injury, invalidity, survivors', retirement, funeral grant, non-contributory pension. Most of them also reveal a health event.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_SSB_BENEFIT – Path

90% `ssb_?(benefit|claim)(_?(type|status|category))?` `benefit_?(type|claim|category|name|code)` `claim_?type` `(sickness|maternity|funeral|invalidity|survivors?|employment_?injury|disablement)_?(benefit|allowance|grant|claim)` `social_?security_?(benefit|claim)(_?type)?` `tipo_?(de_?)?beneficio`

VALUE FORMAT BZ_FIN_SSB_BENEFIT — Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Sickness benefit, Maternity allowance, Maternity grant, Employment injury benefit, Invalidity pension, Survivors pension, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the benefit is replaced by another.

`BZ_SSB_BENEFIT` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SSB_BENEFIT_LIST`.

> `BZ_FLAG` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_SSB_BENEFIT_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `bz-ssb-benefits.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Maternity allowance`	→	**`Survivors' pension`**

11.7 Social programme

BZ_FIN_SOCIAL_PROGRAMME

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Beneficiaries of social assistance: BOOST cash transfers and the Food Assistance Programme of the Ministry of Human Development, the non-contributory pension, National Health Insurance. Being a beneficiary reveals poverty, old age or disability.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_SOCIAL_PROGRAMME – Path

90% `boost(_?(beneficiary|programme|program|member|recipient))?` `food_?(assistance|pantry)(_?(programme|program|beneficiary|recipient))?` `pantry_?(programme|program|beneficiary)` `social_?(programme|program|assistance|welfare|benefit|transfer)s?` `welfare_?(programme|program|recipient|status)` `cash_?transfer` `beneficiary_?of_?(programme|program)` `programme_?beneficiary` `ncp_?(beneficiary|recipient)` `non_?contributory_?pension_?(beneficiary|recipient)` `nhi_?(enrolled|registered|beneficiary|status)` `human_?development_?(programme|program|case)` `programa_?social`

VALUE FORMAT BZ_FIN_SOCIAL_PROGRAMME – Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — BOOST, Food Assistance Programme, Non-Contributory Pension Programme, National Health Insurance, Other programme, None, …	80%	
One of 8 known values, ignoring case — y, n, yes, no, s, sí, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the programme is replaced by another.

`BZ_SOCIAL_PROGRAMME` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SOCIAL_PROGRAMME_LIST`.

> `BZ_FLAG` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `BZ_FLAG_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.
> >
> > `BZ_FLAG_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.
>
> `BZ_CM_ALNUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `BZ_SOCIAL_PROGRAMME_LIST` **SECURE LOOKUP**
>
> Replaces the value with one of the 6 values in `bz-social-programmes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Pantry programme`	→	**`National Health Insurance`**

11.8 Poverty and socioeconomic status

BZ_FIN_POVERTY

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Poverty status (extremely poor, poor, vulnerable), income quintile or decile, means-test scores and vulnerability indexes.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_POVERTY — Path

90% `poverty(_?(status|level|line|index|score|category))?` `indigen(ce|t)(_?status)?` `socio_?economic_?(status|level|index|group|class|score)` `wealth_?(index|quintile)` `income_?(quintile|decile|bracket|band)` `quintile` `decile` `vulnerability_?(index|score)` `mpi` `means_?test(_?(score|result))?` `pobreza` `nivel_?socioecon[oó]mico` `quintil` `decil`

VALUE FORMAT BZ_FIN_POVERTY — Values

PATTERN	STRENGTH	NOTES
One of 9 known values, ignoring case — extremely poor, indigent, poor, not poor, vulnerable, non poor, …	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A quintile or decile becomes another number of the same range, with its prefix; a status, another from the list.

`BZ_POVERTY` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_POVERTY_STATUS`.

> `BZ_QUINTILE` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `bz-quintile.txt`, chosen by a keyed hash.
>
> `BZ_DECILE_HIGH` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `bz-decile-high.txt`, chosen by a keyed hash.
>
> `BZ_DECILE` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `bz-decile.txt`, chosen by a keyed hash.
>
> `BZ_POVERTY_STATUS` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `bz-poverty-statuses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Extremely poor`	→	**`Vulnerable`**
`Quintile 2`	→	**`Quintile 4`**

11.9 Housing tenure

BZ_FIN_HOUSING

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Whether the dwelling is owned, mortgaged, rented privately or from the government, rent free, leased or squatted, as the census asks.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_HOUSING – Path

95%	`housing_?(tenure|status|type|situation)` `dwelling_?(tenure|ownership|type)` `home_?ownership` `own_?or_?rent` `rent_?or_?own` `owns_?(home|house)` `squatt(er|ing)(_?status)?` `tenencia_?(de_?)?(la_?)?vivienda` `tipo_?(de_?)?vivienda`
55%	`tenure`

VALUE FORMAT BZ_FIN_HOUSING – Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Owned, Owned with mortgage, Rented private, Rented government, Rent free, Leased, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the tenure is replaced by another from the list.

`BZ_HOUSING` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_HOUSING_LIST`.

`BZ_FLAG` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_HOUSING_LIST` **SECURE LOOKUP**

Replaces the value with one of the 8 values in `bz-housing-tenure.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Family land`	→	**`Rent free`**

PART 12

Criminal record and proceedings

Section 2 makes sensitive both a criminal record and any proceedings for an offence committed or alleged — including their disposal and the sentence — so a charge that ended in acquittal is as protected as a conviction. Data on criminal convictions is processed only under the control of an official authority (s. 10(2)).

12.1 Criminal record and proceedings

BZ_PENAL_CRIMINAL_RECORD

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Criminal record, police record or clearance, convictions, offences, charges, arrests, remand, bail, verdicts and sentences — the record and the proceedings, whatever their outcome.

HOW IT IS FOUND

COLUMN NAME BZ_PENAL_CRIMINAL_RECORD — Path

95% `criminal_?(record|history|conviction|convictions|status|background|charges?|proceedings|case_?(status|outcome))` `police_?(record|certificate|clearance|report_?status)` `convictions?(_?(status|record|details))?` `convicted` `previous_?convictions` `offen[cs]es?(_?(type|committed|code|description|details))?` `charged_?with` `arrests?(_?(record|history))?` `sentence(_?(imposed|type|length|details))?` `incarcerat(ed|ion)` `imprisonment` `remand(ed)?(_?status)?` `bail(_?status)?` `probation(_?status)?` `parole` `verdict` `acquitt(al|ed)` `antecedentes_?penales` `record_?policial` `delitos?` `sentencia`

55% `court_?(outcome|disposal|decision|status)` `case_?(outcome|disposal)` `disposal`

HOW IT IS MASKED

A flag stays a flag; any other value becomes a generic status: no criminal record, has criminal record, charged, case dismissed, acquitted, convicted or not stated.

`BZ_CRIMINAL_RECORD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_CRIMINAL_RECORD_LIST`.

`BZ_FLAG` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

`BZ_FLAG_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

`BZ_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

`BZ_FLAG_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

`BZ_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_CRIMINAL_RECORD_LIST` SECURE LOOKUP

Replaces the value with one of the 7 values in `bz-criminal-record.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Convicted of burglary, 2019`	→	**Acquitted**

12.2 Case number

BZ_PENAL_CASE_NUMBER

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Court, indictment, charge sheet, police report and occurrence numbers: `C123/2023`, `456 of 2022`.

HOW IT IS FOUND

COLUMN NAME BZ_PENAL_CASE_NUMBER — Path

90% `court_?case_?(no|num|number)` `criminal_?case_?(no|num|number)` `indictment_?(no|num|number)` `charge_?sheet_?(no|num|number)` `police_?(report|occurrence|case)_?(no|num|number)` `occurrence_?(no|num|number)` `docket_?(no|num|number)` `claim_?no_?court` `inquest_?(no|number)` `n(o|um|ro|umero)_?(de_?)?causa` `expediente_?(judicial|penal)`

55% `case_?(no|num|number|ref|reference)`

VALUE FORMAT BZ_PENAL_CASE_NUMBER — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{1,3}\s?\d{1,5}/\d{4}`	50%	
`(?i)\d{1,6}\s+of\s+\d{4}`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`BZ_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`C123/2023`	→	**X275/5782**

13

Where people live: towns and villages

With the population by city, town and village of the 2022 Population and Housing Census and the location of each place, the policy knows the size, district and position of all 221 places the census counts.

- A **town or village** under 5,000 inhabitants becomes the nearest place of the same district with at least 5,000. Thirteen places reach that size: Belize City, San Pedro Town and Ladyville in Belize District; Belmopan, San Ignacio, Santa Elena and Benque Viejo del Carmen in Cayo; Corozal Town; Orange Walk Town and Trial Farm; Dangriga; Punta Gorda and Bella Vista in Toledo.
- The **district** stays: the smallest, Toledo, had 38,944 inhabitants.
- Distance is measured between the places' coordinates. Caye Caulker becomes San Pedro Town, Hopkins becomes Dangriga, Crooked Tree becomes Ladyville.
- Twenty-eight small places share their name with another place — there are four San Antonio and four Santa Cruz. A name is generalized only when every place bearing it is small; then it follows the largest of them, which may lie in another district. Santa Elena in Toledo keeps its name, because the Santa Elena of Cayo is a town, and so does the village of San Pedro in Corozal, because `San Pedro` is how San Pedro Town is written.
- Names are also recognized as they are commonly written: without *Town*, `Benque Viejo`, and the communities the census counts inside another one — `Mango Creek` is Independence, `San Lorenzo` is Orange Walk Town.

The result is always a real place, near the original, and every group of people who end up sharing a name holds at least 5,000 inhabitants. Names that are also given names or surnames, and the district names, are left out of the detection list, so that a surname column is not taken for villages.

14

Limits

- **Binary columns** — scans of the social security card or passport, fingerprint images, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **Electoral divisions stay.** The policy does not mask the 31 constituencies, whose names identify few people on their own but narrow a village down in combination. Where a column holds them next to a birth date and sex, generalize it to the district.
- **Identity numbers keep no check digit.** The social security number has no public one, and the TIN's is not published, so neither is recomputed; applications that validate a TIN check digit may reject masked values.
- **Company TINs are masked too.** They cannot be told apart from a person's.
- **Passport, permit and licence numbers** have no public format and are masked character by character.
- **Data Cleansing leaves unknown values as they are**: a village spelled in a way the list does not have passes unchanged.
- **Villages sharing a name** across districts are generalized by the largest of them, and may end up in another district than the district column says.
- **Free text** is redacted token by token: a phone written with spaces is not found, and a given name that is also a common word (`Angel`, `Iris`) is redacted wherever it appears.
- **Children** — the Act protects persons under 16. A birth date moves at most 60 days, so few people cross their 16th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-

Column Condition.

- **Addresses** are replaced as a whole line. Street, neighbourhood, village and district in separate columns are masked independently and no longer form a coherent address.
- **Plates and VINs** keep their format, but not the VIN check digit.

15

Verification

Before publication the policy was checked outside Delphix:

- Every classifier configuration was reviewed against what Delphix accepts.
- Discovery was simulated on 141 columns with the whole policy at its assignment threshold — well named, badly named, and 32 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The table that generalizes towns and villages was audited for all 221 places.
- The algorithms, run with the Delphix algorithm plugin, masked 145 sample values and 198 placeholders such as `N/A`, checking each output against its vocabulary, and 150 social security numbers for collisions. Each of the 90 algorithms also masked its own sample input.

Every column was assigned as expected and every value masked as expected. Before using the policy on real data, run a discovery job and a masking job on a representative copy.

16

Sources

- Data Protection Act, 2021 — Act No. 45 of 2021, National Assembly of Belize, printed by the Government Printer (copy published by the Belize Companies and Corporate Affairs Registry).
- Population by district, city, town and village; ethnic group; languages spoken; religious affiliation; marital and union status; country of birth; dwelling ownership — 2022 Population and Housing Census, Statistical Institute of Belize.
- Coordinates of populated places — GeoNames (CC BY 4.0).
- Social security card and number, benefits — Social Security Board. Taxpayer identification number — Belize Tax Service, in the OECD register of tax identification numbers.
- Voter identification card — Elections and Boundaries Department. Parties of the 2025 general election — Elections and Boundaries Department.
- Credit Reporting System and Credit Reporting Act, 2023 — Central Bank of Belize. BOOST and the Food Assistance Programme — Ministry of Human Development, Families and Indigenous Peoples' Affairs.
- Belize Health Information System card — Ministry of Health and Wellness. Trade unions — National Trade Union Congress of Belize.
- Frequency of surnames and given names — Forebears. Telephone numbering — national numbering plan. Licence plates — Department of Transport.

APPENDIX A

Algorithms

Every algorithm of the policy in alphabetical order, with its configuration. The one a data class names is the top of its tree; the others are building blocks.

BZ_ADDRESS SECURE LOOKUP

Replaces the value with one of the 3,000 values in `bz-addresses.txt`, chosen by a keyed hash.

Used by: `BZ_L1_ADDRESS`

CONFIGURATION

lookupFile	`bz-addresses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_AGE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_AGE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`
`(0*?)(?:([1-9])(\d)(\.\d+))`	keep · keep · `BZ_CM_ALNUM` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `BZ_CM_ALNUM`
`(0*?)(?:(\d))`	keep · `BZ_CM_ALNUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_BIRTH_DATE DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `BZ_L2_BIRTH_DATE`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

BZ_CAPPED_COUNT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_DEPENDANTS`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CARD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L1_PAYMENT_CARD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `BZ_L1_SOCIAL_SECURITY_NUMBER`, `BZ_L1_TIN`, `BZ_L1_PASSPORT`, `BZ_L1_VOTER_ID`, `BZ_L1_DRIVERS_LICENCE`, `BZ_L1_IMMIGRATION_DOCUMENT`, `BZ_L1_VITAL_RECORD`, `BZ_L1_ADDRESS_DETAIL`, `BZ_L1_BANK_ACCOUNT`, `BZ_L1_VIN`, `BZ_L1_CONTRACT_NUMBER`, `BZ_L1_USERNAME`, `BZ_HEALTH_ID`, `BZ_HEALTH_TEST_RESULT`, `BZ_PENAL_CASE_NUMBER`, `BZ_SUPPRESSED_CATEGORY`, `BZ_GIVEN_NAMES`, `BZ_SURNAMES`, `BZ_FULL_NAME`, `BZ_EMAIL`, `BZ_PHONE`, `BZ_PLATE`, `BZ_PARCEL`, `BZ_COORDINATE`, `BZ_YEAR`, `BZ_AGE`, `BZ_ETHNICITY`, `BZ_LANGUAGE`, `BZ_RELIGION`, `BZ_POLITICAL_OPINION`, `BZ_POLITICAL_PARTY`, `BZ_SEXUAL_ORIENTATION`, `BZ_GENDER_IDENTITY`, `BZ_MEDICATION`, `BZ_DISABILITY`, `BZ_CREDIT`, `BZ_SSB_BENEFIT`, `BZ_SOCIAL_PROGRAMME`, `BZ_HOUSING`, `BZ_CRIMINAL_RECORD`

CONFIGURATION

characterGroups	`0123456789` `AEIOU` `BCDFGHJKLMNPQRSTVWXYZ` `aeiou` `bcdfghjklmnpqrstvwxyz` `ÁÉÍÓÚÜ` `áéíóúü`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

BZ_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `BZ_L1_DEVICE_ID`, `BZ_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

BZ_COORDINATE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L1_GEOLOCATION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)`	keep · `BZ_CM_ALNUM` · keep · `BZ_CM_ALNUM`
`(-?\d{1,3}\.\d)(\d+)`	keep · `BZ_CM_ALNUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CREDIT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_CREDIT_STATUS`.

Used by: `BZ_FIN_CREDIT_REFERENCE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2,3}))`	keep · `BZ_CM_ALNUM`
`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
otherwise	`BZ_CREDIT_STATUS`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CREDIT_STATUS SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-credit-statuses.txt`, chosen by a keyed hash.

Used by: `BZ_CREDIT`

CONFIGURATION

lookupFile	`bz-credit-statuses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_CRIMINAL_RECORD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_CRIMINAL_RECORD_LIST`.

Used by: `BZ_PENAL_CRIMINAL_RECORD`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_CRIMINAL_RECORD_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CRIMINAL_RECORD_LIST SECURE LOOKUP

Replaces the value with one of the 7 values in `bz-criminal-record.txt`, chosen by a keyed hash.

Used by: `BZ_CRIMINAL_RECORD`

CONFIGURATION

lookupFile	`bz-criminal-record.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DECILE SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-decile.txt`, chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	`bz-decile.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DECILE_HIGH SECURE LOOKUP

Replaces the value with one of the 5 values in `bz-decile-high.txt`, chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	`bz-decile-high.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DIAGNOSIS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `BZ_DIAGNOSIS_TEXT`.

Used by: `BZ_HEALTH_DIAGNOSIS`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`BZ_ICD10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3})`	`BZ_ICD10`
`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
otherwise	`BZ_DIAGNOSIS_TEXT`

CONFIGURATION

trimInput	yes

requireMask	no

BZ_DIAGNOSIS_TEXT SECURE LOOKUP

Replaces the value with one of the 30 values in `bz-diagnoses.txt`, chosen by a keyed hash.

Used by: `BZ_DIAGNOSIS`

CONFIGURATION

lookupFile	`bz-diagnoses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DISABILITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_DISABILITY_LIST`.

Used by: `BZ_HEALTH_DISABILITY`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_DISABILITY_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_DISABILITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-disabilities.txt`, chosen by a keyed hash.

Used by: `BZ_DISABILITY`

CONFIGURATION

lookupFile	`bz-disabilities.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_EDUCATION SECURE LOOKUP

Replaces the value with one of the 12 values in `bz-education.txt`, chosen by a keyed hash.

Used by: `BZ_L2_EDUCATION`

CONFIGURATION

lookupFile	`bz-education.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_EMAIL`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24})`	`BZ_CM_ALNUM` · `BZ_CM_ALNUM` · replace with `test`
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_EMPLOYER SECURE LOOKUP

Replaces the value with one of the 25 values in `bz-employers.txt`, chosen by a keyed hash.

Used by: `BZ_L2_EMPLOYER`

CONFIGURATION

lookupFile	`bz-employers.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_ETHNICITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_ETHNICITY_LIST`.

Used by: `BZ_L3_ETHNICITY`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_ETHNICITY_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_ETHNICITY_LIST SECURE LOOKUP

Replaces the value with one of the 14 values in `bz-ethnic-groups.txt`, chosen by a keyed hash.

Used by: `BZ_ETHNICITY`

CONFIGURATION

lookupFile	`bz-ethnic-groups.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_EVENT_DATE DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `BZ_L2_EVENT_DATE`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_SUPPRESSED_CATEGORY`, `BZ_ETHNICITY`, `BZ_LANGUAGE`, `BZ_RELIGION`, `BZ_POLITICAL_OPINION`, `BZ_POLITICAL_PARTY`, `BZ_SEXUAL_ORIENTATION`, `BZ_GENDER_IDENTITY`, `BZ_DIAGNOSIS`, `BZ_MEDICATION`, `BZ_DISABILITY`, `BZ_CREDIT`, `BZ_SSB_BENEFIT`, `BZ_SOCIAL_PROGRAMME`, `BZ_HOUSING`, `BZ_CRIMINAL_RECORD`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no)`	`BZ_FLAG_YES_NO`
`(?i)(s[ií])`	`BZ_FLAG_SI_NO`
`(?i)(true|false)`	`BZ_FLAG_TRUE_FALSE`
`(?i)([yn])`	`BZ_FLAG_Y_N`
`(?i)(s)`	`BZ_FLAG_S_N`
`([01])`	`BZ_FLAG_0_1`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	`bz-flag-0-1.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	`bz-flag-s-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	`bz-flag-si-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	`bz-flag-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	`bz-flag-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	`bz-flag-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FREE_TEXT FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATA]`, and the 858 terms of `bz-text-names.txt` with `[NAME]`.

Used by: `BZ_L1_FREE_TEXT`, `BZ_HEALTH_CLINICAL_TEXT`

PATTERNS, TRIED IN ORDER

`(?<![\d\-])\d{3}-\d{3}-\d{3}(?![\d\-])`
`(?<!\d)\d{9}(?!\d)`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<![\d\-])(\+?501-?)?[2-8]\d{2}-\d{4}(?![\d\-])`
`(?<!\d)(\+?501)?[2-8]\d{6}(?!\d)`
`(?<!\d)\d{13,19}(?!\d)`
`(?<![A-Za-z])(BMP|CZL|TOL|BZ|BC|CY|OW|SC|SP|SI|SE|PG|DG)-?[A-Z]?-?\d{3,5}(?![A-Za-z\d])`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATA]`
lookupFile	`bz-text-names.txt`
lookupFileRedactValue	`[NAME]`
isDenyList	yes

BZ_FULL_NAME REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_FULL_NAME`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`BZ_SURNAMES` · `BZ_GIVEN_NAMES`
`(\S+)`	`BZ_GIVEN_NAME`
`(\S+)\s+(\S+)`	`BZ_GIVEN_NAME` · `BZ_SURNAME`
`(\S+)(\s+)([A-Za-z]\.?)(\s+)(\S+)`	`BZ_GIVEN_NAME` · keep · keep · keep · `BZ_SURNAME`
`(\S+)\s+(\S+)\s+(\S+)`	`BZ_GIVEN_NAME` · `BZ_GIVEN_NAME` · `BZ_SURNAME`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`BZ_GIVEN_NAME` · `BZ_GIVEN_NAME` · `BZ_SURNAME` · `BZ_SURNAME`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`BZ_GIVEN_NAME` · `BZ_GIVEN_NAME` · `BZ_GIVEN_NAME` · `BZ_SURNAME` · `BZ_SURNAME`
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_GENDER_IDENTITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_GENDER_IDENTITY_LIST`.

Used by: `BZ_L3_GENDER_IDENTITY`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_GENDER_IDENTITY_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_GENDER_IDENTITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-gender-identities.txt`, chosen by a keyed hash.

Used by: `BZ_GENDER_IDENTITY`

CONFIGURATION

lookupFile	`bz-gender-identities.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_GIVEN_NAME NAME

Replaces the name with one of the 208 names in `bz-given-names.txt`.

Used by: `BZ_GIVEN_NAMES`, `BZ_FULL_NAME`

CONFIGURATION

lookupFile	`bz-given-names.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

BZ_GIVEN_NAMES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_GIVEN_NAME`, `BZ_FULL_NAME`

PATTERNS, TRIED IN ORDER

`(\S+)`	`BZ_GIVEN_NAME`
`(\S+)\s+(\S+)`	`BZ_GIVEN_NAME` · `BZ_GIVEN_NAME`
`(\S+)\s+(\S+)\s+(\S+)`	`BZ_GIVEN_NAME` · `BZ_GIVEN_NAME` · `BZ_GIVEN_NAME`
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes

requireMask	no

BZ_HOUSING REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_HOUSING_LIST`.

Used by: `BZ_FIN_HOUSING`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_HOUSING_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_HOUSING_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-housing-tenure.txt`, chosen by a keyed hash.

Used by: `BZ_HOUSING`

CONFIGURATION

lookupFile	`bz-housing-tenure.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_ICD10 SECURE LOOKUP

Replaces the value with one of the 37 values in `bz-icd10.txt`, chosen by a keyed hash.

Used by: `BZ_DIAGNOSIS`

CONFIGURATION

lookupFile	`bz-icd10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_ICD10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `bz-icd10-decimal.txt`, chosen by a keyed hash.

Used by: `BZ_DIAGNOSIS`

CONFIGURATION

lookupFile	`bz-icd10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

BZ_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_HEX`.

Used by: `BZ_L1_IP_ADDRESS`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `BZ_OCTET` · `BZ_OCTET` · `BZ_OCTET` · `BZ_OCTET`
otherwise	`BZ_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_LANGUAGE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_LANGUAGE_LIST`.

Used by: `BZ_L3_LANGUAGE`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_LANGUAGE_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_LANGUAGE_LIST SECURE LOOKUP

Replaces the value with one of the 11 values in `bz-languages.txt`, chosen by a keyed hash.

Used by: `BZ_LANGUAGE`

CONFIGURATION

lookupFile	`bz-languages.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_MARITAL_STATUS SECURE LOOKUP

Replaces the value with one of the 7 values in `bz-marital-status.txt`, chosen by a keyed hash.

Used by: `BZ_L2_MARITAL_STATUS`

CONFIGURATION

lookupFile	`bz-marital-status.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

BZ_MEDICATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_MEDICATION_LIST`.

Used by: `BZ_HEALTH_MEDICATION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_MEDICATION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_MEDICATION_LIST SECURE LOOKUP

Replaces the value with one of the 26 values in `bz-medications.txt`, chosen by a keyed hash.

Used by: `BZ_MEDICATION`

CONFIGURATION

lookupFile	`bz-medications.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_NATIONALITY SECURE LOOKUP

Replaces the value with one of the 16 values in `bz-nationalities.txt`, chosen by a keyed hash.

Used by: `BZ_L2_NATIONALITY`

CONFIGURATION

lookupFile	`bz-nationalities.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_NEIGHBOURHOOD SECURE LOOKUP

Replaces the value with one of the 30 values in `bz-neighbourhoods.txt`, chosen by a keyed hash.

Used by: `BZ_L2_NEIGHBOURHOOD`

CONFIGURATION

lookupFile	`bz-neighbourhoods.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_OCCUPATION SECURE LOOKUP

Replaces the value with one of the 40 values in `bz-occupations.txt`, chosen by a keyed hash.

Used by: `BZ_L2_OCCUPATION`

CONFIGURATION

lookupFile	`bz-occupations.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_OCTET NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `BZ_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

BZ_PARCEL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_LAND_PARCEL`

PATTERNS, TRIED IN ORDER

`(?i)(.*?block\s*(?:no\.?\s*)?)(\d+)(.*?parcel\s*(?:no\.?\s*)?)(\d+)(.*)`	keep · `BZ_CM_ALNUM` · keep · `BZ_CM_ALNUM` · keep
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_PHONE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_PHONE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?\(?501\)?[\s\-]?)?([2-8])(\d{2})([\s\-]?)(\d{4}))`	keep · keep · keep · `BZ_CM_ALNUM` · keep · `BZ_CM_ALNUM`
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_PLATE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_LICENCE_PLATE`

PATTERNS, TRIED IN ORDER

`(BMP|CZL|TOL|BZ|BC|CY|OW|SC|SP|SI|SE|PG|DG)([\s\-]?)([A-Z])([\s\-]?)(\d{3,5})`	keep · keep · keep · keep · `BZ_CM_ALNUM`
`(BMP|CZL|TOL|BZ|BC|CY|OW|SC|SP|SI|SE|PG|DG)([\s\-]?)(\d{3,5})`	keep · keep · `BZ_CM_ALNUM`
`([A-Z])([\s\-]?)(\d{3,5})`	keep · keep · `BZ_CM_ALNUM`
`(0*?)(?:(\d{3,5}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POLITICAL_OPINION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_POLITICAL_OPINION_LIST`.

Used by: `BZ_L3_POLITICAL_OPINION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_POLITICAL_OPINION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POLITICAL_OPINION_LIST SECURE LOOKUP

Replaces the value with one of the 7 values in `bz-political-opinions.txt`, chosen by a keyed hash.

Used by: `BZ_POLITICAL_OPINION`

CONFIGURATION

lookupFile	`bz-political-opinions.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_POLITICAL_PARTY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_POLITICAL_PARTY_LIST`.

Used by: `BZ_L3_POLITICAL_MEMBERSHIP`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`

`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_POLITICAL_PARTY_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POLITICAL_PARTY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-political-parties.txt`, chosen by a keyed hash.

Used by: `BZ_POLITICAL_PARTY`

CONFIGURATION

lookupFile	`bz-political-parties.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_POVERTY REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_POVERTY_STATUS`.

Used by: `BZ_FIN_POVERTY`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-5]))`	keep · `BZ_QUINTILE`
`(0*?)(?:([6-9]|10))`	keep · `BZ_DECILE_HIGH`
`(?i)(decile\s*)(\d{1,2})`	keep · `BZ_DECILE`
`(?i)(quintile\s*)([1-5])`	keep · `BZ_QUINTILE`
otherwise	`BZ_POVERTY_STATUS`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POVERTY_STATUS SECURE LOOKUP

Replaces the value with one of the 4 values in `bz-poverty-statuses.txt`, chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	`bz-poverty-statuses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_QUINTILE SECURE LOOKUP

Replaces the value with one of the 5 values in `bz-quintile.txt`, chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	`bz-quintile.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_REDACT REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L1_CREDENTIAL` , `BZ_L3_GENETIC` , `BZ_L3_BIOMETRIC`

PATTERNS, TRIED IN ORDER

`(.+)`	each character → `X`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_RELIGION_LIST` .

Used by: `BZ_L3_RELIGION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_RELIGION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_RELIGION_LIST SECURE LOOKUP

Replaces the value with one of the 19 values in `bz-religions.txt` , chosen by a keyed hash.

Used by: `BZ_RELIGION`

CONFIGURATION

lookupFile	`bz-religions.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SCHOOL SECURE LOOKUP

Replaces the value with one of the 15 values in `bz-schools.txt` , chosen by a keyed hash.

Used by: `BZ_L2_SCHOOL`

CONFIGURATION

lookupFile	`bz-schools.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_SEX`

PATTERNS, TRIED IN ORDER

`(?i)(female|male)`	`BZ_SEX_FEMALE_MALE`
`(?i)(woman|man)`	`BZ_SEX_WOMAN_MAN`
`(?i)(femenino|masculino)`	`BZ_SEX_SPANISH`
`(?i)(mujer|hombre)`	`BZ_SEX_MUJER_HOMBRE`
`(?i)([fm])`	`BZ_SEX_F_M`
`(?i)([hm])`	`BZ_SEX_H_M`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SEX_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-f-m.txt`, chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	`bz-sex-f-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-female-male.txt`, chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	`bz-sex-female-male.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

BZ_SEX_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-h-m.txt`, chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	`bz-sex-h-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	`bz-sex-mujer-hombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_SPANISH SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-spanish.txt`, chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	`bz-sex-spanish.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_WOMAN_MAN SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-woman-man.txt`, chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	`bz-sex-woman-man.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

BZ_SEXUAL_ORIENTATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SEXUAL_ORIENTATION_LIST`.

Used by: `BZ_L3_SEXUAL_ORIENTATION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_SEXUAL_ORIENTATION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SEXUAL_ORIENTATION_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-sexual-orientations.txt`, chosen by a keyed hash.

Used by: `BZ_SEXUAL_ORIENTATION`

CONFIGURATION

lookupFile	`bz-sexual-orientations.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SOCIAL_PROGRAMME REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SOCIAL_PROGRAMME_LIST`.

Used by: `BZ_FIN_SOCIAL_PROGRAMME`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_SOCIAL_PROGRAMME_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SOCIAL_PROGRAMME_LIST SECURE LOOKUP

Replaces the value with one of the 6 values in `bz-social-programmes.txt`, chosen by a keyed hash.

Used by: `BZ_SOCIAL_PROGRAMME`

CONFIGURATION

lookupFile	`bz-social-programmes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SSB_BENEFIT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SSB_BENEFIT_LIST`.

Used by: `BZ_FIN_SSB_BENEFIT`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `BZ_CM_ALNUM`
otherwise	`BZ_SSB_BENEFIT_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SSB_BENEFIT_LIST SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-ssb-benefits.txt`, chosen by a keyed hash.

Used by: `BZ_SSB_BENEFIT`

CONFIGURATION

lookupFile	`bz-ssb-benefits.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SUPPRESS SECURE LOOKUP

Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

Used by: `BZ_SUPPRESSED_CATEGORY`

CONFIGURATION

lookupFile	`bz-not-stated.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SUPPRESSED_CATEGORY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

Used by: `BZ_L3_BELIEF`, `BZ_L3_TRADE_UNION`, `BZ_L3_SEXUAL_LIFE`, `BZ_HEALTH_REPRODUCTIVE`, `BZ_HEALTH_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|s[ií]|true|false|[yns01])`	`BZ_FLAG`

`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))`	keep · keep · keep · keep · keep · `BZ_CM_ALNUM`
otherwise	`BZ_SUPPRESS`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SURNAME NAME

Replaces the name with one of the 225 names in `bz-surnames.txt`.

Used by: `BZ_SURNAMES`, `BZ_FULL_NAME`

CONFIGURATION

lookupFile	`bz-surnames.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

BZ_SURNAMES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_SURNAME`, `BZ_FULL_NAME`

PATTERNS, TRIED IN ORDER

`([^\s\-]+)(\-)([^\s\-]+)`	`BZ_SURNAME` · keep · `BZ_SURNAME`
`(\S+)`	`BZ_SURNAME`
`(\S+)\s+(\S+)`	`BZ_SURNAME` · `BZ_SURNAME`
`(\S+)\s+(\S+)\s+(\S+)`	`BZ_SURNAME` · `BZ_SURNAME` · `BZ_SURNAME`
otherwise	`BZ_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

BZ_TOWN_VILLAGE DATA CLEANSING

Replaces each value found in `bz-town-village-generalized.txt` (489 pairs) by its counterpart; values not in the file stay as they are.

Used by: `BZ_L2_TOWN_VILLAGE`

CONFIGURATION

lookupFile	`bz-town-village-generalized.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

BZ_YEAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_BIRTH_YEAR`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `BZ_CM_ALNUM`

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

APPENDIX B

Files

The lookup and detection files the policy reads. In Delphix each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`bz-addresses.txt`	3,000	`BZ_ADDRESS`	Lot 59, Hopeville, Punta Gorda · Lot 149, Boca del Rio, San Pedro Town · Mile 55 George Price Highway, Belmopan · Mile 9 George Price Highway, Hattieville
`bz-credit-statuses.txt`	10	`BZ_CREDIT_STATUS`	Current · 30 days past due · 60 days past due · 90 days past due
`bz-criminal-record.txt`	7	`BZ_CRIMINAL_RECORD_LIST`	No criminal record · Has criminal record · Charged · Case dismissed
`bz-decile-high.txt`	5	`BZ_DECILE_HIGH`	6 · 7 · 8 · 9
`bz-decile.txt`	10	`BZ_DECILE`	1 · 2 · 3 · 4
`bz-detect-given-names.txt`	208	`BZ_L1_GIVEN_NAME – List` `BZ_L1_FULL_NAME – List`	Maria · Jose · Juan · Carlos
`bz-detect-sex-letter.txt`	3	`BZ_L2_SEX – List`	f · m · h
`bz-detect-sex.txt`	9	`BZ_L2_SEX – List`	female · male · woman · man
`bz-detect-surnames.txt`	225	`BZ_L1_SURNAME – List` `BZ_L1_FULL_NAME – List`	Martinez · Garcia · Castillo · Lopez
`bz-diagnoses.txt`	30	`BZ_DIAGNOSIS_TEXT`	Essential hypertension · Type 2 diabetes mellitus · Asthma · Low back pain
`bz-disabilities.txt`	8	`BZ_DISABILITY_LIST`	Seeing · Hearing · Walking or climbing steps · Remembering or concentrating
`bz-education.txt`	12	`BZ_EDUCATION`	None · Preschool · Primary incomplete · Primary (Standard 6)
`bz-employers.txt`	25	`BZ_EMPLOYER`	Caribbean Trading Company Ltd. · Cayo Valley Services Ltd. · Northern Construction Ltd. · Coastal Transport Ltd.
`bz-ethnic-groups.txt`	14	`BZ_ETHNICITY_LIST`	Mestizo/Hispanic/Latino · Creole · Maya Ketchi · Maya Mopan
`bz-flag-0-1.txt`	2	`BZ_FLAG_0_1`	0 · 1
`bz-flag-s-n.txt`	2	`BZ_FLAG_S_N`	S · N
`bz-flag-si-no.txt`	2	`BZ_FLAG_SI_NO`	Sí · No
`bz-flag-true-false.txt`	2	`BZ_FLAG_TRUE_FALSE`	true · false

FILE	LINES	USED BY	FIRST LINES
bz-flag-y-n.txt	2	BZ_FLAG_Y_N	Y · N
bz-flag-yes-no.txt	2	BZ_FLAG_YES_NO	Yes · No
bz-gender-identities.txt	8	BZ_GENDER_IDENTITY_LIST	Woman · Man · Trans woman · Trans man
bz-given-names.txt	208	BZ_GIVEN_NAME	Maria · Jose · Juan · Carlos
bz-housing-tenure.txt	8	BZ_HOUSING_LIST	Owned · Owned with mortgage · Rented (private) · Rented (government)
bz-icd10-decimal.txt	33	BZ_ICD10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
bz-icd10.txt	37	BZ_ICD10	I10 · E11 · E78 · J45
bz-languages.txt	11	BZ_LANGUAGE_LIST	English · Spanish · Kriol · Maya Q'eqchi'
bz-marital-status.txt	7	BZ_MARITAL_STATUS	Never married · Married · Common-law union · Visiting partner
bz-medications.txt	26	BZ_MEDICATION_LIST	Paracetamol · Ibuprofen · Naproxen · Diclofenac
bz-nationalities.txt	16	BZ_NATIONALITY	Belizean · Guatemalan · Salvadoran · Honduran
bz-neighbourhoods.txt	30	BZ_NEIGHBOURHOOD	Lake Independence · Port Loyola · Collet · Mesopotamia
bz-not-stated.txt	1	BZ_SUPPRESS	Not stated
bz-occupations.txt	40	BZ_OCCUPATION	Clerk · Sales clerk · Shop assistant · Construction worker
bz-political-opinions.txt	7	BZ_POLITICAL_OPINION_LIST	Left · Centre-left · Centre · Centre-right
bz-political-parties.txt	8	BZ_POLITICAL_PARTY_LIST	People's United Party · United Democratic Party · Belize Progressive Party · Belize Justice Movement
bz-poverty-statuses.txt	4	BZ_POVERTY_STATUS	Extremely poor · Poor · Vulnerable · Not poor
bz-quintile.txt	5	BZ_QUINTILE	1 · 2 · 3 · 4
bz-religions.txt	19	BZ_RELIGION_LIST	Roman Catholic · Pentecostal · Seventh-day Adventist · Anglican
bz-schools.txt	15	BZ_SCHOOL	Ebenezer Methodist Primary School · St. Joseph Anglican Primary School · Sacred Heart RC Primary School · Holy Family Primary School
bz-sex-f-m.txt	2	BZ_SEX_F_M	F · M
bz-sex-female-male.txt	2	BZ_SEX_FEMALE_MALE	Female · Male
bz-sex-h-m.txt	2	BZ_SEX_H_M	H · M

FILE	LINES	USED BY	FIRST LINES
`bz-sex-mujer-hombre.txt`	2	`BZ_SEX_MUJER_HOMBRE`	Mujer · Hombre
`bz-sex-spanish.txt`	2	`BZ_SEX_SPANISH`	Femenino · Masculino
`bz-sex-woman-man.txt`	2	`BZ_SEX_WOMAN_MAN`	Woman · Man
`bz-sexual-orientations.txt`	8	`BZ_SEXUAL_ORIENTATION_LIST`	Heterosexual · Gay · Lesbian · Bisexual
`bz-social-programmes.txt`	6	`BZ_SOCIAL_PROGRAMME_LIST`	BOOST · Food Assistance Programme · Non-Contributory Pension Programme · National Health Insurance
`bz-ssb-benefits.txt`	10	`BZ_SSB_BENEFIT_LIST`	Sickness benefit · Maternity allowance · Maternity grant · Employment injury benefit
`bz-surnames.txt`	225	`BZ_SURNAME`	Martinez · Garcia · Castillo · Lopez
`bz-text-names.txt`	858	`BZ_FREE_TEXT`	Maria · MARIA · Jose · JOSE
`bz-town-village-generalized.txt`	489	`BZ_TOWN_VILLAGE`	Corozal Town|Corozal Town · COROZAL TOWN|COROZAL TOWN · Corozal|Corozal · COROZAL|COROZAL

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1

`product` `prod` `item` `article` `company` `business` `trade` `brand` `file` `street` `road` `avenue` `village` `town` `city` `district` `country` `bank` `branch` `plan` `campaign` `project` `service` `table` `column` `field` `user` `host` `server` `domain` `model` `category` `type` `school` `college` `institution` `course` `programme` `program` `subject` `document` `doc` `centre` `center` `unit` `clinic` `hospital` `area` `department` `dept` `position` `system` `app` `application` `group` `list` `report` `process` `event` `task` `profile` `role` `class` `object` `account` `drug` `medication` `diagnosis` `study` `benefit` `party` `union` `religion` `ethnicity` `language` `place` `store` `shop` `warehouse` `supplier` `vendor` `contract` `policy` `insurance` `org` `organi[sz]ation` `entity` `parameter` `variable` `method` `function` `index` `job` `script` `queue` `resource` `network` `device` `template` `image` `photo` `page` `site` `module` `menu` `option` `action` `permission` `tax` `currency` `issuer` `invoice` `payment` `form` `zone` `route` `line` `sector` `building` `display` `key` `tag` `label` `title` `code` `config` `setting` `firm` `employer` `estate` `parcel` `registration_?section` `producto` `articulo` `empresa` `archivo` `calle` `distrito` `pais` `banco` `escuela` `colegio` `documento` `servicio` `categoria` `tipo` `usuario` `customer` `cust` `client` `patient` `employee` `emp` `staff` `worker` `member` `student` `pupil` `insured` `beneficiary` `holder` `account_?holder` `policy_?holder` `mother` `father` `parent` `guardian` `spouse` `partner` `next_?of_?kin` `doctor` `physician` `nurse` `contact` `emergency_?contact` `guarantor` `debtor` `borrower` `applicant` `signatory` `witness` `representative` `owner` `tenant` `landlord` `victim` `complainant` `accused` `defendant` `donor` `heir` `person` `driver` `agent` `citizen` `elector` `voter` `taxpayer` `child` `dependant` `dependent` `relative` `officer` `teacher` `cliente` `paciente` `empleado` `beneficiario` `titular` `madre` `padre` `conyuge` `persona` `completos?` `y_?apellidos?` `apellidos?`

E2

`product` `prod` `item` `article` `company` `business` `trade` `brand` `file` `street` `road` `avenue` `village` `town` `city` `district` `country` `bank` `branch` `plan` `campaign` `project` `service` `table` `column` `field` `user` `host` `server` `domain` `model` `category` `type` `school` `college` `institution` `course` `programme` `program` `subject` `document` `doc` `centre` `center` `unit` `clinic` `hospital` `area` `department` `dept` `position` `system` `app` `application` `group` `list` `report` `process` `event` `task` `profile` `role` `class` `object` `account` `drug` `medication` `diagnosis` `study` `benefit` `party` `union` `religion` `ethnicity` `language` `place` `store` `shop` `warehouse` `supplier` `vendor` `contract` `policy` `insurance` `org` `organi[sz]ation` `entity` `parameter` `variable` `method` `function` `index` `job` `script` `queue` `resource` `network` `device` `template` `image` `photo` `page` `site` `module` `menu` `option` `action` `permission` `tax` `currency` `issuer` `invoice` `payment` `form` `zone` `route` `line` `sector` `building` `display` `key` `tag` `label` `title` `code` `config` `setting` `firm` `employer` `estate` `parcel` `registration_?section` `producto` `articulo` `empresa` `archivo` `calle` `distrito` `pais` `banco` `escuela` `colegio` `documento` `servicio` `categoria` `tipo` `usuario` `customer` `cust` `client` `patient` `employee` `emp` `staff` `worker` `member` `student` `pupil` `insured` `beneficiary` `holder` `account_?holder` `policy_?holder` `mother` `father` `parent` `guardian` `spouse` `partner` `next_?of_?kin` `doctor` `physician` `nurse` `contact` `emergency_?contact` `guarantor` `debtor` `borrower` `applicant` `signatory` `witness` `representative` `owner` `tenant` `landlord` `victim` `complainant` `accused` `defendant` `donor` `heir` `person` `driver` `agent` `citizen` `elector` `voter` `taxpayer` `child` `dependant` `dependent` `relative` `officer` `teacher` `cliente` `paciente` `empleado` `beneficiario` `titular` `madre` `padre` `conyuge` `persona` `full` `complete` `last` `first`

E3	`product` `prod` `item` `article` `company` `business` `trade` `brand` `file` `street` `road` `avenue` `village` `town` `city` `district` `country` `bank` `branch` `plan` `campaign` `project` `service` `table` `column` `field` `user` `host` `server` `domain` `model` `category` `type` `school` `college` `institution` `course` `programme` `program` `subject` `document` `doc` `centre` `center` `unit` `clinic` `hospital` `area` `department` `dept` `position` `system` `app` `application` `group` `list` `report` `process` `event` `task` `profile` `role` `class` `object` `account` `drug` `medication` `diagnosis` `study` `benefit` `party` `union` `religion` `ethnicity` `language` `place` `store` `shop` `warehouse` `supplier` `vendor` `contract` `policy` `insurance` `org` `organi[sz]ation` `entity` `parameter` `variable` `method` `function` `index` `job` `script` `queue` `resource` `network` `device` `template` `image` `photo` `page` `site` `module` `menu` `option` `action` `permission` `tax` `currency` `issuer` `invoice` `payment` `form` `zone` `route` `line` `sector` `building` `display` `key` `tag` `label` `title` `code` `config` `setting` `firm` `employer` `estate` `parcel` `registration_?section` `producto` `articulo` `empresa` `archivo` `calle` `distrito` `pais` `banco` `escuela` `colegio` `documento` `servicio` `categoria` `tipo` `usuario` `customer` `cust` `client` `patient` `employee` `emp` `staff` `worker` `member` `student` `pupil` `insured` `beneficiary` `holder` `account_?holder` `policy_?holder` `mother` `father` `parent` `guardian` `spouse` `partner` `next_?of_?kin` `doctor` `physician` `nurse` `contact` `emergency_?contact` `guarantor` `debtor` `borrower` `applicant` `signatory` `witness` `representative` `owner` `tenant` `landlord` `victim` `complainant` `accused` `defendant` `donor` `heir` `person` `driver` `agent` `citizen` `elector` `voter` `taxpayer` `child` `dependant` `dependent` `relative` `officer` `teacher` `cliente` `paciente` `empleado` `beneficiario` `titular` `madre` `padre` `conyuge` `persona` `completo` `y_?apellidos?` `apellidos?`
E4	`ip` `mac` `email` `e_?mail` `web` `url` `book` `type` `id`
E5	`id` `type` `code` `key` `no` `num` `number` `date` `status` `queue` `count` `log`
E6	`id` `key` `type` `role` `site` `ref` `code` `number` `no` `size`

APPENDIX D

Discovery policy and classifiers

The discovery policy `BZ – Data Protection Act 2021 – v4` runs these 126 classifiers, with an assignment threshold of 60%.

Data Protection Act 2021 - personal data

CLASSIFIER	KIND	DATA CLASS
`BZ_L1_SOCIAL_SECURITY_NUMBER – Path`	COLUMN NAME	`BZ_L1_SOCIAL_SECURITY_NUMBER`
`BZ_L1_SOCIAL_SECURITY_NUMBER – Regex`	VALUE FORMAT	`BZ_L1_SOCIAL_SECURITY_NUMBER`
`BZ_L1_TIN – Path`	COLUMN NAME	`BZ_L1_TIN`
`BZ_L1_PASSPORT – Path`	COLUMN NAME	`BZ_L1_PASSPORT`
`BZ_L1_PASSPORT – Regex`	VALUE FORMAT	`BZ_L1_PASSPORT`
`BZ_L1_VOTER_ID – Path`	COLUMN NAME	`BZ_L1_VOTER_ID`
`BZ_L1_DRIVERS_LICENCE – Path`	COLUMN NAME	`BZ_L1_DRIVERS_LICENCE`
`BZ_L1_IMMIGRATION_DOCUMENT – Path`	COLUMN NAME	`BZ_L1_IMMIGRATION_DOCUMENT`
`BZ_L1_VITAL_RECORD – Path`	COLUMN NAME	`BZ_L1_VITAL_RECORD`
`BZ_L1_GIVEN_NAME – Path`	COLUMN NAME	`BZ_L1_GIVEN_NAME`
`BZ_L1_GIVEN_NAME – List`	KNOWN VALUES	`BZ_L1_GIVEN_NAME`
`BZ_L1_SURNAME – Path`	COLUMN NAME	`BZ_L1_SURNAME`
`BZ_L1_SURNAME – List`	KNOWN VALUES	`BZ_L1_SURNAME`
`BZ_L1_FULL_NAME – Path`	COLUMN NAME	`BZ_L1_FULL_NAME`
`BZ_L1_FULL_NAME – List`	KNOWN VALUES	`BZ_L1_FULL_NAME`
`BZ_L1_EMAIL – Path`	COLUMN NAME	`BZ_L1_EMAIL`
`BZ_L1_EMAIL – Type`	DATA TYPE	`BZ_L1_EMAIL`
`BZ_L1_EMAIL – Regex`	VALUE FORMAT	`BZ_L1_EMAIL`
`BZ_L1_PHONE – Path`	COLUMN NAME	`BZ_L1_PHONE`
`BZ_L1_PHONE – Regex`	VALUE FORMAT	`BZ_L1_PHONE`
`BZ_L1_ADDRESS – Path`	COLUMN NAME	`BZ_L1_ADDRESS`
`BZ_L1_ADDRESS – Type`	DATA TYPE	`BZ_L1_ADDRESS`
`BZ_L1_ADDRESS – Regex`	VALUE FORMAT	`BZ_L1_ADDRESS`
`BZ_L1_ADDRESS_DETAIL – Path`	COLUMN NAME	`BZ_L1_ADDRESS_DETAIL`
`BZ_L1_BANK_ACCOUNT – Path`	COLUMN NAME	`BZ_L1_BANK_ACCOUNT`
`BZ_L1_PAYMENT_CARD – Path`	COLUMN NAME	`BZ_L1_PAYMENT_CARD`
`BZ_L1_PAYMENT_CARD – Regex`	VALUE FORMAT	`BZ_L1_PAYMENT_CARD`
`BZ_L1_IP_ADDRESS – Path`	COLUMN NAME	`BZ_L1_IP_ADDRESS`
`BZ_L1_IP_ADDRESS – Regex`	VALUE FORMAT	`BZ_L1_IP_ADDRESS`
`BZ_L1_DEVICE_ID – Path`	COLUMN NAME	`BZ_L1_DEVICE_ID`
`BZ_L1_DEVICE_ID – Regex`	VALUE FORMAT	`BZ_L1_DEVICE_ID`

CLASSIFIER	KIND	DATA CLASS
BZ_L1_LICENCE_PLATE – Path	COLUMN NAME	BZ_L1_LICENCE_PLATE
BZ_L1_LICENCE_PLATE – Regex	VALUE FORMAT	BZ_L1_LICENCE_PLATE
BZ_L1_VIN – Path	COLUMN NAME	BZ_L1_VIN
BZ_L1_VIN – Regex	VALUE FORMAT	BZ_L1_VIN
BZ_L1_LAND_PARCEL – Path	COLUMN NAME	BZ_L1_LAND_PARCEL
BZ_L1_LAND_PARCEL – Regex	VALUE FORMAT	BZ_L1_LAND_PARCEL
BZ_L1_CONTRACT_NUMBER – Path	COLUMN NAME	BZ_L1_CONTRACT_NUMBER
BZ_L1_USERNAME – Path	COLUMN NAME	BZ_L1_USERNAME
BZ_L1_CREDENTIAL – Path	COLUMN NAME	BZ_L1_CREDENTIAL
BZ_L1_CREDENTIAL – Regex	VALUE FORMAT	BZ_L1_CREDENTIAL
BZ_L1_GEOLOCATION – Path	COLUMN NAME	BZ_L1_GEOLOCATION
BZ_L1_GEOLOCATION – Regex	VALUE FORMAT	BZ_L1_GEOLOCATION
BZ_L1_FREE_TEXT – Path	COLUMN NAME	BZ_L1_FREE_TEXT
BZ_L1_FREE_TEXT – Type	DATA TYPE	BZ_L1_FREE_TEXT
BZ_L1_FREE_TEXT – Regex	VALUE FORMAT	BZ_L1_FREE_TEXT
BZ_L2_BIRTH_DATE – Path	COLUMN NAME	BZ_L2_BIRTH_DATE
BZ_L2_BIRTH_DATE – Type	DATA TYPE	BZ_L2_BIRTH_DATE
BZ_L2_BIRTH_YEAR – Path	COLUMN NAME	BZ_L2_BIRTH_YEAR
BZ_L2_BIRTH_YEAR – Type	DATA TYPE	BZ_L2_BIRTH_YEAR
BZ_L2_AGE – Path	COLUMN NAME	BZ_L2_AGE
BZ_L2_AGE – Type	DATA TYPE	BZ_L2_AGE
BZ_L2_EVENT_DATE – Path	COLUMN NAME	BZ_L2_EVENT_DATE
BZ_L2_EVENT_DATE – Type	DATA TYPE	BZ_L2_EVENT_DATE
BZ_L2_SEX – Path	COLUMN NAME	BZ_L2_SEX
BZ_L2_SEX – List	KNOWN VALUES	BZ_L2_SEX
BZ_L2_TOWN_VILLAGE – Path	COLUMN NAME	BZ_L2_TOWN_VILLAGE
BZ_L2_TOWN_VILLAGE – Values	VALUE FORMAT	BZ_L2_TOWN_VILLAGE
BZ_L2_NEIGHBOURHOOD – Path	COLUMN NAME	BZ_L2_NEIGHBOURHOOD
BZ_L2_NATIONALITY – Path	COLUMN NAME	BZ_L2_NATIONALITY
BZ_L2_NATIONALITY – Values	VALUE FORMAT	BZ_L2_NATIONALITY
BZ_L2_MARITAL_STATUS – Path	COLUMN NAME	BZ_L2_MARITAL_STATUS
BZ_L2_MARITAL_STATUS – Values	VALUE FORMAT	BZ_L2_MARITAL_STATUS
BZ_L2_OCCUPATION – Path	COLUMN NAME	BZ_L2_OCCUPATION
BZ_L2_EMPLOYER – Path	COLUMN NAME	BZ_L2_EMPLOYER
BZ_L2_EDUCATION – Path	COLUMN NAME	BZ_L2_EDUCATION
BZ_L2_EDUCATION – Values	VALUE FORMAT	BZ_L2_EDUCATION
BZ_L2_SCHOOL – Path	COLUMN NAME	BZ_L2_SCHOOL

CLASSIFIER	KIND	DATA CLASS
BZ_L2_DEPENDANTS – Path	COLUMN NAME	BZ_L2_DEPENDANTS
BZ_L2_DEPENDANTS – Type	DATA TYPE	BZ_L2_DEPENDANTS
BZ_L3_ETHNICITY – Path	COLUMN NAME	BZ_L3_ETHNICITY
BZ_L3_ETHNICITY – Values	VALUE FORMAT	BZ_L3_ETHNICITY
BZ_L3_LANGUAGE – Path	COLUMN NAME	BZ_L3_LANGUAGE
BZ_L3_LANGUAGE – Values	VALUE FORMAT	BZ_L3_LANGUAGE
BZ_L3_RELIGION – Path	COLUMN NAME	BZ_L3_RELIGION
BZ_L3_RELIGION – Values	VALUE FORMAT	BZ_L3_RELIGION
BZ_L3_BELIEF – Path	COLUMN NAME	BZ_L3_BELIEF
BZ_L3_POLITICAL_OPINION – Path	COLUMN NAME	BZ_L3_POLITICAL_OPINION
BZ_L3_POLITICAL_OPINION – Values	VALUE FORMAT	BZ_L3_POLITICAL_OPINION
BZ_L3_POLITICAL_MEMBERSHIP – Path	COLUMN NAME	BZ_L3_POLITICAL_MEMBERSHIP
BZ_L3_POLITICAL_MEMBERSHIP – Values	VALUE FORMAT	BZ_L3_POLITICAL_MEMBERSHIP
BZ_L3_TRADE_UNION – Path	COLUMN NAME	BZ_L3_TRADE_UNION
BZ_L3_TRADE_UNION – Values	VALUE FORMAT	BZ_L3_TRADE_UNION
BZ_L3_GENETIC – Path	COLUMN NAME	BZ_L3_GENETIC
BZ_L3_GENETIC – Regex	VALUE FORMAT	BZ_L3_GENETIC
BZ_L3_BIOMETRIC – Path	COLUMN NAME	BZ_L3_BIOMETRIC
BZ_L3_BIOMETRIC – Type	DATA TYPE	BZ_L3_BIOMETRIC
BZ_L3_SEXUAL_ORIENTATION – Path	COLUMN NAME	BZ_L3_SEXUAL_ORIENTATION
BZ_L3_SEXUAL_ORIENTATION – Values	VALUE FORMAT	BZ_L3_SEXUAL_ORIENTATION
BZ_L3_SEXUAL_LIFE – Path	COLUMN NAME	BZ_L3_SEXUAL_LIFE
BZ_L3_GENDER_IDENTITY – Path	COLUMN NAME	BZ_L3_GENDER_IDENTITY
BZ_L3_GENDER_IDENTITY – Values	VALUE FORMAT	BZ_L3_GENDER_IDENTITY
BZ_HEALTH_ID – Path	COLUMN NAME	BZ_HEALTH_ID
BZ_HEALTH_DIAGNOSIS – Path	COLUMN NAME	BZ_HEALTH_DIAGNOSIS
BZ_HEALTH_DIAGNOSIS – Regex	VALUE FORMAT	BZ_HEALTH_DIAGNOSIS
BZ_HEALTH_MEDICATION – Path	COLUMN NAME	BZ_HEALTH_MEDICATION
BZ_HEALTH_MEDICATION – Values	VALUE FORMAT	BZ_HEALTH_MEDICATION
BZ_HEALTH_CLINICAL_TEXT – Path	COLUMN NAME	BZ_HEALTH_CLINICAL_TEXT
BZ_HEALTH_CLINICAL_TEXT – Type	DATA TYPE	BZ_HEALTH_CLINICAL_TEXT
BZ_HEALTH_TEST_RESULT – Path	COLUMN NAME	BZ_HEALTH_TEST_RESULT
BZ_HEALTH_BLOOD_GROUP – Path	COLUMN NAME	BZ_HEALTH_BLOOD_GROUP
BZ_HEALTH_BLOOD_GROUP – Values	VALUE FORMAT	BZ_HEALTH_BLOOD_GROUP
BZ_HEALTH_DISABILITY – Path	COLUMN NAME	BZ_HEALTH_DISABILITY
BZ_HEALTH_DISABILITY – Values	VALUE FORMAT	BZ_HEALTH_DISABILITY
BZ_HEALTH_REPRODUCTIVE – Path	COLUMN NAME	BZ_HEALTH_REPRODUCTIVE

CLASSIFIER	KIND	DATA CLASS
BZ_HEALTH_MENTAL – Path	COLUMN NAME	BZ_HEALTH_MENTAL
BZ_FIN_CREDIT_REFERENCE – Path	COLUMN NAME	BZ_FIN_CREDIT_REFERENCE
BZ_FIN_DEBT – Path	COLUMN NAME	BZ_FIN_DEBT
BZ_FIN_DEBT – Type	DATA TYPE	BZ_FIN_DEBT
BZ_FIN_INCOME – Path	COLUMN NAME	BZ_FIN_INCOME
BZ_FIN_INCOME – Type	DATA TYPE	BZ_FIN_INCOME
BZ_FIN_ASSETS – Path	COLUMN NAME	BZ_FIN_ASSETS
BZ_FIN_ASSETS – Type	DATA TYPE	BZ_FIN_ASSETS
BZ_FIN_PENSION – Path	COLUMN NAME	BZ_FIN_PENSION
BZ_FIN_PENSION – Type	DATA TYPE	BZ_FIN_PENSION
BZ_FIN_SSB_BENEFIT – Path	COLUMN NAME	BZ_FIN_SSB_BENEFIT
BZ_FIN_SSB_BENEFIT – Values	VALUE FORMAT	BZ_FIN_SSB_BENEFIT
BZ_FIN_SOCIAL_PROGRAMME – Path	COLUMN NAME	BZ_FIN_SOCIAL_PROGRAMME
BZ_FIN_SOCIAL_PROGRAMME – Values	VALUE FORMAT	BZ_FIN_SOCIAL_PROGRAMME
BZ_FIN_POVERTY – Path	COLUMN NAME	BZ_FIN_POVERTY
BZ_FIN_POVERTY – Values	VALUE FORMAT	BZ_FIN_POVERTY
BZ_FIN_HOUSING – Path	COLUMN NAME	BZ_FIN_HOUSING
BZ_FIN_HOUSING – Values	VALUE FORMAT	BZ_FIN_HOUSING
BZ_PENAL_CRIMINAL_RECORD – Path	COLUMN NAME	BZ_PENAL_CRIMINAL_RECORD
BZ_PENAL_CASE_NUMBER – Path	COLUMN NAME	BZ_PENAL_CASE_NUMBER
BZ_PENAL_CASE_NUMBER – Regex	VALUE FORMAT	BZ_PENAL_CASE_NUMBER