DELPHIX CONTINUOUS COMPLIANCE · DISCOVERY POLICY

# Chile — Ley 21.719

Discovering and masking Chilean personal data: direct identifiers, quasi-identifiers and the sensitive data of article 2 — socioeconomic situation included.

| 73 | 134 | 97 |
|---|---|---|
| DATA CLASSES | CLASSIFIERS | ALGORITHMS |

Discovery policy `CL – Ley 21.719 – v6`

Version 6 of October 12, 2026 · Assignment threshold 60%

# Contents

The first sections explain what the policy is for and how it works. The data class chapters then describe every data class: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the policy contains.


| | | |
|---|---|---|
| 1 | **About this discovery policy** | |
| 2 | **Ley 21.719 in brief** | |
| 3 | **How sensitive data is discovered** | |
| 4 | **How data is masked** | |
| 5 | **Essential and extended packs** | |
| 6 | **Data classes at a glance** | |

**PART 7 · DIRECT IDENTIFIERS**

| | | |
|---|---|---|
| 7.1 | **RUT / RUN** | CL_L1_RUT |
| 7.2 | **RUT without check digit** | CL_L1_RUT_CUERPO |
| 7.3 | **RUT check digit** | CL_L1_RUT_DV |
| 7.4 | **Given names** | CL_L1_NOMBRE |
| 7.5 | **Surnames** | CL_L1_APELLIDO |
| 7.6 | **Full name** | CL_L1_NOMBRE_COMPLETO |
| 7.7 | **E-mail address** | CL_L1_EMAIL |
| 7.8 | **Telephone** | CL_L1_TELEFONO |
| 7.9 | **Street address** | CL_L1_DIRECCION |
| 7.10 | **Address details** | CL_L1_DIRECCION_COMPLEMENTO |
| 7.11 | **Identity card document number** | CL_L1_NUMERO_DOCUMENTO |
| 7.12 | **Passport** | CL_L1_PASAPORTE |
| 7.13 | **Foreign identity documents** | CL_L1_DOCUMENTO_EXTRANJERO |
| 7.14 | **Bank account** | CL_L1_CUENTA_BANCARIA |
| 7.15 | **Payment card** | CL_L1_TARJETA |
| 7.16 | **IP address** | CL_L1_IP |
| 7.17 | **Device identifiers** | CL_L1_DISPOSITIVO |
| 7.18 | **Vehicle plate** | CL_L1_PATENTE |
| 7.19 | **Chassis and engine numbers** | CL_L1_VEHICULO_ID |
| 7.20 | **Contract and policy numbers** | CL_L1_NUMERO_CONTRATO |
| 7.21 | **Usernames and social profiles** | CL_L1_USUARIO_RRSS |
| 7.22 | **Passwords and secrets** | CL_L1_CREDENCIAL |
| 7.23 | **Geolocation** | CL_L1_GEOLOCALIZACION |
| 7.24 | **Free text** | CL_L1_TEXTO_LIBRE |

## PART 8 · QUASI-IDENTIFIERS

| | | |
|---|---|---|
| 8.1 | Date of birth | CL_L2_FECHA_NACIMIENTO |
| 8.2 | Year of birth | CL_L2_ANIO_NACIMIENTO |
| 8.3 | Age | CL_L2_EDAD |
| 8.4 | Personal event dates | CL_L2_FECHA_EVENTO |
| 8.5 | Sex | CL_L2_SEXO |
| 8.6 | Comuna | CL_L2_COMUNA |
| 8.7 | Comuna code | CL_L2_CODIGO_COMUNA |
| 8.8 | Postal code | CL_L2_CODIGO_POSTAL |
| 8.9 | Nationality | CL_L2_NACIONALIDAD |
| 8.10 | Marital status | CL_L2_ESTADO_CIVIL |
| 8.11 | Occupation and position | CL_L2_OCUPACION |
| 8.12 | Employer | CL_L2_EMPLEADOR |
| 8.13 | Education level | CL_L2_NIVEL_EDUCACIONAL |
| 8.14 | School or university | CL_L2_ESTABLECIMIENTO_EDUCACIONAL |
| 8.15 | Dependants | CL_L2_CARGAS_FAMILIARES |

## PART 9 · SENSITIVE DATA

| | | |
|---|---|---|
| 9.1 | Indigenous peoples and ethnic origin | CL_L3_ETNIA |
| 9.2 | Diagnoses | CL_L3_SALUD_DIAGNOSTICO |
| 9.3 | Medicines | CL_L3_SALUD_MEDICAMENTO |
| 9.4 | Clinical record numbers | CL_L3_SALUD_IDENTIFICADOR |
| 9.5 | Clinical notes | CL_L3_SALUD_TEXTO_CLINICO |
| 9.6 | Test results | CL_L3_SALUD_RESULTADO_EXAMEN |
| 9.7 | Blood group | CL_L3_SALUD_GRUPO_SANGUINEO |
| 9.8 | Disability | CL_L3_SALUD_DISCAPACIDAD |
| 9.9 | Sexual and reproductive health | CL_L3_SALUD_SEXUAL_REPRODUCTIVA |
| 9.10 | Mental health and addictions | CL_L3_SALUD_MENTAL_ADICCIONES |
| 9.11 | Biometric data | CL_L3_BIOMETRICO |
| 9.12 | Genetic profile | CL_L3_PERFIL_GENETICO |
| 9.13 | Sexual orientation | CL_L3_ORIENTACION_SEXUAL |
| 9.14 | Gender identity | CL_L3_IDENTIDAD_GENERO |
| 9.15 | Sexual life | CL_L3_VIDA_SEXUAL |
| 9.16 | Religion | CL_L3_RELIGION |
| 9.17 | Ideological convictions | CL_L3_CONVICCION_IDEOLOGICA |
| 9.18 | Political affiliation | CL_L3_AFILIACION_POLITICA |
| 9.19 | Union affiliation | CL_L3_AFILIACION_SINDICAL |
| 9.20 | Professional association | CL_L3_AFILIACION_GREMIAL |

## PART 10 · SOCIOECONOMIC SITUATION

| | | |
|---|---|---|
| 10.1 | Health insurance and FONASA tier | CL_L3_SOCIOEC_PREVISION_SALUD |
| 10.2 | Health plan | CL_L3_SOCIOEC_PLAN_SALUD |
| 10.3 | Registro Social de Hogares | CL_L3_SOCIOEC_RSH |
| 10.4 | Socioeconomic group | CL_L3_SOCIOEC_NIVEL |
| 10.5 | State benefits | CL_L3_SOCIOEC_BENEFICIO_SOCIAL |
| 10.6 | Debt and credit status | CL_L3_SOCIOEC_MOROSIDAD |
| 10.7 | Debt amounts | CL_L3_SOCIOEC_MONTO_DEUDA |
| 10.8 | Income and salary | CL_L3_SOCIOEC_INGRESOS |
| 10.9 | Pension fund | CL_L3_SOCIOEC_PREVISION_AFP |
| 10.10 | Pension balances | CL_L3_SOCIOEC_SALDO_PREVISIONAL |
| 10.11 | Housing situation | CL_L3_SOCIOEC_VIVIENDA |
| 10.12 | Student aid | CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS |

## PART 11 · CRIMINAL RECORDS

| | | |
|---|---|---|
| 11.1 | Criminal records | CL_L3_PENAL_ANTECEDENTES |
| 11.2 | Court case numbers | CL_L3_PENAL_CAUSA |
| 12 | The RUT check digit | |
| 13 | Limits | |
| 14 | Verification | |
| 15 | Sources | |
| A | Algorithms | |
| B | Files | |
| C | Exclusion lists | |
| D | Discovery policy and classifiers | |

1

# About this discovery policy

This discovery policy finds the personal data in a Chilean database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Ley 21.719 does not apply to anonymized data. That is why the policy does not stop at direct identifiers: it also generalizes the quasi-identifiers that re-identify people in combination, and covers every sensitive category of article 2. Its data classes are organized in the same layers:

- **Direct identifiers** — RUT, names, contact details, documents, accounts, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, comuna, postal code, occupation, employer and similar attributes.
- **Sensitive data** — ethnic origin, health, biometrics, sexual life, orientation and gender identity, beliefs, political, union and professional affiliation.
- **Socioeconomic situation** — FONASA tier and ISAPRE, Registro Social de Hogares, state benefits, commercial debt, income, pension fund, housing, student aid.
- **Criminal records** — convictions and court case numbers.

In Data Control Tower the policy is one discovery policy with its classifiers, the data classes they vote for, the algorithms those data classes name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — `NOMBRE`, `RESULTADO`, `CIUDAD` — needs the values to agree. A column with a meaningless name (`CAMPO1`, `OBS`) is still found when its values have a recognizable shape or vocabulary.

> Before masking, inventory the binary columns (BLOB, images, PDF). The algorithms of this policy work on text, numbers and dates: a scanned ID card stored in a BLOB keeps its RUT readable. Report those columns as residual risk.

2

# Ley 21.719 in brief

Ley 21.719 regulates the protection and processing of personal data and creates the Agencia de Protección de Datos Personales. Its article 2 defines as **sensitive** the data that reveal ethnic or racial origin, political, union or professional affiliation, socioeconomic situation, ideological or philosophical convictions, religious beliefs, health and human biological profile, biometric data, and sexual life, sexual orientation and gender identity.

Socioeconomic situation is a category of Chilean law: data that are ordinary elsewhere — a FONASA tier, an ISAPRE, a Registro Social de Hogares percentile, a DICOM record — are sensitive in Chile, and templates built for GDPR do not cover them.

The law takes effect on 1 December 2026. On 31 August 2026 the Government sent the Senate a bill (Boletín 18.623-07) that would move that date to 1 December 2027; check its status. The date does not change this policy.

> This document describes technical controls. Whether a copy of the data counts as anonymized is a legal assessment of the whole environment — its access, its retention, what else is joined to it — and not of the discovery policy alone.

3

# How sensitive data is discovered

A discovery job looks at every column of its rule set and asks each classifier of the discovery policy how confident it is that the column belongs to its data class. The policy uses the four classifier frameworks of Delphix:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the data class out. It never assigns a data class on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per data class, and the column is assigned to the data class with the highest confidence when it reaches the assignment threshold of the discovery policy — **60%** here. Values that do not match a format or a list count against their data class by the classifier's reject strength.

These are the names Data Control Tower gives the objects: data classes, classifiers and a discovery policy, run by a discovery job. A Continuous Compliance Engine used on its own calls the same objects domains, classifiers and a profile set, run by a profiling job; everything in this document applies to both.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. Discovery tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Discovery proposes; it does not decide. Review the data classes assigned in the rule set before running a masking job, and look for columns the policy left unassigned.

4

# How data is masked

Each data class names one algorithm, which a masking job applies to every column the rule set assigns to the data class. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each data class shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine and compliance node uses the same keys.

Where an algorithm that comes with Delphix already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the policy names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name, the one an engine uses; Data Control Tower lists them without the prefix ( `CM Numeric` , `CreditCard` , `BloodType SL` ). They are on every engine and in every Data Control Tower, and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. With other keys the masked values differ; their shape does not.

5

# Essential and extended packs

The policy can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create just its data classes, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the discovery policy.

| PACK | DATA CLASSES | CLASSIFIERS | ALGORITHMS | FILES |
|---|---|---|---|---|
| **Essential** | 13 | 30 | 21 | 6 |
| **Extended** | 73 | 134 | 97 | 53 |

The essential pack holds these data classes, marked **Essential** in the tables and chapters:

- RUT / RUN — `CL_L1_RUT`
- RUT without check digit — `CL_L1_RUT_CUERPO`
- RUT check digit — `CL_L1_RUT_DV`
- Given names — `CL_L1_NOMBRE`
- Surnames — `CL_L1_APELLIDO`
- Full name — `CL_L1_NOMBRE_COMPLETO`
- E-mail address — `CL_L1_EMAIL`
- Telephone — `CL_L1_TELEFONO`
- Street address — `CL_L1_DIRECCION`
- Address details — `CL_L1_DIRECCION_COMPLEMENTO`
- Identity card document number — `CL_L1_NUMERO_DOCUMENTO`
- Passport — `CL_L1_PASAPORTE`
- Date of birth — `CL_L2_FECHA_NACIMIENTO`

> With fewer data classes competing, a column that a data class of the extended pack would claim by its name can be proposed for an essential data class instead — a numeric code, for instance, can look like a telephone number. Review the discovery result.

6

# Data classes at a glance

Every data class of the policy, how it is found and the algorithm that masks it.

| DATA CLASS | FOUND BY | ALGORITHM |
|---|---|---|
| **DIRECT IDENTIFIERS** | | |
| **RUT / RUN** ESSENTIAL<br>CL_L1_RUT | COLUMN NAME · DATA TYPE · VALUE FORMAT | CL_RUT |
| **RUT without check digit** ESSENTIAL<br>CL_L1_RUT_CUERPO | COLUMN NAME · DATA TYPE · VALUE FORMAT | CL_CM_ALFANUM |
| **RUT check digit** ESSENTIAL<br>CL_L1_RUT_DV | COLUMN NAME · DATA TYPE · VALUE FORMAT | CL_RUT_DV |
| **Given names** ESSENTIAL<br>CL_L1_NOMBRE | COLUMN NAME · KNOWN VALUES | CL_NOMBRES |
| **Surnames** ESSENTIAL<br>CL_L1_APELLIDO | COLUMN NAME · KNOWN VALUES | CL_APELLIDOS |
| **Full name** ESSENTIAL<br>CL_L1_NOMBRE_COMPLETO | COLUMN NAME · KNOWN VALUES | CL_NOMBRE_COMPLETO |
| **E-mail address** ESSENTIAL<br>CL_L1_EMAIL | COLUMN NAME · DATA TYPE · VALUE FORMAT | CL_EMAIL |
| **Telephone** ESSENTIAL<br>CL_L1_TELEFONO | COLUMN NAME · VALUE FORMAT | CL_TELEFONO |
| **Street address** ESSENTIAL<br>CL_L1_DIRECCION | COLUMN NAME · DATA TYPE · VALUE FORMAT | CL_DIRECCION |
| **Address details** ESSENTIAL<br>CL_L1_DIRECCION_COMPLEMENTO | COLUMN NAME | CL_CM_ALFANUM |
| **Identity card document number** ESSENTIAL<br>CL_L1_NUMERO_DOCUMENTO | COLUMN NAME · VALUE FORMAT | CL_CM_ALFANUM |
| **Passport** ESSENTIAL<br>CL_L1_PASAPORTE | COLUMN NAME · VALUE FORMAT | CL_CM_ALFANUM |
| **Foreign identity documents**<br>CL_L1_DOCUMENTO_EXTRANJERO | COLUMN NAME | CL_CM_ALFANUM |
| **Bank account**<br>CL_L1_CUENTA_BANCARIA | COLUMN NAME | CL_CM_ALFANUM |
| **Payment card**<br>CL_L1_TARJETA | COLUMN NAME · VALUE FORMAT | CL_TARJETA |
| **IP address**<br>CL_L1_IP | COLUMN NAME · VALUE FORMAT | CL_IP |
| **Device identifiers**<br>CL_L1_DISPOSITIVO | COLUMN NAME · VALUE FORMAT | CL_CM_ALFANUM |
| **Vehicle plate**<br>CL_L1_PATENTE | COLUMN NAME · VALUE FORMAT | CL_PATENTE |
| **Chassis and engine numbers**<br>CL_L1_VEHICULO_ID | COLUMN NAME · VALUE FORMAT | CL_CM_ALFANUM |

| DATA CLASS | FOUND BY | ALGORITHM |
|---|---|---|
| **Contract and policy numbers**<br>`CL_L1_NUMERO_CONTRATO` | COLUMN NAME | `CL_CM_ALFANUM` |
| **Usernames and social profiles**<br>`CL_L1_USUARIO_RRSS` | COLUMN NAME | `CL_CM_ALFANUM` |
| **Passwords and secrets**<br>`CL_L1_CREDENCIAL` | COLUMN NAME · VALUE FORMAT | `CL_REDACTAR` |
| **Geolocation**<br>`CL_L1_GEOLOCALIZACION` | COLUMN NAME · VALUE FORMAT | `CL_COORDENADA` |
| **Free text**<br>`CL_L1_TEXTO_LIBRE` | COLUMN NAME · DATA TYPE · VALUE FORMAT | `CL_TEXTO_LIBRE` |
| **QUASI-IDENTIFIERS** | | |
| **Date of birth** ESSENTIAL<br>`CL_L2_FECHA_NACIMIENTO` | COLUMN NAME · DATA TYPE | `CL_FECHA_NACIMIENTO` |
| **Year of birth**<br>`CL_L2_ANIO_NACIMIENTO` | COLUMN NAME · DATA TYPE | `CL_ANIO` |
| **Age**<br>`CL_L2_EDAD` | COLUMN NAME · DATA TYPE | `CL_EDAD` |
| **Personal event dates**<br>`CL_L2_FECHA_EVENTO` | COLUMN NAME · DATA TYPE | `CL_FECHA_EVENTO` |
| **Sex**<br>`CL_L2_SEXO` | COLUMN NAME · KNOWN VALUES | `CL_SEXO` |
| **Comuna**<br>`CL_L2_COMUNA` | COLUMN NAME · VALUE FORMAT | `CL_COMUNA` |
| **Comuna code**<br>`CL_L2_CODIGO_COMUNA` | COLUMN NAME · DATA TYPE · VALUE FORMAT | `CL_CODIGO_COMUNA` |
| **Postal code**<br>`CL_L2_CODIGO_POSTAL` | COLUMN NAME · VALUE FORMAT | `CL_CODIGO_POSTAL` |
| **Nationality**<br>`CL_L2_NACIONALIDAD` | COLUMN NAME · KNOWN VALUES | `CL_NACIONALIDAD` |
| **Marital status**<br>`CL_L2_ESTADO_CIVIL` | COLUMN NAME · VALUE FORMAT | `CL_ESTADO_CIVIL` |
| **Occupation and position**<br>`CL_L2_OCUPACION` | COLUMN NAME | `CL_OCUPACION` |
| **Employer**<br>`CL_L2_EMPLEADOR` | COLUMN NAME | `CL_EMPLEADOR` |
| **Education level**<br>`CL_L2_NIVEL_EDUCACIONAL` | COLUMN NAME · VALUE FORMAT | `CL_NIVEL_EDUCACIONAL` |
| **School or university**<br>`CL_L2_ESTABLECIMIENTO_EDUCACIONAL` | COLUMN NAME | `CL_ESTABLECIMIENTO` |
| **Dependants**<br>`CL_L2_CARGAS_FAMILIARES` | COLUMN NAME · DATA TYPE | `CL_CANTIDAD_ACOTADA` |
| **SENSITIVE DATA** | | |
| **Indigenous peoples and ethnic origin**<br>`CL_L3_ETNIA` | COLUMN NAME · VALUE FORMAT | `CL_PUEBLO_ORIGINARIO` |

| DATA CLASS | FOUND BY | ALGORITHM |
|---|---|---|
| **Diagnoses**<br>CL_L3_SALUD_DIAGNOSTICO | COLUMN NAME VALUE FORMAT | CL_DIAGNOSTICO |
| **Medicines**<br>CL_L3_SALUD_MEDICAMENTO | COLUMN NAME VALUE FORMAT | CL_MEDICAMENTO |
| **Clinical record numbers**<br>CL_L3_SALUD_IDENTIFICADOR | COLUMN NAME | CL_CM_ALFANUM |
| **Clinical notes**<br>CL_L3_SALUD_TEXTO_CLINICO | COLUMN NAME DATA TYPE | CL_TEXTO_LIBRE |
| **Test results**<br>CL_L3_SALUD_RESULTADO_EXAMEN | COLUMN NAME | CL_CM_ALFANUM |
| **Blood group**<br>CL_L3_SALUD_GRUPO_SANGUINEO | COLUMN NAME VALUE FORMAT | dlpx-core:BloodType SL |
| **Disability**<br>CL_L3_SALUD_DISCAPACIDAD | COLUMN NAME VALUE FORMAT | CL_DISCAPACIDAD |
| **Sexual and reproductive health**<br>CL_L3_SALUD_SEXUAL_REPRODUCTIVA | COLUMN NAME | CL_CATEGORIA_SUPRIMIDA |
| **Mental health and addictions**<br>CL_L3_SALUD_MENTAL_ADICCIONES | COLUMN NAME | CL_CATEGORIA_SUPRIMIDA |
| **Biometric data**<br>CL_L3_BIOMETRICO | COLUMN NAME DATA TYPE | CL_REDACTAR |
| **Genetic profile**<br>CL_L3_PERFIL_GENETICO | COLUMN NAME VALUE FORMAT | CL_REDACTAR |
| **Sexual orientation**<br>CL_L3_ORIENTACION_SEXUAL | COLUMN NAME VALUE FORMAT | CL_ORIENTACION_SEXUAL |
| **Gender identity**<br>CL_L3_IDENTIDAD_GENERO | COLUMN NAME VALUE FORMAT | CL_IDENTIDAD_GENERO |
| **Sexual life**<br>CL_L3_VIDA_SEXUAL | COLUMN NAME | CL_CATEGORIA_SUPRIMIDA |
| **Religion**<br>CL_L3_RELIGION | COLUMN NAME VALUE FORMAT | CL_RELIGION |
| **Ideological convictions**<br>CL_L3_CONVICCION_IDEOLOGICA | COLUMN NAME VALUE FORMAT | CL_IDEOLOGIA |
| **Political affiliation**<br>CL_L3_AFILIACION_POLITICA | COLUMN NAME VALUE FORMAT | CL_PARTIDO_POLITICO |
| **Union affiliation**<br>CL_L3_AFILIACION_SINDICAL | COLUMN NAME | CL_CATEGORIA_SUPRIMIDA |
| **Professional association**<br>CL_L3_AFILIACION_GREMIAL | COLUMN NAME | CL_CATEGORIA_SUPRIMIDA |
| **SOCIOECONOMIC SITUATION** | | |
| **Health insurance and FONASA tier**<br>CL_L3_SOCIOEC_PREVISION_SALUD | COLUMN NAME VALUE FORMAT | CL_PREVISION_SALUD |
| **Health plan**<br>CL_L3_SOCIOEC_PLAN_SALUD | COLUMN NAME | CL_CM_ALFANUM |
| **Registro Social de Hogares**<br>CL_L3_SOCIOEC_RSH | COLUMN NAME | CL_RSH |

| DATA CLASS | FOUND BY | ALGORITHM |
|---|---|---|
| **Socioeconomic group**<br>`CL_L3_SOCIOEC_NIVEL` | COLUMN NAME · KNOWN VALUES | `CL_NIVEL_SOCIOECONOMICO` |
| **State benefits**<br>`CL_L3_SOCIOEC_BENEFICIO_SOCIAL` | COLUMN NAME · VALUE FORMAT | `CL_BENEFICIO_SOCIAL` |
| **Debt and credit status**<br>`CL_L3_SOCIOEC_MOROSIDAD` | COLUMN NAME | `CL_MOROSIDAD` |
| **Debt amounts**<br>`CL_L3_SOCIOEC_MONTO_DEUDA` | COLUMN NAME · DATA TYPE | `dlpx-core:CM Numeric` |
| **Income and salary**<br>`CL_L3_SOCIOEC_INGRESOS` | COLUMN NAME · DATA TYPE | `dlpx-core:CM Numeric` |
| **Pension fund**<br>`CL_L3_SOCIOEC_PREVISION_AFP` | COLUMN NAME · VALUE FORMAT | `CL_AFP` |
| **Pension balances**<br>`CL_L3_SOCIOEC_SALDO_PREVISIONAL` | COLUMN NAME · DATA TYPE | `dlpx-core:CM Numeric` |
| **Housing situation**<br>`CL_L3_SOCIOEC_VIVIENDA` | COLUMN NAME · VALUE FORMAT | `CL_VIVIENDA` |
| **Student aid**<br>`CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS` | COLUMN NAME · VALUE FORMAT | `CL_FINANCIAMIENTO_ESTUDIOS` |
| **CRIMINAL RECORDS** | | |
| **Criminal records**<br>`CL_L3_PENAL_ANTECEDENTES` | COLUMN NAME | `CL_ANTECEDENTES` |
| **Court case numbers**<br>`CL_L3_PENAL_CAUSA` | COLUMN NAME · VALUE FORMAT | `CL_CM_ALFANUM` |

PART 7

# Direct identifiers

Data that identify a person on their own. Masking them is necessary but not enough: the next parts matter as much.

## 7.1 RUT / RUN

CL_L1_RUT

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · STRING ALGORITHM CHAIN

### WHAT IT IS

The national identification number of a person (RUN) and the tax number of a person or company (RUT), with its check digit: `12.345.678-5`, `12345678-5`, `9075310K`. The central identifier of any Chilean database.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_RUT – Path

80% `rut` `run` `r_u_t` `rol_?unico_?(tributario|nacional)?` `n(ro|um|umero)?_?rut` `rut_?(cli|pac|emp|afil|benef|tit|prov|func|trab|usu|pers|cte|contr|deud|aval|repr|alum|est|pro|med|cond|prop|aseg)[a-z]*` `rutcli[a-z]*` `rutpac[a-z]*` `tax_?id` `id_?tributario`

**DATA TYPE** CL_L1_RUT – Type

Accepts text (length 7 or more); any other type rules the data class out.

**VALUE FORMAT** CL_L1_RUT – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:\d{1,2}\.\d{3}\.\d{3}-[\dkK])` | 100% | |
| `0*(?:\d{7,8}-[\dkK])` | 95% | |
| `0*(?:\d{6,8}[kK])` | 90% | |
| `0*(?:\d{3}\.\d{3}-[\dkK])` | 80% | |

A value that matches none counts 20% against the data class.

### HOW IT IS MASKED

The body is masked and the check digit recomputed, so every masked RUT is valid — `K` included — and keeps its format. The mapping is one-to-one: a RUT used as a key cannot collide with another. Text that is not a RUT is masked character by character. See *The RUT check digit*.

`CL_RUT` STRING ALGORITHM CHAIN

Applies `CL_RUT_PASO_1` → `CL_RUT_PASO_2`, in this order.

`CL_RUT_PASO_1` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

`CL_RUT_CUERPO_8` CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3 4 6` from the right.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_RUT_CUERPO_7` CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3 4` from the right.

`CL_RUT_CUERPO_6` CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3` from the right.

`CL_RUT_PASO_2` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CL_RUT_DV_8` **CHECK DIGIT**
>
> Masks the digits with `CL_SIN_CAMBIO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 2 3` from the right.
>
> > `CL_SIN_CAMBIO` **REGEX DECOMPOSE**
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: keep.
>
> `CL_RUT_DV_7` **CHECK DIGIT**
>
> Masks the digits with `CL_SIN_CAMBIO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 2` from the right.
>
> `CL_RUT_DV_6` **CHECK DIGIT**
>
> Masks the digits with `CL_SIN_CAMBIO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7` from the right.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| 12.345.678-5 | → | **46.916.122-6** |
| 9.075.310-K | → | **9.509.079-6** |
| 7654321-6 | → | **9531739-1** |

---

## 7.2 RUT without check digit

`CL_L1_RUT_CUERPO`

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · CHARACTER MAPPING

**WHAT IT IS**

The RUT body stored on its own, usually as a number, with the check digit in another column.

**HOW IT IS FOUND**

> **COLUMN NAME** `CL_L1_RUT_CUERPO – Path`
>
| | |
|---|---|
| 85% | `rut_?(num\|nro\|numero\|cuerpo\|sin_?dv\|sdv\|base\|n)` `n(ro\|um)?_?rut_?sin_?dv` `rutnum` `rut_?sin_?digito` |
| 60% | `rut` `run` |

> **DATA TYPE** `CL_L1_RUT_CUERPO – Type`
>
> Accepts number (length 5 to 10) or text (length 5 to 10); any other type rules the data class out.

> **VALUE FORMAT** `CL_L1_RUT_CUERPO – Regex`
>
| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:\d{1,2}\.?\d{3}\.?\d{3})` | 40% | |
>
> A value that matches none counts 30% against the data class.

**HOW IT IS MASKED**

The digits are mapped exactly like the body of a full RUT, so a person keeps the same masked body whether the RUT is stored whole or split.

`CL_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 12345678 | → | **46916122** |

## 7.3 RUT check digit

CL_L1_RUT_DV

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

### WHAT IT IS

The check digit ( `0` to `9` or `K` ) stored in its own column.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_RUT_DV — Path

**90%** `dv` `d_v` `digito_?verificador` `dig_?verif(icador)?` `dig_?ver` `dv_?(rut|run)` `(rut|run)_?dv` `dvrut` `rutdv` `check_?digit`

**DATA TYPE** CL_L1_RUT_DV — Type

Accepts text (length up to 2) or number (length up to 2); any other type rules the data class out.

**VALUE FORMAT** CL_L1_RUT_DV — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[\dkK]` | 30% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Replaced by a check digit chosen by hash. The column cannot see the body, so the pair body + check digit is no longer valid; where the application validates it, mask the concatenated RUT instead.

`CL_RUT_DV` SECURE LOOKUP

Replaces the value with one of the 11 values in `cl-digito-verificador.txt` , chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| K | → | **9** |

## 7.4 Given names

CL_L1_NOMBRE

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

### WHAT IT IS

First and middle names ( `NOMBRES` , `PRIMER_NOMBRE` ), including the social name of Ley 21.120.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_NOMBRE — Path

**85%** `primer_?nombre` `segundo_?nombre` `nombres?_?pila` `nombre_?social` `first_?name` `given_?names?` `fname` `name_?first` `middle_?name` `nombre[12]` `nombres` *(except when followed by list E1)*

**50%** `nombre` *(except when followed by list E2)* `nomb?` *(except when followed by list E3)* `name` *(except when followed by list E4)*

KNOWN VALUES CL_L1_NOMBRE — List

| LIST | VALUES | STRENGTH | FIRST VALUES |
|---|---|---|---|
| cl-detectar-nombres.txt | 229 | 70% | María, Maria, José, Jose, Juan, Luis |

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word is replaced by a Chilean given name, keeping the capitalization. Accents do not change the choice, so José and JOSE mask alike.

CL_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM.

CL_NOMBRE_PILA NAME

Replaces the name with one of the 189 names in cl-nombres.txt.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| María José | → | Waldo Sebastián |
| JUAN | → | EMILIANO |

## 7.5 Surnames

CL_L1_APELLIDO

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Paternal and maternal surnames, together or in separate columns.

HOW IT IS FOUND

COLUMN NAME CL_L1_APELLIDO — Path

85% apellidos? apellido_?(paterno|materno|pat|mat|uno|dos|[12]) ape_?(pat|mat|paterno|materno|[12]) apepat apemat appat apmat ap_?(pat|mat|paterno|materno) a_?paterno a_?materno paterno materno last_?name surname lname family_?name second_?last_?name mother_?last_?name

KNOWN VALUES CL_L1_APELLIDO — List

| LIST | VALUES | STRENGTH | FIRST VALUES |
|---|---|---|---|
| cl-detectar-apellidos.txt | 245 | 70% | González, Gonzalez, Muñoz, Munoz, Rojas, Díaz |

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word is replaced by a Chilean surname — the list includes Mapuche, Aymara and Rapa Nui surnames.

CL_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM.

CL_APELLIDO NAME

Replaces the name with one of the 194 names in cl-apellidos.txt.

CL_CM_ALFANUM CHARACTER MAPPING

> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Muñoz Rojas` | → | **`Navarrete Lara`** |

## 7.6 Full name

`CL_L1_NOMBRE_COMPLETO`

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

### WHAT IT IS

A person's whole name in one column: holders, patients, customers, emergency contacts, legal representatives.

### HOW IT IS FOUND

> **COLUMN NAME** `CL_L1_NOMBRE_COMPLETO` – Path
>
> **90%** `nombre_?(completo|compl|full)` `nombres?_?y_?apellidos?` `nombres?_?apellidos?` `nombreapellido` `nom_?completo` `nomcompleto` `nombrecompleto` `full_?name` `fullname` `person_?name` `customer_?name` `employee_?name` `patient_?name` `nombre_?(cliente|cli|paciente|pac|trabajador|trab|funcionario|func|alumno|estudiante|afiliado|beneficiario|titular|madre|padre|tutor|apoderado|conyuge|pareja|medico|doctor|profesional|responsable|contacto|emergencia|aval|codeudor|deudor|remitente|destinatario|receptor|firmante|testigo|representante|propietario|arrendatario|asegurado|contratante|victima|denunciante|imputado|socio|donante|heredero|causante|persona|pers|conductor|chofer|vendedor|ejecutivo|agente|empleado|colaborador)`
>
> **60%** `titular` `beneficiario` `contacto_?emergencia` `conyuge` `apoderado` `tutor_?legal` `representante_?legal` `paciente` `victima` `asegurado` `contratante` `razon_?social_?persona`
>
> **50%** `nombre` *(except when followed by list E2)* `name` *(except when followed by list E4)*

> **KNOWN VALUES** `CL_L1_NOMBRE_COMPLETO` – List
>
| LIST | VALUES | STRENGTH | FIRST VALUES |
|---|---|---|---|
| `cl-detectar-nombres.txt` | 229 | 65% | María, Maria, José, Jose, Juan, Luis |
| `cl-detectar-apellidos.txt` | 245 | 65% | González, Gonzalez, Muñoz, Munoz, Rojas, Díaz |
>
> Values are split into words, and each word is looked up.
>
> A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Follows the Chilean order — given names, then paternal and maternal surname — so `Juan Carlos Pérez González` gets two given names and two surnames. The form `APELLIDOS, NOMBRES` is recognized too; values of six words or more are masked character by character.

`CL_NOMBRE_COMPLETO` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

> `CL_APELLIDOS` REGEX DECOMPOSE
>
> Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .
>
> > `CL_APELLIDO` NAME
> >
> > Replaces the name with one of the 194 names in `cl-apellidos.txt` .
> >
> > `CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_NOMBRES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

`CL_NOMBRE_PILA` NAME

Replaces the name with one of the 189 names in `cl-nombres.txt` .

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Juan Carlos Pérez González | → | **Emiliano Lissette Salas Bello** |
| GONZÁLEZ ROJAS, ANA MARÍA | → | **BELLO LARA, ARIEL WALDO** |

## 7.7 E-mail address

CL_L1_EMAIL

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

COLUMN NAME CL_L1_EMAIL — Path

85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electronico)?[a-z0-9_]*` `casilla(_?electronica)?` `email_?address`

DATA TYPE CL_L1_EMAIL — Type

Accepts text (length 5 or more); any other type rules the data class out.

VALUE FORMAT CL_L1_EMAIL — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}` | 100% | |

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

Name and domain are mapped character by character, so distinct addresses stay distinct, and the top-level domain becomes `.test` , reserved for testing: a masked address can never receive mail.

`CL_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| juan.perez@gmail.com | → | **opfu.yayah@vyaiu.test** |

## 7.8 Telephone

CL_L1_TELEFONO

ESSENTIAL COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Mobile and landline numbers in the usual formats: `+56 9 8765 4321` , `987654321` , `(2) 2345 6789` .

HOW IT IS FOUND

**COLUMN NAME** CL_L1_TELEFONO — Path

85% `tel` `telefono[a-z0-9_]*` `tel[eé]fono` `fono[a-z0-9_]*` `celular[a-z0-9_]*` `cel` `movil` `m[oó]vil` `whatsapp` `wsp` `fax` `phone[a-z0-9_]*` `mobile` `cellphone` `n(ro|um)_?tel(efono)?` `telef` `tlf` `tfno` `anexo`

**VALUE FORMAT** CL_L1_TELEFONO — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:(\+?56[\s\-]?)?9[\s\-]?\d{4}[\s\-]?\d{4})` | 90% | |
| `0*(?:(\+?56[\s\-]?)?\(?(2\|[3-7]\d)\)?[\s\-]?\d{3,4}[\s\-]?\d{4})` | 70% | |
| `0*(?:\+?\d[\d\s()\-]{7,15})` | 30% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The country code, the mobile `9` and the area code stay; the subscriber digits are masked. The number keeps its format and still looks Chilean.

`CL_TELEFONO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| +56 9 8765 4321 | → | **+56 9 3134 0400** |
| (2) 2345 6789 | → | **(2) 8099 7290** |

---

## 7.9 Street address

CL_L1_DIRECCION

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

Street, number and apartment written in one column.

HOW IT IS FOUND

**COLUMN NAME** CL_L1_DIRECCION — Path

80% `direccion[a-z_]*` *(except when followed by list E5)* `direcci[oó]n` `dir` `domicilio[a-z_]*` `calle` `avenida` `pasaje` `address` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`)* `street` `addr` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`)* `dir_?(particular|comercial|laboral|envio|despacho|facturacion|cliente|paciente|trabajo)` `residencia` `villa` `poblacion` `lugar_?residencia` `home_?address`

**DATA TYPE** CL_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the data class out.

VALUE FORMAT CL_L1_DIRECCION — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `(?i)(av(enida)?\.?\|calle\|pasaje\|psje\.?\|pje\.?\|camino\|diagonal\|villa\|poblaci[oó]n\|block)\s+.+\d+.*` | 80% | |
| `[A-Za-zÁÉÍÓÚÑáéíóúñ'.]{2,}(\s+[A-Za-zÁÉÍÓÚÑáéíóúñ'.]+)+\s+#?\d{1,5}(\s*,?\s*(depto\|dpto\|dep\|of\|oficina\|casa\|block)\.?\s*\w+)?` | 60% | |
| `[A-Za-zÁÉÍÓÚÑáéíóúñ'.\s]{4,}\s#?\d{1,5}(\s*,?\s*(depto\|dpto\|dep\|of\|oficina\|casa\|block)\.?\s*\w+)?` | 40% | |

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

Replaced by a fictitious Chilean address from a list of 3,000 built from street names common in Chile, house numbers and apartments.

`CL_DIRECCION` SECURE LOOKUP

Replaces the value with one of the 3,000 values in `cl-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Av. Providencia 1234, depto 502` | → | **`Calle Lord Cochrane 13401, depto 208`** |

## 7.10 Address details

CL_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Apartment, block, tower, house or lot number kept apart from the street.

HOW IT IS FOUND

COLUMN NAME CL_L1_DIRECCION_COMPLEMENTO — Path

70% `depto` `dpto` `n(ro|um)_?depto` `block` `torre` `casa_?(num|nro)` `n(ro|um|umero)_?casa` `n(ro|um|umero)_?domicilio` `numeracion` `n(ro|um|umero)_?calle` `house_?number` `apartment` `apt` `unit_?number` `lote` `sitio` `parcela` `manzana`

HOW IT IS MASKED

Characters are mapped within their kind: digits to digits, letters to letters.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Block B 402` | → | **`Ewtas F 299`** |

## 7.11 Identity card document number

CL_L1_NUMERO_DOCUMENTO

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

### WHAT IT IS

The document number of the cédula de identidad — different from the RUN, often forgotten, and enough on its own to identify the card and its holder.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_NUMERO_DOCUMENTO — Path

| | |
|---|---|
| 85% | `(n(ro\|um\|umero)?_?)?serie_?(ci\|cedula\|carnet\|documento\|identidad)?` `serie_?ci` `n(ro\|um\|umero)_?serie` `folio_?(ci\|cedula\|carnet)` `n(ro\|um\|umero)_?(de_?)?documento_?(identidad\|ci\|cedula)` `n(ro\|um\|umero)_?(cedula\|carnet\|ci)` `document_?number` |
| 60% | `n(ro\|um\|umero)_?(de_?)?(documento\|doc)` `documento_?identidad` `cedula` `carnet` |

**VALUE FORMAT** CL_L1_NUMERO_DOCUMENTO — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:\d{3}\.\d{3}\.\d{3})` | 60% | |
| `[A-Za-z]\d{9}` | 40% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 123.456.789 | → | **110.858.568** |

---

## 7.12 Passport

CL_L1_PASAPORTE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

### WHAT IT IS

Chilean and foreign passport numbers.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_PASAPORTE — Path

| | |
|---|---|
| 85% | `pasaporte[a-z_]*` `passport[a-z_]*` `n(ro\|um\|umero)_?pasaporte` `pasap` |

**VALUE FORMAT** CL_L1_PASAPORTE — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[A-Za-z]{1,2}\d{6,9}` | 30% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| F12345678 | → | **E92994949** |

## 7.13 Foreign identity documents

CL_L1_DOCUMENTO_EXTRANJERO

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

DNI, foreign identity cards, visa and residence permit numbers.

HOW IT IS FOUND

COLUMN NAME CL_L1_DOCUMENTO_EXTRANJERO — Path

80% `dni` `doc_?extranjero` `documento_?extranjero` `id_?extranjero` `cedula_?extranjera` `n(ro|um|umero)_?identificacion` `identificacion_?extranjera` `ci_?extranjera` `nie` `n(ro|um)_?visa` `permiso_?residencia` `residencia_?definitiva` `id_?nacional` `national_?id`

HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| AB1234567 | → | **CA5960766** |

## 7.14 Bank account

CL_L1_CUENTA_BANCARIA

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Checking, vista (CuentaRUT included) and savings account numbers.

HOW IT IS FOUND

COLUMN NAME CL_L1_CUENTA_BANCARIA — Path

85% `cuenta_?(corriente|vista|rut|bancaria|banco|ahorro|deposito|abono|pago|destino|origen|cte)` `cta_?(cte|corriente|vista|bancaria|banco|ahorro)` `ctacte` `n(ro|um|umero)?_?cuenta(_?(banco|bancaria|corriente|vista))?` `account_?(number|no|num|nbr)` `bank_?account`

HOW IT IS MASKED

Digits are mapped to digits, keeping the length and the separators.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 00-123-45678-09 | → | **00-101-66386-75** |

## 7.15 Payment card

CL_L1_TARJETA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, with or without spaces.

HOW IT IS FOUND

COLUMN NAME CL_L1_TARJETA – Path

85% `tarjeta(_?(credito|debito|cred|deb|num|nro|numero))?` `n(ro|um|umero)_?tarjeta` `pan` `card_?(number|no|num)` `credit_?card` `cc_?(number|num)` `tdc` `tc_?num`

VALUE FORMAT CL_L1_TARJETA – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:3[47]\d{13}\|[1-9]\d{12,13}\|[1-9]\d{15,18})` | 90% | LUHN check digit; after removing `[\s\-]` |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Credit Card, which comes with Delphix: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`CL_TARJETA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with Delphix and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 4111 1111 1111 1111 | → | **4111 1167 2943 6826** |

## 7.16 IP address

CL_L1_IP

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses — personal data when they relate to a person.

HOW IT IS FOUND

COLUMN NAME CL_L1_IP – Path

85% `ip` `ip_?(address|addr|origen|destino|cliente|usuario|remota|publica|privada|acceso|conexion|login)` `direccion_?ip` `dir_?ip` `ipv[46]` `remote_?addr` `client_?ip` `host_?ip`

VALUE FORMAT CL_L1_IP – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:((25[0-5]\|2[0-4]\d\|1?\d?\d)\.){3}(25[0-5]\|2[0-4]\d\|1?\d?\d))` | 100% | |
| `0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})` | 90% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each IPv4 octet is mapped to a value from 1 to 254, so the address stays valid; IPv6 hex digits are mapped to hex digits.

`CL_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

`CL_OCTETO` NUMERIC MAPPING

Maps the number to another between 1 and 254.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `200.27.1.10` | → | **`146.92.9.16`** |

## 7.17 Device identifiers

CL_L1_DISPOSITIVO

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, device and advertising identifiers, cookie and session identifiers.

HOW IT IS FOUND

COLUMN NAME CL_L1_DISPOSITIVO – Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `direccion_?mac` `device_?id` `id_?dispositivo` `dispositivo_?id` `uuid_?dispositivo` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `id_?sesion` `fingerprint_?dispositivo` `serial_?equipo` `n(ro|um)_?serie_?equipo`

VALUE FORMAT CL_L1_DISPOSITIVO – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})` | 100% | |
| `0*(?:\d{15})` | 80% | LUHN check digit |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Characters are mapped within their kind; hex letters stay hex, so a MAC address remains well formed.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `3c:22:fb:9a:10:e4` | → | **`5e:83:bb:3c:31:f9`** |

## 7.18 Vehicle plate

CL_L1_PATENTE

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

### WHAT IT IS

The Placa Patente Única in its formats: `BBBB·10` since 2007, `AA·1000` before it, and motorcycle plates.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_PATENTE – Path

85% `patente(_?(vehiculo|auto|unica|nro|num))?` `placa(_?patente)?` `ppu` `matricula_?(vehiculo|auto)` `license_?plate` `plate(_?number)?` `n(ro|um)_?patente`

**VALUE FORMAT** CL_L1_PATENTE – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[BCDFGHJKLPRSTVWXYZ]{4}[\s·.\-]?\d{2}` | 100% | |
| `[A-Z]{2}[\s·.\-]?\d{2}[\s·.\-]?\d{2}` | 60% | |
| `[BCDFGHJKLPRSTVWXYZ]{3}[\s·.\-]?\d{2}` | 60% | |
| `[BCDFGHJKLPRSTVWXYZ]{4,5}[\s·.\-]?\d` | 50% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Consonants map to consonants and digits to digits, so a masked plate uses only the letters Chilean plates allow.

`CL_PATENTE` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| BBCD-12 | → | **TYRP-90** |

---

## 7.19 Chassis and engine numbers

CL_L1_VEHICULO_ID

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

### WHAT IT IS

VIN, chassis and engine numbers, which lead to the owner through the vehicle registry.

### HOW IT IS FOUND

**COLUMN NAME** CL_L1_VEHICULO_ID – Path

80% `vin` `chasis` `n(ro|um|umero)_?chasis` `n(ro|um|umero)_?motor` `serie_?motor` `vin_?number`

**VALUE FORMAT** CL_L1_VEHICULO_ID – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[A-HJ-NPR-Z0-9]{17}` | 70% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 9BWZZZ377VT004251 | → | **2AMXKX175PS632677** |

## 7.20 Contract and policy numbers

CL_L1_NUMERO_CONTRATO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Contract, insurance policy, credit operation, member and customer numbers that point to one person.

HOW IT IS FOUND

COLUMN NAME CL_L1_NUMERO_CONTRATO — Path

70% `contrato` `n(ro|um|umero)_?contrato` `p[oó]liza` `n(ro|um|umero)_?poliza` `n(ro|um)_?operacion` `operacion_?credito` `n(ro|um)_?credito` `n(ro|um|umero)_?socio` `n(ro|um|umero)_?cliente` `cod(igo)?_?cliente` `n(ro|um|umero)_?afiliado` `folio_?(contrato|poliza|credito)` `n(ro|um)_?siniestro` `n(ro|um)_?beneficiario` `n(ro|um)_?matricula` `matricula_?alumno` `n(ro|um)_?carnet_?(socio|afiliado)`

HOW IT IS MASKED

Characters are mapped within their kind. The same number masks the same way in every table and system, so relations between them survive.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| POL-123456 | → | **JWH-982973** |

## 7.21 Usernames and social profiles

CL_L1_USUARIO_RRSS

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Logins, aliases and social network handles.

HOW IT IS FOUND

COLUMN NAME CL_L1_USUARIO_RRSS — Path

70% `usuario` `username` `user_?name` `login` `nick(name)?` `alias` `cuenta_?usuario` `usr` `facebook` `instagram` `twitter` `tiktok` `linkedin` `red_?social` `perfil_?(facebook|instagram|twitter|linkedin)` `skype` `telegram` `handle`

HOW IT IS MASKED

Characters are mapped within their kind.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `@maria_munoz` | → | **`@uewma_sumvv`** |

## 7.22 Passwords and secrets

CL_L1_CREDENCIAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Passwords, password hashes, PINs, tokens, API keys and security answers — which should not be in a non-production copy at all.

HOW IT IS FOUND

COLUMN NAME CL_L1_CREDENCIAL – Path

**90%** `password` `passwd` `pwd` `pass` `contrasen[aã]` `contraseña` `clave[a-z_]*` *(except when followed by list E6)*

`pin` `hash_?password` `password_?hash` `secret` `token_?acceso` `access_?token` `refresh_?token`

`api_?key` `otp` `respuesta_?secreta` `pregunta_?secreta`

VALUE FORMAT CL_L1_CREDENCIAL – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}` | 95% | |
| `\$(1\|5\|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}` | 95% | |
| `\$argon2(id\|i\|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+` | 95% | |
| `pbkdf2_sha(1\|256\|512)\$\d+\$\S+\$\S+` | 95% | |
| `\{(SSHA\|SHA\|SSHA256\|SSHA512\|SMD5\|MD5\|CRYPT)\}\S+` | 95% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character is replaced by `X`.

`CL_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Secreta#2024` | → | **`XXXXXXXXXXX`** |

## 7.23 Geolocation

CL_L1_GEOLOCALIZACION

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Latitude, longitude and coordinate pairs.

HOW IT IS FOUND

**COLUMN NAME** CL_L1_GEOLOCALIZACION – Path

85% `lat` `latitud` `latitude` `lon` `lng` `longitude` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `geolocalizacion` `ubicacion_?gps` `gps` `posicion_?gps`

50% `longitud` `long`

**VALUE FORMAT** CL_L1_GEOLOCALIZACION – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `-?\d{1,2}\.\d{3,}\s*,\s*-?\d{1,3}\.\d{3,}` | 90% | |
| `-(1[7-9]\|[2-5]\d)\.\d{3,}` | 70% | |
| `-(6[6-9]\|7\d\|8[01]\|109)\.\d{3,}` | 70% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The integer part and the first decimal stay — about 11 km — and the remaining decimals are masked: the place is generalized, not moved to another region.

`CL_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| -33.448891,-70.669265 | → | **-33.438766,-70.677404** |

## 7.24 Free text

CL_L1_TEXTO_LIBRE

**COLUMN NAME** **DATA TYPE** **VALUE FORMAT** **FREE TEXT REDACTION**

WHAT IT IS

Observations, comments and descriptions where people write RUTs, e-mails, phone numbers and names. Found by the column name, or by identifiers inside the text.

HOW IT IS FOUND

**COLUMN NAME** CL_L1_TEXTO_LIBRE – Path

60% `observaciones?` `obs` `comentarios?` `glosa` `notas?` `detalle` `descripcion_?(caso|reclamo|incidente|solicitud|problema|atencion)` `texto_?libre` `mensaje` `reclamo` `consulta_?texto` `motivo_?(texto|detalle)` `narrativa` `relato` `resumen_?caso` `remarks` `comments?` `notes?` `free_?text` `memo`

**DATA TYPE** CL_L1_TEXTO_LIBRE – Type

Accepts text (length 30 or more); any other type rules the data class out.

**VALUE FORMAT** CL_L1_TEXTO_LIBRE — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:\d{1,2}\.\d{3}\.\d{3}-[\dkK])` | 70% | anywhere in the value |
| `[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}` | 70% | anywhere in the value |
| `0*(?:(\+?56\s?)?9\s?\d{4}\s?\d{4})` | 50% | anywhere in the value |

A value that matches none does not count against the data class.

### HOW IT IS MASKED

RUTs, e-mails, phone numbers written without spaces, plates, card numbers and IP addresses become `[DATO]`; given names and surnames from the lists become `[NOMBRE]`. The rest of the text stays readable.

`CL_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with `[DATO]`, and the 948 terms of `cl-texto-nombres.txt` with `[NOMBRE]`.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Cliente Soto, RUT 12.345.678-5, correo p.soto@gmail.com, fono 987654321.` | → | **`Cliente [NOMBRE], RUT [DATO], correo [DATO], fono [DATO].`** |

PART 8

# Quasi-identifiers

Data that identify no one alone but do in combination: birth date, sex and comuna single out most people, and Chile has many comunas of a few thousand inhabitants. These attributes are generalized or shifted rather than replaced, so the data keep their analytical value.

## 8.1 Date of birth

CL_L2_FECHA_NACIMIENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

### WHAT IT IS

The most important quasi-identifier: with sex and comuna, it re-identifies a large share of the population.

### HOW IT IS FOUND

**COLUMN NAME** CL_L2_FECHA_NACIMIENTO – Path

90% `fecha_?(de_?)?nac(imiento)?` `fec_?nac(imiento)?` `f_?nac(imiento|im)?` `fnac` `fechanac(imiento)?` `fecnac` `nacimiento` `fch_?nac` `dob` `birth_?date` `date_?of_?birth` `birthdate` `birthday` `cumplea(n|ñ)os`

**DATA TYPE** CL_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

### HOW IT IS MASKED

Shifted by up to 60 days: enough to break the link with the person, small enough that ages and school years barely move.

`CL_FECHA_NACIMIENTO` DATE SHIFT

Moves the date by -60 to 60 days.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 1985-07-20 | → | **1985-08-05T00:00** |

## 8.2 Year of birth

CL_L2_ANIO_NACIMIENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

### WHAT IT IS

The year of birth stored on its own, usually as a number.

### HOW IT IS FOUND

**COLUMN NAME** CL_L2_ANIO_NACIMIENTO – Path

90% `an(i)?o_?nac(imiento)?` `año_?nac(imiento)?` `birth_?year` `year_?of_?birth` `ano_?nacim`

**DATA TYPE** CL_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

### HOW IT IS MASKED

The decade stays and the last digit is masked: `1985` becomes a year of the 1980s.

`CL_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `CL_CM_ALFANUM` **CHARACTER MAPPING**
> Maps each character to another of its group (7 groups), keeping length and format.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| 1985 | → | **1980** |

---

## 8.3 Age

CL_L2_EDAD

**COLUMN NAME** **DATA TYPE** **REGEX DECOMPOSE**

**WHAT IT IS**

Age in years.

**HOW IT IS FOUND**

> **COLUMN NAME** CL_L2_EDAD — Path
>
> 85% `edad(_?(actual|paciente|cliente|afiliado|beneficiario|ingreso|anos|años))?` `age` `anos_?edad` `rango_?etario` `edad_?en_?anos`

> **DATA TYPE** CL_L2_EDAD — Type
> Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

**HOW IT IS MASKED**

The decade stays and the unit is masked — 37 becomes an age in the thirties. Ages of 100 and over become 90: extreme ages identify on their own.

`CL_EDAD` **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CL_CM_ALFANUM` **CHARACTER MAPPING**
> Maps each character to another of its group (7 groups), keeping length and format.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| 37 | → | **35** |
| 104 | → | **90** |

---

## 8.4 Personal event dates

CL_L2_FECHA_EVENTO

**COLUMN NAME** **DATA TYPE** **DATE SHIFT**

**WHAT IT IS**

Dates of death, marriage, hiring, dismissal, hospital admission and discharge, diagnosis, childbirth or arrest.

HOW IT IS FOUND

COLUMN NAME CL_L2_FECHA_EVENTO – Path

80% `fecha_?(de_?)?(defuncion|fallecimiento|muerte|matrimonio|casamiento|divorcio|ingreso_?(laboral|empresa|trabajo)|contratacion|contrato|egreso|despido|desvinculacion|renuncia|jubilacion|pension|licencia|hospitalizacion|alta_?medica|diagnostico|atencion|consulta|parto|embarazo|detencion|condena|vacunacion|cirugia|examen)` `fec_?(defuncion|ingreso_?laboral|egreso|contrato|alta|atencion|diagnostico)` `death_?date` `hire_?date` `termination_?date` `date_?of_?death` `admission_?date` `discharge_?date`

DATA TYPE CL_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted by up to 30 days.

`CL_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 2021-03-15 | → | **2021-03-05T00:00** |

## 8.5 Sex

CL_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Registered sex or gender, as a letter or a word.

HOW IT IS FOUND

COLUMN NAME CL_L2_SEXO – Path

85% `sexo(_?(biologico|registral|paciente|cliente))?` `sex` `g[eé]nero` *(except when followed by* `identidad`, `social`, `autopercibido`*)* `gender` `cod_?sexo`

KNOWN VALUES CL_L2_SEXO – List

| LIST | VALUES | STRENGTH | FIRST VALUES |
|---|---|---|---|
| `cl-detectar-sexo.txt` | 8 | 80% | femenino, masculino, mujer, hombre, female, male |
| `cl-detectar-sexo-letra.txt` | 3 | 60% | f, m, h |

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the data class.

HOW IT IS MASKED

Replaced within its own vocabulary — F/M, H/M, Femenino/Masculino, Mujer/Hombre — so the column keeps its values. Values outside these vocabularies stay.

`CL_SEXO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_SEXO_PALABRA` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-palabra.txt`, chosen by a keyed hash.

`CL_SEXO_MUJER_HOMBRE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-mujer-hombre.txt`, chosen by a keyed hash.

`CL_SEXO_INGLES` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-ingles.txt`, chosen by a keyed hash.

`CL_SEXO_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-f-m.txt`, chosen by a keyed hash.

`CL_SEXO_H_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-h-m.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| F | → | **M** |
| Masculino | → | **Femenino** |

## 8.6 Comuna

CL_L2_COMUNA

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

### WHAT IT IS

Chile has 346 comunas, many with a few thousand inhabitants: a small comuna and a birth date can point to one person.

### HOW IT IS FOUND

COLUMN NAME — CL_L2_COMUNA — Path

| | |
|---|---|
| 85% | `comuna[a-z_]*` `nom(bre)?_?comuna` `municipio` `municipalidad` `localidad` |
| 60% | `ciudad[a-z_]*` `city` `town` |

VALUE FORMAT — CL_L2_COMUNA — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 346 known values, ignoring case — Arica, Camarones, Putre, General Lagos, Iquique, Alto Hospicio, … | 90% | |

A value that matches none counts 40% against the data class.

### HOW IT IS MASKED

Comunas under 20,000 inhabitants (Censo 2024) become the most populous comuna of their province — or of their region, when that one is small too. Larger comunas stay. The result is still a real comuna. Names written without accents or ñ are recognized; other spellings pass unchanged.

`CL_COMUNA` DATA CLEANSING

Replaces each value found in `cl-comuna-generalizada.txt` (428 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Torres del Paine | → | **Natales** |
| Nunoa | → | **Ñuñoa** |

## 8.7 Comuna code

CL_L2_CODIGO_COMUNA

COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The Código Único Territorial (CUT) of the comuna, with or without the leading zero.

HOW IT IS FOUND

COLUMN NAME CL_L2_CODIGO_COMUNA – Path

85% `cod(igo)?_?comuna` `id_?comuna` `cut(_?comuna)?` `comuna_?(cod|codigo|id|cut)` `cod_?com`

DATA TYPE CL_L2_CODIGO_COMUNA – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

VALUE FORMAT CL_L2_CODIGO_COMUNA – Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 552 known values, ignoring case — 15101, 15102, 15201, 15202, 01101, 1101, … | 60% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Generalized exactly like the comuna name.

`CL_CODIGO_COMUNA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`CL_CODIGO_COMUNA_TABLA` DATA CLEANSING

Replaces each value found in `cl-codigo-comuna-generalizado.txt` (346 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 12402 | → | **12401** |

## 8.8 Postal code

CL_L2_CODIGO_POSTAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Seven digits: the first three identify the comuna, the last four the block front.

HOW IT IS FOUND

COLUMN NAME CL_L2_CODIGO_POSTAL – Path

90% `cod(igo)?_?postal` `cp` `zip(_?code)?` `postal_?code` `codpostal` `c_?postal`

VALUE FORMAT CL_L2_CODIGO_POSTAL – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `0*(?:\d{7})` | 20% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The comuna part stays and the block part becomes `0000`.

`CL_CODIGO_POSTAL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

`CL_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| 8320123 | → | **8320000** |

## 8.9 Nationality

`CL_L2_NACIONALIDAD`

**COLUMN NAME** **KNOWN VALUES** **SECURE LOOKUP**

**WHAT IT IS**

Nationality or country of birth — identifying where few foreigners live in a comuna.

**HOW IT IS FOUND**

**COLUMN NAME** `CL_L2_NACIONALIDAD – Path`

**80%** `nacionalidad` `nationality` `pais_?(de_?)?(nacimiento|origen)` `ciudadania` `citizenship` `country_?of_?birth`

**KNOWN VALUES** `CL_L2_NACIONALIDAD – List`

| LIST | VALUES | STRENGTH | FIRST VALUES |
|---|---|---|---|
| `cl-detectar-nacionalidades.txt` | 48 | 70% | Chilena, Venezolana, Peruana, Haitiana, Colombiana, Boliviana |

Values are split into words, and each word is looked up.

A value that matches none counts 40% against the data class.

**HOW IT IS MASKED**

Replaced by one of the nationalities most present in Chile.

`CL_NACIONALIDAD` **SECURE LOOKUP**

Replaces the value with one of the 17 values in `cl-nacionalidades.txt`, chosen by a keyed hash.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| Peruana | → | **Ecuatoriana** |

## 8.10 Marital status

`CL_L2_ESTADO_CIVIL`

**COLUMN NAME** **VALUE FORMAT** **SECURE LOOKUP**

**WHAT IT IS**

Marital status, including the acuerdo de unión civil.

**HOW IT IS FOUND**

**COLUMN NAME** `CL_L2_ESTADO_CIVIL – Path`

**85%** `estado_?civil` `est_?civil` `ecivil` `marital_?status` `civil_?status` `situacion_?conyugal`

**VALUE FORMAT** `CL_L2_ESTADO_CIVIL – Values`

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 21 known values, ignoring case — soltero, soltera, casado, casada, viudo, viuda, … | 70% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced from the list of marital statuses.

`CL_ESTADO_CIVIL` SECURE LOOKUP

Replaces the value with one of the 6 values in `cl-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Casada | → | **Viudo** |

## 8.11 Occupation and position

CL_L2_OCUPACION

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Job titles and professions. A rare title — `Gerente Regional Aysén` — is unique in a company.

HOW IT IS FOUND

> COLUMN NAME CL_L2_OCUPACION — Path
>
> 80% `cargo` *(except when followed by list E7)* `ocupaci[oó]n` `profesi[oó]n` `oficio` `puesto(_?trabajo)?` `job_?title` `occupation` `actividad_?laboral` `titulo_?profesional`

HOW IT IS MASKED

Replaced by a generic occupation.

`CL_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 40 values in `cl-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Gerente Regional Aysén | → | **Administrativo** |

## 8.12 Employer

CL_L2_EMPLEADOR

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The company or institution a person works for.

HOW IT IS FOUND

> COLUMN NAME CL_L2_EMPLEADOR — Path
>
> 80% `empleador` `nombre_?empleador` `razon_?social_?empleador` `empresa_?(empleadora|trabajo|laboral)` `lugar_?(de_?)?trabajo` `employer` `institucion_?laboral`

HOW IT IS MASKED

Replaced by a fictitious employer.

`CL_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 25 values in `cl-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Codelco | → | **Maderas del Sur SpA** |

## 8.13 Education level

CL_L2_NIVEL_EDUCACIONAL

COLUMN NAME · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

Education level and years of schooling.

HOW IT IS FOUND

COLUMN NAME CL_L2_NIVEL_EDUCACIONAL — Path

80% `nivel_?educa(cional|tivo)` `escolaridad` `nivel_?estudios` `education_?level` `grado_?academico` `anos_?escolaridad`

VALUE FORMAT CL_L2_NIVEL_EDUCACIONAL — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 20 known values, ignoring case — Sin estudios, Básica incompleta, Básica completa, Media incompleta, Media completa, Técnico nivel superior incompleta, … | 60% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced from the list of education levels.

`CL_NIVEL_EDUCACIONAL` SECURE LOOKUP

Replaces the value with one of the 10 values in `cl-nivel-educacional.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Media completa | → | **Media completa** |

## 8.14 School or university

CL_L2_ESTABLECIMIENTO_EDUCACIONAL

COLUMN NAME · SECURE LOOKUP

WHAT IT IS

The school, institute or university a person attends or attended.

HOW IT IS FOUND

COLUMN NAME CL_L2_ESTABLECIMIENTO_EDUCACIONAL — Path

75% `colegio` `liceo` `escuela` `establecimiento_?(educacional|estudio|escolar)` `nombre_?(colegio|escuela|liceo)` `universidad` `casa_?de_?estudios` `school(_?name)?` `jardin_?infantil` `sala_?cuna`

HOW IT IS MASKED

Replaced by a fictitious establishment.

`CL_ESTABLECIMIENTO` SECURE LOOKUP

Replaces the value with one of the 15 values in `cl-establecimientos.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Liceo Bicentenario de Excelencia | → | **Escuela Básica N° 12** |

## 8.15 Dependants

CL_L2_CARGAS_FAMILIARES

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Number of family dependants, children or household members. Large families are rare, and therefore identifying.

HOW IT IS FOUND

> COLUMN NAME CL_L2_CARGAS_FAMILIARES — Path
>
> 80% `cargas?_?familiares?` `n(ro|um)?_?cargas` `cantidad_?cargas` `n(ro|um|umero)?_?hijos` `cant_?hijos` `hijos` `integrantes_?(grupo_?)?(familiar|hogar)` `n(ro|um)_?integrantes` `tamano_?hogar` `personas_?(en_?)?hogar`

> DATA TYPE CL_L2_CARGAS_FAMILIARES — Type
>
> Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

Capped at 5.

`CL_CANTIDAD_ACOTADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 9 | → | **5** |

PART 9

# Sensitive data

The categories of article 2 letter g: ethnic origin, health and human biological profile, biometrics, sexual life, sexual orientation and gender identity, religious and ideological convictions, political, union and professional affiliation. A categorical value is replaced by another of the same category, so the column keeps a realistic content; where the values share no vocabulary, they are suppressed.

## 9.1 Indigenous peoples and ethnic origin

CL_L3_ETNIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

### WHAT IT IS

Belonging to one of the peoples recognized by Ley 19.253 — Mapuche, Aymara, Rapa Nui, Lickanantay, Quechua, Colla, Diaguita, Chango, Kawésqar, Yagán, Selk'nam — or to the Chilean Afro-descendant tribal people.

### HOW IT IS FOUND

COLUMN NAME — CL_L3_ETNIA – Path

90% `etnia` `[eé]tnico` `origen_?[eé]tnico` `pueblo_?(originario|ind[ií]gena|orig)` `pertenencia_?(etnica|indigena|pueblo)` `calidad_?indigena` `ind[ií]gena` `raza` `race` `ethnicity` `ethnic_?group` `ascendencia` `afrodescendiente` `comunidad_?indigena`

VALUE FORMAT — CL_L3_ETNIA – Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 38 known values, ignoring case — Mapuche, Aymara, Rapa Nui, Lickanantay, Quechua, Colla, … | 90% | |

A value that matches none counts 40% against the data class.

### HOW IT IS MASKED

Replaced by another value of the list; yes/no flags stay flags and numeric codes get other digits.

`CL_PUEBLO_ORIGINARIO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_PUEBLO_ORIGINARIO_LISTA`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_PUEBLO_ORIGINARIO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 13 values in `cl-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Mapuche–Huilliche | → | **Afrodescendiente chileno** |
| S | → | **S** |

## 9.2 Diagnoses

CL_L3_SALUD_DIAGNOSTICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Diagnoses, CIE-10 codes, GES pathologies, chronic conditions, allergies, causes of sick leave or death.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_DIAGNOSTICO – Path

85%

`diagn[oó]stico[a-z_]*` `diag` `dx` `cie_?10` `cod(igo)?_?cie` `cie` `icd_?10` `icd` `patolog[ií]a[a-z_]*` `enfermedad(es)?[a-z_]*` `morbilidad` `condicion_?(medica|salud|cronica)` `problema_?salud` `ges` `hipotesis_?diagnostica` `causa_?(licencia|muerte|defuncion|hospitalizacion|consulta)` `motivo_?(consulta|hospitalizacion|licencia)` `comorbilidad(es)?` `antecedentes_?(medicos|morbidos|m[oó]rbidos|clinicos)` `alergias?` `condicion_?preexistente` `preexistencias?`

VALUE FORMAT CL_L3_SALUD_DIAGNOSTICO – Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[A-TV-Za-tv-z]\d{2}(\.\d{1,2}\|\d)?` | 60% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

CIE-10 codes become other common codes in the same format; descriptions become generic diagnoses.

`CL_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_DIAGNOSTICO_TEXTO`.

`CL_CIE10_DECIMAL` SECURE LOOKUP

Replaces the value with one of the 33 values in `cl-cie10-decimal.txt`, chosen by a keyed hash.

`CL_CIE10` SECURE LOOKUP

Replaces the value with one of the 37 values in `cl-cie10.txt`, chosen by a keyed hash.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl_bandera_0_1.txt`, chosen by a keyed hash.

`CL_DIAGNOSTICO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 30 values in `cl_diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| F32.9 | → | **J02.9** |
| Depresión mayor | → | **Tendinitis** |

## 9.3 Medicines

CL_L3_SALUD_MEDICAMENTO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Prescribed medicines and treatments. A medicine reveals the illness: antiretrovirals, antidepressants, antipsychotics.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_MEDICAMENTO — Path

85% `medicamentos?` `f[aá]rmacos?` `principio_?activo` `prescripci[oó]n` `receta(_?medica)?` `tratamiento(_?farmacologico)?` `medication` `drug(_?name)?` `posologia`

VALUE FORMAT CL_L3_SALUD_MEDICAMENTO — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 47 known values, ignoring case — Paracetamol, Ibuprofeno, Losartán, Enalapril, Metformina, Atorvastatina, … | 70% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by a common medicine.

`CL_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_MEDICAMENTO_LISTA`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl_bandera_si_no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl_bandera_true_false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl_bandera_s_n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl_bandera_y_n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl_bandera_0_1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_MEDICAMENTO_LISTA` SECURE LOOKUP

Replaces the value with one of the 26 values in `cl_medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Sertralina 50 mg | → | **Ácido acetilsalicílico** |

## 9.4 Clinical record numbers

CL_L3_SALUD_IDENTIFICADOR

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Ficha clínica, clinical history, episode, attention, sick leave and biopsy numbers.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_IDENTIFICADOR — Path

85% `ficha_?clinica` `n(ro|um|umero)_?ficha` `historia_?clinica` `n(ro|um)_?historia` `nhc` `n(ro|um)_?episodio` `n(ro|um)_?atencion` `folio_?(atencion|urgencia|licencia|receta)` `licencia_?medica` `n(ro|um)_?licencia` `folio_?lm` `n(ro|um)_?interconsulta` `n(ro|um)_?dau` `n(ro|um|umero)_?biopsia` `medical_?record_?number` `mrn`

60% `ficha` `hc` `episodio`

HOW IT IS MASKED

Characters are mapped within their kind; the same record number masks the same way in every table.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| HC-2024-00123 | → | **MD-0969-61815** |

## 9.5 Clinical notes

CL_L3_SALUD_TEXTO_CLINICO

COLUMN NAME · DATA TYPE · FREE TEXT REDACTION

WHAT IT IS

Anamnesis, progress notes, discharge summaries and medical reports, where names and identifiers appear inside the text.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_TEXTO_CLINICO — Path

85% `anamnesis` `evoluci[oó]n(_?(medica|clinica))?` `epicrisis` `indicaciones(_?medicas)?` `examen_?fisico` `notas?_?clinicas?` `informe_?(medico|clinico|alta)` `resumen_?(alta|clinico)` `observacion(es)?_?(medica|clinica)s?` `hallazgos` `interconsulta` `historia_?enfermedad` `plan_?tratamiento` `clinical_?notes?` `progress_?notes?`

DATA TYPE CL_L3_SALUD_TEXTO_CLINICO — Type

Accepts text (length 30 or more); any other type rules the data class out.

HOW IT IS MASKED

The same redaction as free text: identifiers become `[DATO]` and names `[NOMBRE]`, while the clinical content stays readable.

`CL_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATO]`, and the 948 terms of `cl-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Paciente Muñoz, RUT 9.075.310-K, consulta por cefalea.` | → | **`Paciente [NOMBRE], RUT [DATO], consulta por cefalea.`** |

## 9.6 Test results

CL_L3_SALUD_RESULTADO_EXAMEN

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Laboratory and imaging results, HIV and COVID tests, viral load, glycemia, blood pressure, body mass index.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_RESULTADO_EXAMEN — Path

80% `resultado_?(examen|laboratorio|lab|test|pcr|antigeno|biopsia|imagen|vih|hiv|covid)` `ex[aá]menes?_?(resultado|laboratorio)` `vih` `hiv` `carga_?viral` `cd4` `glicemia` `hemoglobina(_?glicosilada)?` `colesterol` `presion_?arterial` `imc` `test_?(covid|embarazo|vih|drogas)` `lab_?result`

50% `resultado` `examen`

HOW IT IS MASKED

Characters are mapped within their kind: numbers stay numbers and words become other letters.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Reactivo` | → | **`Ybfdttrq`** |

## 9.7 Blood group

CL_L3_SALUD_GRUPO_SANGUINEO

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

ABO blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `grupo_?sang` `tipo_?(de_?)?sangre` `tipo_?sanguineo` `factor_?rh` `rh` `blood_?type` `blood_?group`

VALUE FORMAT CL_L3_SALUD_GRUPO_SANGUINEO — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 28 known values, ignoring case — A, A-, B, B-, AB, AB-, … | 90% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by a blood group.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with Delphix and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 0+ | → | **0−** |

## 9.8 Disability

CL_L3_SALUD_DISCAPACIDAD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Type and degree of disability, disability credential, invalidity pensions, special educational needs.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `grado_?discapacidad` `credencial_?discapacidad` `invalidez` `porcentaje_?invalidez` `rnd` `registro_?nacional_?discapacidad` `disability` `dependencia_?(severa|moderada|funcional)` `necesidades_?educativas_?especiales` `nee` `pension_?invalidez`

VALUE FORMAT CL_L3_SALUD_DISCAPACIDAD — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 17 known values, ignoring case — Física, Visual, Auditiva, Intelectual, Psíquica, Múltiple, … | 60% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced from the list of disability types; flags stay flags.

`CL_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_DISCAPACIDAD_LISTA`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_DISCAPACIDAD_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-discapacidad.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Psíquica severa | → | **Visual** |

---

## 9.9 Sexual and reproductive health

CL_L3_SALUD_SEXUAL_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, voluntary interruption of pregnancy, contraception, fertility, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_SEXUAL_REPRODUCTIVA — Path

90% `embarazo` `embarazada` `gestaci[oó]n` `semanas_?gestacion` `edad_?gestacional` `fecha_?ultima_?regla` `fur` `aborto` `ive` `interrupcion_?(voluntaria_?)?(del_?)?embarazo` `anticonceptivos?` `metodo_?anticonceptivo` `fertilidad` `infertilidad` `reproduccion_?asistida` `paridad` `gestas` `partos` `cesarea` `its` `ets` `infeccion_?transmision_?sexual` `pregnan[a-z]*` `contracepti[a-z]*`

HOW IT IS MASKED

Suppressed to `Sin información`; flags and numeric codes keep their shape.

`CL_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Embarazo de 12 semanas | → | **Sin información** |
| S | → | **S** |

## 9.10 Mental health and addictions

CL_L3_SALUD_MENTAL_ADICCIONES

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Psychiatric and psychological conditions, suicide risk, alcohol and drug use, SENDA treatment.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_MENTAL_ADICCIONES — Path

90% `salud_?mental` `psiquiatri[a-z]*` `psicologi[a-z]*` `trastorno[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z]*` `autolesi[oó]n` `adicci[oó]n(es)?` `consumo_?(de_?)?(drogas|alcohol|sustancias)` `alcoholismo` `drogadiccion` `dependencia_?(alcohol|drogas)` `senda` `tratamiento_?(adicciones|drogas|alcohol)` `mental_?health` `substance_?(use|abuse)`

HOW IT IS MASKED

Suppressed to `Sin información`; flags and numeric codes keep their shape.

`CL_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Trastorno bipolar | → | **Sin información** |

## 9.11 Biometric data

CL_L3_BIOMETRICO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

### WHAT IT IS

Fingerprint and face templates, iris, voice, digitized signatures — when stored as text (a hash, base64).

### HOW IT IS FOUND

> **COLUMN NAME** CL_L3_BIOMETRICO — Path
>
> **90%** `huella(_?(dactilar|digital))?` `dactilar` `biometri[a-z_]*` `template_?(facial|biometrico|huella)` `rostro` `reconocimiento_?facial` `facial_?(template|id)` `iris` `retina` `voz_?(huella|biometrica)` `firma_?(digitalizada|biometrica|manuscrita)` `fingerprint` `face_?(id|template|encoding)` `palm_?print`

> **DATA TYPE** CL_L3_BIOMETRICO — Type
>
> Accepts text; any other type rules the data class out.

### HOW IT IS MASKED

Every character is replaced by `X`. Binary columns are out of reach of these algorithms; see *Limits*.

`CL_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| A1B2C3D4E5F6 | → | XXXXXXXXXXXX |

---

## 9.12 Genetic profile

CL_L3_PERFIL_GENETICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

### WHAT IT IS

DNA, genotypes, genetic markers and mutations: the human biological profile of the law.

### HOW IT IS FOUND

> **COLUMN NAME** CL_L3_PERFIL_GENETICO — Path
>
> **90%** `adn` `dna` `genoma` `genotipo` `genetic[a-z_]*` `gen[eé]tica` `secuencia_?genetica` `marcador_?genetico` `perfil_?(genetico|biologico)` `mutacion(_?genetica)?` `snp` `brca` `haplotipo` `cariotipo`

> **VALUE FORMAT** CL_L3_PERFIL_GENETICO — Regex
>
| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[ACGTUN]{24,}` | 90% | |
>
> A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Every character is replaced by `X`.

`CL_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| BRCA1 positivo | → | XXXXXXXXXXXXX |

## 9.13 Sexual orientation

CL_L3_ORIENTACION_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Declared sexual orientation.

HOW IT IS FOUND

COLUMN NAME CL_L3_ORIENTACION_SEXUAL — Path

95% `orientaci[oó]n_?sexual` `sexual_?orientation` `orient_?sexual`

VALUE FORMAT CL_L3_ORIENTACION_SEXUAL — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 15 known values, ignoring case — Heterosexual, Homosexual, Lesbiana, Gay, Bisexual, Pansexual, … | 80% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced from the list of orientations; flags stay flags.

`CL_ORIENTACION_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_ORIENTACION_SEXUAL_LISTA`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_ORIENTACION_SEXUAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 9 values in `cl-orientacion-sexual.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Bisexual | → | Lesbiana |

## 9.14 Gender identity

CL_L3_IDENTIDAD_GENERO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

### WHAT IT IS

Gender identity, registral sex change under Ley 21.120, pronouns.

### HOW IT IS FOUND

COLUMN NAME CL_L3_IDENTIDAD_GENERO — Path

95% `identidad_?(de_?)?g[eé]nero` `gender_?identity` `g[eé]nero_?(identidad|social|autopercibido)` `transg[eé]nero` `transexual` `cambio_?(de_?)?sexo_?registral` `rectificacion_?(de_?)?sexo` `pronombres?`

VALUE FORMAT CL_L3_IDENTIDAD_GENERO — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 15 known values, ignoring case — Mujer, Hombre, Mujer trans, Hombre trans, No binario, Género fluido, … | 70% | |

A value that matches none counts 40% against the data class.

### HOW IT IS MASKED

Replaced from the list of gender identities; flags stay flags.

`CL_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_IDENTIDAD_GENERO_LISTA`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `cl-identidad-genero.txt`, chosen by a keyed hash.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Hombre trans | → | **No binario** |

## 9.15 Sexual life

CL_L3_VIDA_SEXUAL

COLUMN NAME | REGEX DECOMPOSE

### WHAT IT IS

Sexual life and behavior.

### HOW IT IS FOUND

COLUMN NAME — CL_L3_VIDA_SEXUAL — Path

90% `vida_?sexual` `conducta_?sexual` `actividad_?sexual` `parejas?_?sexuales?` `practicas_?sexuales` `sexual_?(activity|behavior|history)` `historia_?sexual` `comportamiento_?sexual`

### HOW IT IS MASKED

Suppressed to `Sin información`; flags and numeric codes keep their shape.

`CL_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Activa | → | **Sin información** |

---

## 9.16 Religion

CL_L3_RELIGION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

### WHAT IT IS

Religion, creed or church.

### HOW IT IS FOUND

COLUMN NAME — CL_L3_RELIGION — Path

95% `religi[oó]n[a-z_]*` `credo` `confesion_?religiosa` `culto` `iglesia` `creencia_?religiosa` `religious_?affiliation` `denominacion_?religiosa` `comunidad_?religiosa`

VALUE FORMAT CL_L3_RELIGION — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 33 known values, ignoring case — Católica, Evangélica o protestante, Testigo de Jehová, Santos de los Últimos Días, Judía, Musulmana, … | 90% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the categories of the Censo 2024.

`CL_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_RELIGION_LISTA`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_RELIGION_LISTA` SECURE LOOKUP

Replaces the value with one of the 12 values in `cl-religiones.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Evangélica | → | **Budista** |

## 9.17 Ideological convictions

CL_L3_CONVICCION_IDEOLOGICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Ideology, political position and philosophical convictions.

HOW IT IS FOUND

COLUMN NAME CL_L3_CONVICCION_IDEOLOGICA — Path

90% `ideolog[ií]a` `convicci[oó]n(es)?(_?(ideologica|filosofica|politica)s?)?` `posicion_?politica` `postura_?politica` `tendencia_?politica` `orientacion_?politica` `pensamiento_?politico` `creencias?` `filosofia_?de_?vida` `political_?(view|orientation|opinion)`

VALUE FORMAT CL_L3_CONVICCION_IDEOLOGICA — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 14 known values, ignoring case — Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente, … | 70% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced from a list of political positions.

`CL_IDEOLOGIA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_IDEOLOGIA_LISTA`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_IDEOLOGIA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `cl-ideologias.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Centroderecha | → | **Sin identificación política** |

## 9.18 Political affiliation

CL_L3_AFILIACION_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Party membership, militancy and political coalition.

HOW IT IS FOUND

COLUMN NAME CL_L3_AFILIACION_POLITICA — Path

95% `partido(_?pol[ií]tico)?` `militancia` `militante` `afiliaci[oó]n_?(politica|partidaria|partido)` `afiliado_?partido` `political_?party` `party_?affiliation` `coalici[oó]n` `sector_?politico`

VALUE FORMAT CL_L3_AFILIACION_POLITICA — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 44 known values, ignoring case — Partido Demócrata Cristiano, Partido por la Democracia, Partido Radical de Chile, Partido Socialista de Chile, Federación Regionalista Verde Social, Partido Liberal de Chile, … | 80% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by a legally constituted party (Servel) or `Independiente`.

`CL_PARTIDO_POLITICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_PARTIDO_POLITICO_LISTA`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_PARTIDO_POLITICO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 15 values in `cl-partidos.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Renovación Nacional | → | **Partido de la Gente** |

## 9.19 Union affiliation

CL_L3_AFILIACION_SINDICAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Union membership, union dues and union leadership.

HOW IT IS FOUND

COLUMN NAME CL_L3_AFILIACION_SINDICAL — Path

95% `sindicato[a-z_]*` `sindical` `sindicalizado` `afiliaci[oó]n_?sindical` `socio_?sindicato` `cuota_?sindical` `dirigente_?sindical` `federacion_?sindical` `union_?member(ship)?` `trade_?union` `negociacion_?colectiva`

HOW IT IS MASKED

Suppressed to `Sin información`; flags and amounts keep their shape.

`CL_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Sindicato N°2 de Trabajadores | → | **Sin información** |
| S | → | **S** |

---

## 9.20 Professional association

CL_L3_AFILIACION_GREMIAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Membership of professional colleges and trade associations.

HOW IT IS FOUND

> COLUMN NAME CL_L3_AFILIACION_GREMIAL — Path
>
> 90% `gremio` `gremial` `asociacion_?gremial` `colegio_?profesional` `afiliacion_?gremial` `colegiatura` `n(ro|um)_?colegiatura` `colegio_?de_?(medicos|abogados|profesores|ingenieros|enfermeras|psicologos|arquitectos|contadores)` `professional_?association` `asociacion_?(de_?)?funcionarios`

HOW IT IS MASKED

Suppressed to `Sin información`; flags and numeric codes keep their shape.

`CL_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

> `CL_BANDERA_Y_N` **SECURE LOOKUP**
>
> Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
>
> `CL_BANDERA_0_1` **SECURE LOOKUP**
>
> Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`CL_SUPRIMIR` **SECURE LOOKUP**

Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| Colegio Médico de Chile | → | **Sin información** |

PART 10

# Socioeconomic situation

Sensitive under Chilean law, unlike under GDPR and most foreign laws. Tiers and categories are replaced within their own notation; amounts are mapped into a plausible range with no link to the real value.

## 10.1 Health insurance and FONASA tier

CL_L3_SOCIOEC_PREVISION_SALUD

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

### WHAT IT IS

The FONASA tier (A to D) reveals income directly; the ISAPRE reveals ability to pay.

### HOW IT IS FOUND

COLUMN NAME CL_L3_SOCIOEC_PREVISION_SALUD — Path

| | |
|---|---|
| 95% | `tramo_?fonasa` `fonasa` `grupo_?fonasa` `tramo_?salud` `previsi[oó]n_?(de_?)?salud` `isapre` `institucion_?(de_?)?salud_?previsional` `sistema_?(de_?)?salud` `seguro_?salud` `health_?insurance` `capredena` `dipreca` |
| 60% | `previsi[oó]n` |

VALUE FORMAT CL_L3_SOCIOEC_PREVISION_SALUD — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 38 known values, ignoring case — FONASA A, FONASA B, FONASA C, FONASA D, Isapre Banmédica, Isapre Colmena, … | 80% | |
| One of 4 known values, ignoring case — a, b, c, d | 30% | |

A value that matches none counts 40% against the data class.

### HOW IT IS MASKED

A tier letter becomes another tier letter, also in `FONASA B`; a named insurer becomes another from the list of FONASA tiers, ISAPREs, Capredena and Dipreca.

`CL_PREVISION_SALUD` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_PREVISION_SALUD_LISTA`.

- `CL_TRAMO_FONASA` SECURE LOOKUP
  Replaces the value with one of the 4 values in `cl-tramo-fonasa.txt`, chosen by a keyed hash.
- `CL_BANDERA` REGEX DECOMPOSE
  Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
  - `CL_BANDERA_SI_NO` SECURE LOOKUP
    Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
  - `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
    Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
  - `CL_BANDERA_S_N` SECURE LOOKUP
    Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
  - `CL_BANDERA_Y_N` SECURE LOOKUP
    Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
  - `CL_BANDERA_0_1` SECURE LOOKUP
    Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
- `CL_PREVISION_SALUD_LISTA` SECURE LOOKUP

> Replaces the value with one of the 18 values in `cl-prevision-salud.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| FONASA B | → | **FONASA B** |
| Isapre Colmena | → | **FONASA A** |

## 10.2 Health plan

`CL_L3_SOCIOEC_PLAN_SALUD`

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

ISAPRE plan codes, prices and agreed contributions.

HOW IT IS FOUND

> COLUMN NAME `CL_L3_SOCIOEC_PLAN_SALUD` — Path
>
> 85% `plan_?(isapre|salud|de_?salud)` `cod(igo)?_?plan_?(isapre|salud)?` `precio_?plan` `valor_?plan` `cotizacion_?(pactada|salud|isapre|adicional)` `uf_?plan` `excedente_?cotizacion` `cotizacion_?7`

HOW IT IS MASKED

Characters are mapped within their kind.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| PLN–4521 | → | **WXN–7922** |

## 10.3 Registro Social de Hogares

`CL_L3_SOCIOEC_RSH`

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

The household socioeconomic rating (tiers from 40% to 100%), and the older Ficha de Protección Social and CAS scores.

HOW IT IS FOUND

> COLUMN NAME `CL_L3_SOCIOEC_RSH` — Path
>
> 95% `rsh` `registro_?social_?(de_?)?hogares` `calificaci[oó]n_?socioecon[oó]mica` `cse` `tramo_?(rsh|socioeconomico|cse|registro_?social)` `percentil_?(rsh|socioeconomico|vulnerabilidad)` `ficha_?proteccion_?social` `fps` `puntaje_?(fps|ficha|cas|rsh)` `ficha_?cas` `indice_?vulnerabilidad` `ivm` `vulnerabilidad(_?social)?` `situacion_?socioeconomica`

HOW IT IS MASKED

A tier becomes another tier in the same notation: `40%`, `Tramo 40%`, `70`.

`CL_RSH` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CL_RSH_TRAMO_TEXTO` .

> `CL_RSH_TRAMO_NUMERO` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `cl-rsh-tramo-numero.txt` , chosen by a keyed hash.
>
> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CL_RSH_TRAMO_TEXTO` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `cl-rsh-tramo-texto.txt` , chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Tramo 40% | → | **Tramo 50%** |

## 10.4 Socioeconomic group

CL_L3_SOCIOEC_NIVEL

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Socioeconomic groups (ABC1, C2, C3, D, E), income quintiles and deciles.

HOW IT IS FOUND

> COLUMN NAME CL_L3_SOCIOEC_NIVEL — Path
>
> 90% `nse` `gse` `grupo_?socioeconomico` `estrato_?socioeconomico` `nivel_?socioeconomico` `quintil(_?(de_?)?ingresos?)?` `decil(_?(de_?)?ingresos?)?` `clase_?social`

> KNOWN VALUES CL_L3_SOCIOEC_NIVEL — List
>
| LIST | VALUES | STRENGTH | FIRST VALUES |
|---|---|---|---|
| `cl-detectar-gse.txt` | 9 | 50% | abc1, c1, c1a, c1b, c2, c3 |
>
> Values are split into words, and each word is looked up.
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A group becomes another group; a number becomes a quintile from 1 to 5.

`CL_NIVEL_SOCIOECONOMICO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_GSE` .

> `CL_QUINTIL` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `cl-quintil.txt` , chosen by a keyed hash.
>
> `CL_GSE` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `cl-gse.txt` , chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| C2 | → | **C1b** |

## 10.5 State benefits

CL_L3_SOCIOEC_BENEFICIO_SOCIAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Receiving the Pensión Garantizada Universal, Subsidio Único Familiar, Bono de Invierno, Ingreso Ético Familiar, Bolsillo Familiar Electrónico and other benefits.

HOW IT IS FOUND

COLUMN NAME CL_L3_SOCIOEC_BENEFICIO_SOCIAL – Path

90% `beneficio(s|_?social|_?estatal)?` `beneficiario_?(programa|beneficio|subsidio|bono|pgu|pbs|suf)` `programa_?(social|estatal|gobierno)` `subsidio[a-z_]*` *(except when followed by* ***habitacional*** , ***arriendo*** , ***vivienda*** , ***ds*** *)* `bono[a-z_]*` *(except when followed by list E8)* `pgu` `pbs` `aps` `suf` `ife` `ief` `ingreso_?etico_?familiar` `chile_?solidario` `seguridades_?(y_?)?oportunidades` `aporte_?familiar_?permanente` `bolsillo_?familiar` `asignacion_?familiar` `pension_?(basica|garantizada|asistencial|solidaria)` `pasis` `chile_?cuida` `chile_?crece` `bono_?invierno` `junaeb` `pae`

VALUE FORMAT CL_L3_SOCIOEC_BENEFICIO_SOCIAL – Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 35 known values, ignoring case — Pensión Garantizada Universal, Subsidio Único Familiar, Asignación Familiar, Aporte Familiar Permanente, Bono de Invierno, Bono Bodas de Oro, … | 80% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced from the list of benefits; flags stay flags and amounts keep their digits' shape.

`CL_BENEFICIO_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_BENEFICIO_SOCIAL_LISTA` .

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_BENEFICIO_SOCIAL_LISTA` SECURE LOOKUP

> Replaces the value with one of the 21 values in `cl-beneficios-sociales.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| PGU | → | **CHILE CRECE CONTIGO** |

---

## 10.6 Debt and credit status

CL_L3_SOCIOEC_MOROSIDAD

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

DICOM and Boletín Comercial records, arrears, credit scores, protests, insolvency proceedings.

HOW IT IS FOUND

> COLUMN NAME CL_L3_SOCIOEC_MOROSIDAD — Path
>
> 90% `dicom` `boletin_?comercial` `morosidad` `moroso` `morosa` `deuda_?morosa` `protestos?` `deudor_?moroso` `score_?(crediticio|credito|riesgo|equifax|dicom)` `puntaje_?(crediticio|riesgo|credito)` `clasificacion_?(de_?)?(riesgo|crediticia|deudor)` `riesgo_?crediticio` `equifax` `sinacofi` `transunion` `informe_?comercial` `cartera_?vencida` `castigo` `dias_?(de_?)?mora` `tramo_?mora` `estado_?(deuda|credito|crediticio|morosidad)` `credit_?score` `delinquen[a-z]*` `repactacion` `renegociacion` `quiebra` `insolvencia` `liquidacion_?voluntaria` `reorganizacion_?(de_?)?deudor`

HOW IT IS MASKED

Statuses are replaced from a list; scores and flags keep their shape.

`CL_MOROSIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_MOROSIDAD_LISTA`.

> `CL_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_MOROSIDAD_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `cl-estado-crediticio.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| Moroso DICOM | → | **Al día** |
| 650 | → | **807** |

## 10.7 Debt amounts

CL_L3_SOCIOEC_MONTO_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Debt, arrears and outstanding balances.

HOW IT IS FOUND

COLUMN NAME CL_L3_SOCIOEC_MONTO_DEUDA – Path

85% `monto_?(deuda|moroso|mora|adeudado|castigado|protestado|vencido)` `deuda(_?(total|vigente|vencida|consolidada))?` `saldo_?(deuda|adeudado|insoluto|moroso|vencido)` `total_?adeudado` `monto_?protesto` `debt(_?amount)?` `outstanding_?balance`

DATA TYPE CL_L3_SOCIOEC_MONTO_DEUDA – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 1250000 | → | **5128694** |

## 10.8 Income and salary

CL_L3_SOCIOEC_INGRESOS

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Salaries, taxable income, household and per capita income, assets.

HOW IT IS FOUND

COLUMN NAME CL_L3_SOCIOEC_INGRESOS – Path

85% `sueldo[a-z_]*` `salario[a-z_]*` `remuneraci[oó]n[a-z_]*` `renta(_?(imponible|liquida|bruta|mensual|anual|promedio|declarada|familiar|hogar|per_?capita))?` `ingreso_?(mensual|liquido|bruto|familiar|hogar|per_?capita|total|promedio|declarado|autonomo|laboral)` `ingresos(_?[a-z]+)?` `haberes` `liquido_?a_?pagar` `imponible` `total_?haberes` `salary` `wage` `income` `gross_?pay` `net_?pay` `patrimonio` `avaluo_?fiscal` `capacidad_?(de_?)?pago` `gastos_?mensuales`

DATA TYPE CL_L3_SOCIOEC_INGRESOS – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 985000 | → | **896347** |

## 10.9 Pension fund

CL_L3_SOCIOEC_PREVISION_AFP

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

AFP, IPS, Capredena and Dipreca.

HOW IT IS FOUND

COLUMN NAME CL_L3_SOCIOEC_PREVISION_AFP – Path

95% `afp` `nombre_?afp` `cod(igo)?_?afp` `administradora_?(de_?)?fondos(_?de_?pensiones)?` `institucion_?previsional` `prevision_?social` `entidad_?previsional` `ips` `inp` `caja_?(de_?)?prevision` `regimen_?previsional` `sistema_?previsional` `pension_?fund`

VALUE FORMAT CL_L3_SOCIOEC_PREVISION_AFP – Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 23 known values, ignoring case — AFP Capital, AFP Cuprum, AFP Habitat, AFP Modelo, AFP PlanVital, AFP ProVida, … | 90% | |

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced from the list of pension institutions.

`CL_AFP` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_AFP_LISTA`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

> Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`CL_AFP_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 11 values in `cl-afp.txt`, chosen by a keyed hash.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| AFP Modelo | → | **AFP Habitat** |

## 10.10 Pension balances

`CL_L3_SOCIOEC_SALDO_PREVISIONAL`

**COLUMN NAME** **DATA TYPE** **NUMERIC MAPPING**

**WHAT IT IS**

Individual account balances, contributions, voluntary savings (APV) and pension amounts.

**HOW IT IS FOUND**

**COLUMN NAME** `CL_L3_SOCIOEC_SALDO_PREVISIONAL – Path`

**90%** `saldo_?(afp|cuenta_?individual|cotizaciones|previsional|obligatorio|apv|cuenta_?2|fondo)` `fondo_?(de_?)?(pensiones|previsional)` `cotizaci[oó]n(es)?_?(afp|previsional|obligatoria|pension)` `monto_?pension` `pension_?(monto|mensual|autofinanciada)` `apv` `apvc` `cuenta_?2` `bono_?reconocimiento` `renta_?vitalicia` `retiro_?programado` `pension_?amount` `retirement_?balance`

**DATA TYPE** `CL_L3_SOCIOEC_SALDO_PREVISIONAL – Type`

Accepts number; any other type rules the data class out.

**HOW IT IS MASKED**

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` **NUMERIC MAPPING**

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

**EXAMPLES**

| VALUE | | MASKED |
|---|---|---|
| 38500000 | → | **17634498** |

## 10.11 Housing situation

`CL_L3_SOCIOEC_VIVIENDA`

**COLUMN NAME** **VALUE FORMAT** **REGEX DECOMPOSE**

**WHAT IT IS**

Housing tenure, allegados, overcrowding, camps and housing subsidies.

HOW IT IS FOUND

COLUMN NAME CL_L3_SOCIOEC_VIVIENDA — Path

95% `tipo_?vivienda` `tenencia_?(de_?)?(la_?)?vivienda` `situacion_?(habitacional|vivienda)` `vivienda_?(propia|arrendada|cedida)` `allegad[oa]s?` `allegamiento` `hacinamiento` `campamento` `toma_?terreno` `subsidio_?(habitacional|ds1|ds49|ds19|arriendo|vivienda)` `ds_?49` `ds_?1` `comite_?vivienda` `deficit_?habitacional` `material_?vivienda` `housing_?(type|tenure|status)` `dividendo_?hipotecario`

VALUE FORMAT CL_L3_SOCIOEC_VIVIENDA — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 17 known values, ignoring case — Propia pagada, Propia pagándose, Arrendada con contrato, Arrendada sin contrato, Cedida por familiar, Cedida por trabajo, … | 60% | |

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced from the list of housing situations.

`CL_VIVIENDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_VIVIENDA_LISTA`.

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_VIVIENDA_LISTA` SECURE LOOKUP

Replaces the value with one of the 10 values in `cl-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Allegado` | → | **`Arrendada sin contrato`** |

## 10.12 Student aid

CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Gratuidad, scholarships, the Crédito con Aval del Estado and the Fondo Solidario.

### HOW IT IS FOUND

**COLUMN NAME** CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS — Path

**90%** `beca[a-z_]*` `gratuidad` `credito_?(cae|aval_?del_?estado|universitario|fscu|corfo)` `cae` `fscu` `fuas` `beneficio_?estudiantil` `arancel_?(diferenciado|referencia)` `tne` `beneficio_?(mineduc|arancel)` `scholarship` `student_?loan` `financiamiento_?(de_?)?estudios` `deuda_?(cae|universitaria)`

**VALUE FORMAT** CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS — Values

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| One of 20 known values, ignoring case — Gratuidad, Beca Bicentenario, Beca Juan Gómez Millas, Beca Nuevo Milenio, Beca Excelencia Académica, Beca Vocación de Profesor, … | 70% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Replaced from the list of student aid.

`CL_FINANCIAMIENTO_ESTUDIOS` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_FINANCIAMIENTO_ESTUDIOS_LISTA`.

> `CL_BANDERA` **REGEX DECOMPOSE**
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CL_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CL_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CL_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CL_FINANCIAMIENTO_ESTUDIOS_LISTA` **SECURE LOOKUP**
>
> Replaces the value with one of the 12 values in `cl-financiamiento-estudios.txt`, chosen by a keyed hash.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| CAE | → | **BECA PRESIDENTE DE LA REPÚBLICA** |

PART 11

# Criminal records

Data on criminal offenses, convictions and court cases, handled with the same care as sensitive data.

## 11.1 Criminal records

CL_L3_PENAL_ANTECEDENTES

COLUMN NAME | REGEX DECOMPOSE

### WHAT IT IS

Convictions, offenses, criminal records, disqualifications, precautionary measures, domestic violence.

### HOW IT IS FOUND

COLUMN NAME — CL_L3_PENAL_ANTECEDENTES — Path

95% `antecedentes(_?(penales|judiciales|policiales|criminales))?` *(except when followed by list E9)*

`certificado_?antecedentes` `condenas?` `condenad[oa]` `delitos?` `tipo_?delito` `prontuario` `reincidente` `reincidencia` `imputad[oa]` `formalizad[oa]` `sentencia(_?condenatoria)?` `pena` `privacion_?(de_?)?libertad` `libertad_?condicional` `inhabilidad(es)?` `registro_?(de_?)?inhabilidades` `inhabilitad[oa]` `criminal_?record` `conviction` `offen[cs]e` `detenid[oa]` `detencion` `orden_?(de_?)?detencion` `medida_?cautelar` `violencia_?intrafamiliar` `vif` `causa_?penal`

### HOW IT IS MASKED

Replaced by a generic status ( `Sin antecedentes` , `Con antecedentes` ); flags keep their shape.

`CL_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_ANTECEDENTES_LISTA` .

`CL_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

`CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

`CL_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

`CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CL_ANTECEDENTES_LISTA` SECURE LOOKUP

Replaces the value with one of the 3 values in `cl-antecedentes.txt` , chosen by a keyed hash.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| `Condenado por robo` | → | **`Sin información`** |

## 11.2 Court case numbers

CL_L3_PENAL_CAUSA

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

### WHAT IT IS

RIT and RUC case numbers, police reports and complaint numbers.

### HOW IT IS FOUND

COLUMN NAME — CL_L3_PENAL_CAUSA — Path

90% `rol_?causa` `rit` `ruc` `rol_?(tribunal|judicial)` `n(ro|um|umero)_?causa` `causa_?rol` `rol_?unico_?(de_?)?causa` `parte_?policial` `n(ro|um)_?parte` `folio_?(parte|denuncia)` `n(ro|um|umero)_?denuncia` `expediente(_?(judicial|penal))?` `case_?number`

VALUE FORMAT — CL_L3_PENAL_CAUSA — Regex

| PATTERN | STRENGTH | NOTES |
|---|---|---|
| `[A-Za-z]{1,3}-\d{1,6}-\d{4}` | 80% | |
| `0*(?:\d{10}-[\dkK])` | 80% | |

A value that matches none counts 30% against the data class.

### HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

`CL_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE | | MASKED |
|---|---|---|
| 0-1234-2023 | → | **G-9402-2531** |

12

## The RUT check digit

The RUT check digit is computed modulo 11 with weights 2 to 7 from the right, and a result of 10 is written `K`. The Check Digit framework writes 10 as `0`, so masking a RUT with it alone leaves about one result in eleven invalid.

The algorithm `CL_RUT` takes two passes:

- The first masks the body and writes, in the check digit's place, an auxiliary digit computed with every weight doubled modulo 11. That digit is `9` exactly when the real check digit is `K`.
- The second writes `K` where the auxiliary digit is `9`; anywhere else it recomputes the real check digit without touching the body.

Every masked RUT is valid, `K` appears in its natural proportion, and the mapping stays one-to-one — a RUT used as a key cannot collide. Bodies of 6, 7 and 8 digits keep their format, with or without dots and hyphen, with an upper- or lower-case `k`.

13

## Limits

- **Binary columns** — scanned identity cards, fingerprint images, clinical PDFs stored in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A RUT split in two columns** keeps its masked body consistent, but the check digit column cannot see the body, so the pair is no longer valid.
- **Comunas** spelled in a way the list does not know pass unchanged. Names with and without accents and ñ are both recognized.
- **Free text** is redacted word by word: a phone number written with spaces ( `+56 9 8765 4321` ) is not found there, and a name that is also a common word ( `Rosa` , `Paz` ) is redacted wherever it appears.
- **Minors** — a birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, number and comuna kept in separate columns are masked independently of one another.

14

## Verification

Before publication the policy was checked outside Delphix:

- Every classifier configuration was reviewed against what Delphix accepts.
- Discovery was simulated on 129 columns with the whole policy at its assignment threshold — well named, badly named, and 21 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The algorithms, run with the Delphix algorithm plugin, masked 184 sample values and 204 placeholders such as `S/I`, checking that each masked value comes from the right vocabulary, and 60 random RUTs for a valid check digit. Each of the 101 algorithms also masked its own sample input.

Every column was assigned as expected and every value masked as expected. Before using the policy on real data, run a discovery job and a masking job on a representative copy.

---

15

# Sources

- Ley 21.719 — Biblioteca del Congreso Nacional de Chile.
- Bill postponing the entry into force, Boletín 18.623-07 (31 August 2026).
- Comunas, provinces, regions and Censo 2024 population — Wikipedia, *Anexo:Comunas de Chile*.
- Most registered surnames, 2014–2023 — Servicio de Registro Civil e Identificación.
- Legally constituted political parties — Servicio Electoral (Servel).
- Pension fund administrators — Superintendencia de Pensiones. ISAPREs — Superintendencia de Salud.
- Registro Social de Hogares tiers — Ministerio de Desarrollo Social y Familia.
- Indigenous peoples — Ley 19.253 and its amendments; Chilean Afro-descendant tribal people — Ley 21.151.
- Vehicle plate formats — Registro Civil. Telephone numbering — Subsecretaría de Telecomunicaciones.
- Religion categories — Instituto Nacional de Estadísticas, Censo 2024.

APPENDIX A

# Algorithms

Every algorithm of the policy in alphabetical order, with its configuration. The one a data class names is the top of its tree; the others are building blocks.

## CL_AFP REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_AFP_LISTA`.

Used by: `CL_L3_SOCIOEC_PREVISION_AFP`

### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_AFP_LISTA` |

### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

## CL_AFP_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `cl-afp.txt`, chosen by a keyed hash.

Used by: `CL_AFP`

### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-afp.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

## CL_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L2_ANIO_NACIMIENTO`

### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)(\d{3})(\d)` | keep · keep · `CL_CM_ALFANUM` |
| otherwise | keep |

### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

## CL_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_ANTECEDENTES_LISTA`.

Used by: `CL_L3_PENAL_ANTECEDENTES`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_ANTECEDENTES_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 3 values in `cl-antecedentes.txt`, chosen by a keyed hash.

Used by: `CL_ANTECEDENTES`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-antecedentes.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_APELLIDO NAME

Replaces the name with one of the 194 names in `cl-apellidos.txt`.

Used by: `CL_APELLIDOS`, `CL_NOMBRE_COMPLETO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-apellidos.txt` |
| maskedValueCase | `PRESERVE_INPUT` |
| filterAccent | yes |
| inputCaseSensitive | no |

---

### CL_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

Used by: `CL_L1_APELLIDO`, `CL_NOMBRE_COMPLETO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(\S+)` | `CL_APELLIDO` |
| `(\S+)\s+(\S+)` | `CL_APELLIDO` · `CL_APELLIDO` |
| `(\S+)\s+(\S+)\s+(\S+)` | `CL_APELLIDO` · `CL_APELLIDO` · `CL_APELLIDO` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CL_CATEGORIA_SUPRIMIDA`, `CL_PUEBLO_ORIGINARIO`, `CL_DIAGNOSTICO`, `CL_MEDICAMENTO`, `CL_DISCAPACIDAD`, `CL_ORIENTACION_SEXUAL`, `CL_IDENTIDAD_GENERO`, `CL_RELIGION`, `CL_IDEOLOGIA`, `CL_PARTIDO_POLITICO`, `CL_PREVISION_SALUD`,

`CL_RSH` , `CL_BENEFICIO_SOCIAL` , `CL_MOROSIDAD` , `CL_AFP` , `CL_VIVIENDA` , `CL_FINANCIAMIENTO_ESTUDIOS` , `CL_ANTECEDENTES`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no)` | `CL_BANDERA_SI_NO` |
| `(?i)(true\|false)` | `CL_BANDERA_TRUE_FALSE` |
| `(?i)([sn])` | `CL_BANDERA_S_N` |
| `(?i)(y)` | `CL_BANDERA_Y_N` |
| `([01])` | `CL_BANDERA_0_1` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### `CL_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

Used by: `CL_BANDERA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-bandera-0-1.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### `CL_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

Used by: `CL_BANDERA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-bandera-s-n.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### `CL_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

Used by: `CL_BANDERA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-bandera-si-no.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |

| | |
|---|---|
| trimWhitespaceInLookupFile | yes |

### CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `CL_BANDERA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-bandera-true-false.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `CL_BANDERA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-bandera-y-n.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_BENEFICIO_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_BENEFICIO_SOCIAL_LISTA`.

Used by: `CL_L3_SOCIOEC_BENEFICIO_SOCIAL`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_BENEFICIO_SOCIAL_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_BENEFICIO_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 21 values in `cl-beneficios-sociales.txt`, chosen by a keyed hash.

Used by: `CL_BENEFICIO_SOCIAL`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-beneficios-sociales.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |

| | |
|---|---|
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_CANTIDAD_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CL_L2_CARGAS_FAMILIARES

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| (0*?)(?:([0-5])) | keep · keep |
| (0*?)(?:(\d+)) | keep · replace with 5 |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_SUPRIMIR.

Used by: CL_L3_SALUD_SEXUAL_REPRODUCTIVA, CL_L3_SALUD_MENTAL_ADICCIONES, CL_L3_VIDA_SEXUAL, CL_L3_AFILIACION_SINDICAL, CL_L3_AFILIACION_GREMIAL

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| (?i)(s[ií]\|no\|true\|false\|[sny01]) | CL_BANDERA |
| (0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))) | keep · keep · keep · keep · keep · CL_CM_ALFANUM |
| otherwise | CL_SUPRIMIR |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in cl-cie10.txt, chosen by a keyed hash.

Used by: CL_DIAGNOSTICO

#### CONFIGURATION

| | |
|---|---|
| lookupFile | cl-cie10.txt |
| hashMethod | SHA256 |
| maskedValueCase | PRESERVE_LOOKUP_FILE |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in cl-cie10-decimal.txt, chosen by a keyed hash.

Used by: CL_DIAGNOSTICO

#### CONFIGURATION

| | |
|---|---|
| lookupFile | cl-cie10-decimal.txt |
| hashMethod | SHA256 |

| | |
|---|---|
| maskedValueCase | `PRESERVE_LOOKUP_FILE` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `CL_L1_RUT_CUERPO`, `CL_L1_DIRECCION_COMPLEMENTO`, `CL_L1_NUMERO_DOCUMENTO`, `CL_L1_PASAPORTE`, `CL_L1_DOCUMENTO_EXTRANJERO`, `CL_L1_CUENTA_BANCARIA`, `CL_L1_DISPOSITIVO`, `CL_L1_VEHICULO_ID`, `CL_L1_NUMERO_CONTRATO`, `CL_L1_USUARIO_RRSS`, `CL_L3_SALUD_IDENTIFICADOR`, `CL_L3_SALUD_RESULTADO_EXAMEN`, `CL_L3_SOCIOEC_PLAN_SALUD`, `CL_L3_PENAL_CAUSA`, `CL_CATEGORIA_SUPRIMIDA`, `CL_RUT_CUERPO_8`, `CL_RUT_CUERPO_7`, `CL_RUT_CUERPO_6`, `CL_RUT_PASO_1`, `CL_NOMBRES`, `CL_APELLIDOS`, `CL_NOMBRE_COMPLETO`, `CL_EMAIL`, `CL_TELEFONO`, `CL_IP`, `CL_COORDENADA`, `CL_ANIO`, `CL_EDAD`, `CL_CODIGO_POSTAL`, `CL_PUEBLO_ORIGINARIO`, `CL_MEDICAMENTO`, `CL_DISCAPACIDAD`, `CL_ORIENTACION_SEXUAL`, `CL_IDENTIDAD_GENERO`, `CL_RELIGION`, `CL_IDEOLOGIA`, `CL_PARTIDO_POLITICO`, `CL_BENEFICIO_SOCIAL`, `CL_MOROSIDAD`, `CL_AFP`, `CL_VIVIENDA`, `CL_FINANCIAMIENTO_ESTUDIOS`, `CL_ANTECEDENTES`

#### CONFIGURATION

| | |
|---|---|
| characterGroups | `0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ` `áéíóúüñ` `ÁÉÍÓÚÜÑ` |
| caseSensitive | yes |
| minMaskedPositions | `0` |
| preserveLeadingZeros | yes |

### CL_CODIGO_COMUNA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L2_CODIGO_COMUNA`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)(\d+)` | keep · `CL_CODIGO_COMUNA_TABLA` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_CODIGO_COMUNA_TABLA DATA CLEANSING

Replaces each value found in `cl-codigo-comuna-generalizado.txt` (346 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CL_CODIGO_COMUNA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-codigo-comuna-generalizado.txt` |
| delimiter | `,` |
| caseSensitive | no |
| trimWhitespace | yes |

### CL_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

Used by: `CL_L2_CODIGO_POSTAL`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)(\d{3})-?(\d{4})` | keep · keep · replace with `0000` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### `CL_COMUNA` DATA CLEANSING

Replaces each value found in `cl-comuna-generalizada.txt` (428 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CL_L2_COMUNA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-comuna-generalizada.txt` |
| delimiter | `,` |
| caseSensitive | no |
| trimWhitespace | yes |

---

### `CL_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L1_GEOLOCALIZACION`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)` | keep · `CL_CM_ALFANUM` · keep · `CL_CM_ALFANUM` |
| `(-?\d{1,3}\.\d)(\d+)` | keep · `CL_CM_ALFANUM` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### `CL_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_DIAGNOSTICO_TEXTO`.

Used by: `CL_L3_SALUD_DIAGNOSTICO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `([A-TV-Za-tv-z]\d{2}\.\d{1,2})` | `CL_CIE10_DECIMAL` |
| `([A-TV-Za-tv-z]\d{2,3})` | `CL_CIE10` |
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| otherwise | `CL_DIAGNOSTICO_TEXTO` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### `CL_DIAGNOSTICO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 30 values in `cl-diagnosticos.txt`, chosen by a keyed hash.

Used by: `CL_DIAGNOSTICO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-diagnosticos.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_DIRECCION SECURE LOOKUP

Replaces the value with one of the 3,000 values in `cl-direcciones.txt`, chosen by a keyed hash.

Used by: `CL_L1_DIRECCION`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-direcciones.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_LOOKUP_FILE` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_DISCAPACIDAD_LISTA`.

Used by: `CL_L3_SALUD_DISCAPACIDAD`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_DISCAPACIDAD_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-discapacidad.txt`, chosen by a keyed hash.

Used by: `CL_DISCAPACIDAD`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-discapacidad.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L2_EDAD`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)([1-9]\d{2,})` | keep · replace with `90` |
| `(0*)([1-9])(\d)(\.\d+)` | keep · keep · `CL_CM_ALFANUM` · keep |
| `(0*)([1-9])(\d)` | keep · keep · `CL_CM_ALFANUM` |
| `(0*)(\d)` | keep · `CL_CM_ALFANUM` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

Used by: `CL_L1_EMAIL`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24})` | `CL_CM_ALFANUM` · `CL_CM_ALFANUM` · replace with `test` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 25 values in `cl-empleadores.txt`, chosen by a keyed hash.

Used by: `CL_L2_EMPLEADOR`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-empleadores.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_ESTABLECIMIENTO SECURE LOOKUP

Replaces the value with one of the 15 values in `cl-establecimientos.txt`, chosen by a keyed hash.

Used by: `CL_L2_ESTABLECIMIENTO_EDUCACIONAL`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-establecimientos.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |

| | |
|---|---|
| trimWhitespaceInLookupFile | yes |

### CL_ESTADO_CIVIL SECURE LOOKUP

Replaces the value with one of the 6 values in `cl-estado-civil.txt`, chosen by a keyed hash.

Used by: `CL_L2_ESTADO_CIVIL`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-estado-civil.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `CL_L2_FECHA_EVENTO`

#### CONFIGURATION

| | |
|---|---|
| minRange | `-30` |
| maxRange | `30` |
| unit | `DAYS` |
| roll | no |

### CL_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `CL_L2_FECHA_NACIMIENTO`

#### CONFIGURATION

| | |
|---|---|
| minRange | `-60` |
| maxRange | `60` |
| unit | `DAYS` |
| roll | no |

### CL_FINANCIAMIENTO_ESTUDIOS REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_FINANCIAMIENTO_ESTUDIOS_LISTA`.

Used by: `CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_FINANCIAMIENTO_ESTUDIOS_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_FINANCIAMIENTO_ESTUDIOS_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `cl-financiamiento-estudios.txt`, chosen by a keyed hash.

Used by: `CL_FINANCIAMIENTO_ESTUDIOS`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-financiamiento-estudios.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_GSE SECURE LOOKUP

Replaces the value with one of the 7 values in `cl-gse.txt`, chosen by a keyed hash.

Used by: `CL_NIVEL_SOCIOECONOMICO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-gse.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_LOOKUP_FILE` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_IDENTIDAD_GENERO_LISTA`.

Used by: `CL_L3_IDENTIDAD_GENERO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_IDENTIDAD_GENERO_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-identidad-genero.txt`, chosen by a keyed hash.

Used by: `CL_IDENTIDAD_GENERO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-identidad-genero.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |

| | |
|---|---|
| trimWhitespaceInLookupFile | yes |

### CL_IDEOLOGIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_IDEOLOGIA_LISTA`.

Used by: `CL_L3_CONVICCION_IDEOLOGICA`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_IDEOLOGIA_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_IDEOLOGIA_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-ideologias.txt`, chosen by a keyed hash.

Used by: `CL_IDEOLOGIA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-ideologias.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

Used by: `CL_L1_IP`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))` | keep · `CL_OCTETO` · `CL_OCTETO` · `CL_OCTETO` · `CL_OCTETO` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_MEDICAMENTO_LISTA`.

Used by: `CL_L3_SALUD_MEDICAMENTO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_MEDICAMENTO_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 26 values in `cl-medicamentos.txt`, chosen by a keyed hash.

Used by: `CL_MEDICAMENTO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-medicamentos.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_MOROSIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_MOROSIDAD_LISTA`.

Used by: `CL_L3_SOCIOEC_MOROSIDAD`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_MOROSIDAD_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_MOROSIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-estado-crediticio.txt`, chosen by a keyed hash.

Used by: `CL_MOROSIDAD`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-estado-crediticio.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 17 values in `cl-nacionalidades.txt`, chosen by a keyed hash.

Used by: `CL_L2_NACIONALIDAD`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-nacionalidades.txt` |
| hashMethod | `SHA256` |

| | |
|---|---|
| maskedValueCase | PRESERVE_INPUT |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_NIVEL_EDUCACIONAL SECURE LOOKUP

Replaces the value with one of the 10 values in `cl-nivel-educacional.txt`, chosen by a keyed hash.

Used by: `CL_L2_NIVEL_EDUCACIONAL`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | cl-nivel-educacional.txt |
| hashMethod | SHA256 |
| maskedValueCase | PRESERVE_INPUT |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_GSE`.

Used by: `CL_L3_SOCIOEC_NIVEL`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| (0*?)(?:(\d{1,2})) | keep · CL_QUINTIL |
| otherwise | CL_GSE |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

Used by: `CL_L1_NOMBRE_COMPLETO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| ([^,]+),\s*(.+) | CL_APELLIDOS · CL_NOMBRES |
| (\S+) | CL_NOMBRE_PILA |
| (\S+)\s+(\S+) | CL_NOMBRE_PILA · CL_APELLIDO |
| (\S+)\s+(\S+)\s+(\S+) | CL_NOMBRE_PILA · CL_APELLIDO · CL_APELLIDO |
| (\S+)\s+(\S+)\s+(\S+)\s+(\S+) | CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_APELLIDO · CL_APELLIDO |
| (\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+) | CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_APELLIDO · CL_APELLIDO |
| otherwise | CL_CM_ALFANUM |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_NOMBRE_PILA NAME

Replaces the name with one of the 189 names in `cl-nombres.txt`.

Used by: `CL_NOMBRES` , `CL_NOMBRE_COMPLETO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-nombres.txt` |
| maskedValueCase | `PRESERVE_INPUT` |
| filterAccent | yes |
| inputCaseSensitive | no |

---

### CL_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

Used by: `CL_L1_NOMBRE` , `CL_NOMBRE_COMPLETO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(\S+)` | `CL_NOMBRE_PILA` |
| `(\S+)\s+(\S+)` | `CL_NOMBRE_PILA` · `CL_NOMBRE_PILA` |
| `(\S+)\s+(\S+)\s+(\S+)` | `CL_NOMBRE_PILA` · `CL_NOMBRE_PILA` · `CL_NOMBRE_PILA` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `CL_IP`

#### CONFIGURATION

| | |
|---|---|
| minValue | `1` |
| maxValue | `254` |

---

### CL_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in `cl-ocupaciones.txt` , chosen by a keyed hash.

Used by: `CL_L2_OCUPACION`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-ocupaciones.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_ORIENTACION_SEXUAL_LISTA` .

Used by: `CL_L3_ORIENTACION_SEXUAL`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |

| | |
|---|---|
| otherwise | `CL_ORIENTACION_SEXUAL_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `cl-orientacion-sexual.txt`, chosen by a keyed hash.

Used by: `CL_ORIENTACION_SEXUAL`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-orientacion-sexual.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_PARTIDO_POLITICO_LISTA`.

Used by: `CL_L3_AFILIACION_POLITICA`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_PARTIDO_POLITICO_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 15 values in `cl-partidos.txt`, chosen by a keyed hash.

Used by: `CL_PARTIDO_POLITICO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-partidos.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_PATENTE CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `CL_L1_PATENTE`

#### CONFIGURATION

| | |
|---|---|
| characterGroups | `BCDFGHJKLPRSTVWXYZ` `AEIMNOQU` `bcdfghjklprstvwxyz` `aeimnoqu` `0123456789` |
| caseSensitive | yes |

### CL_PREVISION_SALUD REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_PREVISION_SALUD_LISTA`.

Used by: `CL_L3_SOCIOEC_PREVISION_SALUD`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `([A-Da-d])` | `CL_TRAMO_FONASA` |
| `(?i)(fonasa\s*[\-:]?\s*(?:tramo\s*)?)([A-D])` | keep · `CL_TRAMO_FONASA` |
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| otherwise | `CL_PREVISION_SALUD_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_PREVISION_SALUD_LISTA SECURE LOOKUP

Replaces the value with one of the 18 values in `cl-prevision-salud.txt`, chosen by a keyed hash.

Used by: `CL_PREVISION_SALUD`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-prevision-salud.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_PUEBLO_ORIGINARIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_PUEBLO_ORIGINARIO_LISTA`.

Used by: `CL_L3_ETNIA`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_PUEBLO_ORIGINARIO_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_PUEBLO_ORIGINARIO_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in `cl-pueblos.txt`, chosen by a keyed hash.

Used by: `CL_PUEBLO_ORIGINARIO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-pueblos.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in `cl-quintil.txt`, chosen by a keyed hash.

Used by: `CL_NIVEL_SOCIOECONOMICO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-quintil.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L1_CREDENCIAL`, `CL_L3_BIOMETRICO`, `CL_L3_PERFIL_GENETICO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(.+)` | each character → `X` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_RELIGION_LISTA`.

Used by: `CL_L3_RELIGION`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_RELIGION_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `cl-religiones.txt`, chosen by a keyed hash.

Used by: `CL_RELIGION`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-religiones.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### `CL_RSH` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CL_RSH_TRAMO_TEXTO` .

Used by: `CL_L3_SOCIOEC_RSH`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)(\d{1,3})(\s*%)` | keep · `CL_RSH_TRAMO_NUMERO` · keep |
| `(?i)(tramo\s*)(\d{1,3})(.*)` | keep · `CL_RSH_TRAMO_NUMERO` · keep |
| `(0*)(\d{1,3})` | keep · `CL_RSH_TRAMO_NUMERO` |
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| otherwise | `CL_RSH_TRAMO_TEXTO` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### `CL_RSH_TRAMO_NUMERO` SECURE LOOKUP

Replaces the value with one of the 7 values in `cl-rsh-tramo-numero.txt` , chosen by a keyed hash.

Used by: `CL_RSH`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-rsh-tramo-numero.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### `CL_RSH_TRAMO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 7 values in `cl-rsh-tramo-texto.txt` , chosen by a keyed hash.

Used by: `CL_RSH`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-rsh-tramo-texto.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_RUT STRING ALGORITHM CHAIN

Applies `CL_RUT_PASO_1` → `CL_RUT_PASO_2`, in this order.

Used by: `CL_L1_RUT`

#### CONFIGURATION

| | |
|---|---|
| `algorithmReferences[1]` | `CL_RUT_PASO_1` |
| `algorithmReferences[2]` | `CL_RUT_PASO_2` |

---

### CL_RUT_CUERPO_6 CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3` from the right.

Used by: `CL_RUT_PASO_1`

#### CONFIGURATION

| | |
|---|---|
| `weightList` | `4 6 8 10 1 3` |
| `modulusNumber` | `11` |
| `checkDigitIndex` | `6` |
| `calculateChecksumRightToLeft` | yes |
| `numDigitsForCheckdigitCalculation` | `6` |
| `numericAlgorithm` | `CL_CM_ALFANUM` |
| `preserveRegex` | `[.\-]` |
| `inputHandlingConfig.characterHandling` | `STANDARD` |
| `inputHandlingConfig.invalidInputHandling` | `ERROR` |
| `inputHandlingConfig.shortInputHandling` | `FALLBACK` |
| `inputHandlingConfig.padCharacter` | `0` |
| `inputHandlingConfig.trimWhitespace` | yes |

---

### CL_RUT_CUERPO_7 CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3 4` from the right.

Used by: `CL_RUT_PASO_1`

#### CONFIGURATION

| | |
|---|---|
| `weightList` | `4 6 8 10 1 3 4` |
| `modulusNumber` | `11` |
| `checkDigitIndex` | `7` |
| `calculateChecksumRightToLeft` | yes |
| `numDigitsForCheckdigitCalculation` | `7` |
| `numericAlgorithm` | `CL_CM_ALFANUM` |
| `preserveRegex` | `[.\-]` |
| `inputHandlingConfig.characterHandling` | `STANDARD` |
| `inputHandlingConfig.invalidInputHandling` | `ERROR` |
| `inputHandlingConfig.shortInputHandling` | `FALLBACK` |
| `inputHandlingConfig.padCharacter` | `0` |
| `inputHandlingConfig.trimWhitespace` | yes |

---

### CL_RUT_CUERPO_8 CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3 4 6` from the right.

Used by: `CL_RUT_PASO_1`

#### CONFIGURATION

| | |
|---|---|
| weightList | `4 6 8 10 1 3 4 6` |
| modulusNumber | `11` |
| checkDigitIndex | `8` |
| calculateChecksumRightToLeft | yes |
| numDigitsForCheckdigitCalculation | `8` |
| numericAlgorithm | `CL_CM_ALFANUM` |
| preserveRegex | `[.\-]` |
| inputHandlingConfig.characterHandling | `STANDARD` |
| inputHandlingConfig.invalidInputHandling | `ERROR` |
| inputHandlingConfig.shortInputHandling | `FALLBACK` |
| inputHandlingConfig.padCharacter | `0` |
| inputHandlingConfig.trimWhitespace | yes |

---

### CL_RUT_DV SECURE LOOKUP

Replaces the value with one of the 11 values in `cl-digito-verificador.txt`, chosen by a keyed hash.

Used by: `CL_L1_RUT_DV`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-digito-verificador.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

---

### CL_RUT_DV_6 CHECK DIGIT

Masks the digits with `CL_SIN_CAMBIO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7` from the right.

Used by: `CL_RUT_PASO_2`

#### CONFIGURATION

| | |
|---|---|
| weightList | `2 3 4 5 6 7` |
| modulusNumber | `11` |
| checkDigitIndex | `6` |
| calculateChecksumRightToLeft | yes |
| numDigitsForCheckdigitCalculation | `6` |
| numericAlgorithm | `CL_SIN_CAMBIO` |
| preserveRegex | `[.\-]` |
| inputHandlingConfig.characterHandling | `STANDARD` |
| inputHandlingConfig.invalidInputHandling | `ERROR` |
| inputHandlingConfig.shortInputHandling | `FALLBACK` |

| | |
|---|---|
| inputHandlingConfig.padCharacter | 0 |
| inputHandlingConfig.trimWhitespace | yes |

### CL_RUT_DV_7 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 from the right.

Used by: CL_RUT_PASO_2

#### CONFIGURATION

| | |
|---|---|
| weightList | 2 3 4 5 6 7 2 |
| modulusNumber | 11 |
| checkDigitIndex | 7 |
| calculateChecksumRightToLeft | yes |
| numDigitsForCheckdigitCalculation | 7 |
| numericAlgorithm | CL_SIN_CAMBIO |
| preserveRegex | [.\-] |
| inputHandlingConfig.characterHandling | STANDARD |
| inputHandlingConfig.invalidInputHandling | ERROR |
| inputHandlingConfig.shortInputHandling | FALLBACK |
| inputHandlingConfig.padCharacter | 0 |
| inputHandlingConfig.trimWhitespace | yes |

### CL_RUT_DV_8 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 from the right.

Used by: CL_RUT_PASO_2

#### CONFIGURATION

| | |
|---|---|
| weightList | 2 3 4 5 6 7 2 3 |
| modulusNumber | 11 |
| checkDigitIndex | 8 |
| calculateChecksumRightToLeft | yes |
| numDigitsForCheckdigitCalculation | 8 |
| numericAlgorithm | CL_SIN_CAMBIO |
| preserveRegex | [.\-] |
| inputHandlingConfig.characterHandling | STANDARD |
| inputHandlingConfig.invalidInputHandling | ERROR |
| inputHandlingConfig.shortInputHandling | FALLBACK |
| inputHandlingConfig.padCharacter | 0 |
| inputHandlingConfig.trimWhitespace | yes |

### CL_RUT_PASO_1 REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

Used by: CL_RUT

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| (0*)(\d{2}\.?\d{3}\.?\d{3}-?[0-9kK]) | keep · CL_RUT_CUERPO_8 |
| (0*)(\d\.?\d{3}\.?\d{3}-?[0-9kK]) | keep · CL_RUT_CUERPO_7 |

| | |
|---|---|
| `(0*)(\d{3}\.?\d{3}-?[0-9kK])` | keep · `CL_RUT_CUERPO_6` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_RUT_PASO_2 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CL_RUT`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)(\d{2}\.?\d{3}\.?\d{3}-?)(9)` | keep · keep · replace with `K` |
| `(0*)(\d\.?\d{3}\.?\d{3}-?)(9)` | keep · keep · replace with `K` |
| `(0*)(\d{3}\.?\d{3}-?)(9)` | keep · keep · replace with `K` |
| `(0*)(\d{2}\.?\d{3}\.?\d{3}-?[0-9])` | keep · `CL_RUT_DV_8` |
| `(0*)(\d\.?\d{3}\.?\d{3}-?[0-9])` | keep · `CL_RUT_DV_7` |
| `(0*)(\d{3}\.?\d{3}-?[0-9])` | keep · `CL_RUT_DV_6` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_SEXO REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L2_SEXO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(femenino\|masculino)` | `CL_SEXO_PALABRA` |
| `(?i)(mujer\|hombre)` | `CL_SEXO_MUJER_HOMBRE` |
| `(?i)(female\|male)` | `CL_SEXO_INGLES` |
| `(?i)([fm])` | `CL_SEXO_F_M` |
| `(?i)(h)` | `CL_SEXO_H_M` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

---

### CL_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `CL_SEXO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-sexo-f-m.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |

| | |
|---|---|
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-h-m.txt`, chosen by a keyed hash.

Used by: `CL_SEXO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-sexo-h-m.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_SEXO_INGLES SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-ingles.txt`, chosen by a keyed hash.

Used by: `CL_SEXO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-sexo-ingles.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `CL_SEXO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-sexo-mujer-hombre.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_SEXO_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-palabra.txt`, chosen by a keyed hash.

Used by: `CL_SEXO`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-sexo-palabra.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |

| | |
|---|---|
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_SIN_CAMBIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_RUT_DV_8` , `CL_RUT_DV_7` , `CL_RUT_DV_6`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(.*)` | keep |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cl-sin-informacion.txt` , chosen by a keyed hash.

Used by: `CL_CATEGORIA_SUPRIMIDA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-sin-informacion.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_LOOKUP_FILE` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L1_TARJETA`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)([1-9][\d\s\-]{11,22}\d)` | keep · `dlpx-core:Credit Card` |
| otherwise | keep |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

Used by: `CL_L1_TELEFONO`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(0*)(\+?56[\s\-]?)?(\(?9\)?[\s\-]?)(\d{4})([\s\-]?)(\d{4})` | keep · keep · keep · `CL_CM_ALFANUM` · keep · `CL_CM_ALFANUM` |
| `(0*)(\+?56[\s\-]?)?(\(?(?:2\|[3-7]\d)\)?[\s\-]?)(\d{3,4})([\s\-]?)(\d{4})` | keep · keep · keep · `CL_CM_ALFANUM` · keep · `CL_CM_ALFANUM` |
| otherwise | `CL_CM_ALFANUM` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |
| requireMask | no |

### CL_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATO]`, and the 948 terms of `cl-texto-nombres.txt` with `[NOMBRE]`.

Used by: `CL_L1_TEXTO_LIBRE`, `CL_L3_SALUD_TEXTO_CLINICO`

#### PATTERNS, TRIED IN ORDER

| |
|---|
| `\d{1,2}\.\d{3}\.\d{3}-[\dkK]` |
| `\d{7,8}-[\dkK]` |
| `[\w.+\-]+@[\w\-]+(\.[\w\-]+)+` |
| `\+?56\d{9}` |
| `(?<!\d)9\d{8}(?!\d)` |
| `(?<![A-Za-z])[BCDFGHJKLPRSTVWXYZ]{4}-?\d{2}(?!\d)` |
| `(?<!\d)\d{13,19}(?!\d)` |
| `(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)` |

#### CONFIGURATION

| | |
|---|---|
| regExRedactValue | `[DATO]` |
| lookupFile | `cl-texto-nombres.txt` |
| lookupFileRedactValue | `[NOMBRE]` |
| isDenyList | yes |

### CL_TRAMO_FONASA SECURE LOOKUP

Replaces the value with one of the 4 values in `cl-tramo-fonasa.txt`, chosen by a keyed hash.

Used by: `CL_PREVISION_SALUD`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-tramo-fonasa.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

### CL_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_VIVIENDA_LISTA`.

Used by: `CL_L3_SOCIOEC_VIVIENDA`

#### PATTERNS, TRIED IN ORDER

| | |
|---|---|
| `(?i)(s[ií]\|no\|true\|false\|[sny01])` | `CL_BANDERA` |
| `(0*?)(?:(\d{1,6}))` | keep · `CL_CM_ALFANUM` |
| otherwise | `CL_VIVIENDA_LISTA` |

#### CONFIGURATION

| | |
|---|---|
| trimInput | yes |

| | |
|---|---|
| requireMask | no |

### CL_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cl-vivienda.txt`, chosen by a keyed hash.

Used by: `CL_VIVIENDA`

#### CONFIGURATION

| | |
|---|---|
| lookupFile | `cl-vivienda.txt` |
| hashMethod | `SHA256` |
| maskedValueCase | `PRESERVE_INPUT` |
| inputCaseSensitive | no |
| trimWhitespaceFromInput | yes |
| trimWhitespaceInLookupFile | yes |

APPENDIX B

# Files

The lookup and detection files the policy reads. In Delphix each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

| FILE | LINES | USED BY | FIRST LINES |
|---|---|---|---|
| `cl-afp.txt` | 11 | `CL_AFP_LISTA` | AFP Capital · AFP Cuprum · AFP Habitat · AFP Modelo |
| `cl-antecedentes.txt` | 3 | `CL_ANTECEDENTES_LISTA` | Sin antecedentes · Con antecedentes · Sin información |
| `cl-apellidos.txt` | 194 | `CL_APELLIDO` | González · Muñoz · Rojas · Díaz |
| `cl-bandera-0-1.txt` | 2 | `CL_BANDERA_0_1` | 0 · 1 |
| `cl-bandera-s-n.txt` | 2 | `CL_BANDERA_S_N` | S · N |
| `cl-bandera-si-no.txt` | 2 | `CL_BANDERA_SI_NO` | Si · No |
| `cl-bandera-true-false.txt` | 2 | `CL_BANDERA_TRUE_FALSE` | true · false |
| `cl-bandera-y-n.txt` | 2 | `CL_BANDERA_Y_N` | Y · N |
| `cl-beneficios-sociales.txt` | 21 | `CL_BENEFICIO_SOCIAL_LISTA` | Pensión Garantizada Universal · Subsidio Único Familiar · Asignación Familiar · Aporte Familiar Permanente |
| `cl-cie10-decimal.txt` | 33 | `CL_CIE10_DECIMAL` | E11.9 · E78.5 · J45.9 · J06.9 |
| `cl-cie10.txt` | 37 | `CL_CIE10` | I10 · E11 · E78 · J45 |
| `cl-codigo-comuna-generalizado.txt` | 346 | `CL_CODIGO_COMUNA_TABLA` | 15101,15101 · 15102,15101 · 15201,15101 · 15202,15101 |
| `cl-comuna-generalizada.txt` | 428 | `CL_COMUNA` | Arica,Arica · Camarones,Arica · Putre,Arica · General Lagos,Arica |
| `cl-detectar-apellidos.txt` | 245 | `CL_L1_APELLIDO – List` `CL_L1_NOMBRE_COMPLETO – List` | González · Gonzalez · Muñoz · Munoz |
| `cl-detectar-gse.txt` | 9 | `CL_L3_SOCIOEC_NIVEL – List` | abc1 · c1 · c1a · c1b |
| `cl-detectar-nacionalidades.txt` | 48 | `CL_L2_NACIONALIDAD – List` | Chilena · Venezolana · Peruana · Haitiana |
| `cl-detectar-nombres.txt` | 229 | `CL_L1_NOMBRE – List` `CL_L1_NOMBRE_COMPLETO – List` | María · Maria · José · Jose |
| `cl-detectar-sexo-letra.txt` | 3 | `CL_L2_SEXO – List` | f · m · h |
| `cl-detectar-sexo.txt` | 8 | `CL_L2_SEXO – List` | femenino · masculino · mujer · hombre |

| FILE | LINES | USED BY | FIRST LINES |
|---|---|---|---|
| cl-diagnosticos.txt | 30 | CL_DIAGNOSTICO_TEXTO | Hipertensión arterial esencial · Diabetes mellitus tipo 2 · Asma bronquial · Lumbago |
| cl-digito-verificador.txt | 11 | CL_RUT_DV | 0 · 1 · 2 · 3 |
| cl-direcciones.txt | 3,000 | CL_DIRECCION | El Peumo 762 · Calle Los Robles 1026 · Avenida España 873, depto 1909 · Avenida Matta 1445 |
| cl-discapacidad.txt | 8 | CL_DISCAPACIDAD_LISTA | Física · Visual · Auditiva · Intelectual |
| cl-empleadores.txt | 25 | CL_EMPLEADOR | Comercial Los Andes SpA · Servicios Integrales del Sur Ltda. · Constructora Cordillera S.A. · Transportes Pacífico Norte SpA |
| cl-establecimientos.txt | 15 | CL_ESTABLECIMIENTO | Escuela Básica N° 12 · Escuela Rural Los Aromos · Liceo Bicentenario A-45 · Liceo Técnico Profesional B-23 |
| cl-estado-civil.txt | 6 | CL_ESTADO_CIVIL | Soltero · Casado · Viudo · Divorciado |
| cl-estado-crediticio.txt | 8 | CL_MOROSIDAD_LISTA | Al día · Mora 1 a 30 días · Mora 31 a 90 días · Mora sobre 90 días |
| cl-financiamiento-estudios.txt | 12 | CL_FINANCIAMIENTO_ESTUDIOS_LISTA | Gratuidad · Beca Bicentenario · Beca Juan Gómez Millas · Beca Nuevo Milenio |
| cl-gse.txt | 7 | CL_GSE | ABC1 · C1a · C1b · C2 |
| cl-identidad-genero.txt | 8 | CL_IDENTIDAD_GENERO_LISTA | Mujer · Hombre · Mujer trans · Hombre trans |
| cl-ideologias.txt | 8 | CL_IDEOLOGIA_LISTA | Izquierda · Centroizquierda · Centro · Centroderecha |
| cl-medicamentos.txt | 26 | CL_MEDICAMENTO_LISTA | Paracetamol · Ibuprofeno · Losartán · Enalapril |
| cl-nacionalidades.txt | 17 | CL_NACIONALIDAD | Chilena · Venezolana · Peruana · Haitiana |
| cl-nivel-educacional.txt | 10 | CL_NIVEL_EDUCACIONAL | Sin estudios · Básica incompleta · Básica completa · Media incompleta |
| cl-nombres.txt | 189 | CL_NOMBRE_PILA | María · José · Juan · Luis |
| cl-ocupaciones.txt | 40 | CL_OCUPACION | Administrativo · Vendedor · Técnico en mantención · Contador |
| cl-orientacion-sexual.txt | 9 | CL_ORIENTACION_SEXUAL_LISTA | Heterosexual · Homosexual · Lesbiana · Gay |
| cl-partidos.txt | 15 | CL_PARTIDO_POLITICO_LISTA | Partido Demócrata Cristiano · Partido por la Democracia · Partido Radical de Chile · Partido Socialista de Chile |
| cl-prevision-salud.txt | 18 | CL_PREVISION_SALUD_LISTA | FONASA A · FONASA B · FONASA C · FONASA D |
| cl-pueblos.txt | 13 | CL_PUEBLO_ORIGINARIO_LISTA | Mapuche · Aymara · Rapa Nui · Lickanantay |
| cl-quintil.txt | 5 | CL_QUINTIL | 1 · 2 · 3 · 4 |
| cl-religiones.txt | 12 | CL_RELIGION_LISTA | Católica · Evangélica o protestante · Testigo de Jehová · Santos de los Últimos Días |
| cl-rsh-tramo-numero.txt | 7 | CL_RSH_TRAMO_NUMERO | 40 · 50 · 60 · 70 |

| FILE | LINES | USED BY | FIRST LINES |
|---|---|---|---|
| `cl-rsh-tramo-texto.txt` | 7 | `CL_RSH_TRAMO_TEXTO` | Tramo 40% · Tramo 50% · Tramo 60% · Tramo 70% |
| `cl-sexo-f-m.txt` | 2 | `CL_SEXO_F_M` | F · M |
| `cl-sexo-h-m.txt` | 2 | `CL_SEXO_H_M` | H · M |
| `cl-sexo-ingles.txt` | 2 | `CL_SEXO_INGLES` | Female · Male |
| `cl-sexo-mujer-hombre.txt` | 2 | `CL_SEXO_MUJER_HOMBRE` | Mujer · Hombre |
| `cl-sexo-palabra.txt` | 2 | `CL_SEXO_PALABRA` | Femenino · Masculino |
| `cl-sin-informacion.txt` | 1 | `CL_SUPRIMIR` | Sin información |
| `cl-texto-nombres.txt` | 948 | `CL_TEXTO_LIBRE` | María · MARÍA · Maria · MARIA |
| `cl-tramo-fonasa.txt` | 4 | `CL_TRAMO_FONASA` | A · B · C · D |
| `cl-vivienda.txt` | 10 | `CL_VIVIENDA_LISTA` | Propia pagada · Propia pagándose · Arrendada con contrato · Arrendada sin contrato |

APPENDIX C

# Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

**E1** `producto` `prod` `articulo` `item` `empresa` `emp` `compania` `razon` `fantasia` `archivo` `arch` `file` `calle` `via` `comuna` `region` `provincia` `ciudad` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `estado` `colegio` `establecimiento` `institucion` `isapre` `afp` `curso` `carrera` `asignatura` `documento` `doc` `centro` `unidad` `area` `depto` `departamento` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `examen` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lugar` `local` `tienda` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `org` `organizacion` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `equipo` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `cliente` `cli` `paciente` `pac` `trabajador` `trab` `funcionario` `func` `alumno` `estudiante` `afiliado` `beneficiario` `titular` `madre` `padre` `tutor` `apoderado` `conyuge` `pareja` `medico` `doctor` `profesional` `responsable` `contacto` `emergencia` `aval` `codeudor` `deudor` `remitente` `destinatario` `receptor` `firmante` `testigo` `representante` `propietario` `arrendatario` `asegurado` `contratante` `victima` `denunciante` `imputado` `socio` `donante` `heredero` `causante` `persona` `pers` `conductor` `chofer` `vendedor` `ejecutivo` `agente` `empleado` `colaborador` `completos?` `y_?apellidos?` `apellidos?`

**E2** `producto` `prod` `articulo` `item` `empresa` `emp` `compania` `razon` `fantasia` `archivo` `arch` `file` `calle` `via` `comuna` `region` `provincia` `ciudad` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `estado` `colegio` `establecimiento` `institucion` `isapre` `afp` `curso` `carrera` `asignatura` `documento` `doc` `centro` `unidad` `area` `depto` `departamento` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `examen` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lugar` `local` `tienda` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `org` `organizacion` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `equipo` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `cliente` `cli` `paciente` `pac` `trabajador` `trab` `funcionario` `func` `alumno` `estudiante` `afiliado` `beneficiario` `titular` `madre` `padre` `tutor` `apoderado` `conyuge` `pareja` `medico` `doctor` `profesional` `responsable` `contacto` `emergencia` `aval` `codeudor` `deudor` `remitente` `destinatario` `receptor` `firmante` `testigo` `representante` `propietario` `arrendatario` `asegurado` `contratante` `victima` `denunciante` `imputado` `socio` `donante` `heredero` `causante` `persona` `pers` `conductor` `chofer` `vendedor` `ejecutivo` `agente` `empleado` `colaborador` `completo` `compl` `full` `y_?apellidos?` `apellidos?`

**E3** `producto` `prod` `articulo` `item` `empresa` `emp` `compania` `razon` `fantasia` `archivo` `arch` `file` `calle` `via` `comuna` `region` `provincia` `ciudad` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `estado` `colegio` `establecimiento` `institucion` `isapre` `afp` `curso` `carrera` `asignatura` `documento` `doc` `centro` `unidad` `area` `depto` `departamento` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `examen` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lugar` `local` `tienda` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `org` `organizacion` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `equipo` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `completo`

| | |
|---|---|
| **E4** | `producto` `prod` `articulo` `item` `empresa` `emp` `compania` `razon` `fantasia` `archivo` `arch` `file` `calle` `via` `comuna` `region` `provincia` `ciudad` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `estado` `colegio` `establecimiento` `institucion` `isapre` `afp` `curso` `carrera` `asignatura` `documento` `doc` `centro` `unidad` `area` `depto` `departamento` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `examen` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lugar` `local` `tienda` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `org` `organizacion` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `equipo` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` |
| **E5** | `ip` `mac` `web` `url` `correo` `mail` `electronica` `email` |
| **E6** | `producto` `articulo` `sucursal` `interna` `tipo` `registro` `primaria` `foranea` `elector` |
| **E7** | `fijo` `variable` `monto` `adicional` `servicio` `tarifa` `valor` `cuenta` `extra` |
| **E8** | `produccion` `desempeno` `anual` `gestion` `termino` `vacaciones` `trabajador` `colacion` `movilizacion` |
| **E9** | `medicos` `morbidos` `m[oó]rbidos` `familiares` `clinicos` `academicos` `laborales` `comerciales` `generales` |

APPENDIX D

# Discovery policy and classifiers

The discovery policy `CL – Ley 21.719 – v6` runs these 134 classifiers, with an assignment threshold of 60%.

Ley 21.719 - datos personales y sensibles

| CLASSIFIER | KIND | DATA CLASS |
|---|---|---|
| `CL_L1_RUT – Path` | COLUMN NAME | `CL_L1_RUT` |
| `CL_L1_RUT – Type` | DATA TYPE | `CL_L1_RUT` |
| `CL_L1_RUT – Regex` | VALUE FORMAT | `CL_L1_RUT` |
| `CL_L1_RUT_CUERPO – Path` | COLUMN NAME | `CL_L1_RUT_CUERPO` |
| `CL_L1_RUT_CUERPO – Type` | DATA TYPE | `CL_L1_RUT_CUERPO` |
| `CL_L1_RUT_CUERPO – Regex` | VALUE FORMAT | `CL_L1_RUT_CUERPO` |
| `CL_L1_RUT_DV – Path` | COLUMN NAME | `CL_L1_RUT_DV` |
| `CL_L1_RUT_DV – Type` | DATA TYPE | `CL_L1_RUT_DV` |
| `CL_L1_RUT_DV – Regex` | VALUE FORMAT | `CL_L1_RUT_DV` |
| `CL_L1_NOMBRE – Path` | COLUMN NAME | `CL_L1_NOMBRE` |
| `CL_L1_NOMBRE – List` | KNOWN VALUES | `CL_L1_NOMBRE` |
| `CL_L1_APELLIDO – Path` | COLUMN NAME | `CL_L1_APELLIDO` |
| `CL_L1_APELLIDO – List` | KNOWN VALUES | `CL_L1_APELLIDO` |
| `CL_L1_NOMBRE_COMPLETO – Path` | COLUMN NAME | `CL_L1_NOMBRE_COMPLETO` |
| `CL_L1_NOMBRE_COMPLETO – List` | KNOWN VALUES | `CL_L1_NOMBRE_COMPLETO` |
| `CL_L1_EMAIL – Path` | COLUMN NAME | `CL_L1_EMAIL` |
| `CL_L1_EMAIL – Type` | DATA TYPE | `CL_L1_EMAIL` |
| `CL_L1_EMAIL – Regex` | VALUE FORMAT | `CL_L1_EMAIL` |
| `CL_L1_TELEFONO – Path` | COLUMN NAME | `CL_L1_TELEFONO` |
| `CL_L1_TELEFONO – Regex` | VALUE FORMAT | `CL_L1_TELEFONO` |
| `CL_L1_DIRECCION – Path` | COLUMN NAME | `CL_L1_DIRECCION` |
| `CL_L1_DIRECCION – Type` | DATA TYPE | `CL_L1_DIRECCION` |
| `CL_L1_DIRECCION – Regex` | VALUE FORMAT | `CL_L1_DIRECCION` |
| `CL_L1_DIRECCION_COMPLEMENTO – Path` | COLUMN NAME | `CL_L1_DIRECCION_COMPLEMENTO` |
| `CL_L1_NUMERO_DOCUMENTO – Path` | COLUMN NAME | `CL_L1_NUMERO_DOCUMENTO` |
| `CL_L1_NUMERO_DOCUMENTO – Regex` | VALUE FORMAT | `CL_L1_NUMERO_DOCUMENTO` |
| `CL_L1_PASAPORTE – Path` | COLUMN NAME | `CL_L1_PASAPORTE` |
| `CL_L1_PASAPORTE – Regex` | VALUE FORMAT | `CL_L1_PASAPORTE` |
| `CL_L1_DOCUMENTO_EXTRANJERO – Path` | COLUMN NAME | `CL_L1_DOCUMENTO_EXTRANJERO` |
| `CL_L1_CUENTA_BANCARIA – Path` | COLUMN NAME | `CL_L1_CUENTA_BANCARIA` |
| `CL_L1_TARJETA – Path` | COLUMN NAME | `CL_L1_TARJETA` |

| CLASSIFIER | KIND | DATA CLASS |
|---|---|---|
| CL_L1_TARJETA – Regex | VALUE FORMAT | CL_L1_TARJETA |
| CL_L1_IP – Path | COLUMN NAME | CL_L1_IP |
| CL_L1_IP – Regex | VALUE FORMAT | CL_L1_IP |
| CL_L1_DISPOSITIVO – Path | COLUMN NAME | CL_L1_DISPOSITIVO |
| CL_L1_DISPOSITIVO – Regex | VALUE FORMAT | CL_L1_DISPOSITIVO |
| CL_L1_PATENTE – Path | COLUMN NAME | CL_L1_PATENTE |
| CL_L1_PATENTE – Regex | VALUE FORMAT | CL_L1_PATENTE |
| CL_L1_VEHICULO_ID – Path | COLUMN NAME | CL_L1_VEHICULO_ID |
| CL_L1_VEHICULO_ID – Regex | VALUE FORMAT | CL_L1_VEHICULO_ID |
| CL_L1_NUMERO_CONTRATO – Path | COLUMN NAME | CL_L1_NUMERO_CONTRATO |
| CL_L1_USUARIO_RRSS – Path | COLUMN NAME | CL_L1_USUARIO_RRSS |
| CL_L1_CREDENCIAL – Path | COLUMN NAME | CL_L1_CREDENCIAL |
| CL_L1_CREDENCIAL – Regex | VALUE FORMAT | CL_L1_CREDENCIAL |
| CL_L1_GEOLOCALIZACION – Path | COLUMN NAME | CL_L1_GEOLOCALIZACION |
| CL_L1_GEOLOCALIZACION – Regex | VALUE FORMAT | CL_L1_GEOLOCALIZACION |
| CL_L1_TEXTO_LIBRE – Path | COLUMN NAME | CL_L1_TEXTO_LIBRE |
| CL_L1_TEXTO_LIBRE – Type | DATA TYPE | CL_L1_TEXTO_LIBRE |
| CL_L1_TEXTO_LIBRE – Regex | VALUE FORMAT | CL_L1_TEXTO_LIBRE |
| CL_L2_FECHA_NACIMIENTO – Path | COLUMN NAME | CL_L2_FECHA_NACIMIENTO |
| CL_L2_FECHA_NACIMIENTO – Type | DATA TYPE | CL_L2_FECHA_NACIMIENTO |
| CL_L2_ANIO_NACIMIENTO – Path | COLUMN NAME | CL_L2_ANIO_NACIMIENTO |
| CL_L2_ANIO_NACIMIENTO – Type | DATA TYPE | CL_L2_ANIO_NACIMIENTO |
| CL_L2_EDAD – Path | COLUMN NAME | CL_L2_EDAD |
| CL_L2_EDAD – Type | DATA TYPE | CL_L2_EDAD |
| CL_L2_FECHA_EVENTO – Path | COLUMN NAME | CL_L2_FECHA_EVENTO |
| CL_L2_FECHA_EVENTO – Type | DATA TYPE | CL_L2_FECHA_EVENTO |
| CL_L2_SEXO – Path | COLUMN NAME | CL_L2_SEXO |
| CL_L2_SEXO – List | KNOWN VALUES | CL_L2_SEXO |
| CL_L2_COMUNA – Path | COLUMN NAME | CL_L2_COMUNA |
| CL_L2_COMUNA – Values | VALUE FORMAT | CL_L2_COMUNA |
| CL_L2_CODIGO_COMUNA – Path | COLUMN NAME | CL_L2_CODIGO_COMUNA |
| CL_L2_CODIGO_COMUNA – Type | DATA TYPE | CL_L2_CODIGO_COMUNA |
| CL_L2_CODIGO_COMUNA – Values | VALUE FORMAT | CL_L2_CODIGO_COMUNA |
| CL_L2_CODIGO_POSTAL – Path | COLUMN NAME | CL_L2_CODIGO_POSTAL |
| CL_L2_CODIGO_POSTAL – Regex | VALUE FORMAT | CL_L2_CODIGO_POSTAL |
| CL_L2_NACIONALIDAD – Path | COLUMN NAME | CL_L2_NACIONALIDAD |
| CL_L2_NACIONALIDAD – List | KNOWN VALUES | CL_L2_NACIONALIDAD |

| CLASSIFIER | KIND | DATA CLASS |
|---|---|---|
| CL_L2_ESTADO_CIVIL – Path | COLUMN NAME | CL_L2_ESTADO_CIVIL |
| CL_L2_ESTADO_CIVIL – Values | VALUE FORMAT | CL_L2_ESTADO_CIVIL |
| CL_L2_OCUPACION – Path | COLUMN NAME | CL_L2_OCUPACION |
| CL_L2_EMPLEADOR – Path | COLUMN NAME | CL_L2_EMPLEADOR |
| CL_L2_NIVEL_EDUCACIONAL – Path | COLUMN NAME | CL_L2_NIVEL_EDUCACIONAL |
| CL_L2_NIVEL_EDUCACIONAL – Values | VALUE FORMAT | CL_L2_NIVEL_EDUCACIONAL |
| CL_L2_ESTABLECIMIENTO_EDUCACIONAL – Path | COLUMN NAME | CL_L2_ESTABLECIMIENTO_EDUCACIONAL |
| CL_L2_CARGAS_FAMILIARES – Path | COLUMN NAME | CL_L2_CARGAS_FAMILIARES |
| CL_L2_CARGAS_FAMILIARES – Type | DATA TYPE | CL_L2_CARGAS_FAMILIARES |
| CL_L3_ETNIA – Path | COLUMN NAME | CL_L3_ETNIA |
| CL_L3_ETNIA – Values | VALUE FORMAT | CL_L3_ETNIA |
| CL_L3_SALUD_DIAGNOSTICO – Path | COLUMN NAME | CL_L3_SALUD_DIAGNOSTICO |
| CL_L3_SALUD_DIAGNOSTICO – Regex | VALUE FORMAT | CL_L3_SALUD_DIAGNOSTICO |
| CL_L3_SALUD_MEDICAMENTO – Path | COLUMN NAME | CL_L3_SALUD_MEDICAMENTO |
| CL_L3_SALUD_MEDICAMENTO – Values | VALUE FORMAT | CL_L3_SALUD_MEDICAMENTO |
| CL_L3_SALUD_IDENTIFICADOR – Path | COLUMN NAME | CL_L3_SALUD_IDENTIFICADOR |
| CL_L3_SALUD_TEXTO_CLINICO – Path | COLUMN NAME | CL_L3_SALUD_TEXTO_CLINICO |
| CL_L3_SALUD_TEXTO_CLINICO – Type | DATA TYPE | CL_L3_SALUD_TEXTO_CLINICO |
| CL_L3_SALUD_RESULTADO_EXAMEN – Path | COLUMN NAME | CL_L3_SALUD_RESULTADO_EXAMEN |
| CL_L3_SALUD_GRUPO_SANGUINEO – Path | COLUMN NAME | CL_L3_SALUD_GRUPO_SANGUINEO |
| CL_L3_SALUD_GRUPO_SANGUINEO – Values | VALUE FORMAT | CL_L3_SALUD_GRUPO_SANGUINEO |
| CL_L3_SALUD_DISCAPACIDAD – Path | COLUMN NAME | CL_L3_SALUD_DISCAPACIDAD |
| CL_L3_SALUD_DISCAPACIDAD – Values | VALUE FORMAT | CL_L3_SALUD_DISCAPACIDAD |
| CL_L3_SALUD_SEXUAL_REPRODUCTIVA – Path | COLUMN NAME | CL_L3_SALUD_SEXUAL_REPRODUCTIVA |
| CL_L3_SALUD_MENTAL_ADICCIONES – Path | COLUMN NAME | CL_L3_SALUD_MENTAL_ADICCIONES |
| CL_L3_BIOMETRICO – Path | COLUMN NAME | CL_L3_BIOMETRICO |
| CL_L3_BIOMETRICO – Type | DATA TYPE | CL_L3_BIOMETRICO |
| CL_L3_PERFIL_GENETICO – Path | COLUMN NAME | CL_L3_PERFIL_GENETICO |
| CL_L3_PERFIL_GENETICO – Regex | VALUE FORMAT | CL_L3_PERFIL_GENETICO |
| CL_L3_ORIENTACION_SEXUAL – Path | COLUMN NAME | CL_L3_ORIENTACION_SEXUAL |
| CL_L3_ORIENTACION_SEXUAL – Values | VALUE FORMAT | CL_L3_ORIENTACION_SEXUAL |
| CL_L3_IDENTIDAD_GENERO – Path | COLUMN NAME | CL_L3_IDENTIDAD_GENERO |
| CL_L3_IDENTIDAD_GENERO – Values | VALUE FORMAT | CL_L3_IDENTIDAD_GENERO |
| CL_L3_VIDA_SEXUAL – Path | COLUMN NAME | CL_L3_VIDA_SEXUAL |
| CL_L3_RELIGION – Path | COLUMN NAME | CL_L3_RELIGION |
| CL_L3_RELIGION – Values | VALUE FORMAT | CL_L3_RELIGION |
| CL_L3_CONVICCION_IDEOLOGICA – Path | COLUMN NAME | CL_L3_CONVICCION_IDEOLOGICA |

| CLASSIFIER | KIND | DATA CLASS |
|---|---|---|
| CL_L3_CONVICCION_IDEOLOGICA – Values | VALUE FORMAT | CL_L3_CONVICCION_IDEOLOGICA |
| CL_L3_AFILIACION_POLITICA – Path | COLUMN NAME | CL_L3_AFILIACION_POLITICA |
| CL_L3_AFILIACION_POLITICA – Values | VALUE FORMAT | CL_L3_AFILIACION_POLITICA |
| CL_L3_AFILIACION_SINDICAL – Path | COLUMN NAME | CL_L3_AFILIACION_SINDICAL |
| CL_L3_AFILIACION_GREMIAL – Path | COLUMN NAME | CL_L3_AFILIACION_GREMIAL |
| CL_L3_SOCIOEC_PREVISION_SALUD – Path | COLUMN NAME | CL_L3_SOCIOEC_PREVISION_SALUD |
| CL_L3_SOCIOEC_PREVISION_SALUD – Values | VALUE FORMAT | CL_L3_SOCIOEC_PREVISION_SALUD |
| CL_L3_SOCIOEC_PLAN_SALUD – Path | COLUMN NAME | CL_L3_SOCIOEC_PLAN_SALUD |
| CL_L3_SOCIOEC_RSH – Path | COLUMN NAME | CL_L3_SOCIOEC_RSH |
| CL_L3_SOCIOEC_NIVEL – Path | COLUMN NAME | CL_L3_SOCIOEC_NIVEL |
| CL_L3_SOCIOEC_NIVEL – List | KNOWN VALUES | CL_L3_SOCIOEC_NIVEL |
| CL_L3_SOCIOEC_BENEFICIO_SOCIAL – Path | COLUMN NAME | CL_L3_SOCIOEC_BENEFICIO_SOCIAL |
| CL_L3_SOCIOEC_BENEFICIO_SOCIAL – Values | VALUE FORMAT | CL_L3_SOCIOEC_BENEFICIO_SOCIAL |
| CL_L3_SOCIOEC_MOROSIDAD – Path | COLUMN NAME | CL_L3_SOCIOEC_MOROSIDAD |
| CL_L3_SOCIOEC_MONTO_DEUDA – Path | COLUMN NAME | CL_L3_SOCIOEC_MONTO_DEUDA |
| CL_L3_SOCIOEC_MONTO_DEUDA – Type | DATA TYPE | CL_L3_SOCIOEC_MONTO_DEUDA |
| CL_L3_SOCIOEC_INGRESOS – Path | COLUMN NAME | CL_L3_SOCIOEC_INGRESOS |
| CL_L3_SOCIOEC_INGRESOS – Type | DATA TYPE | CL_L3_SOCIOEC_INGRESOS |
| CL_L3_SOCIOEC_PREVISION_AFP – Path | COLUMN NAME | CL_L3_SOCIOEC_PREVISION_AFP |
| CL_L3_SOCIOEC_PREVISION_AFP – Values | VALUE FORMAT | CL_L3_SOCIOEC_PREVISION_AFP |
| CL_L3_SOCIOEC_SALDO_PREVISIONAL – Path | COLUMN NAME | CL_L3_SOCIOEC_SALDO_PREVISIONAL |
| CL_L3_SOCIOEC_SALDO_PREVISIONAL – Type | DATA TYPE | CL_L3_SOCIOEC_SALDO_PREVISIONAL |
| CL_L3_SOCIOEC_VIVIENDA – Path | COLUMN NAME | CL_L3_SOCIOEC_VIVIENDA |
| CL_L3_SOCIOEC_VIVIENDA – Values | VALUE FORMAT | CL_L3_SOCIOEC_VIVIENDA |
| CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS – Path | COLUMN NAME | CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS |
| CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS – Values | VALUE FORMAT | CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS |
| CL_L3_PENAL_ANTECEDENTES – Path | COLUMN NAME | CL_L3_PENAL_ANTECEDENTES |
| CL_L3_PENAL_CAUSA – Path | COLUMN NAME | CL_L3_PENAL_CAUSA |
| CL_L3_PENAL_CAUSA – Regex | VALUE FORMAT | CL_L3_PENAL_CAUSA |