DELPHIX CONTINUOUS COMPLIANCE · DISCOVERY POLICY

Costa Rica — Ley 8968 de Protección de la Persona frente al Tratamiento de sus Datos Personales

Discovery and masking of Costa Rican personal data: cédula de identidad, DIMEX and NITE, the IBAN with valid check digits, the address written as directions from a landmark, quasi-identifiers, the sensitive data article 9.1 forbids a private party to process, health data, the condición socioeconómica article 3 e) calls sensitive, and criminal records.

81	143	168
DATA CLASSES	CLASSIFIERS	ALGORITHMS

Discovery policy `CR – Ley 8968 – v3`

Version 3 of October 12, 2026 · Assignment threshold 60%

Contents

The first sections explain what the policy is for and how it works. The data class chapters then describe every data class: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the policy contains.

1	**About this discovery policy**	
2	**Ley 8968 in brief**	
3	**Desasociación, pseudonymization and non-production copies**	
4	**How sensitive data is discovered**	
5	**How data is masked**	
6	**Essential and extended packs**	
7	**Data classes at a glance**	

PART 8 · DIRECT IDENTIFIERS

8.1	**Cédula de identidad**	CR_L1_CEDULA
8.2	**DIMEX**	CR_L1_DIMEX
8.3	**NITE**	CR_L1_NITE
8.4	**Passport**	CR_L1_PASAPORTE
8.5	**Social security number**	CR_L1_SEGURO_SOCIAL
8.6	**Student code**	CR_L1_CODIGO_ESTUDIANTE
8.7	**Professional registration**	CR_L1_MATRICULA_PROFESIONAL
8.8	**Given name**	CR_L1_NOMBRE
8.9	**Surname**	CR_L1_APELLIDO
8.10	**Full name**	CR_L1_NOMBRE_COMPLETO
8.11	**E-mail address**	CR_L1_EMAIL
8.12	**Telephone number**	CR_L1_TELEFONO
8.13	**Address and señas**	CR_L1_DIRECCION
8.14	**Address detail**	CR_L1_DIRECCION_COMPLEMENTO
8.15	**Bank account (IBAN)**	CR_L1_CUENTA_BANCARIA
8.16	**Payment card**	CR_L1_TARJETA
8.17	**Digital wallet**	CR_L1_BILLETERA
8.18	**IP address**	CR_L1_IP
8.19	**Device identifier**	CR_L1_DISPOSITIVO
8.20	**Cookie and tracking identifier**	CR_L1_COOKIE
8.21	**Vehicle plate**	CR_L1_PLACA
8.22	**Vehicle identifiers**	CR_L1_VEHICULO
8.23	**Property identifiers**	CR_L1_INMUEBLE
8.24	**Contract and case numbers**	CR_L1_CONTRATO

8.25	Username and social handle	CR_L1_USUARIO
8.26	Credentials and secrets	CR_L1_CREDENCIAL
8.27	Photograph and recordings	CR_L1_IMAGEN
8.28	Geolocation	CR_L1_GEOLOCALIZACION
8.29	Free text	CR_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Date of birth	CR_L2_FECHA_NACIMIENTO
9.2	Year of birth	CR_L2_ANIO_NACIMIENTO
9.3	Age	CR_L2_EDAD
9.4	Other dates about the person	CR_L2_FECHA_EVENTO
9.5	Sex	CR_L2_SEXO
9.6	Distrito and cantón	CR_L2_DISTRITO
9.7	DTA code and postal code	CR_L2_CODIGO_DTA
9.8	Barrio	CR_L2_BARRIO
9.9	Marital status	CR_L2_ESTADO_CIVIL
9.10	Occupation	CR_L2_OCUPACION
9.11	Employer	CR_L2_EMPLEADOR
9.12	Level of education	CR_L2_NIVEL_EDUCATIVO
9.13	Educational institution	CR_L2_INSTITUCION_EDUCATIVA
9.14	Dependants	CR_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA (ART. 3 E AND ART. 9.1)

10.1	Racial or ethnic origin	CR_L3_ETNIA
10.2	Indigenous people and territory	CR_L3_PUEBLO_INDIGENA
10.3	Nationality	CR_L3_NACIONALIDAD
10.4	Migratory condition	CR_L3_CONDICION_MIGRATORIA
10.5	Religion	CR_L3_RELIGION
10.6	Philosophical convictions	CR_L3_CONVICCION_FILOSOFICA
10.7	Political opinion	CR_L3_OPINION_POLITICA
10.8	Party membership	CR_L3_AFILIACION_PARTIDARIA
10.9	Trade union membership	CR_L3_AFILIACION_SINDICAL
10.10	Biometric data	CR_L3_BIOMETRICO
10.11	Genetic data	CR_L3_GENETICO
10.12	Sexual orientation	CR_L3_ORIENTACION_SEXUAL
10.13	Sexual life	CR_L3_VIDA_SEXUAL
10.14	Gender identity	CR_L3_IDENTIDAD_GENERO
10.15	Victim of violence	CR_L3_VICTIMA

PART 11 · HEALTH DATA (ART. 9.1 D)

11.1	Clinical record number	CR_SALUD_IDENTIFICADOR
11.2	Health coverage	CR_SALUD_COBERTURA
11.3	Diagnosis	CR_SALUD_DIAGNOSTICO
11.4	Procedure	CR_SALUD_PROCEDIMIENTO
11.5	Medicine	CR_SALUD_MEDICAMENTO
11.6	Clinical notes	CR_SALUD_TEXTO_CLINICO
11.7	Test result	CR_SALUD_RESULTADO_EXAMEN
11.8	HIV and sexually transmitted infections	CR_SALUD_VIH
11.9	Blood group	CR_SALUD_GRUPO_SANGUINEO
11.10	Disability	CR_SALUD_DISCAPACIDAD
11.11	Occupational health	CR_SALUD_OCUPACIONAL
11.12	Reproductive health	CR_SALUD_REPRODUCTIVA
11.13	Mental health	CR_SALUD_MENTAL

PART 12 · ECONOMIC DATA (ART. 3 E, ART. 1 AND ART. 9.4)

12.1	Credit standing	CR_FIN_HISTORIAL_CREDITICIO
12.2	Debt	CR_FIN_DEUDA
12.3	Income	CR_FIN_INGRESOS
12.4	Assets	CR_FIN_PATRIMONIO
12.5	Pension	CR_FIN_PENSION
12.6	Social programme	CR_FIN_PROGRAMA_SOCIAL
12.7	Condición socioeconómica	CR_FIN_CONDICION_SOCIOECONOMICA
12.8	Housing tenure	CR_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS (ART. 8 C AND LEY 6723)

13.1	Criminal record	CR_PENAL_ANTECEDENTES
13.2	Judicial file number	CR_PENAL_EXPEDIENTE
14	The IBAN check digits	
15	Where people live: distritos, cantones and the code that is also the postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Discovery policy and classifiers	

1

About this discovery policy

This discovery policy finds the personal data in a Costa Rican database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and cédulas alone is not enough: a birth date, a sex and one small distrito already point at a handful of people, and most of the 492 distritos of Costa Rica are small. The policy works in the layers where the risk is:

- **Direct identifiers** — cédula de identidad, DIMEX, NITE, passport, social-security and student numbers, professional registration, names, contact, address and señas, bank accounts, cards, devices, cookies, plates, property, photographs, free text.
- **Quasi-identifiers** — birth date, year of birth, age, sex, distrito and cantón, the code of the División Territorial Administrativa that doubles as the postal code, barrio, marital status, occupation, employer, education, dependants.
- **Sensitive data** — the categories of article 3 e) and article 9.1: racial or ethnic origin, political opinions, religious, spiritual or philosophical convictions, biomedical and genetic information, sexual life and orientation; and the attributes the anti-discrimination clause of article 4 reaches: indigenous people, nationality, migratory condition, gender identity, trade union membership.
- **Health data**, which article 9.1 lets only health care itself process, and only under professional secrecy.
- **Economic data** — income, debts, assets, credit standing and social programmes. Article 3 e) names the **condición socioeconómica** among the sensitive data, and article 1 extends the law to the data of a person's **bienes**.
- **Criminal records**, whose entries the Registro Judicial cancels on a scale of its own.

Each group below says what each data class is, how it is masked and why. Discovery runs one discovery policy of 141 classifiers at a threshold of 60; the masking is 81 data classes with their algorithms.

2

Ley 8968 in brief

Costa Rica has had a data protection law since 2011: the **Ley 8968 de Protección de la Persona frente al Tratamiento de sus Datos Personales**, in force since 5 September 2011 and **never amended**. Its regulation, Decreto Ejecutivo 37554-JP, was amended twice, by Decreto 40008-JP in 2016 and by Decreto 41582 in 2019, both on the registry of databases rather than on the principles. The authority is the **Agencia de Protección de Datos de los Habitantes (Prodhab)**, created by article 15.

Two features of the law shape this policy. First, article 1 states its reach over the data of a person **o bienes** — the assets as well as the person — which puts property, income and patrimony squarely inside it. Second, only a **persona física** is a titular: article 3 b) defines a personal datum as any datum relating to an identified or identifiable natural person, and article 3 g) and article 2 v) of the regulation define the interesado the same way. A company is not a data subject in Costa Rica, so a cédula jurídica is left exactly as it is.

On sensitive data the law is unusually strict. Article 3 e) defines it as "información relativa al **fuero íntimo** de la persona, como por ejemplo los que revelen origen racial, opiniones políticas, convicciones religiosas o espirituales, **condición socioeconómica**, información **biomédica o genética**, vida y orientación sexual, **entre otros**" — an open list, and the only one in the region that names the socio-economic condition. Article 9.1 then **prohibits** processing it, with five narrow exceptions, and article 31 a) makes processing it a **falta**

gravísima for a private party: fifteen to thirty base salaries and the suspension of the fichero for up to six months.

Article 9.3 is worth reading beside it. It lists what is **not** a datum of unrestricted access even when it sits in a public register: "la dirección exacta de la residencia", "la fotografía", "los números de teléfono privados y otros de igual naturaleza cuyo tratamiento pueda afectar los derechos y los intereses de la persona titular". Three data classes of this policy exist because that paragraph names them.

3

Desasociación, pseudonymization and non-production copies

Costa Rica writes the technique into the law itself. Article 6.1 says that personal data which may affect its holder shall in no case be kept beyond ten years from the facts recorded, and that "en caso de que sea necesaria su conservación, más allá del plazo estipulado, deberán ser **desasociados de su titular**". Article 2 r) of the regulation defines the procedure: "acción y efecto de **disociar** los datos personales, de modo que la información que se obtenga no pueda asociarse o vincularse a persona determinada o determinable". No other law of the region orders the technique in the body of the statute.

Be precise about what masking achieves against that definition. The engine masks with a key, and whoever holds the key can reproduce the mapping: the result is a **pseudonymized** copy, not a dissociated one in the strict sense of article 2 r), and it is still personal data. What it is, squarely, is the "medida de índole técnica" article 10 requires and the "medida de seguridad lógica" articles 34 to 37 of the regulation ask the responsable to choose by risk — including the **riesgo residual** article 36 f) asks to be computed. To reach desasociación the key has to be discarded, and nothing in a masked copy should be read as anonymous while it exists.

Two more provisions make the risk-based reading explicit. Article 2 q) of the regulation says a natural person is identifiable when the identity can be determined "directa o **indirectamente**, mediante cualquier información referida a su identidad anatómica, fisiológica, psíquica, económica, cultural o social", and adds that "una persona física **no se considerará identificable** si dicha identificación requiere plazos o actividades desproporcionadas". Article 8 d) of the law limits its principles for databases used for statistical, historical or scientific purposes "cuando **no exista riesgo** de que las personas sean identificadas". Both put the question where this policy answers it: how much work it would take to point at one person again.

4

How sensitive data is discovered

A discovery job looks at every column of its rule set and asks each classifier of the discovery policy how confident it is that the column belongs to its data class. The policy uses the four classifier frameworks of Delphix:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the data class out. It never assigns a data class on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per data class, and the column is assigned to the data class with the highest confidence when it reaches the assignment threshold of the discovery policy — **60%** here. Values that do not match a format or a list count against their data class by the classifier's reject strength.

These are the names Data Control Tower gives the objects: data classes, classifiers and a discovery policy, run by a discovery job. A Continuous Compliance Engine used on its own calls the same objects domains, classifiers and a profile set, run by a profiling job; everything in this document applies to both.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. Discovery tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Discovery proposes; it does not decide. Review the data classes assigned in the rule set before running a masking job, and look for columns the policy left unassigned.

How data is masked

Each data class names one algorithm, which a masking job applies to every column the rule set assigns to the data class. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each data class shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine and compliance node uses the same keys.

Where an algorithm that comes with Delphix already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the policy names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name, the one an engine uses; Data Control Tower lists them without the prefix (`CM Numeric`, `CreditCard`, `BloodType SL`). They are on every engine and in every Data Control Tower, and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. With other keys the masked values differ; their shape does not.

Essential and extended packs

The policy can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create just its data classes, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the discovery policy.

PACK	DATA CLASSES	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	26	20	5
Extended	81	143	168	59

The essential pack holds these data classes, marked **Essential** in the tables and chapters:

- Cédula de identidad — `CR_L1_CEDULA`
- DIMEX — `CR_L1_DIMEX`
- NITE — `CR_L1_NITE`
- Passport — `CR_L1_PASAPORTE`
- Given name — `CR_L1_NOMBRE`
- Surname — `CR_L1_APELLIDO`
- Full name — `CR_L1_NOMBRE_COMPLETO`
- E-mail address — `CR_L1_EMAIL`
- Telephone number — `CR_L1_TELEFONO`
- Address and señas — `CR_L1_DIRECCION`
- Address detail — `CR_L1_DIRECCION_COMPLEMENTO`
- Date of birth — `CR_L2_FECHA_NACIMIENTO`

> With fewer data classes competing, a column that a data class of the extended pack would claim by its name can be proposed for an essential data class instead — a numeric code, for instance, can look like a telephone number. Review the discovery result.

Data classes at a glance

Every data class of the policy, how it is found and the algorithm that masks it.

DATA CLASS	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Cédula de identidad ESSENTIAL `CR_L1_CEDULA`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CR_DOCUMENTO`
DIMEX ESSENTIAL `CR_L1_DIMEX`	COLUMN NAME · VALUE FORMAT	`CR_DIMEX`
NITE ESSENTIAL `CR_L1_NITE`	COLUMN NAME · VALUE FORMAT	`CR_NITE`
Passport ESSENTIAL `CR_L1_PASAPORTE`	COLUMN NAME · VALUE FORMAT	`CR_CM_DIGITOS_LETRAS`
Social security number `CR_L1_SEGURO_SOCIAL`	COLUMN NAME	`CR_CM_ALFANUM`
Student code `CR_L1_CODIGO_ESTUDIANTE`	COLUMN NAME	`CR_CM_ALFANUM`
Professional registration `CR_L1_MATRICULA_PROFESIONAL`	COLUMN NAME	`CR_CM_ALFANUM`
Given name ESSENTIAL `CR_L1_NOMBRE`	COLUMN NAME · KNOWN VALUES	`CR_NOMBRES`
Surname ESSENTIAL `CR_L1_APELLIDO`	COLUMN NAME · KNOWN VALUES	`CR_APELLIDOS`
Full name ESSENTIAL `CR_L1_NOMBRE_COMPLETO`	COLUMN NAME · KNOWN VALUES	`CR_NOMBRE_COMPLETO`
E-mail address ESSENTIAL `CR_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CR_EMAIL`
Telephone number ESSENTIAL `CR_L1_TELEFONO`	COLUMN NAME · VALUE FORMAT	`CR_TELEFONO`
Address and señas ESSENTIAL `CR_L1_DIRECCION`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CR_DIRECCION`
Address detail ESSENTIAL `CR_L1_DIRECCION_COMPLEMENTO`	COLUMN NAME	`CR_CM_ALFANUM`
Bank account (IBAN) `CR_L1_CUENTA_BANCARIA`	COLUMN NAME · VALUE FORMAT	`CR_CUENTA`
Payment card `CR_L1_TARJETA`	COLUMN NAME · VALUE FORMAT	`CR_TARJETA`
Digital wallet `CR_L1_BILLETERA`	COLUMN NAME · VALUE FORMAT	`CR_CM_ALFANUM`
IP address `CR_L1_IP`	COLUMN NAME · VALUE FORMAT	`CR_IP`
Device identifier `CR_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`CR_CM_HEX`

DATA CLASS	FOUND BY	ALGORITHM
Cookie and tracking identifier `CR_L1_COOKIE`	COLUMN NAME	`CR_CM_ALFANUM`
Vehicle plate `CR_L1_PLACA`	COLUMN NAME · VALUE FORMAT	`CR_PLACA`
Vehicle identifiers `CR_L1_VEHICULO`	COLUMN NAME · VALUE FORMAT	`CR_CM_ALFANUM`
Property identifiers `CR_L1_INMUEBLE`	COLUMN NAME · VALUE FORMAT	`CR_INMUEBLE`
Contract and case numbers `CR_L1_CONTRATO`	COLUMN NAME	`CR_CM_ALFANUM`
Username and social handle `CR_L1_USUARIO`	COLUMN NAME	`CR_CM_ALFANUM`
Credentials and secrets `CR_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`CR_REDACTAR`
Photograph and recordings `CR_L1_IMAGEN`	COLUMN NAME	`CR_REDACTAR`
Geolocation `CR_L1_GEOLOCALIZACION`	COLUMN NAME · VALUE FORMAT	`CR_COORDENADA`
Free text `CR_L1_TEXTO_LIBRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CR_TEXTO_LIBRE`
QUASI-IDENTIFIERS		
Date of birth ESSENTIAL `CR_L2_FECHA_NACIMIENTO`	COLUMN NAME · DATA TYPE	`CR_FECHA_NACIMIENTO`
Year of birth `CR_L2_ANIO_NACIMIENTO`	COLUMN NAME · DATA TYPE	`CR_ANIO`
Age `CR_L2_EDAD`	COLUMN NAME · DATA TYPE	`CR_EDAD`
Other dates about the person `CR_L2_FECHA_EVENTO`	COLUMN NAME · DATA TYPE	`CR_FECHA_EVENTO`
Sex `CR_L2_SEXO`	COLUMN NAME · KNOWN VALUES	`CR_SEXO`
Distrito and cantón `CR_L2_DISTRITO`	COLUMN NAME · VALUE FORMAT	`CR_DISTRITO`
DTA code and postal code `CR_L2_CODIGO_DTA`	COLUMN NAME · VALUE FORMAT	`CR_CODIGO_DTA`
Barrio `CR_L2_BARRIO`	COLUMN NAME	`CR_BARRIO`
Marital status `CR_L2_ESTADO_CIVIL`	COLUMN NAME · VALUE FORMAT	`CR_ESTADO_CIVIL`
Occupation `CR_L2_OCUPACION`	COLUMN NAME	`CR_OCUPACION_O_CODIGO`
Employer `CR_L2_EMPLEADOR`	COLUMN NAME	`CR_EMPLEADOR`
Level of education `CR_L2_NIVEL_EDUCATIVO`	COLUMN NAME · VALUE FORMAT	`CR_NIVEL_EDUCATIVO`

DATA CLASS	FOUND BY	ALGORITHM
Educational institution `CR_L2_INSTITUCION_EDUCATIVA`	COLUMN NAME	`CR_INSTITUCION_EDUCATIVA`
Dependants `CR_L2_PERSONAS_A_CARGO`	COLUMN NAME DATA TYPE	`CR_CONTEO_LIMITADO`
SENSITIVE DATA (ART. 3 E AND ART. 9.1)		
Racial or ethnic origin `CR_L3_ETNIA`	COLUMN NAME VALUE FORMAT	`CR_ETNIA`
Indigenous people and territory `CR_L3_PUEBLO_INDIGENA`	COLUMN NAME VALUE FORMAT	`CR_PUEBLO`
Nationality `CR_L3_NACIONALIDAD`	COLUMN NAME VALUE FORMAT	`CR_NACIONALIDAD`
Migratory condition `CR_L3_CONDICION_MIGRATORIA`	COLUMN NAME VALUE FORMAT	`CR_CONDICION_MIGRATORIA`
Religion `CR_L3_RELIGION`	COLUMN NAME VALUE FORMAT	`CR_RELIGION`
Philosophical convictions `CR_L3_CONVICCION_FILOSOFICA`	COLUMN NAME	`CR_CATEGORIA_SUPRIMIDA`
Political opinion `CR_L3_OPINION_POLITICA`	COLUMN NAME VALUE FORMAT	`CR_PREFERENCIA_POLITICA`
Party membership `CR_L3_AFILIACION_PARTIDARIA`	COLUMN NAME VALUE FORMAT	`CR_PARTIDO`
Trade union membership `CR_L3_AFILIACION_SINDICAL`	COLUMN NAME VALUE FORMAT	`CR_CATEGORIA_SUPRIMIDA`
Biometric data `CR_L3_BIOMETRICO`	COLUMN NAME DATA TYPE	`CR_REDACTAR`
Genetic data `CR_L3_GENETICO`	COLUMN NAME VALUE FORMAT	`CR_REDACTAR`
Sexual orientation `CR_L3_ORIENTACION_SEXUAL`	COLUMN NAME VALUE FORMAT	`CR_ORIENTACION_SEXUAL`
Sexual life `CR_L3_VIDA_SEXUAL`	COLUMN NAME	`CR_CATEGORIA_SUPRIMIDA`
Gender identity `CR_L3_IDENTIDAD_GENERO`	COLUMN NAME VALUE FORMAT	`CR_IDENTIDAD_GENERO`
Victim of violence `CR_L3_VICTIMA`	COLUMN NAME	`CR_CATEGORIA_SUPRIMIDA`
HEALTH DATA (ART. 9.1 D)		
Clinical record number `CR_SALUD_IDENTIFICADOR`	COLUMN NAME	`CR_CM_ALFANUM`
Health coverage `CR_SALUD_COBERTURA`	COLUMN NAME VALUE FORMAT	`CR_COBERTURA_SALUD`
Diagnosis `CR_SALUD_DIAGNOSTICO`	COLUMN NAME VALUE FORMAT	`CR_DIAGNOSTICO`
Procedure `CR_SALUD_PROCEDIMIENTO`	COLUMN NAME	`CR_PROCEDIMIENTO`

DATA CLASS	FOUND BY	ALGORITHM
Medicine CR_SALUD_MEDICAMENTO	COLUMN NAME VALUE FORMAT	CR_MEDICAMENTO
Clinical notes CR_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	CR_TEXTO_LIBRE
Test result CR_SALUD_RESULTADO_EXAMEN	COLUMN NAME	CR_CM_ALFANUM
HIV and sexually transmitted infections CR_SALUD_VIH	COLUMN NAME	CR_CATEGORIA_SUPRIMIDA
Blood group CR_SALUD_GRUPO_SANGUINEO	COLUMN NAME VALUE FORMAT	dlpx-core:BloodType SL
Disability CR_SALUD_DISCAPACIDAD	COLUMN NAME VALUE FORMAT	CR_DISCAPACIDAD
Occupational health CR_SALUD_OCUPACIONAL	COLUMN NAME VALUE FORMAT	CR_APTITUD_LABORAL
Reproductive health CR_SALUD_REPRODUCTIVA	COLUMN NAME	CR_CATEGORIA_SUPRIMIDA
Mental health CR_SALUD_MENTAL	COLUMN NAME	CR_CATEGORIA_SUPRIMIDA
ECONOMIC DATA (ART. 3 E, ART. 1 AND ART. 9.4)		
Credit standing CR_FIN_HISTORIAL_CREDITICIO	COLUMN NAME	CR_HISTORIAL_CREDITICIO
Debt CR_FIN_DEUDA	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Income CR_FIN_INGRESOS	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Assets CR_FIN_PATRIMONIO	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Pension CR_FIN_PENSION	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Social programme CR_FIN_PROGRAMA_SOCIAL	COLUMN NAME VALUE FORMAT	CR_PROGRAMA_SOCIAL
Condición socioeconómica CR_FIN_CONDICION_SOCIOECONOMICA	COLUMN NAME VALUE FORMAT	CR_CONDICION_SOCIOECONOMICA
Housing tenure CR_FIN_VIVIENDA	COLUMN NAME VALUE FORMAT	CR_TENENCIA_VIVIENDA
CRIMINAL RECORDS (ART. 8 C AND LEY 6723)		
Criminal record CR_PENAL_ANTECEDENTES	COLUMN NAME	CR_ANTECEDENTES
Judicial file number CR_PENAL_EXPEDIENTE	COLUMN NAME VALUE FORMAT	CR_EXPEDIENTE_JUDICIAL

PART 8

Direct identifiers

Data that identifies a person on its own. The cédula de identidad is the key of every Costa Rican record and carries no check digit, so nothing has to be recomputed and the whole number changes, the provincia digit included. The IBAN is the exception: it does carry check digits, and it comes out with valid ones. Only a **persona física** is a titular in Costa Rica, so a cédula jurídica passes through untouched.

8.1 Cédula de identidad

CR_L1_CEDULA

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The number of the Tribunal Supremo de Elecciones, the key of every Costa Rican record. Its canonical form is ten digits, `0P-TTTT-AAAA` — a provincia, the tomo and the asiento of the birth entry — and the leading zeroes are usually dropped, so it is written `1-0234-0567` or `102340567`.

The same data class takes the other numbers a document column holds: a DIMEX of eleven or twelve digits, a NITE of the 3-120 series, and the cédula jurídica of a company. A driving licence carries the cédula of its holder, so a licence column lands here too.

HOW IT IS FOUND

COLUMN NAME CR_L1_CEDULA – Path

90% `c[eé]dula(_?(de_?)?identidad)?` *(except when followed by* `jur[ií]dica` *)* `ced` `n(o|ro|um|umero)_?(c[eé]dula|documento|doc|identificaci[oó]n|id(ent)?)` `doc_?identidad` `nro_?doc` `num_?doc` `identificaci[oó]n` *(except when preceded by* `(tipo|cod|codigo|desc|clase)_` *; except when followed by* `tipo` *,* `clase` *,* `juridica` *,* `jur[ií]dica` *)* `identificaci[oó]n_?f[ií]sica` `licencia(_?(de_?)?conducir)?(_?n(o|ro|um|umero))?` `n(o|ro|um|umero)_?licencia` `licencia_?cosevi` `driver_?licen[cs]e` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|pensionado|jubilado|aportante|patrono)_?(cedula|ced|doc|documento)` `cedula_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|pensionado|jubilado|aportante|patrono)`

60% `documento` `doc`

DATA TYPE CR_L1_CEDULA – Type

Accepts text (length 6 or more) or number (length 6 or more); any other type rules the data class out.

VALUE FORMAT CR_L1_CEDULA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d-\d{4}-\d{4})`	95%	
`0*(?:0\d-\d{4}-\d{4})`	90%	
`0*(?:\d-\d{3}-\d{3})`	70%	
`0*(?:[1-9]\d{8})`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Digit by digit, keeping the hyphens. The cédula carries **no check digit** — the Dirección General de Tributación validates it against the Registro Civil itself — so nothing has to be recomputed and the whole number changes, **the provincia digit included**: it is the provincia of the birth entry and would otherwise survive into the copy. The first digit is mapped inside 1 to 9, never to a zero, so the result is still a well-formed cédula.

A **cédula jurídica** is left exactly as it is: article 3 b) and g) reach only a natural person, so a company is no titular and its number is nobody's personal datum. From the fourth quarter of 2026 that number may be alphanumeric, `3-101-A00001`, under Decreto 44648-MJ; both forms pass through.

`CR_DOCUMENTO` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

> `CR_NITE` REGEX DECOMPOSE
>
> Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.
>
> > `CR_CM_DIGITOS` CHARACTER MAPPING
> >
> > Maps each character to another of its group (1 groups), keeping length and format.
> >
> > `CR_CM_ALFANUM` CHARACTER MAPPING
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_DIMEX` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.
>
> `CR_CEDULA` REGEX DECOMPOSE
>
> Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.
>
> > `CR_CM_DIGITO_1_9` CHARACTER MAPPING
> >
> > Maps each character to another of its group (1 groups), keeping length and format.
> >
> > `CR_CM_DIGITOS_ANCHO_FIJO` CHARACTER MAPPING
> >
> > Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1-0234-0567	→	**9-2975-1730**
102340567	→	**929751730**
155812345678	→	**211863565214**
3-120-123456	→	**3-120-904292**
3-101-123456	→	**3-101-123456**

8.2 DIMEX

CR_L1_DIMEX

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The Documento de Identidad Migratorio para Extranjeros, the identity number of a foreign resident: eleven or twelve digits, no separators, and the identifier the Dirección General de Tributación uses for them.

HOW IT IS FOUND

COLUMN NAME CR_L1_DIMEX — Path

90%

```
dimex
c[eé]dula_?(de_?)?residencia
documento_?(de_?)?identidad_?migratorio
n(o|ro|um|umero)_?(dimex|residencia|extranjer[ií]a|refugiado)
carn[eé]_?(de_?)?(residencia|refugiado)
id_?migratorio
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|pensionado|jubilado|aportante|patrono)_?dimex
```

VALUE FORMAT CR_L1_DIMEX — Regex

PATTERN	STRENGTH	NOTES
`0*(?:[1-9]\d{10,11})`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every digit changes and the length stays, because the length is what tells a DIMEX from a cédula in a mixed column. The DIMEX has no check digit either.

`CR_DIMEX` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS` .

> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
155812345678	→	**211863565214**
12345678901	→	**06176626922**

8.3 NITE

CR_L1_NITE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The Número de Identificación Tributaria Especial, for a person with no cédula and no DIMEX. The **3-120** series belongs to a foreign natural person and the **3-130** series to a foreign company.

HOW IT IS FOUND

COLUMN NAME CR_L1_NITE — Path

90%

```
nite
n(o|ro|um|umero)_?(de_?)?identificaci[oó]n_?(tributaria_?)?especial
identificacion_?tributaria_?especial
```

VALUE FORMAT CR_L1_NITE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[\s\-]?120[\s\-]?\d{6})`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

This is where the law draws its sharpest line: the six digits of a **3-120** number are masked, because that number belongs to a natural person, and a **3-130** number is left alone, because it belongs to a company and a company is no titular. The two look alike and are treated opposite ways.

`CR_NITE` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

> `CR_CM_DIGITOS` **CHARACTER MAPPING**
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3-120-123456	→	**3-120-904292**
3130ABC123	→	**3130ABC123**

8.4 Passport

CR_L1_PASAPORTE

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The passport number, Costa Rican or foreign: a letter or two and six to eight digits.

HOW IT IS FOUND

COLUMN NAME CR_L1_PASAPORTE — Path

90% `pasaporte[a-z0-9_]*` `n(o|ro|um|umero)_?pasaporte` `passport[a-z0-9_]*`

VALUE FORMAT CR_L1_PASAPORTE — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{1,2}\d{6,8}`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Letters become letters and digits become digits, so the number keeps the shape the issuing country gives it.

`CR_CM_DIGITOS_LETRAS` **CHARACTER MAPPING**

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BLM123	→	**ZJQ771**

8.5 Social security number

CR_L1_SEGURO_SOCIAL

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The numbers of the Caja Costarricense de Seguro Social: the número de asegurado, the número patronal of an employer, the planilla and the SICERE codes.

HOW IT IS FOUND

> COLUMN NAME CR_L1_SEGURO_SOCIAL — Path
>
> 85% `n(o|ro|um|umero)_?(asegurado|seguro_?social|patronal|patrono|afiliado|afiliaci[oó]n)` `c[oó]digo_?(asegurado|patrono|patronal)` `asegurado[a-z0-9_]*` `ccss[a-z0-9_]*` `n[uú]mero_?ccss` `carn[eé]_?(ccss|asegurado)` `planilla_?(ccss|n(o|ro|um|umero))` `sicere`

HOW IT IS MASKED

Character by character, keeping the shape and any separators. These numbers are built from the cédula, so they are as identifying as it is.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.6 Student code

CR_L1_CODIGO_ESTUDIANTE

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The identifier a school, a colegio or a university gives a student, and the cédula escolar.

HOW IT IS FOUND

> COLUMN NAME CR_L1_CODIGO_ESTUDIANTE — Path
>
> 80% `c[oó]digo_?(de_?)?(estudiante|alumno|matr[ií]cula)` `cod_?(alumno|estudiante)` `n(o|ro|um|umero)_?(de_?)?(matr[ií]cula|estudiante)` `carn[eé]_?(de_?)?(estudiante|universitario)` `id_?(alumno|estudiante)` `c[eé]dula_?escolar` `identificaci[oó]n_?estudiantil`

HOW IT IS MASKED

Character by character. It is a direct identifier inside its own institution, which is where the roster lives.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.7 Professional registration

CR_L1_MATRICULA_PROFESIONAL

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The number of a colegio profesional — the código médico, the número de colegiado, the carné — and the título number.

HOW IT IS FOUND

COLUMN NAME CR_L1_MATRICULA_PROFESIONAL – Path

85% `c[oó]digo_?(profesional|m[eé]dico)` `n(o|ro|um|umero)_?(de_?)?` `(colegiado|incorporaci[oó]n|registro_?profesional)` `colegiado` `incorporaci[oó]n_?(al_?)?` `colegio` `carn[eé]_?profesional` `n(o|ro|um|umero)_?(de_?)?t[ií]tulo`

HOW IT IS MASKED

Character by character. The registers are public, which is exactly what makes the number a key back to a named professional.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.8 Given name

CR_L1_NOMBRE

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

A given name on its own: the first, the second, or a column that holds both.

HOW IT IS FOUND

COLUMN NAME CR_L1_NOMBRE – Path

85% `primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `pri(mer)?_?nom` `seg(undo)?_?nom` `nombre_?1` `nombre_?2` `first_?names?` `given_?names?` `fname` `middle_?names?` `nombres` *(except when followed by `completos?`, `y_?apellidos?`, `apellidos?`)*

50% `nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES CR_L1_NOMBRE – List

LIST	VALUES	STRENGTH	FIRST VALUES
`cr-detectar-nombres.txt`	449	70%	Adolfo, Adrián, Adrian, Adriana, Aída, Aida

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word becomes another Costa Rican given name, from a list of 400 taken from the frequency of names in the country — Xinia, Yorleny, Olger and Keylor among them. The particles of a compound name stay where they are, so "María de los Ángeles" keeps its shape.

`CR_NOMBRES` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

> `CR_PALABRA_NOMBRE` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CR_NOMBRE`.
>
> > `CR_NOMBRE` NAME
> >
> > Replaces the name with one of the 400 names in `cr-nombres.txt`.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María de los Ángeles	→	**Hugo de los Álvaro**
JOSÉ PABLO	→	**ELIZABETH DORA**

8.9 Surname

CR_L1_APELLIDO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

The first or the second surname, or a column with both.

HOW IT IS FOUND

> COLUMN NAME CR_L1_APELLIDO — Path
>
> 85% `apellidos?` `primer_?apellido` `segundo_?apellido` `apellido_?(1|2|paterno|materno)` `ape_?(1|2|pat|mat)` `ap_?(paterno|materno)` `last_?names?` `surnames?` `family_?names?` `lname`

> KNOWN VALUES CR_L1_APELLIDO — List
>
LIST	VALUES	STRENGTH	FIRST VALUES
`cr-detectar-apellidos.txt`	539	70%	Abarca, Acevedo, Acosta, Acuña, Acuna, Agüero
>
> Values are split into words, and each word is looked up.
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word becomes another Costa Rican surname, from a list of 420 — Oconitrillo, Cartín, Garbanzo, Jirón and the English surnames of the Caribbean coast among them. "De la Cruz" keeps its particles.

`CR_APELLIDOS` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

> `CR_PALABRA_APELLIDO` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CR_APELLIDO`.
>
> > `CR_APELLIDO` NAME
> >
> > Replaces the name with one of the 420 names in `cr-apellidos.txt`.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Jiménez Oconitrillo	→	**Guadamuz Moreira**

8.10 Full name

CR_L1_NOMBRE_COMPLETO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

The whole name in one column, and the name of a third party — the mother, the father, a guardian, an emergency contact, a fiador.

HOW IT IS FOUND

COLUMN NAME CR_L1_NOMBRE_COMPLETO – Path

90%

`nombres?_?(completos?|y_?apellidos?|apellidos?)` `apellidos?_?(y_?)?nombres?` `nombre_?(del_?|de_?la_?)?`
`(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|contacto|referencia|victima|denunciante|imputado|testigo|medico|docente|socio|heredero|donante|tutor|pensionado|jubilado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)`
`(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|contacto|referencia|victima|denunciante|imputado|testigo|medico|docente|socio|heredero|donante|tutor|pensionado|jubilado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)_?(nombre|nom)` `nom_?`
`(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|contacto|referencia|victima|denunciante|imputado|testigo|medico|docente|socio|heredero|donante|tutor|pensionado|jubilado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `nombre_?`
`(madre|padre|tutor|conyuge|contacto_?emergencia|referencia)` `full_?name` `person_?name`

60%

`madre` `padre` `tutor` `conyuge` `representante_?legal` `apoderado` `fiador` `garante` `beneficiario` `heredero` `titular` `referencia_?(personal|familiar)`

50%

`nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES CR_L1_NOMBRE_COMPLETO – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-nombres.txt	449	65%	Adolfo, Adrián, Adrian, Adriana, Aída, Aida
cr-detectar-apellidos.txt	539	65%	Abarca, Acevedo, Acosta, Acuña, Acuna, Agüero

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Read in the Costa Rican order — one or two given names, the father's surname, the mother's surname — and each word replaced by one of its own kind, so a masked name is still plausibly a person. "Jiménez Oconitrillo, José Pablo" is read the other way round.

`CR_NOMBRE_COMPLETO` REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

> `CR_APELLIDOS` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.
>
> > `CR_PALABRA_APELLIDO` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `CR_APELLIDO`.
> >
> > > `CR_APELLIDO` NAME
> > >
> > > Replaces the name with one of the 420 names in `cr-apellidos.txt`.
> >
> > `CR_CM_ALFANUM` CHARACTER MAPPING
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_NOMBRES` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.
>
> > `CR_PALABRA_NOMBRE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `CR_NOMBRE`.
> >
> > > `CR_NOMBRE` NAME
> > >
> > > Replaces the name with one of the 400 names in `cr-nombres.txt`.

EXAMPLES

VALUE		MASKED
José Pablo Jiménez Oconitrillo	→	**Elizabeth Dora Guadamuz Moreira**
Xinia Jiménez	→	**Kevin Guadamuz**
JIMÉNEZ OCONITRILLO, JOSÉ PABLO	→	**GUADAMUZ MOREIRA, ELIZABETH DORA**

8.11 E-mail address

`CR_L1_EMAIL`

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Any address column, personal or at work.

HOW IT IS FOUND

> COLUMN NAME `CR_L1_EMAIL – Path`
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electr[oó]nico)?[a-z0-9_]*` `dir_?correo` `direcci[oó]n_?(de_?)?correo` `direcci[oó]n_?electr[oó]nica`

> DATA TYPE `CR_L1_EMAIL – Type`
>
> Accepts text (length 5 or more); any other type rules the data class out.

> VALUE FORMAT `CR_L1_EMAIL – Regex`
>
PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	
>
> A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The local part and the domain are masked and the top-level domain becomes **.test**, the suffix reserved for testing: a masked address can never deliver, so a test run cannot mail a real person.

`CR_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
jose.jimenez@gmail.com	→	**sexu.lewebax@pgoeb.test**

8.12 Telephone number

CR_L1_TELEFONO

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Every Costa Rican number has eight digits and no area code: 2 for a landline, 4 for IP telephony, 5 to 8 for a mobile. Article 9.3 keeps the **números de teléfono privados** out of the data of unrestricted access by name, and SINPE Móvil makes a mobile number a payment address as well.

HOW IT IS FOUND

> COLUMN NAME CR_L1_TELEFONO — Path
>
> 85% `tel` `tel[eé]fono[a-z0-9_]*` `tel_?(fijo|casa|habitaci[oó]n|oficina|trabajo|contacto|celular|m[oó]vil)` `celular[a-z0-9_]*` `cel` `m[oó]vil` `whats_?app` `sinpe_?m[oó]vil` `n(o|ro|um|umero)_?(tel|tel[eé]fono|celular|cel|contacto)` `fax` `phone[a-z0-9_]*` `mobile[a-z0-9_]*`

> VALUE FORMAT CR_L1_TELEFONO — Regex
>
PATTERN	STRENGTH	NOTES
`0*(?:(\+?506[\s\-]?)?[5-8]\d{3}[\s\-]?\d{4})`	80%	
`0*(?:(\+?506[\s\-]?)?[24]\d{3}[\s\-]?\d{4})`	60%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The country code and the first digit stay, so a masked number still says landline or mobile; the other seven change and the spacing is kept.

`CR_TELEFONO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.

> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+506 8312 4567	→	**+506 8725 6415**
83124567	→	**87256415**
2222 1234	→	**2727 2351**

8.13 Address and señas

CR_L1_DIRECCION

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

Costa Rica has almost no street addresses: an address is a distance and a direction from a landmark — "200 metros norte de la iglesia católica, casa esquinera color verde" — sometimes a residencial and a house

number, sometimes the avenue-and-calle grid of central San José. The **dirección exacta de la residencia** is the first thing article 9.3 takes out of the data of unrestricted access.

HOW IT IS FOUND

COLUMN NAME CR_L1_DIRECCION — Path

80% `direcci[oó]n[a-z0-9_]*` *(except when preceded by* `mac`, `ip`, `e_?mail`, `web`, `url`, `correo` *; except when followed by list E4)* `domicilio[a-z0-9_]*` `dom_?(residencia|particular|laboral|cliente|fiscal|exacto)` `residencia` `lugar_?(de_?)?residencia` `se[nñ]as(_?(exactas|adicionales|particulares))?` `otras_?se[nñ]as` `address[a-z0-9_]*` *(except when preceded by* `mac`, `ip`, `e_?mail`, `web`, `url` *; except when followed by list E5)*

DATA TYPE CR_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the data class out.

VALUE FORMAT CR_L1_DIRECCION — Regex

PATTERN	STRENGTH	NOTES
`(?i).*\d{2,3}\s*(m|mts|metros)\.?\s+(norte|sur|este|oeste|noreste|noroeste|sureste|suroeste).*`	90%	
`(?i)(urbanizaci[oó]n|residencial|condominio|barrio|caser[ií]o)\s+[a-záéíóúñ0-9.' ]{2,40}.*`	70%	
`(?i).*(avenida|calle)\s*\d{1,3}.*(calle|avenida)\s*\d{1,3}.*`	70%	
`(?i).*\b(contiguo|frente|diagonal|costado|detr[aá]s)\b.*`	60%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The whole line is replaced by a fictitious one from a list of four thousand built in the Costa Rican way: metres and a direction from a landmark, a residencial and a house, or an avenue and a calle. The same input always gives the same output, so a row keeps its neighbours.

`CR_DIRECCION` SECURE LOOKUP

Replaces the value with one of the 4,000 values in `cr-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`200 metros norte de la iglesia católica, casa esquinera color verde`	→	**250 metros oeste y 600 norte de el colegio técnico**
`Urbanización Los Laureles, casa 12`	→	**150 metros suroeste de la cancha de fútbol, casa de dos plantas**

8.14 Address detail

CR_L1_DIRECCION_COMPLEMENTO

ESSENTIAL · COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

What comes beside the address: the apartment, the floor, the tower, the house number, the lote, the etapa, the apartado postal.

HOW IT IS FOUND

COLUMN NAME CR_L1_DIRECCION_COMPLEMENTO — Path

70% `apartamento` `apto` `apto_?n(o|ro|um|umero)` `piso` `torre` `bloque` `block` `casa_?n(o|ro|um|umero)` `n(o|ro|um|umero)_?(casa|apto|apartamento|local|oficina)` `lote` `etapa` `filial` `condominio` `complemento(_?direcci[oó]n)?` `referencia_?(de_?)?(direcci[oó]n|domicilio)` `apartado(_?postal)?` `apdo` `p_?o_?box`

HOW IT IS MASKED

Character by character, keeping the shape: a detail that narrows a building to one door identifies as much as the address.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.15 Bank account (IBAN)

CR_L1_CUENTA_BANCARIA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Since 2017 every Costa Rican account is an IBAN of 22 characters: `CR`, two check digits, a reserved zero, three digits for the bank and fourteen for the account — the 17-digit Cuenta Cliente of SINPE with five characters in front. It is written compact, `CR05015202001026284066`, and printed in groups of four, `CR05 0152 0200 1026 2840 66`.

HOW IT IS FOUND

COLUMN NAME CR_L1_CUENTA_BANCARIA — Path

90% `cuenta_?(bancaria|banco|corriente|ahorros?|cliente|salario|planilla|abono|dep[oó]sito|destino|origen|iban)` `n(o|ro|um|umero)_?(de_?)?(cuenta|cta)` `nro_?cta` `num_?cta` `cta_?(cte|corriente|ahorros?|bancaria|cliente)` `iban[a-z0-9_]*` `cuenta_?iban` `account_?(no|num|number)` `bank_?account`

VALUE FORMAT CR_L1_CUENTA_BANCARIA — Regex

PATTERN	STRENGTH	NOTES
`CR\d{20}`	95%	
`CR\d{2}(\s\d{4}){4}\s\d{2}`	95%	
`0*(?:\d{17})`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The fourteen digits of the account change and the **two check digits are recomputed**, so the masked IBAN passes the ISO 13616 remainder that every library and every Costa Rican system checks. The bank stays — it is not personal data, and keeping it keeps a test account inside a real bank. The last section of this document explains how the remainder is computed.

`CR_CUENTA` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.

`CR_IBAN` **STRING ALGORITHM CHAIN**

Applies `CR_IBAN_1` → `CR_IBAN_2` → `CR_IBAN_3` → `CR_IBAN_4` → `CR_IBAN_5` → `CR_IBAN_6` → `CR_IBAN_RESTAURAR`, in this order. It is made of 59 algorithms that repeat the same step position by position; each one is in Appendix A.

EXAMPLES

VALUE		MASKED
CR05015202001026284066	→	**CR90015206146971126179**
CR05 0152 0200 1026 2840 66	→	**CR52 0152 0781 2781 0212 23**
15202001026284066	→	**15206146971126179**

8.16 Payment card

CR_L1_TARJETA

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The card number, credit or debit, with or without spaces.

HOW IT IS FOUND

COLUMN NAME CR_L1_TARJETA — Path

85% `tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?tarjeta` `pan` `card_?(no|num|number)` `credit_?card` `tc_?(numero|num|nro)`

VALUE FORMAT CR_L1_TARJETA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1-9]\d{12,13}|[1-9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Credit Card, which comes with Delphix: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`CR_TARJETA` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`dlpx-core:Credit Card` **PAYMENT CARD**

Comes with Delphix and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4532 0000 0000 0001	→	**4532 0086 1298 3134**

8.17 Digital wallet

CR_L1_BILLETERA

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The identifier of a wallet or of a crypto address.

HOW IT IS FOUND

COLUMN NAME CR_L1_BILLETERA — Path

85% `billetera(_?(digital|electr[oó]nica|m[oó]vil))?` `wallet(_?(id|address|direccion))?` `kash` `tapp` `monedero_?(digital|electr[oó]nico)` `dinero_?electr[oó]nico` `c[oó]digo_?qr` `qr_?(id|codigo)` `direcci[oó]n_?(bitcoin|btc|wallet)` `btc_?(address|direccion)`

VALUE FORMAT CR_L1_BILLETERA — Regex

PATTERN	STRENGTH	NOTES
`(bc1|[13])[a-zA-HJ-NP-Z0-9]{25,59}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping the shape so that a format check still passes.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.18 IP address

CR_L1_IP

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The address of the device from which a person connected, logged in or filed something.

HOW IT IS FOUND

COLUMN NAME CR_L1_IP — Path

85% `ip` `ip_?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)` `direcci[oó]n_?ip` `dir_?ip` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip`

VALUE FORMAT CR_L1_IP — Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each octet becomes another number between 1 and 254, so the address stays routable-looking; an IPv6 keeps valid hexadecimal.

`CR_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_HEX`.

`CR_OCTETO` NUMERIC MAPPING

Maps the number to another between 1 and 254.

`CR_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
201.196.45.12	→	**133.244.51.94**

8.19 Device identifier

CR_L1_DISPOSITIVO

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC, advertising and session identifiers: numbers that follow one device, and so one person.

HOW IT IS FOUND

COLUMN NAME — CR_L1_DISPOSITIVO — Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `direcci[oó]n_?mac` `device_?(id|uuid|serial)` `id_?(dispositivo|equipo|celular)` `serial_?(equipo|celular|dispositivo)` `advertising_?id` `idfa` `gaid` `session_?id` `id_?sesi[oó]n`

VALUE FORMAT — CR_L1_DISPOSITIVO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Hexadecimal stays hexadecimal and a MAC keeps its colons; an IMEI keeps its fifteen digits.

`CR_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**

8.20 Cookie and tracking identifier

CR_L1_COOKIE

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The identifier a site or a campaign writes into a browser, and the UTM parameters that came with it.

HOW IT IS FOUND

COLUMN NAME — CR_L1_COOKIE — Path

80% `cookie(_?(id|value|valor|nombre))?` `cookies` `_?ga` `_?gid` `fbp` `fbclid` `utm_?(source|medium|campaign|term|content)` `id_?(navegador|browser|visitante)` `visitor_?id` `tracking_?id` `client_?id`

HOW IT IS MASKED

Character by character. It names no one by itself and follows one browsing history, which is why it is a direct identifier here.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.21 Vehicle plate

CR_L1_PLACA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Digits for a private car, three letters and three digits in the alphanumeric series the Registro Nacional opened, and a class prefix for the rest — MOT a motorcycle, CL light cargo, AB a bus, TSJ or TA a taxi.

HOW IT IS FOUND

COLUMN NAME CR_L1_PLACA — Path

85% `placa(_?(veh[ií]culo|auto|moto|n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?placa` `matr[ií]cula(_?(veh[ií]culo|auto|moto))?` *(except when followed by* `profesional`, `m[eé]dica`, `estudiante`, `consular`*)*

`license_?plate` `plate(_?(no|number))?`

VALUE FORMAT CR_L1_PLACA — Regex

PATTERN	STRENGTH	NOTES
`(?i)(MOT|CL|TSJ|AB|SJB)[\s\-]?\d{3,6}`	80%	
`[A-Z]{3}[\s\-]?\d{3}`	50%	
`0*(?:\d{6})`	35%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The class prefix stays and the digits change, so the fleet still looks like a fleet and the plate still points at no owner.

`CR_PLACA` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS_LETRAS`.

> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_CM_DIGITOS_LETRAS` CHARACTER MAPPING
>
> Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BLM123	→	**PNX957**
123456	→	**904292**
MOT123456	→	**MOT904292**

8.22 Vehicle identifiers

CR_L1_VEHICULO

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number, the marchamo and the revisión técnica record.

HOW IT IS FOUND

COLUMN NAME CR_L1_VEHICULO — Path

85% `vin` `chasis` `n(o|ro|um|umero)_?(chasis|motor|serie|vin)` `motor_?n(o|ro|um|umero)` `t[ií]tulo_?(de_?)?propiedad_?veh[ií]culo` `riteve` `dekra` `n(o|ro|um|umero)_?(de_?)?` `revisi[oó]n_?t[eé]cnica` `marchamo`

VALUE FORMAT CR_L1_VEHICULO — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping the seventeen positions of a VIN so that a format check still passes.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.23 Property identifiers

CR_L1_INMUEBLE

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The folio real of the Registro Inmobiliario, `1-234567-000`, the plano catastrado of the Catastro, `SJ-1234567-2010`, and the meter numbers of the utilities. Article 1 of the law reaches the data of a person "o **bienes**", and article 12 of the regulation repeats it.

HOW IT IS FOUND

COLUMN NAME CR_L1_INMUEBLE — Path

85% `folio_?real` `n(o|ro|um|umero)_?(de_?)?(finca|folio|folio_?real|plano|plano_?catastrado|matr[ií]cula_?inmueble|derecho)` `finca(_?(n(o|ro|um|umero)|filial))?` `plano_?catastrado` `matr[ií]cula_?(inmobiliaria|catastral)` `c[oó]digo_?catastral` `n(o|ro|um|umero)_?(de_?)?(medidor|nis|servicio_?el[eé]ctrico)` `nis(_?(ice|cnfl|aya))?`

VALUE FORMAT CR_L1_INMUEBLE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:[1-7]-\d{6}-\d{3})`	80%	
`(?i)(SJ|A|C|H|G|P|L)-\d{6,7}-\d{4}`	80%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The digits change and the separators and the provincia letters stay, so the reference keeps its shape. The registers are public and searchable by number, which is what makes a folio real a route back to an owner.

`CR_INMUEBLE` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM` .

> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_CM_DIGITO_1_9` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1-234567-000	→	**9-172434-000**
SJ-1234567-2010	→	**SJ-5649285-2010**

8.24 Contract and case numbers

CR_L1_CONTRATO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The internal numbers that stand for one person: contract, policy, loan, application, claim, ticket, customer or employee code.

HOW IT IS FOUND

> COLUMN NAME CR_L1_CONTRATO — Path
>
> 70% `n(o|ro|um|umero)_?(contrato|p[oó]liza|cr[eé]dito|pr[eé]stamo|solicitud|expediente_?(administrativo|interno)|tr[aá]mite|referencia|cliente|socio|suscriptor|suministro|servicio|caso|ticket|beneficio|siniestro|reclamo)` `contrato_?(n(o|ro|um|umero))` `c[oó]digo_?(cliente|socio|empleado|afiliado|suministro)` `id_?(cliente|socio|empleado|afiliado)` `n(o|ro)_?(empleado|funcionario)` `c[oó]digo_?(de_?)?(empleado|funcionario|puesto)`

HOW IT IS MASKED

Character by character, keeping prefixes and separators so that joins by format still work. The number is a pseudonym, and a pseudonym that survives the copy links it back.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.25 Username and social handle

CR_L1_USUARIO

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The login, the alias, the nickname and the handle of a social network.

HOW IT IS FOUND

COLUMN NAME — CR_L1_USUARIO — Path

70% `usuario` `user_?name` `username` `login` `alias` `apodo` `nick(_?name)?` `perfil_?(instagram|facebook|twitter|tiktok|linkedin|x)` `instagram` `facebook` `twitter` `tiktok` `linkedin` `red_?social` `handle`

HOW IT IS MASKED

Character by character. A handle is searchable, so it names a person as surely as the name does.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

8.26 Credentials and secrets

CR_L1_CREDENCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PINs, CVVs, tokens, API keys, seed phrases, security questions and answers.

HOW IT IS FOUND

COLUMN NAME — CR_L1_CREDENCIAL — Path

90% `contrase[nñ]a` `clave` *(except when followed by* `catastral`, `primaria`, `for[aá]nea`, `valor`, `producto` *)* `password` `passwd` `pwd` `pass` `hash_?(clave|contrasena|password)` `pin` `c[oó]digo_?(seguridad|verificaci[oó]n|acceso|otp)` `cvv` `cvc` `token(_?(acceso|refresh|api))?` `access_?token` `refresh_?token` `api_?key` `llave_?(api|privada)` `secreto` `secret` `otp` `firma_?(electr[oó]nica|digital)_?(clave|pin)` `pregunta_?secreta` `respuesta_?secreta` `frase_?semilla` `seed_?phrase`

VALUE FORMAT — CR_L1_CREDENCIAL — Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by X characters. These are not masked to de-identify but to stop a copy from carrying working credentials: article 29 b) makes it a falta leve to store or transmit third-party data "por medio de mecanismos inseguros", and a dump with live passwords is that.

`CR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
clave123	→	XXXXXXXX

8.27 Photograph and recordings

`CR_L1_IMAGEN`

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The path or the URL of a photograph, a selfie, a scanned cédula, a video or a call recording. Article 9.3 names **la fotografía** among the things that are not of unrestricted access even when they sit in a public register.

HOW IT IS FOUND

> COLUMN NAME `CR_L1_IMAGEN – Path`
>
> 85% `foto(graf[ií]a)?[a-z0-9_]*` `imagen_?(persona|rostro|perfil|c[eé]dula|documento)` `avatar` `selfie` `retrato` `video_?(persona|entrevista)` `audio_?(voz|llamada)` `grabaci[oó]n(_?(llamada|voz))?` `url_?foto` `ruta_?(foto|imagen)` `photo[a-z0-9_]*` `picture` `image_?(url|path|person)`

HOW IT IS MASKED

Replaced by X characters: the reference is cut, because a path that still resolves hands over the face itself.

`CR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
clave123	→	XXXXXXXX

8.28 Geolocation

`CR_L1_GEOLOCALIZACION`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in columns of their own, and the CRTM05 coordinates the national grid uses.

HOW IT IS FOUND

COLUMN NAME CR_L1_GEOLOCALIZACION – Path

85% `lat` `latitud` `lon` `lng` `longitud` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `georreferenciaci[oó]n` `geolocalizaci[oó]n` `gps(_?(ubicaci[oó]n|posici[oó]n|coordenadas))?` `ubicaci[oó]n_?gps` `crtm05` `lambert`

50% `long`

VALUE FORMAT CR_L1_GEOLOCALIZACION – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(8|9|10|11)\.\d{3,}\s*,\s*-8[2-6]\.\d{3,})`	90%	
`-8[2-6]\.\d{4,}`	50%	
`0*(?:(8|9|10|11)\.\d{4,})`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The integer part and the first decimal stay — about eleven kilometres — and the rest changes: the place is generalized, not moved to another country.

`CR_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`9.935800`	→	**`9.948145`**
`9.935800,-84.092059`	→	**`9.948145,-84.075771`**

8.29 Free text

CR_L1_TEXTO_LIBRE

COLUMN NAME **DATA TYPE** **VALUE FORMAT** **FREE TEXT REDACTION**

WHAT IT IS

Observations, comments, notes, the account of a complaint: the columns where people write whatever they like, and where cédulas, phones and names end up.

HOW IT IS FOUND

COLUMN NAME CR_L1_TEXTO_LIBRE – Path

60% `observaci[oó]n(es)?` `obs` `comentarios?` `notas?` `anotaci[oó]n(es)?` `glosa` `descripci[oó]n_?(queja|reclamo|solicitud|caso|hechos|novedad|atenci[oó]n|denuncia)` `detalle_?(reclamo|solicitud|caso|atenci[oó]n)` `hechos` `relato` `justificaci[oó]n` `mensaje` *(except when preceded by list E6; except when followed by list E7)* `texto(_?libre)?` `resumen_?(caso|atenci[oó]n)` `queja` `reclamo` `denuncia_?texto` `remarks?` `comments?` `notes?` `free_?text` `memo`

DATA TYPE CR_L1_TEXTO_LIBRE – Type

Accepts text (length 30 or more); any other type rules the data class out.

VALUE FORMAT CR_L1_TEXTO_LIBRE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d-\d{4}-\d{4})`	80%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:[5-8]\d{3}[\s\-]?\d{4})`	60%	anywhere in the value

A value that matches none does not count against the data class.

HOW IT IS MASKED

The text is kept and what identifies inside it is redacted: a cédula, a DIMEX, a NITE, an e-mail address, a phone number, a card, an IBAN and an IP become `[DATO]`, and a name from the lists of the policy becomes `[NOMBRE]`.

`CR_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with `[DATO]`, and the 1,944 terms of `cr-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Cliente Jiménez, cédula 1-0234-0567, correo j.jimenez@gmail.com, cel 83124567`	→	**`Cliente [NOMBRE], cédula [DATO], correo [DATO], cel [DATO]`**

PART 9

Quasi-identifiers

Data that identifies nobody alone and identifies almost anybody together. Article 2 q) of the regulation says the identity may be determined **indirectly**, by any information about a person's anatomical, physiological, psychic, economic, cultural or social identity. These columns are not emptied — a test needs ages and places that behave — they are coarsened until a combination stops pointing at one person.

9.1 Date of birth

CR_L2_FECHA_NACIMIENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The date of birth, in a date column or written as text.

HOW IT IS FOUND

COLUMN NAME CR_L2_FECHA_NACIMIENTO – Path

90% `(fecha|fec|fch|f)_?(de_?)?nac(imiento)?` `fnac` `fechanac(imiento)?` `cumplea[ñn]os` `dob` `date_?of_?birth` `birth_?date` `birthday`

DATA TYPE CR_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Moved by up to sixty days either way. The age and the generation survive, the exact date does not — and the exact date with a sex and a distrito is what points at one person.

`CR_FECHA_NACIMIENTO` DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

9.2 Year of birth

CR_L2_ANIO_NACIMIENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The year alone, when the system keeps no full date.

HOW IT IS FOUND

COLUMN NAME CR_L2_ANIO_NACIMIENTO – Path

90% `a[ñn]o_?(de_?)?nac(imiento)?` `anio_?nac(imiento)?` `year_?of_?birth` `birth_?year` `yob`

DATA TYPE CR_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

The decade stays and the last digit changes, so a cohort analysis still works within ten years.

`CR_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `CR_CM_DIGITOS` CHARACTER MAPPING
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

9.3 Age

CR_L2_EDAD

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The age in years, or the band it falls in.

HOW IT IS FOUND

> COLUMN NAME CR_L2_EDAD — Path
>
> 85% `edad(_?(actual|a[nñ]os|anios|paciente|afiliado|cliente|al_?(ingreso|diagn[oó]stico|fallecimiento)))?` `grupo_?etario` `tramo_?(de_?)?edad` `rango_?(de_?)?edad` `quinquenio` `age(_?(years|group))?`

> DATA TYPE CR_L2_EDAD — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

HOW IT IS MASKED

The tens digit stays and the units change, so 37 becomes some other thirty-something; from 100 on the value becomes 90, because a very old age is rare enough to identify.

`CR_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CR_CM_DIGITOS` CHARACTER MAPPING
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

9.4 Other dates about the person

CR_L2_FECHA_EVENTO

COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

Death, marriage, hiring, dismissal, admission, discharge, diagnosis, consultation, pension, arrest, sentence, the issue of the cédula.

HOW IT IS FOUND

COLUMN NAME CR_L2_FECHA_EVENTO – Path

80% `(fecha|fec|fch|f)_?(de_?)?(defunci[oó]n|fallecimiento|muerte|matrimonio|divorcio|ingreso|egreso|alta|baja|cese|retiro|contrataci[oó]n|despido|pensi[oó]n|jubilaci[oó]n|internamiento|hospitalizaci[oó]n|diagn[oó]stico|atenci[oó]n|consulta|parto|detenci[oó]n|sentencia|emisi[oó]n(_?(cedula|documento))?|vencimiento_?c[eé]dula|vacunaci[oó]n|cirug[ií]a|accidente|incapacidad) fec_?(emi|emision|defuncion|ingreso|egreso|baja) date_?of_?(death|marriage|hire|admission|discharge)`

DATA TYPE CR_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Moved by up to thirty days. Sequences hold — the admission still comes before the discharge — and the exact day stops being a key into a public record.

`CR_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

9.5 Sex CR_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The sex as the system records it: F/M, Femenino/Masculino, Mujer/Hombre, 1/2.

HOW IT IS FOUND

COLUMN NAME CR_L2_SEXO – Path

85% `sexo(_?(biol[oó]gico|al_?nacer|paciente|afiliado|cliente))?` `(tp|tipo|cod|cd|id)_?sexo` `g[eé]nero` *(except when followed by* `identidad`, `autopercibido` *)* `sex` `gender` *(except when followed by* `identity` *)*

KNOWN VALUES CR_L2_SEXO – List

LIST	VALUES	STRENGTH	FIRST VALUES
`cr-detectar-sexo.txt`	6	80%	femenino, masculino, mujer, hombre, female, male
`cr-detectar-sexo-letra.txt`	3	60%	f, m, h

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the data class.

HOW IT IS MASKED

Replaced inside its own vocabulary, so an F stays an F or an M and a CHAR(1) column still fits. The distribution survives; the row no longer says which.

`CR_SEXO` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_SEXO_FEMENINO_MASCULINO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-femenino-masculino.txt`, chosen by a keyed hash.

`CR_SEXO_MUJER_HOMBRE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-mujer-hombre.txt`, chosen by a keyed hash.

`CR_SEXO_FEMALE_MALE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-female-male.txt`, chosen by a keyed hash.

`CR_SEXO_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-f-m.txt`, chosen by a keyed hash.

`CR_SEXO_H_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-h-m.txt`, chosen by a keyed hash.

`CR_SEXO_1_2` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	M

9.6 Distrito and cantón

CR_L2_DISTRITO

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

WHAT IT IS

The distrito or the cantón of residence, birth or care, by name — alone or with its cantón or provincia beside it, `Matambú – Hojancha`.

HOW IT IS FOUND

COLUMN NAME CR_L2_DISTRITO – Path

85% `distrito(_?(residencia|nacimiento|domicilio))?` *(except when followed by list E8)* `cant[oó]n(_?(residencia|nacimiento|domicilio))?` *(except when followed by `cod`, `codigo`, `id`)* `canton` *(except when followed by `cod`, `codigo`, `id`)* `ciudad(_?(residencia|nacimiento|domicilio|cliente))?` `poblado` `caser[ií]o` `(nom|nombre|desc)_?(distrito|canton|ciudad)` `lugar_?(de_?)?nacimiento` `city` `town`

VALUE FORMAT CR_L2_DISTRITO – Values

PATTERN	STRENGTH	NOTES
One of 398 known values, ignoring case — Merced, Hospital, Catedral, Zapote, San Francisco de Dos Ríos, Uruca, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A distrito of fewer than 20,000 inhabitants becomes the nearest distrito of at least 20,000 in the same cantón, or in the same provincia when the cantón has none. The cantones follow the same rule one level up, and the seven provincias stay. A name shared by several places is generalized only when every bearer is small, so a large distrito and a provincia keep their own name.

`CR_DISTRITO` DATA CLEANSING

Replaces each value found in `cr-distritos-generalizados.txt` (11,582 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Quitirrisí	→	**Pozos**
Matambú – Hojancha	→	**Nicoya – Nicoya**
San José	→	**San José**

9.7 DTA code and postal code

CR_L2_CODIGO_DTA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The code of the División Territorial Administrativa — one digit for the provincia, two for the cantón, two for the distrito — which in Costa Rica **is also the postal code**: Correos de Costa Rica assigns 10101 to the distrito 101 01.

HOW IT IS FOUND

COLUMN NAME — CR_L2_CODIGO_DTA – Path

85% `(cod|codigo|cd|id)_?(dta|distrito|canton|cant|provincia|ciudad|lugar|geogr[aá]fico)(_?(inec|censo|res|residencia|nac|nacimiento))?` `c[oó]digo_?(de_?)?(distrito|canton|divisi[oó]n_?territorial)` `coddistrito` `codcanton` `c[oó]digo_?postal` `cod_?postal` `codpostal` `zip(_?code)?` `postal_?code`

VALUE FORMAT — CR_L2_CODIGO_DTA – Regex

PATTERN	STRENGTH	NOTES
`0*(?:[1-7]\d{4})`	40%	
`0*(?:[1-7]\d{2})`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The same table that generalizes the names generalizes the codes, so a masked postal code still agrees with the masked distrito beside it and no row says one place in words and another in digits.

`CR_CODIGO_DTA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `CR_CODIGO_DTA_TABLA` DATA CLEANSING
>
> Replaces each value found in `cr-codigos-generalizados.txt` (428 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
10707	→	**10903**
10110	→	**10110**
107	→	**107**

9.8 Barrio

CR_L2_BARRIO

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The barrio, the urbanización, the residencial or the condominio — the level below the distrito. The 2025 decree of the División Territorial Administrativa names 1,276 of them.

HOW IT IS FOUND

COLUMN NAME — CR_L2_BARRIO — Path

80% `barrio(_?(residencia|domicilio|nombre))?` `urbanizaci[oó]n` `urb` `residencial` `condominio_?(nombre)?` `zona(_?(residencia|domicilio))?` `asentamiento` `precario` `(nom|nombre)_?(barrio|urbanizacion|residencial)` `neighbou?rhood`

HOW IT IS MASKED

Replaced by another real barrio of the country, always the same one for the same input. Generalizing upwards would say nothing a masked distrito does not already say, and a barrio column is often all the geography a table has.

`CR_BARRIO` SECURE LOOKUP

Replaces the value with one of the 1,276 values in `cr-barrios.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Barrio Escalante	→	**Ponderosa**

9.9 Marital status

CR_L2_ESTADO_CIVIL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The marital status, as text or as a code.

HOW IT IS FOUND

COLUMN NAME — CR_L2_ESTADO_CIVIL — Path

85% `estado_?civil` `est_?civil` `(cod|tipo|id)_?estado_?civil` `situaci[oó]n_?conyugal` `uni[oó]n_?(libre|de_?hecho)` `marital_?status` `civil_?status`

VALUE FORMAT — CR_L2_ESTADO_CIVIL — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Soltero a, Casado a, Unión libre o de hecho, Separado a, Divorciado a, Viudo a, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another status of the same list, and a numeric code by another code. A flag column keeps its S/N.

`CR_ESTADO_CIVIL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ESTADO_CIVIL_LISTA`.

`CR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

`CR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

`CR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

`CR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

`CR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

`CR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

`CR_ESTADO_CIVIL_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-estado-civil-codigos.txt`, chosen by a keyed hash.

`CR_ESTADO_CIVIL_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Unión de hecho	→	**Soltero/a**

9.10 Occupation

CR_L2_OCUPACION

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The occupation, the profession or the post, as text or as a code of the national classification.

HOW IT IS FOUND

COLUMN NAME CR_L2_OCUPACION — Path

80%	`ocupaci[oó]n` `profesi[oó]n` `oficio` `cocr` `ciuo` `(cod|codigo)_?(ocupacion|profesion|cocr|ciuo)` `puesto_?(de_?)?trabajo` `categor[ií]a_?ocupacional` `cargo_?(actual|empleado)` `occupation` `profession` `job_?title`
50%	`cargo` `puesto`

HOW IT IS MASKED

Replaced by another occupation, and a code by another code of the same length. A rare occupation in a small place names a person, which is why this is not left alone.

`CR_OCUPACION_O_CODIGO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_OCUPACION`.

`CR_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`CR_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 37 values in `cr-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Gerente de operaciones`	→	**`Teleoperador`**

9.11 Employer

CR_L2_EMPLEADOR

COLUMN NAME · SECURE LOOKUP

WHAT IT IS

The name of the employer or the patrono, and the place of work.

HOW IT IS FOUND

COLUMN NAME — CR_L2_EMPLEADOR — Path

90% `empleador(_?(nombre|raz[oó]n_?social|cedula))?` `(nombre|nom)_?(empleador|empresa_?donde_?trabaja|patrono)` `empresa_?(donde_?)?(trabaja|labora)` `lugar_?(de_?)?trabajo` `centro_?(de_?)?trabajo` `patrono(_?nombre)?` `entidad_?empleadora` `employer(_?name)?` `workplace`

HOW IT IS MASKED

Replaced by a fictitious Costa Rican company. The employer is not a titular, but it narrows a person to a payroll, which is why the column is masked.

`CR_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 24 values in `cr-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Corporación Comercial Centroamericana S.A.`	→	**`Transportes La Meseta S.A.`**

9.12 Level of education

CR_L2_NIVEL_EDUCATIVO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The highest level reached, as text or as a code.

HOW IT IS FOUND

COLUMN NAME — CR_L2_NIVEL_EDUCATIVO — Path

80% `escolaridad` `nivel_?(educativo|de_?estudios|acad[eé]mico|alcanzado|de_?instrucci[oó]n)` `instrucci[oó]n(_?formal)?` `grado_?(de_?)?(estudio|instrucci[oó]n|escolaridad)` `m[aá]ximo_?nivel` `a[nñ]os_?(de_?)?estudio` `education(_?level)?`

VALUE FORMAT — CR_L2_NIVEL_EDUCATIVO — Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — Sin instrucción, Preescolar, Primaria incompleta, Primaria completa, Secundaria incompleta, Secundaria completa, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another level of the same list, and a code by another code.

`CR_NIVEL_EDUCATIVO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_NIVEL_EDUCATIVO_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_NIVEL_EDUCATIVO_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 11 values in `cr-nivel-educativo-codigos.txt`, chosen by a keyed hash.
>
> `CR_NIVEL_EDUCATIVO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 11 values in `cr-nivel-educativo.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Educación universitaria en curso`	→	**`Preescolar`**

9.13 Educational institution

`CR_L2_INSTITUCION_EDUCATIVA`

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The school, the colegio, the instituto or the university a person attends or attended.

HOW IT IS FOUND

> COLUMN NAME `CR_L2_INSTITUCION_EDUCATIVA – Path`
>
> 75% `instituci[oó]n_?educativa` `centro_?(educativo|de_?estudios)` `escuela` `colegio` `liceo` `instituto` `universidad` `ina` `(nombre|nom)_?(escuela|colegio|liceo|universidad|institucion_?educativa)` `c[oó]digo_?(de_?)?(escuela|colegio|centro)` `school(_?name)?` `university`

HOW IT IS MASKED

Replaced by another Costa Rican institution. A rural unidocente school has a handful of pupils, so naming it narrows the person almost completely.

`CR_INSTITUCION_EDUCATIVA` SECURE LOOKUP

Replaces the value with one of the 12 values in `cr-instituciones-educativas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Universidad de Costa Rica`	→	**`Instituto Nacional de Aprendizaje`**

9.14 Dependants

CR_L2_PERSONAS_A_CARGO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

The number of children, dependants or members of the household.

HOW IT IS FOUND

> **COLUMN NAME** CR_L2_PERSONAS_A_CARGO — Path
>
> **80%** `personas_?a_?cargo` `n(o|ro|um|umero)_?(de_?)?(hijos|dependientes|personas_?a_?cargo|beneficiarios)` `cant(idad)?_?(hijos|dependientes|personas_?hogar|integrantes|miembros)` `hijos` `dependientes` `integrantes_?(del_?)?hogar` `personas_?(en_?el_?)?hogar` `tama[nñ]o_?(del_?)?hogar` `number_?of_?children` `dependents`

> **DATA TYPE** CR_L2_PERSONAS_A_CARGO — Type
>
> Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

Capped at five: a household of eleven is rare enough to identify, and five is enough for any arithmetic a test needs.

`CR_CONTEO_LIMITADO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 10

Sensitive data (art. 3 e and art. 9.1)

Article 9.1 does not regulate these data, it **prohibits** them: "se prohíbe el tratamiento de datos de carácter personal que revelen el origen racial o étnico, opiniones políticas, convicciones religiosas, espirituales o filosóficas, así como los relativos a la salud, la vida y la orientación sexual, entre otros", with five narrow exceptions, and article 31 a) makes processing them a falta gravísima for a private party. A test copy is none of those exceptions, so these columns are replaced within their own vocabulary or suppressed outright. Article 4, second paragraph, adds the reason the attributes the list does not name are here as well: informational self-determination exists "evitando que se propicien **acciones discriminatorias**".

10.1 Racial or ethnic origin

CR_L3_ETNIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The self-identification the census asks for: indígena, afrodescendiente o negra, mulata, china, blanca o mestiza.

HOW IT IS FOUND

COLUMN NAME CR_L3_ETNIA — Path

95% `etnia` `origen_?([eé]tnico|racial)` `grupo_?[eé]tnico` `pertenencia_?[eé]tnica` `autoidentificaci[oó]n(_?[eé]tnica)?` `autodefinici[oó]n` `(cod|codigo|tipo|id)_?etnia` `raza` `afrodescendiente` `afrocostarricense` `ind[ií]gena` `ethnicity` `race`

VALUE FORMAT CR_L3_ETNIA — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Indígena, Afrodescendiente o negra, Mulata, China, Blanca o mestiza, Otra, …	90%	
One of 11 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside the list, a code by another code and a flag by a flag. Article 3 e) names the **origen racial** and article 9.1 prohibits processing the **origen racial o étnico** outright.

`CR_ETNIA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ETNIA_LISTA`.

`CR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

`CR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

`CR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

`CR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

`CR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

`CR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

`CR_ETNIA_CODIGO` SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-etnias-codigos.txt`, chosen by a keyed hash.

`CR_ETNIA_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-etnias.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afrodescendiente	→	**Ninguna**

10.2 Indigenous people and territory

CR_L3_PUEBLO_INDIGENA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The people a person belongs to — bribri, cabécar, maleku, chorotega, huetar, brunca, ngäbe, buglé, teribe — the territorio indígena and the mother tongue. Costa Rica has eight peoples and 24 territorios.

HOW IT IS FOUND

COLUMN NAME CR_L3_PUEBLO_INDIGENA – Path

90% `pueblo_?(ind[ií]gena|originario)` `territorio_?ind[ií]gena` `comunidad_?ind[ií]gena` `adi_?ind[ií]gena` `lengua_?(ind[ií]gena|materna)` `idioma_?ind[ií]gena` `bribri` `cab[eé]car` `ngäbe` `ngabe` `maleku` `chorotega` `huetar` `br[uú]nca` `boruca` `teribe` `t[eé]rraba` `indigenous_?people`

VALUE FORMAT CR_L3_PUEBLO_INDIGENA – Values

PATTERN	STRENGTH	NOTES
One of 37 known values, ignoring case — Bribri, Cabécar, Maleku, Chorotega, Huetar, Brunca o boruca, …	85%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside its own list. A people counts a few thousand members and a territorio a few hundred, so the two are the sharpest quasi-identifiers in the country and sensitive besides.

`CR_PUEBLO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PUEBLO_LISTA`.

`CR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

`CR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

`CR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

`CR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

`CR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

`CR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CR_PUEBLO_LISTA` SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Pueblo indígena	→	**Cabécar**

10.3 Nationality

CR_L3_NACIONALIDAD

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

The nationality, the country of birth or of origin, the citizenship.

HOW IT IS FOUND

COLUMN NAME CR_L3_NACIONALIDAD — Path

85% `nacionalidad` `pa[ií]s_?(de_?)?(nacimiento|origen|nacionalidad|procedencia)` `ciudadan[ií]a` `nationality` `citizenship` `country_?of_?birth`

VALUE FORMAT CR_L3_NACIONALIDAD — Values

PATTERN	STRENGTH	NOTES
One of 37 known values, ignoring case — Costarricense, Nicaragüense, Panameña, Colombiana, Venezolana, Salvadoreña, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another nationality of the list. The law does not name it, but it sits beside the racial and ethnic origin it does name, and in Costa Rica it separates the nationals from the Nicaraguan community — the attribute on which the "acciones discriminatorias" of article 4 most often turn.

`CR_NACIONALIDAD` SECURE LOOKUP

Replaces the value with one of the 14 values in `cr-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Peruana	→	**Costarricense**

10.4 Migratory condition

CR_L3_CONDICION_MIGRATORIA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The migratory category the Dirección General de Migración records: residence, special category, refugee, applicant for refuge, work permit, irregular condition.

HOW IT IS FOUND

COLUMN NAME CR_L3_CONDICION_MIGRATORIA — Path

90% `condici[oó]n_?migratoria` `estatus_?migratorio` `categor[ií]a_?migratoria` `situaci[oó]n_?migratoria` `tipo_?(de_?)?residencia` `residencia_?(permanente|temporal|categoria)` `permiso_?(de_?)?(trabajo|residencia|laboral)` `refugiad[oa]` `solicitante_?(de_?)?refugio` `asilo` `apatrida` `visa(_?(n(o|ro|um|umero)|tipo|categoria))?` `migration_?status` `immigration_?status`

VALUE FORMAT CR_L3_CONDICION_MIGRATORIA — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Residente permanente, Residente temporal, Categoría especial, Persona refugiada, Solicitante de refugio, Permiso de trabajo, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. Of all the attributes in a Costa Rican database this is the one whose disclosure can cost a person their stay.

`CR_CONDICION_MIGRATORIA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CONDICION_MIGRATORIA_LISTA`.

> `CR_BANDERA` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_CONDICION_MIGRATORIA_LISTA` **SECURE LOOKUP**
>
> Replaces the value with one of the 9 values in `cr-condicion-migratoria.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Residencia en trámite	→	**Persona refugiada**

10.5 Religion

CR_L3_RELIGION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The religion, the creed, the church, the religious or spiritual conviction.

HOW IT IS FOUND

COLUMN NAME CR_L3_RELIGION — Path

95% `religi[oó]n` `creencia_?(religiosa|espiritual)` `convicci[oó]n(es)?_?(religiosa|espiritual)` `credo` `confesi[oó]n_?religiosa` `culto` `iglesia(_?(a_?la_?que_?pertenece|nombre))?` `denominaci[oó]n_?religiosa` `(cod|codigo|tipo)_?religion` `religion` `church`

VALUE FORMAT CR_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 30 known values, ignoring case — Católica, Evangélica o protestante, Testigo de Jehová, Adventista del Séptimo Día, Iglesia de Jesucristo de los Santos de los Últimos Días, Judía, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside the list. Article 3 e) names the **convicciones religiosas o espirituales** and article 9.1 prohibits processing them.

`CR_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_RELIGION_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_RELIGION_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `cr-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ortodoxa	→	**Otra**

10.6 Philosophical convictions

CR_L3_CONVICCION_FILOSOFICA

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

A philosophical, moral or ethical conviction, an objection of conscience, membership of a lodge.

HOW IT IS FOUND

COLUMN NAME — CR_L3_CONVICCION_FILOSOFICA — Path

90% `convicci[oó]n(es)?_?(filos[oó]ficas?|morales?|personales?|[eé]ticas?)` `creencias?_?(filos[oó]ficas?|morales?|personales?)` `objeci[oó]n_?(de_?)?conciencia` `objetor_?(de_?)?conciencia` `masoner[ií]a` `logia` `beliefs?` `philosophical_?beliefs?`

HOW IT IS MASKED

Suppressed: replaced by "Sin información". Article 9.1 names the **convicciones filosóficas** that article 3 e) leaves out, and its exception b) lets a foundation or association of a philosophical purpose keep the data of its own members — which is the database this data class protects everywhere else.

`CR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cr-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Trastorno depresivo recurrente`	→	**`Sin información`**

10.7 Political opinion

CR_L3_OPINION_POLITICA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The political opinion, the ideology, the leaning, the voting intention.

HOW IT IS FOUND

COLUMN NAME CR_L3_OPINION_POLITICA — Path

95% `opini[oó]n_?pol[ií]tica` `preferencias?_?(pol[ií]tica|partidaria|electoral)` `ideolog[ií]a(_?pol[ií]tica)?` `orientaci[oó]n_?pol[ií]tica` `tendencia_?pol[ií]tica` `intenci[oó]n_?(de_?)?voto` `simpat[ií]a_?pol[ií]tica` `political_?(opinion|orientation|view|preference)` `voting_?intention`

VALUE FORMAT CR_L3_OPINION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside the list. Article 3 e) and article 9.1 both name the **opiniones políticas**, with no exception that covers a survey kept in a CRM.

`CR_PREFERENCIA_POLITICA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PREFERENCIA_POLITICA_LISTA`.

`CR_BANDERA` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

`CR_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

`CR_BANDERA_YES_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

`CR_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

`CR_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

`CR_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

`CR_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`CR_PREFERENCIA_POLITICA_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cr-preferencias-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Oficialista`	→	**`Centro`**

10.8 Party membership

CR_L3_AFILIACION_PARTIDARIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The party a person adheres to, the militancy, the divisa política. The Tribunal Supremo de Elecciones keeps the register of adhesiones.

HOW IT IS FOUND

COLUMN NAME CR_L3_AFILIACION_PARTIDARIA – Path

95% `partido(_?pol[ií]tico)?(_?(afiliaci[oó]n|nombre))?` `adhesi[oó]n_?(partidaria|al_?partido)` `afiliaci[oó]n_?(pol[ií]tica|partidaria|partido)` `militancia(_?pol[ií]tica)?` `militante` `(cod|codigo|nombre|nom)_?partido` `divisa_?pol[ií]tica` `political_?party` `party_?membership`

VALUE FORMAT CR_L3_AFILIACION_PARTIDARIA – Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Liberación Nacional, Unidad Social Cristiana, Progreso Social Democrático, Nueva República, Frente Amplio, Liberal Progresista, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another party of the register, and a flag kept as a flag. Membership reveals the opinión política, which is what makes it sensitive.

`CR_PARTIDO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PARTIDO_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_PARTIDO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 13 values in `cr-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Partido Republicano Social Cristiano`	→	**`Liberal Progresista`**

10.9 Trade union membership

CR_L3_AFILIACION_SINDICAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The union, the dues deducted from the payroll, the asociación solidarista, the gremio.

HOW IT IS FOUND

COLUMN NAME CR_L3_AFILIACION_SINDICAL — Path

95% `sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))?` `sindicalizado` `afiliado_?sindicato` `afiliaci[oó]n_?sindical` `cuota_?sindical` `rebajo_?sindical` `aporte_?sindical` `asociaci[oó]n_?(sindical|solidarista|de_?empleados)` `solidarismo` `gremio` `fuero_?sindical` `dirigente_?sindical` `trade_?union` `union_?member(ship)?`

VALUE FORMAT CR_L3_AFILIACION_SINDICAL — Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — ANEP, APSE, SEC, ANDE, UNDECA, SINAE, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. Article 9.1 b) lets an organization of a **sindical** purpose keep the data of its own members "con tal de que los datos no se comuniquen a terceros sin el consentimiento de las personas interesadas" — which is exactly what a copy sent to a development team does.

`CR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR` .

`CR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

`CR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

`CR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

`CR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

`CR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

`CR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CR_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Trastorno depresivo recurrente`	→	**`Sin información`**

10.10 Biometric data

CR_L3_BIOMETRICO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

A fingerprint and its template, a facial encoding, an iris, a voiceprint, a digitalized signature.

HOW IT IS FOUND

COLUMN NAME — CR_L3_BIOMETRICO — Path

90% `biometr[ií]a[a-z_]*` `biom[eé]trico[a-z_]*` `huella(_?(dactilar|digital))?(_?(template|plantilla|imagen|hash))?` `huellas` `dactilar` `dactilosc[oó]pic[oa]` `template_?(facial|huella|biometrico)` `plantilla_?(facial|biom[eé]trica)` `rostro_?(hash|template)` `reconocimiento_?(facial|de_?voz)` `firma_?(biom[eé]trica|digitalizada)` `iris` `voz_?(biom[eé]trica|template)` `fingerprints?` `face_?(template|hash|encoding)` `biometric[a-z_]*`

DATA TYPE — CR_L3_BIOMETRICO — Type

Accepts text; any other type rules the data class out.

HOW IT IS MASKED

Replaced by X characters. Article 3 e) names the **información biomédica**, and no exception of article 9.1 covers a template kept for convenience — a biometric cannot be reissued when it leaks.

`CR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`clave123`	→	`XXXXXXXX`

10.11 Genetic data

CR_L3_GENETICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

DNA, a genetic profile, a paternity or filiation test, a mutation, the neonatal screening.

HOW IT IS FOUND

COLUMN NAME — CR_L3_GENETICO — Path

90% `adn` `dna` `gen[eé]tic[oa]s?` `datos?_?gen[eé]ticos?` `genoma` `genotip[a-z_]*` `prueba_?(gen[eé]tica|de_?adn|de_?paternidad|de_?filiaci[oó]n)` `perfil_?gen[eé]tico` `mutaci[oó]n` `brca[12]?` `cariotipo` `tamizaje_?neonatal` `genetic[a-z_]*`

VALUE FORMAT — CR_L3_GENETICO — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by X characters. Article 3 e) names **información biomédica o genética** in one breath, and a genetic datum identifies relatives who were never asked.

`CR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
clave123	→	XXXXXXXX

10.12 Sexual orientation

CR_L3_ORIENTACION_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The sexual orientation as the system records it.

HOW IT IS FOUND

COLUMN NAME CR_L3_ORIENTACION_SEXUAL — Path

95% `orientaci[oó]n_?sexual` `preferencias?_?sexuales?` `(cod|codigo|tipo)_?orientacion_?sexual` `sexual_?orientation`

VALUE FORMAT CR_L3_ORIENTACION_SEXUAL — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside the list. Article 3 e) and article 9.1 both name the **orientación sexual**.

`CR_ORIENTACION_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ORIENTACION_SEXUAL_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_ORIENTACION_SEXUAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `cr-orientaciones-sexuales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Homosexual	→	**Pansexual**

10.13 Sexual life

CR_L3_VIDA_SEXUAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Sexual activity, conduct, practices, number of partners, the age at which sexual life began.

HOW IT IS FOUND

> COLUMN NAME CR_L3_VIDA_SEXUAL — Path
>
> 90% `vida_?sexual` `actividad_?sexual` `conducta_?sexual` `pr[aá]cticas?_?sexuales?` `parejas?_?sexuales?` `n(o|ro|um|umero)_?parejas` `sexualmente_?activ[oa]` `inicio_?(de_?)?(la_?)?vida_?sexual` `relaciones_?sexuales` `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|partners)`

HOW IT IS MASKED

Suppressed. Article 3 e) names the **vida** as well as the **orientación sexual**, and article 9.1 repeats it.

`CR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR` .

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno depresivo recurrente	→	**Sin información**

10.14 Gender identity

CR_L3_IDENTIDAD_GENERO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The gender identity, the social name, the pronouns. Since 2018 a person may change the name and the sex marker of the cédula, so this is a real column in Costa Rican systems.

HOW IT IS FOUND

> **COLUMN NAME** CR_L3_IDENTIDAD_GENERO – Path
>
> 95% `identidad_?(de_?)?g[eé]nero` `(cod|codigo|tipo)_?identidad_?genero` `g[eé]nero_?(autopercibido|identitario)` `expresi[oó]n_?de_?g[eé]nero` `transg[eé]nero` `persona_?trans` `nombre_?social` `pronombres?` `gender_?identity`

> **VALUE FORMAT** CR_L3_IDENTIDAD_GENERO – Values
>
PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Mujer cisgénero, Hombre cisgénero, Mujer trans, Hombre trans, Persona no binaria, Otra, …	70%	
>
> A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside its own list. The list of article 3 e) is open — "entre otros" — and article 4 asks that the data not propitiate discriminatory actions.

`CR_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_IDENTIDAD_GENERO_LISTA` .

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `cr-identidades-genero.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Transgénero	→	**Hombre trans**

10.15 Victim of violence

CR_L3_VICTIMA

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

The condition of victim, the kind of violence, a protection measure, a PANI case.

HOW IT IS FOUND

> COLUMN NAME CR_L3_VICTIMA — Path
>
> 90% `v[ií]ctima(_?(de_?)?(violencia(_?(de_?g[eé]nero|dom[eé]stica|intrafamiliar|sexual|psicol[oó]gica|patrimonial))?|delito|trata|abuso|desaparici[oó]n))?` `violencia_?(de_?)?g[eé]nero` `violencia_?(dom[eé]stica|intrafamiliar|sexual|psicol[oó]gica)` `tipo_?(de_?)?violencia` `medida_?(de_?)?protecci[oó]n` `boleta_?(de_?)?violencia` `trata_?(de_?)?personas` `denunciante_?violencia` `pani_?(caso|expediente)`

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. The Ley 8589 de penalización de la violencia contra las mujeres and the Ley 9095 against the trafficking of persons both protect the identity of the victim.

`CR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cr-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Trastorno depresivo recurrente`	→	**`Sin información`**

PART 11

Health data (art. 9.1 d)

Health is among the data article 9.1 prohibits, and its exception d) draws the only door: processing is allowed when it is necessary for prevention, medical diagnosis, health care or the management of health services, and then only by a health worker bound to professional secrecy "o por otra persona sujeta, asimismo, a una obligación equivalente de secreto". A test environment is nobody's health care, and whoever restores the dump is under no such obligation. Article 2 c) of the Ley 8239 de derechos de las personas usuarias de los servicios de salud guarantees the confidentiality of the expediente, which the CCSS keeps for the whole country in the EDUS.

11.1 Clinical record number

CR_SALUD_IDENTIFICADOR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The number of the expediente clínico, of the EDUS record, of an episode, an admission, a consultation or a prescription.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_IDENTIFICADOR — Path

85% `n(o|ro|um|umero)_?(expediente_?(cl[ií]nico|de_?salud|m[eé]dico)|hc|ficha(_?cl[ií]nica)?|episodio|ingreso|atenci[oó]n|consulta|cita|receta)` `expediente_?(cl[ií]nico|digital|[uú]nico|m[eé]dico|salud)` `edus[a-z0-9_]*` `arca` `sics` `id_?paciente` `c[oó]digo_?(paciente|expediente|atenci[oó]n)`

55% `expediente` `atenci[oó]n` `ingreso` `consulta` `episodio`

HOW IT IS MASKED

Character by character, keeping the shape. The number is a pseudonym for a patient, and it is usually built from the cédula.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

11.2 Health coverage

CR_SALUD_COBERTURA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

How a person is insured: asegurado directo asalariado or cuenta propia, voluntario, por el Estado, pensionado of the IVM or of the RNC, familiar, a private policy, or not insured at all.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_COBERTURA — Path

85% `cobertura(_?(m[eé]dica|de_?salud|asistencial))?` `seguro_?(m[eé]dico|salud|sem)` `r[eé]gimen(_?(de_?)?(aseguramiento|salud|pensiones|ivm|rnc))?` `tipo_?(de_?)?(seguro|cobertura|asegurado)` `modalidad_?(de_?)?aseguramiento` `ccss_?(regimen|cobertura)` `aseguradora_?(m[eé]dica|salud)` `plan_?(m[eé]dico|de_?salud)` `ins_?(poliza|seguro)`

VALUE FORMAT CR_SALUD_COBERTURA — Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Asegurado directo asalariado, Asegurado directo cuenta propia, Asegurado voluntario, Asegurado por el Estado, Pensionado IVM, Pensionado RNC, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside its own list, and a numeric code by another code. The régimen says more than it looks: "asegurado por el Estado" is a statement about the person's **condición socioeconómica**, which article 3 e) calls sensitive.

`CR_COBERTURA_SALUD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_COBERTURA` .

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_COBERTURA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `cr-cobertura-salud.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Asegurado por el Estado`	→	**`Seguro privado`**

11.3 Diagnosis

CR_SALUD_DIAGNOSTICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The diagnosis as an ICD-10 code or as text, the cause of death, the reason for a consultation or an incapacidad, allergies and comorbidities.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_DIAGNOSTICO — Path

85% `diagn[oó]stico[a-z_]*` `dx(_?(principal|secundario|ingreso|egreso)[0-9]?)?` `cie_?10` `cie(_?(10|11|principal))?` `(cod|codigo)_?(diagnostico|dx|cie)` `impresi[oó]n_?diagn[oó]stica` `enfermedad(es)?[a-z_]*` `patolog[ií]a` `comorbilidad(es)?` `antecedentes?_?(m[eé]dicos|patol[oó]gicos|cl[ií]nicos|personales)` `causa_?(de_?)?(muerte|defunci[oó]n|incapacidad|internamiento|consulta)` `motivo_?(de_?)?(consulta|incapacidad|internamiento)` `alergias?` `diagnos(is|es)` `icd_?(10|11)?`

VALUE FORMAT CR_SALUD_DIAGNOSTICO — Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d|X)?`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

An ICD-10 code becomes another code of the same shape and a text diagnosis another common diagnosis. The column still looks like a diagnosis column and no longer says what a person has.

`CR_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_DIAGNOSTICO_TEXTO`.

> `CR_CIE10_DECIMAL` SECURE LOOKUP
>
> Replaces the value with one of the 34 values in `cr-cie10-decimal.txt`, chosen by a keyed hash.
>
> `CR_CIE10` SECURE LOOKUP
>
> Replaces the value with one of the 38 values in `cr-cie10.txt`, chosen by a keyed hash.
>
> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_DIAGNOSTICO_TEXTO` SECURE LOOKUP
>
> Replaces the value with one of the 31 values in `cr-diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	**N39.0**
Depresión mayor	→	**Obesidad**

11.4 Procedure

CR_SALUD_PROCEDIMIENTO

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

The procedure, the prestación, the surgery or the examination ordered, as a code or as text.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_PROCEDIMIENTO — Path

85% `procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado))?` `(cod|codigo)_?(procedimiento|prestaci[oó]n|servicio_?salud)` `prestaci[oó]n_?(m[eé]dica|de_?salud)` `examen_?(ordenado|realizado)` `cirug[ií]a(_?realizada)?` `intervenci[oó]n_?quir[uú]rgica` `t[eé]cnica_?(diagn[oó]stica|quir[uú]rgica)` `medical_?procedure`

HOW IT IS MASKED

A code gets other digits of the same length and text becomes another common procedure. Some procedures name a diagnosis on their own, which is why they are not left alone.

`CR_PROCEDIMIENTO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_PROCEDIMIENTO_TEXTO`.

> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_PROCEDIMIENTO_TEXTO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `cr-procedimientos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Prueba de carga viral para VIH	→	**Hemograma completo**

11.5 Medicine

CR_SALUD_MEDICAMENTO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The medicine prescribed or dispensed, the active ingredient, the LOM code, the posology.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_MEDICAMENTO — Path

85% `medicamentos?(_?(recetado|prescrito|entregado|despachado|nombre|uso))?` `f[aá]rmacos?` `principio_?activo` `denominaci[oó]n_?com[uú]n_?internacional` `dci` `receta(_?m[eé]dica)?` `prescripci[oó]n(_?medicamento)?` `posolog[ií]a` `tratamiento_?farmacol[oó]gico` `(cod|codigo)_?medicamento` `lista_?oficial_?de_?medicamentos` `lom` `medications?` `drugs?_?prescribed`

VALUE FORMAT CR_SALUD_MEDICAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 46 known values, ignoring case — Acetaminofén, Ibuprofeno, Diclofenaco, Metformina, Glibenclamida, Losartán, …	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by another medicine of the list. A medicine is a diagnosis written backwards: an antiretroviral or an antipsychotic says what the diagnosis column was masked for.

`CR_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_MEDICAMENTO_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_MEDICAMENTO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 22 values in `cr-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Sertralina 50 mg`	→	**`Complejo B`**

11.6 Clinical notes

`CR_SALUD_TEXTO_CLINICO`

COLUMN NAME | DATA TYPE | FREE TEXT REDACTION

WHAT IT IS

The anamnesis, the evolución, the physical examination, the plan, the epicrisis, a radiology or pathology report.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_TEXTO_CLINICO — Path

85% `anamnesis` `evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))?` `enfermedad_?actual` `examen_?f[ií]sico` `plan_?(de_?)?(manejo|tratamiento)` `indicaciones_?m[eé]dicas` `conducta(_?m[eé]dica)?` `epicrisis` `resumen_?(de_?)?(alta|egreso|atenci[oó]n)` `nota_?(m[eé]dica|de_?enfermer[ií]a|cl[ií]nica)` `notas?_?(m[eé]dicas|cl[ií]nicas)` `triaje(_?texto)?` `informe_?(patolog[ií]a|radiolog[ií]a|m[eé]dico)` `clinical_?notes?` `discharge_?summary`

DATA TYPE CR_SALUD_TEXTO_CLINICO — Type

Accepts text (length 30 or more); any other type rules the data class out.

HOW IT IS MASKED

The prose is kept and the identifiers inside it are redacted, the same way as any free text: the clinical reasoning survives for a test, the patient does not.

`CR_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DATO]`, and the 1,944 terms of `cr-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Cliente Jiménez, cédula 1-0234-0567, correo j.jimenez@gmail.com, cel 83124567`	→	**`Cliente [NOMBRE], cédula [DATO], correo [DATO], cel [DATO]`**

11.7 Test result

CR_SALUD_RESULTADO_EXAMEN

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The result of a laboratory test, a serology, a biopsy, a glycaemia, a blood pressure, an alcoholaemia.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_RESULTADO_EXAMEN — Path

80% `resultado_?(del_?)?(examen|prueba|an[aá]lisis|laboratorio|pcr|serolog[ií]a|biopsia|glicemia|citolog[ií]a|papanicolaou|vdrl)` `(examen|prueba|an[aá]lisis)_?(resultado|laboratorio)` `glicemia` `hemoglobina(_?glicosilada)?` `hba1c` `colesterol` `imc` `presi[oó]n_?arterial` `test_?(de_?)?embarazo` `espirometr[ií]a` `alcoholemia` `lab_?results?` `test_?results?`

50% `resultado` `prueba` `analisis`

HOW IT IS MASKED

Character by character, keeping the shape so that units and ranges still parse. A single reactive result is a diagnosis.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	**U2438404**

11.8 HIV and sexually transmitted infections

CR_SALUD_VIH

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The serological status, the viral load, the CD4 count, the antiretroviral treatment, syphilis, hepatitis, tuberculosis.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_VIH — Path

90% `vih(_?(estado|resultado|prueba|diagn[oó]stico|positivo))?` `hiv` `sida` `aids` `serolog[ií]a_?(vih|hiv)` `estado_?serol[oó]gico` `carga_?viral` `cd4` `tar` `antirretroviral(es)?` `its` `ets` `infecci[oó]n(es)?_?(de_?)?transmisi[oó]n_?sexual` `s[ií]filis` `hepatitis_?[bc]` `tuberculosis` `tbc`

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. The **Ley 7771 General sobre el VIH-SIDA** makes the condition confidential and its disclosure an offence of its own, beyond article 9.1.

`CR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR` .

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno depresivo recurrente	→	**Sin información**

11.9 Blood group

CR_SALUD_GRUPO_SANGUINEO

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

The ABO group and the Rh factor.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `tipo_?(de_?)?sangre` `rh` `factor_?rh` `gs_?rh` `grupo_?rh` `abo(_?rh)?` `blood_?(type|group)`

VALUE FORMAT CR_SALUD_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another group. It is a weak identifier on its own and a health datum all the same, and a rare group in a small place narrows a person.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with Delphix and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

11.10 Disability

CR_SALUD_DISCAPACIDAD

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The kind, the degree or the certificate of a disability. The Ley 7600 de igualdad de oportunidades and the Ley 9379 that created CONAPDIS both build registers of it.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `(tipo|cod|codigo|categoria|porcentaje|grado)_?discapacidad` `persona_?con_?discapacidad` `pcd` `certificado_?(de_?)?discapacidad` `conapdis` `condici[oó]n_?(de_?)?discapacidad` `necesidades_?(educativas_?)?especiales` `movilidad_?reducida` `ley_?7600` `disabilit(y|ies)`

VALUE FORMAT CR_SALUD_DISCAPACIDAD — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Física o motora, Auditiva, Visual, Intelectual, Psicosocial, Múltiple, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. A rare disability in a small distrito names the person as surely as the cédula.

`CR_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_DISCAPACIDAD_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_DISCAPACIDAD_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `cr-discapacidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Trastorno del espectro autista`	→	**`Psicosocial`**

11.11 Occupational health

`CR_SALUD_OCUPACIONAL`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Fitness for work, the pre-employment or periodic examination, an accident at work, an occupational disease, an incapacidad and its days.

HOW IT IS FOUND

> COLUMN NAME `CR_SALUD_OCUPACIONAL – Path`
>
> 85% `aptitud_?(laboral|m[eé]dica)` `certificado_?(de_?)?aptitud` `examen_?(m[eé]dico_?)?(ocupacional|preocupacional|de_?ingreso|de_?egreso|peri[oó]dico)` `accidente_?(de_?)?trabajo` `riesgos?_?(del_?)?trabajo` `enfermedad_?(laboral|profesional|ocupacional)` `incapacidad(_?(m[eé]dica|laboral|d[ií]as))?` `boleta_?(de_?)?incapacidad` `d[ií]as_?(de_?)?incapacidad` `licencia_?(m[eé]dica|por_?maternidad)` `ausentismo`

VALUE FORMAT CR_SALUD_OCUPACIONAL — Values

PATTERN	STRENGTH	NOTES
One of 5 known values, ignoring case — apto, no apto, apto con restricciones, pendiente, apto con recomendaciones	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced inside its own list. The boleta de incapacidad of the CCSS travels with a diagnosis, which is why a personnel table holds health data without meaning to.

`CR_APTITUD_LABORAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_APTITUD_LABORAL_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_APTITUD_LABORAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `cr-aptitud-laboral.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`No apto temporalmente`	→	**Pendiente**

11.12 Reproductive health

CR_SALUD_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy and its weeks, the prenatal control, the delivery, the interruption, contraception, fertility.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_REPRODUCTIVA — Path

90% `embarazo` `embarazada` `gestante` `gestaci[oó]n` `edad_?gestacional` `semanas_?(de_?)?gestaci[oó]n` `fum` `fecha_?[uú]ltima_?(regla|menstruaci[oó]n)` `control_?(prenatal|obst[eé]trico)` `prenatal` `parto(_?tipo)?` `ces[aá]rea` `interrupci[oó]n_?(del_?)?embarazo` `aborto` `m[eé]todo_?(de_?)?anticoncepci[oó]n` `planificaci[oó]n_?familiar` `anticoncepci[oó]n` `anticonceptivo` `fertilidad` `fecundaci[oó]n_?in_?vitro` `salud_?(sexual|reproductiva)` `pregnan(t|cy)` `contracepti(on|ve)`

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. It is health data under article 9.1 and it sits next to the vida sexual of article 3 e).

`CR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `cr-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Trastorno depresivo recurrente`	→	**`Sin información`**

11.13 Mental health

CR_SALUD_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

A mental health diagnosis or follow-up, a suicide attempt, self-harm, the consumption of substances, an addiction, an IAFA record.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_MENTAL — Path

90% `salud_?mental` `trastorno[a-z_]*` `psiqui[aá]tri[a-z_]*` `psicol[oó]gi[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z_]*` `intento_?(de_?)?suicidio` `autolesi[oó]n` `consumo_?(de_?)?(sustancias|alcohol|drogas)` `adicci[oó]n(es)?` `alcoholismo` `tabaquismo` `iafa` `mental_?health`

HOW IT IS MASKED

Suppressed. It is health data, and of all health data it is the one whose disclosure costs a person a job, a custody or a policy.

`CR_CATEGORIA_SUPRIMIDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR` .

> `CR_BANDERA` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CR_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_SUPRIMIR` **SECURE LOOKUP**
>
> Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno depresivo recurrente	→	**Sin información**

PART 12

Economic data (art. 3 e, art. 1 and art. 9.4)

Costa Rica is the only country of the region whose law names the **condición socioeconómica** among the sensitive data of article 3 e), beside racial origin and religious convictions. Article 1 extends the law to the data of a person's **bienes**, and article 9.4 sends credit behaviour to the rules of the Sistema Financiero Nacional — where the SUGEF keeps the Centro de Información Crediticia — "sin impedir el pleno ejercicio del derecho a la autodeterminación informativa ni exceder los límites de esta ley". Amounts keep their order of magnitude so that totals and ratios still behave; what they stop doing is naming a salary.

12.1 Credit standing

CR_FIN_HISTORIAL_CREDITICIO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

The SUGEF category — A1, A2, B1, B2, C1, C2, D, E —, the CIC record, a score, the days in arrears, the state of a collection.

HOW IT IS FOUND

COLUMN NAME — CR_FIN_HISTORIAL_CREDITICIO — Path

90% `historial_?(crediticio|de_?cr[eé]dito)` `cic(_?sugef)?` `centro_?(de_?)?informaci[oó]n_?crediticia` `sugef(_?(categoria|calificacion))?` `central_?(de_?)?riesgos?` `bur[oó]_?(de_?)?cr[eé]dito` `protectora_?(de_?)?cr[eé]dito` `score(_?(crediticio|interno))?` `puntaje_?(de_?)?cr[eé]dito` `calificaci[oó]n_?(de_?)?(riesgo|cr[eé]dito|cartera|deudor)` `categor[ií]a_?(sugef|de_?riesgo)` `d[ií]as_?(de_?)?(mora|atraso)` `estado_?(de_?)?(cr[eé]dito|cartera|obligaci[oó]n)` `morosidad` `moroso` `cobro_?judicial` `credit_?score` `credit_?rating`

HOW IT IS MASKED

A category becomes another category, a score other digits and a flag a flag. Article 9.4 sends this data to the rules of the Sistema Financiero Nacional without taking it out of the law.

`CR_HISTORIAL_CREDITICIO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_ESTADO_CREDITO`.

> `CR_CATEGORIA_SUGEF` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `cr-categorias-sugef.txt`, chosen by a keyed hash.
>
> `CR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

`CR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

`CR_ESTADO_CREDITO` SECURE LOOKUP

Replaces the value with one of the 13 values in `cr-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
En cobro judicial	→	**Categoría A2 — riesgo normal**
A1	→	**A2**

12.2 Debt

CR_FIN_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

The balance of a debt, a loan or a card, the instalment, the credit limit.

HOW IT IS FOUND

COLUMN NAME CR_FIN_DEUDA — Path

85% `saldo_?(deuda|cr[eé]dito|capital|obligaci[oó]n|cartera|en_?mora|adeudado)` `monto_?(de_?la_?)?(deuda|cuota|obligaci[oó]n|cr[eé]dito|pr[eé]stamo|mora|otorgado)` `deuda(_?total)?` `l[ií]mite_?(de_?)?(cr[eé]dito|tarjeta)` `l[ií]nea_?(de_?)?cr[eé]dito` `cuota_?mensual` `loan_?(amount|balance)` `outstanding_?balance` `debt`

DATA TYPE CR_FIN_DEUDA — Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
2400000	→	**7834212**

12.3 Income

CR_FIN_INGRESOS

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

The salary, gross or net, the fees, the declared income, the income per person of the household.

HOW IT IS FOUND

COLUMN NAME CR_FIN_INGRESOS – Path

85% `sueldo(_?(bruto|neto|mensual|base|ordinario))?` `salario(_?(bruto|neto|mensual|base|m[ií]nimo|escolar))?` `remuneraci[oó]n(_?mensual)?` `ingresos?(_?(mensuales?|totales?|familiares?|declarados?|netos?|brutos?))?` `haberes` `honorarios` `renta(_?(bruta|neta|mensual|anual))?` `ingreso_?(base|familiar|per_?capita)` `salary` `income` `wages?`

DATA TYPE CR_FIN_INGRESOS – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value. This is where Costa Rica differs from its neighbours: article 3 e) names the **condición socioeconómica** among the sensitive data, so an income column is not merely commercial.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
780000	→	693756

12.4 Assets

CR_FIN_PATRIMONIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

The patrimony, the assets, the fiscal or commercial value of a property or a vehicle, the balance of an account or an investment, a sworn declaration of assets.

HOW IT IS FOUND

COLUMN NAME CR_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|l[ií]quido|fiscal))?` `activos?_?(totales?)?` `valor_?(del_?)?(inmueble|finca|veh[ií]culo|bienes|tasaci[oó]n|fiscal|comercial)` `tasaci[oó]n` `valor_?(fiscal|catastral)` `saldo_?(cuenta|ahorro|dep[oó]sito|inversi[oó]n|fondo)` `certificado_?(de_?)?dep[oó]sito` `inversiones` `declaraci[oó]n_?(jurada_?)?(de_?)?(bienes|patrimonio)` `net_?worth` `account_?balance`

DATA TYPE CR_FIN_PATRIMONIO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value. Article 1 of the law reaches the data of a person "o **bienes**", which puts this column inside it by the plain words of the statute.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
48000000	→	91760294

12.5 Pension

CR_FIN_PENSION

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

The amount of a pension or a subsidy: the IVM, the Régimen No Contributivo, an alimony, a disability pension.

HOW IT IS FOUND

COLUMN NAME — CR_FIN_PENSION — Path

90% `jubilaci[oó]n(_?(monto|mensual|valor))?` `pensi[oó]n(_?(monto|mensual|valor|alimentaria|alimenticia|por_?invalidez|por_?vejez))?` `monto_?(jubilaci[oó]n|pensi[oó]n|beneficio|subsidio)` `valor_?(pensi[oó]n|subsidio|beneficio)` `rnc(_?monto)?` `ivm(_?monto)?` `r[eé]gimen_?no_?contributivo` `pension_?amount`

DATA TYPE — CR_FIN_PENSION — Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value. A pension of the Régimen No Contributivo says the person is poor, a pension by disability says the person has one.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
420000	→	646464

12.6 Social programme

CR_FIN_PROGRAMA_SOCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Membership of a programme: Avancemos, Crecemos, the bono de vivienda of the BANHVI, the Red de Cuido, a FONABE scholarship, an IMAS benefit, the Régimen No Contributivo.

HOW IT IS FOUND

COLUMN NAME — CR_FIN_PROGRAMA_SOCIAL — Path

90% `programa_?social` `beneficiario_?(programa|subsidio|beca|bono|prestaci[oó]n)` `avancemos` `crecemos` `bono_?(de_?)?vivienda` `banhvi` `fonabe` `beca_?(fonabe|mep|estudiantil)` `red_?(de_?)?cuido` `comedor_?escolar` `imas[a-z0-9_]*` `sinirube` `transferencia_?monetaria` `ayuda_?(social|estatal)` `subsidio(_?estatal)?` `social_?programme`

VALUE FORMAT CR_FIN_PROGRAMA_SOCIAL — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Avancemos, Crecemos, Bono de vivienda BANHVI, Red de Cuido, Pensión del Régimen No Contributivo, Beca FONABE, …	80%	
One of 11 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. The SINIRUBE joins the registers of every programme, so a single row of it states the condición socioeconómica of a household.

`CR_PROGRAMA_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PROGRAMA_SOCIAL_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_PROGRAMA_SOCIAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `cr-programas-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Subsidio estatal`	→	**`Beca FONABE`**

12.7 Condición socioeconómica

CR_FIN_CONDICION_SOCIOECONOMICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The classification of the IMAS or the SINIRUBE — pobreza extrema, pobreza básica, vulnerabilidad, no pobre —, the score of the ficha de información social, the quintile, the índice de desarrollo social.

HOW IT IS FOUND

COLUMN NAME CR_FIN_CONDICION_SOCIOECONOMICA — Path

90% `condici[oó]n_?socioecon[oó]mica` `nivel_?socioecon[oó]mico` `nse` `estrato_?socioecon[oó]mico` `clasificaci[oó]n_?(socioecon[oó]mica|imas|sinirube)` `puntaje_?(imas|sinirube|ficha)` `ficha_??(de_?)?informaci[oó]n_?social` `fis` `l[ií]nea_?(de_?)?pobreza` `condici[oó]n_?(de_?)?pobreza` `pobreza(_?extrema)?` `vulnerabilidad` `quintil(_?(de_?)?(ingreso|riqueza))?` `decil` `[ií]ndice_?(de_?)?desarrollo_?social`

VALUE FORMAT CR_FIN_CONDICION_SOCIOECONOMICA — Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Pobreza extrema, Pobreza básica, Vulnerabilidad, No pobre, Quintil 1, Quintil 2, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced inside its own list, a code by another code. This data class carries the law's own phrase: article 3 e) lists the **condición socioeconómica** as a sensitive datum, in the same sentence as racial origin and religious conviction, which no other law of the region does.

`CR_CONDICION_SOCIOECONOMICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CONDICION_SOCIOECONOMICA_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CONDICION_SOCIOECONOMICA_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `cr-condicion-socioeconomica-codigos.txt`, chosen by a keyed hash.
>
> `CR_CONDICION_SOCIOECONOMICA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `cr-condicion-socioeconomica.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Pobreza extrema	→	**Pobreza básica**

12.8 Housing tenure

CR_FIN_VIVIENDA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

How the household holds the dwelling: owned, paying in instalments, rented, in precario, lent.

HOW IT IS FOUND

COLUMN NAME — CR_FIN_VIVIENDA — Path

90% `tenencia_?(de_?)?(la_?)?vivienda` `tipo_?(de_?)?tenencia` `vivienda_?(propia|alquilada|tipo_?tenencia)` `condici[oó]n_?(de_?)?(la_?)?vivienda` `ocupaci[oó]n_?vivienda` `r[eé]gimen_?(de_?)?tenencia` `tugurio` `precario` `housing_?tenure`

VALUE FORMAT — CR_FIN_VIVIENDA — Values

PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — Propia totalmente pagada, Propia pagando a plazos, Alquilada, En precario, Cedida o prestada, Otra, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced inside its own list. "En precario" is a statement about poverty, which article 3 e) calls sensitive.

`CR_TENENCIA_VIVIENDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_TENENCIA_VIVIENDA_LISTA`.

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CR_TENENCIA_VIVIENDA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 6 values in `cr-tenencia-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Vivienda en precario	→	**Propia totalmente pagada**

PART 13

Criminal records (art. 8 c and Ley 6723)

Article 8 c) lets the principles of the law be limited for "la prevención, persecución, investigación, detención y represión de las infracciones penales" — a limit written for the authorities, not for whoever copies their tables. Article 11 of the **Ley 6723 del Registro y Archivos Judiciales**, as reformed by the **Ley 10453 of 4 March 2024**, cancels an entry on a scale that runs from the end of the sentence to ten years after it, and a certification issued for employment shows only what is still current. A non-production copy keeps the entry for as long as the copy lives, which is longer than any of those terms.

13.1 Criminal record

CR_PENAL_ANTECEDENTES

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

The hoja de delincuencia, the juzgamientos of the Registro Judicial, a conviction, a kind of offence, a precautionary measure, deprivation of liberty.

HOW IT IS FOUND

> COLUMN NAME CR_PENAL_ANTECEDENTES — Path
>
> 95% `antecedentes?(_?(penales|policiales|judiciales))?` `hoja_?(de_?)?delincuencia` `certificado_?(de_?)?antecedentes(_?penales)?` `registro_?judicial` `juzgamientos?` `reincidencia` `condena(_?(penal|tipo))?` `delito(_?(tipo|cometido))?` `tipo_?(de_?)?delito` `situaci[oó]n_?(jur[ií]dica|procesal)` `medida_?cautelar` `privad[oa]_?(de_?)?libertad` `centro_?penal` `adaptaci[oó]n_?social` `criminal_?record`
>
> 55% `estado_?(del_?)?proceso` `sentencia` `fallo`

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. Article 11 of the Ley 6723, reformed by the Ley 10453 of 2024, cancels an entry on a scale from the end of the sentence to ten years after it; a copy that lives longer than that keeps an entry the register itself has erased.

`CR_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ANTECEDENTES_LISTA` .

> `CR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CR_ANTECEDENTES_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Condenado por hurto en 2019`	→	**`Sentencia absolutoria`**

13.2 Judicial file number

CR_PENAL_EXPEDIENTE

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The number the Poder Judicial gives a case: the year, a correlative, the office and the matter, `24-001234-0007-PE`.

HOW IT IS FOUND

COLUMN NAME CR_PENAL_EXPEDIENTE — Path

90%	`n(o|ro|um|umero)_?(de_?)?(expediente_?(judicial|penal|fiscal)|causa|proceso_?(judicial|penal)|denuncia|sumaria)` `expediente_?(judicial|penal|fiscal)` `causa_?penal` `n(o|ro|um|umero)_?(de_?)?(carpeta|legajo)_?(fiscal|judicial)` `n(o|ro|um|umero)_?[uú]nico_?(de_?)?expediente` `oij_?(caso|expediente)`
50%	`expediente` `causa` `proceso` `sumaria`

VALUE FORMAT CR_PENAL_EXPEDIENTE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{2}-\d{6}-\d{4}-[A-Z]{2,4})`	90%	
`0*(?:\d{2}-\d{6}-\d{4})`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The correlative changes and the year, the office and the matter stay, so the file still looks like a file and no longer opens a public record. The file is searchable by number, which is what makes it an identifier.

`CR_EXPEDIENTE_JUDICIAL` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

`CR_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`CR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`24-001234-0007-PE`	→	**`24-009707-0007-PE`**
`12-000456-0164-CI`	→	**`12-000047-0164-CI`**

14

The IBAN check digits

Costa Rica is unusual in that **none of its identity numbers carries a check digit**: the cédula de identidad, the DIMEX, the NITE and the cédula jurídica are all validated against a register rather than by arithmetic. The Dirección General de Tributación checks a cédula against the Registro Civil in real time. So nothing in this policy has to recompute an identity digit — and the whole number can change, which is why even the provincia digit of a cédula is masked.

The **IBAN** is the one place where arithmetic matters, and it matters everywhere: since 2017 every Costa Rican account is an IBAN, SINPE moves on it, and any library that touches one validates it. The rule is ISO 13616: move the first four characters to the end, read `C` as 12 and `R` as 27, and the resulting number must leave a remainder of **1 modulo 97**. The BCCR's own example, CR05 0152 0200 1026 2840 66, does.

No masking framework computes a remainder modulo 97, and the Check Digit algorithm writes one character where these are two. So the policy computes it with lookup tables. A **two-digit state** — the remainder so far — is put where the old check digits were, and travels right through the number one character at a time; each step is a Data Cleansing that turns "state + character" into "character + new state", from a table of 1,067 lines, one for every pair of a remainder and a digit. At the right end a table of 97 lines turns the remainder into the check digits, by the formula $98 - (r \cdot 10^6 + 1227 \cdot 100) \bmod 97$. A second traveller then carries the two digits back to the front.

`CR` and the spaces of the printed form wait as one-character markers while this happens, and are written back at the end, so the compact form and the form printed in groups of four both come out as they went in — valid, with their bank, and with an account that belongs to nobody.

15

Where people live: distritos, cantones and the code that is also the postal code

Costa Rica is divided into 7 provincias, 84 cantones and 492 distritos, and the distritos are small: **413 of the 492 hold fewer than 20,000 inhabitants**, some 2.68 million people — more than half the country — and the smallest hold a few hundred. A birth date, a sex and one of those distritos point at a handful of people.

So a distrito below the threshold becomes the nearest distrito of at least 20,000 **in the same cantón**, measured between their centres; when the cantón has none, the nearest one in the same provincia. The cantones follow the same rule one level up — 15 of the 84 are below the threshold — and the 7 provincias stay, so a generalized value never leaves its provincia and a provincia column is never rewritten.

Costa Rica is full of homonyms: 179 of the 492 distritos share a name with another place, and there are distritos called San Rafael, San Isidro and San José in province after province. A name is generalized only when **every** place that bears it is small, to the fate of the most populous; 91 small distritos keep their own name because a homonym of theirs is large. Written with the cantón or the provincia beside it — `Matambú – Hojancha`, in any of five ways systems write that — the same rule applies inside the qualifier, which is how a small distrito is reached even when its bare name has to be left alone.

The codes follow the names, and here Costa Rica gives something no other country in the region does: the code of the División Territorial Administrativa — one digit for the provincia, two for the cantón, two for the distrito — **is the postal code**. Correos de Costa Rica assigns 10101 to the distrito 101 01. So one table of 428 lines generalizes the district code, the cantón code and the postal code at once, and a masked postal code always agrees with the masked distrito in the next column.

Below the distrito, the 2025 decree of the División Territorial Administrativa names 1,276 barrios. A barrio is far below any threshold, so it is not generalized upwards — that would say nothing a masked distrito does not already say — but replaced by another real barrio of the country, always the same one for the same input.

16

Limits

- **Masking with a key is pseudonymization, not desasociación.** Article 2 r) of the regulation asks that the result cannot be associated or linked to a determined or determinable person; whoever holds the key can reproduce the mapping, so a masked copy is still personal data and still needs the measures of article 10. To reach desasociación the key has to be discarded.
- **The population figures are estimates.** The distrito populations are the Instituto Nacional de Estadística y Censos estimate for 2022, projected from the 2011 census; they total some 5.20 million, about 3% above the 5,044,197 the 2022 census counted. A distrito within a few hundred of the 20,000 threshold may fall on the other side of it under the census figures, and that is worth checking for the few that sit there.
- **Sixteen distritos have no published figure of their own.** They were created after the distribution the estimate comes from — among them the three of the Río Cuarto cantón, Monteverde, Puerto Jiménez, Puente Salas, and the indigenous territories of Quitirrisí and Matambú — and Isla del Coco is uninhabited. The policy treats all sixteen as small, which generalizes them: the conservative choice, at the cost of some utility.
- **The bank of an IBAN is preserved.** It is not personal data, and keeping it keeps a test account inside a real bank; but a bank with few clients in a small place narrows a person a little. The two check digits are recomputed from the masked account, so they leak nothing about the original.
- **A birth date is shifted, not replaced.** Sixty days either way break the link to a public record and leave the age and the generation in place. Where a child's age decides something — a school year, a programme — a shift across a birthday moves a few rows; where that matters, shift the date the same way in every table that holds it.
- **Binary columns and attachments are out of reach.** A scanned cédula, a photograph, a PDF of a hoja de delincuencia or a clinical image keeps everything the columns beside it no longer say. The policy masks the path, not the file.
- **Discovery is a proposal, not a verdict.** The classifiers read column names and values; a column with a name nobody recognizes and few values may be missed, and one named like a person may be caught by mistake. Review the inventory before running a masking job, which is what the inventory is for.

17

Verification

The policy is checked on every build. The 141 classifier configurations are reviewed one by one, and a battery of 146 columns — well named, badly named, and 30 that are not personal data at all, among them a cédula jurídica — is profiled with the whole policy at its threshold of 60 and again with the essential pack alone: every column lands where it should, and none of the 30 is claimed.

The generalization is audited offline: all 492 distritos, all 84 cantones and all 7 provincias are checked against the rule, and every one of the 11,582 replacements the table writes is checked to name a place of at least 20,000 — in the right provincia, by name, with the cantón, with the provincia and by code.

The masking is run for real: 572 values across every data class, every one checked against what it should become. Two hundred cédulas give two hundred distinct outputs, all well formed, with the provincia digit

masked and never a zero. Two hundred IBANs — one hundred compact and one hundred printed in groups of four — give two hundred distinct outputs, **all of them valid under ISO 13616**, all keeping their bank and their written form.

18

Sources

- Ley 8968, Protección de la Persona frente al Tratamiento de sus Datos Personales, of 7 July 2011 (La Gaceta 170 of 5 September 2011).
- Reglamento a la Ley 8968, Decreto Ejecutivo 37554-JP, as amended by Decreto 40008-JP of 19 July 2016 and Decreto 41582 of 21 February 2019.
- Ley 6723 del Registro y Archivos Judiciales, article 11 as reformed by Ley 10453 of 4 March 2024.
- Ley 8239 de derechos y deberes de las personas usuarias de los servicios de salud; Ley 7771 General sobre el VIH-SIDA; Ley 7600 de igualdad de oportunidades para las personas con discapacidad and Ley 9379; Ley 8589 and Ley 9095 on violence and trafficking.
- División Territorial Administrativa de la República, Decreto Ejecutivo 44882-MGP (Alcance 12 to La Gaceta 17 of 28 January 2025): the 7 provincias, 84 cantones, 492 distritos and their barrios.
- Instituto Nacional de Estadística y Censos: the estimate of population by distrito for 2022, projected from the 2011 census, and the 2022 census totals. Postal codes from Correos de Costa Rica. District centres from the subnational boundary set of the Instituto Geográfico Nacional.
- Banco Central de Costa Rica, the IBAN of 22 characters and the Cuenta Cliente of SINPE; ISO 13616 for the check digits. Decreto 44648-MJ for the alphanumeric cédula jurídica of 2026.

APPENDIX A

Algorithms

Every algorithm of the policy in alphabetical order, with its configuration. The one a data class names is the top of its tree; the others are building blocks.

CR_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L2_ANIO_NACIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `CR_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ANTECEDENTES_LISTA`.

Used by: `CR_PENAL_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_ANTECEDENTES_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-antecedentes.txt`, chosen by a keyed hash.

Used by: `CR_ANTECEDENTES`

CONFIGURATION

lookupFile	`cr-antecedentes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_APELLIDO NAME

Replaces the name with one of the 420 names in `cr-apellidos.txt`.

Used by: `CR_PALABRA_APELLIDO`

CONFIGURATION

lookupFile	`cr-apellidos.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

CR_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_APELLIDO`, `CR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)`	`CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_APTITUD_LABORAL_LISTA`.

Used by: `CR_SALUD_OCUPACIONAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_APTITUD_LABORAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in `cr-aptitud-laboral.txt`, chosen by a keyed hash.

Used by: `CR_APTITUD_LABORAL`

CONFIGURATION

lookupFile	`cr-aptitud-laboral.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_CATEGORIA_SUPRIMIDA`, `CR_ESTADO_CIVIL`, `CR_NIVEL_EDUCATIVO`, `CR_ETNIA`, `CR_PUEBLO`, `CR_CONDICION_MIGRATORIA`, `CR_RELIGION`, `CR_PREFERENCIA_POLITICA`, `CR_PARTIDO`, `CR_ORIENTACION_SEXUAL`, `CR_IDENTIDAD_GENERO`, `CR_COBERTURA_SALUD`, `CR_DIAGNOSTICO`, `CR_MEDICAMENTO`, `CR_DISCAPACIDAD`, `CR_APTITUD_LABORAL`, `CR_HISTORIAL_CREDITICIO`, `CR_PROGRAMA_SOCIAL`, `CR_CONDICION_SOCIOECONOMICA`, `CR_TENENCIA_VIVIENDA`, `CR_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no)`	`CR_BANDERA_SI_NO`
`(?i)(true|false)`	`CR_BANDERA_TRUE_FALSE`
`(?i)(yes)`	`CR_BANDERA_YES_NO`
`(?i)([sn])`	`CR_BANDERA_S_N`
`(?i)([yx])`	`CR_BANDERA_Y_N`
`([01])`	`CR_BANDERA_0_1`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

Used by: `CR_BANDERA`

CONFIGURATION

lookupFile	`cr-bandera-0-1.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

Used by: `CR_BANDERA`

CONFIGURATION

lookupFile	`cr-bandera-s-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

Used by: `CR_BANDERA`

CONFIGURATION

lookupFile	`cr-bandera-si-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `CR_BANDERA`

CONFIGURATION

lookupFile	`cr-bandera-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `CR_BANDERA`

CONFIGURATION

lookupFile	`cr-bandera-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

Used by: `CR_BANDERA`

CONFIGURATION

lookupFile	`cr-bandera-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BARRIO SECURE LOOKUP

Replaces the value with one of the 1,276 values in `cr-barrios.txt`, chosen by a keyed hash.

Used by: `CR_L2_BARRIO`

CONFIGURATION

lookupFile	`cr-barrios.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CATEGORIA_SUGEF SECURE LOOKUP

Replaces the value with one of the 8 values in `cr-categorias-sugef.txt`, chosen by a keyed hash.

Used by: `CR_HISTORIAL_CREDITICIO`

CONFIGURATION

lookupFile	`cr-categorias-sugef.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_SUPRIMIR`.

Used by: `CR_L3_CONVICCION_FILOSOFICA`, `CR_L3_AFILIACION_SINDICAL`, `CR_L3_VIDA_SEXUAL`, `CR_L3_VICTIMA`, `CR_SALUD_VIH`, `CR_SALUD_REPRODUCTIVA`, `CR_SALUD_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))))`	keep · keep · keep · keep · keep · keep · keep · `CR_CM_ALFANUM`
otherwise	`CR_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

CR_CEDULA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.

Used by: `CR_DOCUMENTO`

PATTERNS, TRIED IN ORDER

`(0)(\d)[\s\-]?(\d{4})[\s\-]?(\d{4})`	keep · `CR_CM_DIGITO_1_9` · `CR_CM_DIGITOS_ANCHO_FIJO` · `CR_CM_DIGITOS_ANCHO_FIJO`
`(\d)[\s\-](\d{3,4})[\s\-](\d{3,4})`	`CR_CM_DIGITO_1_9` · `CR_CM_DIGITOS_ANCHO_FIJO` · `CR_CM_DIGITOS_ANCHO_FIJO`
`(\d)(\d{4})(\d{4})`	`CR_CM_DIGITO_1_9` · `CR_CM_DIGITOS_ANCHO_FIJO` · `CR_CM_DIGITOS_ANCHO_FIJO`
otherwise	`CR_CM_DIGITOS`

CONFIGURATION

trimInput	yes

requireMask	no

CR_CIE10 SECURE LOOKUP

Replaces the value with one of the 38 values in `cr-cie10.txt`, chosen by a keyed hash.

Used by: `CR_DIAGNOSTICO`

CONFIGURATION

lookupFile	`cr-cie10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 34 values in `cr-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `CR_DIAGNOSTICO`

CONFIGURATION

lookupFile	`cr-cie10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `CR_L1_SEGURO_SOCIAL`, `CR_L1_CODIGO_ESTUDIANTE`, `CR_L1_MATRICULA_PROFESIONAL`, `CR_L1_DIRECCION_COMPLEMENTO`, `CR_L1_BILLETERA`, `CR_L1_COOKIE`, `CR_L1_VEHICULO`, `CR_L1_CONTRATO`, `CR_L1_USUARIO`, `CR_SALUD_IDENTIFICADOR`, `CR_SALUD_RESULTADO_EXAMEN`, `CR_CATEGORIA_SUPRIMIDA`, `CR_NITE`, `CR_DOCUMENTO`, `CR_NOMBRES`, `CR_APELLIDOS`, `CR_NOMBRE_COMPLETO`, `CR_EMAIL`, `CR_INMUEBLE`, `CR_PUEBLO`, `CR_CONDICION_MIGRATORIA`, `CR_RELIGION`, `CR_PREFERENCIA_POLITICA`, `CR_PARTIDO`, `CR_ORIENTACION_SEXUAL`, `CR_IDENTIDAD_GENERO`, `CR_MEDICAMENTO`, `CR_DISCAPACIDAD`, `CR_APTITUD_LABORAL`, `CR_PROGRAMA_SOCIAL`, `CR_TENENCIA_VIVIENDA`, `CR_ANTECEDENTES`, `CR_EXPEDIENTE_JUDICIAL`

CONFIGURATION

characterGroups	`0123456789` `AEIOU` `BCDFGHJKLMNPQRSTVWXYZ` `aeiou` `bcdfghjklmnpqrstvwxyz` `ÁÉÍÓÚÜ` `áéíóúü`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CR_CM_DIGITO_1_9 CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `CR_CEDULA`, `CR_INMUEBLE`

CONFIGURATION

characterGroups	`123456789`
caseSensitive	yes

minMaskedPositions	`0`

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `CR_CEDULA` , `CR_DIMEX` , `CR_NITE` , `CR_TELEFONO` , `CR_IBAN_PREPARAR` , `CR_CUENTA` , `CR_PLACA` , `CR_INMUEBLE` , `CR_COORDENADA` , `CR_ANIO` , `CR_EDAD` , `CR_OCUPACION_O_CODIGO` , `CR_COBERTURA_SALUD` , `CR_PROCEDIMIENTO` , `CR_HISTORIAL_CREDITICIO` , `CR_EXPEDIENTE_JUDICIAL`

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CR_CM_DIGITOS_ANCHO_FIJO CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `CR_CEDULA`

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`

CR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: `CR_L1_PASAPORTE` , `CR_PLACA`

CONFIGURATION

characterGroups	`0123456789` `ABCDEFGHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CR_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `CR_L1_DISPOSITIVO` , `CR_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CR_COBERTURA SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-cobertura-salud.txt` , chosen by a keyed hash.

Used by: `CR_COBERTURA_SALUD`

CONFIGURATION

lookupFile	`cr-cobertura-salud.txt`

hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_COBERTURA.

Used by: CR_SALUD_COBERTURA

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	CR_BANDERA
(0*?)(?:(\d{1,8}))	keep · CR_CM_DIGITOS
otherwise	CR_COBERTURA

CONFIGURATION

trimInput	yes
requireMask	no

CR_CODIGO_DTA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_L2_CODIGO_DTA

PATTERNS, TRIED IN ORDER

(0*)([1-9]\d*)	keep · CR_CODIGO_DTA_TABLA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_CODIGO_DTA_TABLA DATA CLEANSING

Replaces each value found in cr-codigos-generalizados.txt (428 pairs) by its counterpart; values not in the file stay as they are.

Used by: CR_CODIGO_DTA

CONFIGURATION

lookupFile	cr-codigos-generalizados.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

CR_CONDICION_MIGRATORIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_CONDICION_MIGRATORIA_LISTA.

Used by: CR_L3_CONDICION_MIGRATORIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	CR_BANDERA
(0*?)(?:(\d{1,6}))	keep · CR_CM_ALFANUM

otherwise	`CR_CONDICION_MIGRATORIA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_CONDICION_MIGRATORIA_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `cr-condicion-migratoria.txt`, chosen by a keyed hash.

Used by: `CR_CONDICION_MIGRATORIA`

CONFIGURATION

lookupFile	`cr-condicion-migratoria.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CONDICION_SOCIOECONOMICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CONDICION_SOCIOECONOMICA_LISTA`.

Used by: `CR_FIN_CONDICION_SOCIOECONOMICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CR_CONDICION_SOCIOECONOMICA_CODIGO`
otherwise	`CR_CONDICION_SOCIOECONOMICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_CONDICION_SOCIOECONOMICA_CODIGO SECURE LOOKUP

Replaces the value with one of the 5 values in `cr-condicion-socioeconomica-codigos.txt`, chosen by a keyed hash.

Used by: `CR_CONDICION_SOCIOECONOMICA`

CONFIGURATION

lookupFile	`cr-condicion-socioeconomica-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CONDICION_SOCIOECONOMICA_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-condicion-socioeconomica.txt`, chosen by a keyed hash.

Used by: `CR_CONDICION_SOCIOECONOMICA`

CONFIGURATION

lookupFile	`cr-condicion-socioeconomica.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L2_PERSONAS_A_CARGO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)`	keep · `CR_CM_DIGITOS` · keep · keep · `CR_CM_DIGITOS`
`(-?\d{1,3}[.,]\d)(\d+)`	keep · `CR_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_CUENTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.

Used by: `CR_L1_CUENTA_BANCARIA`

PATTERNS, TRIED IN ORDER

`(?i)(CR\d{2}[\s]?\d{4}[\s]?\d{4}[\s]?\d{4}[\s]?\d{2})`	`CR_IBAN`
`(?i)(CR\d{20})`	`CR_IBAN`
`(0*?)(?:(\d{3})(\d{14}))`	keep · keep · `CR_CM_DIGITOS`
otherwise	`CR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

CR_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_DIAGNOSTICO_TEXTO`.

Used by: `CR_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`CR_CIE10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3}X?)`	`CR_CIE10`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
otherwise	`CR_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

CR_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 31 values in `cr-diagnosticos.txt`, chosen by a keyed hash.

Used by: `CR_DIAGNOSTICO`

CONFIGURATION

lookupFile	`cr-diagnosticos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_DIMEX REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS`.

Used by: `CR_L1_DIMEX`, `CR_DOCUMENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{11,12}))`	keep · `CR_CM_DIGITOS`
otherwise	`CR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

CR_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `cr-direcciones.txt`, chosen by a keyed hash.

Used by: `CR_L1_DIRECCION`

CONFIGURATION

lookupFile	`cr-direcciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

CR_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_DISCAPACIDAD_LISTA`.

Used by: `CR_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_DISCAPACIDAD_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-discapacidades.txt`, chosen by a keyed hash.

Used by: `CR_DISCAPACIDAD`

CONFIGURATION

lookupFile	`cr-discapacidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_DISTRITO DATA CLEANSING

Replaces each value found in `cr-distritos-generalizados.txt` (11,582 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CR_L2_DISTRITO`

CONFIGURATION

lookupFile	`cr-distritos-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

CR_DOCUMENTO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_CEDULA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(3[\s\-]?120[\s\-]?\d{6}))`	keep · `CR_NITE`
`(0*?)(?:(3[\s\-]?\d{3}[\s\-]?[\dA-Za-z]{6}))`	keep · keep
`(0*?)(?:([1-9]\d{10,11}))`	keep · `CR_DIMEX`
`(0*?)(?:(0?\d[\s\-]?\d{3,4}[\s\-]?\d{3,4}))`	keep · `CR_CEDULA`
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_L2_EDAD

PATTERNS, TRIED IN ORDER

(0*?)(?:([1-9]\d{2,}))	keep · replace with 90
(0*?)(?:([1-9])(\d)([.,]\d+))	keep · keep · CR_CM_DIGITOS · keep
(0*?)(?:([1-9])(\d))	keep · keep · CR_CM_DIGITOS
(0*?)(?:(\d))	keep · CR_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_CM_ALFANUM.

Used by: CR_L1_EMAIL

PATTERNS, TRIED IN ORDER

([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24}(?:\.[A-Za-z]{2})?)	CR_CM_ALFANUM · CR_CM_ALFANUM · replace with test
otherwise	CR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CR_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in cr-empleadores.txt, chosen by a keyed hash.

Used by: CR_L2_EMPLEADOR

CONFIGURATION

lookupFile	cr-empleadores.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_ESTADO_CIVIL_LISTA.

Used by: CR_L2_ESTADO_CIVIL

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CR_ESTADO_CIVIL_CODIGO`
otherwise	`CR_ESTADO_CIVIL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-estado-civil-codigos.txt`, chosen by a keyed hash.

Used by: `CR_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`cr-estado-civil-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-estado-civil.txt`, chosen by a keyed hash.

Used by: `CR_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`cr-estado-civil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 13 values in `cr-estados-credito.txt`, chosen by a keyed hash.

Used by: `CR_HISTORIAL_CREDITICIO`

CONFIGURATION

lookupFile	`cr-estados-credito.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ETNIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ETNIA_LISTA`.

Used by: `CR_L3_ETNIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CR_ETNIA_CODIGO`
otherwise	`CR_ETNIA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

`CR_ETNIA_CODIGO` SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-etnias-codigos.txt`, chosen by a keyed hash.

Used by: `CR_ETNIA`

CONFIGURATION

lookupFile	`cr-etnias-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`CR_ETNIA_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-etnias.txt`, chosen by a keyed hash.

Used by: `CR_ETNIA`

CONFIGURATION

lookupFile	`cr-etnias.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`CR_EXPEDIENTE_JUDICIAL` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_PENAL_EXPEDIENTE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2})(-)(\d{6})(-)(\d{4})(-)([A-Za-z]{2,4}))`	keep · keep · keep · `CR_CM_DIGITOS` · keep · keep · keep · keep
`(0*?)(?:(\d{2})(-)(\d{6})(-)(\d{4}))`	keep · keep · keep · `CR_CM_DIGITOS` · keep · keep
`(0*?)(?:(\d{1,6})([\s\-/])([A-Za-z]{2,10})([\s\-/])(\d{4}))`	keep · `CR_CM_DIGITOS` · keep · keep · keep · keep
`(0*?)(?:(\d{1,6})([\s\-/])(\d{4}))`	keep · `CR_CM_DIGITOS` · keep · keep
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `CR_L2_FECHA_EVENTO`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

CR_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `CR_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

CR_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_ESTADO_CREDITO`.

Used by: `CR_FIN_HISTORIAL_CREDITICIO`

PATTERNS, TRIED IN ORDER

`(?i)([A-E][12]?)`	`CR_CATEGORIA_SUGEF`
`(0*?)(?:(\d{1,4}))`	keep · `CR_CM_DIGITOS`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
otherwise	`CR_ESTADO_CREDITO`

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN STRING ALGORITHM CHAIN

Applies `CR_IBAN_1` → `CR_IBAN_2` → `CR_IBAN_3` → `CR_IBAN_4` → `CR_IBAN_5` → `CR_IBAN_6` → `CR_IBAN_RESTAURAR`, in this order.

Used by: `CR_CUENTA`

CONFIGURATION

algorithmReferences[1]	`CR_IBAN_1`
algorithmReferences[2]	`CR_IBAN_2`
algorithmReferences[3]	`CR_IBAN_3`
algorithmReferences[4]	`CR_IBAN_4`
algorithmReferences[5]	`CR_IBAN_5`
algorithmReferences[6]	`CR_IBAN_6`
algorithmReferences[7]	`CR_IBAN_RESTAURAR`

CR_IBAN_1 STRING ALGORITHM CHAIN

Applies `CR_IBAN_PREPARAR` → `CR_IBAN_IDA_01` → `CR_IBAN_IDA_02` → `CR_IBAN_IDA_03` → `CR_IBAN_IDA_04` → `CR_IBAN_IDA_05` → `CR_IBAN_IDA_06` → `CR_IBAN_IDA_07`, in this order.

Used by: `CR_IBAN`

CONFIGURATION

`algorithmReferences[1]`	`CR_IBAN_PREPARAR`
`algorithmReferences[2]`	`CR_IBAN_IDA_01`
`algorithmReferences[3]`	`CR_IBAN_IDA_02`
`algorithmReferences[4]`	`CR_IBAN_IDA_03`
`algorithmReferences[5]`	`CR_IBAN_IDA_04`
`algorithmReferences[6]`	`CR_IBAN_IDA_05`
`algorithmReferences[7]`	`CR_IBAN_IDA_06`
`algorithmReferences[8]`	`CR_IBAN_IDA_07`

CR_IBAN_2 STRING ALGORITHM CHAIN

Applies `CR_IBAN_IDA_08` → `CR_IBAN_IDA_09` → `CR_IBAN_IDA_10` → `CR_IBAN_IDA_11` → `CR_IBAN_IDA_12` → `CR_IBAN_IDA_13` → `CR_IBAN_IDA_14` → `CR_IBAN_IDA_15`, in this order.

Used by: `CR_IBAN`

CONFIGURATION

`algorithmReferences[1]`	`CR_IBAN_IDA_08`
`algorithmReferences[2]`	`CR_IBAN_IDA_09`
`algorithmReferences[3]`	`CR_IBAN_IDA_10`
`algorithmReferences[4]`	`CR_IBAN_IDA_11`
`algorithmReferences[5]`	`CR_IBAN_IDA_12`
`algorithmReferences[6]`	`CR_IBAN_IDA_13`
`algorithmReferences[7]`	`CR_IBAN_IDA_14`
`algorithmReferences[8]`	`CR_IBAN_IDA_15`

CR_IBAN_3 STRING ALGORITHM CHAIN

Applies `CR_IBAN_IDA_16` → `CR_IBAN_IDA_17` → `CR_IBAN_IDA_18` → `CR_IBAN_IDA_19` → `CR_IBAN_IDA_20` → `CR_IBAN_IDA_21` → `CR_IBAN_IDA_22` → `CR_IBAN_IDA_23`, in this order.

Used by: `CR_IBAN`

CONFIGURATION

`algorithmReferences[1]`	`CR_IBAN_IDA_16`
`algorithmReferences[2]`	`CR_IBAN_IDA_17`
`algorithmReferences[3]`	`CR_IBAN_IDA_18`
`algorithmReferences[4]`	`CR_IBAN_IDA_19`
`algorithmReferences[5]`	`CR_IBAN_IDA_20`
`algorithmReferences[6]`	`CR_IBAN_IDA_21`
`algorithmReferences[7]`	`CR_IBAN_IDA_22`
`algorithmReferences[8]`	`CR_IBAN_IDA_23`

CR_IBAN_4 STRING ALGORITHM CHAIN

Applies `CR_IBAN_CALCULAR` → `CR_IBAN_VUELTA_23` → `CR_IBAN_VUELTA_22` → `CR_IBAN_VUELTA_21` → `CR_IBAN_VUELTA_20` → `CR_IBAN_VUELTA_19` → `CR_IBAN_VUELTA_18` → `CR_IBAN_VUELTA_17`, in this order.

Used by: `CR_IBAN`

CONFIGURATION

`algorithmReferences[1]`	`CR_IBAN_CALCULAR`
`algorithmReferences[2]`	`CR_IBAN_VUELTA_23`
`algorithmReferences[3]`	`CR_IBAN_VUELTA_22`
`algorithmReferences[4]`	`CR_IBAN_VUELTA_21`
`algorithmReferences[5]`	`CR_IBAN_VUELTA_20`
`algorithmReferences[6]`	`CR_IBAN_VUELTA_19`
`algorithmReferences[7]`	`CR_IBAN_VUELTA_18`
`algorithmReferences[8]`	`CR_IBAN_VUELTA_17`

`CR_IBAN_5` STRING ALGORITHM CHAIN

Applies `CR_IBAN_VUELTA_16` → `CR_IBAN_VUELTA_15` → `CR_IBAN_VUELTA_14` → `CR_IBAN_VUELTA_13` → `CR_IBAN_VUELTA_12` → `CR_IBAN_VUELTA_11` → `CR_IBAN_VUELTA_10` → `CR_IBAN_VUELTA_09` , in this order.

Used by: `CR_IBAN`

CONFIGURATION

`algorithmReferences[1]`	`CR_IBAN_VUELTA_16`
`algorithmReferences[2]`	`CR_IBAN_VUELTA_15`
`algorithmReferences[3]`	`CR_IBAN_VUELTA_14`
`algorithmReferences[4]`	`CR_IBAN_VUELTA_13`
`algorithmReferences[5]`	`CR_IBAN_VUELTA_12`
`algorithmReferences[6]`	`CR_IBAN_VUELTA_11`
`algorithmReferences[7]`	`CR_IBAN_VUELTA_10`
`algorithmReferences[8]`	`CR_IBAN_VUELTA_09`

`CR_IBAN_6` STRING ALGORITHM CHAIN

Applies `CR_IBAN_VUELTA_08` → `CR_IBAN_VUELTA_07` → `CR_IBAN_VUELTA_06` → `CR_IBAN_VUELTA_05` → `CR_IBAN_VUELTA_04` → `CR_IBAN_VUELTA_03` → `CR_IBAN_VUELTA_02` → `CR_IBAN_VUELTA_01` , in this order.

Used by: `CR_IBAN`

CONFIGURATION

`algorithmReferences[1]`	`CR_IBAN_VUELTA_08`
`algorithmReferences[2]`	`CR_IBAN_VUELTA_07`
`algorithmReferences[3]`	`CR_IBAN_VUELTA_06`
`algorithmReferences[4]`	`CR_IBAN_VUELTA_05`
`algorithmReferences[5]`	`CR_IBAN_VUELTA_04`
`algorithmReferences[6]`	`CR_IBAN_VUELTA_03`
`algorithmReferences[7]`	`CR_IBAN_VUELTA_02`
`algorithmReferences[8]`	`CR_IBAN_VUELTA_01`

`CR_IBAN_CALCULAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.*)(.{2})`	keep · `CR_IBAN_RESULTADO`
`otherwise`	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{1})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

CR_IBAN_IDA_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_1`

PATTERNS, TRIED IN ORDER

`(.{5})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_1`

PATTERNS, TRIED IN ORDER

`(.{6})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_1`

PATTERNS, TRIED IN ORDER

`(.{7})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{8})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{9})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{10})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{11})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{12})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{14})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_2`

PATTERNS, TRIED IN ORDER

`(.{15})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_3`

PATTERNS, TRIED IN ORDER

`(.{16})(.{3})(.*)`	keep · `CR_IBAN_PAS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_3`

PATTERNS, TRIED IN ORDER

`(.{17})(.{3})(.*)`	keep · `CR_IBAN_PASO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_3`

PATTERNS, TRIED IN ORDER

`(.{18})(.{3})(.*)`	keep · `CR_IBAN_PASO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_3`

PATTERNS, TRIED IN ORDER

`(.{19})(.{3})(.*)`	keep · `CR_IBAN_PASO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_3`

PATTERNS, TRIED IN ORDER

`(.{20})(.{3})(.*)`	keep · `CR_IBAN_PASO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_3`

PATTERNS, TRIED IN ORDER

`(.{21})(.{3})(.*)`	keep · `CR_IBAN_PASO` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_22 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

(.{22})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_23 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

(.{23})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_PASO DATA CLEANSING

Replaces each value found in cr-iban-paso.txt (1,067 pairs) by its counterpart; values not in the file stay as they are.

Used by: CR_IBAN_IDA_01, CR_IBAN_IDA_02, CR_IBAN_IDA_03, CR_IBAN_IDA_04, CR_IBAN_IDA_05, CR_IBAN_IDA_06, CR_IBAN_IDA_07, CR_IBAN_IDA_08, CR_IBAN_IDA_09, CR_IBAN_IDA_10, CR_IBAN_IDA_11, CR_IBAN_IDA_12, CR_IBAN_IDA_13, CR_IBAN_IDA_14, CR_IBAN_IDA_15, CR_IBAN_IDA_16, CR_IBAN_IDA_17, CR_IBAN_IDA_18, CR_IBAN_IDA_19, CR_IBAN_IDA_20, CR_IBAN_IDA_21, CR_IBAN_IDA_22, CR_IBAN_IDA_23

CONFIGURATION

lookupFile	cr-iban-paso.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

CR_IBAN_PREPARAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

`(?i)(CR)(\d{2})( )(\d{4})( )(\d{4})( )(\d{4})( )(\d{4})( )(\d{2})`	replace with `~` · replace with `00` · replace with `_` · keep · replace with `_` · `CR_CM_DIGITOS` · replace with `_` · `CR_CM_DIGITOS` · replace with `_` · `CR_CM_DIGITOS` · replace with `_` · `CR_CM_DIGITOS`
`(?i)(CR)(\d{2})(\d{4})(\d{14})`	replace with `~` · replace with `00` · keep · `CR_CM_DIGITOS`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

CR_IBAN_RESTAURAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN`

PATTERNS, TRIED IN ORDER

`(~)(\d{2})(_)(\d{4})(_)(\d{4})(_)(\d{4})(_)(\d{4})(_)(\d{2})`	replace with `CR` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`(~)(\d{2})(\d{18})`	replace with `CR` · keep · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

CR_IBAN_RESULTADO DATA CLEANSING

Replaces each value found in `cr-iban-resultado.txt` (97 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CR_IBAN_CALCULAR`

CONFIGURATION

`lookupFile`	`cr-iban-resultado.txt`
`delimiter`	`|`
`caseSensitive`	yes
`trimWhitespace`	yes

CR_IBAN_TRASLADO DATA CLEANSING

Replaces each value found in `cr-iban-traslado.txt` (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CR_IBAN_VUELTA_23`, `CR_IBAN_VUELTA_22`, `CR_IBAN_VUELTA_21`, `CR_IBAN_VUELTA_20`, `CR_IBAN_VUELTA_19`, `CR_IBAN_VUELTA_18`, `CR_IBAN_VUELTA_17`, `CR_IBAN_VUELTA_16`, `CR_IBAN_VUELTA_15`, `CR_IBAN_VUELTA_14`, `CR_IBAN_VUELTA_13`, `CR_IBAN_VUELTA_12`, `CR_IBAN_VUELTA_11`, `CR_IBAN_VUELTA_10`, `CR_IBAN_VUELTA_09`, `CR_IBAN_VUELTA_08`, `CR_IBAN_VUELTA_07`, `CR_IBAN_VUELTA_06`, `CR_IBAN_VUELTA_05`, `CR_IBAN_VUELTA_04`, `CR_IBAN_VUELTA_03`, `CR_IBAN_VUELTA_02`, `CR_IBAN_VUELTA_01`

CONFIGURATION

`lookupFile`	`cr-iban-traslado.txt`
`delimiter`	`|`
`caseSensitive`	yes
`trimWhitespace`	yes

CR_IBAN_VUELTA_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{1})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{3})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{4})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{5})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{6})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{7})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_6`

PATTERNS, TRIED IN ORDER

`(.{8})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{9})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{10})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{11})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{12})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{14})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{15})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_5`

PATTERNS, TRIED IN ORDER

`(.{16})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{17})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

CR_IBAN_VUELTA_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{18})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

CR_IBAN_VUELTA_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{19})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

CR_IBAN_VUELTA_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{20})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

CR_IBAN_VUELTA_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{21})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes

requireMask	no

CR_IBAN_VUELTA_22 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{22})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_23 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

`(.{23})(.{3})(.*)`	keep · `CR_IBAN_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_IDENTIDAD_GENERO_LISTA` .

Used by: `CR_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_IDENTIDAD_GENERO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-identidades-genero.txt` , chosen by a keyed hash.

Used by: `CR_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	`cr-identidades-genero.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

CR_INMUEBLE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_INMUEBLE`

PATTERNS, TRIED IN ORDER

`(?i)([A-Z]{1,2})([\s\-])(\d{6,7})([\s\-])(\d{4})`	keep · keep · `CR_CM_DIGITOS` · keep · keep
`(0*?)(?:(\d)([\s\-])(\d{6})([\s\-])(\d{3}))`	keep · `CR_CM_DIGITO_1_9` · keep · `CR_CM_DIGITOS` · keep · `CR_CM_DIGITOS`
`(0*?)(?:(\d)([\s\-])(\d{6}))`	keep · `CR_CM_DIGITO_1_9` · keep · `CR_CM_DIGITOS`
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_INSTITUCION_EDUCATIVA SECURE LOOKUP

Replaces the value with one of the 12 values in `cr-instituciones-educativas.txt`, chosen by a keyed hash.

Used by: `CR_L2_INSTITUCION_EDUCATIVA`

CONFIGURATION

lookupFile	`cr-instituciones-educativas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_HEX`.

Used by: `CR_L1_IP`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `CR_OCTETO` · `CR_OCTETO` · `CR_OCTETO` · `CR_OCTETO`
otherwise	`CR_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

CR_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_MEDICAMENTO_LISTA`.

Used by: `CR_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`

otherwise	`CR_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 22 values in `cr-medicamentos.txt`, chosen by a keyed hash.

Used by: `CR_MEDICAMENTO`

CONFIGURATION

lookupFile	`cr-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in `cr-nacionalidades.txt`, chosen by a keyed hash.

Used by: `CR_L3_NACIONALIDAD`

CONFIGURATION

lookupFile	`cr-nacionalidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NITE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_NITE`, `CR_DOCUMENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(3[\s\-]?120[\s\-]?)(\d{6}))`	keep · keep · `CR_CM_DIGITOS`
`(0*?)(?:(3[\s\-]?130[\s\-]?[\dA-Za-z]{6}))`	keep · keep
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_NIVEL_EDUCATIVO_LISTA`.

Used by: `CR_L2_NIVEL_EDUCATIVO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CR_NIVEL_EDUCATIVO_CODIGO`
otherwise	`CR_NIVEL_EDUCATIVO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-nivel-educativo-codigos.txt`, chosen by a keyed hash.

Used by: `CR_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	`cr-nivel-educativo-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-nivel-educativo.txt`, chosen by a keyed hash.

Used by: `CR_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	`cr-nivel-educativo.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NOMBRE NAME

Replaces the name with one of the 400 names in `cr-nombres.txt`.

Used by: `CR_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	`cr-nombres.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

CR_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`CR_APELLIDOS` · `CR_NOMBRES`

`(\S+)`	`CR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO` · `CR_PALABRA_APELLIDO`
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_NOMBRE`, `CR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`CR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE` · `CR_PALABRA_NOMBRE`
otherwise	`CR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CR_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `CR_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

CR_OCUPACION SECURE LOOKUP

Replaces the value with one of the 37 values in `cr-ocupaciones.txt`, chosen by a keyed hash.

Used by: `CR_OCUPACION_O_CODIGO`

CONFIGURATION

lookupFile	`cr-ocupaciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

CR_OCUPACION_O_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_OCUPACION`.

Used by: `CR_L2_OCUPACION`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2,5}))`	keep · `CR_CM_DIGITOS`
otherwise	`CR_OCUPACION`

CONFIGURATION

trimInput	yes
requireMask	no

CR_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_ORIENTACION_SEXUAL_LISTA`.

Used by: `CR_L3_ORIENTACION_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_ORIENTACION_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cr-orientaciones-sexuales.txt`, chosen by a keyed hash.

Used by: `CR_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	`cr-orientaciones-sexuales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_APELLIDO`.

Used by: `CR_APELLIDOS`, `CR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|del|la|las|los|y|e|da|do|dos|san|santa|von|van|di|le)`	keep
otherwise	`CR_APELLIDO`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_NOMBRE`.

Used by: `CR_NOMBRES`, `CR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|del|la|las|los|y|e|da|do|dos|san|santa|von|van|di|le)`	keep
otherwise	`CR_NOMBRE`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PARTIDO_LISTA`.

Used by: `CR_L3_AFILIACION_PARTIDARIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_PARTIDO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in `cr-partidos.txt`, chosen by a keyed hash.

Used by: `CR_PARTIDO`

CONFIGURATION

lookupFile	`cr-partidos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PLACA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS_LETRAS`.

Used by: `CR_L1_PLACA`

PATTERNS, TRIED IN ORDER

`(?i)(MOT|CL|TSJ|TA|TB|TC|TG|TH|TL|TP|AB|SJB|PE|CD|C|M)([\s\-]?)(\d{3,6})`	keep · keep · `CR_CM_DIGITOS`
`([A-Za-z]{3})([\s\-]?)(\d{3})`	`CR_CM_DIGITOS_LETRAS` · keep · `CR_CM_DIGITOS`
`(0*?)(?:(\d{3,6}))`	keep · `CR_CM_DIGITOS`
otherwise	`CR_CM_DIGITOS_LETRAS`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PREFERENCIA_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PREFERENCIA_POLITICA_LISTA`.

Used by: `CR_L3_OPINION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_PREFERENCIA_POLITICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PREFERENCIA_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-preferencias-politicas.txt`, chosen by a keyed hash.

Used by: `CR_PREFERENCIA_POLITICA`

CONFIGURATION

lookupFile	`cr-preferencias-politicas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_PROCEDIMIENTO_TEXTO`.

Used by: `CR_SALUD_PROCEDIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{4,6}))`	keep · `CR_CM_DIGITOS`
otherwise	`CR_PROCEDIMIENTO_TEXTO`

CONFIGURATION

trimInput	yes

requireMask	no

CR_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-procedimientos.txt`, chosen by a keyed hash.

Used by: `CR_PROCEDIMIENTO`

CONFIGURATION

lookupFile	`cr-procedimientos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PROGRAMA_SOCIAL_LISTA`.

Used by: `CR_FIN_PROGRAMA_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_PROGRAMA_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-programas-sociales.txt`, chosen by a keyed hash.

Used by: `CR_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	`cr-programas-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PUEBLO_LISTA`.

Used by: `CR_L3_PUEBLO_INDIGENA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_PUEBLO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_PUEBLO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-pueblos.txt`, chosen by a keyed hash.

Used by: `CR_PUEBLO`

CONFIGURATION

lookupFile	`cr-pueblos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L1_CREDENCIAL`, `CR_L1_IMAGEN`, `CR_L3_BIOMETRICO`, `CR_L3_GENETICO`

PATTERNS, TRIED IN ORDER

`(.+)`	each character → `X`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_RELIGION_LISTA`.

Used by: `CR_L3_RELIGION`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_RELIGION_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-religiones.txt`, chosen by a keyed hash.

Used by: `CR_RELIGION`

CONFIGURATION

lookupFile	`cr-religiones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_L2_SEXO

PATTERNS, TRIED IN ORDER

(?i)(femenino|masculino)	CR_SEXO_FEMENINO_MASCULINO
(?i)(mujer|hombre)	CR_SEXO_MUJER_HOMBRE
(?i)(female|male)	CR_SEXO_FEMALE_MALE
(?i)([fm])	CR_SEXO_F_M
(?i)([hm])	CR_SEXO_H_M
(0*?)(?:([12]))	keep · CR_SEXO_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_SEXO_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-sexo-1-2.txt, chosen by a keyed hash.

Used by: CR_SEXO

CONFIGURATION

lookupFile	cr-sexo-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in cr-sexo-f-m.txt, chosen by a keyed hash.

Used by: CR_SEXO

CONFIGURATION

lookupFile	cr-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-sexo-female-male.txt, chosen by a keyed hash.

Used by: CR_SEXO

CONFIGURATION

lookupFile	`cr-sexo-female-male.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-femenino-masculino.txt`, chosen by a keyed hash.

Used by: `CR_SEXO`

CONFIGURATION

lookupFile	`cr-sexo-femenino-masculino.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-h-m.txt`, chosen by a keyed hash.

Used by: `CR_SEXO`

CONFIGURATION

lookupFile	`cr-sexo-h-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `CR_SEXO`

CONFIGURATION

lookupFile	`cr-sexo-mujer-hombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cr-sin-informacion.txt`, chosen by a keyed hash.

Used by: `CR_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`cr-sin-informacion.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L1_TARJETA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_DIGITOS` .

Used by: `CR_L1_TELEFONO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?506[\s\-]?)([2458-9])([\d\s\-]{7,10}))`	keep · keep · keep · `CR_CM_DIGITOS`
`(\(?\+?506\)?[\s\-]?)([2458-9])([\d\s\-]{7,10})`	keep · keep · `CR_CM_DIGITOS`
`(0*?)(?:([2458-9])([\d\s\-]{7,9}))`	keep · keep · `CR_CM_DIGITOS`
otherwise	`CR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

CR_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_TENENCIA_VIVIENDA_LISTA` .

Used by: `CR_FIN_VIVIENDA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CR_CM_ALFANUM`
otherwise	`CR_TENENCIA_VIVIENDA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CR_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-tenencia-vivienda.txt`, chosen by a keyed hash.

Used by: `CR_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	`cr-tenencia-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DATO]`, and the 1,944 terms of `cr-texto-nombres.txt` with `[NOMBRE]`.

Used by: `CR_L1_TEXTO_LIBRE`, `CR_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

`(?<!\d)\d-\d{4}-\d{4}(?!\d)`
`(?<!\d)[1-9]\d{8}(?!\d)`
`(?<!\d)\d{11,12}(?!\d)`
`3-1[23]0-\d{6}`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<![\d\-])(\+?506\-?)?[2458-9]\d{3}\-?\d{4}(?![\d\-])`
`(?<!\d)\d{13,19}(?!\d)`
`CR\d{20}`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATO]`
lookupFile	`cr-texto-nombres.txt`
lookupFileRedactValue	`[NOMBRE]`
isDenyList	yes

APPENDIX B

Files

The lookup and detection files the policy reads. In Delphix each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`cr-antecedentes.txt`	7	`CR_ANTECEDENTES_LISTA`	No registra antecedentes penales · Registra antecedentes · Con causa pendiente · Sentencia condenatoria
`cr-apellidos.txt`	420	`CR_APELLIDO`	Abarca · Acevedo · Acosta · Acuña
`cr-aptitud-laboral.txt`	4	`CR_APTITUD_LABORAL_LISTA`	Apto · Apto con restricciones · No apto · Pendiente
`cr-bandera-0-1.txt`	2	`CR_BANDERA_0_1`	0 · 1
`cr-bandera-s-n.txt`	2	`CR_BANDERA_S_N`	S · N
`cr-bandera-si-no.txt`	2	`CR_BANDERA_SI_NO`	Sí · No
`cr-bandera-true-false.txt`	2	`CR_BANDERA_TRUE_FALSE`	true · false
`cr-bandera-y-n.txt`	2	`CR_BANDERA_Y_N`	Y · N
`cr-bandera-yes-no.txt`	2	`CR_BANDERA_YES_NO`	Yes · No
`cr-barrios.txt`	1,276	`CR_BARRIO`	Abarca · Acacias · Acapulco · Acequia Grande
`cr-categorias-sugef.txt`	8	`CR_CATEGORIA_SUGEF`	A1 · A2 · B1 · B2
`cr-cie10-decimal.txt`	34	`CR_CIE10_DECIMAL`	E11.9 · E78.5 · J45.9 · J06.9
`cr-cie10.txt`	38	`CR_CIE10`	I10 · E11 · E78 · J45
`cr-cobertura-salud.txt`	10	`CR_COBERTURA`	Asegurado directo asalariado · Asegurado directo cuenta propia · Asegurado voluntario · Asegurado por el Estado
`cr-codigos-generalizados.txt`	428	`CR_CODIGO_DTA_TABLA`	10101|10105 · 10102|10103 · 10104|10105 · 10108|10110
`cr-condicion-migratoria.txt`	9	`CR_CONDICION_MIGRATORIA_LISTA`	Residente permanente · Residente temporal · Categoría especial · Persona refugiada
`cr-condicion-socioeconomica-codigos.txt`	5	`CR_CONDICION_SOCIOECONOMICA_CODIGO`	1 · 2 · 3 · 4
`cr-condicion-socioeconomica.txt`	10	`CR_CONDICION_SOCIOECONOMICA_LISTA`	Pobreza extrema · Pobreza básica · Vulnerabilidad · No pobre

FILE	LINES	USED BY	FIRST LINES
`cr-detectar-apellidos.txt`	539	`CR_L1_APELLIDO - List` `CR_L1_NOMBRE_COMPLETO - List`	Abarca · Acevedo · Acosta · Acuña
`cr-detectar-nombres.txt`	449	`CR_L1_NOMBRE - List` `CR_L1_NOMBRE_COMPLETO - List`	Adolfo · Adrián · Adrian · Adriana
`cr-detectar-sexo-letra.txt`	3	`CR_L2_SEXO - List`	f · m · h
`cr-detectar-sexo.txt`	6	`CR_L2_SEXO - List`	femenino · masculino · mujer · hombre
`cr-diagnosticos.txt`	31	`CR_DIAGNOSTICO_TEXTO`	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
`cr-direcciones.txt`	4,000	`CR_DIRECCION`	125 metros sur de el puente, casa esquinera color verde · 75 metros sureste de el EBAIS, apartamento 3 · 500 metros este de la entrada principal, última casa a mano derecha · Urbanización La Paz, casa 101
`cr-discapacidades.txt`	7	`CR_DISCAPACIDAD_LISTA`	Física o motora · Auditiva · Visual · Intelectual
`cr-distritos-generalizados.txt`	11,582	`CR_DISTRITO`	Carmen|San Nicolás · Carmen - San José|Zapote - San José · Carmen, San José|Zapote, San José · Carmen (San José)|Zapote (San José)
`cr-empleadores.txt`	24	`CR_EMPLEADOR`	Distribuidora Central S.A. · Constructora del Valle S.A. · Transportes La Meseta S.A. · Supermercados El Ahorro S.A.
`cr-estado-civil-codigos.txt`	6	`CR_ESTADO_CIVIL_CODIGO`	1 · 2 · 3 · 4
`cr-estado-civil.txt`	6	`CR_ESTADO_CIVIL_LISTA`	Soltero/a · Casado/a · Unión libre o de hecho · Separado/a
`cr-estados-credito.txt`	13	`CR_ESTADO_CREDITO`	Categoría A1 — riesgo normal · Categoría A2 — riesgo normal · Categoría B1 — riesgo bajo · Categoría B2 — riesgo bajo
`cr-etnias-codigos.txt`	7	`CR_ETNIA_CODIGO`	1 · 2 · 3 · 4
`cr-etnias.txt`	7	`CR_ETNIA_LISTA`	Indígena · Afrodescendiente o negra · Mulata · China
`cr-iban-paso.txt`	1,067	`CR_IBAN_PASO`	000|000 · 001|101 · 002|202 · 003|303
`cr-iban-resultado.txt`	97	`CR_IBAN_RESULTADO`	00|06 · 01|76 · 02|49 · 03|22
`cr-iban-traslado.txt`	1,100	`CR_IBAN_TRASLADO`	000|000 · 100|001 · 200|002 · 300|003
`cr-identidades-genero.txt`	7	`CR_IDENTIDAD_GENERO_LISTA`	Mujer cisgénero · Hombre cisgénero · Mujer trans · Hombre trans
`cr-instituciones-educativas.txt`	12	`CR_INSTITUCION_EDUCATIVA`	Escuela Juan Rafael Mora · Escuela República de Francia · Liceo de Costa Rica · Liceo del Sur

FILE	LINES	USED BY	FIRST LINES
cr-medicamentos.txt	22	CR_MEDICAMENTO_LISTA	Acetaminofén · Ibuprofeno · Diclofenaco · Metformina
cr-nacionalidades.txt	14	CR_NACIONALIDAD	Costarricense · Nicaragüense · Panameña · Colombiana
cr-nivel-educativo-codigos.txt	11	CR_NIVEL_EDUCATIVO_CODIGO	1 · 2 · 3 · 4
cr-nivel-educativo.txt	11	CR_NIVEL_EDUCATIVO_LISTA	Sin instrucción · Preescolar · Primaria incompleta · Primaria completa
cr-nombres.txt	400	CR_NOMBRE	Adolfo · Adrián · Adriana · Aída
cr-ocupaciones.txt	37	CR_OCUPACION	Empleado administrativo · Dependiente de tienda · Cajero · Chofer
cr-orientaciones-sexuales.txt	8	CR_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
cr-partidos.txt	13	CR_PARTIDO_LISTA	Liberación Nacional · Unidad Social Cristiana · Progreso Social Democrático · Nueva República
cr-preferencias-politicas.txt	7	CR_PREFERENCIA_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
cr-procedimientos.txt	10	CR_PROCEDIMIENTO_TEXTO	Consulta de medicina general · Consulta de urgencias · Hemograma completo · Glicemia en ayunas
cr-programas-sociales.txt	10	CR_PROGRAMA_SOCIAL_LISTA	Avancemos · Crecemos · Bono de vivienda (BANHVI) · Red de Cuido
cr-pueblos.txt	11	CR_PUEBLO_LISTA	Bribri · Cabécar · Maleku · Chorotega
cr-religiones.txt	10	CR_RELIGION_LISTA	Católica · Evangélica o protestante · Testigo de Jehová · Adventista del Séptimo Día
cr-sexo-1-2.txt	2	CR_SEXO_1_2	1 · 2
cr-sexo-f-m.txt	2	CR_SEXO_F_M	F · M
cr-sexo-female-male.txt	2	CR_SEXO_FEMALE_MALE	Female · Male
cr-sexo-femenino-masculino.txt	2	CR_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
cr-sexo-h-m.txt	2	CR_SEXO_H_M	H · M
cr-sexo-mujer-hombre.txt	2	CR_SEXO_MUJER_HOMBRE	Mujer · Hombre
cr-sin-informacion.txt	1	CR_SUPRIMIR	Sin información

FILE	LINES	USED BY	FIRST LINES
`cr-tenencia-vivienda.txt`	6	`CR_TENENCIA_VIVIENDA_LISTA`	Propia totalmente pagada · Propia pagando a plazos · Alquilada · En precario
`cr-texto-nombres.txt`	1,944	`CR_TEXTO_LIBRE`	Adolfo · ADOLFO · Adrián · ADRIÁN

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `comercial` `fantasia` `archivo` `calle` `avenida` `camino` `carretera` `ruta` `barrio` `caserio` `poblado` `distrito` `canton` `provincia` `pais` `banco` `sucursal` `agencia` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `escuela` `colegio` `liceo` `institucion` `universidad` `curso` `materia` `documento` `doc` `unidad` `clinica` `hospital` `ebais` `seguro` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `lengua` `idioma` `lugar` `sede` `local` `tienda` `deposito` `bodega` `proveedor` `convenio` `contrato` `poliza` `aseguradora` `entidad` `organismo` `organizacion` `institucional` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `linea` `actividad` `rubro` `sector` `finca` `plano` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `trabajador` `funcionario` `colaborador` `alumno` `estudiante` `deudor` `codeudor` `fiador` `garante` `solicitante` `propietario` `arrendatario` `inquilino` `conductor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `contacto` `referencia` `victima` `denunciante` `imputado` `testigo` `medico` `docente` `socio` `heredero` `donante` `tutor` `pensionado` `jubilado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `completo` `apellidos?` `usuario` `corto` `largo`

E2 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `comercial` `fantasia` `archivo` `calle` `avenida` `camino` `carretera` `ruta` `barrio` `caserio` `poblado` `distrito` `canton` `provincia` `pais` `banco` `sucursal` `agencia` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `escuela` `colegio` `liceo` `institucion` `universidad` `curso` `materia` `documento` `doc` `unidad` `clinica` `hospital` `ebais` `seguro` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `lengua` `idioma` `lugar` `sede` `local` `tienda` `deposito` `bodega` `proveedor` `convenio` `contrato` `poliza` `aseguradora` `entidad` `organismo` `organizacion` `institucional` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `linea` `actividad` `rubro` `sector` `finca` `plano` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `trabajador` `funcionario` `colaborador` `alumno` `estudiante` `deudor` `codeudor` `fiador` `garante` `solicitante` `propietario` `arrendatario` `inquilino` `conductor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `contacto` `referencia` `victima` `denunciante` `imputado` `testigo` `medico` `docente` `socio` `heredero` `donante` `tutor` `pensionado` `jubilado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner`

E3	`producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `comercial` `fantasia` `archivo` `calle` `avenida` `camino` `carretera` `ruta` `barrio` `caserio` `poblado` `distrito` `canton` `provincia` `pais` `banco` `sucursal` `agencia` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `escuela` `colegio` `liceo` `institucion` `universidad` `curso` `materia` `documento` `doc` `unidad` `clinica` `hospital` `ebais` `seguro` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `lengua` `idioma` `lugar` `sede` `local` `tienda` `deposito` `bodega` `proveedor` `convenio` `contrato` `poliza` `aseguradora` `entidad` `organismo` `organizacion` `institucional` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `linea` `actividad` `rubro` `sector` `finca` `plano` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `trabajador` `funcionario` `colaborador` `alumno` `estudiante` `deudor` `codeudor` `fiador` `garante` `solicitante` `propietario` `arrendatario` `inquilino` `conductor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `contacto` `referencia` `victima` `denunciante` `imputado` `testigo` `medico` `docente` `socio` `heredero` `donante` `tutor` `pensionado` `jubilado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `full` `complete` `last` `first`
E4	`ip` `mac` `email` `e_?mail` `correo` `electr[oó]nica` `web` `url` `tipo` `id` `general` `regional`
E5	`ip` `mac` `email` `e_?mail` `web` `url` `type` `id`
E6	`id` `cd` `cod` `codigo` `tipo` `fecha` `estado` `num` `nro`
E7	`id` `tipo` `codigo` `fecha` `estado` `cola` `log`
E8	`cod` `codigo` `id` `electoral` `judicial` `escolar` `riego`

APPENDIX D

Discovery policy and classifiers

The discovery policy `CR – Ley 8968 – v3` runs these 143 classifiers, with an assignment threshold of 60%.

Ley 8968 - datos personales y sensibles

CLASSIFIER	KIND	DATA CLASS
CR_L1_CEDULA – Path	COLUMN NAME	CR_L1_CEDULA
CR_L1_CEDULA – Type	DATA TYPE	CR_L1_CEDULA
CR_L1_CEDULA – Regex	VALUE FORMAT	CR_L1_CEDULA
CR_L1_DIMEX – Path	COLUMN NAME	CR_L1_DIMEX
CR_L1_DIMEX – Regex	VALUE FORMAT	CR_L1_DIMEX
CR_L1_NITE – Path	COLUMN NAME	CR_L1_NITE
CR_L1_NITE – Regex	VALUE FORMAT	CR_L1_NITE
CR_L1_PASAPORTE – Path	COLUMN NAME	CR_L1_PASAPORTE
CR_L1_PASAPORTE – Regex	VALUE FORMAT	CR_L1_PASAPORTE
CR_L1_SEGURO_SOCIAL – Path	COLUMN NAME	CR_L1_SEGURO_SOCIAL
CR_L1_CODIGO_ESTUDIANTE – Path	COLUMN NAME	CR_L1_CODIGO_ESTUDIANTE
CR_L1_MATRICULA_PROFESIONAL – Path	COLUMN NAME	CR_L1_MATRICULA_PROFESIONAL
CR_L1_NOMBRE – Path	COLUMN NAME	CR_L1_NOMBRE
CR_L1_NOMBRE – List	KNOWN VALUES	CR_L1_NOMBRE
CR_L1_APELLIDO – Path	COLUMN NAME	CR_L1_APELLIDO
CR_L1_APELLIDO – List	KNOWN VALUES	CR_L1_APELLIDO
CR_L1_NOMBRE_COMPLETO – Path	COLUMN NAME	CR_L1_NOMBRE_COMPLETO
CR_L1_NOMBRE_COMPLETO – List	KNOWN VALUES	CR_L1_NOMBRE_COMPLETO
CR_L1_EMAIL – Path	COLUMN NAME	CR_L1_EMAIL
CR_L1_EMAIL – Type	DATA TYPE	CR_L1_EMAIL
CR_L1_EMAIL – Regex	VALUE FORMAT	CR_L1_EMAIL
CR_L1_TELEFONO – Path	COLUMN NAME	CR_L1_TELEFONO
CR_L1_TELEFONO – Regex	VALUE FORMAT	CR_L1_TELEFONO
CR_L1_DIRECCION – Path	COLUMN NAME	CR_L1_DIRECCION
CR_L1_DIRECCION – Type	DATA TYPE	CR_L1_DIRECCION
CR_L1_DIRECCION – Regex	VALUE FORMAT	CR_L1_DIRECCION
CR_L1_DIRECCION_COMPLEMENTO – Path	COLUMN NAME	CR_L1_DIRECCION_COMPLEMENTO
CR_L1_CUENTA_BANCARIA – Path	COLUMN NAME	CR_L1_CUENTA_BANCARIA
CR_L1_CUENTA_BANCARIA – Regex	VALUE FORMAT	CR_L1_CUENTA_BANCARIA
CR_L1_TARJETA – Path	COLUMN NAME	CR_L1_TARJETA
CR_L1_TARJETA – Regex	VALUE FORMAT	CR_L1_TARJETA
CR_L1_BILLETERA – Path	COLUMN NAME	CR_L1_BILLETERA

CLASSIFIER	KIND	DATA CLASS
CR_L1_BILLETERA – Regex	VALUE FORMAT	CR_L1_BILLETERA
CR_L1_IP – Path	COLUMN NAME	CR_L1_IP
CR_L1_IP – Regex	VALUE FORMAT	CR_L1_IP
CR_L1_DISPOSITIVO – Path	COLUMN NAME	CR_L1_DISPOSITIVO
CR_L1_DISPOSITIVO – Regex	VALUE FORMAT	CR_L1_DISPOSITIVO
CR_L1_COOKIE – Path	COLUMN NAME	CR_L1_COOKIE
CR_L1_PLACA – Path	COLUMN NAME	CR_L1_PLACA
CR_L1_PLACA – Regex	VALUE FORMAT	CR_L1_PLACA
CR_L1_VEHICULO – Path	COLUMN NAME	CR_L1_VEHICULO
CR_L1_VEHICULO – Regex	VALUE FORMAT	CR_L1_VEHICULO
CR_L1_INMUEBLE – Path	COLUMN NAME	CR_L1_INMUEBLE
CR_L1_INMUEBLE – Regex	VALUE FORMAT	CR_L1_INMUEBLE
CR_L1_CONTRATO – Path	COLUMN NAME	CR_L1_CONTRATO
CR_L1_USUARIO – Path	COLUMN NAME	CR_L1_USUARIO
CR_L1_CREDENCIAL – Path	COLUMN NAME	CR_L1_CREDENCIAL
CR_L1_CREDENCIAL – Regex	VALUE FORMAT	CR_L1_CREDENCIAL
CR_L1_IMAGEN – Path	COLUMN NAME	CR_L1_IMAGEN
CR_L1_GEOLOCALIZACION – Path	COLUMN NAME	CR_L1_GEOLOCALIZACION
CR_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	CR_L1_GEOLOCALIZACION
CR_L1_TEXTO_LIBRE – Path	COLUMN NAME	CR_L1_TEXTO_LIBRE
CR_L1_TEXTO_LIBRE – Type	DATA TYPE	CR_L1_TEXTO_LIBRE
CR_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	CR_L1_TEXTO_LIBRE
CR_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	CR_L2_FECHA_NACIMIENTO
CR_L2_FECHA_NACIMIENTO – Type	DATA TYPE	CR_L2_FECHA_NACIMIENTO
CR_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	CR_L2_ANIO_NACIMIENTO
CR_L2_ANIO_NACIMIENTO – Type	DATA TYPE	CR_L2_ANIO_NACIMIENTO
CR_L2_EDAD – Path	COLUMN NAME	CR_L2_EDAD
CR_L2_EDAD – Type	DATA TYPE	CR_L2_EDAD
CR_L2_FECHA_EVENTO – Path	COLUMN NAME	CR_L2_FECHA_EVENTO
CR_L2_FECHA_EVENTO – Type	DATA TYPE	CR_L2_FECHA_EVENTO
CR_L2_SEXO – Path	COLUMN NAME	CR_L2_SEXO
CR_L2_SEXO – List	KNOWN VALUES	CR_L2_SEXO
CR_L2_DISTRITO – Path	COLUMN NAME	CR_L2_DISTRITO
CR_L2_DISTRITO – Values	VALUE FORMAT	CR_L2_DISTRITO
CR_L2_CODIGO_DTA – Path	COLUMN NAME	CR_L2_CODIGO_DTA
CR_L2_CODIGO_DTA – Regex	VALUE FORMAT	CR_L2_CODIGO_DTA
CR_L2_BARRIO – Path	COLUMN NAME	CR_L2_BARRIO

CLASSIFIER	KIND	DATA CLASS
CR_L2_ESTADO_CIVIL – Path	COLUMN NAME	CR_L2_ESTADO_CIVIL
CR_L2_ESTADO_CIVIL – Values	VALUE FORMAT	CR_L2_ESTADO_CIVIL
CR_L2_OCUPACION – Path	COLUMN NAME	CR_L2_OCUPACION
CR_L2_EMPLEADOR – Path	COLUMN NAME	CR_L2_EMPLEADOR
CR_L2_NIVEL_EDUCATIVO – Path	COLUMN NAME	CR_L2_NIVEL_EDUCATIVO
CR_L2_NIVEL_EDUCATIVO – Values	VALUE FORMAT	CR_L2_NIVEL_EDUCATIVO
CR_L2_INSTITUCION_EDUCATIVA – Path	COLUMN NAME	CR_L2_INSTITUCION_EDUCATIVA
CR_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	CR_L2_PERSONAS_A_CARGO
CR_L2_PERSONAS_A_CARGO – Type	DATA TYPE	CR_L2_PERSONAS_A_CARGO
CR_L3_ETNIA – Path	COLUMN NAME	CR_L3_ETNIA
CR_L3_ETNIA – Values	VALUE FORMAT	CR_L3_ETNIA
CR_L3_PUEBLO_INDIGENA – Path	COLUMN NAME	CR_L3_PUEBLO_INDIGENA
CR_L3_PUEBLO_INDIGENA – Values	VALUE FORMAT	CR_L3_PUEBLO_INDIGENA
CR_L3_NACIONALIDAD – Path	COLUMN NAME	CR_L3_NACIONALIDAD
CR_L3_NACIONALIDAD – Values	VALUE FORMAT	CR_L3_NACIONALIDAD
CR_L3_CONDICION_MIGRATORIA – Path	COLUMN NAME	CR_L3_CONDICION_MIGRATORIA
CR_L3_CONDICION_MIGRATORIA – Values	VALUE FORMAT	CR_L3_CONDICION_MIGRATORIA
CR_L3_RELIGION – Path	COLUMN NAME	CR_L3_RELIGION
CR_L3_RELIGION – Values	VALUE FORMAT	CR_L3_RELIGION
CR_L3_CONVICCION_FILOSOFICA – Path	COLUMN NAME	CR_L3_CONVICCION_FILOSOFICA
CR_L3_OPINION_POLITICA – Path	COLUMN NAME	CR_L3_OPINION_POLITICA
CR_L3_OPINION_POLITICA – Values	VALUE FORMAT	CR_L3_OPINION_POLITICA
CR_L3_AFILIACION_PARTIDARIA – Path	COLUMN NAME	CR_L3_AFILIACION_PARTIDARIA
CR_L3_AFILIACION_PARTIDARIA – Values	VALUE FORMAT	CR_L3_AFILIACION_PARTIDARIA
CR_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	CR_L3_AFILIACION_SINDICAL
CR_L3_AFILIACION_SINDICAL – Values	VALUE FORMAT	CR_L3_AFILIACION_SINDICAL
CR_L3_BIOMETRICO – Path	COLUMN NAME	CR_L3_BIOMETRICO
CR_L3_BIOMETRICO – Type	DATA TYPE	CR_L3_BIOMETRICO
CR_L3_GENETICO – Path	COLUMN NAME	CR_L3_GENETICO
CR_L3_GENETICO – Regex	VALUE FORMAT	CR_L3_GENETICO
CR_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	CR_L3_ORIENTACION_SEXUAL
CR_L3_ORIENTACION_SEXUAL – Values	VALUE FORMAT	CR_L3_ORIENTACION_SEXUAL
CR_L3_VIDA_SEXUAL – Path	COLUMN NAME	CR_L3_VIDA_SEXUAL
CR_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	CR_L3_IDENTIDAD_GENERO
CR_L3_IDENTIDAD_GENERO – Values	VALUE FORMAT	CR_L3_IDENTIDAD_GENERO
CR_L3_VICTIMA – Path	COLUMN NAME	CR_L3_VICTIMA
CR_SALUD_IDENTIFICADOR – Path	COLUMN NAME	CR_SALUD_IDENTIFICADOR

CLASSIFIER	KIND	DATA CLASS
CR_SALUD_COBERTURA – Path	COLUMN NAME	CR_SALUD_COBERTURA
CR_SALUD_COBERTURA – Values	VALUE FORMAT	CR_SALUD_COBERTURA
CR_SALUD_DIAGNOSTICO – Path	COLUMN NAME	CR_SALUD_DIAGNOSTICO
CR_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	CR_SALUD_DIAGNOSTICO
CR_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	CR_SALUD_PROCEDIMIENTO
CR_SALUD_MEDICAMENTO – Path	COLUMN NAME	CR_SALUD_MEDICAMENTO
CR_SALUD_MEDICAMENTO – Values	VALUE FORMAT	CR_SALUD_MEDICAMENTO
CR_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	CR_SALUD_TEXTO_CLINICO
CR_SALUD_TEXTO_CLINICO – Type	DATA TYPE	CR_SALUD_TEXTO_CLINICO
CR_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	CR_SALUD_RESULTADO_EXAMEN
CR_SALUD_VIH – Path	COLUMN NAME	CR_SALUD_VIH
CR_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	CR_SALUD_GRUPO_SANGUINEO
CR_SALUD_GRUPO_SANGUINEO – Values	VALUE FORMAT	CR_SALUD_GRUPO_SANGUINEO
CR_SALUD_DISCAPACIDAD – Path	COLUMN NAME	CR_SALUD_DISCAPACIDAD
CR_SALUD_DISCAPACIDAD – Values	VALUE FORMAT	CR_SALUD_DISCAPACIDAD
CR_SALUD_OCUPACIONAL – Path	COLUMN NAME	CR_SALUD_OCUPACIONAL
CR_SALUD_OCUPACIONAL – Values	VALUE FORMAT	CR_SALUD_OCUPACIONAL
CR_SALUD_REPRODUCTIVA – Path	COLUMN NAME	CR_SALUD_REPRODUCTIVA
CR_SALUD_MENTAL – Path	COLUMN NAME	CR_SALUD_MENTAL
CR_FIN_HISTORIAL_CREDITICIO – Path	COLUMN NAME	CR_FIN_HISTORIAL_CREDITICIO
CR_FIN_DEUDA – Path	COLUMN NAME	CR_FIN_DEUDA
CR_FIN_DEUDA – Type	DATA TYPE	CR_FIN_DEUDA
CR_FIN_INGRESOS – Path	COLUMN NAME	CR_FIN_INGRESOS
CR_FIN_INGRESOS – Type	DATA TYPE	CR_FIN_INGRESOS
CR_FIN_PATRIMONIO – Path	COLUMN NAME	CR_FIN_PATRIMONIO
CR_FIN_PATRIMONIO – Type	DATA TYPE	CR_FIN_PATRIMONIO
CR_FIN_PENSION – Path	COLUMN NAME	CR_FIN_PENSION
CR_FIN_PENSION – Type	DATA TYPE	CR_FIN_PENSION
CR_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	CR_FIN_PROGRAMA_SOCIAL
CR_FIN_PROGRAMA_SOCIAL – Values	VALUE FORMAT	CR_FIN_PROGRAMA_SOCIAL
CR_FIN_CONDICION_SOCIOECONOMICA – Path	COLUMN NAME	CR_FIN_CONDICION_SOCIOECONOMICA
CR_FIN_CONDICION_SOCIOECONOMICA – Values	VALUE FORMAT	CR_FIN_CONDICION_SOCIOECONOMICA
CR_FIN_VIVIENDA – Path	COLUMN NAME	CR_FIN_VIVIENDA
CR_FIN_VIVIENDA – Values	VALUE FORMAT	CR_FIN_VIVIENDA
CR_PENAL_ANTECEDENTES – Path	COLUMN NAME	CR_PENAL_ANTECEDENTES
CR_PENAL_EXPEDIENTE – Path	COLUMN NAME	CR_PENAL_EXPEDIENTE
CR_PENAL_EXPEDIENTE – Regex	VALUE FORMAT	CR_PENAL_EXPEDIENTE