DELPHIX CONTINUOUS COMPLIANCE · DISCOVERY POLICY

Mexico — LFPDPPP

Discovering and masking Mexican personal data: direct identifiers with valid check digits, quasi-identifiers, the sensitive data of article 2 and the financial and patrimonial data of article 7.

83	155	148
DATA CLASSES	CLASSIFIERS	ALGORITHMS

Discovery policy `MX – LFPDPPP – v4`

Version 4 of October 12, 2026 · Assignment threshold 60%

Contents

The first sections explain what the policy is for and how it works. The data class chapters then describe every data class: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the policy contains.

1	**About this discovery policy**	
2	**The LFPDPPP in brief**	
3	**How sensitive data is discovered**	
4	**How data is masked**	
5	**Essential and extended packs**	
6	**Data classes at a glance**	

PART 7 · DIRECT IDENTIFIERS

7.1	**CURP**	MX_L1_CURP
7.2	**RFC**	MX_L1_RFC
7.3	**Social security number (NSS)**	MX_L1_NSS
7.4	**INE voter key**	MX_L1_CLAVE_ELECTOR
7.5	**INE credential numbers**	MX_L1_CREDENCIAL_INE
7.6	**Given names**	MX_L1_NOMBRE
7.7	**Surnames**	MX_L1_APELLIDO
7.8	**Full name**	MX_L1_NOMBRE_COMPLETO
7.9	**E-mail**	MX_L1_EMAIL
7.10	**Phone number**	MX_L1_TELEFONO
7.11	**Address**	MX_L1_DIRECCION
7.12	**Address details**	MX_L1_DIRECCION_COMPLEMENTO
7.13	**CLABE**	MX_L1_CLABE
7.14	**Bank account**	MX_L1_CUENTA_BANCARIA
7.15	**Payment card**	MX_L1_TARJETA
7.16	**Passport**	MX_L1_PASAPORTE
7.17	**Immigration document**	MX_L1_DOCUMENTO_MIGRATORIO
7.18	**Professional license**	MX_L1_CEDULA_PROFESIONAL
7.19	**Driver's license**	MX_L1_LICENCIA_CONDUCIR
7.20	**e.firma certificate**	MX_L1_EFIRMA
7.21	**IP address**	MX_L1_IP
7.22	**Device identifier**	MX_L1_DISPOSITIVO
7.23	**License plate**	MX_L1_PLACA
7.24	**Vehicle identification number**	MX_L1_NIV
7.25	**Contract and customer numbers**	MX_L1_NUMERO_CONTRATO

7.26	Username and social media	MX_L1_USUARIO_RRSS
7.27	Credentials	MX_L1_CREDENCIAL
7.28	Geolocation	MX_L1_GEOLOCALIZACION
7.29	Free text	MX_L1_TEXTO_LIBRE

PART 8 · QUASI-IDENTIFIERS

8.1	Birth date	MX_L2_FECHA_NACIMIENTO
8.2	Birth year	MX_L2_ANIO_NACIMIENTO
8.3	Age	MX_L2_EDAD
8.4	Life event dates	MX_L2_FECHA_EVENTO
8.5	Sex	MX_L2_SEXO
8.6	Municipality	MX_L2_MUNICIPIO
8.7	Municipality code	MX_L2_CLAVE_MUNICIPIO
8.8	Locality	MX_L2_LOCALIDAD
8.9	Colonia	MX_L2_COLONIA
8.10	Postal code	MX_L2_CODIGO_POSTAL
8.11	Nationality	MX_L2_NACIONALIDAD
8.12	Marital status	MX_L2_ESTADO_CIVIL
8.13	Occupation	MX_L2_OCUPACION
8.14	Employer	MX_L2_EMPLEADOR
8.15	Schooling	MX_L2_ESCOLARIDAD
8.16	School	MX_L2_ESCUELA
8.17	School code (CCT)	MX_L2_CCT
8.18	Dependents and children	MX_L2_DEPENDIENTES

PART 9 · SENSITIVE DATA

9.1	Ethnic origin	MX_L3_ETNIA
9.2	Indigenous language	MX_L3_LENGUA_INDIGENA
9.3	Diagnosis	MX_L3_SALUD_DIAGNOSTICO
9.4	Medication	MX_L3_SALUD_MEDICAMENTO
9.5	Health record identifiers	MX_L3_SALUD_IDENTIFICADOR
9.6	Clinical notes	MX_L3_SALUD_TEXTO_CLINICO
9.7	Test results	MX_L3_SALUD_RESULTADO_EXAMEN
9.8	Blood type	MX_L3_SALUD_GRUPO_SANGUINEO
9.9	Disability	MX_L3_SALUD_DISCAPACIDAD
9.10	Sexual and reproductive health	MX_L3_SALUD_SEXUAL_REPRODUCTIVA
9.11	Mental health and addictions	MX_L3_SALUD_MENTAL_ADICCIONES
9.12	Biometric data	MX_L3_BIOMETRICO

9.13	Genetic information	MX_L3_INFORMACION_GENETICA
9.14	Sexual preference	MX_L3_PREFERENCIA_SEXUAL
9.15	Gender identity	MX_L3_IDENTIDAD_GENERO
9.16	Sexual life	MX_L3_VIDA_SEXUAL
9.17	Religion	MX_L3_RELIGION
9.18	Philosophical and moral beliefs	MX_L3_CREENCIA_FILOSOFICA_MORAL
9.19	Political opinions	MX_L3_OPINION_POLITICA
9.20	Party membership	MX_L3_AFILIACION_POLITICA
9.21	Union membership	MX_L3_AFILIACION_SINDICAL

PART 10 · FINANCIAL AND PATRIMONIAL DATA

10.1	Credit bureau record	MX_FIN_BURO_CREDITO
10.2	Debt amount	MX_FIN_MONTO_DEUDA
10.3	Monthly income	MX_FIN_INGRESO_MENSUAL
10.4	Daily wage (SDI, SBC)	MX_FIN_SALARIO_DIARIO
10.5	Assets	MX_FIN_PATRIMONIO
10.6	AFORE	MX_FIN_AFORE
10.7	Retirement and housing savings	MX_FIN_SALDO_RETIRO
10.8	Housing credit	MX_FIN_CREDITO_VIVIENDA
10.9	Social security coverage	MX_FIN_SEGURIDAD_SOCIAL
10.10	Social programs	MX_FIN_PROGRAMA_SOCIAL
10.11	Socioeconomic level	MX_FIN_NIVEL_SOCIOECONOMICO
10.12	Housing tenure	MX_FIN_VIVIENDA
10.13	Tax regime	MX_FIN_REGIMEN_FISCAL

PART 11 · CRIMINAL RECORDS

11.1	Criminal records	MX_PENAL_ANTECEDENTES
11.2	Case numbers	MX_PENAL_CAUSA
12	Check digits computed by the policy	
13	Dates inside keys	
14	Limits	
15	Verification	
16	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Discovery policy and classifiers	

1

About this discovery policy

This discovery policy finds the personal data in a Mexican database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and CURPs does not achieve that: a birth date, a sex and a small municipality single people out on their own. The policy works in the same layers the risk does:

- **Direct identifiers** — CURP, RFC, NSS, INE voter key, names, contact details, CLABE and cards, documents, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, municipality, locality, colonia, postal code, occupation, employer, schooling.
- **Sensitive data** — ethnic origin and indigenous language, health, genetic information, religious, philosophical and moral beliefs, political opinions, sexual preference, and union membership.
- **Financial and patrimonial data** — credit bureau records, debts, income, assets, retirement savings, housing credit, social security, social programs, socioeconomic level, tax regime.
- **Criminal records** — records and case numbers.

In Data Control Tower the policy is one discovery policy with its classifiers, the data classes they vote for, the algorithms those data classes name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — `NOMBRE`, `RESULTADO`, `CIUDAD` — needs the values to agree. A column with a meaningless name (`CAMPO1`, `OBS`) is still found when its values have a recognizable shape or vocabulary: a CURP, an RFC, an INE voter key, a CLABE, a plate, a municipality.

Column names are recognized in Spanish, in the abbreviations of Mexican systems (`AP_PATERNO`, `FEC_NAC`, `NUM_EXT`, `CVE_MUN`, `SDI`), in the attribute names of CFDI 4.0 invoices (`RfcReceptor`, `DomicilioFiscalReceptor`, `RegimenFiscalReceptor`) and in English.

> Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often store photos of the INE credential: the CURP and the voter key stay readable in the image. Report those columns as residual risk.

2

The LFPDPPP in brief

The Ley Federal de Protección de Datos Personales en Posesión de los Particulares was published in the Diario Oficial de la Federación on 20 March 2025 and took effect the next day, repealing the law of 2010. Its last amendment (14 November 2025) touched only its supplementary procedural rules. The INAI was dissolved: the authority is now the **Secretaría Anticorrupción y Buen Gobierno**. The public sector has its own law, the Ley General de Protección de Datos Personales en Posesión de Sujetos Obligados, issued the same day.

What matters for a copy of production data:

- **Personal data** is any information about an identified or identifiable person — identifiable directly or indirectly, through any information (art. 2, V).
- **Sensitive data** are those that touch the most intimate sphere of a person or whose misuse may lead to discrimination or serious risk. The law names, as examples and not as a closed list, data that may reveal racial or ethnic origin, present or future health, genetic information, religious, philosophical and moral

beliefs, political opinions and sexual preference (art. 2, VI). They need express written consent, and databases of sensitive data may only be created for legitimate, specific purposes (art. 8).

- **Financial and patrimonial data** need express consent (art. 7).
- **Purpose.** Data may only be processed for the purposes of the privacy notice; a different purpose needs new consent (art. 11). Development and testing are rarely among the purposes a customer agreed to.
- **Dissociation** — a procedure after which data can no longer be associated with the person nor, by their structure, content or level of detail, identify them (art. 2, IX). Consent is not required for data subjected to prior dissociation (art. 9, III).
- **Security.** Administrative, technical and physical measures proportional to the sensitivity of the data (art. 18); breaches that significantly affect people must be reported to them (art. 19); everyone involved keeps confidentiality (art. 20).
- **Sanctions.** Fines up to 320,000 times the UMA, which may be doubled for sensitive data (art. 59); prison of three months to five years for the crimes of chapter XII, doubled for sensitive data (arts. 62 to 64).

A test environment filled with production data is processing for a purpose the privacy notice does not cover, and holds sensitive and financial data outside the controls built for them. A dissociated copy is the route the law itself provides: that is what this policy is for.

Two notes on the categories. The 2010 law listed **union membership** as sensitive; the 2025 text no longer names it. Its list is not exhaustive and union membership still exposes people to discrimination, so the policy keeps it. **Biometric data** are not named either; they identify a person by definition and are treated as sensitive here.

> This document describes technical controls. Whether a copy counts as dissociated is a legal assessment of the whole environment — its access, its retention, what else is joined to it — and not of the discovery policy alone.

3

How sensitive data is discovered

A discovery job looks at every column of its rule set and asks each classifier of the discovery policy how confident it is that the column belongs to its data class. The policy uses the four classifier frameworks of Delphix:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the data class out. It never assigns a data class on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per data class, and the column is assigned to the data class with the highest confidence when it reaches the assignment threshold of the discovery policy — **60%** here. Values that do not match a format or a list count against their data class by the classifier's reject strength.

These are the names Data Control Tower gives the objects: data classes, classifiers and a discovery policy, run by a discovery job. A Continuous Compliance Engine used on its own calls the same objects domains, classifiers and a profile set, run by a profiling job; everything in this document applies to both.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. Discovery tests values as they come, so every format pattern first

removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Discovery proposes; it does not decide. Review the data classes assigned in the rule set before running a masking job, and look for columns the policy left unassigned.

4

How data is masked

Each data class names one algorithm, which a masking job applies to every column the rule set assigns to the data class. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each data class shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine and compliance node uses the same keys.

Where an algorithm that comes with Delphix already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the policy names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name, the one an engine uses; Data Control Tower lists them without the prefix (`CM Numeric`, `CreditCard`, `BloodType SL`). They are on every engine and in every Data Control Tower, and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. With other keys the masked values differ; their shape does not.

5

Essential and extended packs

The policy can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create just its data classes, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the discovery policy.

PACK	DATA CLASSES	CLASSIFIERS	ALGORITHMS	FILES
Essential	13	31	63	25
Extended	83	155	148	74

The essential pack holds these data classes, marked **Essential** in the tables and chapters:

- CURP — `MX_L1_CURP`
- RFC — `MX_L1_RFC`
- Social security number (NSS) — `MX_L1_NSS`
- INE voter key — `MX_L1_CLAVE_ELECTOR`
- Given names — `MX_L1_NOMBRE`
- Surnames — `MX_L1_APELLIDO`
- Full name — `MX_L1_NOMBRE_COMPLETO`
- E-mail — `MX_L1_EMAIL`
- Phone number — `MX_L1_TELEFONO`
- Address — `MX_L1_DIRECCION`
- Address details — `MX_L1_DIRECCION_COMPLEMENTO`
- Passport — `MX_L1_PASAPORTE`
- Birth date — `MX_L2_FECHA_NACIMIENTO`

> With fewer data classes competing, a column that a data class of the extended pack would claim by its name can be proposed for an essential data class instead — a numeric code, for instance, can look like a telephone number. Review the discovery result.

6

Data classes at a glance

Every data class of the policy, how it is found and the algorithm that masks it.

DATA CLASS	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
CURP ESSENTIAL MX_L1_CURP	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_CURP
RFC ESSENTIAL MX_L1_RFC	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_RFC
Social security number (NSS) ESSENTIAL MX_L1_NSS	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_NSS
INE voter key ESSENTIAL MX_L1_CLAVE_ELECTOR	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_CLAVE_ELECTOR
INE credential numbers MX_L1_CREDENCIAL_INE	COLUMN NAME · VALUE FORMAT	MX_CM_ALFANUM
Given names ESSENTIAL MX_L1_NOMBRE	COLUMN NAME · KNOWN VALUES	MX_NOMBRES
Surnames ESSENTIAL MX_L1_APELLIDO	COLUMN NAME · KNOWN VALUES	MX_APELLIDOS
Full name ESSENTIAL MX_L1_NOMBRE_COMPLETO	COLUMN NAME · KNOWN VALUES	MX_NOMBRE_COMPLETO
E-mail ESSENTIAL MX_L1_EMAIL	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_EMAIL
Phone number ESSENTIAL MX_L1_TELEFONO	COLUMN NAME · VALUE FORMAT	MX_TELEFONO
Address ESSENTIAL MX_L1_DIRECCION	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_DIRECCION
Address details ESSENTIAL MX_L1_DIRECCION_COMPLEMENTO	COLUMN NAME	MX_CM_ALFANUM
CLABE MX_L1_CLABE	COLUMN NAME · DATA TYPE · VALUE FORMAT	MX_CLABE
Bank account MX_L1_CUENTA_BANCARIA	COLUMN NAME	MX_CM_ALFANUM
Payment card MX_L1_TARJETA	COLUMN NAME · VALUE FORMAT	MX_TARJETA
Passport ESSENTIAL MX_L1_PASAPORTE	COLUMN NAME · VALUE FORMAT	MX_CM_ALFANUM
Immigration document MX_L1_DOCUMENTO_MIGRATORIO	COLUMN NAME	MX_CM_ALFANUM
Professional license MX_L1_CEDULA_PROFESIONAL	COLUMN NAME · VALUE FORMAT	MX_CM_ALFANUM
Driver's license MX_L1_LICENCIA_CONDUCIR	COLUMN NAME	MX_CM_ALFANUM

DATA CLASS	FOUND BY	ALGORITHM
e.firma certificate `MX_L1_EFIRMA`	COLUMN NAME · VALUE FORMAT	`MX_CM_ALFANUM`
IP address `MX_L1_IP`	COLUMN NAME · VALUE FORMAT	`MX_IP`
Device identifier `MX_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`MX_CM_HEX`
License plate `MX_L1_PLACA`	COLUMN NAME · VALUE FORMAT	`MX_PLACA`
Vehicle identification number `MX_L1_NIV`	COLUMN NAME · VALUE FORMAT	`MX_CM_ALFANUM`
Contract and customer numbers `MX_L1_NUMERO_CONTRATO`	COLUMN NAME	`MX_CM_ALFANUM`
Username and social media `MX_L1_USUARIO_RRSS`	COLUMN NAME	`MX_CM_ALFANUM`
Credentials `MX_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`MX_REDACTAR`
Geolocation `MX_L1_GEOLOCALIZACION`	COLUMN NAME · VALUE FORMAT	`MX_COORDENADA`
Free text `MX_L1_TEXTO_LIBRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`MX_TEXTO_LIBRE`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `MX_L2_FECHA_NACIMIENTO`	COLUMN NAME · DATA TYPE	`MX_FECHA_NACIMIENTO`
Birth year `MX_L2_ANIO_NACIMIENTO`	COLUMN NAME · DATA TYPE	`MX_ANIO`
Age `MX_L2_EDAD`	COLUMN NAME · DATA TYPE	`MX_EDAD`
Life event dates `MX_L2_FECHA_EVENTO`	COLUMN NAME · DATA TYPE	`MX_FECHA_EVENTO`
Sex `MX_L2_SEXO`	COLUMN NAME · KNOWN VALUES	`MX_SEXO`
Municipality `MX_L2_MUNICIPIO`	COLUMN NAME · VALUE FORMAT	`MX_MUNICIPIO`
Municipality code `MX_L2_CLAVE_MUNICIPIO`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`MX_CLAVE_MUNICIPIO`
Locality `MX_L2_LOCALIDAD`	COLUMN NAME	`MX_LOCALIDAD`
Colonia `MX_L2_COLONIA`	COLUMN NAME	`MX_COLONIA`
Postal code `MX_L2_CODIGO_POSTAL`	COLUMN NAME · VALUE FORMAT	`MX_CODIGO_POSTAL`
Nationality `MX_L2_NACIONALIDAD`	COLUMN NAME · VALUE FORMAT	`MX_NACIONALIDAD`
Marital status `MX_L2_ESTADO_CIVIL`	COLUMN NAME · VALUE FORMAT	`MX_ESTADO_CIVIL`

DATA CLASS	FOUND BY	ALGORITHM
Occupation MX_L2_OCUPACION	COLUMN NAME	MX_OCUPACION
Employer MX_L2_EMPLEADOR	COLUMN NAME	MX_EMPLEADOR
Schooling MX_L2_ESCOLARIDAD	COLUMN NAME VALUE FORMAT	MX_ESCOLARIDAD
School MX_L2_ESCUELA	COLUMN NAME	MX_ESCUELA
School code (CCT) MX_L2_CCT	COLUMN NAME VALUE FORMAT	MX_CM_ALFANUM
Dependents and children MX_L2_DEPENDIENTES	COLUMN NAME DATA TYPE	MX_CANTIDAD_ACOTADA
SENSITIVE DATA		
Ethnic origin MX_L3_ETNIA	COLUMN NAME VALUE FORMAT	MX_PUEBLO
Indigenous language MX_L3_LENGUA_INDIGENA	COLUMN NAME VALUE FORMAT	MX_LENGUA_INDIGENA
Diagnosis MX_L3_SALUD_DIAGNOSTICO	COLUMN NAME VALUE FORMAT	MX_DIAGNOSTICO
Medication MX_L3_SALUD_MEDICAMENTO	COLUMN NAME VALUE FORMAT	MX_MEDICAMENTO
Health record identifiers MX_L3_SALUD_IDENTIFICADOR	COLUMN NAME	MX_CM_ALFANUM
Clinical notes MX_L3_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	MX_TEXTO_LIBRE
Test results MX_L3_SALUD_RESULTADO_EXAMEN	COLUMN NAME	MX_CM_ALFANUM
Blood type MX_L3_SALUD_GRUPO_SANGUINEO	COLUMN NAME VALUE FORMAT	dlpx-core:BloodType SL
Disability MX_L3_SALUD_DISCAPACIDAD	COLUMN NAME VALUE FORMAT	MX_DISCAPACIDAD
Sexual and reproductive health MX_L3_SALUD_SEXUAL_REPRODUCTIVA	COLUMN NAME	MX_CATEGORIA_SUPRIMIDA
Mental health and addictions MX_L3_SALUD_MENTAL_ADICCIONES	COLUMN NAME	MX_CATEGORIA_SUPRIMIDA
Biometric data MX_L3_BIOMETRICO	COLUMN NAME DATA TYPE	MX_REDACTAR
Genetic information MX_L3_INFORMACION_GENETICA	COLUMN NAME VALUE FORMAT	MX_REDACTAR
Sexual preference MX_L3_PREFERENCIA_SEXUAL	COLUMN NAME VALUE FORMAT	MX_PREFERENCIA_SEXUAL
Gender identity MX_L3_IDENTIDAD_GENERO	COLUMN NAME VALUE FORMAT	MX_IDENTIDAD_GENERO
Sexual life MX_L3_VIDA_SEXUAL	COLUMN NAME	MX_CATEGORIA_SUPRIMIDA

DATA CLASS	FOUND BY	ALGORITHM
Religion `MX_L3_RELIGION`	COLUMN NAME · VALUE FORMAT	`MX_RELIGION`
Philosophical and moral beliefs `MX_L3_CREENCIA_FILOSOFICA_MORAL`	COLUMN NAME	`MX_CATEGORIA_SUPRIMIDA`
Political opinions `MX_L3_OPINION_POLITICA`	COLUMN NAME · VALUE FORMAT	`MX_OPINION_POLITICA`
Party membership `MX_L3_AFILIACION_POLITICA`	COLUMN NAME · VALUE FORMAT	`MX_PARTIDO_POLITICO`
Union membership `MX_L3_AFILIACION_SINDICAL`	COLUMN NAME · VALUE FORMAT	`MX_CATEGORIA_SUPRIMIDA`
FINANCIAL AND PATRIMONIAL DATA		
Credit bureau record `MX_FIN_BURO_CREDITO`	COLUMN NAME	`MX_BURO_CREDITO`
Debt amount `MX_FIN_MONTO_DEUDA`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Monthly income `MX_FIN_INGRESO_MENSUAL`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Daily wage (SDI, SBC) `MX_FIN_SALARIO_DIARIO`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Assets `MX_FIN_PATRIMONIO`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
AFORE `MX_FIN_AFORE`	COLUMN NAME · VALUE FORMAT	`MX_AFORE`
Retirement and housing savings `MX_FIN_SALDO_RETIRO`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Housing credit `MX_FIN_CREDITO_VIVIENDA`	COLUMN NAME · VALUE FORMAT	`MX_CREDITO_VIVIENDA`
Social security coverage `MX_FIN_SEGURIDAD_SOCIAL`	COLUMN NAME · VALUE FORMAT	`MX_SEGURIDAD_SOCIAL`
Social programs `MX_FIN_PROGRAMA_SOCIAL`	COLUMN NAME · VALUE FORMAT	`MX_PROGRAMA_SOCIAL`
Socioeconomic level `MX_FIN_NIVEL_SOCIOECONOMICO`	COLUMN NAME · VALUE FORMAT	`MX_NIVEL_SOCIOECONOMICO`
Housing tenure `MX_FIN_VIVIENDA`	COLUMN NAME · VALUE FORMAT	`MX_VIVIENDA`
Tax regime `MX_FIN_REGIMEN_FISCAL`	COLUMN NAME	`MX_REGIMEN_FISCAL`
CRIMINAL RECORDS		
Criminal records `MX_PENAL_ANTECEDENTES`	COLUMN NAME	`MX_ANTECEDENTES`
Case numbers `MX_PENAL_CAUSA`	COLUMN NAME · VALUE FORMAT	`MX_CM_ALFANUM`

PART 7

Direct identifiers

Data that identify a person on their own. The national keys — CURP, RFC, NSS, CLABE — keep a valid check digit after masking, because applications validate them and a test environment where they fail validation tests nothing.

7.1 CURP

MX_L1_CURP

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The Clave Única de Registro de Población: 18 characters built from the names (4 letters), the birth date, the sex, the state of birth, three internal consonants, a differentiator — a digit for people born before 2000, a letter after — and a check digit. `HEGA850720MDFRRL04`. The key of almost every Mexican record, and a quasi-identifier in itself: it carries the birth date, sex and state.

HOW IT IS FOUND

COLUMN NAME MX_L1_CURP — Path

90%

```
curp[a-z0-9_]*  c_?u_?r_?p  clave_?unica(_?de_?registro)?(_?de_?poblacion)?  curp_?(cte|cliente|emp|empleado|trab|trabajador|pac|paciente|alumno|benef|beneficiario|titular|asegurado|afiliado|derechohabiente|receptor|usuario|persona)  (cte|cliente|emp|trab|pac|alumno|benef|titular|asegurado)_?curp
```

DATA TYPE MX_L1_CURP — Type

Accepts text (length 18 or more); any other type rules the data class out.

VALUE FORMAT MX_L1_CURP — Regex

PATTERN	STRENGTH	NOTES
`[A-Z][AEIOUX][A-Z]{2}\d{2}(0[1-9]|1[0-2])(0[1-9]|[12]\d|3[01])[HMX](AS|BC|BS|CC|CL|CM|CS|CH|DF|DG|GT|GR|HG|JC|MC|MN|MS|NT|NL|OC|PL|QT|QR|SP|SL|SR|TC|TS|TL|VZ|YN|ZS|NE)[B-DF-HJ-NP-TV-Z]{3}[0-9A-Z]\d`	100%	
`[A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d`	90%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

Letters become other letters (vowel for vowel, consonant for consonant), the birth date another valid date of the same decade, the sex and state other values, the consonants and differentiator other ones of their kind — and the check digit is recomputed, so every masked CURP passes validation. The mapping is one-to-one: a CURP used as a key cannot collide. See *Check digits computed by the policy*.

`MX_CURP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

`MX_CURP_VALIDA` STRING ALGORITHM CHAIN

Applies `MX_CURP_CUERPO` → `MX_CURP_DV`, in this order.

`MX_CURP_CUERPO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_FECHA_AAMMDD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

`MX_MES` **NUMERIC MAPPING**

Maps the number to another between 1 and 12.

`MX_DIA_1_28` **NUMERIC MAPPING**

Maps the number to another between 1 and 28.

`MX_MES_30_DIAS` **SECURE LOOKUP**

Replaces the value with one of the 11 values in `mx-meses-30-dias.txt` , chosen by a keyed hash.

`MX_DIA_29_30` **NUMERIC MAPPING**

Maps the number to another between 29 and 30.

`MX_MES_31_DIAS` **SECURE LOOKUP**

Replaces the value with one of the 7 values in `mx-meses-31-dias.txt` , chosen by a keyed hash.

`MX_SEXO_H_M` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-h-m.txt` , chosen by a keyed hash.

`MX_ENTIDAD_CURP` **SECURE LOOKUP**

Replaces the value with one of the 33 values in `mx-entidad-curp.txt` , chosen by a keyed hash.

`MX_CURP_DV` **STRING ALGORITHM CHAIN**

Applies `MX_CURP_DV_P1` → `MX_CURP_DV_P2` → `MX_CURP_DV_P3` → `MX_CURP_DV_P4` → `MX_CURP_DV_P5` → `MX_CURP_DV_P6` → `MX_CURP_DV_P7` → `MX_CURP_DV_P8` , in this order. It is made of 16 algorithms that repeat the same step position by position; each one is in Appendix A.

EXAMPLES

VALUE		MASKED
HEGA850720MDFRRL04	→	**WUVU800428HTLBZD04**
LOPM030215HJCPRRA8	→	**GIFW090514HTLHDLE3**

7.2 RFC

MX_L1_RFC

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The Registro Federal de Contribuyentes: 13 characters for a person (4 letters, birth date, 2-character differentiator, check digit), 12 for a company. `HEGA850720ABA` . Appears in payroll, supplier and CFDI invoice tables.

HOW IT IS FOUND

COLUMN NAME MX_L1_RFC — Path

90% `rfc[a-z0-9_]*` `r_?f_?c` `registro_?federal(_?de)?(_?contribuyentes)?` `rfc_?(cte|cliente|emp|empleado|trab|trabajador|prov|proveedor|receptor|emisor|titular|contribuyente|persona|pf|fisica)` `(cte|cliente|emp|trab|prov|receptor|emisor|titular)_?rfc` `tax_?id` `id_?fiscal`

DATA TYPE MX_L1_RFC — Type

Accepts text (length 10 or more); any other type rules the data class out.

VALUE FORMAT MX_L1_RFC — Regex

PATTERN	STRENGTH	NOTES
`[A-ZÑ&]{4}\d{2}(0[1-9]|1[0-2])(0[1-9]|[12]\d|3[01])[A-Z0-9]{2}[0-9A]`	100%	
`[A-ZÑ&]{3}\d{2}(0[1-9]|1[0-2])(0[1-9]|[12]\d|3[01])[A-Z0-9]{2}[0-9A]`	90%	
`[A-ZÑ&]{4}\d{2}(0[1-9]|1[0-2])(0[1-9]|[12]\d|3[01])`	60%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

Same treatment as the CURP, with the SAT's modulo 11 check digit, `A` included. A person's RFC shares its first ten characters with their CURP, and both are masked with the same algorithms: after masking they still share them. Company RFCs are masked too — a column mixes both, and the incorporation date of a small company can point to its owner. An RFC without differentiator (10 characters) keeps its shape.

`MX_RFC` **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

> `MX_RFC_FISICA` **STRING ALGORITHM CHAIN**
>
> Applies `MX_RFC_CUERPO_FISICA` → `MX_RFC_DV`, in this order.
>
> > `MX_RFC_CUERPO_FISICA` **REGEX DECOMPOSE**
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: keep.
> >
> > > `MX_CM_ALFANUM` **CHARACTER MAPPING**
> > >
> > > Maps each character to another of its group (7 groups), keeping length and format.
> >
> > `MX_FECHA_AAMMDD` **REGEX DECOMPOSE**
> >
> > Tries 4 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.
> >
> > > `MX_MES` **NUMERIC MAPPING**
> > >
> > > Maps the number to another between 1 and 12.
> > >
> > > `MX_DIA_1_28` **NUMERIC MAPPING**
> > >
> > > Maps the number to another between 1 and 28.
> > >
> > > `MX_MES_30_DIAS` **SECURE LOOKUP**
> > >
> > > Replaces the value with one of the 11 values in `mx-meses-30-dias.txt`, chosen by a keyed hash.
> > >
> > > `MX_DIA_29_30` **NUMERIC MAPPING**
> > >
> > > Maps the number to another between 29 and 30.
> > >
> > > `MX_MES_31_DIAS` **SECURE LOOKUP**
> > >
> > > Replaces the value with one of the 7 values in `mx-meses-31-dias.txt`, chosen by a keyed hash.
>
> `MX_RFC_DV` **STRING ALGORITHM CHAIN**
>
> Applies `MX_RFC_DV_P1` → `MX_RFC_DV_P2` → `MX_RFC_DV_P3` → `MX_RFC_DV_P4` → `MX_RFC_DV_P5` → `MX_RFC_DV_P6`, in this order. It is made of 12 algorithms that repeat the same step position by position; each one is in Appendix A.

`MX_RFC_MORAL` **STRING ALGORITHM CHAIN**

Applies `MX_RFC_CUERPO_MORAL` → `MX_RFC_RELLENO` → `MX_RFC_DV` → `MX_RFC_SIN_RELLENO`, in this order.

> `MX_RFC_CUERPO_MORAL` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: keep.
>
> `MX_RFC_RELLENO` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: keep.
>
> > `MX_RFC_RELLENO_TABLA` **DATA CLEANSING**
> >
> > Replaces each value found in `mx-rfc-relleno.txt` (38 pairs) by its counterpart; values not in the file stay as they are.
>
> `MX_RFC_SIN_RELLENO` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
HEGA850720ABA	→	**WUVU800428EX5**
WMT970714R10	→	**DHL950413V22**

7.3 Social security number (NSS)

MX_L1_NSS

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The IMSS number: 11 digits holding the subdelegation, registration year, birth year, a sequence and a check digit. Present in every payroll and HR system.

HOW IT IS FOUND

COLUMN NAME MX_L1_NSS – Path

90% `nss[a-z0-9_]*` `n_?s_?s` `num(ero)?_?(de_?)?seguro_?social` `n(o|um|ro)_?(seg|seguro)_?soc(ial)?` `num(ero)?_?(de_?)?seguridad_?social` `numero_?imss` `n(o|um|ro)_?imss` `imss_?(num|nss|no)` `afiliacion_?imss` `nss_?(trab|trabajador|emp|empleado|asegurado|derechohabiente)`

DATA TYPE MX_L1_NSS – Type

Accepts text (length 11 to 13) or number (length 10 to 11); any other type rules the data class out.

VALUE FORMAT MX_L1_NSS – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{11})`	70%	LUHN check digit
`0*(?:\d{2}-?\d{2}-?\d{2}-?\d{4}-?\d)`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by another NSS that passes the same Luhn check — the check of payment cards, which the Payment Card framework keeps valid. The mapping is one-to-one. Written with dashes, it is masked digit by digit, without a valid check digit.

`MX_NSS` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

`MX_NSS_LUHN` PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345678903	→	**68774252859**

7.4 INE voter key

MX_L1_CLAVE_ELECTOR

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The clave de elector of the INE credential: 6 consonants from the names, birth date, state number, sex and a 3-digit differentiator. `GRHRAL85072009M100` . The INE credential is the most used identity document in Mexico.

HOW IT IS FOUND

COLUMN NAME MX_L1_CLAVE_ELECTOR — Path

90% `clave_?(de_?)?elector` `cve_?elector` `clave_?electoral` `clave_?ine` `clave_?ife` `elector_?(clave|key)` `voter_?key`

DATA TYPE MX_L1_CLAVE_ELECTOR — Type

Accepts text (length 18 or more); any other type rules the data class out.

VALUE FORMAT MX_L1_CLAVE_ELECTOR — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{6}\d{8}[HM]\d{3}`	100%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

Consonants mapped, birth date through the same algorithm as in the CURP (so a person's CURP and voter key keep the same masked date), state and sex replaced, differentiator mapped. The key has no check digit.

`MX_CLAVE_ELECTOR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_FECHA_AAMMDD` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .
>
> > `MX_MES` NUMERIC MAPPING
> >
> > Maps the number to another between 1 and 12.
> >
> > `MX_DIA_1_28` NUMERIC MAPPING
> >
> > Maps the number to another between 1 and 28.
> >
> > `MX_MES_30_DIAS` SECURE LOOKUP
> >
> > Replaces the value with one of the 11 values in `mx-meses-30-dias.txt` , chosen by a keyed hash.
> >
> > `MX_DIA_29_30` NUMERIC MAPPING
> >
> > Maps the number to another between 29 and 30.
> >
> > `MX_MES_31_DIAS` SECURE LOOKUP
> >
> > Replaces the value with one of the 7 values in `mx-meses-31-dias.txt` , chosen by a keyed hash.
>
> `MX_ENTIDAD_NUMERO` SECURE LOOKUP
>
> Replaces the value with one of the 32 values in `mx-entidad-numero.txt` , chosen by a keyed hash.
>
> `MX_SEXO_H_M` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `mx-sexo-h-m.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
GRHRAL85072009M100	→	**WVBMIF80042822H896**

7.5 INE credential numbers

MX_L1_CREDENCIAL_INE

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

The numbers that identify the physical credential: OCR (13 digits), CIC (9 digits), the citizen identifier and the issue number.

HOW IT IS FOUND

COLUMN NAME MX_L1_CREDENCIAL_INE — Path

85% `ocr(_?(ine|ife|credencial))?` `cic(_?(ine|ife|credencial))?` `id_?ciudadano` `identificador_?ciudadano` `folio_?(ine|ife|credencial|credencial_?elector)` `n(o|um|ro)_?(credencial_?(de_?)?elector|ine|ife)` `num(ero)?_?(de_?)?(ine|ife)` `credencial_?(ine|ife|elector|para_?votar)` `ine` `ife` `numero_?vertical` `num_?emision`

55% `credencial` `identificacion_?oficial` `n(o|um|ro)_?identificacion`

VALUE FORMAT MX_L1_CREDENCIAL_INE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{13})`	30%	
`0*(?:\d{9})`	20%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1234567890123	→	**4957065550289**

7.6 Given names

MX_L1_NOMBRE

ESSENTIAL | COLUMN NAME | KNOWN VALUES | REGEX DECOMPOSE

WHAT IT IS

First and middle names (`NOMBRES` , `PRIMER_NOMBRE`), including compound names such as `María Guadalupe` or `José Luis` .

HOW IT IS FOUND

COLUMN NAME MX_L1_NOMBRE — Path

85% `primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `nombre_?social` `first_?name` `given_?names?` `fname` `name_?first` `middle_?name` `nombre[12]` `nombres` *(except when followed by list E1)* `nom_?(pila|trab|emp)`

50% `nombre` *(except when followed by list E2)* `nomb?` *(except when followed by list E3)* `name` *(except when followed by list E4)*

KNOWN VALUES MX_L1_NOMBRE — List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-nombres.txt	301	70%	María, Maria, José, Jose, Juan, Luis

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word is replaced by a Mexican given name from a list of 255, keeping the number of words and the case. More than three words are masked character by character.

MX_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM.

MX_NOMBRE_PILA NAME

Replaces the name with one of the 255 names in mx-nombres.txt.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María Guadalupe	→	Gloria Pedro
JOSÉ LUIS	→	ROSARIO RODOLFO

7.7 Surnames

MX_L1_APELLIDO

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Paternal and maternal surnames, in one column or two.

HOW IT IS FOUND

COLUMN NAME MX_L1_APELLIDO — Path

85% apellidos? apellido_?(paterno|materno|pat|mat|uno|dos|[12]) ape_?(pat|mat|paterno|materno|[12]) apepat apemat appat apmat ap_?(pat|mat|paterno|materno) a_?paterno a_?materno paterno materno primer_?apellido segundo_?apellido last_?name surname lname family_?name second_?last_?name mother_?last_?name

KNOWN VALUES MX_L1_APELLIDO — List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-apellidos.txt	423	70%	Hernández, Hernandez, García, Garcia, Martínez, Martinez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word is replaced by one of the 337 most frequent Mexican surnames, keeping the number of words and the case.

MX_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM.

MX_APELLIDO NAME

Replaces the name with one of the 337 names in mx-apellidos.txt.

`MX_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Hernández López	→	**Lozano Salazar**

7.8 Full name

`MX_L1_NOMBRE_COMPLETO`

ESSENTIAL **COLUMN NAME** **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Given names and both surnames in one column, in Mexican order, or as `SURNAMES, NAMES`. Also the name of a titular, beneficiary, insured person or invoice receiver.

HOW IT IS FOUND

COLUMN NAME `MX_L1_NOMBRE_COMPLETO – Path`

90% `nombre_?(completo|compl|full)` `nombres?_?y_?apellidos?` `nombres?_?apellidos?` `nombreapellido` `nom_?completo` `nomcompleto` `nombrecompleto` `full_?name` `fullname` `person_?name` `customer_?name` `employee_?name` `patient_?name` `nombre_?(cliente|cte|cli|paciente|pac|trabajador|trab|empleado|colaborador|alumno|estudiante|afiliado|asegurado|derechohabiente|beneficiario|benef|titular|madre|padre|tutor|conyuge|pareja|medico|doctor|profesional|responsable|contacto|emergencia|aval|obligado|coacreditado|deudor|acreditado|remitente|destinatario|receptor|firmante|testigo|representante|apoderado|propietario|arrendatario|contratante|victima|denunciante|imputado|socio|donante|heredero|persona|pers|conductor|chofer|vendedor|ejecutivo|agente|solicitante|usuario_?final|ciudadano|elector|votante|contribuyente|jefe_?(de_?)?familia|hijo|hija|familiar|dependiente)` `nombre_?razon_?social_?receptor`

60% `titular` `beneficiario` `contacto_?emergencia` `conyuge` `tutor_?legal` `representante_?legal` `apoderado_?legal` `paciente` `victima` `asegurado` `contratante` `derechohabiente` `acreditado` `obligado_?solidario` `aval`

50% `nombre` *(except when followed by list E2)* `name` *(except when followed by list E4)*

KNOWN VALUES `MX_L1_NOMBRE_COMPLETO – List`

LIST	VALUES	STRENGTH	FIRST VALUES
`mx-detectar-nombres.txt`	301	65%	María, Maria, José, Jose, Juan, Luis
`mx-detectar-apellidos.txt`	423	65%	Hernández, Hernandez, García, Garcia, Martínez, Martinez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Given names become given names and surnames become surnames, by position: one word is a name, two are name and surname, three are name and two surnames, four are two names and two surnames. A comma separates surnames from names.

`MX_NOMBRE_COMPLETO` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

`MX_APELLIDOS` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

> `MX_APELLIDO` NAME
>
> Replaces the name with one of the 337 names in `mx-apellidos.txt`.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

`MX_NOMBRES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

> `MX_NOMBRE_PILA` NAME
>
> Replaces the name with one of the 255 names in `mx-nombres.txt`.

EXAMPLES

VALUE		MASKED
María Guadalupe Hernández López	→	**Gloria Pedro Lozano Salazar**
HERNÁNDEZ LÓPEZ, JUAN CARLOS	→	**LOZANO SALAZAR, CECILIA GERARDO**

7.9 E-mail

MX_L1_EMAIL

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

> COLUMN NAME MX_L1_EMAIL — Path
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electronico)?[a-z0-9_]*` `email_?address` `correo_?(personal|laboral|contacto|receptor|cliente)`

> DATA TYPE MX_L1_EMAIL — Type
>
> Accepts text (length 5 or more); any other type rules the data class out.

> VALUE FORMAT MX_L1_EMAIL — Regex

PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	

> A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes `.test`, reserved for tests: a masked address can never receive mail.

`MX_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
guadalupe.hernandez@gmail.com	→	**koepupoqe.vadvamdul@pgoeb.test**

7.10 Phone number

MX_L1_TELEFONO

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Landlines and mobiles. Since August 2019 every Mexican number has 10 digits: a 2-digit area code for Mexico City, Guadalajara and Monterrey (55, 56, 33, 81), 3 digits elsewhere.

HOW IT IS FOUND

> **COLUMN NAME** MX_L1_TELEFONO — Path
>
> 85% `tel` `telefono[a-z0-9_]*` `tel[eé]fono` `tel_?` `(cel|casa|particular|oficina|trabajo|movil|contacto|fijo|recados)` `celular[a-z0-9_]*` `cel` `movil` `m[oó]vil` `whatsapp` `wa` `fax` `phone[a-z0-9_]*` `mobile` `cellphone` `n(o|um|ro)_?` `tel(efono)?` `telef` `tlf` `lada` `extension`

> **VALUE FORMAT** MX_L1_TELEFONO — Regex
>
PATTERN	STRENGTH	NOTES
`0*(?:(\+?52[\s\-]?)?(1[\s\-]?)?\(?(55|56|33|81)\)?[\s\-]?\d{4}[\s\-]?\d{4})`	90%	
`0*(?:(\+?52[\s\-]?)?(1[\s\-]?)?\(?[2-9]\d{2}\)?[\s\-]?\d{3}[\s\-]?\d{4})`	80%	
`0*(?:\+?\d[\d\s()\-]{7,15})`	30%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The subscriber digits are masked; `+52` , the old mobile `1` , the area code and the separators stay. A number that does not have the shape of a Mexican number is masked digit by digit.

`MX_TELEFONO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+52 55 1234 5678	→	**+52 55 9707 7565**
(222) 123 4567	→	**(222) 957 9910**

7.11 Address

MX_L1_DIRECCION

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

The street line of an address: street, exterior and interior number, or block and lot (`Mz. 12 Lt. 5`).

HOW IT IS FOUND

COLUMN NAME MX_L1_DIRECCION — Path

80% `direccion[a-z_]*` *(except when followed by list ES)* `direcci[oó]n` `dir` `domicilio[a-z_]*` *(except when followed by `fiscal`)* `calle(_?y_?numero)?` `avenida` `address` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`)* `street` `addr` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`)* `dir_?(particular|comercial|laboral|envio|entrega|facturacion|cliente|paciente|trabajo)` `entre_?calles` `y_?calle` `residencia` `lugar_?(de_?)?residencia` `home_?address`

DATA TYPE MX_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the data class out.

VALUE FORMAT MX_L1_DIRECCION — Regex

PATTERN	STRENGTH	NOTES
`(?i)(av(enida)?\.?|calle|c\.|privada|priv\.?|andador|cerrada|calzada|calz\.?|blvd\.?|boulevard|bulevar|prolongaci[oó]n|prol\.?|carretera|camino|circuito|retorno)\s+.+\d+.*`	80%	
`[A-Za-zÁÉÍÓÚÑáéíóúñ'.\s]{4,}\s(#|no\.?\s?)?\d{1,5}(\s*(int|interior|depto|dpto|local)\.?\s*\w+)?`	40%	
`(?i).+\s(mz|mza|manzana)\.?\s*\d+\s*(lt|lte|lote)\.?\s*\d+`	70%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

Replaced by one of 3,000 fictitious Mexican addresses on common street names, with interior numbers and blocks and lots in realistic proportions.

`MX_DIRECCION` SECURE LOOKUP

Replaces the value with one of the 3,000 values in `mx-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Av. Insurgentes Sur 1602 Int. 4`	→	**`Calle Abasolo 7005`**

7.12 Address details

MX_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Exterior and interior numbers, block, lot, building or tower kept in their own columns.

HOW IT IS FOUND

COLUMN NAME MX_L1_DIRECCION_COMPLEMENTO — Path

70% `n(o|um|ro|umero)_?(ext|exterior|int|interior)` `num_?ext` `num_?int` `no_?ext` `no_?int` `numext` `numint` `exterior` `interior` `depto` `dpto` `manzana` `mza` `mz` `lote` `lt` `lte` `edificio` `torre` `casa_?(num|no|numero)` `house_?number` `apartment` `apt` `unit_?number`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Mz 12 Lt 5`	→	**`Jj 37 Jp 7`**

7.13 CLABE

MX_L1_CLABE

COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The 18-digit standardized bank key: bank (3), plaza (3), account (11) and check digit. Used in every SPEI transfer and payroll deposit.

HOW IT IS FOUND

COLUMN NAME — MX_L1_CLABE — Path

90% `clabe[a-z0-9_]*` `cta_?clabe` `cuenta_?clabe` `clabe_?interbancaria` `clave_?bancaria_?estandarizada` `cuenta_?interbancaria` `clabe_?(deposito|pago|cliente|beneficiario|trab|nomina)`

DATA TYPE — MX_L1_CLABE — Type

Accepts text (length 18 or more) or number (length 18 or more); any other type rules the data class out.

VALUE FORMAT — MX_L1_CLABE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{18})`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The bank code stays, so reports by bank still add up; plaza and account are masked and the check digit (weights 3, 7, 1, modulo 10) recomputed. Every masked CLABE is valid and the mapping is one-to-one.

`MX_CLABE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

> `MX_CLABE_VALIDA` CHECK DIGIT
>
> Masks the digits with `MX_CLABE_CUERPO` and recomputes a modulus 10 check digit with weights `3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7`.
>
> > `MX_CLABE_CUERPO` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: keep.
> >
> > > `MX_CM_ALFANUM` CHARACTER MAPPING
> > >
> > > Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`002180700545678911`	→	**`002141726834346236`**

7.14 Bank account

MX_L1_CUENTA_BANCARIA

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Account numbers other than the CLABE: checking, savings, payroll.

HOW IT IS FOUND

COLUMN NAME MX_L1_CUENTA_BANCARIA – Path

85% `cuenta_?(bancaria|banco|cheques|ahorro|deposito|abono|pago|destino|origen|nomina|debito|inversion)` `cta_?(bancaria|banco|cheques|ahorro|nomina)` `n(o|um|ro|umero)?_?(de_?)?cuenta(_?(banco|bancaria|cheques|nomina))?` `account_?(number|no|num|nbr)` `bank_?account` `num_?cta` `no_?cta`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
0123456789	→	**0110858568**

7.15 Payment card

MX_L1_TARJETA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_TARJETA – Path

85% `tarjeta(_?(credito|debito|cred|deb|num|no|numero|bancaria))?` `n(o|um|ro|umero)_?tarjeta` `pan` `card_?(number|no|num)` `credit_?card` `cc_?(number|num)` `tdc` `tdd` `num_?tdc` `plastico`

VALUE FORMAT MX_L1_TARJETA – Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1–9]\d{12,13}|[1–9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Credit Card, which comes with Delphix: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`MX_TARJETA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with Delphix and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4152 3131 2345 6780	→	**4152 3196 4606 3896**

7.16 Passport

MX_L1_PASAPORTE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Mexican and foreign passport numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_PASAPORTE — Path

85% `pasaporte[a-z_]*` `passport[a-z_]*` `n(o|um|ro|umero)_?pasaporte` `pasap`

VALUE FORMAT MX_L1_PASAPORTE — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]\d{8}`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
G12345678	→	**G27909346**

7.17 Immigration document

MX_L1_DOCUMENTO_MIGRATORIO

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Temporary and permanent resident cards, immigration forms, visas and foreign identity numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_DOCUMENTO_MIGRATORIO — Path

80% `tarjeta_?(de_?)?residente` `residente_?(temporal|permanente)` `documento_?migratorio` `doc_?migratorio` `forma_?migratoria` `fm_?[23]` `fmm` `n(o|um|ro)_?(documento_?)?migratorio` `id_?extranjero` `documento_?extranjero` `identificacion_?extranjera` `dni` `visa` `n(o|um|ro)_?visa` `national_?id`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456789	→	**110858568**

7.18 Professional license

MX_L1_CEDULA_PROFESIONAL

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

The number of the cédula profesional issued by the SEP. The registry is public: the number leads straight to the person's name.

HOW IT IS FOUND

COLUMN NAME MX_L1_CEDULA_PROFESIONAL — Path

85% `cedula_?profesional` `ced_?prof` `cedula_?(prof|medica|especialidad)` `n(o|um|ro)_?cedula` `cedula`

VALUE FORMAT MX_L1_CEDULA_PROFESIONAL — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{7,8})`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345678	→	**46916122**

7.19 Driver's license

MX_L1_LICENCIA_CONDUCIR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

State and federal driver's license numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_LICENCIA_CONDUCIR — Path

80% `licencia_?(de_?)?(conducir|manejo|chofer|automovilista|motociclista|federal)` `n(o|um|ro)_?licencia` `licencia` `driver_?license` `drivers_?license`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A12345678	→	**A67558943**

7.20 e.firma certificate

MX_L1_EFIRMA

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

The 20-digit serial number of an e.firma (FIEL) or digital seal certificate issued by the SAT.

HOW IT IS FOUND

COLUMN NAME MX_L1_EFIRMA – Path

85% `e_?firma` `efirma` `fiel` `firma_?electronica(_?avanzada)?` `n(o|um|ro)_?certificado(_?(sat|fiel|efirma|csd))?` `certificado_?(sat|fiel|efirma|digital)` `no_?certificado` `serial_?certificado` `csd`

VALUE FORMAT MX_L1_EFIRMA – Regex

PATTERN	STRENGTH	NOTES
`0*(?:0000[0-9]{16})`	80%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
00001000000504465028	→	**00003892502692600273**

7.21 IP address

MX_L1_IP

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses of users and devices.

HOW IT IS FOUND

COLUMN NAME MX_L1_IP – Path

85% `ip` `ip_?(address|addr|origen|destino|cliente|usuario|remota|publica|privada|acceso|conexion|login)` `direccion_?ip` `dir_?ip` `ipv[46]` `remote_?addr` `client_?ip` `host_?ip`

VALUE FORMAT MX_L1_IP – Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each IPv4 octet is mapped to a number from 1 to 254; an IPv6 address is mapped as hexadecimal.

`MX_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_HEX`.

> `MX_OCTETO` **NUMERIC MAPPING**
> Maps the number to another between 1 and 254.
>
> `MX_CM_HEX` **CHARACTER MAPPING**
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`189.203.4.10`	→	**`160.148.8.16`**

7.22 Device identifier

`MX_L1_DISPOSITIVO`

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

IMEI, MAC address, advertising and session identifiers, device serial numbers.

HOW IT IS FOUND

> **COLUMN NAME** `MX_L1_DISPOSITIVO – Path`
>
> **80%** `imei` `imsi` `iccid` `mac` `mac_?address` `direccion_?mac` `device_?id` `id_?dispositivo` `dispositivo_?id` `uuid_?dispositivo` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `id_?sesion` `serie_?equipo` `n(o|um|ro)_?serie_?(equipo|celular|telefono)`

> **VALUE FORMAT** `MX_L1_DISPOSITIVO – Regex`
>
PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Hexadecimal stays hexadecimal and digits stay digits, so the value keeps its format.

`MX_CM_HEX` **CHARACTER MAPPING**
Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`3c:22:fb:9a:10:e4`	→	**`5e:83:bb:3c:31:f9`**

7.23 License plate

`MX_L1_PLACA`

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

Vehicle plates in the formats of NOM-001-SCT-2-2016 (`URU–197–A`), Mexico City (`A–12–BCD`) and older series.

HOW IT IS FOUND

COLUMN NAME MX_L1_PLACA — Path

85% `placas?(_?(vehiculo|auto|circulacion|vehicular|num|no|numero))?` `n(o|um|ro)_?placas?` `matricula(_?(vehiculo|auto|vehicular))?` `license_?plate` `plate(_?number)?` `tarjeta_?(de_?)?` `circulacion`

VALUE FORMAT MX_L1_PLACA — Regex

PATTERN	STRENGTH	NOTES
`[ABCDEFGHJKLMNPRSTUVWXYZ]{3}[\s\-]?\d{3}[\s\-]?[ABCDEFGHJKLMNPRSTUVWXYZ]`	100%	
`[ABCDEFGHJKLMNPRSTUVWXYZ][\s\-]?\d{2}[\s\-]?[ABCDEFGHJKLMNPRSTUVWXYZ]{3}`	80%	
`[ABCDEFGHJKLMNPRSTUVWXYZ]{3}[\s\-]?\d{2}[\s\-]?\d{2}`	80%	
`0*(?:\d{3}[\s\-]?[ABCDEFGHJKLMNPRSTUVWXYZ]{3})`	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Letters map among the letters plates use — never `I`, `O` or `Q` — and digits among digits: the masked plate is still a valid plate. The state series is not preserved.

`MX_PLACA` CHARACTER MAPPING

Maps each character to another of its group (3 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
URU-197-A	→	**SGK-611-T**

7.24 Vehicle identification number

MX_L1_NIV

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The NIV (VIN), engine and chassis numbers and the REPUVE registration.

HOW IT IS FOUND

COLUMN NAME MX_L1_NIV — Path

80% `niv` `vin` `n(o|um|ro|umero)_?(de_?)?(serie|identificacion)_?(vehicular|vehiculo)` `serie_?vehicul(o|ar)` `n(o|um|ro)_?serie` `numero_?serie` `n(o|um|ro)_?motor` `chasis` `repuve` `folio_?repuve` `constancia_?repuve` `vin_?number`

VALUE FORMAT MX_L1_NIV — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format. The check digit of North American VINs is not recomputed.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3VWFE21C04M000001	→	**7VVCU97M86J091175**

7.25 Contract and customer numbers

MX_L1_NUMERO_CONTRATO

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Contract, policy, credit, customer, member, employee and payroll numbers — internal keys that lead to a person in the source system.

HOW IT IS FOUND

COLUMN NAME MX_L1_NUMERO_CONTRATO – Path

70% `contrato` `n(o|um|ro|umero)_?contrato` `p[oó]liza` `n(o|um|ro|umero)_?poliza` `n(o|um|ro)_?(de_?)?credito(_?(infonavit|fovissste))?` `credito_?(infonavit|fovissste)` `n(o|um|ro)_?operacion` `n(o|um|ro|umero)_?(de_?)?socio` `n(o|um|ro|umero)_?(de_?)?cliente` `id_?cliente` `cve_?cliente` `clave_?cliente` `n(o|um|ro|umero)_?(de_?)?empleado` `num_?emp` `no_?emp` `n(o|um|ro)_?nomina` `n(o|um|ro)_?afiliado` `n(o|um|ro)_?siniestro` `n(o|um|ro)_?(de_?)?matricula` `matricula_?(alumno|estudiante)` `n(o|um|ro)_?expediente_?(cliente|laboral|personal)` `folio_?(contrato|poliza|credito|cliente)`

HOW IT IS MASKED

Character by character, keeping length and format, so the same number masks the same way in every table.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
POL-123456	→	**MIF-194239**

7.26 Username and social media

MX_L1_USUARIO_RRSS

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Usernames, logins, aliases and social media handles.

HOW IT IS FOUND

COLUMN NAME MX_L1_USUARIO_RRSS – Path

70% `usuario` `username` `user_?name` `login` `nick(name)?` `alias` `cuenta_?usuario` `usr` `facebook` `instagram` `twitter` `tiktok` `linkedin` `red_?social` `perfil_?(facebook|instagram|twitter|linkedin|tiktok)` `telegram` `handle`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@lupita_hdz`	→	**`@numaje_hws`**

7.27 Credentials

`MX_L1_CREDENCIAL`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PINs, tokens, API keys, the SAT CIEC password and security questions.

HOW IT IS FOUND

COLUMN NAME `MX_L1_CREDENCIAL – Path`

90% `password` `passwd` `pwd` `pass` `contrasen[aã]` `contraseña` `clave[a-z_]*` *(except when followed by list E6)* `pin` `nip` `ciec` `contrasena_?(sat|efirma|fiel)` `hash_?password` `password_?hash` `secret` `token_?acceso` `access_?token` `refresh_?token` `api_?key` `otp` `respuesta_?secreta` `pregunta_?secreta`

VALUE FORMAT `MX_L1_CREDENCIAL – Regex`

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character becomes `X`. A credential has no place in a test environment.

`MX_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Secreta#2024`	→	**`XXXXXXXXXXX`**

7.28 Geolocation

`MX_L1_GEOLOCALIZACION`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude of homes, deliveries or devices.

HOW IT IS FOUND

COLUMN NAME MX_L1_GEOLOCALIZACION — Path

85% `lat` `latitud` `latitude` `lon` `lng` `longitude` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `geolocalizacion` `ubicacion_?gps` `gps` `posicion_?gps`

50% `longitud` `long`

VALUE FORMAT MX_L1_GEOLOCALIZACION — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(1[4-9]|2\d|3[0-3])\.\d{3,}\s*,\s*-(8[6-9]|9\d|1[01]\d)\.\d{3,})`	90%	
`0*(?:(1[4-9]|2\d|3[0-3])\.\d{3,})`	60%	
`-(8[6-9]|9\d|1[01]\d)\.\d{3,}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved to another region.

`MX_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`19.432608,-99.133209`	→	**`19.463593,-99.198278`**

7.29 Free text

MX_L1_TEXTO_LIBRE

COLUMN NAME DATA TYPE VALUE FORMAT FREE TEXT REDACTION

WHAT IT IS

Observations, comments, complaints, address references and notes where people write identifiers in the middle of a sentence.

HOW IT IS FOUND

COLUMN NAME MX_L1_TEXTO_LIBRE — Path

60% `observaciones?` `obs` `comentarios?` `notas?` `detalle` `descripcion_?(caso|queja|reclamo|incidente|solicitud|problema|atencion|hechos)` `texto_?libre` `mensaje` `queja` `reclamo` `referencias?(_?domicilio)?` `motivo_?(texto|detalle)` `narrativa` `relato` `resumen_?caso` `remarks` `comments?` `notes?` `free_?text` `memo` `bitacora`

DATA TYPE MX_L1_TEXTO_LIBRE — Type

Accepts text (length 30 or more); any other type rules the data class out.

VALUE FORMAT `MX_L1_TEXTO_LIBRE` — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d`	70%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`[A-ZÑ&]{4}\d{6}[A-Z0-9]{3}`	60%	anywhere in the value
`0*(?:(\+?52\s?)?\d{2,3}\s?\d{3,4}\s?\d{4})`	50%	anywhere in the value

A value that matches none does not count against the data class.

HOW IT IS MASKED

CURPs, RFCs, INE voter keys, e-mails, 10-digit phones, NSS, card and CLABE numbers, plates and IPs are replaced by `[DATO]`; given names and surnames from the lists by `[NOMBRE]`.

`MX_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with `[DATO]`, and the 1,436 terms of `mx-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Cliente Hernández, CURP HEGA850720MDFRRL04, correo g.hernandez@gmail.com, tel 5512345678.`	→	**`Cliente [NOMBRE], CURP [DATO], correo [DATO], tel [DATO].`**

PART 8

Quasi-identifiers

Data that identify no one alone but do in combination. Mexico has 2,469 municipalities, and 1,505 of them had fewer than 20,000 inhabitants in 2020: a birth date, a sex and one of those municipalities point to a handful of people. These attributes are generalized or shifted rather than replaced, so the data keep their analytical value.

8.1 Birth date

MX_L2_FECHA_NACIMIENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The strongest quasi-identifier: with sex and municipality it singles out most people.

HOW IT IS FOUND

COLUMN NAME MX_L2_FECHA_NACIMIENTO – Path

90% `fecha_?(de_?)?nac(imiento)?` `fec_?nac(imiento)?` `fch_?nac` `f_?nac(imiento|im)?` `fnac` `fechanac(imiento)?` `fecnac` `nacimiento` `dob` `birth_?date` `date_?of_?birth` `birthdate` `birthday` `cumplea(n|ñ)os`

DATA TYPE MX_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 60 days, the same way in every table for the same date.

`MX_FECHA_NACIMIENTO` DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

8.2 Birth year

MX_L2_ANIO_NACIMIENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The year of birth stored on its own.

HOW IT IS FOUND

COLUMN NAME MX_L2_ANIO_NACIMIENTO – Path

90% `an(i)?o_?(de_?)?nac(imiento)?` `año_?(de_?)?nac(imiento)?` `birth_?year` `year_?of_?birth` `ano_?nacim`

DATA TYPE MX_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

The decade stays and the last digit is masked — with the same mapping as the year inside a CURP, RFC or voter key.

`MX_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

8.3 Age

MX_L2_EDAD

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Age in years.

HOW IT IS FOUND

> COLUMN NAME MX_L2_EDAD — Path
>
> 85% `edad(_?(actual|paciente|cliente|afiliado|asegurado|derechohabiente|beneficiario|ingreso|anos|años|cumplida))?` `age` `anos_?cumplidos` `rango_?(de_?)?edad` `grupo_?(de_?)?edad` `edad_?en_?anos`

> DATA TYPE MX_L2_EDAD — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

HOW IT IS MASKED

The decade stays and the unit is masked (37 → 3x); 100 and over becomes 90, because very old ages are rare enough to identify.

`MX_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

8.4 Life event dates

MX_L2_FECHA_EVENTO

COLUMN NAME | DATA TYPE | DATE SHIFT

WHAT IT IS

Dates of death, marriage, hiring and dismissal, IMSS registration, disability leave, hospitalization, diagnosis, childbirth, arrest.

HOW IT IS FOUND

COLUMN NAME MX_L2_FECHA_EVENTO — Path

80% `fecha_?(de_?)?(defuncion|fallecimiento|muerte|matrimonio|divorcio|ingreso|alta_?(imss|patronal|laboral)|baja(_?(imss|laboral))?|contratacion|contrato|egreso|despido|renuncia|jubilacion|pension|incapacidad|hospitalizacion|alta_?medica|diagnostico|atencion|consulta|parto|embarazo|detencion|sentencia|vacunacion|cirugia|estudio|reingreso|antiguedad)` `fec_?(defuncion|ingreso|alta|baja|egreso|contrato|atencion|diagnostico|incapacidad)` `fch_?(ingreso|alta|baja|egreso)` `death_?date` `hire_?date` `termination_?date` `date_?of_?death` `admission_?date` `discharge_?date`

DATA TYPE MX_L2_FECHA_EVENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 30 days.

`MX_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

8.5 Sex

MX_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Sex or gender as recorded: `H` / `M`, `F` / `M`, `Hombre` / `Mujer`, `Masculino` / `Femenino`.

HOW IT IS FOUND

COLUMN NAME MX_L2_SEXO — Path

85% `sexo(_?(biologico|registral|paciente|cliente|asegurado|trabajador))?` `sex` `g[eé]nero` *(except when followed by* ***`identidad`****,* ***`social`****,* ***`autopercibido`****)* `gender` `cve_?sexo` `cod_?sexo`

KNOWN VALUES MX_L2_SEXO — List

LIST	VALUES	STRENGTH	FIRST VALUES
`mx-detectar-sexo.txt`	8	80%	hombre, mujer, femenino, masculino, female, male
`mx-detectar-sexo-letra.txt`	4	60%	h, m, f, x

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the data class.

HOW IT IS MASKED

Replaced within its own vocabulary. `H` / `M` uses the same lookup as the sex inside a CURP or voter key, so the three stay consistent.

`MX_SEXO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

> `MX_SEXO_PALABRA` SECURE LOOKUP
> Replaces the value with one of the 2 values in `mx-sexo-palabra.txt`, chosen by a keyed hash.
>
> `MX_SEXO_MUJER_HOMBRE` SECURE LOOKUP
> Replaces the value with one of the 2 values in `mx-sexo-mujer-hombre.txt`, chosen by a keyed hash.
>
> `MX_SEXO_INGLES` SECURE LOOKUP
> Replaces the value with one of the 2 values in `mx-sexo-ingles.txt`, chosen by a keyed hash.
>
> `MX_SEXO_H_M` SECURE LOOKUP
> Replaces the value with one of the 2 values in `mx-sexo-h-m.txt`, chosen by a keyed hash.
>
> `MX_SEXO_F_M` SECURE LOOKUP
> Replaces the value with one of the 2 values in `mx-sexo-f-m.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
M	→	**H**
Masculino	→	**Femenino**

8.6 Municipality

MX_L2_MUNICIPIO

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

WHAT IT IS

Municipality or Mexico City borough. 1,505 of the 2,469 municipalities had fewer than 20,000 inhabitants in the 2020 census.

HOW IT IS FOUND

> COLUMN NAME MX_L2_MUNICIPIO – Path
>
> 85% `municipio[a-z_]*` `nom(bre)?_?(mun|mpio|municipio)` `mpio` `mun` `d_?mnpio` `mnpio` `alcaldia` `delegacion` *(except when followed by list E7)* `demarcacion(_?territorial)?` `municipio_?(residencia|nacimiento|domicilio)`
>
> 60% `ciudad[a-z_]*` `city` `town` `d_?ciudad`

> VALUE FORMAT MX_L2_MUNICIPIO – Values
>
PATTERN	STRENGTH	NOTES
One of 2,288 known values, ignoring case — Aguascalientes, Asientos, Calvillo, Cosío, Jesús María, Pabellón de Arteaga, …	90%	
>
> A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A municipality under 20,000 inhabitants becomes the nearest municipality of the same state that has at least 20,000; larger ones stay. The result is a real, nearby municipality. Names without accents and in capitals are recognized. A name shared by several municipalities is generalized only when all of them are small.

`MX_MUNICIPIO` DATA CLEANSING

Replaces each value found in `mx-municipio-generalizado.txt` (6,547 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Santa María Tlahuitoltepec	→	**Santa Lucía del Camino**
Guadalajara	→	**Guadalajara**

8.7 Municipality code

MX_L2_CLAVE_MUNICIPIO

COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The 5-digit INEGI geostatistical code of a municipality (state + municipality), with or without the leading zero.

HOW IT IS FOUND

COLUMN NAME MX_L2_CLAVE_MUNICIPIO – Path

85% `cve_?(geo|mun|mpio|municipio|inegi)` `clave_?(geo(estadistica)?|mun|mpio|municipio|inegi)(_?(inegi|municipal))?` `cod(igo)?_?(mun|mpio|municipio|inegi)` `id_?(mun|mpio|municipio)` `c_?mnpio` `municipio_?(cve|clave|id|cod|inegi)` `cvegeo`

DATA TYPE MX_L2_CLAVE_MUNICIPIO – Type

Accepts number (length up to 5) or text (length up to 5); any other type rules the data class out.

VALUE FORMAT MX_L2_CLAVE_MUNICIPIO – Values

PATTERN	STRENGTH	NOTES
One of 2,758 known values, ignoring case — 01001, 1001, 01002, 1002, 01003, 1003, …	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Generalized exactly like the municipality name, without the ambiguity of homonyms.

`MX_CLAVE_MUNICIPIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`MX_CLAVE_MUNICIPIO_TABLA` DATA CLEANSING

Replaces each value found in `mx-clave-municipio-generalizada.txt` (2,758 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
20426	→	**20006**

8.8 Locality

MX_L2_LOCALIDAD

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

Locality, town, ejido, rancho or community — often a few hundred inhabitants — and place of birth.

HOW IT IS FOUND

COLUMN NAME MX_L2_LOCALIDAD — Path

80% `localidad[a-z_]*` `nom(bre)?_?loc(alidad)?` `poblado` `ranch[oe]ria` `ejido` `comunidad` *(except when followed by* `indigena`, `religiosa`*)* `pueblo_?(residencia|origen)` `lugar_?(de_?)?nacimiento` `origen_?(localidad|poblacion)`

HOW IT IS MASKED

Replaced by the name of a municipality of over 100,000 inhabitants: still a place, no longer theirs.

`MX_LOCALIDAD` SECURE LOOKUP

Replaces the value with one of the 229 values in `mx-localidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
San Isidro Buenavista	→	**Cuautla**

8.9 Colonia

MX_L2_COLONIA

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Colonia, fraccionamiento, barrio or housing unit: with the postal code, it narrows an address down to a few blocks.

HOW IT IS FOUND

COLUMN NAME MX_L2_COLONIA — Path

85% `colonia[a-z_]*` `nom(bre)?_?colonia` `fraccionamiento` `fracc` `barrio` `asentamiento` `d_?asenta` `nom_?asentamiento` `tipo_?asentamiento` `unidad_?habitacional` `conjunto_?habitacional` `ageb` `manzana_?inegi`

HOW IT IS MASKED

Replaced by a common colonia name (`Centro`, `Del Valle`, `Las Flores`).

`MX_COLONIA` SECURE LOOKUP

Replaces the value with one of the 60 values in `mx-colonias.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Santa María la Ribera	→	**Las Flores**

8.10 Postal code

MX_L2_CODIGO_POSTAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Five digits: the first two are the state or Mexico City borough. Also the fiscal address of CFDI invoices.

HOW IT IS FOUND

COLUMN NAME MX_L2_CODIGO_POSTAL — Path

90% `cod(igo)?_?postal` `cp` `c_?p` `zip(_?code)?` `postal_?code` `codpostal` `d_?codigo` `domicilio_?fiscal(_?receptor)?` `lugar_?expedicion` `cp_?(fiscal|domicilio|receptor|emisor)`

VALUE FORMAT MX_L2_CODIGO_POSTAL — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{5})`	20%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The first three digits stay and the last two become `00` (`06760` → `06700`).

`MX_CODIGO_POSTAL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
06760	→	**06700**

8.11 Nationality

MX_L2_NACIONALIDAD

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. A foreign nationality is rare in most tables, and rarity identifies.

HOW IT IS FOUND

COLUMN NAME MX_L2_NACIONALIDAD — Path

80% `nacionalidad` `nationality` `pais_?(de_?)?(nacimiento|origen)` `ciudadania` `citizenship` `country_?of_?birth` `extranjero`

VALUE FORMAT MX_L2_NACIONALIDAD — Values

PATTERN	STRENGTH	NOTES
One of 50 known values, ignoring case — Mexicana, Estadounidense, Guatemalteca, Hondureña, Salvadoreña, Venezolana, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by a nationality from a list of the most frequent in Mexico.

`MX_NACIONALIDAD` SECURE LOOKUP

Replaces the value with one of the 20 values in `mx-nacionalidades.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Guatemalteca	→	**Hondureña**

8.12 Marital status

MX_L2_ESTADO_CIVIL

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Single, married, free union, separated, divorced, widowed.

HOW IT IS FOUND

COLUMN NAME MX_L2_ESTADO_CIVIL — Path

85% `estado_?civil` `edo_?civil` `est_?civil` `ecivil` `situacion_?conyugal` `marital_?status` `civil_?status`

VALUE FORMAT MX_L2_ESTADO_CIVIL — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — soltero, soltera, casado, casada, unión libre, union libre, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another marital status.

`MX_ESTADO_CIVIL` SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Unión libre	→	**Divorciado**

8.13 Occupation

MX_L2_OCUPACION

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

Occupation, profession or position. A rare position identifies on its own.

HOW IT IS FOUND

COLUMN NAME MX_L2_OCUPACION — Path

80% `ocupaci[oó]n` `profesi[oó]n` `oficio` `puesto(_?(trabajo|laboral|actual))?` *(except when followed by* *`votacion`*, *`venta`*, *`trabajo_?id`*) `cargo` *(except when followed by list E8)* `job_?title` `occupation` `actividad_?(laboral|economica_?persona)` `categoria_?laboral`

HOW IT IS MASKED

Replaced by one of 40 common occupations.

`MX_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 40 values in `mx-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Gerente Regional Zona Sierra Tarahumara	→	**Repartidor**

8.14 Employer

MX_L2_EMPLEADOR

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

Employer name or workplace.

HOW IT IS FOUND

COLUMN NAME — MX_L2_EMPLEADOR — Path

80% `empleador` `patron` *(except when followed by* `busqueda`, `regex`, `expresion`*)* `nombre_?patron` `razon_?social_?(patron|empleador)` `registro_?patronal_?nombre` `empresa_?(empleadora|trabajo|laboral)` `lugar_?(de_?)?trabajo` `centro_?(de_?)?trabajo` `employer` `dependencia_?laboral`

HOW IT IS MASKED

Replaced by a fictitious Mexican company.

`MX_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 25 values in `mx-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Petróleos Mexicanos	→	**Ayuntamiento de Villa Nueva**

8.15 Schooling

MX_L2_ESCOLARIDAD

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Highest level of schooling, in INEGI's categories.

HOW IT IS FOUND

COLUMN NAME — MX_L2_ESCOLARIDAD — Path

80% `escolaridad` `nivel_?(educativo|educacional|escolar|de_?estudios|academico)` `grado_?(de_?)?estudios` `grado_?academico` `ultimo_?grado` `education_?level` `anos_?(de_?)?escolaridad`

VALUE FORMAT — MX_L2_ESCOLARIDAD — Values

PATTERN	STRENGTH	NOTES
One of 23 known values, ignoring case — Sin escolaridad, Preescolar, Primaria incompleta, Primaria completa, Secundaria incompleta, Secundaria completa, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another level of the same scale.

`MX_ESCOLARIDAD` SECURE LOOKUP

Replaces the value with one of the 12 values in `mx-escolaridad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Secundaria completa	→	**Preparatoria o bachillerato**

8.16 School

MX_L2_ESCUELA

COLUMN NAME · SECURE LOOKUP

WHAT IT IS

Name of a school, high school or university.

HOW IT IS FOUND

> **COLUMN NAME** MX_L2_ESCUELA — Path
>
> 75% `escuela` `colegio` `plantel` `nombre_?(escuela|plantel|colegio|institucion_?educativa)` `institucion_?educativa` `universidad` `preparatoria` `secundaria` `primaria` `bachillerato` `school(_?name)?` `jardin_?de_?ninos` `guarderia` `estancia_?infantil`

HOW IT IS MASKED

Replaced by a generic school name.

`MX_ESCUELA` SECURE LOOKUP

Replaces the value with one of the 15 values in `mx-escuelas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Instituto Cultural Tampico	→	**Universidad Autónoma del Centro**

8.17 School code (CCT)

MX_L2_CCT

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The Clave de Centro de Trabajo of a school: state, type, number and a letter (`09DPR1234X`).

HOW IT IS FOUND

> **COLUMN NAME** MX_L2_CCT — Path
>
> 85% `cct` `clave_?(de_?)?(centro_?de_?trabajo|escuela|plantel)` `cve_?(cct|escuela|plantel)` `centro_?de_?trabajo_?clave`

> **VALUE FORMAT** MX_L2_CCT — Regex
>
PATTERN	STRENGTH	NOTES
`0*(?:\d{2}[A-Z]{3}\d{4}[A-Z])`	90%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping the format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
09DPR1234X	→	**04KMH7080R**

8.18 Dependents and children

MX_L2_DEPENDIENTES

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Number of economic dependents, children or household members.

HOW IT IS FOUND

COLUMN NAME MX_L2_DEPENDIENTES – Path

80% `dependientes(_?economicos)?` `n(o|um|ro)?_?dependientes` `num_?hijos` `n(o|um|ro)?_?hijos` `cant_?hijos` `hijos` `integrantes_?(del_?)?(hogar|familia)` `n(o|um|ro)_?integrantes` `tamano_?(del_?)?hogar` `personas_?(en_?)?(el_?)?hogar` `hijos_?nacidos_?vivos`

DATA TYPE MX_L2_DEPENDIENTES – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

Values up to 5 stay; larger ones become 5, because large households are rare.

`MX_CANTIDAD_ACOTADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

PART 9

Sensitive data

The categories of article 2, section VI — ethnic origin, health, genetic information, beliefs, political opinions, sexual preference — together with gender identity, sexual life, biometrics and union membership. A categorical value is replaced by another of the same category, so the column keeps a realistic content; where the values share no vocabulary, they are suppressed.

9.1 Ethnic origin

MX_L3_ETNIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Indigenous people, Afro-Mexican self-identification or ethnic group. Named first in the sensitive data of article 2.

HOW IT IS FOUND

COLUMN NAME MX_L3_ETNIA – Path

90% `etnia` `[eé]tnico` `origen_?[eé]tnico` `grupo_?[eé]tnico` `pueblo_?(indigena|originario|orig)` `autoadscripcion(_?(indigena|afromexicana|afro))?` `se_?considera_?(indigena|afromexican[oa]|afro)` `indigena` `ind[ií]gena` `afromexican[oa]` `afrodescendiente` `afro` `raza` `race` `ethnicity` `ethnic_?group` `comunidad_?indigena` `pertenencia_?(etnica|indigena)`

VALUE FORMAT MX_L3_ETNIA – Values

PATTERN	STRENGTH	NOTES
One of 87 known values, ignoring case — Nahua, Maya, Zapoteco, Mixteco, Otomí, Totonaco, …	90%	
One of 7 known values, ignoring case — s, n, sí, no, y, 0, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A yes/no flag stays a flag; a people becomes another from a list of the most numerous indigenous peoples and the Afro-Mexican people, including unlisted ones such as `Kumiai`.

`MX_PUEBLO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PUEBLO_LISTA`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_PUEBLO_LISTA` SECURE LOOKUP

Replaces the value with one of the 31 values in `mx-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Kumiai	→	**Tlapaneco**
S	→	**S**

9.2 Indigenous language

MX_L3_LENGUA_INDIGENA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Whether a person speaks an indigenous language, and which. It reveals ethnic origin as surely as self-identification, and INEGI asks it in every census.

HOW IT IS FOUND

COLUMN NAME MX_L3_LENGUA_INDIGENA – Path

90% `lengua(_?(indigena|materna|originaria))?` `habla_?(lengua_?)?(indigena|originaria)` `hli` `hablante_?(de_?)?lengua_?indigena` `idioma_?(indigena|materno|originario)` `lengua_?que_?habla` `language_?indigenous` `native_?language`

VALUE FORMAT MX_L3_LENGUA_INDIGENA – Values

PATTERN	STRENGTH	NOTES
One of 46 known values, ignoring case — Náhuatl, Maya, Tseltal, Tsotsil, Mixteco, Zapoteco, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A flag stays a flag; a language becomes another from a list of the most spoken.

`MX_LENGUA_INDIGENA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_LENGUA_INDIGENA_LISTA`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_LENGUA_INDIGENA_LISTA` SECURE LOOKUP

Replaces the value with one of the 27 values in `mx-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Chocholteco	→	**Cora**

9.3 Diagnosis

MX_L3_SALUD_DIAGNOSTICO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Diagnoses, ICD-10 codes, conditions, allergies and pathological history.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_DIAGNOSTICO – Path

85% `diagn[oó]stico[a-z_]*` `diag` `dx` `cie_?10` `cie_?11` `cod(igo)?_?cie` `cie` `icd_?10` `icd` `patolog[ií]a[a-z_]*` `padecimiento[a-z_]*` `enfermedad(es)?[a-z_]*` `morbilidad` `condicion_?(medica|de_?salud|cronica)` `problema_?(de_?)?salud` `impresion_?diagnostica` `causa_?(incapacidad|muerte|defuncion|hospitalizacion|consulta)` `motivo_?(de_?)?(consulta|hospitalizacion|incapacidad)` `comorbilidad(es)?` `antecedentes_?(medicos|patologicos|personales_?patologicos|heredofamiliares|clinicos)` `alergias?` `enfermedad_?preexistente` `preexistencias?` `enfermedad_?cronica` `riesgo_?de_?trabajo`

VALUE FORMAT MX_L3_SALUD_DIAGNOSTICO – Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

An ICD-10 code becomes a common code in the same format (`F32.9` → `J45.9`), a description a common diagnosis. The mapping hides the sensitive conditions — HIV, mental health, addictions — among ordinary ones.

`MX_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_DIAGNOSTICO_TEXTO` .

> `MX_CIE10_DECIMAL` SECURE LOOKUP
>
> Replaces the value with one of the 33 values in `mx-cie10-decimal.txt` , chosen by a keyed hash.
>
> `MX_CIE10` SECURE LOOKUP
>
> Replaces the value with one of the 37 values in `mx-cie10.txt` , chosen by a keyed hash.
>
> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_DIAGNOSTICO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 30 values in `mx-diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F32.9	→	**J02.9**
Depresión mayor	→	**Tendinitis**

9.4 Medication

MX_L3_SALUD_MEDICAMENTO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Prescribed medicines. An antiretroviral or an antipsychotic reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_MEDICAMENTO – Path

85% `medicamentos?` `f[aá]rmacos?` `sustancia_?activa` `principio_?activo` `prescripci[oó]n` `receta(_?medica)?` `tratamiento(_?farmacologico)?` `medication` `drug(_?name)?` `posologia` `clave_?cuadro_?basico` `cuadro_?basico`

VALUE FORMAT MX_L3_SALUD_MEDICAMENTO – Values

PATTERN	STRENGTH	NOTES
One of 54 known values, ignoring case — Paracetamol, Ibuprofeno, Naproxeno, Metamizol, Ketorolaco, Diclofenaco, …	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by a common medicine.

`MX_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_MEDICAMENTO_LISTA`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_MEDICAMENTO_LISTA` SECURE LOOKUP

Replaces the value with one of the 26 values in `mx-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Sertralina 50 mg	→	**Bezafibrato**

9.5 Health record identifiers

MX_L3_SALUD_IDENTIFICADOR

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Clinical file numbers (NOM-004-SSA3-2012), episode, prescription, bed and disability certificate numbers.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_IDENTIFICADOR — Path

85% `expediente_?clinico` `n(o|um|ro|umero)_?expediente(_?clinico)?` `historia_?clinica` `n(o|um|ro)_?historia` `nhc` `n(o|um|ro)_?episodio` `folio_?(atencion|urgencias|receta|incapacidad|certificado_?(de_?)?defuncion)` `n(o|um|ro)_?incapacidad` `certificado_?(de_?)?incapacidad` `serie_?folio_?incapacidad` `n(o|um|ro)_?(de_?)?cama` `n(o|um|ro)_?interconsulta` `n(o|um|ro)_?(de_?)?receta` `agregado_?medico` `n(o|um|ro)_?biopsia` `medical_?record_?number` `mrn`

55% `expediente` `episodio` `cama`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
EXP-2024-00123	→	**IRH-7843-85225**

9.6 Clinical notes

MX_L3_SALUD_TEXTO_CLINICO

COLUMN NAME · DATA TYPE · FREE TEXT REDACTION

WHAT IT IS

Medical, progress, admission and discharge notes, current illness, physical examination — free text where names and CURPs appear.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_TEXTO_CLINICO — Path

85% `nota_?(medica|de_?evolucion|evolucion|de_?ingreso|ingreso|de_?egreso|egreso|de_?urgencias|urgencias|postoperatoria|preoperatoria|de_?enfermeria|clinica)s?` `notas?_?clinicas?` `padecimiento_?actual` `interrogatorio` `exploracion_?fisica` `evoluci[oó]n(_?(medica|clinica))?` `epicrisis` `indicaciones(_?medicas)?` `resumen_?clinico` `resumen_?(de_?)?egreso` `historia_?(de_?la_?)?enfermedad` `plan_?(de_?)?tratamiento` `pronostico` `hallazgos` `interpretacion` `clinical_?notes?` `progress_?notes?`

DATA TYPE MX_L3_SALUD_TEXTO_CLINICO — Type

Accepts text (length 30 or more); any other type rules the data class out.

HOW IT IS MASKED

The same free text redaction as other text: identifiers become `[DATO]`, names `[NOMBRE]`. The clinical content stays.

`MX_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DATO]`, and the 1,436 terms of `mx-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Paciente López, CURP HEGA850720MDFRRL04, acude por cefalea.`	→	**`Paciente [NOMBRE], CURP [DATO], acude por cefalea.`**

9.7 Test results

MX_L3_SALUD_RESULTADO_EXAMEN

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Laboratory and imaging results: HIV, viral load, glucose, HbA1c, pregnancy and drug tests.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_RESULTADO_EXAMEN — Path

80% `resultado_?(estudio|examen|laboratorio|lab|prueba|pcr|antigeno|biopsia|imagen|vih|covid|papanicolaou|mastografia)` `estudios?_?(de_?)?laboratorio` `vih` `hiv` `carga_?viral` `cd4` `glucosa` `glicemia` `hemoglobina(_?glucosilada)?` `hba1c` `colesterol` `trigliceridos` `presion_?arterial` `tension_?arterial` `imc` `prueba_?(covid|embarazo|vih|antidoping|toxicologica)` `antidoping` `lab_?result`

50% `resultado` `estudio`

HOW IT IS MASKED

Character by character, keeping length and format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Reactivo	→	**`Quilqaju`**

9.8 Blood type

MX_L3_SALUD_GRUPO_SANGUINEO

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

ABO group and Rh factor.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `grupo_?sang` `tipo_?(de_?)?sangre` `tipo_?sanguineo` `factor_?rh` `rh` `blood_?type` `blood_?group`

VALUE FORMAT MX_L3_SALUD_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another blood type.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with Delphix and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

9.9 Disability

MX_L3_SALUD_DISCAPACIDAD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Type or degree of disability, in the categories of the 2020 census.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `tipo_?(de_?)?discapacidad` `grado_?(de_?)?discapacidad` `certificado_?(de_?)?discapacidad` `persona_?con_?discapacidad` `pcd` `invalidez` `porcentaje_?(de_?)?invalidez` `pension_?(de_?)?invalidez` `limitacion(_?(fisica|actividad))?` `disability` `dependencia_?funcional` `nee` `necesidades_?educativas_?especiales` `condicion_?mental`

VALUE FORMAT MX_L3_SALUD_DISCAPACIDAD — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Caminar subir o bajar, Ver aun usando lentes, Oír aun usando aparato auditivo, Hablar o comunicarse, Recordar o concentrarse, Bañarse vestirse o comer, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A flag stays a flag; a type becomes another census category.

`MX_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_DISCAPACIDAD_LISTA`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_DISCAPACIDAD_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `mx-discapacidad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Discapacidad psicosocial severa	→	**Oír, aun usando aparato auditivo**

9.10 Sexual and reproductive health

MX_L3_SALUD_SEXUAL_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, gestational age, legal interruption of pregnancy, contraception, fertility, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_SEXUAL_REPRODUCTIVA — Path

90% `embarazo` `embarazada` `gestaci[oó]n` `semanas_?(de_?)?gestacion` `edad_?gestacional` `fum` `fecha_?ultima_?menstruacion` `aborto` `ile` `ive` `interrupcion_?(legal_?|voluntaria_?)?(del_?)?embarazo` `anticonceptivos?` `metodo_?(de_?)?planificacion(_?familiar)?` `planificacion_?familiar` `fertilidad` `infertilidad` `reproduccion_?asistida` `gestas` `partos` `cesareas?` `puerperio` `its` `ets` `infeccion_?(de_?)?transmision_?sexual` `prep` `pregnan[a-z]*` `contracepti[a-z]*`

HOW IT IS MASKED

A flag stays a flag and a number gets other digits; anything else becomes `Sin información`.

`MX_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Embarazo de 12 semanas	→	**Sin información**
S	→	**S**

9.11 Mental health and addictions

MX_L3_SALUD_MENTAL_ADICCIONES

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Psychiatric and psychological care, disorders, suicide risk, substance use and treatment.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_MENTAL_ADICCIONES – Path

90% `salud_?mental` `psiquiatri[a-z]*` `psicologi[a-z]*` `trastorno[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z]*` `autolesi[oó]n` `adicci[oó]n(es)?` `consumo_?(de_?)?(drogas|alcohol|sustancias|tabaco)` `alcoholismo` `farmacodependencia` `drogadiccion` `toxicomania` `dependencia_?(alcohol|drogas|sustancias)` `cij` `conadic` `tratamiento_?(adicciones|drogas|alcohol)` `anexo_?(rehabilitacion)?` `mental_?health` `substance_?(use|abuse)`

HOW IT IS MASKED

Suppressed to `Sin información`; flags and codes keep their shape.

`MX_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno bipolar	→	**Sin información**

9.12 Biometric data

MX_L3_BIOMETRICO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

Fingerprint and facial templates, iris, voice and digitized signatures stored as text.

HOW IT IS FOUND

COLUMN NAME MX_L3_BIOMETRICO — Path

90% `huella(_?(dactilar|digital))?` `huellas` `dactilar` `biometri[a-z_]*` `template_?(facial|biometrico|huella)` `rostro` `reconocimiento_?facial` `facial_?(template|id)` `iris` `retina` `voz_?(huella|biometrica)` `firma_?(digitalizada|biometrica|autografa_?digital)` `fingerprint` `face_?(id|template|encoding)` `palm_?print` `minucias`

DATA TYPE MX_L3_BIOMETRICO — Type

Accepts text; any other type rules the data class out.

HOW IT IS MASKED

Every character becomes `X`. Binary columns cannot be masked by the policy; see *Limits*.

`MX_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	**XXXXXXXXXXXX**

9.13 Genetic information

MX_L3_INFORMACION_GENETICA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

DNA profiles, genotypes, mutations, genetic screening and paternity tests — named by article 2.

HOW IT IS FOUND

COLUMN NAME MX_L3_INFORMACION_GENETICA — Path

90% `adn` `dna` `genoma` `genotipo` `genetic[a-z_]*` `gen[eé]tic[ao]` `informacion_?genetica` `secuencia_?genetica` `marcador_?genetico` `perfil_?(genetico|biologico)` `mutacion(_?genetica)?` `snp` `brca` `haplotipo` `cariotipo` `tamiz_?(genetico|metabolico)` `prueba_?(de_?)?paternidad`

VALUE FORMAT MX_L3_INFORMACION_GENETICA — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character becomes `X`.

`MX_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXXXX

9.14 Sexual preference

MX_L3_PREFERENCIA_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Sexual orientation — *preferencia sexual* in the words of the law.

HOW IT IS FOUND

COLUMN NAME `MX_L3_PREFERENCIA_SEXUAL – Path`

95% `preferencia_?sexual` `orientaci[oó]n_?sexual` `sexual_?(orientation|preference)` `orient_?sexual` `pref_?sexual`

VALUE FORMAT `MX_L3_PREFERENCIA_SEXUAL – Values`

PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — Heterosexual, Homosexual, Lesbiana, Gay, Bisexual, Pansexual, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another value of the same scale.

`MX_PREFERENCIA_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PREFERENCIA_SEXUAL_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_PREFERENCIA_SEXUAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 9 values in `mx-preferencia-sexual.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Bisexual	→	**Lesbiana**

9.15 Gender identity

MX_L3_IDENTIDAD_GENERO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Self-perceived gender identity and legal gender recognition.

HOW IT IS FOUND

COLUMN NAME MX_L3_IDENTIDAD_GENERO — Path

95% `identidad_?(de_?)?g[eé]nero` `gender_?identity` `g[eé]nero_?(identidad|social|autopercibido)` `transg[eé]nero` `transexual` `persona_?trans` `reconocimiento_?(de_?)?identidad` `cambio_?(de_?)?(sexo|genero)` `pronombres?`

VALUE FORMAT MX_L3_IDENTIDAD_GENERO — Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — Mujer, Hombre, Mujer trans, Hombre trans, No binario, Género fluido, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another value of the same scale.

`MX_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_IDENTIDAD_GENERO_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `mx-identidad-genero.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Hombre trans	→	**No binario**

9.16 Sexual life

MX_L3_VIDA_SEXUAL

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behavior and history.

HOW IT IS FOUND

COLUMN NAME MX_L3_VIDA_SEXUAL — Path

90% `vida_?sexual` `conducta_?sexual` `actividad_?sexual` `parejas?_?sexuales?` `practicas_?sexuales` `inicio_?(de_?)?vida_?sexual` `ivsa` `sexual_?(activity|behavior|history)` `historia_?sexual` `comportamiento_?sexual`

HOW IT IS MASKED

Suppressed to `Sin información`.

`MX_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Activa	→	**Sin información**

9.17 Religion

MX_L3_RELIGION

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Religious affiliation — religious beliefs are named by article 2.

HOW IT IS FOUND

COLUMN NAME MX_L3_RELIGION — Path

95% `religi[oó]n[a-z_]*` `credo` `culto` `iglesia` `creencia_?religiosa` `confesion_?religiosa` `denominacion_?religiosa` `asociacion_?religiosa` `religious_?affiliation` `comunidad_?religiosa`

VALUE FORMAT MX_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 37 known values, ignoring case — Católica, Protestante o cristiana evangélica, Pentecostal, Testigo de Jehová, Adventista del Séptimo Día, Iglesia de Jesucristo de los Santos de los Últimos Días, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by a religion group of the 2020 census, including unlisted churches such as `Luz del Mundo`.

`MX_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_RELIGION_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_RELIGION_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 13 values in `mx-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Luz del Mundo`	→	**Católica**

9.18 Philosophical and moral beliefs

MX_L3_CREENCIA_FILOSOFICA_MORAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Convictions, conscientious objection, ethical positions — the article 2 wording for beliefs that are not religious.

HOW IT IS FOUND

COLUMN NAME MX_L3_CREENCIA_FILOSOFICA_MORAL — Path

90% `creencias?_?(filosoficas?|morales?|personales)` `convicci[oó]n(es)?(_?(filosoficas?|morales?|eticas?|personales))?` `objecion_?(de_?)?conciencia` `postura_?(etica|moral)` `valores_?personales` `filosofia_?(de_?)?vida` `cosmovision`

HOW IT IS MASKED

Suppressed to `Sin información`.

`MX_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Rechaza transfusiones	→	**Sin información**

9.19 Political opinions

MX_L3_OPINION_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Ideology, political position, voting intention and electoral preference.

HOW IT IS FOUND

COLUMN NAME MX_L3_OPINION_POLITICA — Path

90% `opini[oó]n(es)?_?pol[ií]ticas?` `ideolog[ií]a(_?politica)?` `posicion_?politica` `postura_?politica` `tendencia_?politica` `orientacion_?politica` `preferencia_?(politica|electoral|partidista)` `intencion_?(de_?)?voto` `simpatia_?(politica|partidista)` `political_?(view|orientation|opinion)`

VALUE FORMAT MX_L3_OPINION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Izquierda, Centro izquierda, Centro, Centro derecha, Derecha, Sin preferencia, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another position of the same scale.

`MX_OPINION_POLITICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_OPINION_POLITICA_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_OPINION_POLITICA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `mx-opiniones-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Centro derecha`	→	**`Centro`**

9.20 Party membership

MX_L3_AFILIACION_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Party membership or sympathy. A party list reveals political opinion.

HOW IT IS FOUND

COLUMN NAME MX_L3_AFILIACION_POLITICA — Path

95% `partido(_?pol[ií]tico)?` `militancia` `militante` `afiliaci[oó]n_?(politica|partidista|partido)` `afiliado_?(a_?)?partido` `padron_?(de_?)?militantes` `political_?party` `party_?affiliation` `coalici[oó]n` `simpatizante`

VALUE FORMAT MX_L3_AFILIACION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 29 known values, ignoring case — Morena, Partido Acción Nacional, Partido Revolucionario Institucional, Partido del Trabajo, Partido Verde Ecologista de México, Movimiento Ciudadano, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the national parties registered in 2026, including those that lost registration (`PRD`).

`MX_PARTIDO_POLITICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PARTIDO_POLITICO_LISTA` .

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_PARTIDO_POLITICO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `mx-partidos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Partido de la Revolución Democrática`	→	**`Somos México`**

9.21 Union membership

MX_L3_AFILIACION_SINDICAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Union membership, union dues, section and unionized or trust worker status.

HOW IT IS FOUND

COLUMN NAME MX_L3_AFILIACION_SINDICAL — Path

95% `sindicato[a-z_]*` `sindical` `sindicalizado` `afiliaci[oó]n_?sindical` `agremiado` `cuota_?sindical` `delegado_?sindical` `seccion_?sindical` `trabajador_?(de_?)?confianza` `tipo_?(de_?)?trabajador_?(sindicalizado|confianza)` `union_?member(ship)?` `trade_?union` `contrato_?colectivo`

VALUE FORMAT MX_L3_AFILIACION_SINDICAL — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — SNTE, CNTE, STPRM, SUTERM, CTM, CROC, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A flag stays a flag; anything else becomes `Sin información`.

`MX_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
SNTE Sección 22	→	**Sin información**
S	→	**S**

PART 10

Financial and patrimonial data

Article 7 requires express consent for financial and patrimonial data — a regime of its own, between ordinary and sensitive data, that GDPR-based templates do not have. It covers more than bank accounts: a credit bureau record, a daily wage, a housing credit, a social program or a tax regime tell as much about a person's economic situation as an income. Categories are replaced within their own notation; amounts are mapped into a plausible range with no link to the real value.

10.1 Credit bureau record

MX_FIN_BURO_CREDITO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Buró de Crédito and Círculo de Crédito data: payment behaviour codes (MOP), score, arrears status, write-offs.

HOW IT IS FOUND

COLUMN NAME — MX_FIN_BURO_CREDITO — Path

90% `buro(_?(de_?)?credito)?` `bur[oó]` `circulo_?(de_?)?credito` `historial_?crediticio` `score(_?(buro|crediticio|credito|riesgo|bc))?` `bc_?score` `puntaje_?(crediticio|buro|riesgo|credito)` `calificacion_?(crediticia|buro|riesgo)` `mop` `forma_?de_?pago_?buro` `clave_?(de_?)?observacion` `morosidad` `moroso` `morosa` `atraso` `dias_?(de_?)?atraso` `dias_?(de_?)?mora` `cartera_?vencida` `quebranto` `estatus_?(credito|crediticio|cartera)` `estado_?(de_?)?(cuenta_?)?(credito|crediticio|cartera)` `credit_?score` `delinquen[a-z]*` `reestructura` `insolvencia` `concurso_?mercantil`

HOW IT IS MASKED

A MOP code becomes another MOP code, a 3-digit score other digits, a status another status.

`MX_BURO_CREDITO` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `MX_ESTADO_CREDITICIO` .

`MX_MOP` SECURE LOOKUP

Replaces the value with one of the 9 values in `mx-mop.txt` , chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

`MX_ESTADO_CREDITICIO` SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-estado-crediticio.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
MOP 05	→	**MOP 04**
650	→	**807**

10.2 Debt amount

MX_FIN_MONTO_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Outstanding balance, amount owed, credit limit, minimum payment.

HOW IT IS FOUND

COLUMN NAME MX_FIN_MONTO_DEUDA – Path

85% `monto_?(deuda|adeudo|adeudado|vencido|quebranto|credito|prestamo|financiado)` `adeudo(_?(total|vigente|vencido))?` `deuda(_?(total|vigente|vencida))?` `saldo_?(deudor|insoluto|vencido|credito|prestamo|tarjeta|adeudo)` `limite_?(de_?)?credito` `linea_?(de_?)?credito` `pago_?minimo` `debt(_?amount)?` `outstanding_?balance`

DATA TYPE MX_FIN_MONTO_DEUDA – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
85000	→	**78007**

10.3 Monthly income

MX_FIN_INGRESO_MENSUAL

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Salary, perceptions, net pay, household income.

HOW IT IS FOUND

COLUMN NAME MX_FIN_INGRESO_MENSUAL – Path

85% `sueldo[a-z_]*` *(except when followed by* `diario`, `base_?cotizacion`*)* `salario[a-z_]*` *(except when followed by* `diario`, `base_?(de_?)?cotizacion`, `minimo_?(general|profesional|zona)`*)* `remuneraci[oó]n[a-z_]*` `ingreso_?(mensual|neto|bruto|familiar|del_?hogar|hogar|per_?capita|total|promedio|declarado|laboral|comprobable|anual)` `ingresos(_?[a-z]+)?` `percepciones?(_?(totales|gravadas|exentas))?` `total_?percepciones` `neto_?a_?pagar` `nomina_?(neta|bruta)` `gasto_?(mensual|familiar)` `capacidad_?(de_?)?pago` `salary` `wage` `income` `gross_?pay` `net_?pay`

DATA TYPE MX_FIN_INGRESO_MENSUAL – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
18500	→	**10882**

10.4 Daily wage (SDI, SBC)

MX_FIN_SALARIO_DIARIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

The integrated daily wage and the contribution base wage used by the IMSS — the way Mexican payrolls store pay.

HOW IT IS FOUND

COLUMN NAME MX_FIN_SALARIO_DIARIO – Path

90% `sdi` `sbc` `salario_?diario(_?integrado)?` `sueldo_?diario` `salario_?base_?(de_?)?cotizacion` `sal_?(diario|base|integrado)` `sd_?integrado` `cuota_?diaria` `daily_?wage`

DATA TYPE MX_FIN_SALARIO_DIARIO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
452	→	**274**

10.5 Assets

MX_FIN_PATRIMONIO

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

Net worth, cadastral and appraisal values, investments and savings.

HOW IT IS FOUND

COLUMN NAME MX_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|total))?` `valor_?(catastral|comercial|avaluo|inmueble|propiedad|vivienda|vehiculo|de_?la_?garantia)` `avaluo` `bienes_?(inmuebles|muebles)` `valor_?bienes` `activos_?(personales|totales)` `saldo_?(inversion|ahorro|cuenta)` `monto_?(inversion|ahorro)` `net_?worth` `assets`

DATA TYPE MX_FIN_PATRIMONIO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
1850000	→	**4398071**

10.6 AFORE

MX_FIN_AFORE

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The retirement fund administrator, and the pension regime.

HOW IT IS FOUND

COLUMN NAME MX_FIN_AFORE – Path

95% `afore` `nombre_?afore` `cve_?afore` `clave_?afore` `administradora_?(de_?)?fondos_?(para_?el_?)?retiro` `sar` `siefore` `cuenta_?individual_?(afore|retiro)` `regimen_?(de_?)?pension(_?(ley_?73|ley_?97))?` `pension_?fund`

VALUE FORMAT MX_FIN_AFORE — Values

PATTERN	STRENGTH	NOTES
One of 27 known values, ignoring case — Afore Azteca, Afore Banamex, Afore Coppel, Afore Inbursa, Afore Invercap, PensionISSSTE, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the ten AFOREs authorized by CONSAR in 2026.

`MX_AFORE` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_AFORE_LISTA` .

> `MX_BANDERA` **REGEX DECOMPOSE**
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.
>
> `MX_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_AFORE_LISTA` **SECURE LOOKUP**
>
> Replaces the value with one of the 11 values in `mx-afores.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Afore Coppel`	→	**`Afore Principal`**

10.7 Retirement and housing savings

MX_FIN_SALDO_RETIRO

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Balances of the retirement and housing subaccounts, voluntary savings, pension amounts.

HOW IT IS FOUND

COLUMN NAME MX_FIN_SALDO_RETIRO — Path

90% `saldo_?(afore|retiro|rcv|subcuenta|vivienda|infonavit|fovissste|sar|cuenta_?individual|voluntario)` `subcuenta_?(de_?)?(retiro|vivienda|rcv)` `aportaciones?_?(voluntarias|patronales|infonavit)` `monto_?pension` `pension_?(mensual|monto)` `retiro_?cesantia_?vejez` `rcv` `ahorro_?voluntario` `retirement_?balance`

DATA TYPE MX_FIN_SALDO_RETIRO — Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
385000	→	797256

10.8 Housing credit

MX_FIN_CREDITO_VIVIENDA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Infonavit, Fovissste, Cofinavit or bank mortgage, and payroll discount notices.

HOW IT IS FOUND

COLUMN NAME MX_FIN_CREDITO_VIVIENDA – Path

90% `tipo_?(de_?)?credito_?(vivienda|hipotecario)` `credito_?(vivienda|hipotecario)` `hipoteca` `infonavit` `fovissste` `cofinavit` `mejoravit` `descuento_?infonavit` `factor_?(de_?)?descuento` `aviso_?(de_?)?retencion` `mortgage`

VALUE FORMAT MX_FIN_CREDITO_VIVIENDA – Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Crédito Infonavit, Crédito Fovissste, Cofinavit, Crédito hipotecario bancario, Crédito de otra institución, Sin crédito de vivienda, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another type of housing credit.

`MX_CREDITO_VIVIENDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_CREDITO_VIVIENDA_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_CREDITO_VIVIENDA_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-credito-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Mejoravit	→	**Cofinavit**

10.9 Social security coverage

MX_FIN_SEGURIDAD_SOCIAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Derechohabiencia: IMSS, ISSSTE, IMSS-Bienestar, Pemex, armed forces, private insurance, none. It reveals formal or informal work.

HOW IT IS FOUND

COLUMN NAME MX_FIN_SEGURIDAD_SOCIAL – Path

90% `derechohabiencia` `derecho_?habiencia` `afiliacion_?(a_?)?(servicios_?de_?salud|seguridad_?social)` `institucion_?(de_?)?(seguridad_?social|salud)` `servicio_?medico` `seguridad_?social` `regimen_?(de_?)?seguridad_?social` `seguro_?(medico|de_?salud|popular)` `imss_?bienestar` `insabi` `umf` `unidad_?medica_?familiar` `health_?insurance`

VALUE FORMAT MX_FIN_SEGURIDAD_SOCIAL – Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — IMSS, ISSSTE, ISSSTE estatal, IMSS-Bienestar, Pemex, Sedena, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another institution of the same list.

`MX_SEGURIDAD_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SEGURIDAD_SOCIAL_LISTA`.

`MX_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_SEGURIDAD_SOCIAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-seguridad-social.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
ISSSTE	→	**ISSSTE estatal**

10.10 Social programs

MX_FIN_PROGRAMA_SOCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Beneficiaries of the Programas para el Bienestar and their predecessors: pensions, scholarships, Sembrando Vida, Jóvenes Construyendo el Futuro.

HOW IT IS FOUND

COLUMN NAME — MX_FIN_PROGRAMA_SOCIAL — Path

90% `programa_?(social|del_?bienestar|bienestar|federal|de_?apoyo|gobierno)` `programas_?sociales` `beneficiario_?(de_?)?(programa|pension|beca|apoyo)` `apoyo_?(social|gubernamental|bienestar|economico)` `pension_?(bienestar|adultos_?mayores|mujeres|discapacidad|65)` `beca_?(bienestar|benito_?juarez|rita_?cetina)` `becas?_?bienestar` `jovenes_?construyendo` `jcf` `sembrando_?vida` `prospera` `oportunidades` `progresa` `padron_?(de_?)?beneficiarios` `tarjeta_?bienestar` `social_?program`

VALUE FORMAT — MX_FIN_PROGRAMA_SOCIAL — Values

PATTERN	STRENGTH	NOTES
One of 25 known values, ignoring case — Pensión para el Bienestar de las Personas Adultas Mayores, Pensión Mujeres Bienestar, Pensión para el Bienestar de las Personas con Discapacidad, Beca Universal Rita Cetina, Beca Universal Benito Juárez, Jóvenes Construyendo el Futuro, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A flag stays a flag; a program becomes another program of 2026.

`MX_PROGRAMA_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PROGRAMA_SOCIAL_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_PROGRAMA_SOCIAL_LISTA` SECURE LOOKUP

> Replaces the value with one of the 13 values in `mx-programas-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Prospera	→	**Jóvenes Escribiendo el Futuro**

10.11 Socioeconomic level

`MX_FIN_NIVEL_SOCIOECONOMICO`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

AMAI socioeconomic level (`A/B` to `E`), income decile or quintile, marginalization and poverty indicators.

HOW IT IS FOUND

> COLUMN NAME `MX_FIN_NIVEL_SOCIOECONOMICO` – Path
>
> **90%** `nse` `nivel_?socioeconomico` `nivel_?socio_?economico` `estrato(_?socioeconomico)?` `clase_?social` `decil(_?(de_?)?ingresos?)?` `quintil(_?(de_?)?ingresos?)?` `grado_?(de_?)?marginacion` `indice_?(de_?)?marginacion` `marginacion` `rezago_?social` `pobreza(_?(extrema|moderada|multidimensional))?` `carencias?_?sociales?` `vulnerabilidad(_?(por_?ingresos|social))?` `socioeconomic_?level`

> VALUE FORMAT `MX_FIN_NIVEL_SOCIOECONOMICO` – Values
>
PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — a b, ab, c, c, c-, d, …	40%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

An AMAI level becomes another, a quintile another quintile, a decile another decile.

`MX_NIVEL_SOCIOECONOMICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_NSE`.

> `MX_QUINTIL` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `mx-quintil.txt`, chosen by a keyed hash.
>
> `MX_DECIL_ALTO` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `mx-decil-alto.txt`, chosen by a keyed hash.
>
> `MX_DECIL` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `mx-decil.txt`, chosen by a keyed hash.
>
> `MX_NSE` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `mx-nse.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
C–	→	**E**
Decil 8	→	**Decil 10**

10.12 Housing tenure

MX_FIN_VIVIENDA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Whether the home is owned, being paid, rented, lent or in litigation, and its conditions.

HOW IT IS FOUND

COLUMN NAME — MX_FIN_VIVIENDA — Path

95% `tenencia_?(de_?)?(la_?)?vivienda` `tipo_?(de_?)?vivienda` `situacion_?(de_?la_?)?vivienda` `vivienda_?(propia|rentada|prestada)` `condicion_?(de_?)?(la_?)?vivienda` `material_?(de_?)?(la_?)?vivienda` `piso_?de_?tierra` `hacinamiento` `asentamiento_?irregular` `housing_?(type|tenure|status)`

VALUE FORMAT — MX_FIN_VIVIENDA — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Propia, Propia en proceso de pago, Rentada o alquilada, Prestada, Intestada o en litigio, Otra situación, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by another tenure of the census scale.

`MX_VIVIENDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_VIVIENDA_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_VIVIENDA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 6 values in `mx-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Asentamiento irregular`	→	**Propia**

10.13 Tax regime

MX_FIN_REGIMEN_FISCAL

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

The SAT tax regime of an individual (CFDI catalog `c_RegimenFiscal`): wages, rent, business activity, RESICO. It reveals the source of a person's income.

HOW IT IS FOUND

> COLUMN NAME MX_FIN_REGIMEN_FISCAL — Path
>
> 90% `regimen_?fiscal(_?receptor)?` `c_?regimen_?fiscal` `cve_?regimen` `clave_?regimen(_?fiscal)?` `regimen_?(sat|tributario)` `tax_?regime`

HOW IT IS MASKED

A code becomes another individual regime code, a description another description; `626 – ...` keeps both parts.

`MX_REGIMEN_FISCAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_REGIMEN_FISCAL_NOMBRE`.

> `MX_REGIMEN_FISCAL_CLAVE` SECURE LOOKUP
>
> Replaces the value with one of the 13 values in `mx-regimen-fiscal-clave.txt`, chosen by a keyed hash.
>
> `MX_REGIMEN_FISCAL_NOMBRE` SECURE LOOKUP
>
> Replaces the value with one of the 13 values in `mx-regimen-fiscal-nombre.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`626 – Régimen Simplificado de Confianza`	→	**`612 – Sin obligaciones fiscales`**

PART 11

Criminal records

Not named by the LFPDPPP, but among the data most likely to lead to discrimination, which is what article 2 describes as sensitive. They are handled with the same care.

11.1 Criminal records

MX_PENAL_ANTECEDENTES

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Criminal records, sentences, offenses, pretrial detention, arrest warrants.

HOW IT IS FOUND

COLUMN NAME — MX_PENAL_ANTECEDENTES — Path

95% `antecedentes(_?(penales|judiciales|policiacos|criminales|no_?penales))?` *(except when followed by list E9)* `carta_?(de_?)?no_?antecedentes` `constancia_?(de_?)?(no_?)?antecedentes` `sentencia(_?condenatoria)?` `sentenciad[oa]` `condena(do|da)?` `delitos?` `tipo_?(de_?)?delito` `reincidente` `reincidencia` `imputad[oa]` `vinculado_?a_?proceso` `vinculacion_?a_?proceso` `prision_?preventiva` `pena` `reclusion` `interno` `centro_?penitenciario` `cereso` `libertad_?condicional` `criminal_?record` `conviction` `offen[cs]e` `detenid[oa]` `orden_?de_?aprehension` `medida_?cautelar` `violencia_?familiar`

HOW IT IS MASKED

A flag stays a flag; anything else becomes a generic status.

`MX_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_ANTECEDENTES_LISTA`.

> `MX_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `MX_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `MX_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.
>
> `MX_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `MX_ANTECEDENTES_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 3 values in `mx-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Sentenciado por robo`	→	**`Sin información`**

11.2 Case numbers

MX_PENAL_CAUSA

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

Investigation folders, preliminary inquiries, criminal case and appeal numbers (`123/2024`).

HOW IT IS FOUND

COLUMN NAME MX_PENAL_CAUSA — Path

90% `carpeta_?(de_?)?investigacion` `n(o|um|ro)_?carpeta` `averiguacion_?previa` `n(o|um|ro)_?averiguacion` `causa_?penal` `n(o|um|ro|umero)_?(de_?)?causa` `expediente_?(judicial|penal)` `n(o|um|ro)_?expediente_?(judicial|penal)` `toca_?penal` `n(o|um|ro)_?toca` `amparo_?(n(o|um|ro))?` `n(o|um|ro)_?(de_?)?denuncia` `folio_?denuncia` `case_?number`

VALUE FORMAT MX_PENAL_CAUSA — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{2,6}(/[A-Z0-9\-]{1,12}){2,}/\d{2,6}[/\-]\d{2,4}`	80%	
`0*(?:\d{1,5}/\d{4})`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping the format.

`MX_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123/2024	→	**845/5120**

12

Check digits computed by the policy

Mexican applications validate their keys, and a masked key that fails validation breaks the test it was meant for. Two keys are covered by the plugin's own frameworks: the CLABE by Check Digit (weights 3, 7, 1, modulo 10), and the NSS by Payment Card, since its check digit is Luhn — the check of payment cards. The CURP and the RFC need more:

- **CURP** — every character counts, letters included (`0 – 9` , `A – N` → 10–23, `Ñ` 24, `O – Z` → 25–36), with weights 18 down to 2, modulo 10. Check Digit reads letters in base 36, where `0 – Z` are worth one less.
- **RFC** — the SAT table (`&` 24, space 37, `Ñ` 38), weights 13 down to 2, modulo 11, with 10 written `A` . A company RFC counts as if preceded by a space. Check Digit writes a result of 10 as `0` and does not accept `&` or `Ñ` .

For these two the policy computes the check digit itself. After the body is masked, a running sum travels through the value two characters at a time: a lookup table turns *sum + next two characters* into *those characters + new sum*, and the last table writes the check digit in place. Each table lists only what its positions can hold — digits for the date, letters for the names — so the CURP takes 8 steps and the RFC 6, each a Regex Decompose and a Data Cleansing file generated with the policy, in a single String Algorithm Chain.

Every masked CURP, RFC and NSS is valid, and the mapping stays one-to-one — a key cannot collide with another. The cost is paid per value, per step, not per algorithm configured. Measured with the plugin outside the engine, on a laptop, a CURP masks in about 11 µs, an RFC in about 9 and an NSS in about 3, against about 2 for a Character Mapping: some 90,000 CURPs per second per thread. Half of the CURP's cost is its body — the date, and the keyed lookups for sex and state; the check digit is the other half. An engine's throughput depends on its hardware and job settings.

13

Dates inside keys

CURP, RFC and the INE voter key carry the birth date as `YYMMDD` . Leaving it would leave the strongest quasi-identifier in the key; changing its digits freely would produce dates that do not exist.

The decade stays and the unit of the year is masked, as in a birth year column. The month goes through a one-to-one mapping of 1–12, the day through one of 1–28, 29–30 among themselves, and a 31st keeps a 31-day month. The result is always a real date, and two different dates never become the same.

The same algorithm masks the date in the three keys, so a person's CURP, RFC and voter key keep agreeing with each other. They do not agree with the birth date column, which moves by up to 60 days: no algorithm can see two columns at once.

14

Limits

- **Binary columns** — photos of INE credentials, fingerprint images, clinical PDFs stored in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **Keys and the columns they derive from.** The letters of a masked CURP or RFC no longer come from the masked name, and its date is not the masked birth date. Where an application recomputes the CURP

from the name, it will not match.

- **Inconvenient words.** RENAPO replaces some offensive letter combinations at the start of a CURP; a masked CURP may form one. It still passes the check digit.
- **Lowercase or formatted keys** — a CURP in lower case, an NSS with dashes — are masked character by character, without a valid check digit.
- **Municipalities** spelled in a way the list does not know pass unchanged. A name shared by a large and a small municipality stays as it is; the 5-digit code has no such ambiguity. A 3-digit municipality code without its state is not generalized.
- **Free text** is redacted word by word: a phone number written with spaces (`55 1234 5678`) is not found there, and a given name that is also a common word (`Luz` , `Paz` , `Rosa`) is redacted wherever it appears.
- **Minors** — a birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, colonia, postal code and municipality in separate columns are masked independently and no longer form a coherent address.
- **Plates and VINs** keep their format but not the state series or the VIN check digit.

15

Verification

Before publication the policy was checked outside Delphix:

- Every classifier configuration was reviewed against what Delphix accepts.
- Discovery was simulated on 151 columns with the whole policy at its assignment threshold — well named, badly named, and 26 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The algorithms, run with the Delphix algorithm plugin, masked 350 sample values and 228 placeholders such as `S/D` . Random CURPs, RFCs, NSS and CLABEs were checked for a valid check digit and a valid date, 150 of each for collisions, and pairs of CURP and RFC of the same person for agreement.

Every column was assigned as expected and every value masked as expected. Before using the policy on real data, run a discovery job and a masking job on a representative copy.

16

Sources

- Ley Federal de Protección de Datos Personales en Posesión de los Particulares — DOF 20 March 2025, last amendment DOF 14 November 2025 (Cámara de Diputados). The 2010 law, DOF 5 July 2010, for comparison.
- CURP structure and check digit — Registro Nacional de Población (RENAPO).
- RFC check digit — Servicio de Administración Tributaria (SAT). Tax regime catalog `c_RegimenFiscal` — SAT, CFDI 4.0.
- NSS structure — Instituto Mexicano del Seguro Social (IMSS). CLABE — Banco de México and the Asociación de Bancos de México.
- INE voter key — Instituto Nacional Electoral. National political parties, including the registration of Partido Paz and Somos México on 1 July 2026 — INE.

- Municipalities, geostatistical codes, coordinates and population — INEGI, Censo de Población y Vivienda 2020. Religion, disability, schooling and housing categories — the same census.
- Most frequent surnames — INE and RENAPO registers. Given names — INEGI and name frequency registers.
- Indigenous peoples — Instituto Nacional de los Pueblos Indígenas, Catálogo Nacional de Pueblos y Comunidades Indígenas y Afromexicanas (2024).
- AFOREs — Comisión Nacional del Sistema de Ahorro para el Retiro (CONSAR), 2026. Social programs — Programas para el Bienestar, Government of Mexico, 2026.
- Socioeconomic levels — Asociación Mexicana de Agencias de Inteligencia de Mercado y Opinión (AMAI).
- Ten-digit dialing — Instituto Federal de Telecomunicaciones, 3 August 2019. Postal codes — Correos de México (SEPOMEX). License plates — NOM-001-SCT-2-2016.

APPENDIX A

Algorithms

Every algorithm of the policy in alphabetical order, with its configuration. The one a data class names is the top of its tree; the others are building blocks.

MX_AFORE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_AFORE_LISTA`.

Used by: `MX_FIN_AFORE`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_AFORE_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_AFORE_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `mx-afores.txt`, chosen by a keyed hash.

Used by: `MX_AFORE`

CONFIGURATION

lookupFile	`mx-afores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_ANIO_NACIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `MX_CM_ALFANUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_ANTECEDENTES_LISTA`.

Used by: `MX_PENAL_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_ANTECEDENTES_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 3 values in `mx-antecedentes.txt`, chosen by a keyed hash.

Used by: `MX_ANTECEDENTES`

CONFIGURATION

lookupFile	`mx-antecedentes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_APELLIDO NAME

Replaces the name with one of the 337 names in `mx-apellidos.txt`.

Used by: `MX_APELLIDOS`, `MX_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	`mx-apellidos.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

MX_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_APELLIDO`, `MX_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`MX_APELLIDO`
`(\S+)\s+(\S+)`	`MX_APELLIDO` · `MX_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`MX_APELLIDO` · `MX_APELLIDO` · `MX_APELLIDO`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CATEGORIA_SUPRIMIDA`, `MX_PUEBLO`, `MX_LENGUA_INDIGENA`, `MX_DIAGNOSTICO`, `MX_MEDICAMENTO`, `MX_DISCAPACIDAD`, `MX_PREFERENCIA_SEXUAL`, `MX_IDENTIDAD_GENERO`, `MX_RELIGION`, `MX_OPINION_POLITICA`, `MX_PARTIDO_POLITICO`,

`MX_BURO_CREDITO`, `MX_AFORE`, `MX_CREDITO_VIVIENDA`, `MX_SEGURIDAD_SOCIAL`, `MX_PROGRAMA_SOCIAL`, `MX_VIVIENDA`, `MX_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no)`	`MX_BANDERA_SI_NO`
`(?i)(true|false)`	`MX_BANDERA_TRUE_FALSE`
`(?i)([sn])`	`MX_BANDERA_S_N`
`(?i)(y)`	`MX_BANDERA_Y_N`
`([01])`	`MX_BANDERA_0_1`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	`mx-bandera-0-1.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	`mx-bandera-s-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	`mx-bandera-si-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	`mx-bandera-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	`mx-bandera-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_BURO_CREDITO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `MX_ESTADO_CREDITICIO`.

Used by: `MX_FIN_BURO_CREDITO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(0[0-7]|9[679]))`	keep · `MX_MOP`
`(?i)(mop\s*)(0[0-7]|9[679])`	keep · `MX_MOP`
`(0*?)(?:(\d{3}))`	keep · `MX_CM_ALFANUM`
`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
otherwise	`MX_ESTADO_CREDITICIO`

CONFIGURATION

trimInput	yes
requireMask	no

MX_CANTIDAD_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_DEPENDIENTES`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR`.

Used by: `MX_L3_SALUD_SEXUAL_REPRODUCTIVA`, `MX_L3_SALUD_MENTAL_ADICCIONES`, `MX_L3_VIDA_SEXUAL`, `MX_L3_CREENCIA_FILOSOFICA_MORAL`, `MX_L3_AFILIACION_SINDICAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))`	keep · keep · keep · keep · keep · `MX_CM_ALFANUM`
otherwise	`MX_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

MX_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `mx-cie10.txt`, chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

CONFIGURATION

lookupFile	`mx-cie10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `mx-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

CONFIGURATION

lookupFile	`mx-cie10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_CLABE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_CLABE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{18}))`	keep · `MX_CLABE_VALIDA`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_CLABE_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CLABE_VALIDA`

PATTERNS, TRIED IN ORDER

`(\d{3})(\d{14})`	keep · `MX_CM_ALFANUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CLABE_VALIDA CHECK DIGIT

Masks the digits with `MX_CLABE_CUERPO` and recomputes a modulus 10 check digit with weights `3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7`.

Used by: `MX_CLABE`

CONFIGURATION

weightList	`3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7`
modulusNumber	`10`
checkDigitIndex	`17`
calculateChecksumRightToLeft	no
numDigitsForCheckdigitCalculation	`17`
numericAlgorithm	`MX_CLABE_CUERPO`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

MX_CLAVE_ELECTOR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_CLAVE_ELECTOR`

PATTERNS, TRIED IN ORDER

`([A-Z]{6})(\d{6})(\d{2})([HM])(\d{3})`	`MX_CM_ALFANUM` · `MX_FECHA_AAMMDD` · `MX_ENTIDAD_NUMERO` · `MX_SEXO_H_M` · `MX_CM_ALFANUM`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes

requireMask	no

MX_CLAVE_MUNICIPIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_L2_CLAVE_MUNICIPIO

PATTERNS, TRIED IN ORDER

(0*)([1-9]\d*)	keep · MX_CLAVE_MUNICIPIO_TABLA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CLAVE_MUNICIPIO_TABLA DATA CLEANSING

Replaces each value found in mx-clave-municipio-generalizada.txt (2,758 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_CLAVE_MUNICIPIO

CONFIGURATION

lookupFile	mx-clave-municipio-generalizada.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: MX_L1_CREDENCIAL_INE, MX_L1_DIRECCION_COMPLEMENTO, MX_L1_CUENTA_BANCARIA, MX_L1_PASAPORTE, MX_L1_DOCUMENTO_MIGRATORIO, MX_L1_CEDULA_PROFESIONAL, MX_L1_LICENCIA_CONDUCIR, MX_L1_EFIRMA, MX_L1_NIV, MX_L1_NUMERO_CONTRATO, MX_L1_USUARIO_RRSS, MX_L2_CCT, MX_L3_SALUD_IDENTIFICADOR, MX_L3_SALUD_RESULTADO_EXAMEN, MX_PENAL_CAUSA, MX_CATEGORIA_SUPRIMIDA, MX_FECHA_AAMMDD, MX_CURP_CUERPO, MX_CURP, MX_RFC_CUERPO_FISICA, MX_RFC_CUERPO_MORAL, MX_RFC, MX_NSS, MX_CLAVE_ELECTOR, MX_NOMBRES, MX_APELLIDOS, MX_NOMBRE_COMPLETO, MX_EMAIL, MX_TELEFONO, MX_CLABE_CUERPO, MX_CLABE, MX_COORDENADA, MX_ANIO, MX_EDAD, MX_CODIGO_POSTAL, MX_PUEBLO, MX_LENGUA_INDIGENA, MX_MEDICAMENTO, MX_DISCAPACIDAD, MX_PREFERENCIA_SEXUAL, MX_IDENTIDAD_GENERO, MX_RELIGION, MX_OPINION_POLITICA, MX_PARTIDO_POLITICO, MX_BURO_CREDITO, MX_AFORE, MX_CREDITO_VIVIENDA, MX_SEGURIDAD_SOCIAL, MX_PROGRAMA_SOCIAL, MX_VIVIENDA, MX_ANTECEDENTES

CONFIGURATION

characterGroups	0123456789 AEIOU BCDFGHJKLMNPQRSTVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚÜ áéíóúü
caseSensitive	yes
minMaskedPositions	0
preserveLeadingZeros	yes

MX_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: MX_L1_DISPOSITIVO, MX_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes

minMaskedPositions	0
preserveLeadingZeros	yes

MX_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM.

Used by: MX_L2_CODIGO_POSTAL

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d{3})(\d{2}))	keep · keep · replace with 00
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_COLONIA SECURE LOOKUP

Replaces the value with one of the 60 values in mx-colonias.txt, chosen by a keyed hash.

Used by: MX_L2_COLONIA

CONFIGURATION

lookupFile	mx-colonias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: MX_L1_GEOLOCALIZACION

PATTERNS, TRIED IN ORDER

(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)	keep · MX_CM_ALFANUM · keep · MX_CM_ALFANUM
(-?\d{1,3}\.\d)(\d+)	keep · MX_CM_ALFANUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CREDITO_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_CREDITO_VIVIENDA_LISTA.

Used by: MX_FIN_CREDITO_VIVIENDA

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|[sny01])	MX_BANDERA
(0*?)(?:(\d{1,6}))	keep · MX_CM_ALFANUM
otherwise	MX_CREDITO_VIVIENDA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_CREDITO_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-credito-vivienda.txt`, chosen by a keyed hash.

Used by: `MX_CREDITO_VIVIENDA`

CONFIGURATION

lookupFile	`mx-credito-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_CURP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_CURP`

PATTERNS, TRIED IN ORDER

`([A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d)`	`MX_CURP_VALIDA`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_CUERPO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CURP_VALIDA`

PATTERNS, TRIED IN ORDER

`([A-Z])([A-Z])([A-Z]{2})(\d{6})([HM])([A-Z]{2})([A-Z]{3})([0-9A-Z])(\d)`	`MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_FECHA_AAMMDD` · `MX_SEXO_H_M` · `MX_ENTIDAD_CURP` · `MX_CM_ALFANUM` · `MX_CM_ALFANUM` · replace with `0`
`([A-Z])([A-Z])([A-Z]{2})(\d{6})(X)([A-Z]{2})([A-Z]{3})([0-9A-Z])(\d)`	`MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_FECHA_AAMMDD` · keep · `MX_ENTIDAD_CURP` · `MX_CM_ALFANUM` · `MX_CM_ALFANUM` · replace with `0`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV STRING ALGORITHM CHAIN

Applies `MX_CURP_DV_P1` → `MX_CURP_DV_P2` → `MX_CURP_DV_P3` → `MX_CURP_DV_P4` → `MX_CURP_DV_P5` → `MX_CURP_DV_P6` → `MX_CURP_DV_P7` → `MX_CURP_DV_P8`, in this order.

Used by: `MX_CURP_VALIDA`

CONFIGURATION

algorithmReferences[1]	MX_CURP_DV_P1
algorithmReferences[2]	MX_CURP_DV_P2
algorithmReferences[3]	MX_CURP_DV_P3
algorithmReferences[4]	MX_CURP_DV_P4
algorithmReferences[5]	MX_CURP_DV_P5
algorithmReferences[6]	MX_CURP_DV_P6
algorithmReferences[7]	MX_CURP_DV_P7
algorithmReferences[8]	MX_CURP_DV_P8

MX_CURP_DV_P1 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{0})(.{2})(.*)	keep · MX_CURP_DV_T1 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P2 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · MX_CURP_DV_T2 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P3 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · MX_CURP_DV_T3 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P4 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

`(.{6})(.{3})(.*)`	keep · `MX_CURP_DV_T4` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P5 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CURP_DV`

PATTERNS, TRIED IN ORDER

`(.{8})(.{3})(.*)`	keep · `MX_CURP_DV_T5` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P6 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CURP_DV`

PATTERNS, TRIED IN ORDER

`(.{10})(.{4})(.*)`	keep · `MX_CURP_DV_T6` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P7 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CURP_DV`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `MX_CURP_DV_T7` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P8 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CURP_DV`

PATTERNS, TRIED IN ORDER

`(.{15})(.{4})(.*)`	keep · `MX_CURP_DV_T8` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_T1 DATA CLEANSING

Replaces each value found in `mx-curp-dv-1.txt` (676 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P1`

CONFIGURATION

lookupFile	`mx-curp-dv-1.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T2 DATA CLEANSING

Replaces each value found in `mx-curp-dv-2.txt` (6,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P2`

CONFIGURATION

lookupFile	`mx-curp-dv-2.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T3 DATA CLEANSING

Replaces each value found in `mx-curp-dv-3.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P3`

CONFIGURATION

lookupFile	`mx-curp-dv-3.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T4 DATA CLEANSING

Replaces each value found in `mx-curp-dv-4.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P4`

CONFIGURATION

lookupFile	`mx-curp-dv-4.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T5 DATA CLEANSING

Replaces each value found in `mx-curp-dv-5.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P5`

CONFIGURATION

lookupFile	`mx-curp-dv-5.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T6 DATA CLEANSING

Replaces each value found in `mx-curp-dv-6.txt` (20,280 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P6`

CONFIGURATION

lookupFile	`mx-curp-dv-6.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T7 DATA CLEANSING

Replaces each value found in `mx-curp-dv-7.txt` (6,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P7`

CONFIGURATION

lookupFile	`mx-curp-dv-7.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T8 DATA CLEANSING

Replaces each value found in `mx-curp-dv-8.txt` (9,360 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P8`

CONFIGURATION

lookupFile	`mx-curp-dv-8.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_CURP_VALIDA STRING ALGORITHM CHAIN

Applies `MX_CURP_CUERPO` → `MX_CURP_DV` , in this order.

Used by: `MX_CURP`

CONFIGURATION

algorithmReferences[1]	`MX_CURP_CUERPO`

algorithmReferences[2]	MX_CURP_DV

MX_DECIL SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-decil.txt`, chosen by a keyed hash.

Used by: MX_NIVEL_SOCIOECONOMICO

CONFIGURATION

lookupFile	mx-decil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DECIL_ALTO SECURE LOOKUP

Replaces the value with one of the 5 values in `mx-decil-alto.txt`, chosen by a keyed hash.

Used by: MX_NIVEL_SOCIOECONOMICO

CONFIGURATION

lookupFile	mx-decil-alto.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DIA_1_28 NUMERIC MAPPING

Maps the number to another between 1 and 28.

Used by: MX_FECHA_AAMMDD

CONFIGURATION

minValue	1
maxValue	28

MX_DIA_29_30 NUMERIC MAPPING

Maps the number to another between 29 and 30.

Used by: MX_FECHA_AAMMDD

CONFIGURATION

minValue	29
maxValue	30

MX_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_DIAGNOSTICO_TEXTO`.

Used by: MX_L3_SALUD_DIAGNOSTICO

PATTERNS, TRIED IN ORDER

([A-TV-Za-tv-z]\d{2}\.\d{1,2})	MX_CIE10_DECIMAL

`([A-TV-Za-tv-z]\d{2,3})`	`MX_CIE10`
`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
otherwise	`MX_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

MX_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `mx-diagnosticos.txt`, chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

CONFIGURATION

lookupFile	`mx-diagnosticos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DIRECCION SECURE LOOKUP

Replaces the value with one of the 3,000 values in `mx-direcciones.txt`, chosen by a keyed hash.

Used by: `MX_L1_DIRECCION`

CONFIGURATION

lookupFile	`mx-direcciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_DISCAPACIDAD_LISTA`.

Used by: `MX_L3_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_DISCAPACIDAD_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `mx-discapacidad.txt`, chosen by a keyed hash.

Used by: `MX_DISCAPACIDAD`

CONFIGURATION

lookupFile	`mx-discapacidad.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`MX_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_EDAD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`
`(0*?)(?:([1-9])(\d)(\.\d+))`	keep · keep · `MX_CM_ALFANUM` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `MX_CM_ALFANUM`
`(0*?)(?:(\d))`	keep · `MX_CM_ALFANUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

`MX_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_EMAIL`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24})`	`MX_CM_ALFANUM` · `MX_CM_ALFANUM` · replace with `test`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

`MX_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 25 values in `mx-empleadores.txt`, chosen by a keyed hash.

Used by: `MX_L2_EMPLEADOR`

CONFIGURATION

lookupFile	`mx-empleadores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`MX_ENTIDAD_CURP` SECURE LOOKUP

Replaces the value with one of the 33 values in `mx-entidad-curp.txt`, chosen by a keyed hash.

Used by: `MX_CURP_CUERPO`

CONFIGURATION

lookupFile	`mx-entidad-curp.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ENTIDAD_NUMERO SECURE LOOKUP

Replaces the value with one of the 32 values in `mx-entidad-numero.txt`, chosen by a keyed hash.

Used by: `MX_CLAVE_ELECTOR`

CONFIGURATION

lookupFile	`mx-entidad-numero.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESCOLARIDAD SECURE LOOKUP

Replaces the value with one of the 12 values in `mx-escolaridad.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESCOLARIDAD`

CONFIGURATION

lookupFile	`mx-escolaridad.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESCUELA SECURE LOOKUP

Replaces the value with one of the 15 values in `mx-escuelas.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESCUELA`

CONFIGURATION

lookupFile	`mx-escuelas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESTADO_CIVIL SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-estado-civil.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`mx-estado-civil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESTADO_CREDITICIO SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-estado-crediticio.txt`, chosen by a keyed hash.

Used by: `MX_BURO_CREDITO`

CONFIGURATION

lookupFile	`mx-estado-crediticio.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_FECHA_AAMMDD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_CURP_CUERPO`, `MX_RFC_CUERPO_FISICA`, `MX_RFC_CUERPO_MORAL`, `MX_RFC`, `MX_CLAVE_ELECTOR`

PATTERNS, TRIED IN ORDER

`(\d)(\d)(0[1-9]|1[0-2])(0[1-9]|1\d|2[0-8])`	keep · `MX_CM_ALFANUM` · `MX_MES` · `MX_DIA_1_28`
`(\d)(\d)(0[13-9]|1[0-2])(29|30)`	keep · `MX_CM_ALFANUM` · `MX_MES_30_DIAS` · `MX_DIA_29_30`
`(\d)(\d)(0[13578]|1[02])(31)`	keep · `MX_CM_ALFANUM` · `MX_MES_31_DIAS` · keep
`(\d)(\d)(02)(29)`	keep · `MX_CM_ALFANUM` · keep · replace with `28`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `MX_L2_FECHA_EVENTO`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

MX_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `MX_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

MX_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_IDENTIDAD_GENERO_LISTA`.

Used by: `MX_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_IDENTIDAD_GENERO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `mx-identidad-genero.txt`, chosen by a keyed hash.

Used by: `MX_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	`mx-identidad-genero.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_HEX`.

Used by: `MX_L1_IP`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `MX_OCTETO` · `MX_OCTETO` · `MX_OCTETO` · `MX_OCTETO`
otherwise	`MX_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

MX_LENGUA_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_LENGUA_INDIGENA_LISTA`.

Used by: `MX_L3_LENGUA_INDIGENA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_LENGUA_INDIGENA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_LENGUA_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 27 values in `mx-lenguas.txt`, chosen by a keyed hash.

Used by: `MX_LENGUA_INDIGENA`

CONFIGURATION

lookupFile	`mx-lenguas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_LOCALIDAD SECURE LOOKUP

Replaces the value with one of the 229 values in `mx-localidades.txt`, chosen by a keyed hash.

Used by: `MX_L2_LOCALIDAD`

CONFIGURATION

lookupFile	`mx-localidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_MEDICAMENTO_LISTA`.

Used by: `MX_L3_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 26 values in `mx-medicamentos.txt`, chosen by a keyed hash.

Used by: `MX_MEDICAMENTO`

CONFIGURATION

lookupFile	`mx-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MES NUMERIC MAPPING

Maps the number to another between 1 and 12.

Used by: `MX_FECHA_AAMMDD`

CONFIGURATION

minValue	`1`
maxValue	`12`

MX_MES_30_DIAS SECURE LOOKUP

Replaces the value with one of the 11 values in `mx-meses-30-dias.txt`, chosen by a keyed hash.

Used by: `MX_FECHA_AAMMDD`

CONFIGURATION

lookupFile	`mx-meses-30-dias.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MES_31_DIAS SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-meses-31-dias.txt`, chosen by a keyed hash.

Used by: `MX_FECHA_AAMMDD`

CONFIGURATION

lookupFile	`mx-meses-31-dias.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MOP SECURE LOOKUP

Replaces the value with one of the 9 values in `mx-mop.txt`, chosen by a keyed hash.

Used by: `MX_BURO_CREDITO`

CONFIGURATION

lookupFile	`mx-mop.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MUNICIPIO DATA CLEANSING

Replaces each value found in `mx-municipio-generalizado.txt` (6,547 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_L2_MUNICIPIO`

CONFIGURATION

lookupFile	mx-municipio-generalizado.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

MX_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 20 values in `mx-nacionalidades.txt`, chosen by a keyed hash.

Used by: `MX_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	mx-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_NSE`.

Used by: `MX_FIN_NIVEL_SOCIOECONOMICO`

PATTERNS, TRIED IN ORDER

(0*?)(?:([1-5]))	keep · MX_QUINTIL
(0*?)(?:([6-9]|10))	keep · MX_DECIL_ALTO
(?i)(decil\s*)(\d{1,2})	keep · MX_DECIL
otherwise	MX_NSE

CONFIGURATION

trimInput	yes
requireMask	no

MX_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

([^,]+),\s*(.+)	MX_APELLIDOS · MX_NOMBRES
(\S+)	MX_NOMBRE_PILA

`(\S+)\s+(\S+)`	`MX_NOMBRE_PILA` · `MX_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`MX_NOMBRE_PILA` · `MX_APELLIDO` · `MX_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`MX_NOMBRE_PILA` · `MX_NOMBRE_PILA` · `MX_APELLIDO` · `MX_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`MX_NOMBRE_PILA` · `MX_NOMBRE_PILA` · `MX_NOMBRE_PILA` · `MX_APELLIDO` · `MX_APELLIDO`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_NOMBRE_PILA NAME

Replaces the name with one of the 255 names in `mx-nombres.txt`.

Used by: `MX_NOMBRES`, `MX_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	`mx-nombres.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

MX_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_NOMBRE`, `MX_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`MX_NOMBRE_PILA`
`(\S+)\s+(\S+)`	`MX_NOMBRE_PILA` · `MX_NOMBRE_PILA`
`(\S+)\s+(\S+)\s+(\S+)`	`MX_NOMBRE_PILA` · `MX_NOMBRE_PILA` · `MX_NOMBRE_PILA`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_NSE SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-nse.txt`, chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`mx-nse.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_NSS`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{11}))`	keep · `MX_NSS_LUHN`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_NSS_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: `MX_NSS`

CONFIGURATION

preserve	`0`

MX_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `MX_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

MX_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in `mx-ocupaciones.txt`, chosen by a keyed hash.

Used by: `MX_L2_OCUPACION`

CONFIGURATION

lookupFile	`mx-ocupaciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_OPINION_POLITICA_LISTA`.

Used by: `MX_L3_OPINION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_OPINION_POLITICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-opiniones-politicas.txt`, chosen by a keyed hash.

Used by: `MX_OPINION_POLITICA`

CONFIGURATION

lookupFile	`mx-opiniones-politicas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PARTIDO_POLITICO_LISTA`.

Used by: `MX_L3_AFILIACION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_PARTIDO_POLITICO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-partidos.txt`, chosen by a keyed hash.

Used by: `MX_PARTIDO_POLITICO`

CONFIGURATION

lookupFile	`mx-partidos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PLACA CHARACTER MAPPING

Maps each character to another of its group (3 groups), keeping length and format.

Used by: `MX_L1_PLACA`

CONFIGURATION

characterGroups	`ABCDEFGHJKLMNPRSTUVWXYZ` `abcdefghjklmnprstuvwxyz` `0123456789`
caseSensitive	yes

MX_PREFERENCIA_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PREFERENCIA_SEXUAL_LISTA`.

Used by: `MX_L3_PREFERENCIA_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_PREFERENCIA_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_PREFERENCIA_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `mx-preferencia-sexual.txt`, chosen by a keyed hash.

Used by: `MX_PREFERENCIA_SEXUAL`

CONFIGURATION

lookupFile	`mx-preferencia-sexual.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PROGRAMA_SOCIAL_LISTA`.

Used by: `MX_FIN_PROGRAMA_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_PROGRAMA_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-programas-sociales.txt`, chosen by a keyed hash.

Used by: `MX_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	`mx-programas-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_PUEBLO_LISTA`.

Used by: `MX_L3_ETNIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_PUEBLO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_PUEBLO_LISTA SECURE LOOKUP

Replaces the value with one of the 31 values in `mx-pueblos.txt`, chosen by a keyed hash.

Used by: `MX_PUEBLO`

CONFIGURATION

lookupFile	`mx-pueblos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in `mx-quintil.txt`, chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`mx-quintil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_CREDENCIAL`, `MX_L3_BIOMETRICO`, `MX_L3_INFORMACION_GENETICA`

PATTERNS, TRIED IN ORDER

`(.+)`	each character → `X`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_REGIMEN_FISCAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_REGIMEN_FISCAL_NOMBRE`.

Used by: `MX_FIN_REGIMEN_FISCAL`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(6\d{2}))`	keep · `MX_REGIMEN_FISCAL_CLAVE`
`(0*?)(?:(6\d{2})(\s*[—]\s*)(.+))`	keep · `MX_REGIMEN_FISCAL_CLAVE` · keep · `MX_REGIMEN_FISCAL_NOMBRE`
otherwise	`MX_REGIMEN_FISCAL_NOMBRE`

CONFIGURATION

trimInput	yes
requireMask	no

MX_REGIMEN_FISCAL_CLAVE SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-regimen-fiscal-clave.txt`, chosen by a keyed hash.

Used by: `MX_REGIMEN_FISCAL`

CONFIGURATION

lookupFile	`mx-regimen-fiscal-clave.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_REGIMEN_FISCAL_NOMBRE SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-regimen-fiscal-nombre.txt`, chosen by a keyed hash.

Used by: `MX_REGIMEN_FISCAL`

CONFIGURATION

lookupFile	`mx-regimen-fiscal-nombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_RELIGION_LISTA`.

Used by: `MX_L3_RELIGION`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_RELIGION_LISTA`

CONFIGURATION

trimInput	yes

requireMask	no

MX_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-religiones.txt`, chosen by a keyed hash.

Used by: `MX_RELIGION`

CONFIGURATION

lookupFile	`mx-religiones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_RFC REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_RFC`

PATTERNS, TRIED IN ORDER

`([A-ZÑ&]{4}\d{6}[A-Z0-9]{2}[0-9A])`	`MX_RFC_FISICA`
`([A-ZÑ&]{3}\d{6}[A-Z0-9]{2}[0-9A])`	`MX_RFC_MORAL`
`([A-ZÑ&])([A-ZÑ&])([A-ZÑ&]{2})(\d{6})`	`MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_FECHA_AAMMDD`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_CUERPO_FISICA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_FISICA`

PATTERNS, TRIED IN ORDER

`([A-ZÑ&])([A-ZÑ&])([A-ZÑ&]{2})(\d{6})([A-Z0-9]{2})([0-9A])`	`MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_CM_ALFANUM` · `MX_FECHA_AAMMDD` · `MX_CM_ALFANUM` · replace with `0`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_CUERPO_MORAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_MORAL`

PATTERNS, TRIED IN ORDER

`([A-ZÑ&]{3})(\d{6})([A-Z0-9]{2})([0-9A])`	`MX_CM_ALFANUM` · `MX_FECHA_AAMMDD` · `MX_CM_ALFANUM` · replace with `0`
otherwise	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

`MX_RFC_DV` STRING ALGORITHM CHAIN

Applies `MX_RFC_DV_P1` → `MX_RFC_DV_P2` → `MX_RFC_DV_P3` → `MX_RFC_DV_P4` → `MX_RFC_DV_P5` → `MX_RFC_DV_P6`, in this order.

Used by: `MX_RFC_FISICA`, `MX_RFC_MORAL`

CONFIGURATION

`algorithmReferences[1]`	`MX_RFC_DV_P1`
`algorithmReferences[2]`	`MX_RFC_DV_P2`
`algorithmReferences[3]`	`MX_RFC_DV_P3`
`algorithmReferences[4]`	`MX_RFC_DV_P4`
`algorithmReferences[5]`	`MX_RFC_DV_P5`
`algorithmReferences[6]`	`MX_RFC_DV_P6`

`MX_RFC_DV_P1` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_DV`

PATTERNS, TRIED IN ORDER

`(.{0})(.{2})(.*)`	keep · `MX_RFC_DV_T1` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

`MX_RFC_DV_P2` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_DV`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `MX_RFC_DV_T2` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

`MX_RFC_DV_P3` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_DV`

PATTERNS, TRIED IN ORDER

`(.{4})(.{3})(.*)`	keep · `MX_RFC_DV_T3` · keep
`otherwise`	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P4 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · MX_RFC_DV_T4 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P5 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · MX_RFC_DV_T5 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P6 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{10})(.{4})(.*)	keep · MX_RFC_DV_T6 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_T1 DATA CLEANSING

Replaces each value found in mx-rfc-dv-1.txt (812 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P1

CONFIGURATION

lookupFile	mx-rfc-dv-1.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T2 DATA CLEANSING

Replaces each value found in `mx-rfc-dv-2.txt` (8,624 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_DV_P2`

CONFIGURATION

lookupFile	`mx-rfc-dv-2.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T3 DATA CLEANSING

Replaces each value found in `mx-rfc-dv-3.txt` (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_DV_P3`

CONFIGURATION

lookupFile	`mx-rfc-dv-3.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T4 DATA CLEANSING

Replaces each value found in `mx-rfc-dv-4.txt` (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_DV_P4`

CONFIGURATION

lookupFile	`mx-rfc-dv-4.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T5 DATA CLEANSING

Replaces each value found in `mx-rfc-dv-5.txt` (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_DV_P5`

CONFIGURATION

lookupFile	`mx-rfc-dv-5.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T6 DATA CLEANSING

Replaces each value found in `mx-rfc-dv-6.txt` (14,256 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_DV_P6`

CONFIGURATION

lookupFile	`mx-rfc-dv-6.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_RFC_FISICA STRING ALGORITHM CHAIN

Applies `MX_RFC_CUERPO_FISICA` → `MX_RFC_DV`, in this order.

Used by: `MX_RFC`

CONFIGURATION

algorithmReferences[1]	`MX_RFC_CUERPO_FISICA`
algorithmReferences[2]	`MX_RFC_DV`

MX_RFC_MORAL STRING ALGORITHM CHAIN

Applies `MX_RFC_CUERPO_MORAL` → `MX_RFC_RELLENO` → `MX_RFC_DV` → `MX_RFC_SIN_RELLENO`, in this order.

Used by: `MX_RFC`

CONFIGURATION

algorithmReferences[1]	`MX_RFC_CUERPO_MORAL`
algorithmReferences[2]	`MX_RFC_RELLENO`
algorithmReferences[3]	`MX_RFC_DV`
algorithmReferences[4]	`MX_RFC_SIN_RELLENO`

MX_RFC_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_MORAL`

PATTERNS, TRIED IN ORDER

`(.)(.{11})`	`MX_RFC_RELLENO_TABLA` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_RELLENO_TABLA DATA CLEANSING

Replaces each value found in `mx-rfc-relleno.txt` (38 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_RELLENO`

CONFIGURATION

lookupFile	`mx-rfc-relleno.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

MX_RFC_SIN_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_MORAL`

PATTERNS, TRIED IN ORDER

`(_)(.{12})`	remove · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_SEGURIDAD_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SEGURIDAD_SOCIAL_LISTA`.

Used by: `MX_FIN_SEGURIDAD_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,2}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_SEGURIDAD_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_SEGURIDAD_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-seguridad-social.txt`, chosen by a keyed hash.

Used by: `MX_SEGURIDAD_SOCIAL`

CONFIGURATION

lookupFile	`mx-seguridad-social.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_SEXO REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_SEXO`

PATTERNS, TRIED IN ORDER

`(?i)(femenino|masculino)`	`MX_SEXO_PALABRA`
`(?i)(mujer|hombre)`	`MX_SEXO_MUJER_HOMBRE`
`(?i)(female|male)`	`MX_SEXO_INGLES`
`(?i)([hm])`	`MX_SEXO_H_M`
`(?i)(f)`	`MX_SEXO_F_M`
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

MX_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	`mx-sexo-f-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-h-m.txt`, chosen by a keyed hash.

Used by: `MX_CURP_CUERPO`, `MX_CLAVE_ELECTOR`, `MX_SEXO`

CONFIGURATION

lookupFile	`mx-sexo-h-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_SEXO_INGLES SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-ingles.txt`, chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	`mx-sexo-ingles.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	`mx-sexo-mujer-hombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

MX_SEXO_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-palabra.txt`, chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	`mx-sexo-palabra.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

Used by: `MX_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`mx-sin-informacion.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_TARJETA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L1_TELEFONO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?52[\s\-]?)?(1[\s\-]?)?(\(?(?:55|56|33|81)\)?[\s\-]?)(\d{4})([\s\-]?)(\d{4}))`	keep · keep · keep · keep · `MX_CM_ALFANUM` · keep · `MX_CM_ALFANUM`
`(0*?)(?:(\+?52[\s\-]?)?(1[\s\-]?)?(\(?[2-9]\d{2}\)?[\s\-]?)(\d{3})([\s\-]?)(\d{4}))`	keep · keep · keep · keep · `MX_CM_ALFANUM` · keep · `MX_CM_ALFANUM`
otherwise	`MX_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

MX_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DATO]`, and the 1,436 terms of `mx-texto-nombres.txt` with `[NOMBRE]`.

Used by: `MX_L1_TEXTO_LIBRE`, `MX_L3_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

`[A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d`
`[A-ZÑ&]{3,4}\d{6}[A-Z0-9]{2}[0-9A]`
`[A-Z]{6}\d{8}[HM]\d{3}`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<!\d)(\+?52)?1?\d{10}(?!\d)`
`(?<!\d)\d{11}(?!\d)`
`(?<!\d)\d{13,19}(?!\d)`
`(?<![A-Za-z])[A-HJ-NPR-Z]{3}-?\d{3}-?[A-HJ-NPR-Z](?![A-Za-z])`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATO]`
lookupFile	`mx-texto-nombres.txt`
lookupFileRedactValue	`[NOMBRE]`
isDenyList	yes

MX_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_VIVIENDA_LISTA`.

Used by: `MX_FIN_VIVIENDA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`MX_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `MX_CM_ALFANUM`
otherwise	`MX_VIVIENDA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

MX_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-vivienda.txt`, chosen by a keyed hash.

Used by: `MX_VIVIENDA`

CONFIGURATION

lookupFile	`mx-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the policy reads. In Delphix each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`mx-afores.txt`	11	`MX_AFORE_LISTA`	Afore Azteca · Afore Banamex · Afore Coppel · Afore Inbursa
`mx-antecedentes.txt`	3	`MX_ANTECEDENTES_LISTA`	Sin antecedentes penales · Con antecedentes penales · Sin información
`mx-apellidos.txt`	337	`MX_APELLIDO`	Hernández · García · Martínez · López
`mx-bandera-0-1.txt`	2	`MX_BANDERA_0_1`	0 · 1
`mx-bandera-s-n.txt`	2	`MX_BANDERA_S_N`	S · N
`mx-bandera-si-no.txt`	2	`MX_BANDERA_SI_NO`	Sí · No
`mx-bandera-true-false.txt`	2	`MX_BANDERA_TRUE_FALSE`	true · false
`mx-bandera-y-n.txt`	2	`MX_BANDERA_Y_N`	Y · N
`mx-cie10-decimal.txt`	33	`MX_CIE10_DECIMAL`	E11.9 · E78.5 · J45.9 · J06.9
`mx-cie10.txt`	37	`MX_CIE10`	I10 · E11 · E78 · J45
`mx-clave-municipio-generalizada.txt`	2,758	`MX_CLAVE_MUNICIPIO_TABLA`	01001,01001 · 1001,1001 · 01002,01002 · 1002,1002
`mx-colonias.txt`	60	`MX_COLONIA`	Centro · Del Valle · San Miguel · Santa María
`mx-credito-vivienda.txt`	6	`MX_CREDITO_VIVIENDA_LISTA`	Crédito Infonavit · Crédito Fovissste · Cofinavit · Crédito hipotecario bancario
`mx-curp-dv-1.txt`	676	`MX_CURP_DV_T1`	AA,AA0 · AB,AB7 · AC,AC4 · AD,AD1
`mx-curp-dv-2.txt`	6,760	`MX_CURP_DV_T2`	0AA,AA0 · 0AB,AB5 · 0AC,AC0 · 0AD,AD5
`mx-curp-dv-3.txt`	1,000	`MX_CURP_DV_T3`	000,000 · 001,013 · 002,026 · 003,039
`mx-curp-dv-4.txt`	1,000	`MX_CURP_DV_T4`	000,000 · 001,011 · 002,022 · 003,033
`mx-curp-dv-5.txt`	1,000	`MX_CURP_DV_T5`	000,000 · 001,019 · 002,028 · 003,037

FILE	LINES	USED BY	FIRST LINES
mx-curp-dv-6.txt	20,280	MX_CURP_DV_T6	0HAA,HAA6 · 0HAB,HAB2 · 0HAC,HAC8 · 0HAD,HAD4
mx-curp-dv-7.txt	6,760	MX_CURP_DV_T7	0AA,AA0 · 0AB,AB4 · 0AC,AC8 · 0AD,AD2
mx-curp-dv-8.txt	9,360	MX_CURP_DV_T8	0A00,A00 · 0A10,A18 · 0A20,A26 · 0A30,A34
mx-decil-alto.txt	5	MX_DECIL_ALTO	6 · 7 · 8 · 9
mx-decil.txt	10	MX_DECIL	1 · 2 · 3 · 4
mx-detectar-apellidos.txt	423	MX_L1_APELLIDO – List MX_L1_NOMBRE_COMPLETO – List	Hernández · Hernandez · García · Garcia
mx-detectar-nombres.txt	301	MX_L1_NOMBRE – List MX_L1_NOMBRE_COMPLETO – List	María · Maria · José · Jose
mx-detectar-sexo-letra.txt	4	MX_L2_SEXO – List	h · m · f · x
mx-detectar-sexo.txt	8	MX_L2_SEXO – List	hombre · mujer · femenino · masculino
mx-diagnosticos.txt	30	MX_DIAGNOSTICO_TEXTO	Hipertensión arterial sistémica · Diabetes mellitus tipo 2 · Asma · Lumbalgia
mx-direcciones.txt	3,000	MX_DIRECCION	Calle Belisario Domínguez 681 · Calle Coahuila 741 · Calle Marte 348 Int. 17 · Xicoténcatl 1448
mx-discapacidad.txt	8	MX_DISCAPACIDAD_LISTA	Caminar, subir o bajar · Ver, aun usando lentes · Oír, aun usando aparato auditivo · Hablar o comunicarse
mx-empleadores.txt	25	MX_EMPLEADOR	Comercializadora del Bajío S.A. de C.V. · Servicios Integrales del Norte S.A. de C.V. · Constructora Sierra Madre S.A. de C.V. · Transportes Golfo Pacífico S.A. de C.V.
mx-entidad-curp.txt	33	MX_ENTIDAD_CURP	AS · BC · BS · CC
mx-entidad-numero.txt	32	MX_ENTIDAD_NUMERO	01 · 02 · 03 · 04
mx-escolaridad.txt	12	MX_ESCOLARIDAD	Sin escolaridad · Preescolar · Primaria incompleta · Primaria completa
mx-escuelas.txt	15	MX_ESCUELA	Escuela Primaria Miguel Hidalgo · Escuela Primaria Rural Emiliano Zapata · Escuela Secundaria Técnica No. 14 · Telesecundaria Josefa Ortiz de Domínguez
mx-estado-civil.txt	6	MX_ESTADO_CIVIL	Soltero · Casado · Unión libre · Separado
mx-estado-crediticio.txt	10	MX_ESTADO_CREDITICIO	Al corriente · Atraso de 1 a 29 días · Atraso de 30 a 59 días · Atraso de 60 a 89 días

FILE	LINES	USED BY	FIRST LINES
mx-identidad-genero.txt	8	MX_IDENTIDAD_GENERO_LISTA	Mujer · Hombre · Mujer trans · Hombre trans
mx-lenguas.txt	27	MX_LENGUA_INDIGENA_LISTA	Náhuatl · Maya · Tseltal · Tsotsil
mx-localidades.txt	229	MX_LOCALIDAD	Aguascalientes · Jesús María · Ensenada · Mexicali
mx-medicamentos.txt	26	MX_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Naproxeno · Metamizol
mx-meses-30-dias.txt	11	MX_MES_30_DIAS	01 · 03 · 04 · 05
mx-meses-31-dias.txt	7	MX_MES_31_DIAS	01 · 03 · 05 · 07
mx-mop.txt	9	MX_MOP	01 · 02 · 03 · 04
mx-municipio-generalizado.txt	6,547	MX_MUNICIPIO	Aguascalientes|Aguascalientes · AGUASCALIENTES|AGUASCALIENTES · Asientos|Asientos · ASIENTOS|ASIENTOS
mx-nacionalidades.txt	20	MX_NACIONALIDAD	Mexicana · Estadounidense · Guatemalteca · Hondureña
mx-nombres.txt	255	MX_NOMBRE_PILA	María · José · Juan · Luis
mx-nse.txt	7	MX_NSE	A/B · C+ · C · C-
mx-ocupaciones.txt	40	MX_OCUPACION	Empleado administrativo · Comerciante · Vendedor · Obrero
mx-opiniones-politicas.txt	7	MX_OPINION_POLITICA_LISTA	Izquierda · Centro izquierda · Centro · Centro derecha
mx-partidos.txt	10	MX_PARTIDO_POLITICO_LISTA	Morena · Partido Acción Nacional · Partido Revolucionario Institucional · Partido del Trabajo
mx-preferencia-sexual.txt	9	MX_PREFERENCIA_SEXUAL_LISTA	Heterosexual · Homosexual · Lesbiana · Gay
mx-programas-sociales.txt	13	MX_PROGRAMA_SOCIAL_LISTA	Pensión para el Bienestar de las Personas Adultas Mayores · Pensión Mujeres Bienestar · Pensión para el Bienestar de las Personas con Discapacidad · Beca Universal Rita Cetina
mx-pueblos.txt	31	MX_PUEBLO_LISTA	Nahua · Maya · Zapoteco · Mixteco
mx-quintil.txt	5	MX_QUINTIL	1 · 2 · 3 · 4
mx-regimen-fiscal-clave.txt	13	MX_REGIMEN_FISCAL_CLAVE	605 · 606 · 607 · 608
mx-regimen-fiscal-nombre.txt	13	MX_REGIMEN_FISCAL_NOMBRE	Sueldos y Salarios e Ingresos Asimilados a Salarios · Arrendamiento · Régimen de Enajenación o Adquisición de Bienes · Demás ingresos

FILE	LINES	USED BY	FIRST LINES
mx-religiones.txt	13	MX_RELIGION_LISTA	Católica · Protestante o cristiana evangélica · Pentecostal · Testigo de Jehová
mx-rfc-dv-1.txt	812	MX_RFC_DV_T1	AA,AA8 · AB,AB9 · AC,ACA · AD,AD0
mx-rfc-dv-2.txt	8,624	MX_RFC_DV_T2	0AA,AA1 · 0AB,AB0 · 0AC,ACA · 0AD,AD9
mx-rfc-dv-3.txt	1,100	MX_RFC_DV_T3	000,000 · 001,018 · 002,025 · 003,032
mx-rfc-dv-4.txt	1,100	MX_RFC_DV_T4	000,000 · 001,016 · 002,021 · 003,037
mx-rfc-dv-5.txt	1,100	MX_RFC_DV_T5	000,000 · 001,014 · 002,028 · 003,031
mx-rfc-dv-6.txt	14,256	MX_RFC_DV_T6	0000,000 · 0010,019 · 0020,027 · 0030,035
mx-rfc-relleno.txt	38	MX_RFC_RELLENO_TABLA	0,_0 · 1,_1 · 2,_2 · 3,_3
mx-seguridad-social.txt	10	MX_SEGURIDAD_SOCIAL_LISTA	IMSS · ISSSTE · ISSSTE estatal · IMSS-Bienestar
mx-sexo-f-m.txt	2	MX_SEXO_F_M	F · M
mx-sexo-h-m.txt	2	MX_SEXO_H_M	H · M
mx-sexo-ingles.txt	2	MX_SEXO_INGLES	Female · Male
mx-sexo-mujer-hombre.txt	2	MX_SEXO_MUJER_HOMBRE	Mujer · Hombre
mx-sexo-palabra.txt	2	MX_SEXO_PALABRA	Femenino · Masculino
mx-sin-informacion.txt	1	MX_SUPRIMIR	Sin información
mx-texto-nombres.txt	1,436	MX_TEXTO_LIBRE	María · MARÍA · Maria · MARIA
mx-vivienda.txt	6	MX_VIVIENDA_LISTA	Propia · Propia en proceso de pago · Rentada o alquilada · Prestada

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `colonia` `col` `municipio` `mpio` `mun` `alcaldia` `delegacion` `localidad` `estado` `edo` `entidad` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `plantel` `establecimiento` `institucion` `afore` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `umf` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `prov` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `regimen` `concepto` `impuesto` `moneda` `emisor` `comprobante` `cfdi` `uso` `pago` `forma` `metodo` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `cliente` `cte` `cli` `paciente` `pac` `trabajador` `trab` `empleado` `colaborador` `alumno` `estudiante` `afiliado` `asegurado` `derechohabiente` `beneficiario` `benef` `titular` `madre` `padre` `tutor` `conyuge` `pareja` `medico` `doctor` `profesional` `responsable` `contacto` `emergencia` `aval` `obligado` `coacreditado` `deudor` `acreditado` `remitente` `destinatario` `receptor` `firmante` `testigo` `representante` `apoderado` `propietario` `arrendatario` `contratante` `victima` `denunciante` `imputado` `socio` `donante` `heredero` `persona` `pers` `conductor` `chofer` `vendedor` `ejecutivo` `agente` `solicitante` `usuario_?final` `ciudadano` `elector` `votante` `contribuyente` `jefe_?(de_?)?familia` `hijo` `hija` `familiar` `dependiente` `completos?` `y_?apellidos?` `apellidos?`

E2 `producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `colonia` `col` `municipio` `mpio` `mun` `alcaldia` `delegacion` `localidad` `estado` `edo` `entidad` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `plantel` `establecimiento` `institucion` `afore` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `umf` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `prov` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `regimen` `concepto` `impuesto` `moneda` `emisor` `comprobante` `cfdi` `uso` `pago` `forma` `metodo` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `cliente` `cte` `cli` `paciente` `pac` `trabajador` `trab` `empleado` `colaborador` `alumno` `estudiante` `afiliado` `asegurado` `derechohabiente` `beneficiario` `benef` `titular` `madre` `padre` `tutor` `conyuge` `pareja` `medico` `doctor` `profesional` `responsable` `contacto` `emergencia` `aval` `obligado` `coacreditado` `deudor` `acreditado` `remitente` `destinatario` `receptor` `firmante` `testigo` `representante` `apoderado` `propietario` `arrendatario` `contratante` `victima` `denunciante` `imputado` `socio` `donante` `heredero` `persona` `pers` `conductor` `chofer` `vendedor` `ejecutivo` `agente` `solicitante` `usuario_?final` `ciudadano` `elector` `votante` `contribuyente` `jefe_?(de_?)?familia` `hijo` `hija` `familiar` `dependiente` `completo` `compl` `full` `y_?apellidos?` `apellidos?`

E3	`producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `colonia` `col` `municipio` `mpio` `mun` `alcaldia` `delegacion` `localidad` `estado` `edo` `entidad` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `plantel` `establecimiento` `institucion` `afore` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `umf` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `prov` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `regimen` `concepto` `impuesto` `moneda` `emisor` `comprobante` `cfdi` `uso` `pago` `forma` `metodo` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `completo`
E4	`producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `colonia` `col` `municipio` `mpio` `mun` `alcaldia` `delegacion` `localidad` `estado` `edo` `entidad` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `plantel` `establecimiento` `institucion` `afore` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `umf` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `prov` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `regimen` `concepto` `impuesto` `moneda` `emisor` `comprobante` `cfdi` `uso` `pago` `forma` `metodo` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector`
E5	`ip` `mac` `web` `url` `correo` `mail` `electronica` `email`
E6	`producto` `prod` `serv` `prodserv` `articulo` `sucursal` `interna` `tipo` `registro` `primaria` `foranea` `elector` `electoral` `unica` `bancaria` `interbancaria` `municipio` `mun` `entidad` `ent` `localidad` `loc` `escuela` `centro` `cct` `clues` `sat` `producto` `servicio` `unidad` `plaza` `banco` `pais` `moneda` `regimen` `uso` `cfdi` `postal` `lada` `zona` `ageb` `area`
E7	`imss` `issste` `sat` `federal` `estatal` `regional` `administrativa`
E8	`fijo` `variable` `monto` `adicional` `servicio` `tarifa` `valor` `cuenta` `extra` `automatico` `recurrente` `domiciliado`
E9	`medicos` `patologicos` `personales_?patologicos` `heredofamiliares` `gineco` `obstetricos` `familiares` `clinicos` `academicos` `laborales` `crediticios` `comerciales` `generales`

APPENDIX D

Discovery policy and classifiers

The discovery policy `MX – LFPDPPP – v4` runs these 155 classifiers, with an assignment threshold of 60%.

LFPDPPP 2025 - datos personales y sensibles

CLASSIFIER	KIND	DATA CLASS
`MX_L1_CURP – Path`	COLUMN NAME	`MX_L1_CURP`
`MX_L1_CURP – Type`	DATA TYPE	`MX_L1_CURP`
`MX_L1_CURP – Regex`	VALUE FORMAT	`MX_L1_CURP`
`MX_L1_RFC – Path`	COLUMN NAME	`MX_L1_RFC`
`MX_L1_RFC – Type`	DATA TYPE	`MX_L1_RFC`
`MX_L1_RFC – Regex`	VALUE FORMAT	`MX_L1_RFC`
`MX_L1_NSS – Path`	COLUMN NAME	`MX_L1_NSS`
`MX_L1_NSS – Type`	DATA TYPE	`MX_L1_NSS`
`MX_L1_NSS – Regex`	VALUE FORMAT	`MX_L1_NSS`
`MX_L1_CLAVE_ELECTOR – Path`	COLUMN NAME	`MX_L1_CLAVE_ELECTOR`
`MX_L1_CLAVE_ELECTOR – Type`	DATA TYPE	`MX_L1_CLAVE_ELECTOR`
`MX_L1_CLAVE_ELECTOR – Regex`	VALUE FORMAT	`MX_L1_CLAVE_ELECTOR`
`MX_L1_CREDENCIAL_INE – Path`	COLUMN NAME	`MX_L1_CREDENCIAL_INE`
`MX_L1_CREDENCIAL_INE – Regex`	VALUE FORMAT	`MX_L1_CREDENCIAL_INE`
`MX_L1_NOMBRE – Path`	COLUMN NAME	`MX_L1_NOMBRE`
`MX_L1_NOMBRE – List`	KNOWN VALUES	`MX_L1_NOMBRE`
`MX_L1_APELLIDO – Path`	COLUMN NAME	`MX_L1_APELLIDO`
`MX_L1_APELLIDO – List`	KNOWN VALUES	`MX_L1_APELLIDO`
`MX_L1_NOMBRE_COMPLETO – Path`	COLUMN NAME	`MX_L1_NOMBRE_COMPLETO`
`MX_L1_NOMBRE_COMPLETO – List`	KNOWN VALUES	`MX_L1_NOMBRE_COMPLETO`
`MX_L1_EMAIL – Path`	COLUMN NAME	`MX_L1_EMAIL`
`MX_L1_EMAIL – Type`	DATA TYPE	`MX_L1_EMAIL`
`MX_L1_EMAIL – Regex`	VALUE FORMAT	`MX_L1_EMAIL`
`MX_L1_TELEFONO – Path`	COLUMN NAME	`MX_L1_TELEFONO`
`MX_L1_TELEFONO – Regex`	VALUE FORMAT	`MX_L1_TELEFONO`
`MX_L1_DIRECCION – Path`	COLUMN NAME	`MX_L1_DIRECCION`
`MX_L1_DIRECCION – Type`	DATA TYPE	`MX_L1_DIRECCION`
`MX_L1_DIRECCION – Regex`	VALUE FORMAT	`MX_L1_DIRECCION`
`MX_L1_DIRECCION_COMPLEMENTO – Path`	COLUMN NAME	`MX_L1_DIRECCION_COMPLEMENTO`
`MX_L1_CLABE – Path`	COLUMN NAME	`MX_L1_CLABE`
`MX_L1_CLABE – Type`	DATA TYPE	`MX_L1_CLABE`
`MX_L1_CLABE – Regex`	VALUE FORMAT	`MX_L1_CLABE`

CLASSIFIER	KIND	DATA CLASS
MX_L1_CUENTA_BANCARIA - Path	COLUMN NAME	MX_L1_CUENTA_BANCARIA
MX_L1_TARJETA - Path	COLUMN NAME	MX_L1_TARJETA
MX_L1_TARJETA - Regex	VALUE FORMAT	MX_L1_TARJETA
MX_L1_PASAPORTE - Path	COLUMN NAME	MX_L1_PASAPORTE
MX_L1_PASAPORTE - Regex	VALUE FORMAT	MX_L1_PASAPORTE
MX_L1_DOCUMENTO_MIGRATORIO - Path	COLUMN NAME	MX_L1_DOCUMENTO_MIGRATORIO
MX_L1_CEDULA_PROFESIONAL - Path	COLUMN NAME	MX_L1_CEDULA_PROFESIONAL
MX_L1_CEDULA_PROFESIONAL - Regex	VALUE FORMAT	MX_L1_CEDULA_PROFESIONAL
MX_L1_LICENCIA_CONDUCIR - Path	COLUMN NAME	MX_L1_LICENCIA_CONDUCIR
MX_L1_EFIRMA - Path	COLUMN NAME	MX_L1_EFIRMA
MX_L1_EFIRMA - Regex	VALUE FORMAT	MX_L1_EFIRMA
MX_L1_IP - Path	COLUMN NAME	MX_L1_IP
MX_L1_IP - Regex	VALUE FORMAT	MX_L1_IP
MX_L1_DISPOSITIVO - Path	COLUMN NAME	MX_L1_DISPOSITIVO
MX_L1_DISPOSITIVO - Regex	VALUE FORMAT	MX_L1_DISPOSITIVO
MX_L1_PLACA - Path	COLUMN NAME	MX_L1_PLACA
MX_L1_PLACA - Regex	VALUE FORMAT	MX_L1_PLACA
MX_L1_NIV - Path	COLUMN NAME	MX_L1_NIV
MX_L1_NIV - Regex	VALUE FORMAT	MX_L1_NIV
MX_L1_NUMERO_CONTRATO - Path	COLUMN NAME	MX_L1_NUMERO_CONTRATO
MX_L1_USUARIO_RRSS - Path	COLUMN NAME	MX_L1_USUARIO_RRSS
MX_L1_CREDENCIAL - Path	COLUMN NAME	MX_L1_CREDENCIAL
MX_L1_CREDENCIAL - Regex	VALUE FORMAT	MX_L1_CREDENCIAL
MX_L1_GEOLOCALIZACION - Path	COLUMN NAME	MX_L1_GEOLOCALIZACION
MX_L1_GEOLOCALIZACION - Regex	VALUE FORMAT	MX_L1_GEOLOCALIZACION
MX_L1_TEXTO_LIBRE - Path	COLUMN NAME	MX_L1_TEXTO_LIBRE
MX_L1_TEXTO_LIBRE - Type	DATA TYPE	MX_L1_TEXTO_LIBRE
MX_L1_TEXTO_LIBRE - Regex	VALUE FORMAT	MX_L1_TEXTO_LIBRE
MX_L2_FECHA_NACIMIENTO - Path	COLUMN NAME	MX_L2_FECHA_NACIMIENTO
MX_L2_FECHA_NACIMIENTO - Type	DATA TYPE	MX_L2_FECHA_NACIMIENTO
MX_L2_ANIO_NACIMIENTO - Path	COLUMN NAME	MX_L2_ANIO_NACIMIENTO
MX_L2_ANIO_NACIMIENTO - Type	DATA TYPE	MX_L2_ANIO_NACIMIENTO
MX_L2_EDAD - Path	COLUMN NAME	MX_L2_EDAD
MX_L2_EDAD - Type	DATA TYPE	MX_L2_EDAD
MX_L2_FECHA_EVENTO - Path	COLUMN NAME	MX_L2_FECHA_EVENTO
MX_L2_FECHA_EVENTO - Type	DATA TYPE	MX_L2_FECHA_EVENTO
MX_L2_SEXO - Path	COLUMN NAME	MX_L2_SEXO

CLASSIFIER	KIND	DATA CLASS
MX_L2_SEXO – List	KNOWN VALUES	MX_L2_SEXO
MX_L2_MUNICIPIO – Path	COLUMN NAME	MX_L2_MUNICIPIO
MX_L2_MUNICIPIO – Values	VALUE FORMAT	MX_L2_MUNICIPIO
MX_L2_CLAVE_MUNICIPIO – Path	COLUMN NAME	MX_L2_CLAVE_MUNICIPIO
MX_L2_CLAVE_MUNICIPIO – Type	DATA TYPE	MX_L2_CLAVE_MUNICIPIO
MX_L2_CLAVE_MUNICIPIO – Values	VALUE FORMAT	MX_L2_CLAVE_MUNICIPIO
MX_L2_LOCALIDAD – Path	COLUMN NAME	MX_L2_LOCALIDAD
MX_L2_COLONIA – Path	COLUMN NAME	MX_L2_COLONIA
MX_L2_CODIGO_POSTAL – Path	COLUMN NAME	MX_L2_CODIGO_POSTAL
MX_L2_CODIGO_POSTAL – Regex	VALUE FORMAT	MX_L2_CODIGO_POSTAL
MX_L2_NACIONALIDAD – Path	COLUMN NAME	MX_L2_NACIONALIDAD
MX_L2_NACIONALIDAD – Values	VALUE FORMAT	MX_L2_NACIONALIDAD
MX_L2_ESTADO_CIVIL – Path	COLUMN NAME	MX_L2_ESTADO_CIVIL
MX_L2_ESTADO_CIVIL – Values	VALUE FORMAT	MX_L2_ESTADO_CIVIL
MX_L2_OCUPACION – Path	COLUMN NAME	MX_L2_OCUPACION
MX_L2_EMPLEADOR – Path	COLUMN NAME	MX_L2_EMPLEADOR
MX_L2_ESCOLARIDAD – Path	COLUMN NAME	MX_L2_ESCOLARIDAD
MX_L2_ESCOLARIDAD – Values	VALUE FORMAT	MX_L2_ESCOLARIDAD
MX_L2_ESCUELA – Path	COLUMN NAME	MX_L2_ESCUELA
MX_L2_CCT – Path	COLUMN NAME	MX_L2_CCT
MX_L2_CCT – Regex	VALUE FORMAT	MX_L2_CCT
MX_L2_DEPENDIENTES – Path	COLUMN NAME	MX_L2_DEPENDIENTES
MX_L2_DEPENDIENTES – Type	DATA TYPE	MX_L2_DEPENDIENTES
MX_L3_ETNIA – Path	COLUMN NAME	MX_L3_ETNIA
MX_L3_ETNIA – Values	VALUE FORMAT	MX_L3_ETNIA
MX_L3_LENGUA_INDIGENA – Path	COLUMN NAME	MX_L3_LENGUA_INDIGENA
MX_L3_LENGUA_INDIGENA – Values	VALUE FORMAT	MX_L3_LENGUA_INDIGENA
MX_L3_SALUD_DIAGNOSTICO – Path	COLUMN NAME	MX_L3_SALUD_DIAGNOSTICO
MX_L3_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	MX_L3_SALUD_DIAGNOSTICO
MX_L3_SALUD_MEDICAMENTO – Path	COLUMN NAME	MX_L3_SALUD_MEDICAMENTO
MX_L3_SALUD_MEDICAMENTO – Values	VALUE FORMAT	MX_L3_SALUD_MEDICAMENTO
MX_L3_SALUD_IDENTIFICADOR – Path	COLUMN NAME	MX_L3_SALUD_IDENTIFICADOR
MX_L3_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	MX_L3_SALUD_TEXTO_CLINICO
MX_L3_SALUD_TEXTO_CLINICO – Type	DATA TYPE	MX_L3_SALUD_TEXTO_CLINICO
MX_L3_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	MX_L3_SALUD_RESULTADO_EXAMEN
MX_L3_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	MX_L3_SALUD_GRUPO_SANGUINEO
MX_L3_SALUD_GRUPO_SANGUINEO – Values	VALUE FORMAT	MX_L3_SALUD_GRUPO_SANGUINEO

CLASSIFIER	KIND	DATA CLASS
MX_L3_SALUD_DISCAPACIDAD – Path	COLUMN NAME	MX_L3_SALUD_DISCAPACIDAD
MX_L3_SALUD_DISCAPACIDAD – Values	VALUE FORMAT	MX_L3_SALUD_DISCAPACIDAD
MX_L3_SALUD_SEXUAL_REPRODUCTIVA – Path	COLUMN NAME	MX_L3_SALUD_SEXUAL_REPRODUCTIVA
MX_L3_SALUD_MENTAL_ADICCIONES – Path	COLUMN NAME	MX_L3_SALUD_MENTAL_ADICCIONES
MX_L3_BIOMETRICO – Path	COLUMN NAME	MX_L3_BIOMETRICO
MX_L3_BIOMETRICO – Type	DATA TYPE	MX_L3_BIOMETRICO
MX_L3_INFORMACION_GENETICA – Path	COLUMN NAME	MX_L3_INFORMACION_GENETICA
MX_L3_INFORMACION_GENETICA – Regex	VALUE FORMAT	MX_L3_INFORMACION_GENETICA
MX_L3_PREFERENCIA_SEXUAL – Path	COLUMN NAME	MX_L3_PREFERENCIA_SEXUAL
MX_L3_PREFERENCIA_SEXUAL – Values	VALUE FORMAT	MX_L3_PREFERENCIA_SEXUAL
MX_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	MX_L3_IDENTIDAD_GENERO
MX_L3_IDENTIDAD_GENERO – Values	VALUE FORMAT	MX_L3_IDENTIDAD_GENERO
MX_L3_VIDA_SEXUAL – Path	COLUMN NAME	MX_L3_VIDA_SEXUAL
MX_L3_RELIGION – Path	COLUMN NAME	MX_L3_RELIGION
MX_L3_RELIGION – Values	VALUE FORMAT	MX_L3_RELIGION
MX_L3_CREENCIA_FILOSOFICA_MORAL – Path	COLUMN NAME	MX_L3_CREENCIA_FILOSOFICA_MORAL
MX_L3_OPINION_POLITICA – Path	COLUMN NAME	MX_L3_OPINION_POLITICA
MX_L3_OPINION_POLITICA – Values	VALUE FORMAT	MX_L3_OPINION_POLITICA
MX_L3_AFILIACION_POLITICA – Path	COLUMN NAME	MX_L3_AFILIACION_POLITICA
MX_L3_AFILIACION_POLITICA – Values	VALUE FORMAT	MX_L3_AFILIACION_POLITICA
MX_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	MX_L3_AFILIACION_SINDICAL
MX_L3_AFILIACION_SINDICAL – Values	VALUE FORMAT	MX_L3_AFILIACION_SINDICAL
MX_FIN_BURO_CREDITO – Path	COLUMN NAME	MX_FIN_BURO_CREDITO
MX_FIN_MONTO_DEUDA – Path	COLUMN NAME	MX_FIN_MONTO_DEUDA
MX_FIN_MONTO_DEUDA – Type	DATA TYPE	MX_FIN_MONTO_DEUDA
MX_FIN_INGRESO_MENSUAL – Path	COLUMN NAME	MX_FIN_INGRESO_MENSUAL
MX_FIN_INGRESO_MENSUAL – Type	DATA TYPE	MX_FIN_INGRESO_MENSUAL
MX_FIN_SALARIO_DIARIO – Path	COLUMN NAME	MX_FIN_SALARIO_DIARIO
MX_FIN_SALARIO_DIARIO – Type	DATA TYPE	MX_FIN_SALARIO_DIARIO
MX_FIN_PATRIMONIO – Path	COLUMN NAME	MX_FIN_PATRIMONIO
MX_FIN_PATRIMONIO – Type	DATA TYPE	MX_FIN_PATRIMONIO
MX_FIN_AFORE – Path	COLUMN NAME	MX_FIN_AFORE
MX_FIN_AFORE – Values	VALUE FORMAT	MX_FIN_AFORE
MX_FIN_SALDO_RETIRO – Path	COLUMN NAME	MX_FIN_SALDO_RETIRO
MX_FIN_SALDO_RETIRO – Type	DATA TYPE	MX_FIN_SALDO_RETIRO
MX_FIN_CREDITO_VIVIENDA – Path	COLUMN NAME	MX_FIN_CREDITO_VIVIENDA
MX_FIN_CREDITO_VIVIENDA – Values	VALUE FORMAT	MX_FIN_CREDITO_VIVIENDA

CLASSIFIER	KIND	DATA CLASS
MX_FIN_SEGURIDAD_SOCIAL – Path	COLUMN NAME	MX_FIN_SEGURIDAD_SOCIAL
MX_FIN_SEGURIDAD_SOCIAL – Values	VALUE FORMAT	MX_FIN_SEGURIDAD_SOCIAL
MX_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	MX_FIN_PROGRAMA_SOCIAL
MX_FIN_PROGRAMA_SOCIAL – Values	VALUE FORMAT	MX_FIN_PROGRAMA_SOCIAL
MX_FIN_NIVEL_SOCIOECONOMICO – Path	COLUMN NAME	MX_FIN_NIVEL_SOCIOECONOMICO
MX_FIN_NIVEL_SOCIOECONOMICO – Values	VALUE FORMAT	MX_FIN_NIVEL_SOCIOECONOMICO
MX_FIN_VIVIENDA – Path	COLUMN NAME	MX_FIN_VIVIENDA
MX_FIN_VIVIENDA – Values	VALUE FORMAT	MX_FIN_VIVIENDA
MX_FIN_REGIMEN_FISCAL – Path	COLUMN NAME	MX_FIN_REGIMEN_FISCAL
MX_PENAL_ANTECEDENTES – Path	COLUMN NAME	MX_PENAL_ANTECEDENTES
MX_PENAL_CAUSA – Path	COLUMN NAME	MX_PENAL_CAUSA
MX_PENAL_CAUSA – Regex	VALUE FORMAT	MX_PENAL_CAUSA