DELPHIX CONTINUOUS COMPLIANCE · DISCOVERY POLICY

Panama — Ley 81 de 2019

Discovery and masking of Panamanian personal data: cédula and RUC with a valid check digit, quasi-identifiers, the sensitive data of article 4, economic and credit data, and criminal records.

76	137	138
DATA CLASSES	CLASSIFIERS	ALGORITHMS

Discovery policy `PA – Ley 81 de 2019 – v4`

Version 4 of October 12, 2026 · Assignment threshold 60%

Contents

The first sections explain what the policy is for and how it works. The data class chapters then describe every data class: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the policy contains.

1	**About this discovery policy**	
2	**Law 81 of 2019 at a glance**	
3	**How sensitive data is discovered**	
4	**How data is masked**	
5	**Essential and extended packs**	
6	**Data classes at a glance**	

PART 7 · DIRECT IDENTIFIERS

7.1	**Cédula (national ID)**	PA_L1_CEDULA
7.2	**RUC (taxpayer number)**	PA_L1_RUC
7.3	**DV in its own column**	PA_L1_RUC_DV
7.4	**Passport**	PA_L1_PASAPORTE
7.5	**Immigration document**	PA_L1_DOCUMENTO_MIGRATORIO
7.6	**Social security number**	PA_L1_SEGURO_SOCIAL
7.7	**Professional license (idoneidad)**	PA_L1_IDONEIDAD
7.8	**Given names**	PA_L1_NOMBRE
7.9	**Surnames**	PA_L1_APELLIDO
7.10	**Full name**	PA_L1_NOMBRE_COMPLETO
7.11	**E-mail**	PA_L1_EMAIL
7.12	**Phone**	PA_L1_TELEFONO
7.13	**Address**	PA_L1_DIRECCION
7.14	**Address detail**	PA_L1_DIRECCION_COMPLEMENTO
7.15	**Bank account**	PA_L1_CUENTA_BANCARIA
7.16	**Payment card**	PA_L1_TARJETA
7.17	**IP address**	PA_L1_IP
7.18	**Device identifier**	PA_L1_DISPOSITIVO
7.19	**License plate**	PA_L1_PLACA
7.20	**Vehicle identification number**	PA_L1_VIN
7.21	**Property number (finca)**	PA_L1_FINCA
7.22	**Contract or customer number**	PA_L1_NUMERO_CONTRATO
7.23	**User name or social network**	PA_L1_USUARIO_RRSS
7.24	**Credential**	PA_L1_CREDENCIAL
7.25	**Geolocation**	PA_L1_GEOLOCALIZACION

7.26	Free text	PA_L1_TEXTO_LIBRE

PART 8 · QUASI-IDENTIFIERS

8.1	Birth date	PA_L2_FECHA_NACIMIENTO
8.2	Birth year	PA_L2_ANIO_NACIMIENTO
8.3	Age	PA_L2_EDAD
8.4	Life event dates	PA_L2_FECHA_EVENTO
8.5	Sex	PA_L2_SEXO
8.6	District	PA_L2_DISTRITO
8.7	Corregimiento	PA_L2_CORREGIMIENTO
8.8	Corregimiento or district code	PA_L2_CODIGO_LUGAR
8.9	Populated place	PA_L2_LUGAR_POBLADO
8.10	Barriada or neighborhood	PA_L2_BARRIADA
8.11	Postal code	PA_L2_CODIGO_POSTAL
8.12	Nationality	PA_L2_NACIONALIDAD
8.13	Marital status	PA_L2_ESTADO_CIVIL
8.14	Occupation	PA_L2_OCUPACION
8.15	Employer	PA_L2_EMPLEADOR
8.16	Schooling	PA_L2_ESCOLARIDAD
8.17	School	PA_L2_ESCUELA
8.18	Children and dependents	PA_L2_DEPENDIENTES

PART 9 · SENSITIVE DATA

9.1	Ethnic origin	PA_L3_ETNIA
9.2	Indigenous language	PA_L3_LENGUA_INDIGENA
9.3	Diagnosis	PA_L3_SALUD_DIAGNOSTICO
9.4	Medication	PA_L3_SALUD_MEDICAMENTO
9.5	Clinical identifier	PA_L3_SALUD_IDENTIFICADOR
9.6	Clinical text	PA_L3_SALUD_TEXTO_CLINICO
9.7	Test result	PA_L3_SALUD_RESULTADO_EXAMEN
9.8	Blood group	PA_L3_SALUD_GRUPO_SANGUINEO
9.9	Disability	PA_L3_SALUD_DISCAPACIDAD
9.10	Sexual and reproductive health	PA_L3_SALUD_SEXUAL_REPRODUCTIVA
9.11	Mental health and addiction	PA_L3_SALUD_MENTAL_ADICCIONES
9.12	Biometric data	PA_L3_BIOMETRICO
9.13	Genetic data	PA_L3_INFORMACION_GENETICA
9.14	Sexual orientation	PA_L3_ORIENTACION_SEXUAL
9.15	Gender identity	PA_L3_IDENTIDAD_GENERO

9.16	Sexual life	PA_L3_VIDA_SEXUAL
9.17	Religion	PA_L3_RELIGION
9.18	Philosophical and moral beliefs	PA_L3_CREENCIA_FILOSOFICA_MORAL
9.19	Political opinion	PA_L3_OPINION_POLITICA
9.20	Political affiliation	PA_L3_AFILIACION_POLITICA
9.21	Union membership	PA_L3_AFILIACION_SINDICAL

PART 10 · ECONOMIC AND CREDIT DATA

10.1	Credit reference	PA_FIN_REFERENCIA_CREDITO
10.2	Debt amount	PA_FIN_MONTO_DEUDA
10.3	Salary and income	PA_FIN_INGRESO_MENSUAL
10.4	Assets	PA_FIN_PATRIMONIO
10.5	Pension and individual account	PA_FIN_PENSION
10.6	Social security coverage	PA_FIN_SEGURO_SOCIAL
10.7	Social program	PA_FIN_PROGRAMA_SOCIAL
10.8	Socioeconomic level	PA_FIN_NIVEL_SOCIOECONOMICO
10.9	Housing tenure	PA_FIN_VIVIENDA

PART 11 · CRIMINAL RECORDS

11.1	Criminal record	PA_PENAL_ANTECEDENTES
11.2	Case number	PA_PENAL_CAUSA
12	The RUC check digit, computed by the policy	
13	Where people live: districts and corregimientos	
14	Limits	
15	Verification	
16	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Discovery policy and classifiers	

1

About this discovery policy

This discovery policy finds the personal data in a Panamanian database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and cédulas does not get there: a birth date, a sex and a small corregimiento are enough to point at one person. The policy works on the same layers the risk is in:

- **Direct identifiers** — cédula, RUC and its DV, names, contact, accounts and cards, passport and immigration documents, professional licenses, property, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, district, corregimiento, barriada, postal code, occupation, employer, schooling.
- **Sensitive data** — ethnic origin and indigenous language, health, biometric and genetic data, religious, philosophical and moral beliefs, political opinions and affiliation, union membership, sexual orientation.
- **Economic and credit data** — APC credit references, debt, salary, assets, pensions, social security coverage, social programs, poverty, housing tenure.
- **Criminal records** — police records and case numbers.

In Data Control Tower the policy is one discovery policy with its classifiers, the data classes they vote for, the algorithms those data classes name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — `NOMBRE`, `RESULTADO`, `CIUDAD` — needs the values to agree. A column with a meaningless name (`CAMPO1`, `OBS`) is still found when its values have a recognizable shape or vocabulary: a cédula, a RUC with its DV, a plate, a corregimiento.

Column names are recognized in Spanish, in the abbreviations of Panamanian systems (`NUM_CEDULA`, `CIP`, `FEC_NAC`, `COD_CORREG`, `NIS`), in the fields of the electronic invoice (`dRuc`, `dDV`) and in English.

> Before masking, inventory the binary columns (BLOBs, images, PDFs). Onboarding processes often store a photo of the cédula: the number is still readable in the image. Report those columns as residual risk.

2

Law 81 of 2019 at a glance

Law 81 of 26 March 2019, on Personal Data Protection, was published in Gaceta Oficial 28743-A of 29 March 2019 and has been in force since 29 March 2021, two years after its enactment (art. 47). Executive Decree 285 of 28 May 2021 regulates it. The supervisory authority is the **National Authority for Transparency and Access to Information (ANTAI)**, through its Personal Data Protection Directorate.

What matters for a copy of production data:

- **Personal data** is any information concerning natural persons that identifies them or makes them identifiable (art. 4, 9). The law protects natural persons: a legal entity's data is outside its scope.
- **Sensitive data** is data that refers to the data subject's intimate sphere, or whose misuse may give rise to discrimination or carry a serious risk. As examples, not as a closed list, the law names data that may reveal racial or ethnic origin; religious, philosophical and moral beliefs or convictions; union membership; political opinions; data concerning health, life, sexual preference or orientation, genetic data or biometric data (art. 4, 11). Decree 285 defines biometric, genetic and health data (art. 4, 2 to 4).

- **Anonymized data is out of scope.** Processing of information obtained through a prior dissociation or anonymization procedure, such that the result cannot be associated with the data subject, is excluded from the law (art. 3, 5). *Dissociated data* cannot be associated with the data subject nor, by its structure, content or level of detail, allow their identification (art. 4, 10).
- **Purpose.** Data is used for the purposes it was authorized for; any other use needs consent, a special law or another legal basis (arts. 2, 2 and 11). Further processing for research or studies needs no consent when the data is anonymized (art. 12).
- **Health and sensitive data.** Consent for health data must be prior, irrefutable and express (art. 8; Decree 285, art. 18). Sensitive data may not be transferred save for exceptions, and for historical, statistical or scientific purposes it must be dissociated (art. 13).
- **Economic, financial, banking or commercial data** is processed with prior consent (art. 8, 3). Credit references also have a law of their own, Law 24 of 2002.
- **Criminal convictions** have their own disclosure rules (art. 30; Decree 285, art. 7).
- **Security.** Proportionate technical and organizational measures, especially for sensitive data (art. 2, 5; Decree 285, art. 36). A security breach is notified to ANTAI and to the affected data subjects within seventy-two hours (Decree 285, art. 37).
- **Sanctions.** Fines from one thousand to ten thousand balboas set by ANTAI (art. 36). Disregarding the rules on sensitive data is a very serious infringement, which can lead to closing the database's records or suspending the processing activity (arts. 41 and 43).

A test environment with production data is processing for a purpose the data subject did not authorize, and it holds sensitive and financial data outside the controls built for them. A copy that is effectively anonymized falls, under article 3, outside the law: that is what the policy is for.

The list of sensitive data is not exhaustive. The policy also treats gender identity and sexual life as sensitive, since they expose people to discrimination in the same way. Reform proposals are under discussion, among them higher fines; this document follows the text in force in September 2026.

> This document describes technical controls. Whether a copy counts as anonymized is a legal assessment of the whole environment — access, retention, what else it is combined with — not of the discovery policy alone.

3

How sensitive data is discovered

A discovery job looks at every column of its rule set and asks each classifier of the discovery policy how confident it is that the column belongs to its data class. The policy uses the four classifier frameworks of Delphix:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the data class out. It never assigns a data class on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per data class, and the column is assigned to the data class with the highest confidence when it reaches the assignment threshold of the discovery policy — **60%** here. Values that do not match a format or a list count against their data class by the classifier's reject strength.

These are the names Data Control Tower gives the objects: data classes, classifiers and a discovery policy, run by a discovery job. A Continuous Compliance Engine used on its own calls the same objects domains, classifiers and a profile set, run by a profiling job; everything in this document applies to both.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. Discovery tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Discovery proposes; it does not decide. Review the data classes assigned in the rule set before running a masking job, and look for columns the policy left unassigned.

4

How data is masked

Each data class names one algorithm, which a masking job applies to every column the rule set assigns to the data class. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each data class shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine and compliance node uses the same keys.

Where an algorithm that comes with Delphix already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the policy names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name, the one an engine uses; Data Control Tower lists them without the prefix (`CM Numeric`, `CreditCard`, `BloodType SL`). They are on every engine and in every Data Control Tower, and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. With other keys the masked values differ; their shape does not.

5

Essential and extended packs

The policy can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create just its data classes, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the discovery policy.

PACK	DATA CLASSES	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	27	59	10
Extended	76	137	138	57

The essential pack holds these data classes, marked **Essential** in the tables and chapters:

- Cédula (national ID) — `PA_L1_CEDULA`
- RUC (taxpayer number) — `PA_L1_RUC`
- DV in its own column — `PA_L1_RUC_DV`
- Passport — `PA_L1_PASAPORTE`
- Given names — `PA_L1_NOMBRE`
- Surnames — `PA_L1_APELLIDO`
- Full name — `PA_L1_NOMBRE_COMPLETO`
- E-mail — `PA_L1_EMAIL`
- Phone — `PA_L1_TELEFONO`
- Address — `PA_L1_DIRECCION`
- Address detail — `PA_L1_DIRECCION_COMPLEMENTO`
- Birth date — `PA_L2_FECHA_NACIMIENTO`

> With fewer data classes competing, a column that a data class of the extended pack would claim by its name can be proposed for an essential data class instead — a numeric code, for instance, can look like a telephone number. Review the discovery result.

6

Data classes at a glance

Every data class of the policy, how it is found and the algorithm that masks it.

DATA CLASS	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Cédula (national ID) ESSENTIAL `PA_L1_CEDULA`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PA_CEDULA`
RUC (taxpayer number) ESSENTIAL `PA_L1_RUC`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PA_RUC`
DV in its own column ESSENTIAL `PA_L1_RUC_DV`	COLUMN NAME · DATA TYPE	`PA_DV`
Passport ESSENTIAL `PA_L1_PASAPORTE`	COLUMN NAME · VALUE FORMAT	`PA_CM_ALFANUM`
Immigration document `PA_L1_DOCUMENTO_MIGRATORIO`	COLUMN NAME	`PA_CM_ALFANUM`
Social security number `PA_L1_SEGURO_SOCIAL`	COLUMN NAME	`PA_CM_ALFANUM`
Professional license (idoneidad) `PA_L1_IDONEIDAD`	COLUMN NAME	`PA_CM_ALFANUM`
Given names ESSENTIAL `PA_L1_NOMBRE`	COLUMN NAME · KNOWN VALUES	`PA_NOMBRES`
Surnames ESSENTIAL `PA_L1_APELLIDO`	COLUMN NAME · KNOWN VALUES	`PA_APELLIDOS`
Full name ESSENTIAL `PA_L1_NOMBRE_COMPLETO`	COLUMN NAME · KNOWN VALUES	`PA_NOMBRE_COMPLETO`
E-mail ESSENTIAL `PA_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PA_EMAIL`
Phone ESSENTIAL `PA_L1_TELEFONO`	COLUMN NAME · VALUE FORMAT	`PA_TELEFONO`
Address ESSENTIAL `PA_L1_DIRECCION`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PA_DIRECCION`
Address detail ESSENTIAL `PA_L1_DIRECCION_COMPLEMENTO`	COLUMN NAME	`PA_CM_ALFANUM`
Bank account `PA_L1_CUENTA_BANCARIA`	COLUMN NAME	`PA_CM_ALFANUM`
Payment card `PA_L1_TARJETA`	COLUMN NAME · VALUE FORMAT	`PA_TARJETA`
IP address `PA_L1_IP`	COLUMN NAME · VALUE FORMAT	`PA_IP`
Device identifier `PA_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`PA_CM_HEX`
License plate `PA_L1_PLACA`	COLUMN NAME · VALUE FORMAT	`PA_PLACA`

DATA CLASS	FOUND BY	ALGORITHM
Vehicle identification number `PA_L1_VIN`	COLUMN NAME · VALUE FORMAT	`PA_CM_ALFANUM`
Property number (finca) `PA_L1_FINCA`	COLUMN NAME	`PA_CM_ALFANUM`
Contract or customer number `PA_L1_NUMERO_CONTRATO`	COLUMN NAME	`PA_CM_ALFANUM`
User name or social network `PA_L1_USUARIO_RRSS`	COLUMN NAME	`PA_CM_ALFANUM`
Credential `PA_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`PA_REDACTAR`
Geolocation `PA_L1_GEOLOCALIZACION`	COLUMN NAME · VALUE FORMAT	`PA_COORDENADA`
Free text `PA_L1_TEXTO_LIBRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PA_TEXTO_LIBRE`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `PA_L2_FECHA_NACIMIENTO`	COLUMN NAME · DATA TYPE	`PA_FECHA_NACIMIENTO`
Birth year `PA_L2_ANIO_NACIMIENTO`	COLUMN NAME · DATA TYPE	`PA_ANIO`
Age `PA_L2_EDAD`	COLUMN NAME · DATA TYPE	`PA_EDAD`
Life event dates `PA_L2_FECHA_EVENTO`	COLUMN NAME · DATA TYPE	`PA_FECHA_EVENTO`
Sex `PA_L2_SEXO`	COLUMN NAME · KNOWN VALUES	`PA_SEXO`
District `PA_L2_DISTRITO`	COLUMN NAME · VALUE FORMAT	`PA_DISTRITO`
Corregimiento `PA_L2_CORREGIMIENTO`	COLUMN NAME · VALUE FORMAT	`PA_CORREGIMIENTO`
Corregimiento or district code `PA_L2_CODIGO_LUGAR`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PA_CODIGO_LUGAR`
Populated place `PA_L2_LUGAR_POBLADO`	COLUMN NAME	`PA_LUGAR_POBLADO`
Barriada or neighborhood `PA_L2_BARRIADA`	COLUMN NAME	`PA_BARRIADA`
Postal code `PA_L2_CODIGO_POSTAL`	COLUMN NAME · VALUE FORMAT	`PA_CODIGO_POSTAL`
Nationality `PA_L2_NACIONALIDAD`	COLUMN NAME · VALUE FORMAT	`PA_NACIONALIDAD`
Marital status `PA_L2_ESTADO_CIVIL`	COLUMN NAME · VALUE FORMAT	`PA_ESTADO_CIVIL`
Occupation `PA_L2_OCUPACION`	COLUMN NAME	`PA_OCUPACION`
Employer `PA_L2_EMPLEADOR`	COLUMN NAME	`PA_EMPLEADOR`

DATA CLASS	FOUND BY	ALGORITHM
Schooling `PA_L2_ESCOLARIDAD`	COLUMN NAME VALUE FORMAT	`PA_ESCOLARIDAD`
School `PA_L2_ESCUELA`	COLUMN NAME	`PA_ESCUELA`
Children and dependents `PA_L2_DEPENDIENTES`	COLUMN NAME DATA TYPE	`PA_CANTIDAD_ACOTADA`
SENSITIVE DATA		
Ethnic origin `PA_L3_ETNIA`	COLUMN NAME VALUE FORMAT	`PA_PUEBLO`
Indigenous language `PA_L3_LENGUA_INDIGENA`	COLUMN NAME VALUE FORMAT	`PA_LENGUA_INDIGENA`
Diagnosis `PA_L3_SALUD_DIAGNOSTICO`	COLUMN NAME VALUE FORMAT	`PA_DIAGNOSTICO`
Medication `PA_L3_SALUD_MEDICAMENTO`	COLUMN NAME VALUE FORMAT	`PA_MEDICAMENTO`
Clinical identifier `PA_L3_SALUD_IDENTIFICADOR`	COLUMN NAME	`PA_CM_ALFANUM`
Clinical text `PA_L3_SALUD_TEXTO_CLINICO`	COLUMN NAME DATA TYPE	`PA_TEXTO_LIBRE`
Test result `PA_L3_SALUD_RESULTADO_EXAMEN`	COLUMN NAME	`PA_CM_ALFANUM`
Blood group `PA_L3_SALUD_GRUPO_SANGUINEO`	COLUMN NAME VALUE FORMAT	`dlpx-core:BloodType SL`
Disability `PA_L3_SALUD_DISCAPACIDAD`	COLUMN NAME VALUE FORMAT	`PA_DISCAPACIDAD`
Sexual and reproductive health `PA_L3_SALUD_SEXUAL_REPRODUCTIVA`	COLUMN NAME	`PA_CATEGORIA_SUPRIMIDA`
Mental health and addiction `PA_L3_SALUD_MENTAL_ADICCIONES`	COLUMN NAME	`PA_CATEGORIA_SUPRIMIDA`
Biometric data `PA_L3_BIOMETRICO`	COLUMN NAME DATA TYPE	`PA_REDACTAR`
Genetic data `PA_L3_INFORMACION_GENETICA`	COLUMN NAME VALUE FORMAT	`PA_REDACTAR`
Sexual orientation `PA_L3_ORIENTACION_SEXUAL`	COLUMN NAME VALUE FORMAT	`PA_ORIENTACION_SEXUAL`
Gender identity `PA_L3_IDENTIDAD_GENERO`	COLUMN NAME VALUE FORMAT	`PA_IDENTIDAD_GENERO`
Sexual life `PA_L3_VIDA_SEXUAL`	COLUMN NAME	`PA_CATEGORIA_SUPRIMIDA`
Religion `PA_L3_RELIGION`	COLUMN NAME VALUE FORMAT	`PA_RELIGION`
Philosophical and moral beliefs `PA_L3_CREENCIA_FILOSOFICA_MORAL`	COLUMN NAME	`PA_CATEGORIA_SUPRIMIDA`
Political opinion `PA_L3_OPINION_POLITICA`	COLUMN NAME VALUE FORMAT	`PA_OPINION_POLITICA`

DATA CLASS	FOUND BY	ALGORITHM
Political affiliation `PA_L3_AFILIACION_POLITICA`	COLUMN NAME VALUE FORMAT	`PA_PARTIDO_POLITICO`
Union membership `PA_L3_AFILIACION_SINDICAL`	COLUMN NAME VALUE FORMAT	`PA_CATEGORIA_SUPRIMIDA`
ECONOMIC AND CREDIT DATA		
Credit reference `PA_FIN_REFERENCIA_CREDITO`	COLUMN NAME	`PA_APC`
Debt amount `PA_FIN_MONTO_DEUDA`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Salary and income `PA_FIN_INGRESO_MENSUAL`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Assets `PA_FIN_PATRIMONIO`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Pension and individual account `PA_FIN_PENSION`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Social security coverage `PA_FIN_SEGURO_SOCIAL`	COLUMN NAME VALUE FORMAT	`PA_SEGURO_SOCIAL`
Social program `PA_FIN_PROGRAMA_SOCIAL`	COLUMN NAME VALUE FORMAT	`PA_PROGRAMA_SOCIAL`
Socioeconomic level `PA_FIN_NIVEL_SOCIOECONOMICO`	COLUMN NAME VALUE FORMAT	`PA_NIVEL_SOCIOECONOMICO`
Housing tenure `PA_FIN_VIVIENDA`	COLUMN NAME VALUE FORMAT	`PA_VIVIENDA`
CRIMINAL RECORDS		
Criminal record `PA_PENAL_ANTECEDENTES`	COLUMN NAME	`PA_ANTECEDENTES`
Case number `PA_PENAL_CAUSA`	COLUMN NAME VALUE FORMAT	`PA_CM_ALFANUM`

PART 7

Direct identifiers

Data that identifies a person on its own. The cédula is the key of almost every Panamanian record: it is a natural person's RUC, the number of their driver's license and their identification at the Social Security Fund. It is masked the same way everywhere, and the RUC keeps a valid check digit, because applications validate it.

7.1 Cédula (national ID)

PA_L1_CEDULA

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The number of the identity card issued by the Electoral Tribunal: province of birth (1 to 13; 10, 11 and 12 are the Guna Yala, Emberá-Wounaan and Ngäbe-Buglé comarcas), tomo and asiento of the civil registry entry. `8-442-445`. Letters mark other cases: `E` resident foreigner, `N` naturalized, `PE` Panamanian born abroad, `AV` registered before the civil registry law, `PI` indigenous Panamanian; `8-NT-12-3456` is the tax number of someone without a cédula. In Panama the driver's license carries the cédula number, so license columns fall here too.

HOW IT IS FOUND

COLUMN NAME PA_L1_CEDULA – Path

90%	`cedula[a-z0-9_]*` `c[eé]dula` `ced` `cip` `n(o|um|ro|umero)_?(de_?)?cedula` `cedula_?(identidad|personal|cliente|empleado|paciente|asegurado|beneficiario|titular|conyuge|acudiente)` `(cliente|empleado|paciente|asegurado|beneficiario|titular)_?cedula` `documento_?(de_?)?identidad` `doc_?identidad` `id_?personal` `identificacion_?personal` `n(o|um|ro)_?identificacion` `numero_?documento` `num_?doc` `nro_?doc` `national_?id` `dni`
80%	`licencia_?(de_?)?(conducir|manejo|chofer|conductor)` `n(o|um|ro)_?licencia(_?conducir)?` `licencia` `driver_?license` `drivers_?license`

DATA TYPE PA_L1_CEDULA – Type

Accepts text (length 5 or more); any other type rules the data class out.

VALUE FORMAT PA_L1_CEDULA – Regex

PATTERN	STRENGTH	NOTES
`(?!\d{1,2}-\d{1,2}-(19|20)\d{2}$)(([1-9]|1[0-3])(AV|PI)?|E|N|PE)-\d{1,4}-\d{1,6}`	100%	
`0*(?:([1-9]|1[0-3])-NT-\d{1,4}-\d{1,6})`	90%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The province becomes another province between 1 and 13, and tomo and asiento are mapped digit by digit keeping their length; the letters stay, and so does the document type. The mapping is one-to-one: a cédula used as a key does not collide. The same algorithm masks the cédula inside the RUC, so a person's cédula and RUC still agree. Text that is not shaped like a cédula is masked character by character.

`PA_CEDULA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

`PA_PROVINCIA_CEDULA` NUMERIC MAPPING

Maps the number to another between 1 and 13.

`PA_CM_ALFANUM` CHARACTER MAPPING

> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
8–442–445	→	**1–433–300**
E–8–123456	→	**E–1–904292**
4PI–234–123	→	**8PI–158–957**

7.2 RUC (taxpayer number)

PA_L1_RUC

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The DGI's Single Taxpayer Registry number. A natural person's RUC is their cédula, with a two-digit check digit next to it: `8–442–445 DV 08`. A legal entity's RUC is its Public Registry number: `155596713–2–2015 DV 59`. One column often mixes both.

HOW IT IS FOUND

> **COLUMN NAME** PA_L1_RUC – Path
>
> **90%** `ruc[a-z0-9_]*` `d_?ruc` `n(o|um|ro|umero)_?(de_?)?ruc` `registro_?unico(_?de)?(_?contribuyentes?)?` `ruc_?(cliente|proveedor|emisor|receptor|contribuyente|persona|natural|empleado|beneficiario|titular)` `(cliente|proveedor|emisor|receptor)_?ruc` `tax_?id` `id_?fiscal` `nit`

> **DATA TYPE** PA_L1_RUC – Type
>
> Accepts text (length 5 or more); any other type rules the data class out.

> **VALUE FORMAT** PA_L1_RUC – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(?:(?:[1-9]|1[0-3])(?:AV|PI)?-\d{1,4}-\d{1,6}|(?:E|N|PE)-\d{1,4}-\d{1,6})(?:+DV +| +DV|-| +)\d{2})`	100%	
`(?!\d{1,2}-\d{1,2}-(19|20)\d{2}$)(([1-9]|1[0-3])(AV|PI)?|E|N|PE)-\d{1,4}-\d{1,6}`	60%	
`0*(?:\d{3,10}-\d{1,4}-\d{1,7}(\s*DV\s*\d{2})?)`	60%	

> A value that matches none counts 20% against the data class.

HOW IT IS MASKED

A natural person's RUC is masked as their cédula and the DV is recomputed, so every masked RUC passes DGI validation. The separators `DV`, `DV`, `–` and a space are recognized. A legal entity's RUC stays as it is: it is not personal data under article 4, and keeping it keeps joins with supplier catalogs working. See *The RUC check digit, computed by the policy*.

`PA_RUC` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

> `PA_RUC_DV` STRING ALGORITHM CHAIN
>
> Applies `PA_RUC_DV_1` → `PA_RUC_DV_2` → `PA_RUC_DV_3` → `PA_RUC_DV_4` → `PA_RUC_DV_5`, in this order. It is made of 46 algorithms that repeat the same step position by position; each one is in Appendix A.
>
> `PA_CEDULA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

EXAMPLES

VALUE		MASKED
8-442-445 DV 08	→	**1-433-300 DV 12**
1AV-432-658 DV 96	→	**9AV-920-061 DV 24**
155596713-2-2015 DV 59	→	**155596713-2-2015 DV 59**

7.3 DV in its own column

PA_L1_RUC_DV

ESSENTIAL · COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The RUC check digit kept apart, as in the electronic invoice (`dDV`) or a `DV` column.

HOW IT IS FOUND

> **COLUMN NAME** PA_L1_RUC_DV – Path
>
> **90%** `dv` `d_?dv` `digito_?verificador` `dig_?verif` `dv_?ruc` `ruc_?dv` `check_?digit`

> **DATA TYPE** PA_L1_RUC_DV – Type
>
> Accepts text (length up to 3) or number (length up to 2); any other type rules the data class out.

HOW IT IS MASKED

The two digits are mapped. They cannot be recomputed: an algorithm sees one column, and the RUC is in another. Masking it keeps it from helping link the row to the real RUC.

`PA_DV` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM` .

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
08	→	**02**

7.4 Passport

PA_L1_PASAPORTE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Panamanian and foreign passport numbers.

HOW IT IS FOUND

> **COLUMN NAME** PA_L1_PASAPORTE – Path
>
> **85%** `pasaporte[a-z_]*` `passport[a-z_]*` `n(o|um|ro|umero)_?pasaporte` `pasap`

> **VALUE FORMAT** PA_L1_PASAPORTE – Regex
>
> | PATTERN | STRENGTH | NOTES |
> |---|---|---|
> | `[A-Z]{1,2}\d{6,8}` | 30% | |
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PA0123456	→	**PU0730277**

7.5 Immigration document

PA_L1_DOCUMENTO_MIGRATORIO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Resident cards, residence and work permits, visas and foreign identification numbers. A permanent resident's `E` cédula is in the cédula data class.

HOW IT IS FOUND

COLUMN NAME PA_L1_DOCUMENTO_MIGRATORIO — Path

80% `carne_?(migratorio|de_?migracion|residente|de_?residente|residencia|refugiado|trabajo)` `carnet_?(migratorio|residente|residencia)` `permiso_?(de_?)?(residencia|trabajo|migratorio)` `n(o|um|ro)_?carne(t)?` `documento_?migratorio` `doc_?migratorio` `filiacion_?migratoria` `visa` `n(o|um|ro)_?visa` `id_?extranjero` `documento_?extranjero` `identificacion_?extranjera`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456789	→	**110858568**

7.6 Social security number

PA_L1_SEGURO_SOCIAL

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The insured person's or card number of the Social Security Fund (CSS) kept by older systems. Today the CSS identifies the insured by their cédula.

HOW IT IS FOUND

COLUMN NAME PA_L1_SEGURO_SOCIAL — Path

85% `n(o|um|ro|umero)_?(de_?)?seguro_?social` `seguro_?social_?(num|no|nro|numero)` `nss` `n(o|um|ro)_?css` `css_?(num|no|numero|asegurado)` `n(o|um|ro)_?asegurado` `num_?asegurado` `n(o|um|ro)_?(de_?)?afiliado(_?css)?` `carne_?(del_?)?seguro(_?social)?` `ss_?number` `social_?security`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123–4567	→	**564–9285**

7.7 Professional license (idoneidad) PA_L1_IDONEIDAD

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The idoneidad number that allows someone to practice a regulated profession — medicine, nursing, law, engineering. The registries are public: the number leads straight to the person's name.

HOW IT IS FOUND

> COLUMN NAME PA_L1_IDONEIDAD – Path
>
> 85% `idoneidad` `n(o|um|ro|umero)_?(de_?)?idoneidad` `registro_?(medico|profesional|de_?idoneidad)` `licencia_?profesional` `codigo_?(medico|profesional)` `colegiatura` `n(o|um|ro)_?registro_?profesional`

HOW IT IS MASKED

Character by character, keeping the length.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345	→	**31564**

7.8 Given names PA_L1_NOMBRE

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

First and middle names (`NOMBRES` , `PRIMER_NOMBRE`), including compound names such as `Luis Carlos` .

HOW IT IS FOUND

> COLUMN NAME PA_L1_NOMBRE – Path
>
> 85% `primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `nombre_?usual` `first_?name` `given_?names?` `fname` `name_?first` `middle_?name` `nombre[12]` `nombres` *(except when followed by list E1)* `nom_?(pila|trab|emp)`
>
> 50% `nombre` *(except when followed by list E2)* `nomb?` *(except when followed by list E3)* `name` *(except when followed by list E4)*

KNOWN VALUES PA_L1_NOMBRE — List

LIST	VALUES	STRENGTH	FIRST VALUES
pa-detectar-nombres.txt	291	70%	María, Maria, José, Jose, Luis, Carlos

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each word is replaced by a name from a list of 253 names used in Panama, keeping the number of words and the case. More than three words are masked character by character.

PA_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: PA_CM_ALFANUM.

PA_NOMBRE_PILA NAME

Replaces the name with one of the 253 names in pa-nombres.txt.

PA_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Luis Carlos	→	Teodoro Norberto
YAMILETH	→	ZULEIKA

7.9 Surnames

PA_L1_APELLIDO

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Paternal and maternal surnames, in one column or two, and a married woman's surname: González de Pérez.

HOW IT IS FOUND

COLUMN NAME PA_L1_APELLIDO — Path

85% apellidos? apellido_?(paterno|materno|pat|mat|uno|dos|casada|de_?casada|[12]) ape_?(pat|mat|paterno|materno|casada|[12]) apepat apemat ap_?(pat|mat|paterno|materno) a_?paterno a_?materno paterno materno primer_?apellido segundo_?apellido apellido_?usual last_?name surname lname family_?name second_?last_?name married_?name

KNOWN VALUES PA_L1_APELLIDO — List

LIST	VALUES	STRENGTH	FIRST VALUES
pa-detectar-apellidos.txt	258	70%	Rodríguez, Rodriguez, González, Gonzalez, Sánchez, Sanchez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each surname is replaced by one from a list of 200 surnames common in Panama — led by Rodríguez, González, Sánchez, Martínez, Castillo and Ábrego —, keeping the number of words and the case. The de of a married surname stays.

PA_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: PA_CM_ALFANUM.

`PA_APELLIDO` NAME

Replaces the name with one of the 200 names in `pa-apellidos.txt`.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
González de Pérez	→	**Tapia de Aguilar**

7.10 Full name

PA_L1_NOMBRE_COMPLETO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column, in Panamanian order, with `de` and the husband's surname where present, or as `APELLIDOS, NOMBRES`. Also the name of an account holder, beneficiary, insured person or guardian (*acudiente*).

HOW IT IS FOUND

COLUMN NAME PA_L1_NOMBRE_COMPLETO – Path

90% `nombre_?(completo|compl|full)` `nombres?_?y_?apellidos?` `nombres?_?apellidos?` `nombreapellido` `nom_?completo` `nomcompleto` `nombrecompleto` `full_?name` `fullname` `person_?name` `customer_?name` `employee_?name` `patient_?name` `nombre_?(cliente|cte|cli|paciente|pac|trabajador|trab|empleado|colaborador|funcionario|servidor_?publico|alumno|estudiante|afiliado|asegurado|cotizante|jubilado|pensionado|beneficiario|benef|titular|madre|padre|acudiente|tutor|conyuge|pareja|medico|doctor|profesional|responsable|contacto|emergencia|fiador|codeudor|deudor|remitente|destinatario|receptor|firmante|testigo|representante|apoderado|propietario|arrendatario|inquilino|contratante|victima|denunciante|imputado|socio|donante|heredero|persona|pers|conductor|chofer|vendedor|ejecutivo|agente|solicitante|ciudadano|elector|votante|contribuyente|jefe_?(de_?)?hogar|hijo|hija|familiar|dependiente)`

60% `titular` `beneficiario` `acudiente` `contacto_?emergencia` `conyuge` `tutor_?legal` `representante_?legal` `apoderado` `paciente` `victima` `asegurado` `contratante` `fiador` `codeudor` `jubilado` `pensionado`

50% `nombre` *(except when followed by list E2)* `name` *(except when followed by list E4)*

KNOWN VALUES PA_L1_NOMBRE_COMPLETO – List

LIST	VALUES	STRENGTH	FIRST VALUES
`pa-detectar-nombres.txt`	291	65%	María, Maria, José, Jose, Luis, Carlos
`pa-detectar-apellidos.txt`	258	65%	Rodríguez, Rodriguez, González, Gonzalez, Sánchez, Sanchez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Given names become given names and surnames become surnames, by position: one word is a given name, two are a given name and a surname, three are a given name and two surnames, four are two given names

and two surnames. `María Elena González de Pérez` keeps its `de` and its structure. A comma separates surnames from given names.

`PA_NOMBRE_COMPLETO` REGEX DECOMPOSE

Tries 8 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

> `PA_APELLIDOS` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.
>
> > `PA_APELLIDO` NAME
> >
> > Replaces the name with one of the 200 names in `pa-apellidos.txt`.
> >
> > `PA_CM_ALFANUM` CHARACTER MAPPING
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_NOMBRES` REGEX DECOMPOSE
>
> Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.
>
> > `PA_NOMBRE_PILA` NAME
> >
> > Replaces the name with one of the 253 names in `pa-nombres.txt`.

EXAMPLES

VALUE		MASKED
`María Elena González de Pérez`	→	**Édgar Evelyn Tapia de Aguilar**
`SÁNCHEZ ÁBREGO, LUIS CARLOS`	→	**VALDÉS BATISTA, TEODORO NORBERTO**

7.11 E-mail

PA_L1_EMAIL

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

> COLUMN NAME PA_L1_EMAIL – Path
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electronico)?[a-z0-9_]*` `email_?address` `correo_?(personal|laboral|contacto|receptor|cliente)`

> DATA TYPE PA_L1_EMAIL – Type
>
> Accepts text (length 5 or more); any other type rules the data class out.

> VALUE FORMAT PA_L1_EMAIL – Regex

PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	

> A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes `.test`, reserved for testing: a masked address never receives mail.

`PA_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
yamileth.gonzalez@gmail.com	→	**tificefk.yedsiquv@pgoeb.test**

7.12 Phone

PA_L1_TELEFONO

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Seven-digit landlines (`223–4567`) and eight-digit mobiles starting with 6 (`6123–4567`), with or without `+507` . Panama has no area codes.

HOW IT IS FOUND

COLUMN NAME PA_L1_TELEFONO – Path

85% `tel` `telefono[a-z0-9_]*` `tel[eé]fono` `tel_?(cel|casa|residencia|oficina|trabajo|movil|contacto|fijo|emergencia)` `celular[a-z0-9_]*` `cel` `movil` `m[oó]vil` `whatsapp` `wa` `fax` `phone[a-z0-9_]*` `mobile` `cellphone` `n(o|um|ro)_?tel(efono)?` `telef` `tlf` `extension`

VALUE FORMAT PA_L1_TELEFONO – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(\+?\(?507\)?[\s\-]?)?6\d{3}[\s\-]?\d{4})`	90%	
`0*(?:(\+?\(?507\)?[\s\-]?)?[2-9]\d{2}[\s\-]?\d{4})`	70%	
`0*(?:\+?\d[\d\s()\-]{6,15})`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

`+507` , the separators and the first digit — the 6 of a mobile, the region of a landline — stay; the rest is masked digit by digit. A number not shaped like a Panamanian number is masked whole.

`PA_TELEFONO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM` .

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+507 6123–4567	→	**+507 6957–9910**
223–4567	→	**246–9910**

7.13 Address

PA_L1_DIRECCION

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

The address line as written in Panama, which rarely has a street number: street or road, building, floor and apartment, or barriada, street and house.

HOW IT IS FOUND

COLUMN NAME PA_L1_DIRECCION — Path

80% `direccion[a-z_]*` *(except when followed by list E5)* `direcci[oó]n` `dir` `domicilio[a-z_]*` `calle(_?y_?casa)?` `avenida` `address` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`)* `street` `addr` `dir_?(residencial|residencia|particular|comercial|laboral|envio|entrega|facturacion|cliente|pacient e|trabajo)` `residencia` `lugar_?(de_?)?residencia` `home_?address` `ubicacion_?(domicilio|vivienda)` `senas` `punto_?de_?referencia`

DATA TYPE PA_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the data class out.

VALUE FORMAT PA_L1_DIRECCION — Regex

PATTERN	STRENGTH	NOTES
`(?i)(v[ií]a|ave?\.?|avenida|calle|c\.|carretera|paseo|boulevard|blvd\.? |corredor|camino)\s+.+`	70%	
`(?i).*(edificio|edif\.?|torre|ph)\s+.+(piso|apto\.? |apartamento|oficina|local)\s*\w+.*`	80%	
`(?i).*(barriada|urbanizaci[oó]n|urb\.|residencial|sector|manzana)\s+.+ (casa|lote)\s*(n[oº°]\.?\s*)?\w+.*`	80%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

It is replaced by one of 3,000 fictitious Panamanian addresses, with common streets, roads, barriadas and buildings in realistic proportions.

`PA_DIRECCION` SECURE LOOKUP

Replaces the value with one of the 3,000 values in `pa-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Calle 50, Edificio Global Bank, Piso 21, Oficina 2104`	→	**`Las Cumbres, Casa No. 242`**

7.14 Address detail

PA_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

House, apartment, floor, building, tower or lot numbers in columns of their own.

HOW IT IS FOUND

COLUMN NAME PA_L1_DIRECCION_COMPLEMENTO — Path

70% `n(o|um|ro|umero)_?casa` `casa_?(num|no|numero)` `apto` `apartamento` `n(o|um|ro)_?apto` `piso` `edificio` `torre` `ph` `lote` `manzana` `local` `oficina_?num` `house_?number` `apartment` `apt` `unit_?number` `floor`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Casa 23	→	**Miya 82**

7.15 Bank account

PA_L1_CUENTA_BANCARIA

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Checking, savings and payroll account numbers, in each bank's formats.

HOW IT IS FOUND

COLUMN NAME PA_L1_CUENTA_BANCARIA — Path

85% `cuenta_?` `(bancaria|banco|corriente|ahorro|ahorros|deposito|abono|pago|destino|origen|planilla|debito|ach|plazo_?fijo)` `cta_?(bancaria|banco|corriente|ahorro|planilla|ach)` `n(o|um|ro|umero)?_?(de_?)?cuenta(_?(banco|bancaria|corriente|ahorro|ach))?` `account_?(number|no|num|nbr)` `bank_?account` `num_?cta` `no_?cta` `iban`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
04-72-01-123456-7	→	**08-16-12-393050-4**

7.16 Payment card

PA_L1_TARJETA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Credit, debit and prepaid card numbers, including the Tarjeta Clave Social through which MIDES pays its programs.

HOW IT IS FOUND

COLUMN NAME PA_L1_TARJETA — Path

85% `tarjeta(_?(credito|debito|cred|deb|num|no|numero|bancaria|clave|clave_?social|prepago))?` `clave_?social` `n(o|um|ro|umero)_?tarjeta` `pan` `card_?(number|no|num)` `credit_?card` `cc_?(number|num)` `tdc` `tdd` `num_?tdc` `plastico`

VALUE FORMAT PA_L1_TARJETA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1-9]\d{12,13}|[1-9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Credit Card, which comes with Delphix: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`PA_TARJETA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with Delphix and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
`4916 3131 2345 6780`	→	**`4916 3196 4606 3896`**

7.17 IP address

PA_L1_IP

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses of users and devices.

HOW IT IS FOUND

> COLUMN NAME PA_L1_IP – Path
>
> 85% `ip` `ip_?`
> `(address|addr|origen|destino|cliente|usuario|remota|publica|privada|acceso|conexion|login)`
> `direccion_?ip` `dir_?ip` `ipv[46]` `remote_?addr` `client_?ip` `host_?ip`

> VALUE FORMAT PA_L1_IP – Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each IPv4 octet is mapped to a number from 1 to 254; an IPv6 address is mapped as hexadecimal.

`PA_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_HEX`.

> `PA_OCTET0` NUMERIC MAPPING
>
> Maps the number to another between 1 and 254.
>
> `PA_CM_HEX` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`190.140.22.10`	→	**`164.230.40.16`**

7.18 Device identifier

PA_L1_DISPOSITIVO

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, advertising and session identifiers, equipment serial numbers.

HOW IT IS FOUND

COLUMN NAME PA_L1_DISPOSITIVO – Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `direccion_?mac` `device_?id` `id_?dispositivo` `dispositivo_?id` `uuid_?dispositivo` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `id_?sesion` `serie_?equipo` `n(o|um|ro)_?serie_?(equipo|celular|telefono)`

VALUE FORMAT PA_L1_DISPOSITIVO – Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Hex stays hex and digits stay digits, so the value keeps its format.

`PA_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`3c:22:fb:9a:10:e4`	→	**`5e:83:bb:3c:31:f9`**

7.19 License plate

PA_L1_PLACA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Plates in the format used since 2013, two letters and four digits (`AB1234`), the earlier six-digit ones, and category plates: `M` motorcycle, `T` taxi, `B` bus, `G` government, `CD` diplomatic corps, `PR` press and others.

HOW IT IS FOUND

COLUMN NAME PA_L1_PLACA – Path

85% `placas?(_?(vehiculo|auto|circulacion|vehicular|num|no|numero))?` `n(o|um|ro)_?placas?` `matricula(_?(vehiculo|auto|vehicular))?` `license_?plate` `plate(_?number)?` `registro_?vehicular` `revisado`

VALUE FORMAT PA_L1_PLACA – Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{2}[\s\-]?\d{4}`	80%	
`(ADM|MB|MI|PR|BC|CD|CC|M|T|B|G|D|E)[\s\-]?\d{3,6}`	70%	
`0*(?:\d{6})`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Serial letters and digits are mapped; category letters stay, so a taxi plate is still a taxi plate.

`PA_PLACA` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AB1234	→	**EX9707**
T12345	→	**T31564**

7.20 Vehicle identification number

PA_L1_VIN

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The VIN, and engine and chassis numbers.

HOW IT IS FOUND

> COLUMN NAME PA_L1_VIN — Path
>
> 80% `vin` `n(o|um|ro|umero)_?(de_?)?(serie|identificacion)_?(vehicular|vehiculo)` `serie_?vehicul(o|ar)` `n(o|um|ro)_?serie` `numero_?serie` `n(o|um|ro)_?motor` `chasis` `n(o|um|ro)_?chasis` `vin_?number`

> VALUE FORMAT PA_L1_VIN — Regex
>
PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3VWFE21C04M000001	→	**7VVCU97M86J091175**

7.21 Property number (finca)

PA_L1_FINCA

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

A property's finca number, folio real or cadastral location code. The Public Registry can be searched by anyone: the finca leads to its owner.

HOW IT IS FOUND

COLUMN NAME PA_L1_FINCA — Path

85% `finca` `n(o|um|ro|umero)_?(de_?)?finca` `folio_?real` `codigo_?(de_?)?ubicacion` `numero_?catastral` `n(o|um|ro)_?catastro` `catastro` `inmueble_?(num|no|numero|registro)` `registro_?(de_?la_?)?propiedad`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
30162456	→	**39020887**

7.22 Contract or customer number

PA_L1_NUMERO_CONTRATO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Contract, policy, loan, customer, employee, payroll or claim numbers, and the electricity service's NIS.

HOW IT IS FOUND

COLUMN NAME PA_L1_NUMERO_CONTRATO — Path

70% `contrato` `n(o|um|ro|umero)_?contrato` `p[oó]liza` `n(o|um|ro|umero)_?poliza` `n(o|um|ro)_?(de_?)?(prestamo|credito|hipoteca)` `n(o|um|ro)_?operacion` `n(o|um|ro|umero)_?(de_?)?socio` `n(o|um|ro|umero)_?(de_?)?cliente` `id_?cliente` `cod(igo)?_?cliente` `nis` `n(o|um|ro)_?(de_?)?medidor` `n(o|um|ro|umero)_?(de_?)?empleado` `num_?emp` `no_?emp` `n(o|um|ro)_?planilla` `posicion_?planilla` `n(o|um|ro)_?siniestro` `n(o|um|ro)_?(de_?)?matricula` `n(o|um|ro)_?expediente_?(cliente|laboral|personal)` `folio_?(contrato|poliza|credito|cliente)`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
POL-123456	→	**MIF-194239**

7.23 User name or social network

PA_L1_USUARIO_RRSS

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

User names, aliases and social network profiles.

HOW IT IS FOUND

COLUMN NAME PA_L1_USUARIO_RRSS – Path

70% `usuario` `username` `user_?name` `login` `nick(name)?` `alias` `cuenta_?usuario` `usr` `facebook` `instagram` `twitter` `tiktok` `linkedin` `red_?social` `perfil_?(facebook|instagram|twitter|linkedin|tiktok)` `telegram` `handle`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@yami_gonzalez`	→	`@denu_colwawem`

7.24 Credential

PA_L1_CREDENCIAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Passwords, PINs, password hashes, tokens and API keys.

HOW IT IS FOUND

COLUMN NAME PA_L1_CREDENCIAL – Path

90% `password` `passwd` `pwd` `pass` `contrasen[aã]` `contraseña` `clave[a-z_]*` *(except when followed by list E6)* `pin` `nip` `hash_?password` `password_?hash` `secret` `token_?acceso` `access_?token` `refresh_?token` `api_?key` `otp` `respuesta_?secreta` `pregunta_?secreta`

VALUE FORMAT PA_L1_CREDENCIAL – Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character becomes `X`. A credential has no reason to look real in a test environment.

`PA_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Secreta#2024`	→	`XXXXXXXXXXXX`

7.25 Geolocation

PA_L1_GEOLOCALIZACION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns. Panama lies between 7° and 10° north and 77° and 83° west.

HOW IT IS FOUND

COLUMN NAME — PA_L1_GEOLOCALIZACION – Path

85%	`lat` `latitud` `latitude` `lon` `lng` `longitude` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `geolocalizacion` `ubicacion_?gps` `gps` `posicion_?gps`
50%	`longitud` `long`

VALUE FORMAT — PA_L1_GEOLOCALIZACION – Regex

PATTERN	STRENGTH	NOTES
`0*(?:[7-9]\.\d{3,}\s*,\s*-(7[7-9]|8[0-3])\.\d{3,})`	90%	
`0*(?:[7-9]\.\d{3,})`	60%	
`-(7[7-9]|8[0-3])\.\d{3,}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved.

`PA_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`8.983333,-79.516667`	→	**`8.903230,-79.596978`**

7.26 Free text

PA_L1_TEXTO_LIBRE

COLUMN NAME | DATA TYPE | VALUE FORMAT | FREE TEXT REDACTION

WHAT IT IS

Remarks, comments, complaints and notes where personal data is written without structure.

HOW IT IS FOUND

COLUMN NAME — PA_L1_TEXTO_LIBRE – Path

60%	`observaciones?` `obs` `comentarios?` `notas?` `detalle` `descripcion_?(caso|queja|reclamo|incidente|solicitud|problema|atencion|hechos)` `texto_?libre` `mensaje` `queja` `reclamo` `referencias?` `motivo_?(texto|detalle)` `narrativa` `relato` `resumen_?caso` `remarks` `comments?` `notes?` `free_?text` `memo` `bitacora`

DATA TYPE `PA_L1_TEXTO_LIBRE – Type`

Accepts text (length 30 or more); any other type rules the data class out.

VALUE FORMAT `PA_L1_TEXTO_LIBRE – Regex`

PATTERN	STRENGTH	NOTES
`0*(?:([1-9]|1[0-3])(AV|PI)?|E|N|PE)-\d{1,4}-\d{1,6})`	60%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:(\+?507\s?)?6\d{3}-?\d{4})`	50%	anywhere in the value

A value that matches none does not count against the data class.

HOW IT IS MASKED

Free Text Redaction: cédulas, e-mails, mobiles, hyphenated landlines, card numbers, plates and IPs become `[DATO]`, and the given names and surnames of the lists become `[NOMBRE]`.

`PA_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 7 patterns with `[DATO]`, and the 1,094 terms of `pa-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Cliente González, cédula 8-442-445, correo y.gonzalez@gmail.com, tel 6123-4567.`	→	**`Cliente [NOMBRE], cédula [DATO], correo [DATO], tel [DATO].`**

PART 8

Quasi-identifiers

Data that identifies no one on its own, but does in combination. Panama has 699 corregimientos, and 616 of them had fewer than 10,000 inhabitants in the 2023 census: a birth date, a sex and one of those corregimientos point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

8.1 Birth date

PA_L2_FECHA_NACIMIENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The birth date, in date, timestamp or text columns.

HOW IT IS FOUND

COLUMN NAME PA_L2_FECHA_NACIMIENTO — Path

90% `fecha_?(de_?)?nac(imiento)?` `fec_?nac(imiento)?` `fch_?nac` `f_?nac(imiento|im)?` `fnac` `fechanac(imiento)?` `fecnac` `nacimiento` `dob` `birth_?date` `date_?of_?birth` `birthdate` `birthday` `cumplea(n|ñ)os`

DATA TYPE PA_L2_FECHA_NACIMIENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 60 days back or forward: it breaks the link to the person and keeps ages and cohorts almost intact.

`PA_FECHA_NACIMIENTO` DATE SHIFT
Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

8.2 Birth year

PA_L2_ANIO_NACIMIENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The birth year alone.

HOW IT IS FOUND

COLUMN NAME PA_L2_ANIO_NACIMIENTO — Path

90% `an(i)?o_?(de_?)?nac(imiento)?` `año_?(de_?)?nac(imiento)?` `birth_?year` `year_?of_?birth` `ano_?nacim`

DATA TYPE PA_L2_ANIO_NACIMIENTO — Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: 1985 becomes another year of the eighties.

`PA_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

8.3 Age

PA_L2_EDAD

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Ages in years, whole or with decimals.

HOW IT IS FOUND

> COLUMN NAME PA_L2_EDAD — Path
>
> 85% `edad(_?(actual|paciente|cliente|afiliado|asegurado|beneficiario|ingreso|anos|años|cumplida|jubilacion))?` `age` `anos_?cumplidos` `rango_?(de_?)?edad` `grupo_?(de_?)?edad` `edad_?en_?anos`

> DATA TYPE PA_L2_EDAD — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

HOW IT IS MASKED

The tens digit stays and the units digit is mapped (37 becomes 3x). From 100 on, 90: extreme ages identify on their own.

`PA_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

8.4 Life event dates

PA_L2_FECHA_EVENTO

COLUMN NAME | DATA TYPE | DATE SHIFT

WHAT IT IS

Dates of death, marriage, hiring and leaving a job, retirement, hospitalization, diagnosis, naturalization and other personal events.

HOW IT IS FOUND

COLUMN NAME PA_L2_FECHA_EVENTO — Path

80% `fecha_?(de_?)?(defuncion|fallecimiento|muerte|matrimonio|union|divorcio|ingreso|inicio_?labores|contratacion|contrato|egreso|despido|renuncia|jubilacion|pension|incapacidad|hospitalizacion|alta_?medica|diagnostico|atencion|consulta|parto|embarazo|detencion|sentencia|vacunacion|cirugia|reingreso|afiliacion|inscripcion_?css|naturalizacion|residencia)` `fec_?(defuncion|ingreso|egreso|contrato|atencion|diagnostico|incapacidad|jubilacion)` `fch_?(ingreso|egreso)` `death_?date` `hire_?date` `termination_?date` `date_?of_?death` `admission_?date` `discharge_?date`

DATA TYPE PA_L2_FECHA_EVENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 30 days: less than the birth date, since they are often combined with it.

`PA_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

8.5 Sex

PA_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Registered sex in any notation: `F` / `M`, `H` / `M`, `Femenino`, `Hombre`, `Male`.

HOW IT IS FOUND

COLUMN NAME PA_L2_SEXO — Path

85% `sexo(_?(biologico|registral|paciente|cliente|asegurado|trabajador))?` `sex` `g[eé]nero` *(except when followed by* ***`identidad`*** *,* ***`social`*** *,* ***`autopercibido`*** *)* `gender` `cod_?sexo`

KNOWN VALUES PA_L2_SEXO — List

LIST	VALUES	STRENGTH	FIRST VALUES
`pa-detectar-sexo.txt`	8	80%	hombre, mujer, femenino, masculino, female, male
`pa-detectar-sexo-letra.txt`	3	60%	h, m, f

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the data class.

HOW IT IS MASKED

Replaced within its own vocabulary: `F` / `M` stays `F` / `M`.

`PA_SEXO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_SEXO_PALABRA` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-palabra.txt`, chosen by a keyed hash.

`PA_SEXO_MUJER_HOMBRE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-mujer-hombre.txt`, chosen by a keyed hash.

`PA_SEXO_INGLES` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-ingles.txt`, chosen by a keyed hash.

`PA_SEXO_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-f-m.txt`, chosen by a keyed hash.

`PA_SEXO_H_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-h-m.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
Masculino	→	**Femenino**

8.6 District

PA_L2_DISTRITO

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

WHAT IT IS

The district name. Panama has 81 inhabited districts — the Guna Yala comarca is not divided into districts —, and 47 had fewer than 20,000 inhabitants in 2023.

HOW IT IS FOUND

COLUMN NAME PA_L2_DISTRITO – Path

85% `distrito[a-z_]*` `nom(bre)?_?(dist|distrito)` `dist` `municipio` `mun` `distrito_?(residencia|nacimiento|domicilio)`

VALUE FORMAT PA_L2_DISTRITO – Values

PATTERN	STRENGTH	NOTES
One of 79 known values, ignoring case — Bocas del Toro, Changuinola, Chiriquí Grande, Almirante, Aguadulce, Antón, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A district under 20,000 inhabitants becomes the nearest district of its province or comarca with at least 20,000; larger ones stay. See *Where people live*.

`PA_DISTRITO` DATA CLEANSING

Replaces each value found in `pa-distrito-generalizado.txt` (234 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Santa Isabel	→	**Colón**
David	→	**David**

8.7 Corregimiento

PA_L2_CORREGIMIENTO

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

WHAT IT IS

The corregimiento name, the smallest division with a census population: 699 of them, averaging 5,800 inhabitants.

HOW IT IS FOUND

COLUMN NAME PA_L2_CORREGIMIENTO — Path

85% `corregimiento[a-z_]*` `nom(bre)?_?(correg|corregimiento)` `correg` `corr` `corregimiento_?(residencia|nacimiento|domicilio)`

50% `ciudad[a-z_]*` `city` `town` `poblacion`

VALUE FORMAT PA_L2_CORREGIMIENTO — Values

PATTERN	STRENGTH	NOTES
One of 618 known values, ignoring case — Bocas del Toro, Bastimentos, Punta Laurel, Tierra Oscura, Bocas del Drago, San Cristóbal, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A corregimiento under 10,000 inhabitants becomes the nearest corregimiento of its province or comarca with at least 10,000, or of the country if the province has none. Large ones stay. See *Where people live*.

`PA_CORREGIMIENTO` DATA CLEANSING

Replaces each value found in `pa-corregimiento-generalizado.txt` (1,760 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Cerro Punta	→	**La Concepción**
Tocumen	→	**Tocumen**

8.8 Corregimiento or district code

PA_L2_CODIGO_LUGAR

COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

INEC geographic codes: six digits for a corregimiento (`040612`), four for a district (`0306`), also without the leading zero.

HOW IT IS FOUND

COLUMN NAME PA_L2_CODIGO_LUGAR — Path

85% `cod(igo)?_?(correg|corregimiento|dist|distrito|lugar(_?poblado)?|inec|geografico)` `cve_?(correg|dist|lugar)` `id_?(correg|corregimiento|distrito)` `correg_?(cod|id)` `distrito_?(cod|id)` `codigo_?censal`

DATA TYPE PA_L2_CODIGO_LUGAR — Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

VALUE FORMAT PA_L2_CODIGO_LUGAR — Values

PATTERN	STRENGTH	NOTES
One of 1,405 known values, ignoring case — 010101, 10101, 010102, 10102, 010104, 10104, …	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

By the same rule as the names: a small corregimiento or district becomes the code of the large one it maps to.

`PA_CODIGO_LUGAR` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PA_CODIGO_CORREGIMIENTO` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: keep.
>
> > `PA_CODIGO_CORREGIMIENTO_TABLA` **DATA CLEANSING**
> >
> > Replaces each value found in `pa-codigo-corregimiento-generalizado.txt` (1,259 pairs) by its counterpart; values not in the file stay as they are.
>
> `PA_CODIGO_DISTRITO` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: keep.
>
> > `PA_CODIGO_DISTRITO_TABLA` **DATA CLEANSING**
> >
> > Replaces each value found in `pa-codigo-distrito-generalizado.txt` (146 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
040612	→	**040612**
0306	→	**0301**

8.9 Populated place

PA_L2_LUGAR_POBLADO

COLUMN NAME **SECURE LOOKUP**

WHAT IT IS

Populated places, hamlets and communities, and the place of birth.

HOW IT IS FOUND

COLUMN NAME PA_L2_LUGAR_POBLADO — Path

80% `lugar_?poblado` `nom(bre)?_?lugar_?poblado` `poblado` `comunidad` *(except when followed by* `indigena` , `religiosa` *)* `caserio` `localidad` `lugar_?(de_?)?nacimiento` `pueblo_?(residencia|origen)`

HOW IT IS MASKED

Replaced by the name of a corregimiento of more than 20,000 inhabitants: still a place, no longer theirs.

`PA_LUGAR_POBLADO` **SECURE LOOKUP**

Replaces the value with one of the 52 values in `pa-lugares-poblados.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Los Llanos de Ocú	→	**El Coco**

8.10 Barriada or neighborhood

PA_L2_BARRIADA

COLUMN NAME · SECURE LOOKUP

WHAT IT IS

Barriadas, urbanizaciones, residential developments and sectors.

HOW IT IS FOUND

> COLUMN NAME PA_L2_BARRIADA — Path
>
> 85% `barriada[a-z_]*` `barrio` `urbanizacion` `urb` `residencial` `sector` `nom(bre)?_?` `(barriada|urbanizacion|barrio)` `condominio` `ph_?nombre` `nombre_?ph`

HOW IT IS MASKED

Replaced by one of 75 common barriadas and neighborhoods.

`PA_BARRIADA` SECURE LOOKUP

Replaces the value with one of the 75 values in `pa-barriadas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Villa Guadalupe	→	**Las Acacias**

8.11 Postal code

PA_L2_CODIGO_POSTAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Postal codes of Correos y Telégrafos, little used in Panama. The first two digits give the province.

HOW IT IS FOUND

> COLUMN NAME PA_L2_CODIGO_POSTAL — Path
>
> 85% `cod(igo)?_?postal` `zona_?postal` `cp` `zip(_?code)?` `postal_?code` `codpostal` `apartado_?postal`

> VALUE FORMAT PA_L2_CODIGO_POSTAL — Regex
>
PATTERN	STRENGTH	NOTES
`0*(?:\d{4,5})`		20%
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The first two digits stay and the rest becomes zeros.

`PA_CODIGO_POSTAL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
0801	→	**0800**

8.12 Nationality

PA_L2_NACIONALIDAD

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. In a Panamanian database, an uncommon nationality identifies.

HOW IT IS FOUND

COLUMN NAME PA_L2_NACIONALIDAD — Path

80% `nacionalidad` `nationality` `pais_?(de_?)?(nacimiento|origen)` `ciudadania` `citizenship` `country_?of_?birth` `extranjero`

VALUE FORMAT PA_L2_NACIONALIDAD — Values

PATTERN	STRENGTH	NOTES
One of 50 known values, ignoring case — Panameña, Colombiana, Venezolana, Nicaragüense, China, Estadounidense, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the 20 most common nationalities in Panama.

`PA_NACIONALIDAD` SECURE LOOKUP

Replaces the value with one of the 20 values in `pa-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Venezolana	→	**Estadounidense**

8.13 Marital status

PA_L2_ESTADO_CIVIL

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Marital status, in the census categories: in a union, married, single, separated from a marriage, separated from a union, divorced, widowed.

HOW IT IS FOUND

COLUMN NAME PA_L2_ESTADO_CIVIL — Path

85% `estado_?civil` `edo_?civil` `est_?civil` `ecivil` `estado_?conyugal` `situacion_?conyugal` `marital_?status` `civil_?status`

VALUE FORMAT PA_L2_ESTADO_CIVIL — Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — soltero, soltera, casado, casada, unido, unida, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another of the seven categories.

`PA_ESTADO_CIVIL` SECURE LOOKUP

Replaces the value with one of the 7 values in `pa-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Unida	→	**Casado**

8.14 Occupation

PA_L2_OCUPACION

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Occupation, profession or job title. A rare title (`Gerente Regional de Operaciones Bocas del Toro`) is unique in the database.

HOW IT IS FOUND

COLUMN NAME PA_L2_OCUPACION — Path

80% `ocupaci[oó]n` `profesi[oó]n` `oficio` `puesto(_?(trabajo|laboral|actual))?` *(except when followed by* *`votacion`* , *`venta`* , *`trabajo_?id`* *)* `cargo` *(except when followed by list E7)* `job_?title` `occupation` `actividad_?(laboral|economica_?persona)` `categoria_?laboral`

HOW IT IS MASKED

Replaced by one of 40 common occupations.

`PA_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 40 values in `pa-ocupaciones.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Gerente Regional de Operaciones Bocas del Toro	→	**Bodeguero**

8.15 Employer

PA_L2_EMPLEADOR

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The name of the employer (*patrono*) or workplace.

HOW IT IS FOUND

COLUMN NAME PA_L2_EMPLEADOR — Path

80% `empleador` `patrono` `nombre_?patrono` `razon_?social_?(patrono|empleador)` `empresa_?(empleadora|trabajo|laboral)` `lugar_?(de_?)?trabajo` `centro_?(de_?)?trabajo` `employer` `institucion_?(donde_?)?labora` `entidad_?(donde_?)?labora`

HOW IT IS MASKED

Replaced by one of 25 fictitious employers.

`PA_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 25 values in `pa-empleadores.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Autoridad del Canal de Panamá`	→	**`Ferretería El Constructor, S.A.`**

8.16 Schooling

PA_L2_ESCOLARIDAD

COLUMN NAME · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

Education level in the terms of the Panamanian system: primaria, premedia, media, vocational, higher education.

HOW IT IS FOUND

COLUMN NAME PA_L2_ESCOLARIDAD — Path

80% `escolaridad` `nivel_?(educativo|educacional|escolar|de_?estudios|academico|de_?instruccion)` `grado_?(de_?)?(estudios|instruccion)` `grado_?academico` `ultimo_?grado(_?aprobado)?` `education_?level` `anos_?(de_?)?escolaridad`

VALUE FORMAT PA_L2_ESCOLARIDAD — Values

PATTERN	STRENGTH	NOTES
One of 25 known values, ignoring case — Ningún grado, Primaria incompleta, Primaria completa, Premedia incompleta, Premedia completa, Media incompleta, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another of the 13 levels.

`PA_ESCOLARIDAD` SECURE LOOKUP

Replaces the value with one of the 13 values in `pa-escolaridad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Premedia completa`	→	**`Premedia incompleta`**

8.17 School

PA_L2_ESCUELA

COLUMN NAME · SECURE LOOKUP

WHAT IT IS

The name of the school, colegio, basic education center or university.

HOW IT IS FOUND

COLUMN NAME PA_L2_ESCUELA — Path

75% `escuela` `colegio` `plantel` `nombre_?(escuela|plantel|colegio|centro_?educativo|institucion_?educativa)` `centro_?educativo` `institucion_?educativa` `universidad` `instituto` `school(_?name)?` `cebg` `centro_?basico`

HOW IT IS MASKED

Replaced by one of 15 fictitious schools.

`PA_ESCUELA` **SECURE LOOKUP**

Replaces the value with one of the 15 values in `pa-escuelas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Instituto Nacional de Panamá`	→	**`Universidad Tecnológica del Pacífico`**

8.18 Children and dependents

`PA_L2_DEPENDIENTES`

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Number of children, dependents or household members.

HOW IT IS FOUND

> **COLUMN NAME** `PA_L2_DEPENDIENTES – Path`
>
> **80%** `dependientes` `n(o|um|ro)?_?dependientes` `num_?hijos` `n(o|um|ro)?_?hijos` `cant_?hijos` `hijos` `hijos_?nacidos_?vivos` `integrantes_?(del_?)?(hogar|familia)` `n(o|um|ro)_?integrantes` `tamano_?(del_?)?hogar` `personas_?(en_?)?(el_?)?hogar`

> **DATA TYPE** `PA_L2_DEPENDIENTES – Type`
>
> Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

Capped at 5: large households are rare, and a rare count identifies.

`PA_CANTIDAD_ACOTADA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 9

Sensitive data

The categories of article 4, section 11 — ethnic origin, health, genetic and biometric data, beliefs, political opinions, union membership, sexual orientation — and, because the list is not exhaustive, gender identity and sexual life. Categorical columns keep their shape: a yes/no flag stays a flag, a numeric code gets other digits and any other value is replaced by one from its category's list. Where the values share no vocabulary, they are suppressed to `Sin información`.

9.1 Ethnic origin

PA_L3_ETNIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Belonging to an indigenous people — Ngäbe, Guna, Emberá, Buglé, Wounaan, Naso Tjërdi, Bokota, Bri Bri — or Afro-descendant self-identification — Afro-Panamanian, moreno, black, Afro-colonial, Afro-Antillean —, in the terms of the 2023 census, often as a yes/no flag.

HOW IT IS FOUND

COLUMN NAME — PA_L3_ETNIA – Path

90%

`etnia` `[eé]tnico` `origen_?[eé]tnico` `grupo_?[eé]tnico` `pueblo_?(indigena|originario)` `grupo_?indigena` `indigena` `ind[ií]gena` `afro(panameno|descendiente|panameño)?` `grupo_?afro(descendiente)?` `autoidentificacion(_?(etnica|indigena|afro))?` `se_?considera_?(indigena|afro|afrodescendiente)` `raza` `race` `ethnicity` `ethnic_?group` `comunidad_?indigena` `pertenencia_?(etnica|indigena)`

VALUE FORMAT — PA_L3_ETNIA – Values

PATTERN	STRENGTH	NOTES
One of 42 known values, ignoring case — Guna, Ngäbe, Buglé, Naso Tjërdi, Bokota, Emberá, …	90%	
One of 7 known values, ignoring case — s, n, sí, no, y, 0, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A flag stays a flag in its vocabulary, a code gets other digits and any other value is replaced by one from the census list.

`PA_PUEBLO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_PUEBLO_LISTA`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_PUEBLO_LISTA` SECURE LOOKUP

Replaces the value with one of the 16 values in `pa-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Teribe	→	**Moreno**
S	→	**S**

9.2 Indigenous language

PA_L3_LENGUA_INDIGENA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The indigenous language the person speaks: Ngäbere, Buglere, Guna, Emberá, Wounmeu, Naso Tjërdi, Bribri.

HOW IT IS FOUND

COLUMN NAME PA_L3_LENGUA_INDIGENA — Path

90% `lengua(_?(indigena|materna|originaria))?` `habla_?(lengua_?)?(indigena|originaria)` `idioma_?(indigena|materno|originario)` `lengua_?que_?habla` `dialecto` `native_?language`

VALUE FORMAT PA_L3_LENGUA_INDIGENA — Values

PATTERN	STRENGTH	NOTES
One of 23 known values, ignoring case — Ngäbere, Buglere, Guna, Emberá, Wounmeu, Naso Tjërdi, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Like ethnic origin: flags and codes keep their shape, names are replaced by another language from the list.

`PA_LENGUA_INDIGENA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_LENGUA_INDIGENA_LISTA`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_LENGUA_INDIGENA_LISTA` SECURE LOOKUP

Replaces the value with one of the 9 values in `pa-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ngäbere	→	**No habla lengua indígena**

9.3 Diagnosis

PA_L3_SALUD_DIAGNOSTICO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Diagnoses, as ICD-10 codes (`F32.9` , `B20`) or text, and medical history, allergies and chronic conditions.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_DIAGNOSTICO – Path

85% `diagn[oó]stico[a-z_]*` `diag` `dx` `cie_?10` `cie_?11` `cod(igo)?_?cie` `cie` `icd_?10` `icd` `patolog[ií]a[a-z_]*` `padecimiento[a-z_]*` `enfermedad(es)?[a-z_]*` `morbilidad` `condicion_?(medica|de_?salud|cronica)` `problema_?(de_?)?salud` `impresion_?diagnostica` `causa_?(incapacidad|muerte|defuncion|hospitalizacion|consulta)` `motivo_?(de_?)?(consulta|hospitalizacion|incapacidad)` `comorbilidad(es)?` `antecedentes_?(medicos|patologicos|personales_?patologicos|heredofamiliares|clinicos)` `alergias?` `enfermedad_?preexistente` `preexistencias?` `enfermedad_?cronica` `riesgo_?profesional`

VALUE FORMAT PA_L3_SALUD_DIAGNOSTICO – Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

An ICD-10 code is replaced by another common code of the same format, with or without a decimal; text, by a common diagnosis. The real diagnosis does not survive.

`PA_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PA_DIAGNOSTICO_TEXTO` .

`PA_CIE10_DECIMAL` SECURE LOOKUP

Replaces the value with one of the 33 values in `pa-cie10-decimal.txt` , chosen by a keyed hash.

`PA_CIE10` SECURE LOOKUP

Replaces the value with one of the 37 values in `pa-cie10.txt` , chosen by a keyed hash.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt` , chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt` , chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt` , chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt` , chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt` , chosen by a keyed hash.

`PA_DIAGNOSTICO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 30 values in `pa-diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F32.9	→	**J02.9**
Depresión mayor	→	**Tendinitis**

9.4 Medication

PA_L3_SALUD_MEDICAMENTO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Medications and active ingredients. Some reveal the diagnosis: an antiretroviral, an antipsychotic.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_MEDICAMENTO — Path

85% `medicamentos?` `f[aá]rmacos?` `sustancia_?activa` `principio_?activo` `prescripci[oó]n` `receta(_?medica)?` `tratamiento(_?farmacologico)?` `medication` `drug(_?name)?` `posologia` `lista_?oficial_?medicamentos`

VALUE FORMAT PA_L3_SALUD_MEDICAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 54 known values, ignoring case — Acetaminofén, Ibuprofeno, Naproxeno, Diclofenaco, Ketorolaco, Metformina, …	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced by one of 26 common medications.

`PA_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_MEDICAMENTO_LISTA`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_MEDICAMENTO_LISTA` SECURE LOOKUP

Replaces the value with one of the 26 values in `pa-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Sertralina 50 mg	→	**Amoxicilina**

9.5 Clinical identifier

PA_L3_SALUD_IDENTIFICADOR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Medical record, file, admission, prescription or sick-leave number.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_IDENTIFICADOR — Path

85% `expediente_?clinico` `n(o|um|ro|umero)_?expediente(_?clinico)?` `historia_?clinica` `n(o|um|ro)_?historia` `nhc` `n(o|um|ro)_?episodio` `n(o|um|ro)_?(de_?)?admision` `folio_?(atencion|urgencias|receta|incapacidad)` `n(o|um|ro)_?incapacidad` `certificado_?(de_?)?incapacidad` `n(o|um|ro)_?(de_?)?cama` `n(o|um|ro)_?interconsulta` `n(o|um|ro)_?(de_?)?receta` `n(o|um|ro)_?biopsia` `medical_?record_?number` `mrn`

55% `expediente` `episodio` `cama`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
HC-2024-00123	→	**TW-3389-01317**

9.6 Clinical text

PA_L3_SALUD_TEXTO_CLINICO

COLUMN NAME | DATA TYPE | FREE TEXT REDACTION

WHAT IT IS

Progress notes, medical history, discharge summaries and clinical summaries.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_TEXTO_CLINICO — Path

85% `nota_?(medica|de_?evolucion|evolucion|de_?ingreso|ingreso|de_?egreso|egreso|de_?urgencias|urgencias|postoperatoria|preoperatoria|de_?enfermeria|clinica)s?` `notas?_?clinicas?` `enfermedad_?actual` `anamnesis` `examen_?fisico` `evoluci[oó]n(_?(medica|clinica))?` `epicrisis` `indicaciones(_?medicas)?` `resumen_?clinico` `resumen_?(de_?)?egreso` `historia_?(de_?la_?)?enfermedad` `plan_?(de_?)?tratamiento` `pronostico` `hallazgos` `interpretacion` `clinical_?notes?` `progress_?notes?`

DATA TYPE PA_L3_SALUD_TEXTO_CLINICO — Type

Accepts text (length 30 or more); any other type rules the data class out.

HOW IT IS MASKED

Free Text Redaction, as for free text: cédulas, contact details and names are redacted. The clinical content stays; if it must go too, assign the column to a suppression data class.

`PA_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 7 patterns with `[DATO]`, and the 1,094 terms of `pa-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Paciente Batista, cédula 8-442-445, acude por cefalea.`	→	**`Paciente [NOMBRE], cédula [DATO], acude por cefalea.`**

9.7 Test result

PA_L3_SALUD_RESULTADO_EXAMEN

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Laboratory and imaging results: HIV, viral load, glucose, pregnancy or drug tests.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_RESULTADO_EXAMEN — Path

80% `resultado_?(estudio|examen|laboratorio|lab|prueba|pcr|antigeno|biopsia|imagen|vih|covid|papanicolaou|mamografia)` `examenes?_?(de_?)?laboratorio` `vih` `hiv` `carga_?viral` `cd4` `glucosa` `glicemia` `hemoglobina(_?glicosilada)?` `hba1c` `colesterol` `trigliceridos` `presion_?arterial` `imc` `prueba_?(covid|embarazo|vih|antidoping|toxicologica)` `antidoping` `lab_?result`

50% `resultado` `examen`

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Reactivo	→	**`Quilqaju`**

9.8 Blood group

PA_L3_SALUD_GRUPO_SANGUINEO

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

ABO group and Rh factor.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `grupo_?sang` `tipo_?(de_?)?sangre` `tipo_?sanguineo` `factor_?rh` `rh` `blood_?type` `blood_?group`

VALUE FORMAT PA_L3_SALUD_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another of the eight groups.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with Delphix and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

9.9 Disability

PA_L3_SALUD_DISCAPACIDAD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Type or degree of disability, in the types SENADIS certifies: physical, visual, hearing, intellectual, psychosocial, visceral.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `tipo_?(de_?)?discapacidad` `grado_?(de_?)?discapacidad` `certificado_?(de_?)?discapacidad` `carne_?senadis` `senadis` `persona_?con_?discapacidad` `pcd` `invalidez` `porcentaje_?(de_?)?invalidez` `pension_?(de_?)?invalidez` `limitacion(_?(fisica|actividad))?` `disability` `dependencia_?funcional` `nee` `necesidades_?educativas_?especiales`

VALUE FORMAT PA_L3_SALUD_DISCAPACIDAD — Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Física, Visual, Auditiva, Intelectual, Psicosocial, Visceral, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the type is replaced by another from the list.

`PA_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_DISCAPACIDAD_LISTA`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_DISCAPACIDAD_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `pa-discapacidad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Discapacidad psicosocial severa`	→	**`Auditiva`**

9.10 Sexual and reproductive health

`PA_L3_SALUD_SEXUAL_REPRODUCTIVA`

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Pregnancy, weeks of gestation, abortions, contraception, fertility, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME `PA_L3_SALUD_SEXUAL_REPRODUCTIVA – Path`

90% `embarazo` `embarazada` `gestaci[oó]n` `semanas_?(de_?)?gestacion` `edad_?gestacional` `fum` `fecha_?ultima_?menstruacion` `aborto` `anticonceptivos?` `metodo_?(de_?)?planificacion(_?familiar)?` `planificacion_?familiar` `fertilidad` `infertilidad` `reproduccion_?asistida` `gestas` `partos` `cesareas?` `puerperio` `its` `ets` `infeccion_?(de_?)?transmision_?sexual` `prep` `pregnan[a-z]*` `contracepti[a-z]*`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`PA_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SUPRIMIR`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `pa-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Embarazo de 12 semanas	→	**Sin información**
S	→	**S**

9.11 Mental health and addiction

PA_L3_SALUD_MENTAL_ADICCIONES

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

Mental disorders, suicide attempts, substance use and addiction treatment.

HOW IT IS FOUND

COLUMN NAME PA_L3_SALUD_MENTAL_ADICCIONES – Path

90% `salud_?mental` `psiquiatri[a-z]*` `psicologi[a-z]*` `trastorno[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z]*` `autolesi[oó]n` `adicci[oó]n(es)?` `consumo_?(de_?)?(drogas|alcohol|sustancias|tabaco)` `alcoholismo` `farmacodependencia` `drogadiccion` `toxicomania` `dependencia_?(alcohol|drogas|sustancias)` `tratamiento_?(adicciones|drogas|alcohol)` `rehabilitacion_?(adicciones|drogas)` `mental_?health` `substance_?(use|abuse)`

HOW IT IS MASKED

Suppressed to `Sin información`.

`PA_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SUPRIMIR`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `pa-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno bipolar	→	**Sin información**

9.12 Biometric data

PA_L3_BIOMETRICO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Fingerprint, face, iris or voice templates stored as text (hash, base64). The law names them sensitive and Decree 285 defines them.

HOW IT IS FOUND

COLUMN NAME PA_L3_BIOMETRICO — Path

90% `huella(_?(dactilar|digital))?` `huellas` `dactilar` `biometri[a-z_]*` `template_?(facial|biometrico|huella)` `rostro` `reconocimiento_?facial` `facial_?(template|id)` `iris` `retina` `voz_?(huella|biometrica)` `firma_?(digitalizada|biometrica|autografa_?digital)` `fingerprint` `face_?(id|template|encoding)` `palm_?print` `minucias`

DATA TYPE PA_L3_BIOMETRICO — Type

Accepts text; any other type rules the data class out.

HOW IT IS MASKED

Every character becomes `X`. Binary columns are out of reach: see *Limits*.

`PA_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

9.13 Genetic data

PA_L3_INFORMACION_GENETICA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Genetic profiles, sequences, mutations, karyotypes, paternity tests.

HOW IT IS FOUND

COLUMN NAME PA_L3_INFORMACION_GENETICA — Path

90% `adn` `dna` `genoma` `genotipo` `genetic[a-z_]*` `gen[eé]tic[ao]` `informacion_?genetica` `secuencia_?genetica` `marcador_?genetico` `perfil_?(genetico|biologico)` `mutacion(_?genetica)?` `snp` `brca` `haplotipo` `cariotipo` `tamizaje_?(genetico|neonatal|metabolico)` `prueba_?(de_?)?paternidad`

VALUE FORMAT PA_L3_INFORMACION_GENETICA — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Every character becomes `X`.

`PA_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXXX

9.14 Sexual orientation

PA_L3_ORIENTACION_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Sexual orientation or preference, which the law names explicitly.

HOW IT IS FOUND

COLUMN NAME PA_L3_ORIENTACION_SEXUAL — Path

95% `orientaci[oó]n_?sexual` `preferencia_?sexual` `sexual_?(orientation|preference)` `orient_?sexual` `pref_?sexual`

VALUE FORMAT PA_L3_ORIENTACION_SEXUAL — Values

PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — Heterosexual, Homosexual, Lesbiana, Gay, Bisexual, Pansexual, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`PA_ORIENTACION_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_ORIENTACION_SEXUAL_LISTA`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_ORIENTACION_SEXUAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 9 values in `pa-orientacion-sexual.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Bisexual	→	Lesbiana

9.15 Gender identity

PA_L3_IDENTIDAD_GENERO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Gender identity, name changes for identity, pronouns.

HOW IT IS FOUND

COLUMN NAME PA_L3_IDENTIDAD_GENERO — Path

95% `identidad_?(de_?)?g[eé]nero` `gender_?identity` `g[eé]nero_?(identidad|social|autopercibido)` `transg[eé]nero` `transexual` `persona_?trans` `cambio_?(de_?)?(sexo|genero|nombre_?por_?genero)` `pronombres?`

VALUE FORMAT PA_L3_IDENTIDAD_GENERO — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Mujer, Hombre, Mujer trans, Hombre trans, No binario, Género fluido, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`PA_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_IDENTIDAD_GENERO_LISTA`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `pa-identidad-genero.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Hombre trans`	→	**`No binario`**

9.16 Sexual life

PA_L3_VIDA_SEXUAL

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behavior and history.

HOW IT IS FOUND

COLUMN NAME PA_L3_VIDA_SEXUAL — Path

90% `vida_?sexual` `conducta_?sexual` `actividad_?sexual` `parejas?_?sexuales?` `practicas_?sexuales` `inicio_?(de_?)?(la_?)?vida_?sexual` `sexual_?(activity|behavior|history)` `historia_?sexual` `comportamiento_?sexual`

HOW IT IS MASKED

Suppressed to `Sin información`.

`PA_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SUPRIMIR`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `pa-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Activa	→	**Sin información**

9.17 Religion

PA_L3_RELIGION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Religion or denomination: Catholic, Evangelical, Adventist, Jehovah's Witness, Bahá'í, Jewish, Muslim, and the indigenous religions Mamatata and Ibeorgun.

HOW IT IS FOUND

COLUMN NAME PA_L3_RELIGION — Path

95% `religi[oó]n[a-z_]*` `credo` `culto` `iglesia` `creencia_?religiosa` `confesion_?religiosa` `denominacion_?religiosa` `religious_?affiliation` `comunidad_?religiosa` `congregacion`

VALUE FORMAT PA_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 42 known values, ignoring case — Católica, Evangélica, Adventista del Séptimo Día, Testigo de Jehová, Iglesia de Jesucristo de los Santos de los Últimos Días, Bahá í, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`PA_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_RELIGION_LISTA`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_RELIGION_LISTA` SECURE LOOKUP

Replaces the value with one of the 14 values in `pa-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Episcopal`	→	**`Musulmana`**

9.18 Philosophical and moral beliefs

PA_L3_CREENCIA_FILOSOFICA_MORAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Personal convictions, conscientious objection, ethical positions.

HOW IT IS FOUND

COLUMN NAME PA_L3_CREENCIA_FILOSOFICA_MORAL — Path

90% `creencias?_?(filosoficas?|morales?|personales)` `convicci[oó]n(es)?(_?(filosoficas?|morales?|eticas?|personales))?` `objecion_?(de_?)?conciencia` `postura_?(etica|moral)` `valores_?personales` `filosofia_?(de_?)?vida` `cosmovision`

HOW IT IS MASKED

Suppressed to `Sin información`.

`PA_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SUPRIMIR`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `pa-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Rechaza transfusiones	→	**Sin información**

9.19 Political opinion

PA_L3_OPINION_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Ideology, electoral preference, voting intention.

HOW IT IS FOUND

COLUMN NAME PA_L3_OPINION_POLITICA — Path

90% `opini[oó]n(es)?_?pol[ií]ticas?` `ideolog[ií]a(_?politica)?` `posicion_?politica` `postura_?politica` `tendencia_?politica` `orientacion_?politica` `preferencia_?(politica|electoral|partidista)` `intencion_?(de_?)?voto` `simpatia_?(politica|partidista)` `political_?(view|orientation|opinion)`

VALUE FORMAT PA_L3_OPINION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Izquierda, Centro izquierda, Centro, Centro derecha, Derecha, Sin preferencia, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by another position on a generic scale.

`PA_OPINION_POLITICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_OPINION_POLITICA_LISTA`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_OPINION_POLITICA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `pa-opiniones-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Centro derecha`	→	**`Centro`**

9.20 Political affiliation

PA_L3_AFILIACION_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The party a person is registered with or supports. The Electoral Tribunal counted more than 1.5 million party members in 2026.

HOW IT IS FOUND

COLUMN NAME PA_L3_AFILIACION_POLITICA — Path

95% `partido(_?pol[ií]tico)?` `militancia` `militante` `adherente` `inscrito_?partido` `afiliaci[oó]n_?(politica|partidista|partido)` `afiliado_?(a_?)?partido` `padron_?(de_?)?(militantes|adherentes)` `political_?party` `party_?affiliation` `alianza_?electoral` `simpatizante` `libre_?postulacion`

VALUE FORMAT PA_L3_AFILIACION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 28 known values, ignoring case — Partido Revolucionario Democrático, Realizando Metas, Cambio Democrático, Partido Panameñista, MOLIRENA, Movimiento Otro Camino, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced by one of the legally constituted parties — PRD, Realizando Metas, Cambio Democrático, Panameñista, MOLIRENA, MOCA, FAD, Alianza, Partido Popular — or by independent candidacy (*libre postulación*) or no party.

`PA_PARTIDO_POLITICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_PARTIDO_POLITICO_LISTA` .

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt` , chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_PARTIDO_POLITICO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 11 values in `pa-partidos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Partido Liberal`	→	**`Libre postulación`**

9.21 Union membership

PA_L3_AFILIACION_SINDICAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Membership of a union, guild or workers' association, union dues, collective agreement.

HOW IT IS FOUND

COLUMN NAME PA_L3_AFILIACION_SINDICAL — Path

95% `sindicato[a-z_]*` `sindical` `sindicalizado` `afiliaci[oó]n_?sindical` `cuota_?sindical` `delegado_?sindical` `seccional_?sindical` `gremio` `gremial` `asociacion_?(de_?)?(docentes|educadores|profesores|empleados)` `union_?member(ship)?` `trade_?union` `convencion_?colectiva`

VALUE FORMAT PA_L3_AFILIACION_SINDICAL — Values

PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — SUNTRACS, CONATO, CONUSI, CONATRAB, ASOPROF, AEVE, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`PA_CATEGORIA_SUPRIMIDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SUPRIMIR`.

> `PA_BANDERA` **REGEX DECOMPOSE**
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_SUPRIMIR` **SECURE LOOKUP**
>
> Replaces the value with one of the 1 values in `pa-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
SUNTRACS	→	**Sin información**

PART 10

Economic and credit data

The law does not call them sensitive, but it requires prior consent for economic, financial, banking and commercial data (art. 8, 3), protects data subjects from automated decisions about their credit (art. 19), and credit references have a law of their own, Law 24 of 2002. They go beyond the bank account: an APC credit reference, a pension amount, a MIDES program or a poverty status say as much about a person as their salary. Categories are replaced within their own notation; amounts are mapped into a plausible range unrelated to the real value.

10.1 Credit reference

PA_FIN_REFERENCIA_CREDITO

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

APC scores and references, days past due, delinquent portfolio, collection lawsuits, written-off accounts.

HOW IT IS FOUND

COLUMN NAME PA_FIN_REFERENCIA_CREDITO — Path

90% `apc` `referencia_?(de_?)?credito` `referencias_?crediticias` `historial_?(de_?)?credito` `historial_?crediticio` `score(_?(apc|crediticio|credito|riesgo))?` `puntaje_?(crediticio|apc|riesgo|credito)` `calificacion_?(crediticia|apc|riesgo)` `morosidad` `moroso` `morosa` `dias_?(de_?)?(atraso|mora)` `cartera_?(vencida|morosa)` `cobro_?judicial` `castigad[oa]` `estatus_?(credito|crediticio|cartera)` `estado_?(de_?)?(cuenta_?)?(credito|crediticio|cartera)` `credit_?score` `delinquen[a-z]*`

HOW IT IS MASKED

A score gets other digits, a flag stays a flag and any status is replaced by another credit status.

`PA_APC` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_REFERENCIA_CREDITO`.

> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_REFERENCIA_CREDITO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `pa-referencia-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Morosidad de 90 días	→	**Morosidad de 60 días**
745	→	**471**

10.2 Debt amount

PA_FIN_MONTO_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Balances of loans, cards and mortgages, past-due amounts, credit limits, installments.

HOW IT IS FOUND

> COLUMN NAME PA_FIN_MONTO_DEUDA — Path
>
> 85% `monto_?(deuda|adeudado|vencido|moroso|credito|prestamo|financiado|hipoteca)` `deuda(_?(total|vigente|vencida))?` `adeudo` `saldo_?(deudor|insoluto|vencido|moroso|credito|prestamo|tarjeta|hipoteca)` `limite_?(de_?)?credito` `linea_?(de_?)?credito` `pago_?minimo` `letra_?(mensual|prestamo|hipoteca)` `debt(_?amount)?` `outstanding_?balance`

> DATA TYPE PA_FIN_MONTO_DEUDA — Type
>
> Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
8500	→	**5134**

10.3 Salary and income

PA_FIN_INGRESO_MENSUAL

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Salary, thirteenth-month pay, household income.

HOW IT IS FOUND

COLUMN NAME PA_FIN_INGRESO_MENSUAL – Path

85% `salario[a-z_]*` `sueldo[a-z_]*` `remuneraci[oó]n[a-z_]*` `ingreso_?(mensual|neto|bruto|familiar|del_?hogar|hogar|per_?capita|total|promedio|declarado|laboral|anual)` `ingresos(_?[a-z]+)?` `decimo_?tercer_?mes` `xiii_?mes` `total_?devengado` `neto_?a_?pagar` `planilla_?(neta|bruta)` `gasto_?(mensual|familiar)` `capacidad_?(de_?)?pago` `salary` `wage` `income` `gross_?pay` `net_?pay`

DATA TYPE PA_FIN_INGRESO_MENSUAL – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
1850	→	**1958**

10.4 Assets

PA_FIN_PATRIMONIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Cadastral or market value of real estate and vehicles, savings, term deposits, net worth.

HOW IT IS FOUND

COLUMN NAME PA_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|total))?` `valor_?(catastral|comercial|avaluo|inmueble|propiedad|finca|vivienda|vehiculo|de_?la_?garantia)` `avaluo` `bienes_?(inmuebles|muebles)` `valor_?bienes` `activos_?(personales|totales)` `saldo_?(inversion|ahorro|ahorros|cuenta|plazo_?fijo)` `monto_?(inversion|ahorro|plazo_?fijo)` `net_?worth` `assets`

DATA TYPE PA_FIN_PATRIMONIO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
185000	→	477515

10.5 Pension and individual account

PA_FIN_PENSION

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

CSS retirement or pension amount, balance of the individual account, of SIACAP or of the severance fund.

HOW IT IS FOUND

COLUMN NAME PA_FIN_PENSION — Path

90% `monto_?(pension|jubilacion)` `pension_?(mensual|monto|vejez|invalidez|sobreviviente)` `jubilacion_?(mensual|monto)` `saldo_?(cuenta_?individual|siacap|retiro|fondo_?complementario)` `cuenta_?individual` `siacap` `fondo_?(de_?)?cesantia` `prima_?de_?antiguedad` `retirement_?balance`

DATA TYPE PA_FIN_PENSION — Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
680	→	227

10.6 Social security coverage

PA_FIN_SEGURO_SOCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

A person's standing with the Social Security Fund, in the census categories: direct insured, beneficiary, retired or pensioner, no social security. It reveals formal or informal work.

HOW IT IS FOUND

COLUMN NAME PA_FIN_SEGURO_SOCIAL — Path

90% `tipo_?(de_?)?(asegurado|seguro_?social|cobertura)` `condicion_?(de_?)?asegurado` `cobertura_?(css|salud|seguro_?social)` `afiliacion_?(a_?la_?)?(css|caja_?de_?seguro_?social|seguridad_?social)` `asegurado_?css` `es_?asegurado` `seguro_?(medico|de_?salud|privado)` `health_?insurance`

VALUE FORMAT PA_FIN_SEGURO_SOCIAL — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Asegurado directo, Beneficiario, Jubilado o pensionado por vejez, Pensionado por enfermedad o accidente, Jubilado o pensionado de otro país, No tiene seguro social, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the category is replaced by another.

`PA_SEGURO_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SEGURO_SOCIAL_LISTA`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_SEGURO_SOCIAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 6 values in `pa-seguro-social.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Beneficiario	→	**Jubilado o pensionado de otro país**

10.7 Social program

PA_FIN_PROGRAMA_SOCIAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Beneficiaries of transfer programs: MIDES's 120 a los 65, Red de Oportunidades, Ángel Guardián and Bono Alimenticio Nutricional, IFARHU's PASE-U and scholarships. Being a beneficiary reveals poverty, old age or disability.

HOW IT IS FOUND

COLUMN NAME PA_FIN_PROGRAMA_SOCIAL — Path

90% `programa_?(social|de_?transferencia|de_?apoyo|gobierno|mides)` `programas_?sociales` `beneficiario_?(de_?)?(programa|bono|beca|subsidio|mides)` `bono_?(solidario|alimenticio|nutricional|digital)` `vale_?digital` `subsidio_?(estatal|social|senadis)` `transferencia_?monetaria` `red_?(de_?)?oportunidades` `angel_?guardian` `120_?a_?los_?65` `pase_?u` `beca_?universal` `ifarhu` `senapan` `padron_?(de_?)?beneficiarios` `social_?program`

VALUE FORMAT PA_FIN_PROGRAMA_SOCIAL — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — 120 a los 65, Red de Oportunidades, Ángel Guardián, Bono Alimenticio Nutricional, PASE-U, Beca de excelencia IFARHU, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the program is replaced by another.

`PA_PROGRAMA_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_PROGRAMA_SOCIAL_LISTA`.

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`PA_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

`PA_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

`PA_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

`PA_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

`PA_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`PA_PROGRAMA_SOCIAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 9 values in `pa-programas-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Vale Digital	→	**Auxilio económico IFARHU**

10.8 Socioeconomic level

PA_FIN_NIVEL_SOCIOECONOMICO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Poverty status, income quintile or decile, multidimensional poverty index.

HOW IT IS FOUND

COLUMN NAME PA_FIN_NIVEL_SOCIOECONOMICO — Path

90% `nivel_?socioeconomico` `nivel_?socio_?economico` `estrato(_?socioeconomico)?` `clase_?social` `decil(_?(de_?)?ingresos?)?` `quintil(_?(de_?)?ingresos?)?` `pobreza(_?(extrema|general|multidimensional))?` `indice_?(de_?)?pobreza` `ipm` `vulnerabilidad(_?(social|economica))?` `carencias?` `socioeconomic_?level` `ficha_?socioeconomica`

VALUE FORMAT PA_FIN_NIVEL_SOCIOECONOMICO — Values

PATTERN	STRENGTH	NOTES
One of 10 known values, ignoring case — pobreza extrema, pobreza general, pobre, no pobre, indigente, vulnerable, …	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A quintile or decile becomes another number of the same range, with its prefix; a status, another from the list.

`PA_NIVEL_SOCIOECONOMICO` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PA_POBREZA`.

`PA_QUINTIL` SECURE LOOKUP

Replaces the value with one of the 5 values in `pa-quintil.txt`, chosen by a keyed hash.

`PA_DECIL_ALTO` SECURE LOOKUP

Replaces the value with one of the 5 values in `pa-decil-alto.txt`, chosen by a keyed hash.

`PA_DECIL` SECURE LOOKUP

Replaces the value with one of the 10 values in `pa-decil.txt`, chosen by a keyed hash.

`PA_POBREZA` SECURE LOOKUP

Replaces the value with one of the 4 values in `pa-pobreza.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Pobreza extrema`	→	**`Pobreza general`**
`Quintil 2`	→	**`Quintil 4`**

10.9 Housing tenure

PA_FIN_VIVIENDA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Whether the home is owned, mortgaged, rented, lent or an informal settlement, and its conditions.

HOW IT IS FOUND

COLUMN NAME PA_FIN_VIVIENDA — Path

95% `tenencia_?(de_?)?(la_?)?vivienda` `tipo_?(de_?)?vivienda` `situacion_?(de_?la_?)?vivienda` `vivienda_?(propia|alquilada|prestada)` `condicion_?(de_?)?(la_?)?vivienda` `material_?(de_?)?(la_?)?vivienda` `piso_?de_?tierra` `hacinamiento` `precarista` `invasion` `housing_?(type|tenure|status)`

VALUE FORMAT PA_FIN_VIVIENDA — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Propia, Propia hipotecada, Alquilada, Cedida o prestada, Condena, Otra situación, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Flags and codes keep their shape; the tenure is replaced by another from the census list.

`PA_VIVIENDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_VIVIENDA_LISTA`.

> `PA_BANDERA` **REGEX DECOMPOSE**
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_VIVIENDA_LISTA` **SECURE LOOKUP**
>
> Replaces the value with one of the 6 values in `pa-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Invasión	→	**Propia hipotecada**

PART 11

Criminal records

Criminal convictions have their own rules in the law (art. 30) and its regulation (Decree 285, art. 7), and are among the data most likely to give rise to discrimination. They get the same care as sensitive data.

11.1 Criminal record

PA_PENAL_ANTECEDENTES

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Police record (*récord policivo*), criminal record, sentences, offences, detentions and precautionary measures.

HOW IT IS FOUND

COLUMN NAME — PA_PENAL_ANTECEDENTES — Path

95% `antecedentes(_?(penales|judiciales|policivos|policiales|criminales))?` *(except when followed by list E8)*

`record_?(policivo|policial|penal|criminal)` `certificado_?(de_?)?antecedentes` `sentencia(_?condenatoria)?` `sentenciad[oa]` `condena(do|da)?` `delitos?` `tipo_?(de_?)?delito` `reincidente` `reincidencia` `imputad[oa]` `privado_?de_?libertad` `detencion_?provisional` `medida_?cautelar` `centro_?penitenciario` `pena` `reclusion` `libertad_?condicional` `criminal_?record` `conviction` `offen[cs]e` `detenid[oa]` `violencia_?domestica`

HOW IT IS MASKED

A flag stays a flag; any other value becomes a generic status: with a record, without a record, or no information.

`PA_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_ANTECEDENTES_LISTA`.

> `PA_BANDERA` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PA_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `PA_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.
>
> `PA_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `PA_ANTECEDENTES_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 3 values in `pa-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Condenado por hurto`	→	**`Sin antecedentes penales`**

11.2 Case number

PA_PENAL_CAUSA

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

Case file (*carpetilla*), investigation folder, case, court file or complaint numbers.

HOW IT IS FOUND

COLUMN NAME — PA_PENAL_CAUSA – Path

90% `carpetilla` `n(o|um|ro)_?carpetilla` `carpeta_?(de_?)?investigacion` `n(o|um|ro)_?carpeta` `causa_?penal` `n(o|um|ro|umero)_?(de_?)?causa` `expediente_?(judicial|penal)` `n(o|um|ro)_?expediente_?(judicial|penal)` `n(o|um|ro)_?(de_?)?denuncia` `folio_?denuncia` `n(o|um|ro)_?proceso` `case_?number`

VALUE FORMAT — PA_PENAL_CAUSA – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{12,15})`	40%	
`0*(?:\d{1,6}-\d{4})`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping length and format.

`PA_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
202400012345	→	**917747298420**

12

The RUC check digit, computed by the policy

A natural person's RUC check digit is two digits that the DGI computes over a 21-position table: the cédula fields right-aligned in fixed widths — asiento 5, tomo 3, a two-digit code for the letters (`AV` 15, `PI` 79, `E` 50, `N` 40, `PE` 75), province 2 — and a constant 5. Weights grow from 2 at the right, modulo 11, and a remainder of 0 or 1 gives 0; the second digit repeats the computation with the first one appended. A field longer than its width pushes the fields to its left, and a one-digit province with `AV` or `PI` is padded with two zeros.

No framework of the plugin does this: Check Digit can add weighted digits, but not pad fields or weigh letters. The policy does it with tables:

- The cédula is masked with the same algorithm as the cédula data class. Letters and separators are swapped for one-character markers, and the old DV is replaced by an initial state.
- The state — weighted sum, digit sum and position — travels through the value from right to left, one character per step. Each step is a Data Cleansing that turns *character + state* into *new state + character*.
- At the left end, a table turns the state into the two digits of the DV, and a second pass carries them back to where the old DV was.
- The markers become letters and separators again.

The tables are Data Cleansing files generated with the policy, and the steps are Regex Decompose algorithms joined in String Algorithm Chains of at most eight — the engine's limit. Every masked RUC has a valid DV and the mapping stays one-to-one. The price is a long algorithm tree under the data class and a step table of more than 30,000 lines.

13

Where people live: districts and corregimientos

With the data of the 2023 XII Population Census (INEC), the policy knows the population, district, province and location of each of the 699 corregimientos.

- A **corregimiento** under 10,000 inhabitants becomes the nearest corregimiento of its province or comarca with at least 10,000. Darién, Los Santos and the Emberá-Wounaan and Ngäbe-Buglé comarcas have none: theirs become the nearest one in the country.
- A **district** under 20,000 inhabitants becomes the nearest district of its province or comarca with at least 20,000, or of the country in the Emberá-Wounaan comarca.
- Distance is measured between centroids, a district's weighted by the population of its corregimientos.
- Sixty corregimiento names repeat — there are five San José —: a name is generalized only when every place bearing it is small. INEC codes have no such ambiguity.

The result is always a real place, near the original, and every group of people who end up sharing a name holds at least 10,000 inhabitants. Names that are also given names or surnames are left out of the detection list, so that a surname column is not taken for corregimientos.

14

Limits

- **Binary columns** — photos of the cédula, fingerprint images, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A DV in its own column** is not recomputed: it is masked, and no longer matches the masked RUC. Where the application validates a RUC and DV stored separately, validation fails.
- **The cédula letters stay.** `PI` still marks a registration as an indigenous Panamanian, and `E`, `N` and `PE` the status of foreigner, naturalized or born abroad. Changing them would break the format or make different cédulas collide. If that is sensitive in your case, handle it together with the ethnic origin or nationality column.
- **Cédulas with a zero-padded province** (`08-442-445`) or without hyphens are masked character by character, without recomputing the DV. An `NT` RUC is also masked without recomputing.
- **A legal entity's RUC stays.** A company with a single owner is still a legal entity under the law.
- **Data Cleansing leaves unknown values as they are**: a corregimiento spelled in a way the list does not have passes unchanged.
- **Free text** is redacted token by token: a phone written with spaces is not found, and a given name that is also a common word (`Luz`, `Rosa`) is redacted wherever it appears.
- **Minors** — a birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, barriada, corregimiento and district in separate columns are masked independently and no longer form a coherent address.
- **Plates and VINs** keep their format, but not the VIN check digit.

15

Verification

Before publication the policy was checked outside Delphix:

- The computation of the RUC check digit was first checked against the examples of the published algorithm.
- Every classifier configuration was reviewed against what Delphix accepts.
- Discovery was simulated on 138 columns with the whole policy at its assignment threshold — well named, badly named, and 24 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The algorithms, run with the Delphix algorithm plugin, masked 255 sample values and 210 placeholders such as `N/D` : RUCs with a DV in the four separators and the five letter types, checking each DV; 150 cédulas and 150 RUCs for collisions; and 20 people whose cédula and RUC must still agree.

Every column was assigned as expected and every value masked as expected. Before using the policy on real data, run a discovery job and a masking job on a representative copy.

16

Sources

- Law 81 of 26 March 2019, on Personal Data Protection — Gaceta Oficial 28743-A, 29 March 2019 (National Assembly, Legispan).

- Executive Decree 285 of 28 May 2021, regulating Law 81 of 2019.
- National Authority for Transparency and Access to Information (ANTAI), Personal Data Protection Directorate.
- Algorithm for the RUC check digit — Dirección General de Ingresos and the National Authority for Government Innovation.
- Format of the cédula and its letters — Electoral Tribunal, National Directorate of Identity Cards. Party membership, July and August 2026 — Electoral Tribunal.
- Population, code and location of the 699 corregimientos; indigenous and Afro-descendant groups; marital status; social security; schooling — XII National Population and VIII Housing Census 2023 (INEC), in the geographic service by corregimiento published with Esri Panamá.
- Most frequent surnames and given names — Civil Registry of the Electoral Tribunal.
- Certified disability types — National Secretariat for Disability (SENADIS). Transfer programs, 2026 — Ministry of Social Development (MIDES) and IFARHU (PASE-U).
- Credit references — Law 24 of 2002 and APC. Religion — 2015 national survey. Plates — Land Transit and Transport Authority (2013 format). Phone numbering — ASEP, National Numbering Plan. Postal codes — Correos y Telégrafos.

APPENDIX A

Algorithms

Every algorithm of the policy in alphabetical order, with its configuration. The one a data class names is the top of its tree; the others are building blocks.

PA_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_L2_ANIO_NACIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `PA_CM_ALFANUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_ANTECEDENTES_LISTA`.

Used by: `PA_PENAL_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_ANTECEDENTES_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 3 values in `pa-antecedentes.txt`, chosen by a keyed hash.

Used by: `PA_ANTECEDENTES`

CONFIGURATION

lookupFile	`pa-antecedentes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_APC REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_REFERENCIA_CREDITO`.

Used by: `PA_FIN_REFERENCIA_CREDITO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2,3}))`	keep · `PA_CM_ALFANUM`
`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
otherwise	`PA_REFERENCIA_CREDITO`

CONFIGURATION

trimInput	yes
requireMask	no

`PA_APELLIDO` NAME

Replaces the name with one of the 200 names in `pa-apellidos.txt`.

Used by: `PA_APELLIDOS`, `PA_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	`pa-apellidos.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

`PA_APELLIDOS` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_APELLIDO`, `PA_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`PA_APELLIDO`
`(\S+)\s+(\S+)`	`PA_APELLIDO` · `PA_APELLIDO`
`(\S+)(\s+)([Dd][Ee]|[Vv][Dd][Aa]\.?\s+[Dd][Ee])(\s+)(\S+)`	`PA_APELLIDO` · keep · keep · keep · `PA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`PA_APELLIDO` · `PA_APELLIDO` · `PA_APELLIDO`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

`PA_BANDERA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PA_CATEGORIA_SUPRIMIDA`, `PA_PUEBLO`, `PA_LENGUA_INDIGENA`, `PA_DIAGNOSTICO`, `PA_MEDICAMENTO`, `PA_DISCAPACIDAD`, `PA_ORIENTACION_SEXUAL`, `PA_IDENTIDAD_GENERO`, `PA_RELIGION`, `PA_OPINION_POLITICA`, `PA_PARTIDO_POLITICO`, `PA_APC`, `PA_SEGURO_SOCIAL`, `PA_PROGRAMA_SOCIAL`, `PA_VIVIENDA`, `PA_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no)`	`PA_BANDERA_SI_NO`
`(?i)(true|false)`	`PA_BANDERA_TRUE_FALSE`
`(?i)([sn])`	`PA_BANDERA_S_N`
`(?i)(y)`	`PA_BANDERA_Y_N`
`([01])`	`PA_BANDERA_0_1`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-0-1.txt`, chosen by a keyed hash.

Used by: `PA_BANDERA`

CONFIGURATION

lookupFile	`pa-bandera-0-1.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-s-n.txt`, chosen by a keyed hash.

Used by: `PA_BANDERA`

CONFIGURATION

lookupFile	`pa-bandera-s-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-si-no.txt`, chosen by a keyed hash.

Used by: `PA_BANDERA`

CONFIGURATION

lookupFile	`pa-bandera-si-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `PA_BANDERA`

CONFIGURATION

lookupFile	`pa-bandera-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `PA_BANDERA`

CONFIGURATION

lookupFile	`pa-bandera-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_BARRIADA SECURE LOOKUP

Replaces the value with one of the 75 values in `pa-barriadas.txt`, chosen by a keyed hash.

Used by: `PA_L2_BARRIADA`

CONFIGURATION

lookupFile	`pa-barriadas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_CANTIDAD_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PA_L2_DEPENDIENTES`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SUPRIMIR`.

Used by: `PA_L3_SALUD_SEXUAL_REPRODUCTIVA`, `PA_L3_SALUD_MENTAL_ADICCIONES`, `PA_L3_VIDA_SEXUAL`, `PA_L3_CREENCIA_FILOSOFICA_MORAL`, `PA_L3_AFILIACION_SINDICAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`

`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))`	keep · keep · keep · keep · keep · `PA_CM_ALFANUM`
otherwise	`PA_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

`PA_CEDULA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_CEDULA`, `PA_RUC`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]|1[0-3])([\s\-])(\d{1,4})([\s\-])(\d{1,6}))`	keep · `PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM`
`(0*?)(?:([1-9]|1[0-3])(AV|PI)([\s\-])(\d{1,4})([\s\-])(\d{1,6}))`	keep · `PA_PROVINCIA_CEDULA` · keep · keep · `PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM`
`(E)([\s\-])([1-9]|1[0-3])([\s\-])(\d{1,6})`	keep · keep · `PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM`
`(N|PE)([\s\-])(\d{1,4})([\s\-])(\d{1,6})`	keep · keep · `PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM`
`(0*?)(?:([1-9]|1[0-3])([\s\-]NT[\s\-])(\d{1,4})([\s\-])(\d{1,6}))`	keep · `PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

`PA_CIE10` SECURE LOOKUP

Replaces the value with one of the 37 values in `pa-cie10.txt`, chosen by a keyed hash.

Used by: `PA_DIAGNOSTICO`

CONFIGURATION

lookupFile	`pa-cie10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`PA_CIE10_DECIMAL` SECURE LOOKUP

Replaces the value with one of the 33 values in `pa-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `PA_DIAGNOSTICO`

CONFIGURATION

lookupFile	`pa-cie10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

PA_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: PA_L1_PASAPORTE, PA_L1_DOCUMENTO_MIGRATORIO, PA_L1_SEGURO_SOCIAL, PA_L1_IDONEIDAD, PA_L1_DIRECCION_COMPLEMENTO, PA_L1_CUENTA_BANCARIA, PA_L1_VIN, PA_L1_FINCA, PA_L1_NUMERO_CONTRATO, PA_L1_USUARIO_RRSS, PA_L3_SALUD_IDENTIFICADOR, PA_L3_SALUD_RESULTADO_EXAMEN, PA_PENAL_CAUSA, PA_CATEGORIA_SUPRIMIDA, PA_CEDULA, PA_RUC_DV_PREPARAR, PA_RUC, PA_DV, PA_NOMBRES, PA_APELLIDOS, PA_NOMBRE_COMPLETO, PA_EMAIL, PA_TELEFONO, PA_PLACA, PA_COORDENADA, PA_ANIO, PA_EDAD, PA_CODIGO_POSTAL, PA_PUEBLO, PA_LENGUA_INDIGENA, PA_MEDICAMENTO, PA_DISCAPACIDAD, PA_ORIENTACION_SEXUAL, PA_IDENTIDAD_GENERO, PA_RELIGION, PA_OPINION_POLITICA, PA_PARTIDO_POLITICO, PA_APC, PA_SEGURO_SOCIAL, PA_PROGRAMA_SOCIAL, PA_VIVIENDA, PA_ANTECEDENTES

CONFIGURATION

characterGroups	`0123456789` `AEIOU` `BCDFGHJKLMNPQRSTVWXYZ` `aeiou` `bcdfghjklmnpqrstvwxyz` `ÁÉÍÓÚÜ` `áéíóúü`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

PA_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: PA_L1_DISPOSITIVO, PA_IP

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

PA_CODIGO_CORREGIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_CODIGO_LUGAR

PATTERNS, TRIED IN ORDER

`(0*)([1-9]\d*)`	keep · `PA_CODIGO_CORREGIMIENTO_TABLA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_CODIGO_CORREGIMIENTO_TABLA DATA CLEANSING

Replaces each value found in `pa-codigo-corregimiento-generalizado.txt` (1,259 pairs) by its counterpart; values not in the file stay as they are.

Used by: PA_CODIGO_CORREGIMIENTO

CONFIGURATION

lookupFile	`pa-codigo-corregimiento-generalizado.txt`
delimiter	`,`
caseSensitive	yes

trimWhitespace	yes

PA_CODIGO_DISTRITO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_CODIGO_LUGAR

PATTERNS, TRIED IN ORDER

(0*)([1-9]\d*)	keep · PA_CODIGO_DISTRITO_TABLA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_CODIGO_DISTRITO_TABLA DATA CLEANSING

Replaces each value found in pa-codigo-distrito-generalizado.txt (146 pairs) by its counterpart; values not in the file stay as they are.

Used by: PA_CODIGO_DISTRITO

CONFIGURATION

lookupFile	pa-codigo-distrito-generalizado.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

PA_CODIGO_LUGAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PA_L2_CODIGO_LUGAR

PATTERNS, TRIED IN ORDER

(0*?)(?:((?:0[1-9]|1[0-3]|[1-9])\d{4}))	keep · PA_CODIGO_CORREGIMIENTO
(0*?)(?:((?:0[1-9]|1[0-3]|[1-9])\d{2}))	keep · PA_CODIGO_DISTRITO
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: PA_CM_ALFANUM.

Used by: PA_L2_CODIGO_POSTAL

PATTERNS, TRIED IN ORDER

(0*?)(?:(0[1-9]|1[0-3])(\d{2,3}))	keep · keep · each character → 0
otherwise	PA_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

PA_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PA_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)`	keep · `PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM`
`(-?\d{1,3}\.\d)(\d+)`	keep · `PA_CM_ALFANUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_CORREGIMIENTO DATA CLEANSING

Replaces each value found in `pa-corregimiento-generalizado.txt` (1,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_L2_CORREGIMIENTO`

CONFIGURATION

lookupFile	`pa-corregimiento-generalizado.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PA_DECIL SECURE LOOKUP

Replaces the value with one of the 10 values in `pa-decil.txt`, chosen by a keyed hash.

Used by: `PA_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`pa-decil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_DECIL_ALTO SECURE LOOKUP

Replaces the value with one of the 5 values in `pa-decil-alto.txt`, chosen by a keyed hash.

Used by: `PA_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`pa-decil-alto.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PA_DIAGNOSTICO_TEXTO`.

Used by: `PA_L3_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`PA_CIE10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3})`	`PA_CIE10`
`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
otherwise	`PA_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

PA_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `pa-diagnosticos.txt`, chosen by a keyed hash.

Used by: `PA_DIAGNOSTICO`

CONFIGURATION

lookupFile	`pa-diagnosticos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_DIRECCION SECURE LOOKUP

Replaces the value with one of the 3,000 values in `pa-direcciones.txt`, chosen by a keyed hash.

Used by: `PA_L1_DIRECCION`

CONFIGURATION

lookupFile	`pa-direcciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_DISCAPACIDAD_LISTA`.

Used by: `PA_L3_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_DISCAPACIDAD_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `pa-discapacidad.txt`, chosen by a keyed hash.

Used by: `PA_DISCAPACIDAD`

CONFIGURATION

lookupFile	`pa-discapacidad.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_DISTRITO DATA CLEANSING

Replaces each value found in `pa-distrito-generalizado.txt` (234 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_L2_DISTRITO`

CONFIGURATION

lookupFile	`pa-distrito-generalizado.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PA_DV REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_RUC_DV`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,2}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PA_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PA_L2_EDAD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`
`(0*?)(?:([1-9])(\d)(\.\d+))`	keep · keep · `PA_CM_ALFANUM` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `PA_CM_ALFANUM`
`(0*?)(?:(\d))`	keep · `PA_CM_ALFANUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_EMAIL`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24})`	`PA_CM_ALFANUM` · `PA_CM_ALFANUM` · replace with `test`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PA_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 25 values in `pa-empleadores.txt`, chosen by a keyed hash.

Used by: `PA_L2_EMPLEADOR`

CONFIGURATION

lookupFile	`pa-empleadores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_ESCOLARIDAD SECURE LOOKUP

Replaces the value with one of the 13 values in `pa-escolaridad.txt`, chosen by a keyed hash.

Used by: `PA_L2_ESCOLARIDAD`

CONFIGURATION

lookupFile	`pa-escolaridad.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_ESCUELA SECURE LOOKUP

Replaces the value with one of the 15 values in `pa-escuelas.txt`, chosen by a keyed hash.

Used by: `PA_L2_ESCUELA`

CONFIGURATION

lookupFile	`pa-escuelas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_ESTADO_CIVIL SECURE LOOKUP

Replaces the value with one of the 7 values in `pa-estado-civil.txt`, chosen by a keyed hash.

Used by: `PA_L2_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`pa-estado-civil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `PA_L2_FECHA_EVENTO`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

PA_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `PA_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

PA_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_IDENTIDAD_GENERO_LISTA`.

Used by: `PA_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_IDENTIDAD_GENERO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `pa-identidad-genero.txt`, chosen by a keyed hash.

Used by: `PA_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	`pa-identidad-genero.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PA_CM_HEX`.

Used by: `PA_L1_IP`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `PA_OCTETO` · `PA_OCTETO` · `PA_OCTETO` · `PA_OCTETO`
otherwise	`PA_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

PA_LENGUA_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_LENGUA_INDIGENA_LISTA`.

Used by: `PA_L3_LENGUA_INDIGENA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_LENGUA_INDIGENA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_LENGUA_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `pa-lenguas.txt`, chosen by a keyed hash.

Used by: `PA_LENGUA_INDIGENA`

CONFIGURATION

lookupFile	`pa-lenguas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

PA_LUGAR_POBLADO SECURE LOOKUP

Replaces the value with one of the 52 values in `pa-lugares-poblados.txt`, chosen by a keyed hash.

Used by: `PA_L2_LUGAR_POBLADO`

CONFIGURATION

lookupFile	`pa-lugares-poblados.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_MEDICAMENTO_LISTA`.

Used by: `PA_L3_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 26 values in `pa-medicamentos.txt`, chosen by a keyed hash.

Used by: `PA_MEDICAMENTO`

CONFIGURATION

lookupFile	`pa-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 20 values in `pa-nacionalidades.txt`, chosen by a keyed hash.

Used by: `PA_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	`pa-nacionalidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PA_POBREZA`.

Used by: `PA_FIN_NIVEL_SOCIOECONOMICO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-5]))`	keep · `PA_QUINTIL`
`(0*?)(?:([6-9]|10))`	keep · `PA_DECIL_ALTO`
`(?i)(decil\s*)(\d{1,2})`	keep · `PA_DECIL`
`(?i)(quintil\s*)([1-5])`	keep · `PA_QUINTIL`
otherwise	`PA_POBREZA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 8 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`PA_APELLIDOS` · `PA_NOMBRES`
`(\S+)`	`PA_NOMBRE_PILA`
`(\S+)\s+(\S+)`	`PA_NOMBRE_PILA` · `PA_APELLIDO`
`(\S+)(\s+)(\S+)(\s+)([Dd][Ee]|[Vv][Dd][Aa]\.?\s+[Dd][Ee])(\s+)(\S+)`	`PA_NOMBRE_PILA` · keep · `PA_APELLIDO` · keep · keep · keep · `PA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`PA_NOMBRE_PILA` · `PA_APELLIDO` · `PA_APELLIDO`
`(\S+)(\s+)(\S+)(\s+)(\S+)(\s+)([Dd][Ee]|[Vv][Dd][Aa]\.?\s+[Dd][Ee])(\s+)(\S+)`	`PA_NOMBRE_PILA` · keep · `PA_NOMBRE_PILA` · keep · `PA_APELLIDO` · keep · keep · keep · `PA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PA_NOMBRE_PILA` · `PA_NOMBRE_PILA` · `PA_APELLIDO` · `PA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PA_NOMBRE_PILA` · `PA_NOMBRE_PILA` · `PA_NOMBRE_PILA` · `PA_APELLIDO` · `PA_APELLIDO`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PA_NOMBRE_PILA NAME

Replaces the name with one of the 253 names in `pa-nombres.txt`.

Used by: `PA_NOMBRES`, `PA_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	`pa-nombres.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

PA_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_NOMBRE`, `PA_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`PA_NOMBRE_PILA`
`(\S+)\s+(\S+)`	`PA_NOMBRE_PILA` · `PA_NOMBRE_PILA`
`(\S+)\s+(\S+)\s+(\S+)`	`PA_NOMBRE_PILA` · `PA_NOMBRE_PILA` · `PA_NOMBRE_PILA`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PA_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `PA_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

PA_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in `pa-ocupaciones.txt`, chosen by a keyed hash.

Used by: `PA_L2_OCUPACION`

CONFIGURATION

lookupFile	`pa-ocupaciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_OPINION_POLITICA_LISTA`.

Used by: `PA_L3_OPINION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_OPINION_POLITICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `pa-opiniones-politicas.txt`, chosen by a keyed hash.

Used by: `PA_OPINION_POLITICA`

CONFIGURATION

lookupFile	`pa-opiniones-politicas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_ORIENTACION_SEXUAL_LISTA`.

Used by: `PA_L3_ORIENTACION_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_ORIENTACION_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `pa-orientacion-sexual.txt`, chosen by a keyed hash.

Used by: `PA_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	`pa-orientacion-sexual.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_PARTIDO_POLITICO_LISTA`.

Used by: `PA_L3_AFILIACION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_PARTIDO_POLITICO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `pa-partidos.txt`, chosen by a keyed hash.

Used by: `PA_PARTIDO_POLITICO`

CONFIGURATION

lookupFile	`pa-partidos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_PLACA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_PLACA`

PATTERNS, TRIED IN ORDER

`(ADM|MB|MI|PR|BC|CD|CC|M|T|B|G|D|E)([\s\-]?)(\d{3,6})`	keep · keep · `PA_CM_ALFANUM`
`([A-Z]{2})([\s\-]?)(\d{4})`	`PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM`
`(0*?)(?:(\d{6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PA_POBREZA SECURE LOOKUP

Replaces the value with one of the 4 values in `pa-pobreza.txt`, chosen by a keyed hash.

Used by: `PA_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`pa-pobreza.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_PROGRAMA_SOCIAL_LISTA`.

Used by: `PA_FIN_PROGRAMA_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_PROGRAMA_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `pa-programas-sociales.txt`, chosen by a keyed hash.

Used by: `PA_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	`pa-programas-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_PROVINCIA_CEDULA NUMERIC MAPPING

Maps the number to another between 1 and 13.

Used by: `PA_CEDULA`, `PA_RUC_DV_PREPARAR`, `PA_RUC`

CONFIGURATION

minValue	`1`
maxValue	`13`

PA_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_PUEBLO_LISTA`.

Used by: `PA_L3_ETNIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_PUEBLO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_PUEBLO_LISTA SECURE LOOKUP

Replaces the value with one of the 16 values in `pa-pueblos.txt`, chosen by a keyed hash.

Used by: `PA_PUEBLO`

CONFIGURATION

lookupFile	`pa-pueblos.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in pa-quintil.txt, chosen by a keyed hash.

Used by: PA_NIVEL_SOCIOECONOMICO

CONFIGURATION

lookupFile	pa-quintil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_L1_CREDENCIAL, PA_L3_BIOMETRICO, PA_L3_INFORMACION_GENETICA

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_REFERENCIA_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in pa-referencia-credito.txt, chosen by a keyed hash.

Used by: PA_APC

CONFIGURATION

lookupFile	pa-referencia-credito.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PA_RELIGION_LISTA.

Used by: PA_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|[sny01])	PA_BANDERA
(0*?)(?:(\d{1,6}))	keep · PA_CM_ALFANUM
otherwise	PA_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

PA_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 14 values in `pa-religiones.txt`, chosen by a keyed hash.

Used by: `PA_RELIGION`

CONFIGURATION

lookupFile	`pa-religiones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_RUC REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PA_CM_ALFANUM`.

Used by: `PA_L1_RUC`

PATTERNS, TRIED IN ORDER

`(0*?)(?:((?:(?:[1-9]|1[0-3])(?:AV|PI)?-\d{1,4}-\d{1,6}|(?:E|N|PE)-\d{1,4}-\d{1,6})(?: +DV +| +DV|-| +)\d{2}))`	keep · `PA_RUC_DV`
`(0*?)(?:((?:(?:[1-9]|1[0-3])(?:AV|PI)?-\d{1,4}-\d{1,6}|(?:E|N|PE)-\d{1,4}-\d{1,6})))`	keep · `PA_CEDULA`
`(0*?)(?:([1-9]|1[0-3])(-NT-)(\d{1,4})(-)(\d{1,6})(.*))`	keep · `PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · keep · `PA_CM_ALFANUM` · `PA_CM_ALFANUM`
`(0*?)(?:(\d{3,10}-\d{1,4}-\d{1,7}.*))`	keep · keep
otherwise	`PA_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV STRING ALGORITHM CHAIN

Applies `PA_RUC_DV_1` → `PA_RUC_DV_2` → `PA_RUC_DV_3` → `PA_RUC_DV_4` → `PA_RUC_DV_5`, in this order.

Used by: `PA_RUC`

CONFIGURATION

algorithmReferences[1]	`PA_RUC_DV_1`
algorithmReferences[2]	`PA_RUC_DV_2`
algorithmReferences[3]	`PA_RUC_DV_3`
algorithmReferences[4]	`PA_RUC_DV_4`
algorithmReferences[5]	`PA_RUC_DV_5`

PA_RUC_DV_1 STRING ALGORITHM CHAIN

Applies `PA_RUC_DV_PREPARAR` → `PA_RUC_DV_IDA_01` → `PA_RUC_DV_IDA_02` → `PA_RUC_DV_IDA_03` → `PA_RUC_DV_IDA_04` → `PA_RUC_DV_IDA_05` → `PA_RUC_DV_IDA_06` → `PA_RUC_DV_IDA_07`, in this order.

Used by: `PA_RUC_DV`

CONFIGURATION

`algorithmReferences[1]`	`PA_RUC_DV_PREPARAR`
`algorithmReferences[2]`	`PA_RUC_DV_IDA_01`
`algorithmReferences[3]`	`PA_RUC_DV_IDA_02`
`algorithmReferences[4]`	`PA_RUC_DV_IDA_03`
`algorithmReferences[5]`	`PA_RUC_DV_IDA_04`
`algorithmReferences[6]`	`PA_RUC_DV_IDA_05`
`algorithmReferences[7]`	`PA_RUC_DV_IDA_06`
`algorithmReferences[8]`	`PA_RUC_DV_IDA_07`

`PA_RUC_DV_2` STRING ALGORITHM CHAIN

Applies `PA_RUC_DV_IDA_08` → `PA_RUC_DV_IDA_09` → `PA_RUC_DV_IDA_10` → `PA_RUC_DV_IDA_11` → `PA_RUC_DV_IDA_12` → `PA_RUC_DV_IDA_13` → `PA_RUC_DV_IDA_14` → `PA_RUC_DV_IDA_15`, in this order.

Used by: `PA_RUC_DV`

CONFIGURATION

`algorithmReferences[1]`	`PA_RUC_DV_IDA_08`
`algorithmReferences[2]`	`PA_RUC_DV_IDA_09`
`algorithmReferences[3]`	`PA_RUC_DV_IDA_10`
`algorithmReferences[4]`	`PA_RUC_DV_IDA_11`
`algorithmReferences[5]`	`PA_RUC_DV_IDA_12`
`algorithmReferences[6]`	`PA_RUC_DV_IDA_13`
`algorithmReferences[7]`	`PA_RUC_DV_IDA_14`
`algorithmReferences[8]`	`PA_RUC_DV_IDA_15`

`PA_RUC_DV_3` STRING ALGORITHM CHAIN

Applies `PA_RUC_DV_CALCULAR` → `PA_RUC_DV_VUELTA_01` → `PA_RUC_DV_VUELTA_02` → `PA_RUC_DV_VUELTA_03` → `PA_RUC_DV_VUELTA_04` → `PA_RUC_DV_VUELTA_05` → `PA_RUC_DV_VUELTA_06` → `PA_RUC_DV_VUELTA_07`, in this order.

Used by: `PA_RUC_DV`

CONFIGURATION

`algorithmReferences[1]`	`PA_RUC_DV_CALCULAR`
`algorithmReferences[2]`	`PA_RUC_DV_VUELTA_01`
`algorithmReferences[3]`	`PA_RUC_DV_VUELTA_02`
`algorithmReferences[4]`	`PA_RUC_DV_VUELTA_03`
`algorithmReferences[5]`	`PA_RUC_DV_VUELTA_04`
`algorithmReferences[6]`	`PA_RUC_DV_VUELTA_05`
`algorithmReferences[7]`	`PA_RUC_DV_VUELTA_06`
`algorithmReferences[8]`	`PA_RUC_DV_VUELTA_07`

`PA_RUC_DV_4` STRING ALGORITHM CHAIN

Applies `PA_RUC_DV_VUELTA_08` → `PA_RUC_DV_VUELTA_09` → `PA_RUC_DV_VUELTA_10` → `PA_RUC_DV_VUELTA_11` → `PA_RUC_DV_VUELTA_12` → `PA_RUC_DV_VUELTA_13` → `PA_RUC_DV_VUELTA_14` → `PA_RUC_DV_VUELTA_15`, in this order.

Used by: `PA_RUC_DV`

CONFIGURATION

`algorithmReferences[1]`	`PA_RUC_DV_VUELTA_08`
`algorithmReferences[2]`	`PA_RUC_DV_VUELTA_09`
`algorithmReferences[3]`	`PA_RUC_DV_VUELTA_10`
`algorithmReferences[4]`	`PA_RUC_DV_VUELTA_11`
`algorithmReferences[5]`	`PA_RUC_DV_VUELTA_12`
`algorithmReferences[6]`	`PA_RUC_DV_VUELTA_13`
`algorithmReferences[7]`	`PA_RUC_DV_VUELTA_14`
`algorithmReferences[8]`	`PA_RUC_DV_VUELTA_15`

PA_RUC_DV_5 STRING ALGORITHM CHAIN

Applies `PA_RUC_DV_VUELTA_16` → `PA_RUC_DV_RESTAURAR`, in this order.

Used by: `PA_RUC_DV`

CONFIGURATION

`algorithmReferences[1]`	`PA_RUC_DV_VUELTA_16`
`algorithmReferences[2]`	`PA_RUC_DV_RESTAURAR`

PA_RUC_DV_CALCULAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_3`

PATTERNS, TRIED IN ORDER

`(.{3})(.*)`	`PA_RUC_DV_RESULTADO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PA_RUC_DV_IDA_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_1`

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{1})`	keep · `PA_RUC_DV_PASO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PA_RUC_DV_IDA_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_1`

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{2})`	keep · `PA_RUC_DV_PASO` · keep
`otherwise`	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_1

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{3})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_1

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{4})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_1

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{5})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_1

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{6})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

PA_RUC_DV_IDA_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_1

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{7})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{8})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{9})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

(.*)(.{4})(.{10})	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{11})`	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{12})`	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{13})`	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_2

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{14})`	keep · PA_RUC_DV_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_IDA_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_2`

PATTERNS, TRIED IN ORDER

`(.*)(.{4})(.{15})`	keep · `PA_RUC_DV_PASO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_LETRAS DATA CLEANSING

Replaces each value found in `pa-ruc-dv-letras.txt` (5 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_RUC_DV_PREPARAR`

CONFIGURATION

lookupFile	`pa-ruc-dv-letras.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

PA_RUC_DV_LETRAS_DE_VUELTA DATA CLEANSING

Replaces each value found in `pa-ruc-dv-letras-de-vuelta.txt` (5 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_RUC_DV_RESTAURAR`

CONFIGURATION

lookupFile	`pa-ruc-dv-letras-de-vuelta.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

PA_RUC_DV_PASO DATA CLEANSING

Replaces each value found in `pa-ruc-dv-paso.txt` (32,317 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_RUC_DV_IDA_01`, `PA_RUC_DV_IDA_02`, `PA_RUC_DV_IDA_03`, `PA_RUC_DV_IDA_04`, `PA_RUC_DV_IDA_05`, `PA_RUC_DV_IDA_06`, `PA_RUC_DV_IDA_07`, `PA_RUC_DV_IDA_08`, `PA_RUC_DV_IDA_09`, `PA_RUC_DV_IDA_10`, `PA_RUC_DV_IDA_11`, `PA_RUC_DV_IDA_12`, `PA_RUC_DV_IDA_13`, `PA_RUC_DV_IDA_14`, `PA_RUC_DV_IDA_15`

CONFIGURATION

lookupFile	`pa-ruc-dv-paso.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

PA_RUC_DV_PREPARAR REGEX DECOMPOSE

Tries 16 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_1`

PATTERNS, TRIED IN ORDER

`([1-9]|1[0-3])(-)(\d{1,4})(-)(\d{1,6})( +DV +)(\d{2})`	`PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a!` · remove
`([1-9]|1[0-3])(AV|PI)(-)(\d{1,4})(-)(\d{1,6})( +DV +)(\d{2})`	`PA_PROVINCIA_CEDULA` · `PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a!` · remove
`(E)(-)([1-9]|1[0-3])(-)(\d{1,6})( +DV +)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_PROVINCIA_CEDULA` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a!` · remove
`(N|PE)(-)(\d{1,4})(-)(\d{1,6})( +DV +)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a!` · remove
`([1-9]|1[0-3])(-)(\d{1,4})(-)(\d{1,6})( +DV)(\d{2})`	`PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a#` · remove
`([1-9]|1[0-3])(AV|PI)(-)(\d{1,4})(-)(\d{1,6})( +DV)(\d{2})`	`PA_PROVINCIA_CEDULA` · `PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a#` · remove
`(E)(-)([1-9]|1[0-3])(-)(\d{1,6})( +DV)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_PROVINCIA_CEDULA` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a#` · remove
`(N|PE)(-)(\d{1,4})(-)(\d{1,6})( +DV)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a#` · remove
`([1-9]|1[0-3])(-)(\d{1,4})(-)(\d{1,6})(-)(\d{2})`	`PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a$` · remove
`([1-9]|1[0-3])(AV|PI)(-)(\d{1,4})(-)(\d{1,6})(-)(\d{2})`	`PA_PROVINCIA_CEDULA` · `PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a$` · remove
`(E)(-)([1-9]|1[0-3])(-)(\d{1,6})(-)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_PROVINCIA_CEDULA` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a$` · remove
`(N|PE)(-)(\d{1,4})(-)(\d{1,6})(-)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a$` · remove
`([1-9]|1[0-3])(-)(\d{1,4})(-)(\d{1,6})( +)(\d{2})`	`PA_PROVINCIA_CEDULA` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a%` · remove
`([1-9]|1[0-3])(AV|PI)(-)(\d{1,4})(-)(\d{1,6})( +)(\d{2})`	`PA_PROVINCIA_CEDULA` · `PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a%` · remove
`(E)(-)([1-9]|1[0-3])(-)(\d{1,6})( +)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_PROVINCIA_CEDULA` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a%` · remove
`(N|PE)(-)(\d{1,4})(-)(\d{1,6})( +)(\d{2})`	`PA_RUC_DV_LETRAS` · keep · `PA_CM_ALFANUM` · replace with `_` · `PA_CM_ALFANUM` · replace with `00a%` · remove
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_RESTAURAR REGEX DECOMPOSE

Tries 12 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_5`

PATTERNS, TRIED IN ORDER

`(\d{1,2})(-)(\d{1,4})(_)(\d{1,6})(\!)(\d\d)`	keep · keep · keep · replace with `-` · keep · replace with `DV` · keep
`(\d{1,2})([vi])(-)(\d{1,4})(_)(\d{1,6})(\!)(\d\d)`	keep · `PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `-` · keep · replace with `DV` · keep
`([enq])(-)(\d{1,4})(_)(\d{1,6})(\!)(\d\d)`	`PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `-` · keep · replace with `DV` · keep
`(\d{1,2})(-)(\d{1,4})(_)(\d{1,6})(\#)(\d\d)`	keep · keep · keep · replace with `-` · keep · replace with `DV` · keep
`(\d{1,2})([vi])(-)(\d{1,4})(_)(\d{1,6})(\#)(\d\d)`	keep · `PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `-` · keep · replace with `DV` · keep

`([enq])(–)(\d{1,4})(_)(\d{1,6})(\#)(\d\d)`	`PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `–` · keep · replace with `DV` · keep
`(\d{1,2})(–)(\d{1,4})(_)(\d{1,6})(\$)(\d\d)`	keep · keep · keep · replace with `–` · keep · replace with `–` · keep
`(\d{1,2})([vi])(–)(\d{1,4})(_)(\d{1,6})(\$)(\d\d)`	keep · `PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `–` · keep · replace with `–` · keep
`([enq])(–)(\d{1,4})(_)(\d{1,6})(\$)(\d\d)`	`PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `–` · keep · replace with `–` · keep
`(\d{1,2})(–)(\d{1,4})(_)(\d{1,6})(\%)(\d\d)`	keep · keep · keep · replace with `–` · keep · replace with ` ` · keep
`(\d{1,2})([vi])(–)(\d{1,4})(_)(\d{1,6})(\%)(\d\d)`	keep · `PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `–` · keep · replace with ` ` · keep
`([enq])(–)(\d{1,4})(_)(\d{1,6})(\%)(\d\d)`	`PA_RUC_DV_LETRAS_DE_VUELTA` · keep · keep · replace with `–` · keep · replace with ` ` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_RESULTADO DATA CLEANSING

Replaces each value found in `pa-ruc-dv-resultado.txt` (1,815 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_RUC_DV_CALCULAR`

CONFIGURATION

lookupFile	`pa-ruc-dv-resultado.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

PA_RUC_DV_TRASLADO DATA CLEANSING

Replaces each value found in `pa-ruc-dv-traslado.txt` (2,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PA_RUC_DV_VUELTA_01`, `PA_RUC_DV_VUELTA_02`, `PA_RUC_DV_VUELTA_03`, `PA_RUC_DV_VUELTA_04`, `PA_RUC_DV_VUELTA_05`, `PA_RUC_DV_VUELTA_06`, `PA_RUC_DV_VUELTA_07`, `PA_RUC_DV_VUELTA_08`, `PA_RUC_DV_VUELTA_09`, `PA_RUC_DV_VUELTA_10`, `PA_RUC_DV_VUELTA_11`, `PA_RUC_DV_VUELTA_12`, `PA_RUC_DV_VUELTA_13`, `PA_RUC_DV_VUELTA_14`, `PA_RUC_DV_VUELTA_15`, `PA_RUC_DV_VUELTA_16`

CONFIGURATION

lookupFile	`pa-ruc-dv-traslado.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

PA_RUC_DV_VUELTA_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_3`

PATTERNS, TRIED IN ORDER

`(.{0})(.{3})(.*)`	keep · `PA_RUC_DV_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_3

PATTERNS, TRIED IN ORDER

(.{1})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_3

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_3

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_3

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

PA_RUC_DV_VUELTA_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_3

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_3

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_4

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_4

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_4

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_4

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_4

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_RUC_DV_4

PATTERNS, TRIED IN ORDER

(.{12})(.{3})(.*)	keep · PA_RUC_DV_TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_4`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `PA_RUC_DV_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_4`

PATTERNS, TRIED IN ORDER

`(.{14})(.{3})(.*)`	keep · `PA_RUC_DV_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_RUC_DV_VUELTA_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PA_RUC_DV_5`

PATTERNS, TRIED IN ORDER

`(.{15})(.{3})(.*)`	keep · `PA_RUC_DV_TRASLADO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_SEGURO_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PA_SEGURO_SOCIAL_LISTA`.

Used by: `PA_FIN_SEGURO_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,2}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_SEGURO_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_SEGURO_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `pa-seguro-social.txt`, chosen by a keyed hash.

Used by: `PA_SEGURO_SOCIAL`

CONFIGURATION

lookupFile	pa-seguro-social.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_SEXO REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PA_L2_SEXO

PATTERNS, TRIED IN ORDER

(?i)(femenino|masculino)	PA_SEXO_PALABRA
(?i)(mujer|hombre)	PA_SEXO_MUJER_HOMBRE
(?i)(female|male)	PA_SEXO_INGLES
(?i)([fm])	PA_SEXO_F_M
(?i)([hm])	PA_SEXO_H_M
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in pa-sexo-f-m.txt , chosen by a keyed hash.

Used by: PA_SEXO

CONFIGURATION

lookupFile	pa-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in pa-sexo-h-m.txt , chosen by a keyed hash.

Used by: PA_SEXO

CONFIGURATION

lookupFile	pa-sexo-h-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_SEXO_INGLES SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-ingles.txt`, chosen by a keyed hash.

Used by: `PA_SEXO`

CONFIGURATION

lookupFile	`pa-sexo-ingles.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `PA_SEXO`

CONFIGURATION

lookupFile	`pa-sexo-mujer-hombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_SEXO_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in `pa-sexo-palabra.txt`, chosen by a keyed hash.

Used by: `PA_SEXO`

CONFIGURATION

lookupFile	`pa-sexo-palabra.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `pa-sin-informacion.txt`, chosen by a keyed hash.

Used by: `PA_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`pa-sin-informacion.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PA_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PA_L1_TARJETA

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d[\d\s\-]{11,22}\d))	keep · dlpx-core:Credit Card
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PA_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PA_CM_ALFANUM .

Used by: PA_L1_TELEFONO

PATTERNS, TRIED IN ORDER

(0*?)(?:(\+?\(?507\)?[\s\-]?)?(6)(\d{3})([\s\-]?)(\d{4}))	keep · keep · keep · PA_CM_ALFANUM · keep · PA_CM_ALFANUM
(0*?)(?:(\+?\(?507\)?[\s\-]?)?([2-9])(\d{2})([\s\-]?)(\d{4}))	keep · keep · keep · PA_CM_ALFANUM · keep · PA_CM_ALFANUM
otherwise	PA_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

PA_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 7 patterns with [DATO] , and the 1,094 terms of pa-texto-nombres.txt with [NOMBRE] .

Used by: PA_L1_TEXTO_LIBRE , PA_L3_SALUD_TEXTO_CLINICO

PATTERNS, TRIED IN ORDER

(?<![\w\-])(([1-9]|1[0-3])(AV|PI)?|E|N|PE)-\d{1,4}-\d{1,6}(?![\w\-])
[\w.+\-]+@[\w\-]+(\.[\w\-]+)+
(?<!\d)(\+?507)?6\d{3}-?\d{4}(?!\d)
(?<![\d\-])[2-9]\d{2}-\d{4}(?![\d\-])
(?<!\d)\d{13,19}(?!\d)
(?<![A-Za-z])[A-Z]{2}\d{4}(?![A-Za-z\d])
(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)

CONFIGURATION

regExRedactValue	[DATO]
lookupFile	pa-texto-nombres.txt
lookupFileRedactValue	[NOMBRE]
isDenyList	yes

PA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PA_VIVIENDA_LISTA .

Used by: PA_FIN_VIVIENDA

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|[sny01])`	`PA_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `PA_CM_ALFANUM`
otherwise	`PA_VIVIENDA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `pa-vivienda.txt`, chosen by a keyed hash.

Used by: `PA_VIVIENDA`

CONFIGURATION

lookupFile	`pa-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the policy reads. In Delphix each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`pa-antecedentes.txt`	3	`PA_ANTECEDENTES_LISTA`	Sin antecedentes penales · Con antecedentes penales · Sin información
`pa-apellidos.txt`	200	`PA_APELLIDO`	Rodríguez · González · Sánchez · Martínez
`pa-bandera-0-1.txt`	2	`PA_BANDERA_0_1`	0 · 1
`pa-bandera-s-n.txt`	2	`PA_BANDERA_S_N`	S · N
`pa-bandera-si-no.txt`	2	`PA_BANDERA_SI_NO`	Sí · No
`pa-bandera-true-false.txt`	2	`PA_BANDERA_TRUE_FALSE`	true · false
`pa-bandera-y-n.txt`	2	`PA_BANDERA_Y_N`	Y · N
`pa-barriadas.txt`	75	`PA_BARRIADA`	Villa Lucre · Condado del Rey · Brisas del Golf · Altos de Panamá
`pa-cie10-decimal.txt`	33	`PA_CIE10_DECIMAL`	E11.9 · E78.5 · J45.9 · J06.9
`pa-cie10.txt`	37	`PA_CIE10`	I10 · E11 · E78 · J45
`pa-codigo-corregimiento-generalizado.txt`	1,259	`PA_CODIGO_CORREGIMIENTO_TABLA`	010101,010206 · 10101,10206 · 010102,010206 · 10102,10206
`pa-codigo-distrito-generalizado.txt`	146	`PA_CODIGO_DISTRITO_TABLA`	0101,0104 · 101,104 · 0102,0102 · 102,102
`pa-corregimiento-generalizado.txt`	1,760	`PA_CORREGIMIENTO`	Bocas del Toro|El Empalme · BOCAS DEL TORO|EL EMPALME · Bastimentos|El Empalme · BASTIMENTOS|EL EMPALME
`pa-decil-alto.txt`	5	`PA_DECIL_ALTO`	6 · 7 · 8 · 9
`pa-decil.txt`	10	`PA_DECIL`	1 · 2 · 3 · 4
`pa-detectar-apellidos.txt`	258	`PA_L1_APELLIDO – List` `PA_L1_NOMBRE_COMPLETO – List`	Rodríguez · Rodriguez · González · Gonzalez
`pa-detectar-nombres.txt`	291	`PA_L1_NOMBRE – List` `PA_L1_NOMBRE_COMPLETO – List`	María · Maria · José · Jose
`pa-detectar-sexo-letra.txt`	3	`PA_L2_SEXO – List`	h · m · f

FILE	LINES	USED BY	FIRST LINES
pa-detectar-sexo.txt	8	PA_L2_SEXO — List	hombre · mujer · femenino · masculino
pa-diagnosticos.txt	30	PA_DIAGNOSTICO_TEXTO	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma bronquial · Lumbalgia
pa-direcciones.txt	3,000	PA_DIRECCION	Barriada Villa del Carmen, Calle 5 D, Casa 389 · Don Bosco, Calle 14 B, Casa 147 · Calle 63, Edificio Torre del Mar, Piso 10, Apto. 16E · Villa Grecia, Casa No. 46
pa-discapacidad.txt	8	PA_DISCAPACIDAD_LISTA	Física · Visual · Auditiva · Intelectual
pa-distrito-generalizado.txt	234	PA_DISTRITO	Bocas del Toro|Almirante · BOCAS DEL TORO|ALMIRANTE · Changuinola|Changuinola · CHANGUINOLA|CHANGUINOLA
pa-empleadores.txt	25	PA_EMPLEADOR	Comercializadora del Istmo, S.A. · Servicios Integrales del Pacífico, S.A. · Constructora Cerro Ancón, S.A. · Transportes Canal Seguro, S.A.
pa-escolaridad.txt	13	PA_ESCOLARIDAD	Ningún grado · Primaria incompleta · Primaria completa · Premedia incompleta
pa-escuelas.txt	15	PA_ESCUELA	Escuela República de Colombia · Escuela Juan Demóstenes Arosemena · Centro Básico General Las Mañanitas · Centro de Educación Básica General Guararé
pa-estado-civil.txt	7	PA_ESTADO_CIVIL	Unido · Casado · Soltero · Separado de matrimonio
pa-identidad-genero.txt	8	PA_IDENTIDAD_GENERO_LISTA	Mujer · Hombre · Mujer trans · Hombre trans
pa-lenguas.txt	9	PA_LENGUA_INDIGENA_LISTA	Ngäbere · Buglere · Guna · Emberá
pa-lugares-poblados.txt	52	PA_LUGAR_POBLADO	Penonomé · Cativá · Sabanitas · San Juan
pa-medicamentos.txt	26	PA_MEDICAMENTO_LISTA	Acetaminofén · Ibuprofeno · Naproxeno · Diclofenaco
pa-nacionalidades.txt	20	PA_NACIONALIDAD	Panameña · Colombiana · Venezolana · Nicaragüense
pa-nombres.txt	253	PA_NOMBRE_PILA	María · José · Luis · Carlos
pa-ocupaciones.txt	40	PA_OCUPACION	Oficinista · Comerciante · Vendedor · Obrero de la construcción
pa-opiniones-politicas.txt	7	PA_OPINION_POLITICA_LISTA	Izquierda · Centro izquierda · Centro · Centro derecha
pa-orientacion-sexual.txt	9	PA_ORIENTACION_SEXUAL_LISTA	Heterosexual · Homosexual · Lesbiana · Gay
pa-partidos.txt	11	PA_PARTIDO_POLITICO_LISTA	Partido Revolucionario Democrático · Realizando Metas · Cambio Democrático · Partido Panameñista
pa-pobreza.txt	4	PA_POBREZA	Pobreza extrema · Pobreza general · No pobre · Vulnerable
pa-programas-sociales.txt	9	PA_PROGRAMA_SOCIAL_LISTA	120 a los 65 · Red de Oportunidades · Ángel Guardián · Bono Alimenticio Nutricional
pa-pueblos.txt	16	PA_PUEBLO_LISTA	Guna · Ngäbe · Buglé · Naso Tjërdi
pa-quintil.txt	5	PA_QUINTIL	1 · 2 · 3 · 4

FILE	LINES	USED BY	FIRST LINES
pa-referencia-credito.txt	10	PA_REFERENCIA_CREDITO	Al día · Morosidad de 30 días · Morosidad de 60 días · Morosidad de 90 días
pa-religiones.txt	14	PA_RELIGION_LISTA	Católica · Evangélica · Adventista del Séptimo Día · Testigo de Jehová
pa-ruc-dv-letras-de-vuelta.txt	5	PA_RUC_DV_LETRAS_DE_VUELTA	v,AV · i,PI · e,E · n,N
pa-ruc-dv-letras.txt	5	PA_RUC_DV_LETRAS	AV,v · PI,i · E,e · N,n
pa-ruc-dv-paso.txt	32,317	PA_RUC_DV_PASO	000a,00b0 · 100a,21b1 · 200a,42b2 · 300a,63b3
pa-ruc-dv-resultado.txt	1,815	PA_RUC_DV_RESULTADO	A8J,81 · 40J,33 · 41J,32 · 4Au,99
pa-ruc-dv-traslado.txt	2,100	PA_RUC_DV_TRASLADO	000,000 · 001,100 · 002,200 · 003,300
pa-seguro-social.txt	6	PA_SEGURO_SOCIAL_LISTA	Asegurado directo · Beneficiario · Jubilado o pensionado por vejez · Pensionado por enfermedad o accidente
pa-sexo-f-m.txt	2	PA_SEXO_F_M	F · M
pa-sexo-h-m.txt	2	PA_SEXO_H_M	H · M
pa-sexo-ingles.txt	2	PA_SEXO_INGLES	Female · Male
pa-sexo-mujer-hombre.txt	2	PA_SEXO_MUJER_HOMBRE	Mujer · Hombre
pa-sexo-palabra.txt	2	PA_SEXO_PALABRA	Femenino · Masculino
pa-sin-informacion.txt	1	PA_SUPRIMIR	Sin información
pa-texto-nombres.txt	1,094	PA_TEXTO_LIBRE	María · MARÍA · Maria · MARIA
pa-vivienda.txt	6	PA_VIVIENDA_LISTA	Propia · Propia hipotecada · Alquilada · Cedida o prestada

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `avenida` `barriada` `urbanizacion` `corregimiento` `correg` `distrito` `dist` `provincia` `prov` `comarca` `lugar_?poblado` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `centro_?educativo` `establecimiento` `institucion` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `policlinica` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `comprobante` `factura` `pago` `forma` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `finca` `edificio` `ph` `proyecto` `cliente` `cte` `cli` `paciente` `pac` `trabajador` `trab` `empleado` `colaborador` `funcionario` `servidor_?publico` `alumno` `estudiante` `afiliado` `asegurado` `cotizante` `jubilado` `pensionado` `beneficiario` `benef` `titular` `madre` `padre` `acudiente` `tutor` `conyuge` `pareja` `medico` `doctor` `profesional` `responsable` `contacto` `emergencia` `fiador` `codeudor` `deudor` `remitente` `destinatario` `receptor` `firmante` `testigo` `representante` `apoderado` `propietario` `arrendatario` `inquilino` `contratante` `victima` `denunciante` `imputado` `socio` `donante` `heredero` `persona` `pers` `conductor` `chofer` `vendedor` `ejecutivo` `agente` `solicitante` `ciudadano` `elector` `votante` `contribuyente` `jefe_?(de_?)?hogar` `hijo` `hija` `familiar` `dependiente` `completos?` `y_?apellidos?` `apellidos?`

E2 `producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `avenida` `barriada` `urbanizacion` `corregimiento` `correg` `distrito` `dist` `provincia` `prov` `comarca` `lugar_?poblado` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `centro_?educativo` `establecimiento` `institucion` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `policlinica` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `comprobante` `factura` `pago` `forma` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `finca` `edificio` `ph` `proyecto` `cliente` `cte` `cli` `paciente` `pac` `trabajador` `trab` `empleado` `colaborador` `funcionario` `servidor_?publico` `alumno` `estudiante` `afiliado` `asegurado` `cotizante` `jubilado` `pensionado` `beneficiario` `benef` `titular` `madre` `padre` `acudiente` `tutor` `conyuge` `pareja` `medico` `doctor` `profesional` `responsable` `contacto` `emergencia` `fiador` `codeudor` `deudor` `remitente` `destinatario` `receptor` `firmante` `testigo` `representante` `apoderado` `propietario` `arrendatario` `inquilino` `contratante` `victima` `denunciante` `imputado` `socio` `donante` `heredero` `persona` `pers` `conductor` `chofer` `vendedor` `ejecutivo` `agente` `solicitante` `ciudadano` `elector` `votante` `contribuyente` `jefe_?(de_?)?hogar` `hijo` `hija` `familiar` `dependiente` `completo` `compl` `full` `y_?apellidos?` `apellidos?`

E3 `producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `avenida` `barriada` `urbanizacion` `corregimiento` `correg` `distrito` `dist` `provincia` `prov` `comarca` `lugar_?poblado` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `centro_?educativo` `establecimiento` `institucion` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `policlinica` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `comprobante` `factura` `pago` `forma` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `finca` `edificio` `ph` `proyecto` `completo`

E4 `producto` `prod` `articulo` `art` `item` `empresa` `emp` `compania` `razon` `comercial` `fantasia` `archivo` `arch` `file` `calle` `via` `avenida` `barriada` `urbanizacion` `corregimiento` `correg` `distrito` `dist` `provincia` `prov` `comarca` `lugar_?poblado` `region` `ciudad` `pais` `banco` `sucursal` `plaza` `plan` `campana` `proyecto` `servicio` `equipo` `tabla` `columna` `campo` `usuario` `user` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `centro_?educativo` `establecimiento` `institucion` `curso` `carrera` `materia` `documento` `doc` `centro` `unidad` `policlinica` `clinica` `hospital` `area` `depto` `departamento` `puesto` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `farmaco` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `local` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `org` `organizacion` `dependencia` `entidad` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `template` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `comprobante` `factura` `pago` `forma` `zona` `ruta` `linea` `giro` `actividad` `rama` `sector` `finca` `edificio` `ph` `proyecto`

E5 `ip` `mac` `web` `url` `correo` `mail` `electronica` `email`

E6 `producto` `prod` `articulo` `sucursal` `interna` `tipo` `registro` `primaria` `foranea` `social` `banco` `pais` `moneda` `catastral` `ubicacion` `zona` `area` `postal`

E7 `fijo` `variable` `monto` `adicional` `servicio` `tarifa` `valor` `cuenta` `extra` `automatico` `recurrente`

E8 `medicos` `patologicos` `personales_?patologicos` `heredofamiliares` `gineco` `obstetricos` `familiares` `clinicos` `academicos` `laborales` `crediticios` `comerciales` `generales`

APPENDIX D

Discovery policy and classifiers

The discovery policy `PA – Ley 81 de 2019 – v4` runs these 137 classifiers, with an assignment threshold of 60%.

Ley 81 de 2019 - datos personales y sensibles

CLASSIFIER	KIND	DATA CLASS
PA_L1_CEDULA – Path	COLUMN NAME	PA_L1_CEDULA
PA_L1_CEDULA – Type	DATA TYPE	PA_L1_CEDULA
PA_L1_CEDULA – Regex	VALUE FORMAT	PA_L1_CEDULA
PA_L1_RUC – Path	COLUMN NAME	PA_L1_RUC
PA_L1_RUC – Type	DATA TYPE	PA_L1_RUC
PA_L1_RUC – Regex	VALUE FORMAT	PA_L1_RUC
PA_L1_RUC_DV – Path	COLUMN NAME	PA_L1_RUC_DV
PA_L1_RUC_DV – Type	DATA TYPE	PA_L1_RUC_DV
PA_L1_PASAPORTE – Path	COLUMN NAME	PA_L1_PASAPORTE
PA_L1_PASAPORTE – Regex	VALUE FORMAT	PA_L1_PASAPORTE
PA_L1_DOCUMENTO_MIGRATORIO – Path	COLUMN NAME	PA_L1_DOCUMENTO_MIGRATORIO
PA_L1_SEGURO_SOCIAL – Path	COLUMN NAME	PA_L1_SEGURO_SOCIAL
PA_L1_IDONEIDAD – Path	COLUMN NAME	PA_L1_IDONEIDAD
PA_L1_NOMBRE – Path	COLUMN NAME	PA_L1_NOMBRE
PA_L1_NOMBRE – List	KNOWN VALUES	PA_L1_NOMBRE
PA_L1_APELLIDO – Path	COLUMN NAME	PA_L1_APELLIDO
PA_L1_APELLIDO – List	KNOWN VALUES	PA_L1_APELLIDO
PA_L1_NOMBRE_COMPLETO – Path	COLUMN NAME	PA_L1_NOMBRE_COMPLETO
PA_L1_NOMBRE_COMPLETO – List	KNOWN VALUES	PA_L1_NOMBRE_COMPLETO
PA_L1_EMAIL – Path	COLUMN NAME	PA_L1_EMAIL
PA_L1_EMAIL – Type	DATA TYPE	PA_L1_EMAIL
PA_L1_EMAIL – Regex	VALUE FORMAT	PA_L1_EMAIL
PA_L1_TELEFONO – Path	COLUMN NAME	PA_L1_TELEFONO
PA_L1_TELEFONO – Regex	VALUE FORMAT	PA_L1_TELEFONO
PA_L1_DIRECCION – Path	COLUMN NAME	PA_L1_DIRECCION
PA_L1_DIRECCION – Type	DATA TYPE	PA_L1_DIRECCION
PA_L1_DIRECCION – Regex	VALUE FORMAT	PA_L1_DIRECCION
PA_L1_DIRECCION_COMPLEMENTO – Path	COLUMN NAME	PA_L1_DIRECCION_COMPLEMENTO
PA_L1_CUENTA_BANCARIA – Path	COLUMN NAME	PA_L1_CUENTA_BANCARIA
PA_L1_TARJETA – Path	COLUMN NAME	PA_L1_TARJETA
PA_L1_TARJETA – Regex	VALUE FORMAT	PA_L1_TARJETA

CLASSIFIER	KIND	DATA CLASS
PA_L1_IP – Path	COLUMN NAME	PA_L1_IP
PA_L1_IP – Regex	VALUE FORMAT	PA_L1_IP
PA_L1_DISPOSITIVO – Path	COLUMN NAME	PA_L1_DISPOSITIVO
PA_L1_DISPOSITIVO – Regex	VALUE FORMAT	PA_L1_DISPOSITIVO
PA_L1_PLACA – Path	COLUMN NAME	PA_L1_PLACA
PA_L1_PLACA – Regex	VALUE FORMAT	PA_L1_PLACA
PA_L1_VIN – Path	COLUMN NAME	PA_L1_VIN
PA_L1_VIN – Regex	VALUE FORMAT	PA_L1_VIN
PA_L1_FINCA – Path	COLUMN NAME	PA_L1_FINCA
PA_L1_NUMERO_CONTRATO – Path	COLUMN NAME	PA_L1_NUMERO_CONTRATO
PA_L1_USUARIO_RRSS – Path	COLUMN NAME	PA_L1_USUARIO_RRSS
PA_L1_CREDENCIAL – Path	COLUMN NAME	PA_L1_CREDENCIAL
PA_L1_CREDENCIAL – Regex	VALUE FORMAT	PA_L1_CREDENCIAL
PA_L1_GEOLOCALIZACION – Path	COLUMN NAME	PA_L1_GEOLOCALIZACION
PA_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	PA_L1_GEOLOCALIZACION
PA_L1_TEXTO_LIBRE – Path	COLUMN NAME	PA_L1_TEXTO_LIBRE
PA_L1_TEXTO_LIBRE – Type	DATA TYPE	PA_L1_TEXTO_LIBRE
PA_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	PA_L1_TEXTO_LIBRE
PA_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	PA_L2_FECHA_NACIMIENTO
PA_L2_FECHA_NACIMIENTO – Type	DATA TYPE	PA_L2_FECHA_NACIMIENTO
PA_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	PA_L2_ANIO_NACIMIENTO
PA_L2_ANIO_NACIMIENTO – Type	DATA TYPE	PA_L2_ANIO_NACIMIENTO
PA_L2_EDAD – Path	COLUMN NAME	PA_L2_EDAD
PA_L2_EDAD – Type	DATA TYPE	PA_L2_EDAD
PA_L2_FECHA_EVENTO – Path	COLUMN NAME	PA_L2_FECHA_EVENTO
PA_L2_FECHA_EVENTO – Type	DATA TYPE	PA_L2_FECHA_EVENTO
PA_L2_SEXO – Path	COLUMN NAME	PA_L2_SEXO
PA_L2_SEXO – List	KNOWN VALUES	PA_L2_SEXO
PA_L2_DISTRITO – Path	COLUMN NAME	PA_L2_DISTRITO
PA_L2_DISTRITO – Values	VALUE FORMAT	PA_L2_DISTRITO
PA_L2_CORREGIMIENTO – Path	COLUMN NAME	PA_L2_CORREGIMIENTO
PA_L2_CORREGIMIENTO – Values	VALUE FORMAT	PA_L2_CORREGIMIENTO
PA_L2_CODIGO_LUGAR – Path	COLUMN NAME	PA_L2_CODIGO_LUGAR
PA_L2_CODIGO_LUGAR – Type	DATA TYPE	PA_L2_CODIGO_LUGAR
PA_L2_CODIGO_LUGAR – Values	VALUE FORMAT	PA_L2_CODIGO_LUGAR
PA_L2_LUGAR_POBLADO – Path	COLUMN NAME	PA_L2_LUGAR_POBLADO
PA_L2_BARRIADA – Path	COLUMN NAME	PA_L2_BARRIADA

CLASSIFIER	KIND	DATA CLASS
PA_L2_CODIGO_POSTAL – Path	COLUMN NAME	PA_L2_CODIGO_POSTAL
PA_L2_CODIGO_POSTAL – Regex	VALUE FORMAT	PA_L2_CODIGO_POSTAL
PA_L2_NACIONALIDAD – Path	COLUMN NAME	PA_L2_NACIONALIDAD
PA_L2_NACIONALIDAD – Values	VALUE FORMAT	PA_L2_NACIONALIDAD
PA_L2_ESTADO_CIVIL – Path	COLUMN NAME	PA_L2_ESTADO_CIVIL
PA_L2_ESTADO_CIVIL – Values	VALUE FORMAT	PA_L2_ESTADO_CIVIL
PA_L2_OCUPACION – Path	COLUMN NAME	PA_L2_OCUPACION
PA_L2_EMPLEADOR – Path	COLUMN NAME	PA_L2_EMPLEADOR
PA_L2_ESCOLARIDAD – Path	COLUMN NAME	PA_L2_ESCOLARIDAD
PA_L2_ESCOLARIDAD – Values	VALUE FORMAT	PA_L2_ESCOLARIDAD
PA_L2_ESCUELA – Path	COLUMN NAME	PA_L2_ESCUELA
PA_L2_DEPENDIENTES – Path	COLUMN NAME	PA_L2_DEPENDIENTES
PA_L2_DEPENDIENTES – Type	DATA TYPE	PA_L2_DEPENDIENTES
PA_L3_ETNIA – Path	COLUMN NAME	PA_L3_ETNIA
PA_L3_ETNIA – Values	VALUE FORMAT	PA_L3_ETNIA
PA_L3_LENGUA_INDIGENA – Path	COLUMN NAME	PA_L3_LENGUA_INDIGENA
PA_L3_LENGUA_INDIGENA – Values	VALUE FORMAT	PA_L3_LENGUA_INDIGENA
PA_L3_SALUD_DIAGNOSTICO – Path	COLUMN NAME	PA_L3_SALUD_DIAGNOSTICO
PA_L3_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	PA_L3_SALUD_DIAGNOSTICO
PA_L3_SALUD_MEDICAMENTO – Path	COLUMN NAME	PA_L3_SALUD_MEDICAMENTO
PA_L3_SALUD_MEDICAMENTO – Values	VALUE FORMAT	PA_L3_SALUD_MEDICAMENTO
PA_L3_SALUD_IDENTIFICADOR – Path	COLUMN NAME	PA_L3_SALUD_IDENTIFICADOR
PA_L3_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	PA_L3_SALUD_TEXTO_CLINICO
PA_L3_SALUD_TEXTO_CLINICO – Type	DATA TYPE	PA_L3_SALUD_TEXTO_CLINICO
PA_L3_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	PA_L3_SALUD_RESULTADO_EXAMEN
PA_L3_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	PA_L3_SALUD_GRUPO_SANGUINEO
PA_L3_SALUD_GRUPO_SANGUINEO – Values	VALUE FORMAT	PA_L3_SALUD_GRUPO_SANGUINEO
PA_L3_SALUD_DISCAPACIDAD – Path	COLUMN NAME	PA_L3_SALUD_DISCAPACIDAD
PA_L3_SALUD_DISCAPACIDAD – Values	VALUE FORMAT	PA_L3_SALUD_DISCAPACIDAD
PA_L3_SALUD_SEXUAL_REPRODUCTIVA – Path	COLUMN NAME	PA_L3_SALUD_SEXUAL_REPRODUCTIVA
PA_L3_SALUD_MENTAL_ADICCIONES – Path	COLUMN NAME	PA_L3_SALUD_MENTAL_ADICCIONES
PA_L3_BIOMETRICO – Path	COLUMN NAME	PA_L3_BIOMETRICO
PA_L3_BIOMETRICO – Type	DATA TYPE	PA_L3_BIOMETRICO
PA_L3_INFORMACION_GENETICA – Path	COLUMN NAME	PA_L3_INFORMACION_GENETICA
PA_L3_INFORMACION_GENETICA – Regex	VALUE FORMAT	PA_L3_INFORMACION_GENETICA
PA_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	PA_L3_ORIENTACION_SEXUAL
PA_L3_ORIENTACION_SEXUAL – Values	VALUE FORMAT	PA_L3_ORIENTACION_SEXUAL

CLASSIFIER	KIND	DATA CLASS
PA_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	PA_L3_IDENTIDAD_GENERO
PA_L3_IDENTIDAD_GENERO – Values	VALUE FORMAT	PA_L3_IDENTIDAD_GENERO
PA_L3_VIDA_SEXUAL – Path	COLUMN NAME	PA_L3_VIDA_SEXUAL
PA_L3_RELIGION – Path	COLUMN NAME	PA_L3_RELIGION
PA_L3_RELIGION – Values	VALUE FORMAT	PA_L3_RELIGION
PA_L3_CREENCIA_FILOSOFICA_MORAL – Path	COLUMN NAME	PA_L3_CREENCIA_FILOSOFICA_MORAL
PA_L3_OPINION_POLITICA – Path	COLUMN NAME	PA_L3_OPINION_POLITICA
PA_L3_OPINION_POLITICA – Values	VALUE FORMAT	PA_L3_OPINION_POLITICA
PA_L3_AFILIACION_POLITICA – Path	COLUMN NAME	PA_L3_AFILIACION_POLITICA
PA_L3_AFILIACION_POLITICA – Values	VALUE FORMAT	PA_L3_AFILIACION_POLITICA
PA_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	PA_L3_AFILIACION_SINDICAL
PA_L3_AFILIACION_SINDICAL – Values	VALUE FORMAT	PA_L3_AFILIACION_SINDICAL
PA_FIN_REFERENCIA_CREDITO – Path	COLUMN NAME	PA_FIN_REFERENCIA_CREDITO
PA_FIN_MONTO_DEUDA – Path	COLUMN NAME	PA_FIN_MONTO_DEUDA
PA_FIN_MONTO_DEUDA – Type	DATA TYPE	PA_FIN_MONTO_DEUDA
PA_FIN_INGRESO_MENSUAL – Path	COLUMN NAME	PA_FIN_INGRESO_MENSUAL
PA_FIN_INGRESO_MENSUAL – Type	DATA TYPE	PA_FIN_INGRESO_MENSUAL
PA_FIN_PATRIMONIO – Path	COLUMN NAME	PA_FIN_PATRIMONIO
PA_FIN_PATRIMONIO – Type	DATA TYPE	PA_FIN_PATRIMONIO
PA_FIN_PENSION – Path	COLUMN NAME	PA_FIN_PENSION
PA_FIN_PENSION – Type	DATA TYPE	PA_FIN_PENSION
PA_FIN_SEGURO_SOCIAL – Path	COLUMN NAME	PA_FIN_SEGURO_SOCIAL
PA_FIN_SEGURO_SOCIAL – Values	VALUE FORMAT	PA_FIN_SEGURO_SOCIAL
PA_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	PA_FIN_PROGRAMA_SOCIAL
PA_FIN_PROGRAMA_SOCIAL – Values	VALUE FORMAT	PA_FIN_PROGRAMA_SOCIAL
PA_FIN_NIVEL_SOCIOECONOMICO – Path	COLUMN NAME	PA_FIN_NIVEL_SOCIOECONOMICO
PA_FIN_NIVEL_SOCIOECONOMICO – Values	VALUE FORMAT	PA_FIN_NIVEL_SOCIOECONOMICO
PA_FIN_VIVIENDA – Path	COLUMN NAME	PA_FIN_VIVIENDA
PA_FIN_VIVIENDA – Values	VALUE FORMAT	PA_FIN_VIVIENDA
PA_PENAL_ANTECEDENTES – Path	COLUMN NAME	PA_PENAL_ANTECEDENTES
PA_PENAL_CAUSA – Path	COLUMN NAME	PA_PENAL_CAUSA
PA_PENAL_CAUSA – Regex	VALUE FORMAT	PA_PENAL_CAUSA