DELPHIX MASKING · PROFILE SET

Colombia — Ley 1581 de 2012

Discovery and masking of Colombian personal data: cédula and NIT with a valid check digit, quasi-identifiers, the sensitive data of article 5, victims of the armed conflict, financial data under Law 1266 of 2008 and criminal records.

82	145	140
DOMAINS	CLASSIFIERS	ALGORITHMS

Profile set `CO – Ley 1581 de 2012 – v2`

Version 2 of October 11, 2026 · Assignment threshold 60%

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	**About this profile set**	
2	**Ley 1581 de 2012 in brief**	
3	**Anonymization, pseudonymization and non-production copies**	
4	**How sensitive data is discovered**	
5	**How data is masked**	
6	**Essential and extended packs**	
7	**Domains at a glance**	

PART 8 · DIRECT IDENTIFIERS

8.1	**Cédula and identity document**	CO_L1_CEDULA
8.2	**NIT**	CO_L1_NIT
8.3	**Foreigner documents**	CO_L1_DOCUMENTO_EXTRANJERO
8.4	**Passport**	CO_L1_PASAPORTE
8.5	**Civil registry**	CO_L1_REGISTRO_CIVIL
8.6	**Professional card**	CO_L1_TARJETA_PROFESIONAL
8.7	**Given name**	CO_L1_NOMBRE
8.8	**Surname**	CO_L1_APELLIDO
8.9	**Full name**	CO_L1_NOMBRE_COMPLETO
8.10	**E-mail**	CO_L1_EMAIL
8.11	**Phone**	CO_L1_TELEFONO
8.12	**Address**	CO_L1_DIRECCION
8.13	**Address complement**	CO_L1_DIRECCION_COMPLEMENTO
8.14	**Bank account**	CO_L1_CUENTA_BANCARIA
8.15	**Payment card**	CO_L1_TARJETA
8.16	**Bre-B key**	CO_L1_LLAVE_BREB
8.17	**IP address**	CO_L1_IP
8.18	**Device identifier**	CO_L1_DISPOSITIVO
8.19	**Licence plate**	CO_L1_PLACA
8.20	**Vehicle**	CO_L1_VEHICULO
8.21	**Real estate**	CO_L1_INMUEBLE
8.22	**Contract and enrolment numbers**	CO_L1_CONTRATO
8.23	**User and social media**	CO_L1_USUARIO
8.24	**Credentials**	CO_L1_CREDENCIAL

8.25	Geolocation	CO_L1_GEOLOCALIZACION
8.26	Free text	CO_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	CO_L2_FECHA_NACIMIENTO
9.2	Birth year	CO_L2_ANIO_NACIMIENTO
9.3	Age	CO_L2_EDAD
9.4	Personal event dates	CO_L2_FECHA_EVENTO
9.5	Sex	CO_L2_SEXO
9.6	Municipality	CO_L2_MUNICIPIO
9.7	Municipality code (DIVIPOLA)	CO_L2_CODIGO_MUNICIPIO
9.8	Postal code	CO_L2_CODIGO_POSTAL
9.9	Neighbourhood, locality and commune	CO_L2_BARRIO
9.10	Vereda and corregimiento	CO_L2_VEREDA
9.11	Nationality	CO_L2_NACIONALIDAD
9.12	Marital status	CO_L2_ESTADO_CIVIL
9.13	Occupation	CO_L2_OCUPACION
9.14	Employer	CO_L2_EMPLEADOR
9.15	Education	CO_L2_ESCOLARIDAD
9.16	Educational institution	CO_L2_INSTITUCION_EDUCATIVA
9.17	Dependants and children	CO_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA

10.1	Ethnic self-recognition	CO_L3_GRUPO_ETNICO
10.2	Indigenous people and ethnic community	CO_L3_PUEBLO_INDIGENA
10.3	Native language	CO_L3_LENGUA_NATIVA
10.4	Religion	CO_L3_RELIGION
10.5	Philosophical convictions	CO_L3_CONVICCION_FILOSOFICA
10.6	Political orientation	CO_L3_ORIENTACION_POLITICA
10.7	Party membership	CO_L3_AFILIACION_PARTIDO
10.8	Trade union membership	CO_L3_SINDICATO
10.9	Social and human rights organizations	CO_L3_ORGANIZACION_SOCIAL
10.10	Biometric data	CO_L3_BIOMETRICO
10.11	Genetic data	CO_L3_GENETICO
10.12	Sexual orientation	CO_L3_ORIENTACION_SEXUAL
10.13	Sexual life	CO_L3_VIDA_SEXUAL
10.14	Gender identity	CO_L3_IDENTIDAD_GENERO
10.15	Victim of the armed conflict	CO_L3_VICTIMA_CONFLICTO

10.16	Reincorporation	CO_L3_REINCORPORACION

PART 11 · HEALTH DATA

11.1	Health identifiers	CO_SALUD_IDENTIFICADOR
11.2	Health system affiliation	CO_SALUD_AFILIACION
11.3	Diagnosis and ICD-10	CO_SALUD_DIAGNOSTICO
11.4	Procedures (CUPS)	CO_SALUD_PROCEDIMIENTO
11.5	Medicines	CO_SALUD_MEDICAMENTO
11.6	Clinical text	CO_SALUD_TEXTO_CLINICO
11.7	Test results	CO_SALUD_RESULTADO_EXAMEN
11.8	Blood group and Rh	CO_SALUD_GRUPO_SANGUINEO
11.9	Disability	CO_SALUD_DISCAPACIDAD
11.10	Occupational health	CO_SALUD_OCUPACIONAL
11.11	Sexual and reproductive health	CO_SALUD_REPRODUCTIVA
11.12	Mental health	CO_SALUD_MENTAL

PART 12 · FINANCIAL AND SOCIOECONOMIC DATA

12.1	Credit bureaus	CO_FIN_CREDITO
12.2	Debt	CO_FIN_DEUDA
12.3	Income and salary	CO_FIN_INGRESOS
12.4	Assets	CO_FIN_PATRIMONIO
12.5	Pension and subsidies	CO_FIN_PENSION
12.6	Socioeconomic stratum	CO_FIN_ESTRATO
12.7	Sisbén	CO_FIN_SISBEN
12.8	Social programmes	CO_FIN_PROGRAMA_SOCIAL
12.9	Housing tenure	CO_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS AND PROCEEDINGS

13.1	Records	CO_PENAL_ANTECEDENTES
13.2	Case file number	CO_PENAL_RADICADO
14	The NIT check digit	
15	Where people live: municipalities, veredas and postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	

1

About this profile set

This profile set finds the personal data in a Colombian database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and cédulas alone is not enough: a birth date, a sex and a small municipality already point at one person. The set works in the layers where the risk is:

- **Direct identifiers** — cédula, identity card and NUIP, NIT, foreigner documents (cédula de extranjería, PPT, PEP), passport, civil registry, professional card, names, contact, address, accounts, cards and Bre-B key, devices, vehicles, real estate, free text.
- **Quasi-identifiers** — birth date, age, sex, municipality and DIVIPOLA code, postal code, neighbourhood, vereda, nationality, marital status, occupation, employer, education.
- **Sensitive data** — those of article 5: racial or ethnic origin, political orientation, religious or philosophical convictions, membership of trade unions, of social and human rights organizations and of parties, sexual life and biometric data — and, since the list is illustrative, genetic data, gender identity, being a victim of the armed conflict and being in the reincorporation process.
- **Health data** — sensitive under article 5 too, in a group of its own: medical record, health system affiliation, ICD-10, CUPS procedures, medicines, tests, blood group, disability, occupational, reproductive and mental health.
- **Financial data** — those of Law 1266 of 2008: credit bureau reports, debt, income, assets, pension; and those that reveal the socioeconomic situation: stratum, Sisbén IV, social programmes, housing tenure.
- **Criminal records and proceedings** — judicial, disciplinary and fiscal records, corrective measures, legal situation and case file numbers.

On a Masking Engine, the set is a profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those lean on — and the lookup files they read. The appendices list each of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it on its own; an ambiguous one — `NOMBRE`, `DOCUMENTO`, `CARGO`, `PROCESO` — needs the values to agree. A column whose name means nothing (`CAMPO1`, `OBS`) is still found when the values have a recognizable format or vocabulary: a cédula with dots, a NIT, an address in the street grid notation, a plate, a municipality.

Column names are recognized in Spanish, in the abbreviations of Colombian systems (`NRO_DOCUMENTO`, `CC_CLIENTE`, `FEC_NAC`, `COD_MPIO`, `DX_PRINCIPAL`, `ESTRATO`, `GRUPO_SISBEN`) and in English.

> Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often store a photo of the cédula — with the fingerprint and blood group — and a biometric validation selfie. Report those columns as residual risk.

2

Ley 1581 de 2012 in brief

Statutory Law 1581 of 17 October 2012 — Diario Oficial 48.587 — sets the general rules for personal data protection and develops the habeas data right of article 15 of the Constitution. It went through prior constitutional review (judgment C-748 of 2011) and is regulated by Decree 1377 of 2013, compiled in the Single Regulatory Decree 1074 of 2015. The authority is the **Superintendencia de Industria y Comercio (SIC)**, through its Delegation for Personal Data Protection.

What matters for a copy of production data:

- **Personal data** is any information linked or that can be associated with one or more determined or determinable natural persons (art. 3, c). Data that can no longer be associated with anyone ceases to be personal data.
- **Sensitive data** is data that affects the privacy of the data subject or whose misuse can lead to discrimination, *such as* data revealing racial or ethnic origin, political orientation, religious or philosophical convictions, membership of trade unions, social or human rights organizations or organizations promoting the interests of any political party or guaranteeing the rights of opposition parties, and data concerning health, sexual life and biometric data (art. 5). Processing it is **prohibited** save for the exceptions of article 6; for historical, statistical or scientific purposes the **suppression of the data subjects' identity** is required (art. 6, e).
- **Children and adolescents.** Processing their data is proscribed except for data of a public nature (art. 7); the Constitutional Court allowed it when it serves their best interest and respects their rights (C-748 of 2011), and Decree 1377 sets the requirements.
- **Principles.** Purpose, freedom, restricted access and circulation, **security** and **confidentiality** (art. 4): whoever takes part in the processing must prevent unauthorized or fraudulent consultation, use or access, and keep it confidential even after their work ends. A test database with real data, open to developers and vendors, hardly meets either.
- **Security incidents.** The controller informs the SIC of breaches of security codes (art. 17, n); the SIC sets a term of fifteen business days from detection, through the National Database Registry.
- **Sanctions.** Personal and institutional fines of up to 2,000 monthly minimum wages — in 2026, about 3.5 billion pesos —, suspension of processing for up to six months, temporary closure and **immediate and definitive closure** of any operation involving sensitive data (art. 23). Obtaining, compiling, selling or disclosing personal data without authorization is also a crime: article 269F of the Criminal Code (Law 1273 of 2009) punishes it with 48 to 96 months in prison.

Financial data. Databases governed by Law 1266 of 2008 — financial, credit and commercial habeas data — are outside Law 1581, but its principles apply to them (art. 2, e and paragraph). Law 2157 of 2021 limits how long negative data stays to twice the time in arrears, four years at most.

Archived reform. In August 2025 statutory bills 214 and 274 of 2025, merged, were filed in the House of Representatives to update Law 1581 (definitions of genetic and biometric data, profiling, automated decisions, higher fines). The bill passed its first debate in October 2025, and in September 2026 it is listed as **archived** on the House website: a statutory law must be passed within a single legislative term (art. 153 of the Constitution). This set follows the law in force.

3

Anonymization, pseudonymization and non-production copies

Law 1581 has no anonymization clause: the consequence follows from the definition of personal data. If data can no longer be associated with a determined or determinable person, it is not personal data. The **Guide to the Anonymization of Structured Data** of the Archivo General de la Nación (2020), written with the ICT Ministry, the SIC, the Civil Service Department, the National Planning Department and DANE, draws the line: **pseudonymization** replaces one attribute with another, does not produce completely anonymous records and *cannot be said to be an anonymization method*, although it reduces the risk of identification.

The algorithms of this set are deterministic for the key of the Masking Engine: the same cédula masks the same way in every table, which keeps joins working. So for whoever holds the key **and** production, the

masked copy can be linked back — it is pseudonymized and still personal data. For whoever holds only the copy, direct identifiers were replaced and quasi-identifiers generalized.

- Keep the engine key out of reach of the users of the masked copy.
- Do not hand the copy to people who also access production without need.
- Review quasi-identifiers the set does not know. The AGN guide and the DANE guide (2024) recommend measuring the re-identification risk before publishing or sharing.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. The profiler tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

Where an algorithm that comes with the Masking Engine already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the set names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name; they are on every engine and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	25	37	5
Extended	82	145	140	66

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- Cédula and identity document — `CO_L1_CEDULA`
- NIT — `CO_L1_NIT`
- Foreigner documents — `CO_L1_DOCUMENTO_EXTRANJERO`
- Passport — `CO_L1_PASAPORTE`
- Given name — `CO_L1_NOMBRE`
- Surname — `CO_L1_APELLIDO`
- Full name — `CO_L1_NOMBRE_COMPLETO`
- E-mail — `CO_L1_EMAIL`
- Phone — `CO_L1_TELEFONO`
- Address — `CO_L1_DIRECCION`
- Address complement — `CO_L1_DIRECCION_COMPLEMENTO`
- Birth date — `CO_L2_FECHA_NACIMIENTO`

> With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

7

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Cédula and identity document ESSENTIAL `CO_L1_CEDULA`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CO_DOCUMENTO`
NIT ESSENTIAL `CO_L1_NIT`	COLUMN NAME · VALUE FORMAT	`CO_NIT`
Foreigner documents ESSENTIAL `CO_L1_DOCUMENTO_EXTRANJERO`	COLUMN NAME	`CO_CM_ALFANUM`
Passport ESSENTIAL `CO_L1_PASAPORTE`	COLUMN NAME · VALUE FORMAT	`CO_CM_ALFANUM`
Civil registry `CO_L1_REGISTRO_CIVIL`	COLUMN NAME	`CO_CM_ALFANUM`
Professional card `CO_L1_TARJETA_PROFESIONAL`	COLUMN NAME	`CO_CM_ALFANUM`
Given name ESSENTIAL `CO_L1_NOMBRE`	COLUMN NAME · KNOWN VALUES	`CO_NOMBRES`
Surname ESSENTIAL `CO_L1_APELLIDO`	COLUMN NAME · KNOWN VALUES	`CO_APELLIDOS`
Full name ESSENTIAL `CO_L1_NOMBRE_COMPLETO`	COLUMN NAME · KNOWN VALUES	`CO_NOMBRE_COMPLETO`
E-mail ESSENTIAL `CO_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CO_EMAIL`
Phone ESSENTIAL `CO_L1_TELEFONO`	COLUMN NAME · VALUE FORMAT	`CO_TELEFONO`
Address ESSENTIAL `CO_L1_DIRECCION`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CO_DIRECCION`
Address complement ESSENTIAL `CO_L1_DIRECCION_COMPLEMENTO`	COLUMN NAME	`CO_CM_ALFANUM`
Bank account `CO_L1_CUENTA_BANCARIA`	COLUMN NAME	`CO_CM_DIGITOS`
Payment card `CO_L1_TARJETA`	COLUMN NAME · VALUE FORMAT	`CO_TARJETA`
Bre-B key `CO_L1_LLAVE_BREB`	COLUMN NAME · VALUE FORMAT	`CO_LLAVE_BREB`
IP address `CO_L1_IP`	COLUMN NAME · VALUE FORMAT	`CO_IP`
Device identifier `CO_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`CO_CM_HEX`
Licence plate `CO_L1_PLACA`	COLUMN NAME · VALUE FORMAT	`CO_PLACA`

DOMAIN	FOUND BY	ALGORITHM
Vehicle `CO_L1_VEHICULO`	COLUMN NAME · VALUE FORMAT	`CO_CM_ALFANUM`
Real estate `CO_L1_INMUEBLE`	COLUMN NAME · VALUE FORMAT	`CO_INMUEBLE`
Contract and enrolment numbers `CO_L1_CONTRATO`	COLUMN NAME	`CO_CM_ALFANUM`
User and social media `CO_L1_USUARIO`	COLUMN NAME	`CO_CM_ALFANUM`
Credentials `CO_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`CO_REDACTAR`
Geolocation `CO_L1_GEOLOCALIZACION`	COLUMN NAME · VALUE FORMAT	`CO_COORDENADA`
Free text `CO_L1_TEXTO_LIBRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`CO_TEXTO_LIBRE`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `CO_L2_FECHA_NACIMIENTO`	COLUMN NAME · DATA TYPE	`CO_FECHA_NACIMIENTO`
Birth year `CO_L2_ANIO_NACIMIENTO`	COLUMN NAME · DATA TYPE	`CO_ANIO`
Age `CO_L2_EDAD`	COLUMN NAME · DATA TYPE	`CO_EDAD`
Personal event dates `CO_L2_FECHA_EVENTO`	COLUMN NAME · DATA TYPE	`CO_FECHA_EVENTO`
Sex `CO_L2_SEXO`	COLUMN NAME · KNOWN VALUES	`CO_SEXO`
Municipality `CO_L2_MUNICIPIO`	COLUMN NAME · VALUE FORMAT	`CO_MUNICIPIO`
Municipality code (DIVIPOLA) `CO_L2_CODIGO_MUNICIPIO`	COLUMN NAME · VALUE FORMAT	`CO_CODIGO_MUNICIPIO`
Postal code `CO_L2_CODIGO_POSTAL`	COLUMN NAME · DATA TYPE	`CO_CODIGO_POSTAL`
Neighbourhood, locality and commune `CO_L2_BARRIO`	COLUMN NAME	`CO_BARRIO`
Vereda and corregimiento `CO_L2_VEREDA`	COLUMN NAME	`CO_ZONA_RURAL`
Nationality `CO_L2_NACIONALIDAD`	COLUMN NAME · VALUE FORMAT	`CO_NACIONALIDAD`
Marital status `CO_L2_ESTADO_CIVIL`	COLUMN NAME · VALUE FORMAT	`CO_ESTADO_CIVIL`
Occupation `CO_L2_OCUPACION`	COLUMN NAME	`CO_OCUPACION_O_CIUO`
Employer `CO_L2_EMPLEADOR`	COLUMN NAME	`CO_EMPLEADOR`
Education `CO_L2_ESCOLARIDAD`	COLUMN NAME · VALUE FORMAT	`CO_ESCOLARIDAD`

DOMAIN	FOUND BY	ALGORITHM
Educational institution `CO_L2_INSTITUCION_EDUCATIVA`	COLUMN NAME	`CO_INSTITUCION_EDUCATIVA`
Dependants and children `CO_L2_PERSONAS_A_CARGO`	COLUMN NAME DATA TYPE	`CO_CONTEO_LIMITADO`
SENSITIVE DATA		
Ethnic self-recognition `CO_L3_GRUPO_ETNICO`	COLUMN NAME VALUE FORMAT	`CO_GRUPO_ETNICO`
Indigenous people and ethnic community `CO_L3_PUEBLO_INDIGENA`	COLUMN NAME VALUE FORMAT	`CO_PUEBLO_INDIGENA`
Native language `CO_L3_LENGUA_NATIVA`	COLUMN NAME VALUE FORMAT	`CO_LENGUA`
Religion `CO_L3_RELIGION`	COLUMN NAME VALUE FORMAT	`CO_RELIGION`
Philosophical convictions `CO_L3_CONVICCION_FILOSOFICA`	COLUMN NAME	`CO_CATEGORIA_SUPRIMIDA`
Political orientation `CO_L3_ORIENTACION_POLITICA`	COLUMN NAME VALUE FORMAT	`CO_ORIENTACION_POLITICA`
Party membership `CO_L3_AFILIACION_PARTIDO`	COLUMN NAME VALUE FORMAT	`CO_PARTIDO`
Trade union membership `CO_L3_SINDICATO`	COLUMN NAME VALUE FORMAT	`CO_CATEGORIA_SUPRIMIDA`
Social and human rights organizations `CO_L3_ORGANIZACION_SOCIAL`	COLUMN NAME	`CO_CATEGORIA_SUPRIMIDA`
Biometric data `CO_L3_BIOMETRICO`	COLUMN NAME DATA TYPE	`CO_REDACTAR`
Genetic data `CO_L3_GENETICO`	COLUMN NAME VALUE FORMAT	`CO_REDACTAR`
Sexual orientation `CO_L3_ORIENTACION_SEXUAL`	COLUMN NAME VALUE FORMAT	`CO_ORIENTACION_SEXUAL`
Sexual life `CO_L3_VIDA_SEXUAL`	COLUMN NAME	`CO_CATEGORIA_SUPRIMIDA`
Gender identity `CO_L3_IDENTIDAD_GENERO`	COLUMN NAME VALUE FORMAT	`CO_IDENTIDAD_GENERO`
Victim of the armed conflict `CO_L3_VICTIMA_CONFLICTO`	COLUMN NAME VALUE FORMAT	`CO_VICTIMA`
Reincorporation `CO_L3_REINCORPORACION`	COLUMN NAME	`CO_CATEGORIA_SUPRIMIDA`
HEALTH DATA		
Health identifiers `CO_SALUD_IDENTIFICADOR`	COLUMN NAME	`CO_CM_ALFANUM`
Health system affiliation `CO_SALUD_AFILIACION`	COLUMN NAME VALUE FORMAT	`CO_AFILIACION_SALUD`
Diagnosis and ICD-10 `CO_SALUD_DIAGNOSTICO`	COLUMN NAME VALUE FORMAT	`CO_DIAGNOSTICO`

DOMAIN	FOUND BY	ALGORITHM
Procedures (CUPS) `CO_SALUD_PROCEDIMIENTO`	COLUMN NAME	`CO_PROCEDIMIENTO`
Medicines `CO_SALUD_MEDICAMENTO`	COLUMN NAME VALUE FORMAT	`CO_MEDICAMENTO`
Clinical text `CO_SALUD_TEXTO_CLINICO`	COLUMN NAME DATA TYPE	`CO_TEXTO_LIBRE`
Test results `CO_SALUD_RESULTADO_EXAMEN`	COLUMN NAME	`CO_CM_ALFANUM`
Blood group and Rh `CO_SALUD_GRUPO_SANGUINEO`	COLUMN NAME VALUE FORMAT	`dlpx-core:BloodType SL`
Disability `CO_SALUD_DISCAPACIDAD`	COLUMN NAME VALUE FORMAT	`CO_DISCAPACIDAD`
Occupational health `CO_SALUD_OCUPACIONAL`	COLUMN NAME VALUE FORMAT	`CO_SALUD_LABORAL`
Sexual and reproductive health `CO_SALUD_REPRODUCTIVA`	COLUMN NAME	`CO_CATEGORIA_SUPRIMIDA`
Mental health `CO_SALUD_MENTAL`	COLUMN NAME	`CO_CATEGORIA_SUPRIMIDA`
FINANCIAL AND SOCIOECONOMIC DATA		
Credit bureaus `CO_FIN_CREDITO`	COLUMN NAME	`CO_CREDITO`
Debt `CO_FIN_DEUDA`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Income and salary `CO_FIN_INGRESOS`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Assets `CO_FIN_PATRIMONIO`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Pension and subsidies `CO_FIN_PENSION`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Socioeconomic stratum `CO_FIN_ESTRATO`	COLUMN NAME VALUE FORMAT	`CO_ESTRATO`
Sisbén `CO_FIN_SISBEN`	COLUMN NAME VALUE FORMAT	`CO_SISBEN`
Social programmes `CO_FIN_PROGRAMA_SOCIAL`	COLUMN NAME VALUE FORMAT	`CO_PROGRAMA_SOCIAL`
Housing tenure `CO_FIN_VIVIENDA`	COLUMN NAME VALUE FORMAT	`CO_TENENCIA_VIVIENDA`
CRIMINAL RECORDS AND PROCEEDINGS		
Records `CO_PENAL_ANTECEDENTES`	COLUMN NAME	`CO_ANTECEDENTES`
Case file number `CO_PENAL_RADICADO`	COLUMN NAME VALUE FORMAT	`CO_RADICADO`

PART 8

Direct identifiers

Data that identifies a person on its own. The cédula is the key of almost every Colombian record, and the same number follows a person through life: the NUIP of the civil registry is that of the identity card and then of the cédula, the driving licence and the military service card, and with a check digit it is their NIT. It is masked the same way everywhere, and the NIT comes out with a valid check digit, because applications validate it.

8.1 Cédula and identity document

CO_L1_CEDULA

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The number of the cédula de ciudadanía issued by the National Civil Registry — 3 to 10 digits, written with thousands dots, `79.456.123`, `1.023.456.789` —, and those that share its number: the identity card and NUIP of minors, the driving licence and the military service card.

`NUMERO_DOCUMENTO` columns often mix cédulas, identity cards, NITs with their digit and passports: each value is masked by its shape.

HOW IT IS FOUND

COLUMN NAME CO_L1_CEDULA — Path

90%

`c[eé]dula(_?(de_?)?ciudadan[ií]a)?` `cc` `c_c` `n(o|ro|um|umero|u)_?(cc|c[eé]dula|documento|doc|identificaci[oó]n|id(ent)?)` `documento_?(de_?)?identidad` `doc_?identidad` `identificaci[oó]n(_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|funcionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|propietario|arrendatario|conductor|acudiente|responsable|representante|persona|ciudadano|votante|contribuyente|proveedor|tercero|cotizante))?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|funcionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|propietario|arrendatario|conductor|acudiente|responsable|representante|persona|ciudadano|votante|contribuyente|proveedor|tercero|cotizante)_?(cc|c[eé]dula|documento|doc|identificaci[oó]n)` `tarjeta_?(de_?)?identidad` `nuip` `numero_?unico_?identificacion_?personal` `licencia_?(de_?)?conducci[oó]n(_?(n(o|ro|um|umero)))?` `pase_?(de_?)?conducci[oó]n` `libreta_?militar(_?(n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?libreta`

60%

`documento` `doc_?id` `id_?documento` `nit_?cc` `cc_?nit`

DATA TYPE CO_L1_CEDULA — Type

Accepts text (length 3 or more) or number (length 3 or more); any other type rules the domain out.

VALUE FORMAT CO_L1_CEDULA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{1,3}(\.\d{3}){1,3})`	80%	
`0*(?:1\d{9})`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, keeping the length and the dots. The mapping is one-to-one: a cédula used as a key does not collide, and the same number masks the same way on the identity card, the licence and the military card. A value with a check digit is masked as a NIT; one with letters, character by character.

`CO_DOCUMENTO` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

> `CO_NIT_6` STRING ALGORITHM CHAIN
>
> Applies `CO_NIT_6_AUX` → `CO_NIT_6_AJUSTE`, in this order.
>
> > `CO_NIT_6_AUX` CHECK DIGIT
> >
> > Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46` from the right.
> >
> > > `CO_CM_DIGITOS_ANCHO_FIJO` CHARACTER MAPPING
> > >
> > > Maps each character to another of its group (1 groups), keeping length and format.
>
> > `CO_NIT_6_AJUSTE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_6_DV`.
> >
> > > `CO_NIT_6_DV` CHECK DIGIT
> > >
> > > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23` from the right.
> > >
> > > > `CO_IDENTIDAD` REGEX DECOMPOSE
> > > >
> > > > Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `CO_NIT_7` STRING ALGORITHM CHAIN
>
> Applies `CO_NIT_7_AUX` → `CO_NIT_7_AJUSTE`, in this order.
>
> > `CO_NIT_7_AUX` CHECK DIGIT
> >
> > Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58` from the right.
>
> > `CO_NIT_7_AJUSTE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_7_DV`.
> >
> > > `CO_NIT_7_DV` CHECK DIGIT
> > >
> > > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29` from the right.

> `CO_NIT_8` STRING ALGORITHM CHAIN
>
> Applies `CO_NIT_8_AUX` → `CO_NIT_8_AJUSTE`, in this order.
>
> > `CO_NIT_8_AUX` CHECK DIGIT
> >
> > Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74` from the right.
>
> > `CO_NIT_8_AJUSTE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_8_DV`.
> >
> > > `CO_NIT_8_DV` CHECK DIGIT
> > >
> > > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37` from the right.

> `CO_NIT_9` STRING ALGORITHM CHAIN
>
> Applies `CO_NIT_9_AUX` → `CO_NIT_9_AJUSTE`, in this order.
>
> > `CO_NIT_9_AUX` CHECK DIGIT
> >
> > Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74 82` from the right.
>
> > `CO_NIT_9_AJUSTE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_9_DV`.
> >
> > > `CO_NIT_9_DV` CHECK DIGIT
> > >
> > > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41` from the right.

`CO_NIT_10` STRING ALGORITHM CHAIN

Applies `CO_NIT_10_AUX` → `CO_NIT_10_AJUSTE`, in this order.

> `CO_NIT_10_AUX` CHECK DIGIT
>
> Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74 82 86` from the right.
>
> `CO_NIT_10_AJUSTE` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_10_DV`.
>
> > `CO_NIT_10_DV` CHECK DIGIT
> >
> > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41 43` from the right.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
79.456.123	→	**69.583.619**
1023456789	→	**2556091343**
800197268-4	→	**265590357-6**

8.2 NIT

`CO_L1_NIT`

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The tax identification number of the DIAN's RUT with its check digit, `800.197.268-4`. A natural person's is their cédula plus the digit; a legal entity's has nine digits and starts with 8 or 9.

The digit uses the weights 3, 7, 13, 17, 19, 23, 29, 37, 41, 43, 47, 53, 59, 67 and 71 from the right, modulus 11: when the remainder is 0 or 1 the digit is the remainder, otherwise eleven minus the remainder.

HOW IT IS FOUND

> COLUMN NAME `CO_L1_NIT – Path`
>
> **90%** `nit[a-z0-9_]*` `n(o|ro|um|umero)_?nit` `nit_?(proveedor|cliente|empresa|tercero|emisor|adquiriente|receptor|contribuyente|empleador)` `(proveedor|cliente|empresa|tercero|emisor|adquiriente|receptor|empleador)_?nit` `rut` `registro_?unico_?tributario` `n(o|ro|um|umero)_?identificacion_?tributaria`

> VALUE FORMAT `CO_L1_NIT – Regex`
>
PATTERN	STRENGTH	NOTES
`0*(?:\d{3}\.?\d{3}\.?\d{3}-\d)`	90%	
`0*(?:\d{1,3}(\.\d{3}){1,3}-\d)`	80%	
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The body is mapped digit by digit — with the same algorithm as the cédula, so a person's NIT still matches their cédula — and the check digit is recomputed. Every masked NIT is valid and the mapping is one-to-one. See *The NIT check digit*.

`CO_NIT` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.

`CO_NIT_6` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_6_AUX` → `CO_NIT_6_AJUSTE`, in this order.

> `CO_NIT_6_AUX` **CHECK DIGIT**
>
> Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46` from the right.
>
> > `CO_CM_DIGITOS_ANCHO_FIJO` **CHARACTER MAPPING**
> >
> > Maps each character to another of its group (1 groups), keeping length and format.
>
> `CO_NIT_6_AJUSTE` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_6_DV`.
>
> > `CO_NIT_6_DV` **CHECK DIGIT**
> >
> > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23` from the right.
> >
> > > `CO_IDENTIDAD` **REGEX DECOMPOSE**
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: keep.

`CO_NIT_7` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_7_AUX` → `CO_NIT_7_AJUSTE`, in this order.

> `CO_NIT_7_AUX` **CHECK DIGIT**
>
> Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58` from the right.
>
> `CO_NIT_7_AJUSTE` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_7_DV`.
>
> > `CO_NIT_7_DV` **CHECK DIGIT**
> >
> > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29` from the right.

`CO_NIT_8` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_8_AUX` → `CO_NIT_8_AJUSTE`, in this order.

> `CO_NIT_8_AUX` **CHECK DIGIT**
>
> Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74` from the right.
>
> `CO_NIT_8_AJUSTE` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_8_DV`.
>
> > `CO_NIT_8_DV` **CHECK DIGIT**
> >
> > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37` from the right.

`CO_NIT_9` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_9_AUX` → `CO_NIT_9_AJUSTE`, in this order.

> `CO_NIT_9_AUX` **CHECK DIGIT**
>
> Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74 82` from the right.
>
> `CO_NIT_9_AJUSTE` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_9_DV`.
>
> > `CO_NIT_9_DV` **CHECK DIGIT**
> >
> > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41` from the right.

`CO_NIT_10` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_10_AUX` → `CO_NIT_10_AJUSTE`, in this order.

> `CO_NIT_10_AUX` **CHECK DIGIT**
>
> Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74 82 86` from the right.
>
> `CO_NIT_10_AJUSTE` **REGEX DECOMPOSE**
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_10_DV`.
>
> > `CO_NIT_10_DV` **CHECK DIGIT**

> > Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41 43` from the right.

`CO_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
800.197.268-4	→	**265.590.357-6**
79456123-7	→	**69583619-0**

8.3 Foreigner documents

`CO_L1_DOCUMENTO_EXTRANJERO`

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

The cédula de extranjería, the Temporary Protection Permit (PPT) of Venezuelan migrants, the Special Stay Permit (PEP), the safe-conduct and the visa number.

HOW IT IS FOUND

> **COLUMN NAME** `CO_L1_DOCUMENTO_EXTRANJERO — Path`
>
> **85%** `c[eé]dula_?(de_?)?extranjer[ií]a` `ce` `c_e` `ppt` `permiso_?(por_?)?protecci[oó]n_?temporal` `pep` `permiso_?especial_?(de_?)?permanencia` `salvoconducto` `visa(_?(n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?(ce|ppt|pep|visa)` `documento_?migratorio` `carne_?diplom[aá]tico`

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PEP 123456789	→	**BAK 712017988**

8.4 Passport

`CO_L1_PASAPORTE`

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

Colombian passport numbers — two letters and six or seven digits, `AB123456` — and foreign ones.

HOW IT IS FOUND

> **COLUMN NAME** `CO_L1_PASAPORTE — Path`
>
> **90%** `pasaporte[a-z0-9_]*` `n(o|ro|um|umero)_?pasaporte` `passport[a-z0-9_]*`

> **VALUE FORMAT** `CO_L1_PASAPORTE — Regex`
>
PATTERN	STRENGTH	NOTES
`[A-Z]{2}\d{6,7}`	40%	
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AB123456	→	**0X623407**

8.5 Civil registry

`CO_L1_REGISTRO_CIVIL`

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The serial indicator of birth, marriage and death records, and the number of the live birth or death certificate.

HOW IT IS FOUND

> COLUMN NAME `CO_L1_REGISTRO_CIVIL` — Path
>
> 85% `registro_?civil(_?(de_?)?(nacimiento|matrimonio|defunci[oó]n))?(_?(serial|indicativo|n(o|ro|um|umero)))?` `indicativo_?serial` `serial_?registro` `certificado_?(de_?)?(nacido_?vivo|defunci[oó]n)` `n(o|ro|um|umero)_?(registro_?civil|certificado_?defuncion)`

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
52345678	→	**11443774**

8.6 Professional card

`CO_L1_TARJETA_PROFESIONAL`

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The number of the professional card or registration and of the ReTHUS health workforce registry. Professional councils publish these registers with the person's name.

HOW IT IS FOUND

> COLUMN NAME `CO_L1_TARJETA_PROFESIONAL` — Path
>
> 85% `tarjeta_?profesional(_?(n(o|ro|um|umero)))?` `t_?p` `n(o|ro|um|umero)_?tarjeta_?profesional` `matr[ií]cula_?profesional` `registro_?(m[eé]dico|profesional)` `rethus` `registro_?rethus`

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456-T	→	**111512-X**

8.7 Given name

`CO_L1_NOMBRE`

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

The given name, one or two: `Luz`, `Juan Carlos`, `María del Pilar`.

HOW IT IS FOUND

COLUMN NAME `CO_L1_NOMBRE – Path`

85% `primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `pri(mer)?_?nom` `seg(undo)?_?nom` `nombre_?1` `nombre_?2` `first_?names?` `given_?names?` `fname` `middle_?names?` `nombres` *(except when followed by `completos?`, `y_?apellidos?`, `apellidos?`)*

50% `nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES `CO_L1_NOMBRE – List`

LIST	VALUES	STRENGTH	FIRST VALUES
`co-detectar-nombres.txt`	280	70%	María, Maria, José, Jose, Luis, Carlos

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, each name replaced with one from the list. `de`, `del` and `la` stay in place. More than three words are masked character by character.

`CO_NOMBRES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_PALABRA_NOMBRE` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NOMBRE`.
>
> > `CO_NOMBRE` NAME
> >
> > Replaces the name with one of the 232 names in `co-nombres.txt`.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María del Pilar	→	**Elizabeth del Blanca**
JUAN CARLOS	→	**NATALIA ORLANDO**

8.8 Surname

CO_L1_APELLIDO

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The surnames — the first, the father's, and the second, the mother's —, in separate columns or together, and the married name: `López de Gómez`.

HOW IT IS FOUND

> **COLUMN NAME** CO_L1_APELLIDO — Path
>
> 85% `apellidos?` `primer_?apellido` `segundo_?apellido` `pri(mer)?_?ape` `seg(undo)?_?ape` `apellido_?(1|2|paterno|materno|casada)` `ape_?(1|2)` `last_?names?` `surnames?` `family_?names?` `lname`

> **KNOWN VALUES** CO_L1_APELLIDO — List
>
LIST	VALUES	STRENGTH	FIRST VALUES
`co-detectar-apellidos.txt`	328	70%	Rodríguez, Rodriguez, Gómez, Gomez, González, Gonzalez
>
> Values are split into words, and each word is looked up.
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, each surname replaced with one from the list; particles stay in place.

`CO_APELLIDOS` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_PALABRA_APELLIDO` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_APELLIDO`.
>
> > `CO_APELLIDO` NAME
> >
> > Replaces the name with one of the 255 names in `co-apellidos.txt`.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`López de Gómez`	→	**`Rengifo de Pinzón`**

8.9 Full name

CO_L1_NOMBRE_COMPLETO

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column: `Juan Carlos Rodríguez Gómez`. Also those of the mother, father, guardian, spouse, personal or family reference, and the identity name of a trans person.

A column called just `NOMBRE` may hold given names or full names: the values decide between the two domains.

HOW IT IS FOUND

COLUMN NAME CO_L1_NOMBRE_COMPLETO — Path

90% `nombres?_?(completos?|y_?apellidos?|apellidos?)` `nombre_?razon_?social` `nombre_?(del_?|de_?la_?)?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|funcionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|propietario|arrendatario|arrendador|conductor|acudiente|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|companero|contacto|referencia|victima|denunciante|sindicado|imputado|procesado|testigo|medico|docente|socio|accionista|heredero|causante|donante|tutor|curador|cotizante|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|funcionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|propietario|arrendatario|arrendador|conductor|acudiente|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|companero|contacto|referencia|victima|denunciante|sindicado|imputado|procesado|testigo|medico|docente|socio|accionista|heredero|causante|donante|tutor|curador|cotizante|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)_?(nombre|nom)` `nom_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|funcionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|propietario|arrendatario|arrendador|conductor|acudiente|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|companero|contacto|referencia|victima|denunciante|sindicado|imputado|procesado|testigo|medico|docente|socio|accionista|heredero|causante|donante|tutor|curador|cotizante|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `nombre_?(madre|padre|acudiente|conyuge|contacto_?emergencia|referencia)` `full_?name` `person_?name`

60% `madre` `padre` `acudiente` `conyuge` `companero_?permanente` `representante_?legal` `apoderado` `codeudor` `fiador` `beneficiario` `heredero` `titular` `referencia_?(personal|familiar)`

50% `nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES CO_L1_NOMBRE_COMPLETO — List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-nombres.txt	280	65%	María, Maria, José, Jose, Luis, Carlos
co-detectar-apellidos.txt	328	65%	Rodríguez, Rodriguez, Gómez, Gomez, González, Gonzalez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

In Colombian order: two words are a given name and a surname; three, a given name and two surnames; four, two and two; five, two given names and three words of surnames. `SURNAMES, GIVEN NAMES` with a comma, as in lists, is recognized too. The result is a plausible name, never the original.

`CO_NOMBRE_COMPLETO` **REGEX DECOMPOSE**

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

`CO_APELLIDOS` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_PALABRA_APELLIDO` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_APELLIDO`.
>
> > `CO_APELLIDO` NAME
> >
> > Replaces the name with one of the 255 names in `co-apellidos.txt`.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

`CO_NOMBRES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_PALABRA_NOMBRE` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_NOMBRE`.
>
> > `CO_NOMBRE` NAME
> >
> > Replaces the name with one of the 232 names in `co-nombres.txt`.

EXAMPLES

VALUE		MASKED
Juan Carlos Rodríguez Gómez	→	**Natalia Orlando Lara Pinzón**
Luz Rodríguez	→	**Maximiliano Lara**
RODRÍGUEZ GÓMEZ, JUAN CARLOS	→	**LARA PINZÓN, NATALIA ORLANDO**

8.10 E-mail

`CO_L1_EMAIL`

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and corporate e-mail addresses.

HOW IT IS FOUND

> COLUMN NAME `CO_L1_EMAIL — Path`
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electr[oó]nico)?[a-z0-9_]*` `dir_?correo` `direcci[oó]n_?(de_?)?correo` `direcci[oó]n_?electr[oó]nica`

> DATA TYPE `CO_L1_EMAIL — Type`
>
> Accepts text (length 5 or more); any other type rules the domain out.

> VALUE FORMAT `CO_L1_EMAIL — Regex`
>
PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	
>
> A value that matches none counts 20% against the domain.

HOW IT IS MASKED

User and domain are mapped character by character, and the top-level domain — `.com`, `.com.co` — becomes `.test`, reserved for testing: a masked address never delivers a message.

`CO_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`luz.rodriguez@gmail.com`	→	**`vim.seskotuuk@pgoeb.test`**

8.11 Phone

`CO_L1_TELEFONO`

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Ten-digit numbers since the 2021 numbering plan: mobiles starting with 3 (`310 456 7890`) and landlines starting with 60 and the regional digit (`601 345 6789` in Bogotá, `604` in Antioquia), with or without `+57` . Also seven-digit landlines from before 2021.

HOW IT IS FOUND

COLUMN NAME `CO_L1_TELEFONO – Path`

85% `tel` `tel[eé]fono[a-z0-9_]*` `tel_?(fijo|movil|m[oó]vil|celular|casa|oficina|contacto)` `celular[a-z0-9_]*` `cel` `m[oó]vil` `whats_?app` `n(o|ro|um|umero)_?` `(tel|tel[eé]fono|celular|cel|contacto|movil)` `fax` `ext(ension)?_?tel` `phone[a-z0-9_]*` `mobile[a-z0-9_]*`

VALUE FORMAT `CO_L1_TELEFONO – Regex`

PATTERN	STRENGTH	NOTES
`0*(?:(\+?57[\s\-]?)?3[0-2]\d[\s\-]?\d{3}[\s\-]?\d{4})`	100%	
`0*(?:(\+?57[\s\-]?)?\(?60[1-8]\)?[\s\-]?\d{3}[\s\-]?\d{4})`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The `+57` , the first three digits — the operator's range or the region — and the separators stay; the other seven digits are mapped.

`CO_TELEFONO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS` .

> `CO_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`+57 310 456 7890`	→	**`+57 310 047 9607`**
`601 345 6789`	→	**`601 203 7290`**

8.12 Address

`CO_L1_DIRECCION`

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

The address in the urban grid notation — the street, its number, the crossing street and the distance to it: `Carrera 7 # 32-16` , `Cl 100 No. 19-54 Apto 802` —, which places a door on a block, and rural addresses with a vereda, farm or kilometre.

HOW IT IS FOUND

COLUMN NAME CO_L1_DIRECCION — Path

80% `direcci[oó]n[a-z0-9_]*` *(except when preceded by* `mac` , `ip` , `e_?mail` , `web` , `url` , `correo` *; except when followed by list E4)* `dir_?(residencia|domicilio|correspondencia|notificaci[oó]n|entrega|cobro|oficina|trabajo|cliente|paciente)?` *(except when preceded by* `mac` , `ip` , `e_?mail` , `web` , `url` *; except when followed by* `ip` , `mac` , `correo` , `email` *)* `domicilio[a-z0-9_]*` `residencia` `lugar_?(de_?)?residencia` `address[a-z0-9_]*` *(except when preceded by* `mac` , `ip` , `e_?mail` , `web` , `url` *; except when followed by list E5)*

DATA TYPE CO_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT CO_L1_DIRECCION — Regex

PATTERN	STRENGTH	NOTES
`(?i)((av|avenida)\.?\s+)?(calle|cll?|carrera|cra|crr|kra?|cr|avenida|av|ak|ac|diagonal|dg|transversal|tv|tr|circular|cq|autopista|aut)\.?\s*\d+\s*[a-z]?(\s*(bis|sur|este))?\s*(#|no\.?|n[°º]|num\.?)?\s*\d+\s*[a-z]?\s*-\s*\d+.*`	90%	
`(?i).*\b(vereda|finca|corregimiento|kil[oó]metro|km)\b.*`	40%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced with a fictitious Colombian address in the same notation. Neighbourhood, vereda, municipality and postal code in their own columns are handled by their domains.

`CO_DIRECCION` **SECURE LOOKUP**

Replaces the value with one of the 4,000 values in `co-direcciones.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Carrera 7 # 32-16 Oficina 1203`	→	**`Carrera 52 # 100-66`**

8.13 Address complement

CO_L1_DIRECCION_COMPLEMENTO

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

Apartment, interior, tower, block, lot, floor or office in their own columns.

HOW IT IS FOUND

COLUMN NAME CO_L1_DIRECCION_COMPLEMENTO — Path

70% `complemento(_?direcci[oó]n)?` `apto` `apartamento` `interior` `int` `torre` `bloque` `casa_?(n(o|ro|um|umero))?` `manzana` `mz` `lote` `piso` `oficina` `local` `conjunto(_?residencial)?` `edificio`

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Torre 3 Apto 502	→	**Hablu 6 Ihye 654**

8.14 Bank account

CO_L1_CUENTA_BANCARIA

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Savings and current account numbers, low-value deposits and wallets. The bank code is not personal data and has no domain.

HOW IT IS FOUND

COLUMN NAME — CO_L1_CUENTA_BANCARIA — Path

85% `cuenta_?(bancaria|banco|ahorros?|corriente|n[oó]mina|deposito|dep[oó]sito|abono|pago|destino|origen)` `n(o|ro|um|umero)_?cuenta` `nro_?cta` `num_?cta` `cta_?(bancaria|ahorros|corriente)` `tipo_?y_?n(o|ro|um|umero)_?cuenta` `iban` `account_?(no|num|number)` `bank_?account` `dep[oó]sito_?electr[oó]nico` `billetera`

HOW IT IS MASKED

Digits are mapped; separators stay.

`CO_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123-456789-01	→	**061-766269-22**

8.15 Payment card

CO_L1_TARJETA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, recognized by the Luhn algorithm.

HOW IT IS FOUND

COLUMN NAME — CO_L1_TARJETA — Path

85% `tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?tarjeta` `pan` `card_?(no|num|number)` `credit_?card` `tc_?(numero|num)`

VALUE FORMAT — CO_L1_TARJETA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1-9]\d{12,13}|[1-9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Credit Card, which comes with the Masking Engine: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`CO_TARJETA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with the Masking Engine and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4539 5787 6362 1486	→	**4539 5722 0015 3609**

8.16 Bre-B key

CO_L1_LLAVE_BREB

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The key of Bre-B, the instant payment system of the Banco de la República: an identity document number, a mobile number, an e-mail or an alphanumeric key starting with `@`.

HOW IT IS FOUND

> COLUMN NAME CO_L1_LLAVE_BREB – Path
>
> **90%** `llave(_?(bre_?b|breb|pago|transferencia))?` `bre_?b(_?llave)?` `breb` `llave_?alfanum[eé]rica`

> VALUE FORMAT CO_L1_LLAVE_BREB – Regex
>
PATTERN	STRENGTH	NOTES
`@[A-Za-z0-9]{3,20}`		60%
>
> A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Each kind of key is masked as its own domain: the document digit by digit, the mobile keeping its range, the e-mail with `.test`, the alphanumeric key character by character keeping the `@`. A key holding the cédula and the same person's cédula still agree.

`CO_LLAVE_BREB` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

> `CO_EMAIL` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.
>
> > `CO_CM_ALFANUM` CHARACTER MAPPING
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_TELEFONO` REGEX DECOMPOSE
>
> Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.
>
> > `CO_CM_DIGITOS` CHARACTER MAPPING
> >
> > Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@luzrodriguez83`	→	**`@tofbetxutiib61`**
`3104567890`	→	**`3100479607`**

8.17 IP address

`CO_L1_IP`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses from access and transaction logs.

HOW IT IS FOUND

COLUMN NAME `CO_L1_IP – Path`

85% `ip` `ip_?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)` `direcci[oó]n_?ip` `dir_?ip` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip`

VALUE FORMAT `CO_L1_IP – Regex`

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to 1–254; an IPv6 is mapped keeping its hexadecimal characters.

`CO_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_HEX`.

`CO_OCTETO` NUMERIC MAPPING

Maps the number to another between 1 and 254.

`CO_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`190.85.46.120`	→	**`164.54.50.254`**

8.18 Device identifier

`CO_L1_DISPOSITIVO`

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

IMEI — which in Colombia is registered with the operators against theft —, IMSI, ICCID, MAC address, advertising identifiers, cookies and sessions.

HOW IT IS FOUND

COLUMN NAME CO_L1_DISPOSITIVO — Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `direcci[oó]n_?mac` `device_?(id|uuid|serial)` `id_?(dispositivo|equipo|celular)` `serial_?(equipo|celular|dispositivo)` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `id_?sesi[oó]n`

VALUE FORMAT CO_L1_DISPOSITIVO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, with hexadecimal digits kept hexadecimal: a MAC stays a MAC.

`CO_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**

8.19 Licence plate

CO_L1_PLACA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Car plates, three letters and three digits (`KDZ123`), and motorcycle plates, three letters, two digits and a letter (`XYZ12D`). The RUNT leads from the plate to the owner.

HOW IT IS FOUND

COLUMN NAME CO_L1_PLACA — Path

85% `placa(_?(veh[ií]culo|carro|moto|automotor))?` `n(o|ro|um|umero)_?placa` `license_?plate` `plate(_?(no|number))?`

VALUE FORMAT CO_L1_PLACA — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{3}[\s\-]?\d{3}`	80%	
`[A-Z]{3}[\s\-]?\d{2}[A-Z]`	80%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters become letters and digits become digits, position by position, with the hyphen: the plate format stays.

`CO_PLACA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM` .

> `CO_CM_DIGITOS_LETRAS` CHARACTER MAPPING
>
> Maps each character to another of its group (2 groups), keeping length and format.

`CO_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
KDZ123	→	**RRI957**
XYZ12D	→	**HOU58K**

8.20 Vehicle

`CO_L1_VEHICULO`

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number and the vehicle registration (licencia de tránsito) number.

HOW IT IS FOUND

COLUMN NAME `CO_L1_VEHICULO — Path`

85% `vin` `chasis` `n(o|ro|um|umero)_?(chasis|motor|serie|vin)` `serie_?veh[ií]culo` `motor_?n(o|ro|um|umero)` `licencia_?(de_?)?tr[aá]nsito(_?(n(o|ro|um|umero)))?` `tarjeta_?(de_?)?propiedad` `runt`

VALUE FORMAT `CO_L1_VEHICULO — Regex`

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
9FBHS41A1YM123456	→	**0PQRZ7700SS723598**

8.21 Real estate

`CO_L1_INMUEBLE`

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The folio de matrícula inmobiliaria — the registry office code and a number, `50C-1234567` —, the 30-digit national cadastral number, which starts with the DIVIPOLA code, and the cadastral code. Title certificates are public and lead to the owner.

HOW IT IS FOUND

COLUMN NAME CO_L1_INMUEBLE — Path

85% `folio_?(de_?)?matr[iíi]cula(_?inmobiliaria)?` `matr[iíi]cula_?inmobiliaria` `fmi` `c[eéi]dula_?catastral` `n(o|ro|um|umero)_?predial(_?nacional)?` `c[oói]digo_?catastral` `chip(_?predio)?` `referencia_?catastral` `predio_?(n(o|ro|um|umero)|codigo|id)`

VALUE FORMAT CO_L1_INMUEBLE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{2,3}[A-Z]?-\d{3,9})`	60%	
`0*(?:\d{30})`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The registry office and the municipality stay; the rest is mapped digit by digit.

`CO_INMUEBLE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.

> `CO_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
50C-1234567	→	**50C-5649285**

8.22 Contract and enrolment numbers

CO_L1_CONTRATO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Contract, policy, obligation, loan, subscriber or utility account (NIC, NIU) numbers, student enrolment and customer or employee codes.

HOW IT IS FOUND

COLUMN NAME CO_L1_CONTRATO — Path

70% `n(o|ro|um|umero)_?(contrato|p[oói]liza|obligaci[oói]n|cr[eéi]dito|pr[eéi]stamo|radicado_?(pqr|solicitud)|solicitud|afiliaci[oói]n|matr[iíi]cula|carn[eéi]|suscriptor|contador|medidor|cliente|cuenta_?contrato|factura_?servicio)` `contrato_?(n(o|ro|um|umero))` `matr[iíi]cula(_?(estudiante|alumno))?` *(except when followed by* `inmobiliaria`, `profesional`, `mercantil` *)* `c[oói]digo_?(estudiante|empleado|cliente|afiliado|suscriptor)` `id_?(cliente|empleado|afiliado|estudiante)` `n(o|ro|um|umero)_?suscriptor` `nic` `niu` `cuenta_?contrato` `carne`

HOW IT IS MASKED

Character by character, keeping length and format. The mapping is deterministic, so joins keep working.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
CT-123456	→	**NG-557411**

8.23 User and social media

CO_L1_USUARIO

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Login, alias and social media profiles.

HOW IT IS FOUND

COLUMN NAME CO_L1_USUARIO — Path

70% `usuario` `user_?name` `username` `login` `alias` `apodo` `nick(_?name)?` `perfil_?(instagram|facebook|twitter|tiktok|linkedin|x)` `instagram` `facebook` `twitter` `tiktok` `linkedin` `red_?social` `handle`

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
@luz_rodriguez	→	**@vim_seskotuuk**

8.24 Credentials

CO_L1_CREDENCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PINs, security codes and OTPs, CVV, tokens, API keys and secret answers.

HOW IT IS FOUND

COLUMN NAME CO_L1_CREDENCIAL — Path

90% `contrase[nñ]a` `clave` *(except when followed by* `producto`, `catastral`, `primaria`, `for[aá]nea`, `valor`, `dian`*)* `password` `passwd` `pwd` `pass` `hash_?(clave|contrasena|password)` `pin` `c[oó]digo_?(seguridad|verificaci[oó]n|acceso|otp)` `cvv` `cvc` `token(_?(acceso|refresh|api))?` `access_?token` `refresh_?token` `api_?key` `llave_?api` `secreto` `secret` `otp` `pregunta_?secreta` `respuesta_?secreta`

VALUE FORMAT CO_L1_CREDENCIAL — Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`. A credential has no use in a test copy, and a hash masked character by character could still be attacked.

`CO_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Clave#2024`	→	XXXXXXXXXX

8.25 Geolocation

CO_L1_GEOLOCALIZACION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns, from apps, visits, deliveries and property georeferencing.

HOW IT IS FOUND

COLUMN NAME CO_L1_GEOLOCALIZACION — Path

85%	`lat` `latitud` `lon` `lng` `longitud` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `georreferenciaci[oó]n` `geolocalizaci[oó]n` `gps(_?(ubicaci[oó]n|posici[oó]n|coordenadas))?` `ubicaci[oó]n_?gps`
50%	`long`

VALUE FORMAT CO_L1_GEOLOCALIZACION — Regex

PATTERN	STRENGTH	NOTES
`-?([0-9]|1[0-3])\.\d{3,}\s*,\s*-(6[6-9]|7\d|8[01])\.\d{3,}`	90%	
`-(6[6-9]|7\d|8[01])\.\d{4,}`	60%	
`-?([0-9]|1[0-3])\.\d{4,}`	30%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and the first decimal stay — about 11 km — and the other decimals are mapped: the place is generalized, not moved far away.

`CO_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`4.609710,-74.081750`	→	**`4.608357,-74.088248`**

8.26 Free text

`CO_L1_TEXTO_LIBRE`

COLUMN NAME **DATA TYPE** **VALUE FORMAT** **FREE TEXT REDACTION**

WHAT IT IS

Remarks, complaint (PQRS) descriptions, accounts of events, justifications and messages where anything gets written — cédula, mobile and name included.

HOW IT IS FOUND

COLUMN NAME `CO_L1_TEXTO_LIBRE – Path`

60% `observaci[oó]n(es)?` `obs` `comentarios?` `notas?` `anotaci[oó]n(es)?` `descripci[oó]n_?` `(pqr|pqrs|pqrsd|queja|reclamo|solicitud|caso|hechos|novedad|atenci[oó]n)` `detalle_?` `(pqr|solicitud|caso|atenci[oó]n)` `hechos` `relato` `justificaci[oó]n` `mensaje` *(except when preceded by list E6; except when followed by list E7)* `texto(_?libre)?` `resumen_?(caso|atenci[oó]n)` `queja` `reclamo` `pqrs?d?` `remarks?` `comments?` `notes?` `free_?text` `memo`

DATA TYPE `CO_L1_TEXTO_LIBRE – Type`

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT `CO_L1_TEXTO_LIBRE – Regex`

PATTERN	STRENGTH	NOTES
`0*(?:\d{1,3}(\.\d{3}){2,3})`	60%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:3\d{2}\s?\d{3}\s?\d{4})`	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: cédulas with dots, NITs, numbers of 6 to 11 digits, e-mail, mobiles, cards, plates and IPs become `[DATO]` ; given names and surnames from the list become `[NOMBRE]` . The rest of the text stays.

`CO_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with `[DATO]` , and the 1,188 terms of `co-texto-nombres.txt` with `[NOMBRE]` .

EXAMPLES

VALUE		MASKED
`Cliente Rodríguez, CC 79.456.123, correo l.rodriguez@gmail.com, cel 3104567890.`	→	**`Cliente [NOMBRE], CC [DATO], correo [DATO], cel [DATO].`**

PART 9

Quasi-identifiers

Data that identifies no one on its own, but does in combination. DIVIPOLA has 1,102 municipalities, Bogotá and 20 non-municipalized areas; 694 of those 1,122 units have fewer than 20,000 inhabitants in the DANE projection for 2026, and a few hundred people live in the smallest. A birth date, a sex and one of those municipalities point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

9.1 Birth date

CO_L2_FECHA_NACIMIENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The birth date, as a date, timestamp or text.

HOW IT IS FOUND

COLUMN NAME CO_L2_FECHA_NACIMIENTO – Path

90% `(fecha|fec|fch|f)_?(de_?)?nac(imiento)?` `fnac` `fechanac(imiento)?` `cumplea[ñn]os` `dob` `date_?of_?birth` `birth_?date` `birthday`

DATA TYPE CO_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days either way. Ages and school years change for few people; the date stays plausible and the same birth shifts the same way in every table.

`CO_FECHA_NACIMIENTO` DATE SHIFT
Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

9.2 Birth year

CO_L2_ANIO_NACIMIENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The birth year in a column of its own.

HOW IT IS FOUND

COLUMN NAME CO_L2_ANIO_NACIMIENTO – Path

90% `a[ñn]o_?(de_?)?nac(imiento)?` `anio_?nac(imiento)?` `year_?of_?birth` `birth_?year` `yob`

DATA TYPE CO_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: `1985` becomes a year from 1980 to 1989.

`CO_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `CO_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

9.3 Age

CO_L2_EDAD

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Age in years, also age group.

HOW IT IS FOUND

> COLUMN NAME CO_L2_EDAD — Path
>
> 85% `edad(_?(actual|a[nñ]os|anios|paciente|afiliado|cliente|al_?(ingreso|diagn[oó]stico|fallecimiento)))?` `grupo_?etario` `rango_?(de_?)?edad` `quinquenio` `age(_?(years|group))?`

> DATA TYPE CO_L2_EDAD — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the unit is mapped (37 becomes 30 to 39). A hundred or more becomes 90: rare ages identify.

`CO_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CO_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

9.4 Personal event dates

CO_L2_FECHA_EVENTO

COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

Dates that say something about the person: death, marriage, hiring and leaving, pension, hospitalization and discharge, diagnosis, childbirth, arrest, conviction, issue of the cédula, displacement, sick leave.

HOW IT IS FOUND

COLUMN NAME CO_L2_FECHA_EVENTO — Path

80% `(fecha|fec|fch|f)_?(de_?)?(defunci[oó]n|fallecimiento|muerte|matrimonio|divorcio|ingreso|retiro|vinculaci[oó]n|desvinculaci[oó]n|contrataci[oó]n|terminaci[oó]n_?contrato|pensi[oó]n|hospitalizaci[oó]n|egreso|diagn[oó]stico|atenci[oó]n|consulta|parto|captura|condena|expedici[oó]n(_?(documento|c[eé]dula|cc))?|desplazamiento|declaraci[oó]n|hecho_?victimizante|vacunaci[oó]n|cirug[ií]a|accidente|incapacidad) fec_?(exp|expedicion|defuncion|ingreso|retiro) date_?of_?(death|marriage|hire|admission|discharge)`

DATA TYPE CO_L2_FECHA_EVENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days either way. The cédula's issue date is asked as an identity check: masked, it can no longer be used to impersonate.

`CO_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

9.5 Sex

CO_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Sex as the record holds it: `F` / `M`, `Femenino` / `Masculino`, `Mujer` / `Hombre` or the codes 1 and 2.

HOW IT IS FOUND

COLUMN NAME CO_L2_SEXO — Path

85% `sexo(_?(biol[oó]gico|al_?nacer|paciente|afiliado|cliente))?` `(tp|tipo|cod|cd|id)_?sexo` `g[eé]nero` *(except when followed by* `identidad`, `autopercibido` *)* `sex` `gender` *(except when followed by* `identity` *)*

KNOWN VALUES CO_L2_SEXO — List

LIST	VALUES	STRENGTH	FIRST VALUES
`co-detectar-sexo.txt`	6	80%	femenino, masculino, mujer, hombre, female, male
`co-detectar-sexo-letra.txt`	3	60%	f, m, h

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: `F` stays `F` or `M`, `1` stays `1` or `2`.

`CO_SEXO` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CO_SEXO_FEMENINO_MASCULINO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-sexo-femenino-masculino.txt`, chosen by a keyed hash.
>
> `CO_SEXO_MUJER_HOMBRE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-sexo-mujer-hombre.txt`, chosen by a keyed hash.
>
> `CO_SEXO_FEMALE_MALE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-sexo-female-male.txt`, chosen by a keyed hash.
>
> `CO_SEXO_F_M` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-sexo-f-m.txt`, chosen by a keyed hash.
>
> `CO_SEXO_H_M` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-sexo-h-m.txt`, chosen by a keyed hash.
>
> `CO_SEXO_1_2` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
Masculino	→	**Femenino**

9.6 Municipality

`CO_L2_MUNICIPIO`

COLUMN NAME · VALUE FORMAT · DATA CLEANSING

WHAT IT IS

The municipality of residence, birth, document issue or occurrence, by name — on its own or with the department, `La Unión – Sucre`, `La Unión (Sucre)`.

HOW IT IS FOUND

> **COLUMN NAME** `CO_L2_MUNICIPIO – Path`
>
> **85%** `municipio(_?(residencia|nacimiento|expedici[oó]n|domicilio|paciente|cliente|ocurrencia|atenci[oó]n|notificaci[oó]n))?` *(except when followed by* `dane`, `cod`, `codigo`, `id`*)* `mpio(_?(res|nac|residencia|nacimiento))?` `ciudad(_?(residencia|nacimiento|expedici[oó]n|domicilio|cliente|origen))?` `(nom|nombre|desc)_?(municipio|mpio|ciudad)` `lugar_?(de_?)?(nacimiento|expedici[oó]n)` `municipio_?expedici[oó]n` `city` `town` `localidad_?residencia`

> **VALUE FORMAT** `CO_L2_MUNICIPIO – Values`
>
PATTERN	STRENGTH	NOTES
One of 1,008 known values, ignoring case — Medellín, Abejorral, Abriaquí, Alejandría, Amagá, Amalfi, …	80%	
>
> A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A municipality with fewer than 20,000 inhabitants becomes the nearest municipality of the same department with at least 20,000; larger ones stay. See *Where people live*.

`CO_MUNICIPIO` DATA CLEANSING

Replaces each value found in `co-municipios-generalizados.txt` (12,622 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Jardín	→	**Andes**
La Unión – Sucre	→	**San Marcos – Sucre**
Medellín	→	**Medellín**

9.7 Municipality code (DIVIPOLA)

CO_L2_CODIGO_MUNICIPIO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The DANE DIVIPOLA code, five digits: two for the department and three for the municipality, `05001` for Medellín.

HOW IT IS FOUND

COLUMN NAME CO_L2_CODIGO_MUNICIPIO – Path

85% `(cod|codigo|cd|id)_?(municipio|mpio|ciudad|mun)(_?(dane|res|residencia|nac|nacimiento|ocurrencia|divipola))?` `(cod|codigo)_?dane(_?(municipio|mpio))?` `divipola` `cod_?mpio` `codmpio` `dane_?mpio`

VALUE FORMAT CO_L2_CODIGO_MUNICIPIO – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(05|08|11|13|15|17|18|19|20|23|25|27|41|44|47|50|52|54|63|66|68|70|73|76|81|85|86|88|91|94|95|97|99)\d{3})`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same generalization as the name: a small municipality's code becomes that of the municipality replacing its name. The two still agree.

`CO_CODIGO_MUNICIPIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `CO_CODIGO_MUNICIPIO_TABLA` DATA CLEANSING
>
> Replaces each value found in `co-codigos-municipio-generalizados.txt` (767 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
05364	→	**05034**

9.8 Postal code

CO_L2_CODIGO_POSTAL

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The six-digit 4-72 postal code: two for the department, two for the postal zone and two for the postal district.

HOW IT IS FOUND

COLUMN NAME CO_L2_CODIGO_POSTAL – Path

85% `c[oó]digo_?postal` `cod_?postal` `codpostal` `zip(_?code)?` `postal_?code` `cp`

DATA TYPE CO_L2_CODIGO_POSTAL – Type

Accepts text (length 6 to 6) or number (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The two department digits stay and the others become zero: `110231` becomes `110000`.

`CO_CODIGO_POSTAL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
110231	→	**110000**

9.9 Neighbourhood, locality and commune

CO_L2_BARRIO

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The neighbourhood, housing estate or residential complex, locality or commune of residence.

HOW IT IS FOUND

COLUMN NAME CO_L2_BARRIO – Path

80% `barrio(_?(residencia|domicilio|cliente))?` `(nom|nombre)_?barrio` `urbanizaci[oó]n` `conjunto_?residencial` `localidad` *(except when followed by* `c[oó]digo`, `cod`*)* `comuna` `upz` `neighbou?rhood`

HOW IT IS MASKED

Replaced with a neighbourhood name common in Colombia — Centro, La Esperanza, San José —, unrelated to the original.

`CO_BARRIO` SECURE LOOKUP

Replaces the value with one of the 35 values in `co-barrios.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Chapinero Alto	→	**Santa Mónica**

9.10 Vereda and corregimiento

CO_L2_VEREDA

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The vereda, corregimiento, populated centre, indigenous reserve or farm of a rural address: communities of a few dozen families.

HOW IT IS FOUND

COLUMN NAME CO_L2_VEREDA — Path

85% `vereda(_?(residencia|nombre))?` `corregimiento` `centro_?poblado` `inspecci[oó]n_?(de_?)?` `polic[ií]a` `resguardo(_?ind[ií]gena)?` `caser[ií]o` `finca` `parcela`

HOW IT IS MASKED

Replaced with `Zona rural`.

`CO_ZONA_RURAL` SECURE LOOKUP

Replaces the value with one of the 1 values in `co-zona-rural.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Vereda La Esperanza	→	**Zona rural**

9.11 Nationality

CO_L2_NACIONALIDAD

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. Venezuelans are by far the largest foreign community.

HOW IT IS FOUND

COLUMN NAME CO_L2_NACIONALIDAD — Path

80% `nacionalidad` `pa[ií]s_?(de_?)?(nacimiento|origen|nacionalidad)` `ciudadan[ií]a` `nationality` `citizenship` `country_?of_?birth`

VALUE FORMAT CO_L2_NACIONALIDAD — Values

PATTERN	STRENGTH	NOTES
One of 41 known values, ignoring case — Colombiana, Venezolana, Ecuatoriana, Peruana, Estadounidense, Española, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a nationality from the list: Colombian and the largest foreign communities.

`CO_NACIONALIDAD` SECURE LOOKUP

Replaces the value with one of the 16 values in `co-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Haitiana	→	**Mexicana**

9.12 Marital status

CO_L2_ESTADO_CIVIL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Single, married, de facto marital union, separated, divorced or widowed, in words or as a code.

HOW IT IS FOUND

COLUMN NAME CO_L2_ESTADO_CIVIL — Path

85% `estado_?civil` `est_?civil` `(cod|tipo|id)_?estado_?civil` `situaci[oó]n_?conyugal` `marital_?status` `civil_?status`

VALUE FORMAT CO_L2_ESTADO_CIVIL — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Soltero a, Casado a, Unión marital de hecho, Separado a, Divorciado a, Viudo a, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another status from the list; a code stays a code.

`CO_ESTADO_CIVIL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ESTADO_CIVIL_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_ESTADO_CIVIL_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `co-estado-civil-codigos.txt`, chosen by a keyed hash.

`CO_ESTADO_CIVIL_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `co-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Unión libre	→	**Divorciado(a)**

9.13 Occupation

CO_L2_OCUPACION

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Occupation, profession or trade, in words or by the CIUO-08 code adapted for Colombia. A rare occupation in a small municipality identifies.

HOW IT IS FOUND

COLUMN NAME — CO_L2_OCUPACION — Path

80% `ocupaci[oó]n` `profesi[oó]n` `oficio` `ciuo` `(cod|codigo)_?(ocupacion|ciuo|profesion)` `actividad_?econ[oó]mica_?(persona|afiliado)` `cargo_?(actual|empleado|trabajador)` `occupation` `profession` `job_?title`

50% `cargo`

HOW IT IS MASKED

A text is replaced with a common occupation; a code is mapped digit by digit.

`CO_OCUPACION_O_CIUO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_OCUPACION`.

`CO_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`CO_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 39 values in `co-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Gerente de operaciones regionales`	→	**`Modista`**

9.14 Employer

CO_L2_EMPLEADOR

COLUMN NAME — SECURE LOOKUP

WHAT IT IS

The name of the company or body the person works for.

HOW IT IS FOUND

COLUMN NAME — CO_L2_EMPLEADOR — Path

80% `empleador(_?(nombre|raz[oó]n_?social))?` `(nombre|nom)_?(empleador|empresa_?donde_?trabaja|empresa_?labora)` `empresa_?(donde_?)?(trabaja|labora)` `lugar_?(de_?)?trabajo` `empresa_?empleadora` `patrono` `employer(_?name)?` `workplace`

HOW IT IS MASKED

Replaced with a fictitious company.

`CO_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 24 values in `co-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Ecopetrol S.A.`	→	**`Droguería El Buen Vecino`**

9.15 Education

CO_L2_ESCOLARIDAD

COLUMN NAME — VALUE FORMAT — REGEX DECOMPOSE

WHAT IT IS

The highest education level — from none to doctorate —, in words or as a code.

HOW IT IS FOUND

COLUMN NAME CO_L2_ESCOLARIDAD — Path

80% `escolaridad` `nivel_?(educativo|de_?estudios|acad[eé]mico|escolaridad|formaci[oó]n)` `grado_?(de_?)?(instrucci[oó]n|escolaridad)` `m[aá]ximo_?nivel` `formaci[oó]n_?acad[eé]mica` `education(_?level)?`

VALUE FORMAT CO_L2_ESCOLARIDAD — Values

PATTERN	STRENGTH	NOTES
One of 24 known values, ignoring case — Ninguno, Preescolar, Básica primaria, Básica secundaria, Media bachiller, Técnica profesional, …	60%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another level from the list; a code stays a code.

`CO_ESCOLARIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ESCOLARIDAD_LISTA` .

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CO_ESCOLARIDAD_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 11 values in `co-escolaridad-codigos.txt` , chosen by a keyed hash.
>
> `CO_ESCOLARIDAD_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 11 values in `co-escolaridad.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Posdoctorado	→	**Preescolar**

9.16 Educational institution

CO_L2_INSTITUCION_EDUCATIVA

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The school, educational institution or university, by name or by the DANE code of the establishment.

HOW IT IS FOUND

COLUMN NAME CO_L2_INSTITUCION_EDUCATIVA — Path

75% `colegio(_?(nombre|egreso))?` `(nombre|nom)_?(colegio|instituci[oó]n_?educativa|universidad|establecimiento_?educativo)` `instituci[oó]n_?educativa` `establecimiento_?educativo` `universidad` `(cod|codigo)_?dane_?(colegio|establecimiento|sede)` `school(_?name)?` `university`

HOW IT IS MASKED

Replaced with a fictitious institution.

`CO_INSTITUCION_EDUCATIVA` SECURE LOOKUP

Replaces the value with one of the 12 values in `co-instituciones-educativas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Colegio Mayor de San Bartolomé	→	**Corporación Universitaria del Valle**

9.17 Dependants and children

CO_L2_PERSONAS_A_CARGO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of dependants, children or household members.

HOW IT IS FOUND

COLUMN NAME CO_L2_PERSONAS_A_CARGO — Path

80% `personas_?a_?cargo` `n(o|ro|um|umero)_?(de_?)?(hijos|dependientes|personas_?a_?cargo)` `cant(idad)?_?(hijos|dependientes|personas_?hogar)` `hijos` `dependientes` `personas_?(en_?el_?)?hogar` `tama[nñ]o_?hogar` `number_?of_?children` `dependents`

DATA TYPE CO_L2_PERSONAS_A_CARGO — Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values from 0 to 5 stay; above 5 they become 5. Very large families are rare, and a rare count identifies.

`CO_CONTEO_LIMITADO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 10

Sensitive data

The categories of article 5 that are not health data — which has a group of its own: racial or ethnic origin, political orientation, religious or philosophical convictions, membership of trade unions, of social and human rights organizations and of parties, sexual life and biometric data. The list is illustrative (*such as*): the set includes genetic data, sexual orientation and gender identity, and two categories that in Colombia expose people to discrimination and violence — being a **victim of the armed conflict**, whose information is confidential (Law 1448 of 2011, arts. 29 and 156), and being a **person in the reincorporation process**. Categorical columns keep their shape: an S/N flag stays a flag, a code is replaced by another code of the same catalog and any other value by one from the list of its category. Where the values share no vocabulary, they are suppressed to `Sin información`.

10.1 Ethnic self-recognition

CO_L3_GRUPO_ETNICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The ethnic group a person recognizes themselves in, in the categories of the 2018 census: indigenous (1,905,617 people, 4.4%), Gypsy or Rrom, Raizal of the San Andrés, Providencia and Santa Catalina Archipelago, Palenquero of San Basilio, Black, mulatto, Afro-descendant or Afro-Colombian, or none; in words, as a code or as a flag.

HOW IT IS FOUND

COLUMN NAME — CO_L3_GRUPO_ETNICO — Path

95% `etnia` `grupo_?[eé]tnico` `pertenencia_?[eé]tnica` `autorreconocimiento(_?[eé]tnico)?` `auto_?reconocimiento` `(cod|codigo|tipo|id)_?(etnia|pertenencia_?etnica)` `raza` `origen_?[eé]tnico` `afrocolombiano` `afrodescendiente` `raizal` `palenquero` `rrom` `gitano` `ethnicity` `race`

VALUE FORMAT — CO_L3_GRUPO_ETNICO — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Indígena, Gitano a o Rrom, Raizal del Archipiélago de San Andrés Providencia y Santa Catalina, Palenquero a de San Basilio, Negro a mulato a afrodescendiente afrocolombiano a, Ningún grupo étnico, …	90%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag, a code is replaced by another code of the catalog and any other value by a census category.

`CO_GRUPO_ETNICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_GRUPO_ETNICO_LISTA`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_GRUPO_ETNICO_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `co-grupos-etnicos-codigos.txt`, chosen by a keyed hash.

`CO_GRUPO_ETNICO_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `co-grupos-etnicos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afrocolombiana	→	**Raizal del Archipiélago de San Andrés, Providencia y Santa Catalina**
5	→	**3**

10.2 Indigenous people and ethnic community

`CO_L3_PUEBLO_INDIGENA`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The indigenous people — the 2018 census identified 115; the Wayuu (380,460), Zenú (307,091), Nasa (243,176) and Pastos (163,873) make up 58.1% of the indigenous population —, the reserve or council, the Afro-descendant community council and the Rrom kumpania.

HOW IT IS FOUND

COLUMN NAME `CO_L3_PUEBLO_INDIGENA – Path`

90% `pueblo(_?ind[ií]gena)?` `(cod|codigo|nombre|nom)_?pueblo` `resguardo_?ind[ií]gena` `cabildo(_?ind[ií]gena)?` `comunidad_?(ind[ií]gena|negra|afro)` `consejo_?comunitario` `parcialidad` `kumpania` `indigenous_?people`

VALUE FORMAT `CO_L3_PUEBLO_INDIGENA – Values`

PATTERN	STRENGTH	NOTES
One of 112 known values, ignoring case — Achagua, Amorúa, Andoke, Arhuaco, Awá, Bara, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A people code is replaced with another code; a name with one of the most numerous peoples.

`CO_PUEBLO_INDIGENA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PUEBLO_INDIGENA_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_PUEBLO_INDIGENA_CODIGO` SECURE LOOKUP

Replaces the value with one of the 10 values in `co-pueblos-indigenas-codigos.txt`, chosen by a keyed hash.

`CO_PUEBLO_INDIGENA_LISTA` SECURE LOOKUP

Replaces the value with one of the 20 values in `co-pueblos-indigenas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Kuna	→	**Muisca**

10.3 Native language

`CO_L3_LENGUA_NATIVA`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The language a person speaks: Colombia has 65 indigenous languages, besides the San Andrés creole, the Palenquero language and Romani. Speaking Wayuunaiki or Nasa Yuwe reveals the people of origin.

HOW IT IS FOUND

COLUMN NAME `CO_L3_LENGUA_NATIVA – Path`

90% `lengua_?(nativa|materna|ind[ií]gena|propia)` `idioma_?(nativo|materno|ind[ií]gena)` `habla_?` `lengua` `lengua` *(except when followed by* `extranjera`, `codigo`, `cod`*)* `mother_?tongue` `native_?language`

VALUE FORMAT `CO_L3_LENGUA_NATIVA – Values`

PATTERN	STRENGTH	NOTES
One of 32 known values, ignoring case — Español, Wayuunaiki, Nasa Yuwe, Emberá, Namtrik, Sikuani, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a language from the list; a flag stays a flag.

`CO_LENGUA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_LENGUA_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_LENGUA_LISTA` SECURE LOOKUP

Replaces the value with one of the 12 values in `co-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Tikuna	→	**Ninguna lengua nativa**

10.4 Religion

`CO_L3_RELIGION`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The religion, church or congregation a person belongs to.

HOW IT IS FOUND

COLUMN NAME `CO_L3_RELIGION – Path`

95% `religi[oó]n` `creencia_?religiosa` `convicci[oó]n_?religiosa` `credo` `confesi[oó]n_?religiosa` `culto` `iglesia(_?(a_?la_?que_?pertenece|nombre))?` `denominaci[oó]n_?religiosa` `(cod|codigo|tipo)_?religion` `religion` `church`

VALUE FORMAT `CO_L3_RELIGION – Values`

PATTERN	STRENGTH	NOTES
One of 29 known values, ignoring case — Católica, Cristiana evangélica, Pentecostal, Adventista del Séptimo Día, Testigo de Jehová, Iglesia de Jesucristo de los Santos de los Últimos Días, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a religion from the list.

`CO_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_RELIGION_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_RELIGION_LISTA` SECURE LOOKUP

Replaces the value with one of the 12 values in `co-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Anglicana	→	**Musulmana**

10.5 Philosophical convictions

`CO_L3_CONVICCION_FILOSOFICA`

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Philosophical and moral convictions, conscientious objection — invoked in Colombia, for instance, against military service — and membership of lodges.

HOW IT IS FOUND

COLUMN NAME `CO_L3_CONVICCION_FILOSOFICA – Path`

90% `convicci[oó]n(es)?_?(filos[oó]fica|moral|personal)` `creencias?_?(filos[oó]ficas?|personales)` `objeci[oó]n_?(de_?)?conciencia` `objetor_?(de_?)?conciencia` `masoner[ií]a logia` `beliefs?` `philosophical_?beliefs?`

HOW IT IS MASKED

The values share no vocabulary: they are suppressed to `Sin información`. Flags and codes keep their shape.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Se niega a transfusiones	→	**Sin información**

10.6 Political orientation

CO_L3_ORIENTACION_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Political leaning, ideology, sympathy and voting intention, from surveys and registers.

HOW IT IS FOUND

COLUMN NAME CO_L3_ORIENTACION_POLITICA — Path

90% `orientaci[oó]n_?pol[ií]tica` `opini[oó]n_?pol[ií]tica` `tendencia_?pol[ií]tica` `ideolog[ií]a(_?pol[ií]tica)?` `preferencia_?(pol[ií]tica|partidista|electoral)` `intenci[oó]n_?(de_?)?voto` `simpat[ií]a_?pol[ií]tica` `political_?(opinion|orientation|view)` `voting_?intention`

VALUE FORMAT CO_L3_ORIENTACION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a position from the list — left to right, independent.

`CO_ORIENTACION_POLITICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ORIENTACION_POLITICA_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_ORIENTACION_POLITICA_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `co-orientaciones-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Uribista	→	**Centroderecha**

10.7 Party membership

CO_L3_AFILIACION_PARTIDO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The party or political movement a person is a member of, and belonging to the opposition. The National Electoral Council certified 28 political organizations with legal personality in September 2026.

HOW IT IS FOUND

COLUMN NAME CO_L3_AFILIACION_PARTIDO — Path

95% `partido(_?pol[ií]tico)?(_?(afiliaci[oó]n|nombre|militancia))?` `movimiento_?pol[ií]tico` `afiliaci[oó]n_?(pol[ií]tica|partidista|partido)` `militancia(_?pol[ií]tica)?` `militante` `(cod|codigo|nombre|nom)_?partido` `colectividad` `bancada` `oposici[oó]n` `political_?party` `party_?membership`

VALUE FORMAT CO_L3_AFILIACION_PARTIDO — Values

PATTERN	STRENGTH	NOTES
One of 50 known values, ignoring case — Partido Liberal Colombiano, Partido Conservador Colombiano, Partido Cambio Radical, Partido Alianza Verde, Movimiento Autoridades Indígenas de Colombia AICO, Partido Alianza Social Independiente ASI, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another organization from the list of those with legal personality; a flag stays a flag.

`CO_PARTIDO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PARTIDO_LISTA`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_PARTIDO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 29 values in `co-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Polo Democrático Alternativo	→	**Partido Colombia Renaciente**

10.8 Trade union membership

CO_L3_SINDICATO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The union, being unionized, the union fee deducted from payroll, union immunity and the confederation — CUT, CGT, CTC.

HOW IT IS FOUND

COLUMN NAME CO_L3_SINDICATO — Path

95% `sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))?` `sindicalizado` `afiliado_?sindicato` `afiliaci[oó]n_?sindical` `cuota_?sindical` `descuento_?sindical` `aporte_?sindical` `asociaci[oó]n_?sindical` `fuero_?sindical` `directivo_?sindical` `central_?obrera` `convenci[oó]n_?colectiva` `pacto_?colectivo` `trade_?union` `union_?member(ship)?`

VALUE FORMAT CO_L3_SINDICATO — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — CUT, CGT, CTC, FECODE, USO, SINTRAINAL, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
SINTRAINAL	→	**Sin información**
S	→	**S**

10.9 Social and human rights organizations

CO_L3_ORGANIZACION_SOCIAL

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

Membership of social, community and human rights organizations, the community action board, and being a social leader or human rights defender — in Colombia, among the conditions most exposed to violence.

HOW IT IS FOUND

> COLUMN NAME CO_L3_ORGANIZACION_SOCIAL — Path
>
> 90% `organizaci[oó]n_?(social|comunitaria|de_?base|de_?derechos_?humanos|defensora)` `l[ií]der(esa)?_?(social|comunal|comunitario)` `liderazgo_?social` `defensor(a)?_?(de_?)?derechos_?humanos` `ddhh` `junta_?(de_?)?acci[oó]n_?comunal` `jac` `movimiento_?social` `asociaci[oó]n_?(de_?)?(v[ií]ctimas|campesinos|mujeres)` `colectivo_?social` `ong_?(afiliado|miembro)` `human_?rights_?defender`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Junta de Acción Comunal vereda El Salitre	→	**Sin información**

10.10 Biometric data

CO_L3_BIOMETRICO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Fingerprint templates — biometric validation against the Registry is common in banks and notaries —, face, iris, voice and digitized signature.

HOW IT IS FOUND

COLUMN NAME CO_L3_BIOMETRICO — Path

90% `biometr[ií]a[a-z_]*` `biom[eé]trico[a-z_]*` `huella(_?dactilar)?(_?(template|plantilla|imagen|hash))?` `huellas` `dactilar` `template_?(facial|huella|biometrico)` `plantilla_?(facial|biom[eé]trica)` `rostro_?(hash|template)` `reconocimiento_?facial` `firma_?(biom[eé]trica|digitalizada|manuscrita)` `iris` `voz_?(biom[eé]trica|template)` `fingerprints?` `face_?(template|hash|encoding)` `biometric[a-z_]*`

DATA TYPE CO_L3_BIOMETRICO — Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. A masked template authenticates no one.

`CO_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

10.11 Genetic data

CO_L3_GENETICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Genetic and DNA test results, paternity tests, genetic profiles, mutations, karyotype, newborn screening. Not on the list of article 5, but they reveal health and origin.

HOW IT IS FOUND

COLUMN NAME CO_L3_GENETICO — Path

90% `adn` `dna` `gen[eé]tic[oa]s?` `datos?_?gen[eé]ticos?` `genoma` `genotip[a-z_]*` `prueba_?(gen[eé]tica|de_?adn|de_?paternidad)` `perfil_?gen[eé]tico` `mutaci[oó]n` `brca[12]?` `cariotipo` `tamizaje_?neonatal` `genetic[a-z_]*`

VALUE FORMAT CO_L3_GENETICO — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`.

`CO_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXXXX

10.12 Sexual orientation

CO_L3_ORIENTACION_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Self-declared sexual orientation, in health and diversity registers. It is data concerning sexual life.

HOW IT IS FOUND

COLUMN NAME CO_L3_ORIENTACION_SEXUAL — Path

95% `orientaci[oó]n_?sexual` `orient_?sexual` `(cod|codigo|tipo)_?orientacion_?sexual` `preferencia_?sexual` `sexual_?orientation`

VALUE FORMAT CO_L3_ORIENTACION_SEXUAL — Values

PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a category from the list.

`CO_ORIENTACION_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ORIENTACION_SEXUAL_LISTA`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_ORIENTACION_SEXUAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `co-orientaciones-sexuales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Homosexual	→	**Pansexual**

10.13 Sexual life

CO_L3_VIDA_SEXUAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Sexual activity and behaviour, number of partners, sexual debut.

HOW IT IS FOUND

COLUMN NAME CO_L3_VIDA_SEXUAL — Path

90% `vida_?sexual` `actividad_?sexual` `conducta_?sexual` `pr[aá]cticas?_?sexuales?` `parejas?_?sexuales?` `n(o|ro|um|umero)_?parejas` `sexualmente_?activ[oa]` `inicio_?(de_?)?(la_?)?vida_?sexual` `relaciones_?sexuales` `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|partners)`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Activa	→	**Sin información**

10.14 Gender identity

CO_L3_IDENTIDAD_GENERO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Self-declared gender identity. Not on the list of article 5, but it exposes people to the same discrimination. The identity name falls under the full-name domain.

HOW IT IS FOUND

COLUMN NAME CO_L3_IDENTIDAD_GENERO — Path

95% `identidad_?(de_?)?g[eé]nero` `(cod|codigo|tipo)_?identidad_?genero` `g[eé]nero_?(autopercibido|identitario)` `transg[eé]nero` `persona_?trans` `nombre_?identitario` `pronombres?` `gender_?identity`

VALUE FORMAT CO_L3_IDENTIDAD_GENERO — Values

PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — Mujer cisgénero, Hombre cisgénero, Mujer trans, Hombre trans, Persona no binaria, Otra, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a category from the list.

`CO_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_IDENTIDAD_GENERO_LISTA`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `co-identidades-genero.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Transgénero	→	**Hombre trans**

10.15 Victim of the armed conflict

CO_L3_VICTIMA_CONFLICTO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Being a victim and the victimizing event of the Single Victims Registry — forced displacement, homicide, threat, enforced disappearance, kidnapping, crimes against sexual freedom, landmines, recruitment —, often as a flag. The information a victim provides is confidential (Law 1448 of 2011, arts. 29 and 156).

HOW IT IS FOUND

COLUMN NAME CO_L3_VICTIMA_CONFLICTO – Path

95% `v[ií]ctima(_?(del_?)?(conflicto(_?armado)?|ruv))?` `hecho_?victimizante` `(cod|codigo|tipo)_?hecho(_?victimizante)?` `ruv` `registro_?[uú]nico_?(de_?)?v[ií]ctimas` `desplazad[oa](_?(forzad[oa]))?` `condici[oó]n_?(de_?)?(v[ií]ctima|desplazado)` `poblaci[oó]n_?desplazada` `estado_?ruv` `sujeto_?(de_?)?reparaci[oó]n` `victim_?of_?conflict`

VALUE FORMAT CO_L3_VICTIMA_CONFLICTO – Values

PATTERN	STRENGTH	NOTES
One of 24 known values, ignoring case — Desplazamiento forzado, Homicidio, Amenaza, Desaparición forzada, Pérdida de bienes muebles o inmuebles, Secuestro, …	80%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a victimizing event from the list.

`CO_VICTIMA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_VICTIMA_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_VICTIMA_LISTA` SECURE LOOKUP

Replaces the value with one of the 15 values in `co-hechos-victimizantes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Masacre	→	**Confinamiento**
S	→	**S**

10.16 Reincorporation

CO_L3_REINCORPORACION

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Being in the reincorporation or reintegration process of the Agency for Reincorporation and Normalization (ARN): ex-combatants and peace signatories.

HOW IT IS FOUND

> COLUMN NAME CO_L3_REINCORPORACION — Path
>
> 95% `reincorporad[oa]` `reincorporaci[oó]n` `reintegrad[oa]` `reintegraci[oó]n` `desmovilizad[oa]` `desmovilizaci[oó]n` `excombatiente` `ex_?combatiente` `firmante_?(de_?)?paz` `arn` `poblaci[oó]n_?(en_?proceso_?de_?)?(reincorporaci[oó]n|reintegraci[oó]n)` `ex_?farc` `ex_?guerriller[oa]`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Excombatiente FARC-EP	→	**Sin información**

PART 11

Health data

Data concerning health is sensitive (art. 5), and the medical record is also a confidential document that can only be accessed with the patient's authorization or in the cases the law provides. The group covers what hospitals and clinics (IPS), health insurers (EPS), laboratories, occupational risk insurers (ARL) and occupational health teams keep: identifiers, affiliation, diagnoses, procedures, medicines, tests, blood group, disability, occupational, reproductive and mental health.

11.1 Health identifiers

`CO_SALUD_IDENTIFICADOR`

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Medical record, admission, visit, service authorization, prescription, sick-leave and MIPRES numbers. The medical record is identified by the patient's document number, which falls under the cédula domain.

HOW IT IS FOUND

COLUMN NAME — `CO_SALUD_IDENTIFICADOR` — Path

85%

```
n(o|ro|um|umero)_?(historia(_?cl[ií]nica)?|hc|ingreso|atenci[oó]n|autorizaci[oó]n|orden_?m[eé]dica|f[oó]rmula|incapacidad|carn[eé]_?(eps|salud)|afiliaci[oó]n_?eps|mipres|prescripci[oó]n)
historia_?cl[ií]nica
hc_?(n(o|ro|um|umero))?
autorizaci[oó]n_?(servicio|eps)
mipres
c[oó]digo_?(paciente|afiliado)
id_?paciente
n(o|ro)_?rips
```

55%

```
atenci[oó]n
ingreso
autorizaci[oó]n
episodio
```

HOW IT IS MASKED

Character by character, keeping length and format.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
HC-2024-00123	→	**TW-3389-01317**

11.2 Health system affiliation

`CO_SALUD_AFILIACION`

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The regime — contributory, subsidized, special or exception — and the health insurer (EPS). Being in the subsidized regime says the person cannot pay contributions.

HOW IT IS FOUND

COLUMN NAME — `CO_SALUD_AFILIACION` — Path

85%

```
r[eé]gimen(_?(de_?)?(salud|afiliaci[oó]n))?
tipo_?(de_?)?(regimen|afiliado|afiliaci[oó]n)
eps(_?(afiliado|actual|nombre|codigo))?
(cod|codigo|nombre|nom)_?eps
entidad_?promotora(_?(de_?)?salud)?
aseguradora_?salud
administradora_?(de_?)?salud
eapb
prepagada
medicina_?prepagada
plan_?complementario
```

VALUE FORMAT CO_SALUD_AFILIACION — Values

PATTERN	STRENGTH	NOTES
One of 37 known values, ignoring case — Contributivo, Subsidiado, Especial, De excepción, No afiliado, Nueva EPS, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A regime is replaced with another regime and an EPS with another EPS from the list; a flag stays a flag.

`CO_AFILIACION_SALUD` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_EPS`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_REGIMEN_SALUD` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `co-regimenes-salud.txt`, chosen by a keyed hash.
>
> `CO_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `CO_EPS` SECURE LOOKUP
>
> Replaces the value with one of the 18 values in `co-eps.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Subsidiado`	→	**`Contributivo`**
`Medimás EPS`	→	**`Famisanar EPS`**

11.3 Diagnosis and ICD-10

`CO_SALUD_DIAGNOSTICO`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Diagnoses in words or by ICD-10 code, with the dot (`F33.1`) or without it, as in the RIPS (`F331` , `I10X`); causes of death, sick leave and hospitalization, history and allergies.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_DIAGNOSTICO — Path

85% `diagn[oó]stico[a-z_]*` `dx(_?(principal|relacionado|ingreso|egreso)[0-9]?)?` `cie_?10` `cie(_?(10|11|principal))?` `(cod|codigo)_?(diagnostico|dx|cie)` `impresi[oó]n_?diagn[oó]stica` `enfermedad(es)?[a-z_]*` `patolog[ií]a` `comorbilidad(es)?` `antecedentes?_?(m[eé]dicos|patol[oó]gicos|familiares|personales)` `causa_?(de_?)?` `(muerte|defunci[oó]n|incapacidad|hospitalizaci[oó]n|consulta)` `motivo_?(de_?)?` `(consulta|incapacidad|hospitalizaci[oó]n)` `alergias?` `diagnos(is|es)` `icd_?(10|11)?`

VALUE FORMAT CO_SALUD_DIAGNOSTICO — Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d|X)?`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another common code in the same format, and a text a common diagnosis: an HIV or mental disorder diagnosis does not survive as a category.

`CO_DIAGNOSTICO` **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_DIAGNOSTICO_TEXTO`.

> `CO_CIE10_DECIMAL` **SECURE LOOKUP**
>
> Replaces the value with one of the 33 values in `co-cie10-decimal.txt`, chosen by a keyed hash.
>
> `CO_CIE10` **SECURE LOOKUP**
>
> Replaces the value with one of the 37 values in `co-cie10.txt`, chosen by a keyed hash.
>
> `CO_BANDERA` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_DIAGNOSTICO_TEXTO` **SECURE LOOKUP**
>
> Replaces the value with one of the 30 values in `co-diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	**K21.9**
B24X	→	**R51**

11.4 Procedures (CUPS)

CO_SALUD_PROCEDIMIENTO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Procedures, tests and surgeries, in words or by the code of the Single Classification of Health Procedures. A viral load or a voluntary termination of pregnancy reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_PROCEDIMIENTO — Path

85% `cups` `(cod|codigo)_?(cups|procedimiento|servicio_?salud)` `procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado))?` `servicio_?(de_?)?salud_?(prestado|autorizado)` `examen_?(ordenado|realizado)` `cirug[ií]a(_?realizada)?` `intervenci[oó]n_?quir[uú]rgica` `medical_?procedure`

HOW IT IS MASKED

A CUPS code is replaced with another common code; a text with a common procedure.

`CO_PROCEDIMIENTO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_PROCEDIMIENTO_TEXTO`.

> `CO_CUPS` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `co-cups.txt`, chosen by a keyed hash.
>
> `CO_PROCEDIMIENTO_TEXTO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `co-procedimientos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
906249	→	**903815**

11.5 Medicines

CO_SALUD_MEDICAMENTO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Medicines prescribed, dispensed or taken continuously, by name or by CUM code. An antiretroviral, an antipsychotic or a contraceptive reveals a diagnosis.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_MEDICAMENTO — Path

85% `medicamentos?(_?(formulado|prescrito|entregado|dispensado|nombre|uso))?` `f[aá]rmacos?` `principio_?activo` `cum` `(cod|codigo)_?(cum|medicamento)` `f[oó]rmula_?m[eé]dica` `prescripci[oó]n_?(medicamento)?` `posolog[ií]a` `tratamiento_?farmacol[oó]gico` `medications?` `drugs?_?prescribed`

VALUE FORMAT CO_SALUD_MEDICAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 48 known values, ignoring case — Acetaminofén, Ibuprofeno, Naproxeno, Diclofenaco, Metformina, Glibenclamida, …	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced with a common medicine from the list; a flag stays a flag.

`CO_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_MEDICAMENTO_LISTA` .

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_MEDICAMENTO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 24 values in `co-medicamentos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Sertralina 50 mg	→	**Ibuprofeno**

11.6 Clinical text

`CO_SALUD_TEXTO_CLINICO`

COLUMN NAME | DATA TYPE | FREE TEXT REDACTION

WHAT IT IS

Medical history, current illness, progress notes, physical examination, management plan, discharge summary and nursing notes.

HOW IT IS FOUND

> COLUMN NAME `CO_SALUD_TEXTO_CLINICO – Path`
>
> 85% `anamnesis` `evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))?` `enfermedad_?actual` `examen_?f[ií]sico` `an[aá]lisis_?(y_?)?plan` `plan_?(de_?)?manejo` `conducta(_?m[eé]dica)?` `epicrisis` `resumen_?(de_?)?(egreso|atenci[oó]n)` `nota_?(m[eé]dica|de_?enfermer[ií]a|cl[ií]nica)` `notas?_?(m[eé]dicas|cl[ií]nicas)` `triage(_?texto)?` `motivo_?consulta_?texto` `interpretaci[oó]n_?(resultado|examen)` `informe_?(patolog[ií]a|radiolog[ií]a)` `clinical_?notes?` `discharge_?summary`

> DATA TYPE `CO_SALUD_TEXTO_CLINICO – Type`
>
> Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same Free Text Redaction as free text: documents, contacts and names from the list are redacted. The clinical content stays — if it must not be in the copy, suppress the column.

`CO_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATO]`, and the 1,188 terms of `co-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Paciente Rodríguez, CC 79.456.123, consulta por cefalea.`	→	**`Paciente [NOMBRE], CC [DATO], consulta por cefalea.`**

11.7 Test results

`CO_SALUD_RESULTADO_EXAMEN`

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Laboratory and test results — HIV, viral load, blood glucose, pregnancy, drug test, blood alcohol —, also as numeric values.

HOW IT IS FOUND

COLUMN NAME `CO_SALUD_RESULTADO_EXAMEN – Path`

80% `resultado_?(del_?)?(examen|prueba|laboratorio|vih|covid|pcr|serolog[ií]a|biopsia|glicemia|citolog[ií]a|patolog[ií]a)` `(examen|prueba)_?(resultado|laboratorio)` `vih(_?(estado|resultado|prueba))?` `carga_?viral` `cd4` `glicemia` `glucosa` `hemoglobina_?glicosilada` `hba1c` `colesterol` `imc` `presi[oó]n_?arterial` `tensi[oó]n_?arterial` `prueba_?(de_?)?embarazo` `toxicol[oó]gico` `alcoholemia` `lab_?results?` `test_?results?`

50% `resultado` `prueba`

HOW IT IS MASKED

Character by character, keeping the format: a number stays a number.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Reactivo`	→	**`Quilqaju`**

11.8 Blood group and Rh

`CO_SALUD_GRUPO_SANGUINEO`

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor — printed on the cédula and asked by almost every employer.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `tipo_?(de_?)?sangre` `rh` `factor_?rh` `gs_?rh` `grupo_?rh` `hemoclasificaci[oó]n` `abo(_?rh)?` `blood_?(type|group)`

VALUE FORMAT CO_SALUD_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another group from the list.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with the Masking Engine and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

11.9 Disability

CO_SALUD_DISCAPACIDAD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Disability and its category in the Ministry of Health certification — physical, hearing, visual, deafblindness, intellectual, psychosocial, multiple — and the Registry for the Location and Characterization of Persons with Disabilities.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `(tipo|cod|codigo|categoria)_?discapacidad` `persona_?con_?discapacidad` `pcd` `condici[oó]n_?(de_?)?discapacidad` `certificado_?(de_?)?discapacidad` `rlcpd` `necesidades_?(educativas_?)?especiales` `movilidad_?reducida` `disabilit(y|ies)`

VALUE FORMAT CO_SALUD_DISCAPACIDAD — Values

PATTERN	STRENGTH	NOTES
One of 24 known values, ignoring case — Física, Auditiva, Visual, Sordoceguera, Intelectual, Psicosocial mental, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a category from the list.

`CO_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_DISCAPACIDAD_LISTA`.

> `CO_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_DISCAPACIDAD_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `co-discapacidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno del espectro autista	→	**Ninguna**

11.10 Occupational health

`CO_SALUD_OCUPACIONAL`

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The fitness result of occupational medical exams, work accident (FURAT) and occupational disease (FUREL) reports, sick leaves, the assessment of loss of working capacity and medical restrictions.

HOW IT IS FOUND

COLUMN NAME `CO_SALUD_OCUPACIONAL — Path`

85% `concepto_?(de_?)?aptitud` `aptitud_?(laboral|m[eé]dica)` `examen_?(m[eé]dico_?)?(ocupacional|de_?ingreso|de_?retiro|peri[oó]dico)` `resultado_?examen_?ocupacional` `accidente_?(de_?)?trabajo` `at_?(tipo|reporte)` `furat` `enfermedad_?laboral` `furel` `incapacidad(_?(m[eé]dica|laboral|tipo|motivo|d[ií]as))?` `d[ií]as_?(de_?)?incapacidad` `licencia_?(de_?)?(maternidad|paternidad)` `calificaci[oó]n_?(de_?)?(p[eé]rdida|origen)` `p[eé]rdida_?(de_?)?capacidad_?laboral` `pcl` `restricciones_?m[eé]dicas` `recomendaciones_?m[eé]dicas` `reintegro_?laboral`

VALUE FORMAT `CO_SALUD_OCUPACIONAL — Values`

PATTERN	STRENGTH	NOTES
One of 5 known values, ignoring case — apto, no apto, apto con restricciones, aplazado, apto con recomendaciones	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A result is replaced with another from the list — fit, unfit —; a flag stays a flag; the diagnosis of the sick leave falls under its domain.

`CO_SALUD_LABORAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SALUD_LABORAL_LISTA`.

> `CO_BANDERA` REGEX DECOMPOSE
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP
> > Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_TRUE_FALSE` SECURE LOOKUP
> > Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_YES_NO` SECURE LOOKUP
> > Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_S_N` SECURE LOOKUP
> > Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_Y_N` SECURE LOOKUP
> > Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `CO_BANDERA_0_1` SECURE LOOKUP
> > Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.
>
> `CO_CM_ALFANUM` CHARACTER MAPPING
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `CO_SALUD_LABORAL_LISTA` SECURE LOOKUP
> Replaces the value with one of the 4 values in `co-aptitud-laboral.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
No apto temporalmente	→	**Aplazado**

11.11 Sexual and reproductive health

`CO_SALUD_REPRODUCTIVA`

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, last menstrual period, prenatal care, childbirth, voluntary termination of pregnancy, family planning, fertility, sexually transmitted infections.

HOW IT IS FOUND

> COLUMN NAME `CO_SALUD_REPRODUCTIVA` — Path
>
> 90% `gestante` `embarazo` `embarazada` `gestaci[oó]n` `edad_?gestacional` `semanas_?(de_?)?gestaci[oó]n` `fum` `fecha_?[uú]ltima_?menstruaci[oó]n` `control_?prenatal` `prenatal` `parto(_?tipo)?` `ces[aá]rea` `aborto` `ive` `interrupci[oó]n_?voluntaria(_?del_?embarazo)?` `m[eé]todo_?(de_?)?planificaci[oó]n` `planificaci[oó]n_?familiar` `anticoncepci[oó]n` `anticonceptivo` `fertilidad` `infertilidad` `its` `ets` `infecci[oó]n(es)?_?(de_?)?transmisi[oó]n_?sexual` `pregnan(t|cy)` `contracepti(on|ve)`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE
Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

> `CO_BANDERA` REGEX DECOMPOSE
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
12 semanas de gestación	→	**Sin información**
S	→	**S**

11.12 Mental health

CO_SALUD_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Mental disorders, psychiatric or psychological care, suicide attempts, use of psychoactive substances.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_MENTAL — Path

90% `salud_?mental` `trastorno[a-z_]*` `psiqui[aá]tri[a-z_]*` `psicol[oó]gi[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z_]*` `intento_?(de_?)?suicidio` `autolesi[oó]n` `consumo_?(de_?)?(sustancias|spa|alcohol|drogas)` `spa` `sustancias_?psicoactivas` `adicci[oó]n(es)?` `farmacodependencia` `alcoholismo` `tabaquismo` `mental_?health`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

> Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.
>
> `CO_BANDERA_Y_N` **SECURE LOOKUP**
>
> Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
>
> `CO_BANDERA_0_1` **SECURE LOOKUP**
>
> Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`CO_SUPRIMIR` **SECURE LOOKUP**

Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Trastorno bipolar`	→	**`Sin información`**

PART 12

Financial and socioeconomic data

Financial, credit and commercial information has its own habeas data regime (Law 1266 of 2008, amended by Law 2157 of 2021), and a negative report is among the data with the heaviest consequences for a person. Colombia adds two indicators that say a lot about whoever lives in a dwelling: the **socioeconomic stratum** from 1 to 6 and the **Sisbén IV** group, which decides access to the subsidized health regime and to social programmes. Categories are replaced within their own notation; amounts are mapped into a plausible range unrelated to the real value.

12.1 Credit bureaus

CO_FIN_CREDITO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The credit score (in DataCrédito, 150 to 950), the negative report, days and level of arrears, the status of the obligation and portfolio written off or in legal collection.

HOW IT IS FOUND

COLUMN NAME CO_FIN_CREDITO — Path

90% `score(_?(cr[eé]dito|datacr[eé]dito|cifin|transunion|experian|interno))?` `puntaje_?(de_?)?cr[eé]dito` `calificaci[oó]n_?(de_?)?(riesgo|cr[eé]dito|cartera)` `centrales?_?(de_?)?riesgo` `reporte_?(negativo|centrales|datacr[eé]dito|cifin)` `reportado` `dato_?negativo` `datacr[eé]dito` `cifin` `transunion` `d[ií]as_?(de_?)?mora` `altura_?(de_?)?mora` `edad_?(de_?)?mora` `estado_?(de_?)?(cartera|obligaci[oó]n|cr[eé]dito)` `morosidad` `moroso` `cartera_?castigada` `cobro_?jur[ií]dico` `credit_?score` `credit_?rating`

HOW IT IS MASKED

A score gets other digits of the same length; a flag stays a flag; a status is replaced with another from the list.

`CO_CREDITO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ESTADO_CREDITO`.

`CO_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_ESTADO_CREDITO` SECURE LOOKUP

Replaces the value with one of the 10 values in `co-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Reportado en DataCrédito	→	**Reportado negativamente**
745	→	**471**

12.2 Debt

CO_FIN_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Loan and portfolio balances, overdue amounts, instalments, disbursed amounts and credit limits.

HOW IT IS FOUND

COLUMN NAME CO_FIN_DEUDA – Path

85% `saldo_?(deuda|cr[eé]dito|capital|obligaci[oó]n|cartera|en_?mora|adeudado)` `valor_?(de_?la_?)?(deuda|cuota|obligaci[oó]n|cr[eé]dito|pr[eé]stamo|mora|en_?mora)` `vr_?(cuota|deuda|mora|saldo)` `deuda(_?total)?` `cupo_?(de_?)?(cr[eé]dito|tarjeta)` `cupo_?aprobado` `monto_?(cr[eé]dito|pr[eé]stamo|desembolsado)` `cuota_?mensual` `loan_?(amount|balance)` `outstanding_?balance` `debt`

DATA TYPE CO_FIN_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
8500000	→	**9340619**

12.3 Income and salary

CO_FIN_INGRESOS

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Salary, monthly or household income, fees and contribution base income (IBC).

HOW IT IS FOUND

COLUMN NAME CO_FIN_INGRESOS — Path

85% `salario(_?(b[aá]sico|integral|mensual|devengado))?` `sueldo(_?(b[aá]sico|mensual))?` `ingresos?(_?(mensuales?|totales?|familiares?|laborales?|declarados?))?` `ibc` `ingreso_?base_?(de_?)?cotizaci[oó]n` `devengado` `asignaci[oó]n_?b[aá]sica` `honorarios` `remuneraci[oó]n` `vr_?(salario|ingreso)` `valor_?(salario|ingresos?)` `salary` `income` `wages?`

DATA TYPE CO_FIN_INGRESOS — Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
3200000	→	**9018715**

12.4 Assets

CO_FIN_PATRIMONIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Net worth, assets, cadastral and market valuations, account balances, term deposits and investments, severance funds.

HOW IT IS FOUND

COLUMN NAME CO_FIN_PATRIMONIO — Path

85% `patrimonio(_?(l[ií]quido|bruto))?` `activos?_?(totales?)?` `valor_?(del_?)?(inmueble|veh[ií]culo|bienes|aval[uú]o|comercial|catastral|inversi[oó]n)` `aval[uú]o(_?catastral)?` `saldo_?(cuenta|ahorros|cdt|inversi[oó]n|cesant[ií]as|pensi[oó]n_?voluntaria)` `cdt(_?valor)?` `cesant[ií]as` `net_?worth` `account_?balance`

DATA TYPE CO_FIN_PATRIMONIO — Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
185000000	→	233522319

12.5 Pension and subsidies

CO_FIN_PENSION

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

The amount of the monthly pension, subsidies and allowances, and child support.

HOW IT IS FOUND

COLUMN NAME CO_FIN_PENSION — Path

90% `mesada(_?pensional)?` `valor_?(de_?la_?)?(pensi[oó]n|mesada|subsidio|auxilio|beneficio)` `pensi[oó]n_?(valor|mensual|monto)` `vr_?(pension|subsidio)` `cuota_?alimentaria` `pension_?amount`

DATA TYPE CO_FIN_PENSION — Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
2400000	→	7834212

12.6 Socioeconomic stratum

CO_FIN_ESTRATO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The stratum from 1 to 6 that classifies a dwelling for utility tariffs (Law 142 of 1994). It says, roughly, how much whoever lives there earns, and in which part of town.

HOW IT IS FOUND

COLUMN NAME CO_FIN_ESTRATO — Path

90% `estrato(_?(socioecon[oó]mico|vivienda|residencia))?` `estr` `nivel_?socioecon[oó]mico` `stratum`

VALUE FORMAT CO_FIN_ESTRATO — Values

PATTERN	STRENGTH	NOTES
One of 12 known values, ignoring case — 1, 2, 3, 4, 5, 6, …	40%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within its band — low (1–2), middle (3–4), high (5–6) —, so analysis by band keeps its shape. `Estrato 4` stays written the same way.

`CO_ESTRATO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

> `CO_ESTRATO_BAJO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-estrato-bajo.txt`, chosen by a keyed hash.
>
> `CO_ESTRATO_MEDIO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-estrato-medio.txt`, chosen by a keyed hash.
>
> `CO_ESTRATO_ALTO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `co-estrato-alto.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
2	→	**2**
Estrato 5	→	**Estrato 5**

12.7 Sisbén

CO_FIN_SISBEN

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The Sisbén IV group — A1–A5 extreme poverty, B1–B7 moderate poverty, C1–C18 vulnerable, D1–D21 neither poor nor vulnerable —, which decides access to the subsidized regime and to social programmes, and the Sisbén III score.

HOW IT IS FOUND

> COLUMN NAME CO_FIN_SISBEN – Path
>
> 95% `sisb[eé]n(_?(iv|4|iii|grupo|puntaje|clasificaci[oó]n|nivel|categor[ií]a))?` `grupo_?sisb[eé]n` `puntaje_?sisb[eé]n` `clasificaci[oó]n_?sisb[eé]n` `nivel_?sisb[eé]n` `ficha_?sisb[eé]n`

> VALUE FORMAT CO_FIN_SISBEN – Regex
>
PATTERN	STRENGTH	NOTES
`[A-D]\s?\d{1,2}`	50%	
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The group letter stays and the subgroup is replaced with another of the same group; a score is mapped digit by digit.

`CO_SISBEN` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_SISBEN_GRUPO`.

> `CO_SISBEN_A` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `co-sisben-a.txt`, chosen by a keyed hash.
>
> `CO_SISBEN_B` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `co-sisben-b.txt`, chosen by a keyed hash.
>
> `CO_SISBEN_C` SECURE LOOKUP
>
> Replaces the value with one of the 18 values in `co-sisben-c.txt`, chosen by a keyed hash.

`CO_SISBEN_D` SECURE LOOKUP

Replaces the value with one of the 21 values in `co-sisben-d.txt`, chosen by a keyed hash.

`CO_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`CO_SISBEN_GRUPO` SECURE LOOKUP

Replaces the value with one of the 4 values in `co-sisben-grupos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
A3	→	**A3**
C15	→	**C17**

12.8 Social programmes

CO_FIN_PROGRAMA_SOCIAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Taking part in social programmes — Renta Ciudadana, Renta Joven, Colombia Mayor, VAT refund — and in housing and unemployment subsidies, often as a flag.

HOW IT IS FOUND

COLUMN NAME CO_FIN_PROGRAMA_SOCIAL – Path

90% `programa_?(social|beneficiario|de_?gobierno|prosperidad)` `beneficiario_?(programa|subsidio|renta|familias|colombia_?mayor)` `renta_?(ciudadana|joven|b[aá]sica)` `familias_?en_?acci[oó]n` `j[oó]venes_?en_?acci[oó]n` `colombia_?mayor` `ingreso_?solidario` `devoluci[oó]n_?(del_?)?iva` `subsidio(_?(familiar|vivienda|desempleo|tipo))?` `mi_?casa_?ya` `transferencia_?monetaria` `social_?programme`

VALUE FORMAT CO_FIN_PROGRAMA_SOCIAL – Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — Renta Ciudadana, Renta Joven, Colombia Mayor, Devolución del IVA, Mi Casa Ya, Subsidio familiar de vivienda, …	80%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a programme from the list.

`CO_PROGRAMA_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PROGRAMA_SOCIAL_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_PROGRAMA_SOCIAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `co-programas-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Familias en Acción	→	**Mi Casa Ya**

12.9 Housing tenure

`CO_FIN_VIVIENDA`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Tenure of the dwelling — owned outright or being paid, rented, usufruct, possession without title, collective property.

HOW IT IS FOUND

COLUMN NAME `CO_FIN_VIVIENDA` – Path

90% `tenencia_?(de_?)?(la_?)?vivienda` `tipo_?(de_?)?tenencia` `vivienda_?(propia|arrendada|tipo_?tenencia)` `condici[oó]n_?(de_?)?(la_?)?vivienda` `ocupaci[oó]n_?vivienda` `housing_?tenure`

VALUE FORMAT `CO_FIN_VIVIENDA` – Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Propia totalmente pagada, Propia la están pagando, En arriendo o subarriendo, En usufructo, Posesión sin título, Propiedad colectiva, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced with another tenure from the list.

`CO_TENENCIA_VIVIENDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_TENENCIA_VIVIENDA_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

> `CO_BANDERA_Y_N` **SECURE LOOKUP**
>
> Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.
>
> `CO_BANDERA_0_1` **SECURE LOOKUP**
>
> Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`CO_TENENCIA_VIVIENDA_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 7 values in `co-tenencia-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Invasión	→	**Posesión sin título**

PART 13

Criminal records and proceedings

Not on the list of article 5, but for the Constitutional Court criminal records are *the negative data par excellence* (SU-458 of 2012): their circulation must be restricted to those with a legitimate interest. They get the same care as sensitive data.

13.1 Records

CO_PENAL_ANTECEDENTES

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Judicial records of the Police, disciplinary records of the Procuraduría and fiscal records of the Contraloría, the National Registry of Corrective Measures, type of crime, legal situation, pre-trial detention, being an INPEC inmate and arrest warrants.

HOW IT IS FOUND

COLUMN NAME CO_PENAL_ANTECEDENTES — Path

95% `antecedentes?(_?(judiciales|penales|disciplinarios|fiscales))?` `certificado_?(de_?)?antecedentes` `medidas_?correctivas` `rnmc` `registro_?nacional_?(de_?)?medidas_?correctivas` `condena(_?(penal|tipo))?` `delito(_?(tipo|cometido))?` `tipo_?(de_?)?delito` `conducta_?punible` `situaci[oó]n_?jur[ií]dica` `medida_?(de_?)?aseguramiento` `detenci[oó]n_?domiciliaria` `privad[oa]_?(de_?)?(la_?)?libertad` `recluso` `interno_?inpec` `td_?inpec` `reincidente` `orden_?(de_?)?captura` `inhabilidad(es)?` `sanciones_?disciplinarias` `criminal_?record`

55% `estado_?(del_?)?proceso` `sentido_?(del_?)?fallo` `fallo`

HOW IT IS MASKED

Replaced with a generic status from the list — nothing pending, convicted, acquitted —, whatever the outcome; a flag stays a flag.

`CO_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ANTECEDENTES_LISTA`.

`CO_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

`CO_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`CO_ANTECEDENTES_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 8 values in `co-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Condenado por hurto en 2019`	→	**`No tiene asuntos pendientes con las autoridades judiciales`**

13.2 Case file number

`CO_PENAL_RADICADO`

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The file number of a Judiciary proceeding — 23 digits: DIVIPOLA code, court corporation, specialty, office, year, consecutive and appeal, `11001310300120200012300` — and SPOA criminal complaint numbers. Proceedings can be looked up online and lead to the parties.

HOW IT IS FOUND

COLUMN NAME `CO_PENAL_RADICADO — Path`

90% `n(o|ro|um|umero)_?(de_?)?(radicado|radicaci[oó]n|proceso|expediente|noticia_?criminal|spoa|cui|denuncia|tutela|acci[oó]n_?de_?tutela)(_?(judicial|penal))?` `radicado_?(judicial|proceso|penal|tutela)?` `radicaci[oó]n_?proceso` `c[oó]digo_?[uú]nico_?(de_?)?` `investigaci[oó]n` `cui` `spoa` `noticia_?criminal`

50% `proceso` `expediente`

VALUE FORMAT `CO_PENAL_RADICADO — Regex`

PATTERN	STRENGTH	NOTES
`0*(?:\d{23})`	80%	
`0*(?:\d{21})`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The consecutive is mapped digit by digit; city, corporation, specialty, office, year and appeal stay. Other numbers are masked character by character.

`CO_RADICADO` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

`CO_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

`CO_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`11001310300120200012300`	→	**`11001310300120200095700`**

14

The NIT check digit

The Check Digit algorithm of the Masking Engine computes a modulus 11 digit as *eleven minus the remainder* and writes 10 as 0. For the NIT that is right for ten of the eleven possible remainders: when the remainder is 1, the DIAN writes 1 and Check Digit would write 0. One masked NIT in eleven would be invalid.

The set solves it in two steps, without tables:

- A Check Digit with **doubled weights** maps the body and writes an auxiliary digit where the check digit goes. Since $2 \times 1 \equiv 2$ modulus 11, the auxiliary digit is 9 exactly when the remainder of the masked body with the true weights is 1.
- A Regex Decompose turns a final 9 into 1, and otherwise applies a Check Digit with the true weights over the body, which it leaves as it is, and recomputes the digit.

Check Digit needs as many weights as digits, so there is one pair of steps per body length, from 6 to 10 digits, and a Regex Decompose that picks by the shape of the value, with or without dots and hyphen. The body is mapped with the same Character Mapping as the cédula: a natural person's NIT still matches their masked cédula.

15

Where people live: municipalities, veredas and postal code

With DANE's municipal population projection for 2026 (based on the 2018 census, post COVID-19 update) and the location of each seat in DIVIPOLA, the set knows the size, department and position of 1,122 municipalities and non-municipalized areas.

- A **municipality** with fewer than 20,000 inhabitants becomes the nearest municipality of the same department with at least 20,000. There are 694 of them, with 6.4 million inhabitants — 12% of the population. Jardín (Antioquia) becomes Andes; Providencia, San Andrés; the non-municipalized areas of Guainía, Inírida.
- The **department** stays. Every one has at least one municipality of 20,000 inhabitants.
- Distance is measured between the coordinates of the seats, in a straight line.
- Some names repeat — four La Unión, four Villanueva, four Buenavista — and others differ only in an accent. A name on its own is generalized only when every municipality bearing it is small, and then it follows the largest of them. With the department (`La Unión – Sucre` , `La Unión (Sucre)` , `La Unión, Sucre`) there is no ambiguity, and the municipality is always generalized.
- The **DIVIPOLA code** follows the same table, and a person's name and code still agree.
- Names are also recognized as people write them: `Cartagena` , `Cúcuta` , `Mompox` , `Bogotá` .
- The **vereda** and the **corregimiento** become `Zona rural` , and the **postal code** keeps only the department.

Municipality names that are also given names or surnames, and department names, are left out of the detection list, so that a column of surnames is not taken for municipalities.

16

Limits

- **Binary columns** — cédula photos, biometric validation selfies, fingerprints, medical record PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A NIT whose body has 5 digits or fewer, or more than 10,** is masked digit by digit, without recomputing the digit. A NIT with neither hyphen nor dots is read as body and digit: `8001972684` is `800197268–4`.
- **A check digit in a column of its own** is not recomputed: it is masked and no longer matches the masked NIT.
- **The department, the bank code and the phone prefix stay.**
- **Data Cleansing lets through what it does not know**: a municipality written in a way the table does not have — abbreviated, misspelled — passes unchanged.
- **Free text** is redacted word by word: a mobile written with spaces is not found, and a name that is also a common word (`Luz` , `Rosa` , `León`) is redacted wherever it appears.
- **Children and adolescents** — a birth date moves at most 60 days, so few people cross their 14th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, neighbourhood, municipality and postal code in separate columns are masked independently and no longer form a coherent address.
- **The engine key** links masked values back to production for whoever holds both: in that case the result is pseudonymized data, still personal data. Keep the key away from the users of the copy.

17

Verification

Before publication, the set was checked outside a Masking Engine:

- The check-digit rule was checked against the DIAN's own NIT, `800.197.268–4`.
- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 151 columns with the whole set at its assignment threshold — well named, badly named and 31 columns that are not personal data — and again with only the classifiers of the essential pack.
- The table that generalizes municipalities was audited for all 1,122 DIVIPOLA units: by name, by name with the department and by code.
- The algorithms, run with the Delphix algorithm plugin, masked each domain's sample values and placeholders such as `N/A`, checking every output against its vocabulary; 200 NITs of every length — remainder 1 included — for validity and collisions; 150 cédulas for collisions; and 20 people whose cédula and NIT must still agree. Every algorithm also masked its own sample value.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

18

Sources

- Statutory Law 1581 of 2012 (Senate Secretariat, text in force). Constitutional Court, judgments C-748 of 2011 and SU-458 of 2012. Decree 1377 of 2013, compiled in Decree 1074 of 2015. Political Constitution, arts. 15 and 153.

- Superintendencia de Industria y Comercio: security incident reporting in the National Database Registry; reform of Law 1581 (bills 214 and 274 of 2025, House of Representatives).
- Law 1266 of 2008 and Law 2157 of 2021 (financial habeas data). Law 1273 of 2009 (art. 269F). Law 1448 of 2011 (victims). Law 142 of 1994 (stratification). Decree 1469 of 2025 (2026 minimum wage).
- Archivo General de la Nación, Guide to the Anonymization of Structured Data (2020). DANE, Data anonymization guide (2024).
- DANE: municipal population projections 2020–2035 (post COVID-19 update); DIVIPOLA (datos.gov.co); 2018 census, ethnic self-recognition and indigenous peoples.
- National Electoral Council: political organizations with legal personality (16 September 2026). DIAN: NIT check digit. Banco de la República: Bre-B keys. National Planning Department: Sisbén IV. Communications Regulation Commission: numbering plan. Judiciary: case file numbering.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

CO_AFILIACION_SALUD REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_EPS`.

Used by: `CO_SALUD_AFILIACION`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(?i)(contributivo|subsidiado|especial|de\s+excepci[oó]n|excepci[oó]n|no\s+afiliado)`	`CO_REGIMEN_SALUD`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_DIGITOS`
otherwise	`CO_EPS`

CONFIGURATION

trimInput	yes
requireMask	no

CO_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L2_ANIO_NACIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `CO_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ANTECEDENTES_LISTA`.

Used by: `CO_PENAL_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_ANTECEDENTES_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-antecedentes.txt`, chosen by a keyed hash.

Used by: `CO_ANTECEDENTES`

CONFIGURATION

lookupFile	`co-antecedentes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_APELLIDO NAME

Replaces the name with one of the 255 names in `co-apellidos.txt`.

Used by: `CO_PALABRA_APELLIDO`

CONFIGURATION

lookupFile	`co-apellidos.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

CO_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_APELLIDO`, `CO_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)`	`CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CO_CATEGORIA_SUPRIMIDA`, `CO_ESTADO_CIVIL`, `CO_ESCOLARIDAD`, `CO_GRUPO_ETNICO`, `CO_PUEBLO_INDIGENA`, `CO_LENGUA`, `CO_RELIGION`, `CO_ORIENTACION_POLITICA`, `CO_PARTIDO`, `CO_ORIENTACION_SEXUAL`, `CO_IDENTIDAD_GENERO`, `CO_VICTIMA`, `CO_AFILIACION_SALUD`, `CO_DIAGNOSTICO`, `CO_MEDICAMENTO`, `CO_DISCAPACIDAD`, `CO_SALUD_LABORAL`, `CO_CREDITO`, `CO_PROGRAMA_SOCIAL`, `CO_TENENCIA_VIVIENDA`, `CO_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no)`	`CO_BANDERA_SI_NO`
`(?i)(true|false)`	`CO_BANDERA_TRUE_FALSE`
`(?i)(yes)`	`CO_BANDERA_YES_NO`
`(?i)([sn])`	`CO_BANDERA_S_N`

`(?i)([yx])`	`CO_BANDERA_Y_N`
`([01])`	`CO_BANDERA_0_1`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

`CO_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

`lookupFile`	`co-bandera-0-1.txt`
`hashMethod`	`SHA256`
`maskedValueCase`	`PRESERVE_INPUT`
`inputCaseSensitive`	no
`trimWhitespaceFromInput`	yes
`trimWhitespaceInLookupFile`	yes

`CO_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

`lookupFile`	`co-bandera-s-n.txt`
`hashMethod`	`SHA256`
`maskedValueCase`	`PRESERVE_INPUT`
`inputCaseSensitive`	no
`trimWhitespaceFromInput`	yes
`trimWhitespaceInLookupFile`	yes

`CO_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

`lookupFile`	`co-bandera-si-no.txt`
`hashMethod`	`SHA256`
`maskedValueCase`	`PRESERVE_INPUT`
`inputCaseSensitive`	no
`trimWhitespaceFromInput`	yes
`trimWhitespaceInLookupFile`	yes

`CO_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	`co-bandera-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`CO_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	`co-bandera-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`CO_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	`co-bandera-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`CO_BARRIO` SECURE LOOKUP

Replaces the value with one of the 35 values in `co-barrios.txt`, chosen by a keyed hash.

Used by: `CO_L2_BARRIO`

CONFIGURATION

lookupFile	`co-barrios.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`CO_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

Used by: `CO_L3_CONVICCION_FILOSOFICA`, `CO_L3_SINDICATO`, `CO_L3_ORGANIZACION_SOCIAL`, `CO_L3_VIDA_SEXUAL`, `CO_L3_REINCORPORACION`, `CO_SALUD_REPRODUCTIVA`, `CO_SALUD_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))))`	keep · keep · keep · keep · keep · keep · keep · `CO_CM_ALFANUM`
otherwise	`CO_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

CO_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `co-cie10.txt`, chosen by a keyed hash.

Used by: `CO_DIAGNOSTICO`

CONFIGURATION

lookupFile	`co-cie10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `co-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `CO_DIAGNOSTICO`

CONFIGURATION

lookupFile	`co-cie10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `CO_L1_DOCUMENTO_EXTRANJERO`, `CO_L1_PASAPORTE`, `CO_L1_REGISTRO_CIVIL`, `CO_L1_TARJETA_PROFESIONAL`, `CO_L1_DIRECCION_COMPLEMENTO`, `CO_L1_VEHICULO`, `CO_L1_CONTRATO`, `CO_L1_USUARIO`, `CO_SALUD_IDENTIFICADOR`, `CO_SALUD_RESULTADO_EXAMEN`, `CO_CATEGORIA_SUPRIMIDA`, `CO_DOCUMENTO`, `CO_NOMBRES`, `CO_APELLIDOS`, `CO_NOMBRE_COMPLETO`, `CO_EMAIL`, `CO_LLAVE_BREB`, `CO_PLACA`, `CO_LENGUA`, `CO_RELIGION`, `CO_ORIENTACION_POLITICA`, `CO_PARTIDO`, `CO_ORIENTACION_SEXUAL`, `CO_IDENTIDAD_GENERO`, `CO_VICTIMA`, `CO_MEDICAMENTO`, `CO_DISCAPACIDAD`, `CO_SALUD_LABORAL`, `CO_PROGRAMA_SOCIAL`, `CO_TENENCIA_VIVIENDA`, `CO_ANTECEDENTES`, `CO_RADICADO`

CONFIGURATION

characterGroups	`0123456789` `AEIOU` `BCDFGHJKLMNPQRSTVWXYZ` `aeiou` `bcdfghjklmnpqrstvwxyz` `ÁÉÍÓÚÜ` `áéíóúü`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `CO_L1_CUENTA_BANCARIA`, `CO_NIT`, `CO_DOCUMENTO`, `CO_TELEFONO`, `CO_LLAVE_BREB`, `CO_PLACA`, `CO_INMUEBLE`, `CO_COORDENADA`, `CO_ANIO`, `CO_EDAD`, `CO_OCUPACION_O_CIUO`, `CO_AFILIACION_SALUD`, `CO_CREDITO`, `CO_SISBEN`, `CO_RADICADO`

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CO_CM_DIGITOS_ANCHO_FIJO CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `CO_NIT_6_AUX`, `CO_NIT_7_AUX`, `CO_NIT_8_AUX`, `CO_NIT_9_AUX`, `CO_NIT_10_AUX`

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`

CO_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: `CO_PLACA`

CONFIGURATION

characterGroups	`0123456789` `ABCDEFGHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CO_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `CO_L1_DISPOSITIVO`, `CO_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

CO_CODIGO_MUNICIPIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L2_CODIGO_MUNICIPIO`

PATTERNS, TRIED IN ORDER

`(0*)([1-9]\d*)`	keep · `CO_CODIGO_MUNICIPIO_TABLA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_CODIGO_MUNICIPIO_TABLA DATA CLEANSING

Replaces each value found in `co-codigos-municipio-generalizados.txt` (767 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CO_CODIGO_MUNICIPIO`

CONFIGURATION

lookupFile	`co-codigos-municipio-generalizados.txt`
delimiter	`,`
caseSensitive	yes
trimWhitespace	yes

CO_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L2_CODIGO_POSTAL`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2})(\d{4}))`	keep · keep · replace with `0000`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L2_PERSONAS_A_CARGO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)`	keep · `CO_CM_DIGITOS` · keep · keep · `CO_CM_DIGITOS`
`(-?\d{1,3}[.,]\d)(\d+)`	keep · `CO_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_CREDITO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ESTADO_CREDITO`.

Used by: `CO_FIN_CREDITO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,4}))`	keep · `CO_CM_DIGITOS`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
otherwise	`CO_ESTADO_CREDITO`

CONFIGURATION

trimInput	yes
requireMask	no

CO_CUPS SECURE LOOKUP

Replaces the value with one of the 10 values in `co-cups.txt`, chosen by a keyed hash.

Used by: `CO_PROCEDIMIENTO`

CONFIGURATION

lookupFile	`co-cups.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_DIAGNOSTICO_TEXTO`.

Used by: `CO_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`CO_CIE10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3}X?)`	`CO_CIE10`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
otherwise	`CO_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

CO_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `co-diagnosticos.txt`, chosen by a keyed hash.

Used by: `CO_DIAGNOSTICO`

CONFIGURATION

lookupFile	`co-diagnosticos.txt`

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in co-direcciones.txt, chosen by a keyed hash.

Used by: CO_L1_DIRECCION

CONFIGURATION

lookupFile	co-direcciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_DISCAPACIDAD_LISTA.

Used by: CO_SALUD_DISCAPACIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	CO_BANDERA
(0*?)(?:(\d{1,6}))	keep · CO_CM_ALFANUM
otherwise	CO_DISCAPACIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in co-discapacidades.txt, chosen by a keyed hash.

Used by: CO_DISCAPACIDAD

CONFIGURATION

lookupFile	co-discapacidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DOCUMENTO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM.

Used by: CO_L1_CEDULA

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3}(?:\.\d{3})+|\d{3,11}))`	keep · `CO_CM_DIGITOS`
`(0*?)(?:(\d{3}\.?\d{3}\s?-\s?\d))`	keep · `CO_NIT_6`
`(0*?)(?:(\d{1}\.?\d{3}\.?\d{3}\s?-\s?\d))`	keep · `CO_NIT_7`
`(0*?)(?:(\d{2}\.?\d{3}\.?\d{3}\s?-\s?\d))`	keep · `CO_NIT_8`
`(0*?)(?:(\d{3}\.?\d{3}\.?\d{3}\s?-\s?\d))`	keep · `CO_NIT_9`
`(0*?)(?:(\d{1}\.?\d{3}\.?\d{3}\.?\d{3}\s?-\s?\d))`	keep · `CO_NIT_10`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

`CO_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L2_EDAD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`
`(0*?)(?:([1-9])(\d)([.,]\d+))`	keep · keep · `CO_CM_DIGITOS` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `CO_CM_DIGITOS`
`(0*?)(?:(\d))`	keep · `CO_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

`CO_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_EMAIL`, `CO_LLAVE_BREB`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24}(?:\.[A-Za-z]{2})?)`	`CO_CM_ALFANUM` · `CO_CM_ALFANUM` · replace with `test`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

`CO_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 24 values in `co-empleadores.txt`, chosen by a keyed hash.

Used by: `CO_L2_EMPLEADOR`

CONFIGURATION

lookupFile	`co-empleadores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_EPS SECURE LOOKUP

Replaces the value with one of the 18 values in `co-eps.txt`, chosen by a keyed hash.

Used by: `CO_AFILIACION_SALUD`

CONFIGURATION

lookupFile	`co-eps.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESCOLARIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ESCOLARIDAD_LISTA`.

Used by: `CO_L2_ESCOLARIDAD`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CO_ESCOLARIDAD_CODIGO`
otherwise	`CO_ESCOLARIDAD_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_ESCOLARIDAD_CODIGO SECURE LOOKUP

Replaces the value with one of the 11 values in `co-escolaridad-codigos.txt`, chosen by a keyed hash.

Used by: `CO_ESCOLARIDAD`

CONFIGURATION

lookupFile	`co-escolaridad-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESCOLARIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `co-escolaridad.txt`, chosen by a keyed hash.

Used by: `CO_ESCOLARIDAD`

CONFIGURATION

lookupFile	`co-escolaridad.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_ESTADO_CIVIL_LISTA.

Used by: CO_L2_ESTADO_CIVIL

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	CO_BANDERA
(0*)([1-9]\d{0,5}|0)	keep · CO_ESTADO_CIVIL_CODIGO
otherwise	CO_ESTADO_CIVIL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in co-estado-civil-codigos.txt, chosen by a keyed hash.

Used by: CO_ESTADO_CIVIL

CONFIGURATION

lookupFile	co-estado-civil-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in co-estado-civil.txt, chosen by a keyed hash.

Used by: CO_ESTADO_CIVIL

CONFIGURATION

lookupFile	co-estado-civil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in co-estados-credito.txt, chosen by a keyed hash.

Used by: CO_CREDITO

CONFIGURATION

lookupFile	co-estados-credito.txt

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTRATO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CO_FIN_ESTRATO

PATTERNS, TRIED IN ORDER

(?i)(estrato\s*)?([12])	keep · CO_ESTRATO_BAJO
(?i)(estrato\s*)?([34])	keep · CO_ESTRATO_MEDIO
(?i)(estrato\s*)?([56])	keep · CO_ESTRATO_ALTO
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_ESTRATO_ALTO SECURE LOOKUP

Replaces the value with one of the 2 values in co-estrato-alto.txt, chosen by a keyed hash.

Used by: CO_ESTRATO

CONFIGURATION

lookupFile	co-estrato-alto.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTRATO_BAJO SECURE LOOKUP

Replaces the value with one of the 2 values in co-estrato-bajo.txt, chosen by a keyed hash.

Used by: CO_ESTRATO

CONFIGURATION

lookupFile	co-estrato-bajo.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTRATO_MEDIO SECURE LOOKUP

Replaces the value with one of the 2 values in co-estrato-medio.txt, chosen by a keyed hash.

Used by: CO_ESTRATO

CONFIGURATION

lookupFile	`co-estrato-medio.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `CO_L2_FECHA_EVENTO`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

CO_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `CO_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

CO_GRUPO_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_GRUPO_ETNICO_LISTA`.

Used by: `CO_L3_GRUPO_ETNICO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CO_GRUPO_ETNICO_CODIGO`
otherwise	`CO_GRUPO_ETNICO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_GRUPO_ETNICO_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `co-grupos-etnicos-codigos.txt`, chosen by a keyed hash.

Used by: `CO_GRUPO_ETNICO`

CONFIGURATION

lookupFile	`co-grupos-etnicos-codigos.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_GRUPO_ETNICO_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in co-grupos-etnicos.txt, chosen by a keyed hash.

Used by: CO_GRUPO_ETNICO

CONFIGURATION

lookupFile	co-grupos-etnicos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CO_NIT_6_DV, CO_NIT_7_DV, CO_NIT_8_DV, CO_NIT_9_DV, CO_NIT_10_DV

PATTERNS, TRIED IN ORDER

(.*)	keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_IDENTIDAD_GENERO_LISTA.

Used by: CO_L3_IDENTIDAD_GENERO

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	CO_BANDERA
(0*?)(?:(\d{1,6}))	keep · CO_CM_ALFANUM
otherwise	CO_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in co-identidades-genero.txt, chosen by a keyed hash.

Used by: CO_IDENTIDAD_GENERO

CONFIGURATION

lookupFile	co-identidades-genero.txt

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_INMUEBLE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_CM_DIGITOS .

Used by: CO_L1_INMUEBLE

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d{2,3}[A-Za-z]?)([\s\-]+)(\d{3,9}))	keep · keep · keep · CO_CM_DIGITOS
(0*?)(?:(\d{5})(\d{25}))	keep · keep · CO_CM_DIGITOS
otherwise	CO_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

CO_INSTITUCION_EDUCATIVA SECURE LOOKUP

Replaces the value with one of the 12 values in co-instituciones-educativas.txt , chosen by a keyed hash.

Used by: CO_L2_INSTITUCION_EDUCATIVA

CONFIGURATION

lookupFile	co-instituciones-educativas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_HEX .

Used by: CO_L1_IP

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))	keep · CO_OCTETO · CO_OCTETO · CO_OCTETO · CO_OCTETO
otherwise	CO_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

CO_LENGUA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_LENGUA_LISTA .

Used by: CO_L3_LENGUA_NATIVA

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_LENGUA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_LENGUA_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `co-lenguas.txt`, chosen by a keyed hash.

Used by: `CO_LENGUA`

CONFIGURATION

lookupFile	`co-lenguas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_LLAVE_BREB REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_LLAVE_BREB`

PATTERNS, TRIED IN ORDER

`([^@\s]+@[^@\s]+)`	`CO_EMAIL`
`(@)(\S+)`	keep · `CO_CM_ALFANUM`
`(0*?)(?:(3\d{9}))`	keep · `CO_TELEFONO`
`(0*?)(?:(\d{3,11}))`	keep · `CO_CM_DIGITOS`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CO_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_MEDICAMENTO_LISTA`.

Used by: `CO_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 24 values in `co-medicamentos.txt`, chosen by a keyed hash.

Used by: `CO_MEDICAMENTO`

CONFIGURATION

lookupFile	`co-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_MUNICIPIO DATA CLEANSING

Replaces each value found in `co-municipios-generalizados.txt` (12,622 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CO_L2_MUNICIPIO`

CONFIGURATION

lookupFile	`co-municipios-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

CO_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 16 values in `co-nacionalidades.txt`, chosen by a keyed hash.

Used by: `CO_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	`co-nacionalidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_NIT REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.

Used by: `CO_L1_NIT`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3}\.?\d{3}\s?-?\s?\d))`	keep · `CO_NIT_6`
`(0*?)(?:(\d{1}\.?\d{3}\.?\d{3}\s?-?\s?\d))`	keep · `CO_NIT_7`
`(0*?)(?:(\d{2}\.?\d{3}\.?\d{3}\s?-?\s?\d))`	keep · `CO_NIT_8`
`(0*?)(?:(\d{3}\.?\d{3}\.?\d{3}\s?-?\s?\d))`	keep · `CO_NIT_9`
`(0*?)(?:(\d{1}\.?\d{3}\.?\d{3}\.?\d{3}\s?-?\s?\d))`	keep · `CO_NIT_10`
otherwise	`CO_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_10 STRING ALGORITHM CHAIN

Applies `CO_NIT_10_AUX` → `CO_NIT_10_AJUSTE`, in this order.

Used by: `CO_NIT`, `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	`CO_NIT_10_AUX`
algorithmReferences[2]	`CO_NIT_10_AJUSTE`

CO_NIT_10_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_10_DV`.

Used by: `CO_NIT_10`

PATTERNS, TRIED IN ORDER

`(.*)(9)`	keep · replace with `1`
otherwise	`CO_NIT_10_DV`

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_10_AUX CHECK DIGIT

Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74 82 86` from the right.

Used by: `CO_NIT_10`

CONFIGURATION

weightList	`6 14 26 34 38 46 58 74 82 86`
modulusNumber	`11`
checkDigitIndex	`10`
numDigitsForCheckdigitCalculation	`10`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_10_DV CHECK DIGIT

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41 43` from the right.

Used by: `CO_NIT_10_AJUSTE`

CONFIGURATION

weightList	`3 7 13 17 19 23 29 37 41 43`
modulusNumber	`11`
checkDigitIndex	`10`
numDigitsForCheckdigitCalculation	`10`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_IDENTIDAD`
alphaNumericAlgorithm	`CO_IDENTIDAD`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_6 STRING ALGORITHM CHAIN

Applies `CO_NIT_6_AUX` → `CO_NIT_6_AJUSTE`, in this order.

Used by: `CO_NIT`, `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	`CO_NIT_6_AUX`
algorithmReferences[2]	`CO_NIT_6_AJUSTE`

CO_NIT_6_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_6_DV`.

Used by: `CO_NIT_6`

PATTERNS, TRIED IN ORDER

`(.*)(9)`	keep · replace with `1`
otherwise	`CO_NIT_6_DV`

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_6_AUX CHECK DIGIT

Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46` from the right.

Used by: `CO_NIT_6`

CONFIGURATION

weightList	`6 14 26 34 38 46`
modulusNumber	`11`
checkDigitIndex	`6`
numDigitsForCheckdigitCalculation	`6`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`

preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_6_DV CHECK DIGIT

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23` from the right.

Used by: `CO_NIT_6_AJUSTE`

CONFIGURATION

weightList	`3` `7` `13` `17` `19` `23`
modulusNumber	`11`
checkDigitIndex	`6`
numDigitsForCheckdigitCalculation	`6`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_IDENTIDAD`
alphaNumericAlgorithm	`CO_IDENTIDAD`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_7 STRING ALGORITHM CHAIN

Applies `CO_NIT_7_AUX` → `CO_NIT_7_AJUSTE`, in this order.

Used by: `CO_NIT`, `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	`CO_NIT_7_AUX`
algorithmReferences[2]	`CO_NIT_7_AJUSTE`

CO_NIT_7_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_7_DV`.

Used by: `CO_NIT_7`

PATTERNS, TRIED IN ORDER

`(.*)(9)`	keep · replace with `1`
otherwise	`CO_NIT_7_DV`

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_7_AUX CHECK DIGIT

Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58` from the right.

Used by: `CO_NIT_7`

CONFIGURATION

weightList	`6 14 26 34 38 46 58`
modulusNumber	`11`
checkDigitIndex	`7`
numDigitsForCheckdigitCalculation	`7`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_7_DV CHECK DIGIT

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29` from the right.

Used by: `CO_NIT_7_AJUSTE`

CONFIGURATION

weightList	`3 7 13 17 19 23 29`
modulusNumber	`11`
checkDigitIndex	`7`
numDigitsForCheckdigitCalculation	`7`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_IDENTIDAD`
alphaNumericAlgorithm	`CO_IDENTIDAD`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_8 STRING ALGORITHM CHAIN

Applies `CO_NIT_8_AUX` → `CO_NIT_8_AJUSTE`, in this order.

Used by: `CO_NIT`, `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	`CO_NIT_8_AUX`
algorithmReferences[2]	`CO_NIT_8_AJUSTE`

CO_NIT_8_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_8_DV`.

Used by: `CO_NIT_8`

PATTERNS, TRIED IN ORDER

`(.*)(9)`	keep · replace with `1`
otherwise	`CO_NIT_8_DV`

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_8_AUX CHECK DIGIT

Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74` from the right.

Used by: `CO_NIT_8`

CONFIGURATION

weightList	`6` `14` `26` `34` `38` `46` `58` `74`
modulusNumber	`11`
checkDigitIndex	`8`
numDigitsForCheckdigitCalculation	`8`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NIT_8_DV CHECK DIGIT

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37` from the right.

Used by: `CO_NIT_8_AJUSTE`

CONFIGURATION

weightList	`3` `7` `13` `17` `19` `23` `29` `37`
modulusNumber	`11`
checkDigitIndex	`8`
numDigitsForCheckdigitCalculation	`8`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_IDENTIDAD`
alphaNumericAlgorithm	`CO_IDENTIDAD`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`

inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

`CO_NIT_9` STRING ALGORITHM CHAIN

Applies `CO_NIT_9_AUX` → `CO_NIT_9_AJUSTE`, in this order.

Used by: `CO_NIT`, `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	`CO_NIT_9_AUX`
algorithmReferences[2]	`CO_NIT_9_AJUSTE`

`CO_NIT_9_AJUSTE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_9_DV`.

Used by: `CO_NIT_9`

PATTERNS, TRIED IN ORDER

`(.*)(9)`	keep · replace with `1`
otherwise	`CO_NIT_9_DV`

CONFIGURATION

trimInput	yes
requireMask	no

`CO_NIT_9_AUX` CHECK DIGIT

Masks the digits with `CO_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 11 check digit with weights `6 14 26 34 38 46 58 74 82` from the right.

Used by: `CO_NIT_9`

CONFIGURATION

weightList	`6 14 26 34 38 46 58 74 82`
modulusNumber	`11`
checkDigitIndex	`9`
numDigitsForCheckdigitCalculation	`9`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`CO_CM_DIGITOS_ANCHO_FIJO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

`CO_NIT_9_DV` CHECK DIGIT

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41` from the right.

Used by: `CO_NIT_9_AJUSTE`

CONFIGURATION

weightList	`3 7 13 17 19 23 29 37 41`
modulusNumber	`11`
checkDigitIndex	`9`
numDigitsForCheckdigitCalculation	`9`
calculateChecksumRightToLeft	yes
numericAlgorithm	`CO_IDENTIDAD`
alphaNumericAlgorithm	`CO_IDENTIDAD`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

CO_NOMBRE NAME

Replaces the name with one of the 232 names in `co-nombres.txt`.

Used by: `CO_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	`co-nombres.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

CO_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`CO_APELLIDOS` · `CO_NOMBRES`
`(\S+)`	`CO_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO` · `CO_PALABRA_APELLIDO`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CO_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_NOMBRE`, `CO_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`CO_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)`	`CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE` · `CO_PALABRA_NOMBRE`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CO_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `CO_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

CO_OCUPACION SECURE LOOKUP

Replaces the value with one of the 39 values in `co-ocupaciones.txt`, chosen by a keyed hash.

Used by: `CO_OCUPACION_O_CIUO`

CONFIGURATION

lookupFile	`co-ocupaciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_OCUPACION_O_CIUO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_OCUPACION`.

Used by: `CO_L2_OCUPACION`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{4,5}))`	keep · `CO_CM_DIGITOS`
otherwise	`CO_OCUPACION`

CONFIGURATION

trimInput	yes
requireMask	no

CO_ORIENTACION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ORIENTACION_POLITICA_LISTA`.

Used by: `CO_L3_ORIENTACION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_ORIENTACION_POLITICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_ORIENTACION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `co-orientaciones-politicas.txt`, chosen by a keyed hash.

Used by: `CO_ORIENTACION_POLITICA`

CONFIGURATION

lookupFile	`co-orientaciones-politicas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_ORIENTACION_SEXUAL_LISTA`.

Used by: `CO_L3_ORIENTACION_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_ORIENTACION_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-orientaciones-sexuales.txt`, chosen by a keyed hash.

Used by: `CO_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	`co-orientaciones-sexuales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_APELLIDO`.

Used by: `CO_APELLIDOS` , `CO_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)` `(de|del|la|las|los|y|e|san|santa|van|von|di)`	keep
otherwise	`CO_APELLIDO`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NOMBRE` .

Used by: `CO_NOMBRES` , `CO_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)` `(de|del|la|las|los|y|e|san|santa|van|von|di)`	keep
otherwise	`CO_NOMBRE`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PARTIDO_LISTA` .

Used by: `CO_L3_AFILIACION_PARTIDO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_PARTIDO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 29 values in `co-partidos.txt` , chosen by a keyed hash.

Used by: `CO_PARTIDO`

CONFIGURATION

lookupFile	`co-partidos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PLACA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM` .

Used by: `CO_L1_PLACA`

PATTERNS, TRIED IN ORDER

`([A-Za-z]{3})([\s\-]?)(\d{3})`	`CO_CM_DIGITOS_LETRAS` · keep · `CO_CM_DIGITOS`
`([A-Za-z]{3})([\s\-]?)(\d{2})([A-Za-z]?)`	`CO_CM_DIGITOS_LETRAS` · keep · `CO_CM_DIGITOS` · `CO_CM_DIGITOS_LETRAS`
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_PROCEDIMIENTO_TEXTO` .

Used by: `CO_SALUD_PROCEDIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{6}|\d{2}\.\d{2}\.\d{2}))`	keep · `CO_CUPS`
otherwise	`CO_PROCEDIMIENTO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in `co-procedimientos.txt` , chosen by a keyed hash.

Used by: `CO_PROCEDIMIENTO`

CONFIGURATION

lookupFile	`co-procedimientos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PROGRAMA_SOCIAL_LISTA` .

Used by: `CO_FIN_PROGRAMA_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_PROGRAMA_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-programas-sociales.txt`, chosen by a keyed hash.

Used by: `CO_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	`co-programas-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PUEBLO_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PUEBLO_INDIGENA_LISTA`.

Used by: `CO_L3_PUEBLO_INDIGENA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `CO_PUEBLO_INDIGENA_CODIGO`
otherwise	`CO_PUEBLO_INDIGENA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_PUEBLO_INDIGENA_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `co-pueblos-indigenas-codigos.txt`, chosen by a keyed hash.

Used by: `CO_PUEBLO_INDIGENA`

CONFIGURATION

lookupFile	`co-pueblos-indigenas-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PUEBLO_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 20 values in `co-pueblos-indigenas.txt`, chosen by a keyed hash.

Used by: `CO_PUEBLO_INDIGENA`

CONFIGURATION

lookupFile	`co-pueblos-indigenas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

CO_RADICADO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_PENAL_RADICADO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{5}[\s\-]?\d{2}[\s\-]?\d{2}[\s\-]?\d{3}[\s\-]?\d{4}[\s\-]?)(\d{5})([\s\-]?\d{2}))`	keep · keep · `CO_CM_DIGITOS` · keep
otherwise	`CO_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

CO_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L1_CREDENCIAL`, `CO_L3_BIOMETRICO`, `CO_L3_GENETICO`

PATTERNS, TRIED IN ORDER

`(.+)`	each character → `X`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_REGIMEN_SALUD SECURE LOOKUP

Replaces the value with one of the 5 values in `co-regimenes-salud.txt`, chosen by a keyed hash.

Used by: `CO_AFILIACION_SALUD`

CONFIGURATION

lookupFile	`co-regimenes-salud.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_RELIGION_LISTA`.

Used by: `CO_L3_RELIGION`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_RELIGION_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `co-religiones.txt`, chosen by a keyed hash.

Used by: `CO_RELIGION`

CONFIGURATION

lookupFile	`co-religiones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SALUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SALUD_LABORAL_LISTA`.

Used by: `CO_SALUD_OCUPACIONAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_SALUD_LABORAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_SALUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in `co-aptitud-laboral.txt`, chosen by a keyed hash.

Used by: `CO_SALUD_LABORAL`

CONFIGURATION

lookupFile	`co-aptitud-laboral.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L2_SEXO`

PATTERNS, TRIED IN ORDER

`(?i)(femenino|masculino)`	`CO_SEXO_FEMENINO_MASCULINO`
`(?i)(mujer|hombre)`	`CO_SEXO_MUJER_HOMBRE`

`(?i)(female|male)`	`CO_SEXO_FEMALE_MALE`
`(?i)([fm])`	`CO_SEXO_F_M`
`(?i)([hm])`	`CO_SEXO_H_M`
`(0*?)(?:([12]))`	keep · `CO_SEXO_1_2`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_SEXO_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-1-2.txt`, chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	`co-sexo-1-2.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	`co-sexo-f-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-female-male.txt`, chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	`co-sexo-female-male.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-femenino-masculino.txt`, chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	`co-sexo-femenino-masculino.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-h-m.txt`, chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	`co-sexo-h-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	`co-sexo-mujer-hombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_SISBEN_GRUPO`.

Used by: `CO_FIN_SISBEN`

PATTERNS, TRIED IN ORDER

`(?i)(A\s?)([1-5])`	keep · `CO_SISBEN_A`
`(?i)(B\s?)([1-7])`	keep · `CO_SISBEN_B`
`(?i)(C\s?)(1[0-8]|[1-9])`	keep · `CO_SISBEN_C`
`(?i)(D\s?)(2[01]|1\d|[1-9])`	keep · `CO_SISBEN_D`
`(0*?)(?:(\d{1,3})([.,]\d+)?)`	keep · `CO_CM_DIGITOS` · keep
otherwise	`CO_SISBEN_GRUPO`

CONFIGURATION

trimInput	yes

requireMask	no

CO_SISBEN_A SECURE LOOKUP

Replaces the value with one of the 5 values in `co-sisben-a.txt`, chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	`co-sisben-a.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_B SECURE LOOKUP

Replaces the value with one of the 7 values in `co-sisben-b.txt`, chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	`co-sisben-b.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_C SECURE LOOKUP

Replaces the value with one of the 18 values in `co-sisben-c.txt`, chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	`co-sisben-c.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_D SECURE LOOKUP

Replaces the value with one of the 21 values in `co-sisben-d.txt`, chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	`co-sisben-d.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

CO_SISBEN_GRUPO SECURE LOOKUP

Replaces the value with one of the 4 values in `co-sisben-grupos.txt`, chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	`co-sisben-grupos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

Used by: `CO_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`co-sin-informacion.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CO_L1_TARJETA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.

Used by: `CO_L1_TELEFONO`, `CO_LLAVE_BREB`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?57[\s\-]?)?(\(?3\d{2}\)?)([\s\-]?)(\d{3})([\s\-]?)(\d{4}))`	keep · keep · keep · keep · `CO_CM_DIGITOS` · keep · `CO_CM_DIGITOS`
`(0*?)(?:(\+?57[\s\-]?)?(\(?60[1-8]\)?)([\s\-]?)(\d{3})([\s\-]?)(\d{4}))`	keep · keep · keep · keep · `CO_CM_DIGITOS` · keep · `CO_CM_DIGITOS`
`(0*?)(?:([2-8]\d{2})([\s\-]?)(\d{4}))`	keep · `CO_CM_DIGITOS` · keep · `CO_CM_DIGITOS`
otherwise	`CO_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

CO_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_TENENCIA_VIVIENDA_LISTA`.

Used by: `CO_FIN_VIVIENDA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_TENENCIA_VIVIENDA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `co-tenencia-vivienda.txt`, chosen by a keyed hash.

Used by: `CO_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	`co-tenencia-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATO]`, and the 1,188 terms of `co-texto-nombres.txt` with `[NOMBRE]`.

Used by: `CO_L1_TEXTO_LIBRE`, `CO_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

`(?<![\d.])\d{1,3}(\.\d{3}){1,3}(-\d)?(?![\d.])`
`(?<!\d)\d{6,10}-\d(?!\d)`
`(?<!\d)\d{6,11}(?!\d)`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<![\d\-])(\+?57)?3\d{2}[\-]?\d{3}[\-]?\d{4}(?![\d\-])`
`(?<!\d)\d{13,19}(?!\d)`
`(?<![A-Za-z])[A-Z]{3}-?\d{2}[A-Z\d](?![A-Za-z\d])`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATO]`
lookupFile	`co-texto-nombres.txt`
lookupFileRedactValue	`[NOMBRE]`

isDenyList	yes

CO_VICTIMA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_VICTIMA_LISTA`.

Used by: `CO_L3_VICTIMA_CONFLICTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`CO_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `CO_CM_ALFANUM`
otherwise	`CO_VICTIMA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

CO_VICTIMA_LISTA SECURE LOOKUP

Replaces the value with one of the 15 values in `co-hechos-victimizantes.txt`, chosen by a keyed hash.

Used by: `CO_VICTIMA`

CONFIGURATION

lookupFile	`co-hechos-victimizantes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ZONA_RURAL SECURE LOOKUP

Replaces the value with one of the 1 values in `co-zona-rural.txt`, chosen by a keyed hash.

Used by: `CO_L2_VEREDA`

CONFIGURATION

lookupFile	`co-zona-rural.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`co-antecedentes.txt`	8	`CO_ANTECEDENTES_LISTA`	No tiene asuntos pendientes con las autoridades judiciales · Registra antecedentes · Imputado · Acusado
`co-apellidos.txt`	255	`CO_APELLIDO`	Rodríguez · Gómez · González · Martínez
`co-aptitud-laboral.txt`	4	`CO_SALUD_LABORAL_LISTA`	Apto · Apto con restricciones · No apto · Aplazado
`co-bandera-0-1.txt`	2	`CO_BANDERA_0_1`	0 · 1
`co-bandera-s-n.txt`	2	`CO_BANDERA_S_N`	S · N
`co-bandera-si-no.txt`	2	`CO_BANDERA_SI_NO`	Sí · No
`co-bandera-true-false.txt`	2	`CO_BANDERA_TRUE_FALSE`	true · false
`co-bandera-y-n.txt`	2	`CO_BANDERA_Y_N`	Y · N
`co-bandera-yes-no.txt`	2	`CO_BANDERA_YES_NO`	Yes · No
`co-barrios.txt`	35	`CO_BARRIO`	Centro · La Esperanza · San José · El Prado
`co-cie10-decimal.txt`	33	`CO_CIE10_DECIMAL`	E11.9 · E78.5 · J45.9 · J06.9
`co-cie10.txt`	37	`CO_CIE10`	I10 · E11 · E78 · J45
`co-codigos-municipio-generalizados.txt`	767	`CO_CODIGO_MUNICIPIO_TABLA`	05004,05284 · 05021,05670 · 05036,05030 · 05038,05887
`co-cups.txt`	10	`CO_CUPS`	890201 · 890301 · 890701 · 902210
`co-detectar-apellidos.txt`	328	`CO_L1_APELLIDO – List` `CO_L1_NOMBRE_COMPLETO – List`	Rodríguez · Rodriguez · Gómez · Gomez
`co-detectar-nombres.txt`	280	`CO_L1_NOMBRE – List` `CO_L1_NOMBRE_COMPLETO – List`	María · Maria · José · Jose
`co-detectar-sexo-letra.txt`	3	`CO_L2_SEXO – List`	f · m · h
`co-detectar-sexo.txt`	6	`CO_L2_SEXO – List`	femenino · masculino · mujer · hombre
`co-diagnosticos.txt`	30	`CO_DIAGNOSTICO_TEXTO`	Hipertensión esencial · Diabetes mellitus tipo 2 · Asma · Lumbago

FILE	LINES	USED BY	FIRST LINES
co-direcciones.txt	4,000	CO_DIRECCION	Calle 27 # 53-56 · Avenida Calle 40 # 38A-81 Torre 8 Apto 2406 · Carrera 76 Bis # 3-56 Torre 6 Apto 605 · Calle 49 # 53-57
co-discapacidades.txt	8	CO_DISCAPACIDAD_LISTA	Física · Auditiva · Visual · Sordoceguera
co-empleadores.txt	24	CO_EMPLEADOR	Comercializadora El Progreso S.A.S. · Construcciones Andinas S.A.S. · Transportes La Sabana S.A.S. · Supermercados La Económica S.A.S.
co-eps.txt	18	CO_EPS	Nueva EPS · EPS Sura · EPS Sanitas · Salud Total EPS
co-escolaridad-codigos.txt	11	CO_ESCOLARIDAD_CODIGO	1 · 2 · 3 · 4
co-escolaridad.txt	11	CO_ESCOLARIDAD_LISTA	Ninguno · Preescolar · Básica primaria · Básica secundaria
co-estado-civil-codigos.txt	6	CO_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
co-estado-civil.txt	6	CO_ESTADO_CIVIL_LISTA	Soltero(a) · Casado(a) · Unión marital de hecho · Separado(a)
co-estados-credito.txt	10	CO_ESTADO_CREDITO	Al día · Mora de 30 días · Mora de 60 días · Mora de 90 días
co-estrato-alto.txt	2	CO_ESTRATO_ALTO	5 · 6
co-estrato-bajo.txt	2	CO_ESTRATO_BAJO	1 · 2
co-estrato-medio.txt	2	CO_ESTRATO_MEDIO	3 · 4
co-grupos-etnicos-codigos.txt	6	CO_GRUPO_ETNICO_CODIGO	1 · 2 · 3 · 4
co-grupos-etnicos.txt	6	CO_GRUPO_ETNICO_LISTA	Indígena · Gitano(a) o Rrom · Raizal del Archipiélago de San Andrés, Providencia y Santa Catalina · Palenquero(a) de San Basilio
co-hechos-victimizantes.txt	15	CO_VICTIMA_LISTA	Desplazamiento forzado · Homicidio · Amenaza · Desaparición forzada
co-identidades-genero.txt	7	CO_IDENTIDAD_GENERO_LISTA	Mujer cisgénero · Hombre cisgénero · Mujer trans · Hombre trans
co-instituciones-educativas.txt	12	CO_INSTITUCION_EDUCATIVA	Institución Educativa San José · Colegio Nuestra Señora del Rosario · Institución Educativa Técnica Agropecuaria · Colegio Departamental La Esperanza
co-lenguas.txt	12	CO_LENGUA_LISTA	Español · Wayuunaiki · Nasa Yuwe · Emberá
co-medicamentos.txt	24	CO_MEDICAMENTO_LISTA	Acetaminofén · Ibuprofeno · Naproxeno · Diclofenaco
co-municipios-generalizados.txt	12,622	CO_MUNICIPIO	Abriaquí|Frontino · ABRIAQUÍ|FRONTINO · Abriaqui|Frontino · ABRIAQUI|FRONTINO
co-nacionalidades.txt	16	CO_NACIONALIDAD	Colombiana · Venezolana · Ecuatoriana · Peruana

FILE	LINES	USED BY	FIRST LINES
co-nombres.txt	232	CO_NOMBRE	María · José · Luis · Carlos
co-ocupaciones.txt	39	CO_OCUPACION	Auxiliar administrativo · Asistente administrativo · Vendedor · Cajero
co-orientaciones-politicas.txt	7	CO_ORIENTACION_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
co-orientaciones-sexuales.txt	8	CO_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
co-partidos.txt	29	CO_PARTIDO_LISTA	Partido Liberal Colombiano · Partido Conservador Colombiano · Partido Cambio Radical · Partido Alianza Verde
co-procedimientos.txt	10	CO_PROCEDIMIENTO_TEXTO	Consulta de primera vez por medicina general · Consulta de control o de seguimiento por medicina general · Consulta de urgencias por medicina general · Hemograma
co-programas-sociales.txt	8	CO_PROGRAMA_SOCIAL_LISTA	Renta Ciudadana · Renta Joven · Colombia Mayor · Devolución del IVA
co-pueblos-indigenas-codigos.txt	10	CO_PUEBLO_INDIGENA_CODIGO	720 · 800 · 500 · 560
co-pueblos-indigenas.txt	20	CO_PUEBLO_INDIGENA_LISTA	Wayuu · Zenú · Nasa · Pastos
co-regimenes-salud.txt	5	CO_REGIMEN_SALUD	Contributivo · Subsidiado · Especial · De excepción
co-religiones.txt	12	CO_RELIGION_LISTA	Católica · Cristiana evangélica · Pentecostal · Adventista del Séptimo Día
co-sexo-1-2.txt	2	CO_SEXO_1_2	1 · 2
co-sexo-f-m.txt	2	CO_SEXO_F_M	F · M
co-sexo-female-male.txt	2	CO_SEXO_FEMALE_MALE	Female · Male
co-sexo-femenino-masculino.txt	2	CO_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
co-sexo-h-m.txt	2	CO_SEXO_H_M	H · M
co-sexo-mujer-hombre.txt	2	CO_SEXO_MUJER_HOMBRE	Mujer · Hombre
co-sin-informacion.txt	1	CO_SUPRIMIR	Sin información
co-sisben-a.txt	5	CO_SISBEN_A	1 · 2 · 3 · 4
co-sisben-b.txt	7	CO_SISBEN_B	1 · 2 · 3 · 4
co-sisben-c.txt	18	CO_SISBEN_C	1 · 2 · 3 · 4
co-sisben-d.txt	21	CO_SISBEN_D	1 · 2 · 3 · 4
co-sisben-grupos.txt	4	CO_SISBEN_GRUPO	Pobreza extrema · Pobreza moderada · Vulnerable · No pobre, no vulnerable
co-tenencia-vivienda.txt	7	CO_TENENCIA_VIVIENDA_LISTA	Propia, totalmente pagada · Propia, la están pagando · En arriendo o subarriendo · En usufructo

FILE	LINES	USED BY	FIRST LINES
`co-texto-nombres.txt`	1,188	`CO_TEXTO_LIBRE`	María · MARÍA · Maria · MARIA
`co-zona-rural.txt`	1	`CO_ZONA_RURAL`	Zona rural

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `comercial` `archivo` `calle` `via` `barrio` `municipio` `mpio` `ciudad` `departamento` `depto` `dpto` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `institucion` `curso` `materia` `documento` `doc` `centro` `unidad` `clinica` `hospital` `ips` `eps` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `sede` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `entidad` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `pago` `forma` `zona` `ruta` `linea` `actividad` `sector` `vereda` `corregimiento` `localidad` `comuna` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `funcionario` `trabajador` `contratista` `estudiante` `alumno` `deudor` `codeudor` `fiador` `avalista` `tomador` `propietario` `arrendatario` `arrendador` `conductor` `acudiente` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `companero` `contacto` `referencia` `victima` `denunciante` `sindicado` `imputado` `procesado` `testigo` `medico` `docente` `socio` `accionista` `heredero` `causante` `donante` `tutor` `curador` `cotizante` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `completo` `apellidos?` `usuario` `corto` `largo`

E2 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `comercial` `archivo` `calle` `via` `barrio` `municipio` `mpio` `ciudad` `departamento` `depto` `dpto` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `institucion` `curso` `materia` `documento` `doc` `centro` `unidad` `clinica` `hospital` `ips` `eps` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `sede` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `entidad` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `pago` `forma` `zona` `ruta` `linea` `actividad` `sector` `vereda` `corregimiento` `localidad` `comuna` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `funcionario` `trabajador` `contratista` `estudiante` `alumno` `deudor` `codeudor` `fiador` `avalista` `tomador` `propietario` `arrendatario` `arrendador` `conductor` `acudiente` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `companero` `contacto` `referencia` `victima` `denunciante` `sindicado` `imputado` `procesado` `testigo` `medico` `docente` `socio` `accionista` `heredero` `causante` `donante` `tutor` `curador` `cotizante` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner`

E3	`producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `comercial` `archivo` `calle` `via` `barrio` `municipio` `mpio` `ciudad` `departamento` `depto` `dpto` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `institucion` `curso` `materia` `documento` `doc` `centro` `unidad` `clinica` `hospital` `ips` `eps` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `etnia` `pueblo` `lengua` `lugar` `sede` `tienda` `almacen` `bodega` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `entidad` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `pago` `forma` `zona` `ruta` `linea` `actividad` `sector` `vereda` `corregimiento` `localidad` `comuna` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `funcionario` `trabajador` `contratista` `estudiante` `alumno` `deudor` `codeudor` `fiador` `avalista` `tomador` `propietario` `arrendatario` `arrendador` `conductor` `acudiente` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `companero` `contacto` `referencia` `victima` `denunciante` `sindicado` `imputado` `procesado` `testigo` `medico` `docente` `socio` `accionista` `heredero` `causante` `donante` `tutor` `curador` `cotizante` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `full` `complete` `last` `first`
E4	`ip` `mac` `email` `e_?mail` `correo` `electr[oó]nica` `web` `url` `tipo` `id` `general` `t[eé]cnica` `seccional` `regional`
E5	`ip` `mac` `email` `e_?mail` `web` `url` `type` `id`
E6	`id` `cd` `cod` `codigo` `tipo` `fecha` `estado` `num` `nro`
E7	`id` `tipo` `codigo` `fecha` `estado` `cola` `log`

APPENDIX D

Profile set and classifiers

The profile set `CO – Ley 1581 de 2012 – v2` runs these 145 classifiers, with an assignment threshold of 60%.

Ley 1581 de 2012 - datos personales y sensibles

CLASSIFIER	KIND	DOMAIN
CO_L1_CEDULA – Path	COLUMN NAME	CO_L1_CEDULA
CO_L1_CEDULA – Type	DATA TYPE	CO_L1_CEDULA
CO_L1_CEDULA – Regex	VALUE FORMAT	CO_L1_CEDULA
CO_L1_NIT – Path	COLUMN NAME	CO_L1_NIT
CO_L1_NIT – Regex	VALUE FORMAT	CO_L1_NIT
CO_L1_DOCUMENTO_EXTRANJERO – Path	COLUMN NAME	CO_L1_DOCUMENTO_EXTRANJERO
CO_L1_PASAPORTE – Path	COLUMN NAME	CO_L1_PASAPORTE
CO_L1_PASAPORTE – Regex	VALUE FORMAT	CO_L1_PASAPORTE
CO_L1_REGISTRO_CIVIL – Path	COLUMN NAME	CO_L1_REGISTRO_CIVIL
CO_L1_TARJETA_PROFESIONAL – Path	COLUMN NAME	CO_L1_TARJETA_PROFESIONAL
CO_L1_NOMBRE – Path	COLUMN NAME	CO_L1_NOMBRE
CO_L1_NOMBRE – List	KNOWN VALUES	CO_L1_NOMBRE
CO_L1_APELLIDO – Path	COLUMN NAME	CO_L1_APELLIDO
CO_L1_APELLIDO – List	KNOWN VALUES	CO_L1_APELLIDO
CO_L1_NOMBRE_COMPLETO – Path	COLUMN NAME	CO_L1_NOMBRE_COMPLETO
CO_L1_NOMBRE_COMPLETO – List	KNOWN VALUES	CO_L1_NOMBRE_COMPLETO
CO_L1_EMAIL – Path	COLUMN NAME	CO_L1_EMAIL
CO_L1_EMAIL – Type	DATA TYPE	CO_L1_EMAIL
CO_L1_EMAIL – Regex	VALUE FORMAT	CO_L1_EMAIL
CO_L1_TELEFONO – Path	COLUMN NAME	CO_L1_TELEFONO
CO_L1_TELEFONO – Regex	VALUE FORMAT	CO_L1_TELEFONO
CO_L1_DIRECCION – Path	COLUMN NAME	CO_L1_DIRECCION
CO_L1_DIRECCION – Type	DATA TYPE	CO_L1_DIRECCION
CO_L1_DIRECCION – Regex	VALUE FORMAT	CO_L1_DIRECCION
CO_L1_DIRECCION_COMPLEMENTO – Path	COLUMN NAME	CO_L1_DIRECCION_COMPLEMENTO
CO_L1_CUENTA_BANCARIA – Path	COLUMN NAME	CO_L1_CUENTA_BANCARIA
CO_L1_TARJETA – Path	COLUMN NAME	CO_L1_TARJETA
CO_L1_TARJETA – Regex	VALUE FORMAT	CO_L1_TARJETA
CO_L1_LLAVE_BREB – Path	COLUMN NAME	CO_L1_LLAVE_BREB
CO_L1_LLAVE_BREB – Regex	VALUE FORMAT	CO_L1_LLAVE_BREB
CO_L1_IP – Path	COLUMN NAME	CO_L1_IP

CLASSIFIER	KIND	DOMAIN
CO_L1_IP – Regex	VALUE FORMAT	CO_L1_IP
CO_L1_DISPOSITIVO – Path	COLUMN NAME	CO_L1_DISPOSITIVO
CO_L1_DISPOSITIVO – Regex	VALUE FORMAT	CO_L1_DISPOSITIVO
CO_L1_PLACA – Path	COLUMN NAME	CO_L1_PLACA
CO_L1_PLACA – Regex	VALUE FORMAT	CO_L1_PLACA
CO_L1_VEHICULO – Path	COLUMN NAME	CO_L1_VEHICULO
CO_L1_VEHICULO – Regex	VALUE FORMAT	CO_L1_VEHICULO
CO_L1_INMUEBLE – Path	COLUMN NAME	CO_L1_INMUEBLE
CO_L1_INMUEBLE – Regex	VALUE FORMAT	CO_L1_INMUEBLE
CO_L1_CONTRATO – Path	COLUMN NAME	CO_L1_CONTRATO
CO_L1_USUARIO – Path	COLUMN NAME	CO_L1_USUARIO
CO_L1_CREDENCIAL – Path	COLUMN NAME	CO_L1_CREDENCIAL
CO_L1_CREDENCIAL – Regex	VALUE FORMAT	CO_L1_CREDENCIAL
CO_L1_GEOLOCALIZACION – Path	COLUMN NAME	CO_L1_GEOLOCALIZACION
CO_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	CO_L1_GEOLOCALIZACION
CO_L1_TEXTO_LIBRE – Path	COLUMN NAME	CO_L1_TEXTO_LIBRE
CO_L1_TEXTO_LIBRE – Type	DATA TYPE	CO_L1_TEXTO_LIBRE
CO_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	CO_L1_TEXTO_LIBRE
CO_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	CO_L2_FECHA_NACIMIENTO
CO_L2_FECHA_NACIMIENTO – Type	DATA TYPE	CO_L2_FECHA_NACIMIENTO
CO_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	CO_L2_ANIO_NACIMIENTO
CO_L2_ANIO_NACIMIENTO – Type	DATA TYPE	CO_L2_ANIO_NACIMIENTO
CO_L2_EDAD – Path	COLUMN NAME	CO_L2_EDAD
CO_L2_EDAD – Type	DATA TYPE	CO_L2_EDAD
CO_L2_FECHA_EVENTO – Path	COLUMN NAME	CO_L2_FECHA_EVENTO
CO_L2_FECHA_EVENTO – Type	DATA TYPE	CO_L2_FECHA_EVENTO
CO_L2_SEXO – Path	COLUMN NAME	CO_L2_SEXO
CO_L2_SEXO – List	KNOWN VALUES	CO_L2_SEXO
CO_L2_MUNICIPIO – Path	COLUMN NAME	CO_L2_MUNICIPIO
CO_L2_MUNICIPIO – Values	VALUE FORMAT	CO_L2_MUNICIPIO
CO_L2_CODIGO_MUNICIPIO – Path	COLUMN NAME	CO_L2_CODIGO_MUNICIPIO
CO_L2_CODIGO_MUNICIPIO – Regex	VALUE FORMAT	CO_L2_CODIGO_MUNICIPIO
CO_L2_CODIGO_POSTAL – Path	COLUMN NAME	CO_L2_CODIGO_POSTAL
CO_L2_CODIGO_POSTAL – Type	DATA TYPE	CO_L2_CODIGO_POSTAL
CO_L2_BARRIO – Path	COLUMN NAME	CO_L2_BARRIO
CO_L2_VEREDA – Path	COLUMN NAME	CO_L2_VEREDA
CO_L2_NACIONALIDAD – Path	COLUMN NAME	CO_L2_NACIONALIDAD

CLASSIFIER	KIND	DOMAIN
CO_L2_NACIONALIDAD – Values	VALUE FORMAT	CO_L2_NACIONALIDAD
CO_L2_ESTADO_CIVIL – Path	COLUMN NAME	CO_L2_ESTADO_CIVIL
CO_L2_ESTADO_CIVIL – Values	VALUE FORMAT	CO_L2_ESTADO_CIVIL
CO_L2_OCUPACION – Path	COLUMN NAME	CO_L2_OCUPACION
CO_L2_EMPLEADOR – Path	COLUMN NAME	CO_L2_EMPLEADOR
CO_L2_ESCOLARIDAD – Path	COLUMN NAME	CO_L2_ESCOLARIDAD
CO_L2_ESCOLARIDAD – Values	VALUE FORMAT	CO_L2_ESCOLARIDAD
CO_L2_INSTITUCION_EDUCATIVA – Path	COLUMN NAME	CO_L2_INSTITUCION_EDUCATIVA
CO_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	CO_L2_PERSONAS_A_CARGO
CO_L2_PERSONAS_A_CARGO – Type	DATA TYPE	CO_L2_PERSONAS_A_CARGO
CO_L3_GRUPO_ETNICO – Path	COLUMN NAME	CO_L3_GRUPO_ETNICO
CO_L3_GRUPO_ETNICO – Values	VALUE FORMAT	CO_L3_GRUPO_ETNICO
CO_L3_PUEBLO_INDIGENA – Path	COLUMN NAME	CO_L3_PUEBLO_INDIGENA
CO_L3_PUEBLO_INDIGENA – Values	VALUE FORMAT	CO_L3_PUEBLO_INDIGENA
CO_L3_LENGUA_NATIVA – Path	COLUMN NAME	CO_L3_LENGUA_NATIVA
CO_L3_LENGUA_NATIVA – Values	VALUE FORMAT	CO_L3_LENGUA_NATIVA
CO_L3_RELIGION – Path	COLUMN NAME	CO_L3_RELIGION
CO_L3_RELIGION – Values	VALUE FORMAT	CO_L3_RELIGION
CO_L3_CONVICCION_FILOSOFICA – Path	COLUMN NAME	CO_L3_CONVICCION_FILOSOFICA
CO_L3_ORIENTACION_POLITICA – Path	COLUMN NAME	CO_L3_ORIENTACION_POLITICA
CO_L3_ORIENTACION_POLITICA – Values	VALUE FORMAT	CO_L3_ORIENTACION_POLITICA
CO_L3_AFILIACION_PARTIDO – Path	COLUMN NAME	CO_L3_AFILIACION_PARTIDO
CO_L3_AFILIACION_PARTIDO – Values	VALUE FORMAT	CO_L3_AFILIACION_PARTIDO
CO_L3_SINDICATO – Path	COLUMN NAME	CO_L3_SINDICATO
CO_L3_SINDICATO – Values	VALUE FORMAT	CO_L3_SINDICATO
CO_L3_ORGANIZACION_SOCIAL – Path	COLUMN NAME	CO_L3_ORGANIZACION_SOCIAL
CO_L3_BIOMETRICO – Path	COLUMN NAME	CO_L3_BIOMETRICO
CO_L3_BIOMETRICO – Type	DATA TYPE	CO_L3_BIOMETRICO
CO_L3_GENETICO – Path	COLUMN NAME	CO_L3_GENETICO
CO_L3_GENETICO – Regex	VALUE FORMAT	CO_L3_GENETICO
CO_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	CO_L3_ORIENTACION_SEXUAL
CO_L3_ORIENTACION_SEXUAL – Values	VALUE FORMAT	CO_L3_ORIENTACION_SEXUAL
CO_L3_VIDA_SEXUAL – Path	COLUMN NAME	CO_L3_VIDA_SEXUAL
CO_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	CO_L3_IDENTIDAD_GENERO
CO_L3_IDENTIDAD_GENERO – Values	VALUE FORMAT	CO_L3_IDENTIDAD_GENERO
CO_L3_VICTIMA_CONFLICTO – Path	COLUMN NAME	CO_L3_VICTIMA_CONFLICTO
CO_L3_VICTIMA_CONFLICTO – Values	VALUE FORMAT	CO_L3_VICTIMA_CONFLICTO

CLASSIFIER	KIND	DOMAIN
CO_L3_REINCORPORACION – Path	COLUMN NAME	CO_L3_REINCORPORACION
CO_SALUD_IDENTIFICADOR – Path	COLUMN NAME	CO_SALUD_IDENTIFICADOR
CO_SALUD_AFILIACION – Path	COLUMN NAME	CO_SALUD_AFILIACION
CO_SALUD_AFILIACION – Values	VALUE FORMAT	CO_SALUD_AFILIACION
CO_SALUD_DIAGNOSTICO – Path	COLUMN NAME	CO_SALUD_DIAGNOSTICO
CO_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	CO_SALUD_DIAGNOSTICO
CO_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	CO_SALUD_PROCEDIMIENTO
CO_SALUD_MEDICAMENTO – Path	COLUMN NAME	CO_SALUD_MEDICAMENTO
CO_SALUD_MEDICAMENTO – Values	VALUE FORMAT	CO_SALUD_MEDICAMENTO
CO_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	CO_SALUD_TEXTO_CLINICO
CO_SALUD_TEXTO_CLINICO – Type	DATA TYPE	CO_SALUD_TEXTO_CLINICO
CO_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	CO_SALUD_RESULTADO_EXAMEN
CO_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	CO_SALUD_GRUPO_SANGUINEO
CO_SALUD_GRUPO_SANGUINEO – Values	VALUE FORMAT	CO_SALUD_GRUPO_SANGUINEO
CO_SALUD_DISCAPACIDAD – Path	COLUMN NAME	CO_SALUD_DISCAPACIDAD
CO_SALUD_DISCAPACIDAD – Values	VALUE FORMAT	CO_SALUD_DISCAPACIDAD
CO_SALUD_OCUPACIONAL – Path	COLUMN NAME	CO_SALUD_OCUPACIONAL
CO_SALUD_OCUPACIONAL – Values	VALUE FORMAT	CO_SALUD_OCUPACIONAL
CO_SALUD_REPRODUCTIVA – Path	COLUMN NAME	CO_SALUD_REPRODUCTIVA
CO_SALUD_MENTAL – Path	COLUMN NAME	CO_SALUD_MENTAL
CO_FIN_CREDITO – Path	COLUMN NAME	CO_FIN_CREDITO
CO_FIN_DEUDA – Path	COLUMN NAME	CO_FIN_DEUDA
CO_FIN_DEUDA – Type	DATA TYPE	CO_FIN_DEUDA
CO_FIN_INGRESOS – Path	COLUMN NAME	CO_FIN_INGRESOS
CO_FIN_INGRESOS – Type	DATA TYPE	CO_FIN_INGRESOS
CO_FIN_PATRIMONIO – Path	COLUMN NAME	CO_FIN_PATRIMONIO
CO_FIN_PATRIMONIO – Type	DATA TYPE	CO_FIN_PATRIMONIO
CO_FIN_PENSION – Path	COLUMN NAME	CO_FIN_PENSION
CO_FIN_PENSION – Type	DATA TYPE	CO_FIN_PENSION
CO_FIN_ESTRATO – Path	COLUMN NAME	CO_FIN_ESTRATO
CO_FIN_ESTRATO – Values	VALUE FORMAT	CO_FIN_ESTRATO
CO_FIN_SISBEN – Path	COLUMN NAME	CO_FIN_SISBEN
CO_FIN_SISBEN – Regex	VALUE FORMAT	CO_FIN_SISBEN
CO_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	CO_FIN_PROGRAMA_SOCIAL
CO_FIN_PROGRAMA_SOCIAL – Values	VALUE FORMAT	CO_FIN_PROGRAMA_SOCIAL
CO_FIN_VIVIENDA – Path	COLUMN NAME	CO_FIN_VIVIENDA
CO_FIN_VIVIENDA – Values	VALUE FORMAT	CO_FIN_VIVIENDA

CLASSIFIER	KIND	DOMAIN
`CO_PENAL_ANTECEDENTES – Path`	COLUMN NAME	`CO_PENAL_ANTECEDENTES`
`CO_PENAL_RADICADO – Path`	COLUMN NAME	`CO_PENAL_RADICADO`
`CO_PENAL_RADICADO – Regex`	VALUE FORMAT	`CO_PENAL_RADICADO`