
DELPHIX MASKING · PROFILE SET

Chile — Ley 21.719

Discovering and masking Chilean personal data: direct identifiers, quasi-identifiers and the sensitive data of article 2 — socioeconomic situation included.

73

DOMAINS

132

CLASSIFIERS

101

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	Ley 21.719 in brief
3	How sensitive data is discovered
4	How data is masked
5	Essential and extended packs
6	Domains at a glance

PART 7 · DIRECT IDENTIFIERS

7.1	RUT / RUN	CL_L1_RUT
7.2	RUT without check digit	CL_L1_RUT_CUERPO
7.3	RUT check digit	CL_L1_RUT_DV
7.4	Given names	CL_L1_NOMBRE
7.5	Surnames	CL_L1_APELLIDO
7.6	Full name	CL_L1_NOMBRE_COMPLETO
7.7	E-mail address	CL_L1_EMAIL
7.8	Telephone	CL_L1_TELEFONO
7.9	Street address	CL_L1_DIRECCION
7.10	Address details	CL_L1_DIRECCION_COMPLEMENTO
7.11	Identity card document number	CL_L1_NUMERO_DOCUMENTO
7.12	Passport	CL_L1_PASAPORTE
7.13	Foreign identity documents	CL_L1_DOCUMENTO_EXTRANJERO
7.14	Bank account	CL_L1_CUENTA_BANCARIA
7.15	Payment card	CL_L1_TARJETA
7.16	IP address	CL_L1_IP
7.17	Device identifiers	CL_L1_DISPOSITIVO
7.18	Vehicle plate	CL_L1_PATENTE
7.19	Chassis and engine numbers	CL_L1_VEHICULO_ID
7.20	Contract and policy numbers	CL_L1_NUMERO_CONTRATO
7.21	Username and social profiles	CL_L1_USUARIO_RRSS
7.22	Passwords and secrets	CL_L1_CREDENCIAL
7.23	Geolocation	CL_L1_GEOLOCALIZACION
7.24	Free text	CL_L1_TEXTO_LIBRE

PART 8 · QUASI-IDENTIFIERS

8.1	Date of birth	CL_L2_FECHA_NACIMIENTO
8.2	Year of birth	CL_L2_ANIO_NACIMIENTO
8.3	Age	CL_L2_EDAD
8.4	Personal event dates	CL_L2_FECHA_EVENTO
8.5	Sex	CL_L2_SEXO
8.6	Comuna	CL_L2_COMUNA
8.7	Comuna code	CL_L2_CODIGO_COMUNA
8.8	Postal code	CL_L2_CODIGO_POSTAL
8.9	Nationality	CL_L2_NACIONALIDAD
8.10	Marital status	CL_L2_ESTADO_CIVIL
8.11	Occupation and position	CL_L2_OCUPACION
8.12	Employer	CL_L2_EMPLEADOR
8.13	Education level	CL_L2_NIVEL_EDUCACIONAL
8.14	School or university	CL_L2_ESTABLECIMIENTO_EDUCACIONAL
8.15	Dependants	CL_L2_CARGAS_FAMILIARES

PART 9 · SENSITIVE DATA

9.1	Indigenous peoples and ethnic origin	CL_L3_ETNIA
9.2	Diagnoses	CL_L3_SALUD_DIAGNOSTICO
9.3	Medicines	CL_L3_SALUD_MEDICAMENTO
9.4	Clinical record numbers	CL_L3_SALUD_IDENTIFICADOR
9.5	Clinical notes	CL_L3_SALUD_TEXTO_CLINICO
9.6	Test results	CL_L3_SALUD_RESULTADO_EXAMEN
9.7	Blood group	CL_L3_SALUD_GRUPO_SANGUINEO
9.8	Disability	CL_L3_SALUD_DISCAPACIDAD
9.9	Sexual and reproductive health	CL_L3_SALUD_SEXUAL_REPRODUCTIVA
9.10	Mental health and addictions	CL_L3_SALUD_MENTAL_ADICCIONES
9.11	Biometric data	CL_L3_BIOMETRICO
9.12	Genetic profile	CL_L3_PERFIL_GENETICO
9.13	Sexual orientation	CL_L3_ORIENTACION_SEXUAL
9.14	Gender identity	CL_L3_IDENTIDAD_GENERO
9.15	Sexual life	CL_L3_VIDA_SEXUAL
9.16	Religion	CL_L3_RELIGION
9.17	Ideological convictions	CL_L3_CONVICCION_IDEOLOGICA
9.18	Political affiliation	CL_L3_AFILIACION_POLITICA
9.19	Union affiliation	CL_L3_AFILIACION_SINDICAL
9.20	Professional association	CL_L3_AFILIACION_GREMIAL

PART 10 · SOCIOECONOMIC SITUATION

10.1	Health insurance and FONASA tier	CL_L3_SOCIOEC_PREVISION_SALUD
10.2	Health plan	CL_L3_SOCIOEC_PLAN_SALUD
10.3	Registro Social de Hogares	CL_L3_SOCIOEC_RSH
10.4	Socioeconomic group	CL_L3_SOCIOEC_NIVEL
10.5	State benefits	CL_L3_SOCIOEC_BENEFICIO_SOCIAL
10.6	Debt and credit status	CL_L3_SOCIOEC_MOROSIDAD
10.7	Debt amounts	CL_L3_SOCIOEC_MONTO_DEUDA
10.8	Income and salary	CL_L3_SOCIOEC_INGRESOS
10.9	Pension fund	CL_L3_SOCIOEC_PREVISION_AFP
10.10	Pension balances	CL_L3_SOCIOEC_SALDO_PREVISIONAL
10.11	Housing situation	CL_L3_SOCIOEC_VIVIENDA
10.12	Student aid	CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS

PART 11 · CRIMINAL RECORDS

11.1	Criminal records	CL_L3_PENAL_ANTECEDENTES
11.2	Court case numbers	CL_L3_PENAL_CAUSA
12	The RUT check digit	
13	Limits	
14	Verification	
15	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Profile set and classifiers	

About this profile set

This profile set finds the personal data in a Chilean database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Ley 21.719 does not apply to anonymized data. That is why the set does not stop at direct identifiers: it also generalizes the quasi-identifiers that re-identify people in combination, and covers every sensitive category of article 2. Its domains are organized in the same layers:

- **Direct identifiers** — RUT, names, contact details, documents, accounts, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, comuna, postal code, occupation, employer and similar attributes.
- **Sensitive data** — ethnic origin, health, biometrics, sexual life, orientation and gender identity, beliefs, political, union and professional affiliation.
- **Socioeconomic situation** — FONASA tier and ISAPRE, Registro Social de Hogares, state benefits, commercial debt, income, pension fund, housing, student aid.
- **Criminal records** — convictions and court case numbers.

On a Masking Engine the set is one profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — NOMBRE , RESULTADO , CIUDAD — needs the values to agree. A column with a meaningless name (CAMP01 , OBS) is still found when its values have a recognizable shape or vocabulary.

Before masking, inventory the binary columns (BLOB, images, PDF). The algorithms of this set work on text, numbers and dates: a scanned ID card stored in a BLOB keeps its RUT readable. Report those columns as residual risk.

Ley 21.719 in brief

Ley 21.719 regulates the protection and processing of personal data and creates the Agencia de Protección de Datos Personales. Its article 2 defines as **sensitive** the data that reveal ethnic or racial origin, political, union or professional affiliation, socioeconomic situation, ideological or philosophical convictions, religious beliefs, health and human biological profile, biometric data, and sexual life, sexual orientation and gender identity.

Socioeconomic situation is a category of Chilean law: data that are ordinary elsewhere — a FONASA tier, an ISAPRE, a Registro Social de Hogares percentile, a DICOM record — are sensitive in Chile, and templates built for GDPR do not cover them.

The law takes effect on 1 December 2026. On 31 August 2026 the Government sent the Senate a bill (Boletín 18.623-07) that would move that date to 1 December 2027; check its status. The date does not change this set.

This document describes technical controls. Whether a copy of the data counts as anonymized is a legal assessment of the whole environment — its access, its retention, what else is joined to it — and not of the profile set alone.

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters:

`rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	13	30	21	6
Extended	73	132	101	72

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- RUT / RUN — CL_L1_RUT
- RUT without check digit — CL_L1_RUT_CUERPO
- RUT check digit — CL_L1_RUT_DV
- Given names — CL_L1_NOMBRE
- Surnames — CL_L1_APELLIDO
- Full name — CL_L1_NOMBRE_COMPLETO
- E-mail address — CL_L1_EMAIL
- Telephone — CL_L1_TELEFONO
- Street address — CL_L1_DIRECCION
- Address details — CL_L1_DIRECCION_COMPLEMENTO
- Identity card document number — CL_L1_NUMERO_DOCUMENTO
- Passport — CL_L1_PASAPORTE
- Date of birth — CL_L2_FECHA_NACIMIENTO

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
RUT / RUN ESSENTIAL CL_L1_RUT	COLUMN NAME DATA TYPE VALUE FORMAT	CL_RUT
RUT without check digit ESSENTIAL CL_L1_RUT_CUERPO	COLUMN NAME DATA TYPE VALUE FORMAT	CL_CM_ALFANUM
RUT check digit ESSENTIAL CL_L1_RUT_DV	COLUMN NAME DATA TYPE VALUE FORMAT	CL_RUT_DV
Given names ESSENTIAL CL_L1_NOMBRE	COLUMN NAME KNOWN VALUES	CL_NOMBRES
Surnames ESSENTIAL CL_L1_APELLIDO	COLUMN NAME KNOWN VALUES	CL_APELLIDOS
Full name ESSENTIAL CL_L1_NOMBRE_COMPLETO	COLUMN NAME KNOWN VALUES	CL_NOMBRE_COMPLETO
E-mail address ESSENTIAL CL_L1_EMAIL	COLUMN NAME DATA TYPE VALUE FORMAT	CL_EMAIL
Telephone ESSENTIAL CL_L1_TELEFONO	COLUMN NAME VALUE FORMAT	CL_TELEFONO
Street address ESSENTIAL CL_L1_DIRECCION	COLUMN NAME DATA TYPE VALUE FORMAT	CL_DIRECCION
Address details ESSENTIAL CL_L1_DIRECCION_COMPLEMENTO	COLUMN NAME	CL_CM_ALFANUM
Identity card document number ESSENTIAL CL_L1_NUMERO_DOCUMENTO	COLUMN NAME VALUE FORMAT	CL_CM_ALFANUM
Passport ESSENTIAL CL_L1_PASAPORTE	COLUMN NAME VALUE FORMAT	CL_CM_ALFANUM
Foreign identity documents CL_L1_DOCUMENTO_EXTRANJERO	COLUMN NAME	CL_CM_ALFANUM
Bank account CL_L1_CUENTA_BANCARIA	COLUMN NAME	CL_CM_ALFANUM
Payment card CL_L1_TARJETA	COLUMN NAME VALUE FORMAT	CL_TARJETA
IP address CL_L1_IP	COLUMN NAME VALUE FORMAT	CL_IP
Device identifiers CL_L1_DISPOSITIVO	COLUMN NAME VALUE FORMAT	CL_CM_ALFANUM
Vehicle plate CL_L1_PATENTE	COLUMN NAME VALUE FORMAT	CL_PATENTE
Chassis and engine numbers CL_L1_VEHICULO_ID	COLUMN NAME VALUE FORMAT	CL_CM_ALFANUM

DOMAIN	FOUND BY			ALGORITHM
Contract and policy numbers CL_L1_NUMERO_CONTRATO	COLUMN NAME			CL_CM_ALFANUM
Usernames and social profiles CL_L1_USUARIO_RRSS	COLUMN NAME			CL_CM_ALFANUM
Passwords and secrets CL_L1_CREDENCIAL	COLUMN NAME			CL_REDACTAR
Geolocation CL_L1_GEOLOCALIZACION	COLUMN NAME	VALUE FORMAT		CL_COORDENADA
Free text CL_L1_TEXTO_LIBRE	COLUMN NAME	DATA TYPE	VALUE FORMAT	CL_TEXTO_LIBRE
QUASI-IDENTIFIERS				
Date of birth ESSENTIAL CL_L2_FECHA_NACIMIENTO	COLUMN NAME	DATA TYPE		CL_FECHA_NACIMIENTO
Year of birth CL_L2_ANIO_NACIMIENTO	COLUMN NAME	DATA TYPE		CL_ANIO
Age CL_L2_EDAD	COLUMN NAME	DATA TYPE		CL_EDAD
Personal event dates CL_L2_FECHA_EVENTO	COLUMN NAME	DATA TYPE		CL_FECHA_EVENTO
Sex CL_L2_SEXO	COLUMN NAME	KNOWN VALUES		CL_SEXO
Comuna CL_L2_COMUNA	COLUMN NAME	KNOWN VALUES		CL_COMUNA
Comuna code CL_L2_CODIGO_COMUNA	COLUMN NAME	DATA TYPE	KNOWN VALUES	CL_CODIGO_COMUNA
Postal code CL_L2_CODIGO_POSTAL	COLUMN NAME	VALUE FORMAT		CL_CODIGO_POSTAL
Nationality CL_L2_NACIONALIDAD	COLUMN NAME	KNOWN VALUES		CL_NACIONALIDAD
Marital status CL_L2_ESTADO_CIVIL	COLUMN NAME	KNOWN VALUES		CL_ESTADO_CIVIL
Occupation and position CL_L2_OCUPACION	COLUMN NAME			CL_OCUPACION
Employer CL_L2_EMPLEADOR	COLUMN NAME			CL_EMPLEADOR
Education level CL_L2_NIVEL_EDUCACIONAL	COLUMN NAME	KNOWN VALUES		CL_NIVEL_EDUCACIONAL
School or university CL_L2_ESTABLECIMIENTO_EDUCACIONAL	COLUMN NAME			CL_ESTABLECIMIENTO
Dependants CL_L2_CARGAS_FAMILIARES	COLUMN NAME	DATA TYPE		CL_CANTIDAD_ACOTADA
SENSITIVE DATA				
Indigenous peoples and ethnic origin CL_L3_ETNIA	COLUMN NAME	KNOWN VALUES		CL_PUEBLO_ORIGINARIO

DOMAIN	FOUND BY		ALGORITHM
Diagnoses CL_L3_SALUD_DIAGNOSTICO	COLUMN NAME	VALUE FORMAT	CL_DIAGNOSTICO
Medicines CL_L3_SALUD_MEDICAMENTO	COLUMN NAME	KNOWN VALUES	CL_MEDICAMENTO
Clinical record numbers CL_L3_SALUD_IDENTIFICADOR	COLUMN NAME		CL_CM_ALFANUM
Clinical notes CL_L3_SALUD_TEXTO_CLINICO	COLUMN NAME	DATA TYPE	CL_TEXTO_LIBRE
Test results CL_L3_SALUD_RESULTADO_EXAMEN	COLUMN NAME		CL_CM_ALFANUM
Blood group CL_L3_SALUD_GRUPO_SANGUINEO	COLUMN NAME	KNOWN VALUES	CL_GRUPO_SANGUINEO
Disability CL_L3_SALUD_DISCAPACIDAD	COLUMN NAME	KNOWN VALUES	CL_DISCAPACIDAD
Sexual and reproductive health CL_L3_SALUD_SEXUAL_REPRODUCTIVA	COLUMN NAME		CL_CATEGORIA_SUPRIMIDA
Mental health and addictions CL_L3_SALUD_MENTAL_ADICCIONES	COLUMN NAME		CL_CATEGORIA_SUPRIMIDA
Biometric data CL_L3_BIOMETRICO	COLUMN NAME	DATA TYPE	CL_REDACTAR
Genetic profile CL_L3_PERFIL_GENETICO	COLUMN NAME		CL_REDACTAR
Sexual orientation CL_L3_ORIENTACION_SEXUAL	COLUMN NAME	KNOWN VALUES	CL_ORIENTACION_SEXUAL
Gender identity CL_L3_IDENTIDAD_GENERO	COLUMN NAME	KNOWN VALUES	CL_IDENTIDAD_GENERO
Sexual life CL_L3_VIDA_SEXUAL	COLUMN NAME		CL_CATEGORIA_SUPRIMIDA
Religion CL_L3_RELIGION	COLUMN NAME	KNOWN VALUES	CL_RELIGION
Ideological convictions CL_L3_CONVICCION_IDEOLOGICA	COLUMN NAME	KNOWN VALUES	CL_IDEOLOGIA
Political affiliation CL_L3_AFILIACION_POLITICA	COLUMN NAME	KNOWN VALUES	CL_PARTIDO_POLITICO
Union affiliation CL_L3_AFILIACION_SINDICAL	COLUMN NAME		CL_CATEGORIA_SUPRIMIDA
Professional association CL_L3_AFILIACION_GREMIAL	COLUMN NAME		CL_CATEGORIA_SUPRIMIDA
SOCIOECONOMIC SITUATION			
Health insurance and FONASA tier CL_L3_SOCIOEC_PREVISION_SALUD	COLUMN NAME	KNOWN VALUES	CL_PREVISION_SALUD
Health plan CL_L3_SOCIOEC_PLAN_SALUD	COLUMN NAME		CL_CM_ALFANUM
Registro Social de Hogares CL_L3_SOCIOEC_RSH	COLUMN NAME		CL_RSH

DOMAIN	FOUND BY		ALGORITHM
Socioeconomic group CL_L3_SOCIOEC_NIVEL	COLUMN NAME	KNOWN VALUES	CL_NIVEL_SOCIOECONOMICO
State benefits CL_L3_SOCIOEC_BENEFICIO_SOCIAL	COLUMN NAME	KNOWN VALUES	CL_BENEFICIO_SOCIAL
Debt and credit status CL_L3_SOCIOEC_MOROSIDAD	COLUMN NAME		CL_MOROSIDAD
Debt amounts CL_L3_SOCIOEC_MONTO_DEUDA	COLUMN NAME	DATA TYPE	CL_MONTO_DEUDA
Income and salary CL_L3_SOCIOEC_INGRESOS	COLUMN NAME	DATA TYPE	CL_MONTO_INGRESO
Pension fund CL_L3_SOCIOEC_PREVISION_AFP	COLUMN NAME	KNOWN VALUES	CL_AFP
Pension balances CL_L3_SOCIOEC_SALDO_PREVISIONAL	COLUMN NAME	DATA TYPE	CL_MONTO_PREVISIONAL
Housing situation CL_L3_SOCIOEC_VIVIENDA	COLUMN NAME	KNOWN VALUES	CL_VIVIENDA
Student aid CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS	COLUMN NAME	KNOWN VALUES	CL_FINANCIAMIENTO_ESTUDIOS
CRIMINAL RECORDS			
Criminal records CL_L3_PENAL_ANTECEDENTES	COLUMN NAME		CL_ANTECEDENTES
Court case numbers CL_L3_PENAL_CAUSA	COLUMN NAME	VALUE FORMAT	CL_CM_ALFANUM

Direct identifiers

Data that identify a person on their own. Masking them is necessary but not enough: the next parts matter as much.

7.1 RUT / RUN

CL_L1_RUT

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

STRING ALGORITHM CHAIN

WHAT IT IS

The national identification number of a person (RUN) and the tax number of a person or company (RUT), with its check digit: 12.345.678-5 , 12345678-5 , 9075310K . The central identifier of any Chilean database.

HOW IT IS FOUND

COLUMN NAME

CL_L1_RUT - Path

80%

rutrunr_u_trol?unico?(tributario|nacional)?n(ro|um|umero)?_?rutrut?(cli|pac|emp|afil|benef|tit|prov|func|trab|usu|pers|cte|contr|deud|aval|repr|alum|est|pro|med|cond|prop|aseg)[a-z]*rutcli[a-z]*rutpac[a-z]*tax_?idid_?tributario

DATA TYPE

CL_L1_RUT - Type

Accepts text (length 7 or more); any other type rules the domain out.

VALUE FORMAT

CL_L1_RUT - Regex

PATTERN	STRENGTH	NOTES
\d{1,2}\.\d{3}\.\d{3}-[\dkK]		100%
\d{7,8}-[\dkK]		95%
\d{6,8}[\dkK]		90%
\d{3}\.\d{3}-[\dkK]		80%

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The body is masked and the check digit recomputed, so every masked RUT is valid — K included — and keeps its format. The mapping is one-to-one: a RUT used as a key cannot collide with another. Text that is not a RUT is masked character by character. See *The RUT check digit*.

CL_RUT STRING ALGORITHM CHAIN

Applies CL_RUT_PASO_1 → CL_RUT_PASO_2 , in this order.

CL_RUT_PASO_1

REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_RUT_CUERPO_8

CHECK DIGIT

Masks the digits with CL_CM_ALFANUM and recomputes a modulus 11 check digit with weights 4 6 8 10 1 3 4 6 from the right.

CL_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_RUT_CUERPO_7

CHECK DIGIT

Masks the digits with CL_CM_ALFANUM and recomputes a modulus 11 check digit with weights 4 6 8 10 1 3 4 from the right.

CL_RUT_CUERPO_6

CHECK DIGIT

Masks the digits with CL_CM_ALFANUM and recomputes a modulus 11 check digit with weights 4 6 8 10 1 3 from the right.

CL_RUT_PASO_2 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_RUT_DV_8 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 from the right.

CL_SIN_CAMBIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CL_RUT_DV_7 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 from the right.

CL_RUT_DV_6 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 from the right.

EXAMPLES

VALUE		MASKED
12.345.678-5	→	46.916.122-6
9.075.310-K	→	9.509.079-6
7654321-6	→	9531739-1

7.2 RUT without check digit

CL_L1_RUT_CUERPO

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The RUT body stored on its own, usually as a number, with the check digit in another column.

HOW IT IS FOUND

COLUMN NAME CL_L1_RUT_CUERPO - Path

85% rut?(num|nro|numero|cuerpo|sin?dv|sdv|base|n) n(ro|um)?_?rut?sin?dv rutnum rut?sin? digito

60% rut run

DATA TYPE CL_L1_RUT_CUERPO - Type

Accepts number (length 5 to 10) or text (length 5 to 10); any other type rules the domain out.

VALUE FORMAT CL_L1_RUT_CUERPO - Regex

PATTERN	STRENGTH	NOTES
\d{1,2}\.?\d{3}\.?\d{3}		40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The digits are mapped exactly like the body of a full RUT, so a person keeps the same masked body whether the RUT is stored whole or split.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345678	→	46916122

7.3 RUT check digit

CL_L1_RUT_DV

- ESSENTIAL
- COLUMN NAME
- DATA TYPE
- VALUE FORMAT
- SECURE LOOKUP

WHAT IT IS

The check digit (0 to 9 or K) stored in its own column.

HOW IT IS FOUND

COLUMN NAME

CL_L1_RUT_DV – Path

90%

dv d_v digito_?verificador dig_?verif(icador)? dig_?ver dv_?(rut|run) (rut|run)?dv

dvrut rutdv check_?digit

DATA TYPE

CL_L1_RUT_DV – Type

Accepts text (length up to 2) or number (length up to 2); any other type rules the domain out.

VALUE FORMAT

CL_L1_RUT_DV – Regex

PATTERN	STRENGTH	NOTES
[\\dkK]		30%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a check digit chosen by hash. The column cannot see the body, so the pair body + check digit is no longer valid; where the application validates it, mask the concatenated RUT instead.

CL_RUT_DV SECURE LOOKUP

Replaces the value with one of the 11 values in `cl-digito-verificador.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
K	→	9

7.4 Given names

CL_L1_NOMBRE

- ESSENTIAL
- COLUMN NAME
- KNOWN VALUES
- REGEX DECOMPOSE

WHAT IT IS

First and middle names (NOMBRES , PRIMER_NOMBRE), including the social name of Ley 21.120.

HOW IT IS FOUND

COLUMN NAME

CL_L1_NOMBRE – Path

85%

primer_?nombre segundo_?nombre nombres_?pila nombre_?social first_?name given_?

names? fname name_?first middle_?name nombre[12] nombres (except when followed by list E1)

50%

nombre (except when followed by list E2) nomb? (except when followed by list E3) name (except when followed by list E4)

KNOWN VALUES CL_L1_NOMBRE – List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-nombres.txt	229	70%	María, Maria, José, Jose, Juan, Luis

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word is replaced by a Chilean given name, keeping the capitalization. Accents do not change the choice, so José and JOSE mask alike.

CL_NOMBRES **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_NOMBRE_PILA **NAME**

Replaces the name with one of the 189 names in cl-nombres.txt .

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María José	→	Waldo Sebastián
JUAN	→	EMILIANO

7.5 Surnames

CL_L1_APELLIDO

ESSENTIAL **COLUMN NAME** **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Paternal and maternal surnames, together or in separate columns.

HOW IT IS FOUND

COLUMN NAME CL_L1_APELLIDO – Path

85% apellidos? apellido?(paterno|materno|pat|mat|uno|dos|[12]) ape?(pat|mat|paterno|materno|[12]) apeat apemat appat apmat ap?(pat|mat|paterno|materno) a?paterno a?materno paterno materno last_?name surname lname family_?name second_?last_?name mother_?last_?name

KNOWN VALUES CL_L1_APELLIDO – List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-apellidos.txt	245	70%	González, Gonzalez, Muñoz, Munoz, Rojas, Díaz

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word is replaced by a Chilean surname — the list includes Mapuche, Aymara and Rapa Nui surnames.

CL_APELLIDOS **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_APELLIDO **NAME**

Replaces the name with one of the 194 names in cl-apellidos.txt .

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

Muñoz Rojas

MASKED

→

Navarrete Lara

7.6 Full name

CL_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

A person's whole name in one column: holders, patients, customers, emergency contacts, legal representatives.

HOW IT IS FOUND

COLUMN NAME

CL_L1_NOMBRE_COMPLETO - Path

90%

nombre?(completo|compl|full) nombres?_?y_?apellidos? nombres?_?apellidos?
nombreaellido nom_completo nomcompleto nombrecompleto full_name fullname person_
name customer_name employee_name patient_name nombre_
(cliente|cli|paciente|pac|trabajador|trab|funcionario|func|alumno|estudiante|afiliado|benefici
ario|titular|madre|padre|tutor|apoderado|conyuge|pareja|medico|doctor|profesional|responsable|
contacto|emergencia|aval|codeudor|deudor|remitente|destinatario|receptor|firmante|testigo|repr
esentante|propietario|arrendatario|asegurado|contratante|victima|denunciante|imputado|socio|do
nante|heredero|causante|persona|pers|conductor|chofer|vendedor|ejecutivo|agente|empleado|colab
orador)

60%

titular beneficiario contacto_emergencia conyuge apoderado tutor_legal
representante_legal paciente victima asegurado contratante razon_social_persona

50%

nombre (except when followed by list E2) name (except when followed by list E4)

KNOWN VALUES

CL_L1_NOMBRE_COMPLETO - List

LIST

VALUES

STRENGTH

FIRST VALUES

cl-detectar-nombres.txt

229

60%

María, Maria, José, Jose, Juan, Luis

cl-detectar-apellidos.txt

245

60%

González, Gonzalez, Muñoz, Munoz, Rojas, Díaz

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Follows the Chilean order — given names, then paternal and maternal surname — so Juan Carlos Pérez González gets two given names and two surnames. The form APELLIDOS, NOMBRES is recognized too; values of six words or more are masked character by character.

CL_NOMBRE_COMPLETO

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_APELLIDOS

REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_APELLIDO

NAME

Replaces the name with one of the 194 names in cl-apellidos.txt .

CL_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_NOMBRES **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: **CL_CM_ALFANUM**.

CL_NOMBRE_PILA **NAME**

Replaces the name with one of the 189 names in `cl-nombres.txt`.

EXAMPLES

VALUE		MASKED
Juan Carlos Pérez González	→	Emiliano Lissette Salas Bello
GONZÁLEZ ROJAS, ANA MARÍA	→	BELLO LARA, ARIEL WALDO

7.7 E-mail address

CL_L1_EMAIL

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

COLUMN NAME CL_L1_EMAIL - Path

85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electronico)?[a-z0-9_]*` `casilla(_?electronica)?` `email_?address`

DATA TYPE CL_L1_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT CL_L1_EMAIL - Regex

PATTERN	STRENGTH	NOTES
<code>[A-Za-z0-9._%+'\"-]+@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}</code>	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Name and domain are mapped character by character, so distinct addresses stay distinct, and the top-level domain becomes `.test`, reserved for testing; a masked address can never receive mail.

CL_EMAIL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **CL_CM_ALFANUM**.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
juan.perez@gmail.com	→	ñsel.veuah@mlbxx.test

7.8 Telephone

CL_L1_TELEFONO

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Mobile and landline numbers in the usual formats: `+56 9 8765 4321`, `987654321`, `(2) 2345 6789`.

HOW IT IS FOUND

COLUMN NAME CL_L1_TELEFONO - Path

85% tel telefono[a-z0-9]* tel[eé]fono fono[a-z0-9]* celular[a-z0-9]* cel movil
m[oó]vil whatsapp wsp fax phone[a-z0-9]* mobile cellphone n(ro|um)?tel(efono)?
telef tlf tfno anexo

VALUE FORMAT CL_L1_TELEFONO - Regex

PATTERN	STRENGTH	NOTES
(\+?56[\s-]?)?9[\s-]?\d{4}[\s-]?\d{4}	90%	
(\+?56[\s-]?)?\((?([3-7]\d)\)?[\s-]?\d{3,4}[\s-]?\d{4}	70%	
\+?\d[\d\s()\-]{7,15}	30%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The country code, the mobile 9 and the area code stay; the subscriber digits are masked. The number keeps its format and still looks Chilean.

CL_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
+56 9 8765 4321	→ +56 9 3134 0400
(2) 2345 6789	→ (2) 8099 7290

7.9 Street address

CL_L1_DIRECCION

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT SECURE LOOKUP

WHAT IT IS

Street, number and apartment written in one column.

HOW IT IS FOUND

COLUMN NAME CL_L1_DIRECCION - Path

80% direccion[a-z]* (except when followed by list E5) direcci[oó]n dir domicilio[a-z]* calle
avenida pasaje address (except when preceded by mac , ip , e_?mail , web , url) street addr (except when
preceded by mac , ip , e_?mail , web , url) dir_
(particular|comercial|laboral|envio|despacho|facturacion|cliente|paciente|trabajo)
residencia villa poblacion lugar?residencia home?address

DATA TYPE CL_L1_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT CL_L1_DIRECCION - Regex

PATTERN	STRENGTH	NOTES
(?i)(av(enida)?\.? calle pasaje psje\.? pje\.? camino diagonal villa poblaci[ó]n block)\s+\d+.*	80%	
[A-Za-zÁÉÍÓÚÑáéíóúñ'\.s]{4,}\s#\d{1,5}(\s*,?\s* (depto dpto dep of oficina casa block)\.?\s*\w+)?	40%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Replaced by a fictitious Chilean address from a list of 3,000 built from street names common in Chile, house numbers and apartments.

CL_DIRECCION **SECURE LOOKUP**

Replaces the value with one of the 3,000 values in `cl-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Av. Providencia 1234, depto 502	→ Calle Lord Cochrane 13401, depto 208

7.10 Address details

CL_L1_DIRECCION_COMPLEMENTO

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

Apartment, block, tower, house or lot number kept apart from the street.

HOW IT IS FOUND

COLUMN NAME CL_L1_DIRECCION_COMPLEMENTO - Path

70% depto dpto n(ro|um)?depto block torre casa?(num|nro) n(ro|um|umero)?casa
n(ro|um|umero)?domicilio numeracion n(ro|um|umero)?calle house?number apartment
apt unit?number lote sitio parcela manzana

HOW IT IS MASKED

Characters are mapped within their kind: digits to digits, letters to letters.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
Block B 402	→ Fxsft F 299

7.11 Identity card document number

CL_L1_NUMERO_DOCUMENTO

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The document number of the cédula de identidad — different from the RUN, often forgotten, and enough on its own to identify the card and its holder.

HOW IT IS FOUND

COLUMN NAME	CL_L1_NUMERO_DOCUMENTO – Path	
85%	(n(ro um umero)?_?)?serie_(ci cedula carnet documento identidad)? serie_ci n(ro um umero)?serie folio_(ci cedula carnet) n(ro um umero)?(de_)?documento_? (identidad ci cedula) n(ro um umero)?(cedula carnet ci) document_number	
60%	n(ro um umero)?(de_)?(documento doc) documento_identidad cedula carnet	
VALUE FORMAT	CL_L1_NUMERO_DOCUMENTO – Regex	
PATTERN	STRENGTH	NOTES
\d{3}\.\d{3}\.\d{3}		50%
[A-Za-z]\d{9}		40%
A value that matches none counts 30% against the domain.		

HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
123.456.789	→ 110.858.568

7.12 Passport

CL_L1_PASAPORTE

ESSENTIAL COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

Chilean and foreign passport numbers.

HOW IT IS FOUND

COLUMN NAME	CL_L1_PASAPORTE – Path		
85%	pasaporte[a-z_]* passport[a-z_]* n(ro um umero)?pasaporte pasap		
VALUE FORMAT	CL_L1_PASAPORTE – Regex		
PATTERN	STRENGTH	NOTES	
[A-Za-z]{1,2}\d{6,9}		30%	
A value that matches none counts 30% against the domain.			

HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
F12345678	→ E92994949

7.13 Foreign identity documents

CL_L1_DOCUMENTO_EXTRANJERO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

DNI, foreign identity cards, visa and residence permit numbers.

HOW IT IS FOUND

COLUMN NAME CL_L1_DOCUMENTO_EXTRANJERO - Path

80% dni doc_?extranjero documento_?extranjero id_?extranjero cedula_?extranjera
n(ro|um|umero)?_identificacion identificacion_?extranjera ci_?extranjera nie n(ro|um)?
visa permiso_?residencia residencia_?definitiva id_?nacional national_?id

HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AB1234567	→	CA5960766

7.14 Bank account

CL_L1_CUENTA_BANCARIA

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Checking, vista (CuentaRUT included) and savings account numbers.

HOW IT IS FOUND

COLUMN NAME CL_L1_CUENTA_BANCARIA - Path

85% cuenta_?(corriente|vista|rut|bancaria|banco|ahorro|deposito|abono|pago|destino|origen|cte)
cta_?(cte|corriente|vista|bancaria|banco|ahorro) ctacte n(ro|um|umero)?_?cuenta(_?
(banco|bancaria|corriente|vista))? account_?(number|no|num|nbr) bank_?account

HOW IT IS MASKED

Digits are mapped to digits, keeping the length and the separators.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
00-123-45678-09	→	39-934-05312-87

7.15 Payment card

CL_L1_TARJETA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, with or without spaces.

HOW IT IS FOUND

COLUMN NAMECL_L1_TARJETA – Path

85%tarjeta(_?(credito|debito|cred|deb|num|nro|numero))?n(ro|um|umero)?tarjetapancard_?(number|no|num)credit_?cardcc_?(number|num)tdctc_?num

VALUE FORMATCL_L1_TARJETA – Regex

PATTERN	STRENGTH	NOTES
\d{13,19}	90%	LUHN check digit; after removing [\s\~]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another number that still passes the Luhn check. Values that are not shaped like a card are left as they are.

CL_TARJETA **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CL_TARJETA_LUHN **PAYMENT CARD**

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE	MASKED
4111 1111 1111 1111	→ 1568 3266 2522 9084

7.16 IP address

CL_L1_IP

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses — personal data when they relate to a person.

HOW IT IS FOUND

COLUMN NAMECL_L1_IP – Path

85%ipip_?(address|addr|origen|destino|cliente|usuario|remota|publica|privada|acceso|conexion|login)direccion_?ipdir_?ipip[46]remote_?addrclient_?iphost_?ip

VALUE FORMATCL_L1_IP – Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)	100%	
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to a value from 1 to 254, so the address stays valid; IPv6 hex digits are mapped to hex digits.

CL_IP **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

CL_OCTETO **NUMERIC MAPPING**

Maps the number to another between 1 and 254.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

200.27.1.10

MASKED

→ 146.92.9.16

7.17 Device identifiers

CL_L1_DISPOSITIVO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, device and advertising identifiers, cookie and session identifiers.

HOW IT IS FOUND

COLUMN NAME

CL_L1_DISPOSITIVO - Path

80%

imei imsi iccid mac mac_address direccion_mac device_id id_dispositivo
dispositivo_id uuid_dispositivo advertising_id idfa gaid cookie(_id)? session_
id id_sesion fingerprint_dispositivo serial_equipo n(ro|um)_serie_equipo

VALUE FORMAT

CL_L1_DISPOSITIVO - Regex

PATTERN

([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}

STRENGTH

100%

NOTES

\d{15}

80%

LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Characters are mapped within their kind; hex letters stay hex, so a MAC address remains well formed.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

3c:22:fb:9a:10:e4

MASKED

→ 5e:83:bb:3c:31:f9

7.18 Vehicle plate

CL_L1_PATENTE

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The Placa Patente Única in its formats: BBBB·10 since 2007, AA·1000 before it, and motorcycle plates.

HOW IT IS FOUND

COLUMN NAME

CL_L1_PATENTE - Path

85%

patente(_?(vehiculo|auto|unica|nro|num))? placa(_?patente)? ppu matricula_
(vehiculo|auto) license_plate plate(_?number)? n(ro|um)_patente

VALUE FORMAT CL_L1_PATENTE – Regex

PATTERN	STRENGTH	NOTES
[BCDFGHJKLPRSTVWXYZ]{4}[\s\.\-]?[d]{2}		100%
[A-Z]{2}[\s\.\-]?[d]{2}[\s\.\-]?[d]{2}		60%
[BCDFGHJKLPRSTVWXYZ]{3}[\s\.\-]?[d]{2}		60%
[BCDFGHJKLPRSTVWXYZ]{4,5}[\s\.\-]?[d]		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Consonants map to consonants and digits to digits, so a masked plate uses only the letters Chilean plates allow.

CL_PATENTE **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
BBCD-12	→ TYRP-90

7.19 Chassis and engine numbers

CL_L1_VEHICULO_ID

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

VIN, chassis and engine numbers, which lead to the owner through the vehicle registry.

HOW IT IS FOUND

COLUMN NAME CL_L1_VEHICULO_ID – Path

80% vin chasis n(ro|um|umero)?chasis n(ro|um|umero)?motor serie_?motor vin_?number

VALUE FORMAT CL_L1_VEHICULO_ID – Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NPR-Z0-9]{17}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
9BwZZZ377VT004251	→ 4BJKZX984KÑ862547

7.20 Contract and policy numbers

CL_L1_NUMERO_CONTRATO

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Contract, insurance policy, credit operation, member and customer numbers that point to one person.

HOW IT IS FOUND

COLUMN NAME CL_L1_NUMERO_CONTRATO – Path

70% contrato n(ro|um|umero)?contrato p[oó]liza n(ro|um|umero)?poliza n(ro|um)?operacion
operacion?credito n(ro|um)?credito n(ro|um|umero)?socio n(ro|um|umero)?cliente
cod(igo)?_?cliente n(ro|um|umero)?afiliado folio?(contrato|poliza|credito) n(ro|um)?
siniestro n(ro|um)?beneficiario n(ro|um)?matricula matricula?alumno n(ro|um)?
carnet?(socio|afiliado)

HOW IT IS MASKED

Characters are mapped within their kind. The same number masks the same way in every table and system, so relations between them survive.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
POL-123456	→ GMM-500388

7.21 Usernames and social profiles

CL_L1_USUARIO_RRSS

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Logins, aliases and social network handles.

HOW IT IS FOUND

COLUMN NAME CL_L1_USUARIO_RRSS – Path

70% usuario username user?name login nick(name)? alias cuenta?usuario usr facebook
instagram twitter tiktok linkedin red?social perfil?
(facebook|instagram|twitter|linkedin) skype telegram handle

HOW IT IS MASKED

Characters are mapped within their kind.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
@maria_munoz	→ @ycxgd_hsmxs

7.22 Passwords and secrets

CL_L1_CREDENCIAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Passwords, password hashes, PINs, tokens, API keys and security answers — which should not be in a non-production copy at all.

HOW IT IS FOUND

COLUMN NAME CL_L1_CREDENCIAL - Path

90% password passwd pwd pass contrasen[aa] contraseña clave[a-z]* (except when followed by list E6)
pin hash_?password password_?hash secret token_?acceso access_?token refresh_?token
api_?key otp respuesta_?secreta pregunta_?secreta

HOW IT IS MASKED

Every character is replaced by X .

CL_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
Secreta#2024	→ XXXXXXXXXXXX

7.23 Geolocation

CL_L1_GEOLOCALIZACION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude, longitude and coordinate pairs.

HOW IT IS FOUND

COLUMN NAME CL_L1_GEOLOCALIZACION - Path

85% lat latitud latitude lon lng longitude coordenadas? coord_?[xy] geo_
(lat|lon|lng|loc|localizacion|posicion) geolocalizacion ubicacion_?gps gps posicion_
gps

50% longitud long

VALUE FORMAT CL_L1_GEOLOCALIZACION - Regex

PATTERN	STRENGTH	NOTES
-?\d{1,2}\.\d{3,}\s*,\s*-\d{1,3}\.\d{3,}	90%	
-(1[7-9] [2-5]\d)\.\d{3,}	70%	
-(6[6-9] 7\d 8[01] 109)\.\d{3,}	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and the first decimal stay — about 11 km — and the remaining decimals are masked: the place is generalized, not moved to another region.

CL_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

-33.448891,-70.669265

→

-33.438766,-70.677404

7.24 Free text

CL_L1_TEXT0_LIBRE

COLUMN NAME

DATA TYPE

VALUE FORMAT

FREE TEXT REDACTION

WHAT IT IS

Observations, comments and descriptions where people write RUTs, e-mails, phone numbers and names.

Found by the column name, or by identifiers inside the text.

HOW IT IS FOUND

COLUMN NAME

CL_L1_TEXT0_LIBRE - Path

60%

observaciones? obs comentarios? glosa notas? detalle descripcion_
(caso|reclamo|incidente|solicitud|problema|atencion) texto_?libre mensaje reclamo
consulta_?texto motivo_?(texto|detalle) narrativa relato resumen_?caso remarks
comments? notes? free_?text memo

DATA TYPE

CL_L1_TEXT0_LIBRE - Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT

CL_L1_TEXT0_LIBRE - Regex

PATTERN

STRENGTH

NOTES

\d{1,2}\.\d{3}\.\d{3}-[\dkK]

70% anywhere in the value

[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}

70% anywhere in the value

(\\+?56\\s?)?9\\s?\\d{4}\\s?\\d{4}

50% anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

RUTs, e-mails, phone numbers written without spaces, plates, card numbers and IP addresses become

[DAT0] ; given names and surnames from the lists become [NOMBRE] . The rest of the text stays readable.

CL_TEXT0_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with [DAT0] , and the 948 terms of cl-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE

MASKED

Cliente Soto, RUT 12.345.678-5, correo
p.soto@gmail.com, fono 987654321.

→

Cliente [NOMBRE], RUT [DAT0], correo [DAT0],
fono [DAT0].

Quasi-identifiers

Data that identify no one alone but do in combination: birth date, sex and comuna single out most people, and Chile has many comunas of a few thousand inhabitants. These attributes are generalized or shifted rather than replaced, so the data keep their analytical value.

8.1 Date of birth

CL_L2_FECHA_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The most important quasi-identifier: with sex and comuna, it re-identifies a large share of the population.

HOW IT IS FOUND

COLUMN NAME CL_L2_FECHA_NACIMIENTO - Path

90% fecha_?(de_?)?nac(imiento)? fec_?nac(imiento)? f_?nac(imiento|im)? fnac
fechanac(imiento)? fecnac nacimiento fch_?nac dob birth_?date date_?of_?birth
birthdate birthday cumple(a|n|ñ)os

DATA TYPE CL_L2_FECHA_NACIMIENTO - Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted by up to 60 days: enough to break the link with the person, small enough that ages and school years barely move.

CL_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

8.2 Year of birth

CL_L2_ANIO_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The year of birth stored on its own, usually as a number.

HOW IT IS FOUND

COLUMN NAME CL_L2_ANIO_NACIMIENTO - Path

90% an(i)?o_?nac(imiento)? año_?nac(imiento)? birth_?year year_?of_?birth ano_?nacim

DATA TYPE CL_L2_ANIO_NACIMIENTO - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is masked: 1985 becomes a year of the 1980s.

CL_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

8.3

Age

CL_L2_EDAD

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Age in years.

HOW IT IS FOUND

COLUMN NAME CL_L2_EDAD – Path

85% edad(?:actual|paciente|cliente|afiliado|beneficiario|ingreso|anos|años)? age anos_?edad
rango_?etario edad_?en_?anos

DATA TYPE CL_L2_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the unit is masked — 37 becomes an age in the thirties. Ages of 100 and over become 90: extreme ages identify on their own.

CL_EDAD **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

8.4

Personal event dates

CL_L2_FECHA_EVENTO

COLUMN NAME **DATA TYPE** **DATE SHIFT**

WHAT IT IS

Dates of death, marriage, hiring, dismissal, hospital admission and discharge, diagnosis, childbirth or arrest.

HOW IT IS FOUND

COLUMN NAME CL_L2_FECHA_EVENTO – Path

80% fecha_?(de_)?(defuncion|fallecimiento|muerte|matrimonio|casamiento|divorcio|ingreso_?(laboral|empresa|trabajo)|contratacion|contrato|egreso|despido|desvinculacion|renuncia|jubilacion|pension|licencia|hospitalizacion|alta_?medica|diagnostico|atencion|consulta|parto|embarazo|detencion|condena|vacunacion|cirugia|examen) fec_?(defuncion|ingreso_?laboral|egreso|contrato|alta|atencion|diagnostico) death_?date hire_?date termination_?date date_?of_?death admission_?date discharge_?date

DATA TYPE CL_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted by up to 30 days.

CL_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE

MASKED

2021-03-15

→

2021-03-05T00:00

8.5

Sex

CL_L2_SEX0

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Registered sex or gender, as a letter or a word.

HOW IT IS FOUND

COLUMN NAME CL_L2_SEX0 – Path

85% sexo(_?(biologico|registral|paciente|cliente))? sex g[eé]nero (except when followed by *identidad*, *social*, *autopercebido*) gender cod_?sexo

KNOWN VALUES CL_L2_SEX0 – List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-sexo.txt	11	50%	f, m, h, femenino, masculino, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary — F/M, H/M, Femenino/Masculino, Mujer/Hombre — so the column keeps its values. Values outside these vocabularies stay.

CL_SEX0 REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_SEX0_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-palabra.txt`, chosen by a keyed hash.

CL_SEX0_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-mujer-hombre.txt`, chosen by a keyed hash.

CL_SEX0_INGLES SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-ingles.txt` , chosen by a keyed hash.

`CL_SEX0_F_M` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-sexo-f-m.txt` , chosen by a keyed hash.

`CL_SEX0_H_M` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-sexo-h-m.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	M
Masculino	→	Femenino

8.6

Comuna

CL_L2_COMUNA

COLUMN NAME KNOWN VALUES DATA CLEANSING

WHAT IT IS

Chile has 346 comunas, many with a few thousand inhabitants: a small comuna and a birth date can point to one person.

HOW IT IS FOUND

COLUMN NAME CL_L2_COMUNA – Path

85% comuna[a-z]* nom(bre)?_?comuna municipio municipalidad localidad

60% ciudad[a-z]* city town

KNOWN VALUES CL_L2_COMUNA – List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-comunas.txt	428	90%	Arica, Camarones, Putre, General Lagos, Iquique, Alto Hospicio

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Comunas under 20,000 inhabitants (Censo 2024) become the most populous comuna of their province – or of their region, when that one is small too. Larger comunas stay. The result is still a real comuna. Names written without accents or ñ are recognized; other spellings pass unchanged.

`CL_COMUNA` **DATA CLEANSING**

Replaces each value found in `cl-comuna-generalizada.txt` (428 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Torres del Paine	→	Natales
Nunoa	→	Ñuñoa

8.7

Comuna code

CL_L2_CODIGO_COMUNA

COLUMN NAME DATA TYPE KNOWN VALUES DATA CLEANSING

WHAT IT IS

The Código Único Territorial (CUT) of the comuna, with or without the leading zero.

HOW IT IS FOUND

COLUMN NAME CL_L2_CODIGO_COMUNA – Path

85% `cod(igo)?_?comuna` `id_?comuna` `cut(_?comuna)?` `comuna_?(cod|codigo|id|cut)` `cod_?com`

DATA TYPE CL_L2_CODIGO_COMUNA – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

KNOWN VALUES CL_L2_CODIGO_COMUNA – List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detector-codigo-comuna.txt	552	50%	15101, 15102, 15201, 15202, 01101, 1101

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Generalized exactly like the comuna name.

CL_CODIGO_COMUNA **DATA CLEANSING**

Replaces each value found in `cl-codigo-comuna-generalizado.txt` (552 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE	MASKED
12402	→ 12401

8.8 Postal code

CL_L2_CODIGO_POSTAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Seven digits: the first three identify the comuna, the last four the block front.

HOW IT IS FOUND

COLUMN NAME CL_L2_CODIGO_POSTAL – Path

90% `cod(igo)?_?postal` `cp` `zip(_?code)?` `postal_?code` `codpostal` `c_?postal`

VALUE FORMAT CL_L2_CODIGO_POSTAL – Regex

PATTERN	STRENGTH	NOTES
<code>\d{7}</code>		20%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The comuna part stays and the block part becomes `0000`.

CL_CODIGO_POSTAL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM`.

`CL_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
8320123	→ 8320000

8.9 Nationality

CL_L2_NACIONALIDAD

COLUMN NAME KNOWN VALUES SECURE LOOKUP

WHAT IT IS

Nationality or country of birth — identifying where few foreigners live in a comuna.

HOW IT IS FOUND

COLUMN NAME CL_L2_NACIONALIDAD - Path

80% nacionalidad nationality pais_?(de_?)(nacimient|origen) ciudadania citizenship
country_of_birth

KNOWN VALUES CL_L2_NACIONALIDAD - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-nacionalidades.txt	48	70%	Chilena, Venezolana, Peruana, Haitiana, Colombiana, Boliviana

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the nationalities most present in Chile.

CL_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 17 values in cl-nacionalidades.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Peruana	→ Ecuatoriana

8.10 Marital status

CL_L2_ESTADO_CIVIL

COLUMN NAME KNOWN VALUES SECURE LOOKUP

WHAT IT IS

Marital status, including the acuerdo de unión civil.

HOW IT IS FOUND

COLUMN NAME CL_L2_ESTADO_CIVIL - Path

85% estado_civil est_civil ecivil marital_status civil_status situacion_conyugal

KNOWN VALUES CL_L2_ESTADO_CIVIL - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-estado-civil.txt	22	70%	soltero, soltera, casado, casada, viudo, viuda

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from the list of marital statuses.

CL_ESTADO_CIVIL SECURE LOOKUP

Replaces the value with one of the 6 values in cl-estado-civil.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Casada

→

Viudo

8.11 Occupation and position

CL_L2_OCUPACION

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Job titles and professions. A rare title — Gerente Regional Aysén — is unique in a company.

HOW IT IS FOUND

COLUMN NAME

CL_L2_OCUPACION – Path

80%

cargo (except when followed by list E7) ocupaci[oó]n profes[ió]n oficio puesto(_?trabajo)? job_
title occupation actividad_?laboral titulo_?profesional

HOW IT IS MASKED

Replaced by a generic occupation.

CL_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in cl-ocupaciones.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Gerente Regional Aysén

→

Administrativo

8.12 Employer

CL_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The company or institution a person works for.

HOW IT IS FOUND

COLUMN NAME

CL_L2_EMPLEADOR – Path

80%

empleador nombre_?empleador razon_?social_?empleador empresa_
(empleadora|trabajo|laboral) lugar_?(de_)?trabajo employer institucion_?laboral

HOW IT IS MASKED

Replaced by a fictitious employer.

CL_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 25 values in cl-empleadores.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Codelco

→

Maderas del Sur SpA

8.13 Education level

CL_L2_NIVEL_EDUCACIONAL

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Education level and years of schooling.

HOW IT IS FOUND

COLUMN NAME

CL_L2_NIVEL_EDUCACIONAL - Path

80%

nivel_?educa(cional|tivo) escolaridad nivel_?estudios education_?level grado_? academico anos_?escolaridad

KNOWN VALUES

CL_L2_NIVEL_EDUCACIONAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

cl-detectar-nivel-educacional.txt	28	60%	Sin estudios, Básica incompleta, Basica incompleta, Básica completa, Basica completa, Media incompleta
-----------------------------------	----	-----	--

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from the list of education levels.

CL_NIVEL_EDUCACIONAL

SECURE LOOKUP

Replaces the value with one of the 10 values in `cl-nivel-educacional.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Media completa

→

Media completa

8.14 School or university

CL_L2_ESTABLECIMIENTO_EDUCACIONAL

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The school, institute or university a person attends or attended.

HOW IT IS FOUND

COLUMN NAME

CL_L2_ESTABLECIMIENTO_EDUCACIONAL - Path

75%

colegio liceo escuela establecimiento_?(educacional|estudio|escolar) nombre_?(colegio|escuela|liceo) universidad casa_?de_?estudios school(_?name)? jardin_?infantil sala_?cuna

HOW IT IS MASKED

Replaced by a fictitious establishment.

CL_ESTABLECIMIENTO

SECURE LOOKUP

Replaces the value with one of the 15 values in `cl-establecimientos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Liceo Bicentenario de Excelencia

→

Escuela Básica N° 12

8.15 Dependants

CL_L2_CARGAS_FAMILIARES

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of family dependants, children or household members. Large families are rare, and therefore identifying.

HOW IT IS FOUND

COLUMN NAME CL_L2_CARGAS_FAMILIARES - Path

80% `cargas?_?familiares? n(ro|um)?_?cargas cantidad_?cargas n(ro|um|umero)?_?hijos cant_? hijos hijos integrantes_?(grupo_)?(familiar|hogar) n(ro|um)_?integrantes tamano_?hogar personas_?(en_)?hogar`

DATA TYPE CL_L2_CARGAS_FAMILIARES - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Capped at 5.

CL_CANTIDAD_ACOTADA REGEX DECOMPOSE
Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
9	→ 5

Sensitive data

The categories of article 2 letter g: ethnic origin, health and human biological profile, biometrics, sexual life, sexual orientation and gender identity, religious and ideological convictions, political, union and professional affiliation. A categorical value is replaced by another of the same category, so the column keeps a realistic content; where the values share no vocabulary, they are suppressed.

9.1 Indigenous peoples and ethnic origin

CL_L3_ETNIA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Belonging to one of the peoples recognized by Ley 19.253 — Mapuche, Aymara, Rapa Nui, Lickanantay, Quechua, Colla, Diaguita, Chango, Kawésqar, Yagán, Selk'nam — or to the Chilean Afro-descendant tribal people.

HOW IT IS FOUND

COLUMN NAME CL_L3_ETNIA - Path

90% etnia [eé]tnico origen_?[eé]tnico pueblo_?(originario|ind[ií]gena|orig) pertenencia_?(etnica|indigena|pueblo) calidad_?indigena ind[ií]gena raza race ethnicity ethnic_?group ascendencia afrodescendiente comunidad_?indigena

KNOWN VALUES CL_L3_ETNIA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-pueblos.txt	44	90%	Mapuche, Aymara, Rapa Nui, Lickanantay, Quechua, Colla

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the list; yes/no flags stay flags and numeric codes get other digits.

CL_PUEBLO_ORIGINARIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_PUEBLO_ORIGINARIO_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_PUEBLO_ORIGINARIO_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in cl-pueblos.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Mapuche-Huilliche

→

Afrodescendiente chileno

S

→

S

9.2 Diagnoses

CL_L3_SALUD_DIAGNOSTICO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Diagnoses, CIE-10 codes, GES pathologies, chronic conditions, allergies, causes of sick leave or death.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_DIAGNOSTICO - Path

85%

```
diagn[oó]stico[a-z]* diag dx cie_?10 cod(igo)?_?cie cie icd_?10 icd
patolog[ií]a[a-z]* enfermedad(es)?[a-z]* morbilidad condicion?(medica|salud|cronica)
problema?salud ges hipotesis?diagnostica causa_?
(licencia|muerte|defuncion|hospitalizacion|consulta) motivo_?
(consulta|hospitalizacion|licencia) comorbilidad(es)? antecedentes_?
(medicos|morbidos|m[oó]rbidos|clinicos) alergias? condicion?preexistente
preexistencias?
```

VALUE FORMAT

CL_L3_SALUD_DIAGNOSTICO - Regex

PATTERN

STRENGTH

NOTES

[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?

60%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

CIE-10 codes become other common codes in the same format; descriptions become generic diagnoses.

CL_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CL_DIAGNOSTICO_TEXTO

CL_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `cl-cie10-decimal.txt`, chosen by a keyed hash.

CL_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `cl-cie10.txt`, chosen by a keyed hash.

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

CL_DIAGNOSTICO_TEXTO **SECURE LOOKUP**

Replaces the value with one of the 30 values in `cl-diagnosticos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F32.9	→	J02.9
Depresión mayor	→	Tendinitis

9.3 Medicines

CL_L3_SALUD_MEDICAMENTO

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Prescribed medicines and treatments. A medicine reveals the illness: antiretrovirals, antidepressants, antipsychotics.

HOW IT IS FOUND

COLUMN NAME	CL_L3_SALUD_MEDICAMENTO - Path			
85%	medicamentos? f[aá]rmascos? principio_?activo prescripci[oó]n receta(_?medica)? tratamiento(_?farmacologico)? medication drug(_?name)? posologia			
KNOWN VALUES	CL_L3_SALUD_MEDICAMENTO - List			
LIST	VALUES	STRENGTH	FIRST VALUES	
cl-detectar- medicamentos.txt	50	70%	Paracetamol, Ibuprofeno, Losartán, Losartan, Enalapril, Metformina	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine.

CL_MEDICAMENTO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_MEDICAMENTO_LISTA .

CL_BANDERA	REGEX DECOMPOSE
	Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
CL_BANDERA_SI_NO	SECURE LOOKUP
	Replaces the value with one of the 2 values in <code>cl-bandera-si-no.txt</code> , chosen by a keyed hash.
CL_BANDERA_TRUE_FALSE	SECURE LOOKUP
	Replaces the value with one of the 2 values in <code>cl-bandera-true-false.txt</code> , chosen by a keyed hash.
CL_BANDERA_S_N	SECURE LOOKUP
	Replaces the value with one of the 2 values in <code>cl-bandera-s-n.txt</code> , chosen by a keyed hash.
CL_BANDERA_Y_N	SECURE LOOKUP
	Replaces the value with one of the 2 values in <code>cl-bandera-y-n.txt</code> , chosen by a keyed hash.
CL_BANDERA_0_1	SECURE LOOKUP
	Replaces the value with one of the 2 values in <code>cl-bandera-0-1.txt</code> , chosen by a keyed hash.
CL_CM_ALFANUM	CHARACTER MAPPING
	Maps each character to another of its group (7 groups), keeping length and format.
CL_MEDICAMENTO_LISTA	SECURE LOOKUP
	Replaces the value with one of the 26 values in <code>cl-medicamentos.txt</code> , chosen by a keyed hash.

EXAMPLES

VALUE

Sertralina 50 mg

MASKED

→ **Ácido acetilsalicílico**

9.4 Clinical record numbers

CL_L3_SALUD_IDENTIFICADOR

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Ficha clínica, clinical history, episode, attention, sick leave and biopsy numbers.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_IDENTIFICADOR - Path

85%

ficha_?clinica n(ro|um|umero)_?ficha historia_?clinica n(ro|um)_?historia nhc
n(ro|um)_?episodio n(ro|um)_?atencion folio_?(atencion|urgencia|licencia|receta)
licencia_?medica n(ro|um)_?licencia folio_?lm n(ro|um)_?interconsulta n(ro|um)_?dau
n(ro|um|umero)_?biopsia medical_?record_?number mrn

60%

ficha hc episodio

HOW IT IS MASKED

Characters are mapped within their kind; the same record number masks the same way in every table.

CL_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

HC-2024-00123

MASKED

→ **NC-2156-30782**

9.5 Clinical notes

CL_L3_SALUD_TEXTO_CLINICO

COLUMN NAME

DATA TYPE

FREE TEXT REDACTION

WHAT IT IS

Anamnesis, progress notes, discharge summaries and medical reports, where names and identifiers appear inside the text.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_TEXTO_CLINICO - Path

85%

anamnesis evoluci[oó]n(_?(medica|clinica))? epicrisis indicaciones(_?medicas)? examen_
fisico notas_?clinicas? informe_?(medico|clinico|alta) resumen_?(alta|clinico)
observacion(es)?_?(medica|clinica)s? hallazgos interconsulta historia_?enfermedad plan_
tratamiento clinical_?notes? progress_?notes?

DATA TYPE

CL_L3_SALUD_TEXTO_CLINICO - Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same redaction as free text: identifiers become [DATO] and names [NOMBRE], while the clinical content stays readable.

CL_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with [DATO], and the 948 terms of cl-texto-nombres.txt with [NOMBRE].

EXAMPLES

VALUE

Paciente Muñoz, RUT 9.075.310-K, consulta por cefalea.

MASKED

Paciente [NOMBRE], RUT [DATO], consulta por cefalea.

9.6 Test results

CL_L3_SALUD_RESULTADO_EXAMEN

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Laboratory and imaging results, HIV and COVID tests, viral load, glycemia, blood pressure, body mass index.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_RESULTADO_EXAMEN - Path

80%

```
resultado?(examen|laboratorio|lab|test|pcr|antigeno|biopsia|imagen|vih|hiv|covid)
ex[aá]menes?_(resultado|laboratorio) vih hiv carga_?viral cd4 glicemia
hemoglobina(_?glicosilada)? colesterol presion_?arterial imc test_?
(covid|embarazo|vih|drogas) lab_?result
```

50%

```
resultado examen
```

HOW IT IS MASKED

Characters are mapped within their kind: numbers stay numbers and words become other letters.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

Reactivo

MASKED

→ Pbecsnvg

9.7 Blood group

CL_L3_SALUD_GRUPO_SANGUINEO

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

ABO blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_GRUPO_SANGUINEO - Path

90%

```
grupo_?sangu[ií]neo grupo_?sang tipo_?(de_?)?sangre tipo_?sanguineo factor_?rh rh
blood_?type blood_?group
```

KNOWN VALUES CL_L3_SALUD_GRUPO_SANGUINEO - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-grupo-sanguineo.txt	28	90%	A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a blood group.

CL_GRUPO_SANGUINEO **SECURE LOOKUP**

Replaces the value with one of the 8 values in cl-grupo-sanguineo.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
0+	→ A-

9.8 Disability

CL_L3_SALUD_DISCAPACIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Type and degree of disability, disability credential, invalidity pensions, special educational needs.

HOW IT IS FOUND

COLUMN NAME CL_L3_SALUD_DISCAPACIDAD - Path

90% discapacidad[a-z]* grado_?discapacidad credencial_?discapacidad invalidez porcentaje_
invalidez rnd registro_?nacional_?discapacidad disability dependencia_
(severa|moderada|funcional) necesidades_?educativas_?especiales nee pension_?invalidez

KNOWN VALUES CL_L3_SALUD_DISCAPACIDAD - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-discapacidad.txt	20	60%	Física, Física, Visual, Auditiva, Intelectual, Psíquica

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced from the list of disability types; flags stay flags.

CL_DISCAPACIDAD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_DISCAPACIDAD_LISTA .

CL_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-discapacidad.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Psíquica severa

→

Visual

9.9 Sexual and reproductive health

CL_L3_SALUD_SEXUAL_REPRODUCTIVA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Pregnancy, voluntary interruption of pregnancy, contraception, fertility, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_SEXUAL_REPRODUCTIVA - Path

90%

embarazo embarazada gestaci[oó]n semanas_?gestacion edad_?gestacional fecha_?ultima_?
regla fur aborto ive interrupcion_?(voluntaria_)?(del_)?embarazo anticonceptivos?
metodo_?anticonceptivo fertilidad infertilidad reproduccion_?asistida paridad gestas
partos cesarea its ets infeccion_?transmision_?sexual pregnan[a-z]* contracepti[a-
z]*

HOW IT IS MASKED

Suppressed to `Sin información` ; flags and numeric codes keep their shape.

CL_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR` .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cl-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Embarazo de 12 semanas

→

Sin información

S

→

S

9.10 Mental health and addictions

CL_L3_SALUD_MENTAL_ADICCIONES

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Psychiatric and psychological conditions, suicide risk, alcohol and drug use, SENDA treatment.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SALUD_MENTAL_ADICCIONES - Path

90%

salud_?mental psiquiatri[a-z]* psicologi[a-z]* trastorno[a-z]* depresi[oó]n ansiedad
suicid[a-z]* autolesi[oó]n adicci[oó]n(es)? consumo_?(de_?)(drogas|alcohol|sustancias)
alcoholismo drogadiccion dependencia_?(alcohol|drogas) senda tratamiento_
(adicciones|drogas|alcohol) mental_?health substance_?(use|abuse)

HOW IT IS MASKED

Suppressed to Sin información ; flags and numeric codes keep their shape.

CL_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_SUPRIMIR .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in cl-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno bipolar

→

Sin información

9.11 Biometric data

CL_L3_BIOMETRICO

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Fingerprint and face templates, iris, voice, digitized signatures — when stored as text (a hash, base64).

HOW IT IS FOUND

COLUMN NAME CL_L3_BIOMETRICO – Path

90% huella(_?(dactilar|digital))? dactilar biometri[a-z]* template_
(facial|biometrico|huella) rostro reconocimiento_?facial facial_?(template|id) iris
retina voz_?(huella|biometrica) firma_?(digitalizada|biometrica|manuscrita) fingerprint
face_?(id|template|encoding) palm_?print

DATA TYPE CL_L3_BIOMETRICO – Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character is replaced by X . Binary columns are out of reach of these algorithms; see *Limits*.

CL_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

A1B2C3D4E5F6

→

XXXXXXXXXXXX

9.12 Genetic profile

CL_L3_PERFIL_GENETICO

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

DNA, genotypes, genetic markers and mutations: the human biological profile of the law.

HOW IT IS FOUND

COLUMN NAME CL_L3_PERFIL_GENETICO – Path

90% adn dna genoma genotipo genetic[a-z]* gen[eé]tica secuencia_?genetica marcador_
genetico perfil_?(genetico|biologico) mutacion(_?genetica)? snp brca haplotipo
cariotipo

HOW IT IS MASKED

Every character is replaced by X .

CL_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

BRCA1 positivo

→

XXXXXXXXXXXX

9.13 Sexual orientation

CL_L3_ORIENTACION_SEXUAL

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Declared sexual orientation.

HOW IT IS FOUND

COLUMN NAME CL_L3_ORIENTACION_SEXUAL - Path

95% orientaci[oó]n_?sexual sexual_?orientation orient_?sexual

KNOWN VALUES CL_L3_ORIENTACION_SEXUAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detector-orientacion-sexual.txt	15	80%	Heterosexual, Homosexual, Lesbiana, Gay, Bisexual, Pansexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from the list of orientations; flags stay flags.

CL_ORIENTACION_SEXUAL **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_ORIENTACION_SEXUAL_LISTA .

CL_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

CL_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

CL_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

CL_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CL_ORIENTACION_SEXUAL_LISTA **SECURE LOOKUP**

Replaces the value with one of the 9 values in `cl-orientacion-sexual.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Bisexual	→ Lesbiana

9.14 Gender identity

CL_L3_IDENTIDAD_GENERO

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Gender identity, registral sex change under Ley 21.120, pronouns.

HOW IT IS FOUND

COLUMN NAMECL_L3_IDENTIDAD_GENERO – Path

95%

identidad_?(de_)?g[eé]nero

gender_identity

g[eé]nero?(identidad|social|autopercibido)

transg[eé]nero

transexual

cambio_?(de_)?sexo_?registral

rectificacion_?(de_)?sexo

pronombres?

KNOWN VALUESCL_L3_IDENTIDAD_GENERO – List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-identidad-genero.txt	18	70%	Mujer, Hombre, Mujer trans, Hombre trans, No binario, Género fluido

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from the list of gender identities; flags stay flags.

CL_IDENTIDAD_GENERO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_IDENTIDAD_GENERO_LISTA .

CL_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CL_IDENTIDAD_GENERO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in cl-identidad-genero.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Hombre trans	→ No binario

9.15 Sexual life

CL_L3_VIDA_SEXUAL

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Sexual life and behavior.

HOW IT IS FOUND

COLUMN NAME	CL_L3_VIDA_SEXUAL - Path
90%	vida_?sexual conducta_?sexual actividad_?sexual parejas?_?sexuales? practicas_?sexuales sexual_?(activity behavior history) historia_?sexual comportamiento_?sexual

HOW IT IS MASKED

Suppressed to Sin información ; flags and numeric codes keep their shape.

CL_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_SUPRIMIR .

CL_BANDERA REGEX DECOMPOSE
Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.
CL_BANDERA_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.
CL_BANDERA_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.
CL_BANDERA_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.
CL_BANDERA_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.
CL_BANDERA_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.
CL_CM_ALFANUM CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.
CL_SUPRIMIR SECURE LOOKUP
Replaces the value with one of the 1 values in cl-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Activa	→ Sin información

9.16 Religion

CL_L3_RELIGION

COLUMN NAME	KNOWN VALUES	REGEX DECOMPOSE
-------------	--------------	-----------------

WHAT IT IS

Religion, creed or church.

HOW IT IS FOUND

COLUMN NAME	CL_L3_RELIGION - Path
95%	religi[oó]n[a-z]* credo confesion_?religiosa culto iglesia creencia_?religiosa religious_?affiliation denominacion_?religiosa comunidad_?religiosa

KNOWN VALUES		CL_L3_RELIGION - List	
LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-religiones.txt	50	90%	Católica, Catolica, Evangélica o protestante, Evangelica o protestante, Testigo de Jehová, Testigo de Jehova

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the categories of the Censo 2024.

CL_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_RELIGION_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in cl-religiones.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Evangélica	→ Budista

9.17 Ideological convictions

CL_L3_CONVICCION_IDEOLOGICA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Ideology, political position and philosophical convictions.

HOW IT IS FOUND

COLUMN NAME CL_L3_CONVICCION_IDEOLOGICA - Path

90% ideolog[ií]a convicci[oó]n(es)?(_?(ideologica|filosofica|politica)s)? posicion_?politica
postura_?politica tendencia_?politica orientacion_?politica pensamiento_?politico
creencias? filosofia_?de_?vida political_?(view|orientation|opinion)

KNOWN VALUES CL_L3_CONVICCION_IDEOLOGICA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-ideologias.txt	15	70%	Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from a list of political positions.

CL_IDEOLOGIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_IDEOLOGIA_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_IDEOLOGIA_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in cl-ideologias.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Centroderecha	→ Sin identificación política

9.18 Political affiliation

CL_L3_AFILIACION_POLITICA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Party membership, militancy and political coalition.

HOW IT IS FOUND

COLUMN NAME CL_L3_AFILIACION_POLITICA - Path

95% partido(_?pol[í]tico)? militancia militante afiliaci[oó]n?
(politica|partidaria|partido) afiliado_?partido political_?party party_?affiliation
coalici[oó]n sector_?politico

KNOWN VALUES CL_L3_AFILIACION_POLITICA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-partidos.txt	52	80%	Partido Demócrata Cristiano, Partido Demócrata Cristiano, Partido por la Democracia, Partido Radical de Chile, Partido Socialista de Chile, Federación Regionalista Verde Social

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a legally constituted party (Servel) or Independiente .

CL_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_PARTIDO_POLITICO_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

`CL_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`CL_PARTIDO_POLITICO_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 15 values in `cl-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Renovación Nacional

→ **Partido de la Gente**

9.19 Union affiliation

`CL_L3_AFILIACION_SINDICAL`

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Union membership, union dues and union leadership.

HOW IT IS FOUND

COLUMN NAME

`CL_L3_AFILIACION_SINDICAL` - Path

95%

`sindicato[a-z]*` `sindical` `sindicalizado` `afiliaci[oó]n?sindical` `socio?sindicato`
`cuota?sindical` `dirigente?sindical` `federacion?sindical` `union?member(ship)?` `trade?`
`union` `negociacion?colectiva`

HOW IT IS MASKED

Suppressed to `Sin información`; flags and amounts keep their shape.

`CL_CATEGORIA_SUPRIMIDA`

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_SUPRIMIR`.

`CL_BANDERA` **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

`CL_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

`CL_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

`CL_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Sindicato N°2 de Trabajadores	→	Sin información
S	→	S

9.20 Professional association

CL_L3_AFILIACION_GREMIAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Membership of professional colleges and trade associations.

HOW IT IS FOUND

COLUMN NAME

CL_L3_AFILIACION_GREMIAL - Path

90%

gremio gremial asociacion_?gremial colegio_?profesional afiliacion_?gremial
colegiatura n(ro|um)_?colegiatura colegio_?de_
(medicos|abogados|profesores|ingenieros|enfermeras|psicologos|arquitectos|contadores)
professional_?association asociacion_?(de_)?funcionarios

HOW IT IS MASKED

Suppressed to Sin información ; flags and numeric codes keep their shape.

CL_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_SUPRIMIR .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cl-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Colegio Médico de Chile	→	Sin información

Socioeconomic situation

Sensitive under Chilean law, unlike under GDPR and most foreign laws. Tiers and categories are replaced within their own notation; amounts are mapped into a plausible range with no link to the real value.

10.1 Health insurance and FONASA tier

CL_L3_SOCIOEC_PREVISION_SALUD

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The FONASA tier (A to D) reveals income directly; the ISAPRE reveals ability to pay.

HOW IT IS FOUND

COLUMN NAME	CL_L3_SOCIOEC_PREVISION_SALUD – Path		
95%	tramo_?fonasa fonasa grupo_?fonasa tramo_?salud previsi[oón]n?(de_)?salud isapre institucion?(de_)?salud_?previsional sistema?(de_)?salud seguro_?salud health_? insurance capredena dipreca		
60%	previsi[oón]n		
KNOWN VALUES	CL_L3_SOCIOEC_PREVISION_SALUD – List		
LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-prevision-salud.txt	44	80%	FONASA A, FONASA B, FONASA C, FONASA D, Isapre Banmédica, Isapre Banmedica
cl-detectar-tramo-fonasa.txt	4	30%	a, b, c, d

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A tier letter becomes another tier letter, also in FONASA B ; a named insurer becomes another from the list of FONASA tiers, ISAPREs, Capredena and Dipreca.

CL_PREVISION_SALUD REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CL_PREVISION_SALUD_LISTA .

CL_TRAMO_FONASA SECURE LOOKUP

Replaces the value with one of the 4 values in cl-tramo-fonasa.txt , chosen by a keyed hash.

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_PREVISION_SALUD_LISTA **SECURE LOOKUP**

Replaces the value with one of the 18 values in `cl-prevision-salud.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
FONASA B	→	FONASA B
Isapre Colmena	→	FONASA A

10.2 Health plan

CL_L3_SOCIOEC_PLAN_SALUD

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

ISAPRE plan codes, prices and agreed contributions.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_PLAN_SALUD – Path

85%

```
plan_?(isapre|salud|de_?salud) cod(igo)?_?plan_?(isapre|salud)? precio_?plan valor_?plan  
cotizacion_?(pactada|salud|isapre|adicional) uf_?plan excedente_?cotizacion cotizacion_  
7
```

HOW IT IS MASKED

Characters are mapped within their kind.

CL_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PLN-4521	→	KMY-3364

10.3 Registro Social de Hogares

CL_L3_SOCIOEC_RSH

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The household socioeconomic rating (tiers from 40% to 100%), and the older Ficha de Protección Social and CAS scores.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_RSH – Path

95%

```
rsh registro_?social_?(de_?)?hogares calificaci[oó]n_?socioecon[oó]mica cse tramo_  
(rsh|socioeconomico|cse|registro_?social) percentil_?(rsh|socioeconomico|vulnerabilidad)  
ficha_?proteccion_?social fps puntaje_?(fps|ficha|cas|rsh) ficha_?cas indice_  
vulnerabilidad ivm vulnerabilidad(_?social)? situacion_?socioeconomica
```

HOW IT IS MASKED

A tier becomes another tier in the same notation: 40%, Tramo 40%, 70.

CL_RSH

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

`CL_RSH_TRAMO_TEXT0` .

`CL_RSH_TRAMO_NUMERO` **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cl-rsh-tramo-numero.txt` , chosen by a keyed hash.

`CL_BANDERA` **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`CL_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

`CL_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

`CL_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

`CL_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

`CL_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

`CL_RSH_TRAMO_TEXT0` **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cl-rsh-tramo-texto.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Tramo 40%	→	Tramo 50%

10.4 Socioeconomic group

`CL_L3_SOCIOEC_NIVEL`

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Socioeconomic groups (ABC1, C2, C3, D, E), income quintiles and deciles.

HOW IT IS FOUND

COLUMN NAME `CL_L3_SOCIOEC_NIVEL` – Path

90% `nse gse grupo_?socioeconomico estrato_?socioeconomico nivel_?socioeconomico quintil(_?(de_)?ingresos)? decil(_?(de_)?ingresos)? clase_?social`

KNOWN VALUES `CL_L3_SOCIOEC_NIVEL` – List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>cl-detectar-gse.txt</code>		9	50% abc1, c1, c1a, c1b, c2, c3

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A group becomes another group; a number becomes a quintile from 1 to 5.

`CL_NIVEL_SOCIOECONOMICO` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CL_GSE` .

`CL_QUINTIL` **SECURE LOOKUP**

Replaces the value with one of the 5 values in `cl-quintil.txt` , chosen by a keyed hash.

`CL_GSE` **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cl-gse.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

C2

→

C1b

10.5 State benefits

CL_L3_SOCIOEC_BENEFICIO_SOCIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Receiving the Pensión Garantizada Universal, Subsidio Único Familiar, Bono de Invierno, Ingreso Ético Familiar, Bolsillo Familiar Electrónico and other benefits.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_BENEFICIO_SOCIAL – Path

90%

```
beneficio(s|_?social|_?estatal)? beneficiario_?
(programa|beneficio|subsidio|bono|pgu|pbs|suf) programa?(social|estatal|gobierno)
subsidio[a-z]* (except when followed by habitacional, arriendo, vivienda, ds) bono[a-z]* (except when
followed by list E8) pgu pbs aps suf ife ief ingreso_?etico_?familiar chile_?solidario
seguridades?(y_?)?oportunidades aporte_?familiar_?permanente bolsillo_?familiar
asignacion_?familiar pension?(basica|garantizada|asistencial|solidaria) pasis chile_?
cuida chile_?crece bono_?invierno junaeb pae
```

KNOWN VALUES

CL_L3_SOCIOEC_BENEFICIO_SOCIAL – List

LIST

VALUES

STRENGTH

FIRST VALUES

cl-detectar-
beneficios.txt

45

80%

Pensión Garantizada Universal, Pension Garantizada Universal, Subsidio Único Familiar, Subsidio Unico Familiar, Asignación Familiar, Asignacion Familiar

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from the list of benefits; flags stay flags and amounts keep their digits' shape.

CL_BENEFICIO_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_BENEFICIO_SOCIAL_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_BENEFICIO_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 21 values in `cl-beneficios-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

PGU

→

CHILE CRECE CONTIGO

10.6 Debt and credit status

CL_L3_SOCIOEC_MOROSIDAD

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

DICOM and Boletín Comercial records, arrears, credit scores, protests, insolvency proceedings.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_MOROSIDAD - Path

90%

```
dicom boletin_comercial morosidad moroso morosa deuda_morosa protestos? deudor_?
moroso score_(crediticio|credito|riesgo|equifax|dicom) puntaje_?
(crediticio|riesgo|credito) clasificacion_(de_)?(riesgo|crediticia|deudor) riesgo?
crediticio equifax sinacofi transunion informe_comercial cartera_vencida castigo
dias_(de_)?mora tramo_mora estado_(deuda|credito|crediticio|morosidad) credit_score
delinquen[a-z]* repactacion renegociacion quiebra insolvencia liquidacion_voluntaria
reorganizacion_(de_)?deudor
```

HOW IT IS MASKED

Statuses are replaced from a list; scores and flags keep their shape.

CL_MOROSIDAD

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_MOROSIDAD_LISTA .

CL_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt`, chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt`, chosen by a keyed hash.

CL_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt`, chosen by a keyed hash.

CL_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt`, chosen by a keyed hash.

CL_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt`, chosen by a keyed hash.

CL_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_MOROSIDAD_LISTA

SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-estado-crediticio.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Moroso DICOM

→

Al día

650

→

807

10.7 Debt amounts

CL_L3_SOCIOEC_MONTO_DEUDA

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Debt, arrears and outstanding balances.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_MONTO_DEUDA – Path

85%

monto_?(deuda|moroso|mora|adeudado|castigado|protestado|vencido) deuda(_?
(total|vigente|vencida|consolidada))? saldo_?(deuda|adeudado|insoluto|moroso|vencido)
total_?adeudado monto_?protesto debt(_?amount)? outstanding_?balance

DATA TYPE

CL_L3_SOCIOEC_MONTO_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between \$10,000 and \$50,000,000.

CL_MONTO_DEUDA

NUMERIC MAPPING

Maps the number to another between 10,000 and 50,000,000.

EXAMPLES

VALUE

MASKED

1250000

→

5128694

10.8 Income and salary

CL_L3_SOCIOEC_INGRESOS

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Salaries, taxable income, household and per capita income, assets.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_INGRESOS – Path

85%

sueldo[a-z]* salario[a-z]* remuneraci[ó]n[a-z]* renta(_?
(imponible|liquida|bruta|mensual|anual|promedio|declarada|familiar|hogar|per_?capita))?
ingreso_?(mensual|liquido|bruto|familiar|hogar|per_?
capita|total|promedio|declarado|autonomo|laboral) ingresos(_?[a-z]+)? haberes liquido_?a_?
pagar imponible total_?haberes salary wage income gross_?pay net_?pay patrimonio
avaluo_?fiscal capacidad_?(de_?)?pago gastos_?mensuales

DATA TYPE

CL_L3_SOCIOEC_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between \$450,000 and \$8,000,000: plausible, with no link to the real value.

CL_MONT0_INGRESO NUMERIC MAPPING

Maps the number to another between 450,000 and 8,000,000.

EXAMPLES

VALUE

985000

→

MASKED

896347

10.9 Pension fund

CL_L3_SOCIOEC_PREVISION_AFP

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

AFP, IPS, Capredena and Dipreca.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_PREVISION_AFP - Path

95%

```
afp nombre_afp cod(igo)?_afp administradora?(de_)?fondos(_?de_?pensiones)?
institucion_previsional prevision_social entidad_previsional ips inp caja?(de_)?
prevision regimen_previsional sistema_previsional pension_fund
```

KNOWN VALUES

CL_L3_SOCIOEC_PREVISION_AFP - List

LIST

VALUES

STRENGTH

FIRST VALUES

cl-detectar-
afp.txt

24

90%

AFP Capital, AFP Cuprum, AFP Habitat, AFP Modelo, AFP PlanVital, AFP ProVida

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced from the list of pension institutions.

CL_AFP REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_AFP_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_AFP_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in cl-afp.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

AFP Modelo

→

AFP Habitat

10.10 Pension balances

CL_L3_SOCIOEC_SALDO_PREVISIONAL

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Individual account balances, contributions, voluntary savings (APV) and pension amounts.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_SALDO_PREVISIONAL - Path

90%

saldo_?(afp|cuenta_?individual|cotizaciones|previsional|obligatorio|apv|cuenta_?2|fondo)
fondo_?(de_?)(pensiones|previsional) cotizaci[oó]n(es)?_
(afp|previsional|obligatoria|pension) monto_?pension pension_
(monto|mensual|autofinanciada) apv apvc cuenta_?2 bono_?reconocimiento renta_
vitalicia retiro_?programado pension_?amount retirement_?balance

DATA TYPE

CL_L3_SOCIOEC_SALDO_PREVISIONAL - Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between \$100,000 and \$250,000,000.

CL_MONTO_PREVISIONAL

NUMERIC MAPPING

Maps the number to another between 100,000 and 250,000,000.

EXAMPLES

VALUE

MASKED

38500000

→

17634498

10.11 Housing situation

CL_L3_SOCIOEC_VIVIENDA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Housing tenure, allegados, overcrowding, camps and housing subsidies.

HOW IT IS FOUND

COLUMN NAME

CL_L3_SOCIOEC_VIVIENDA - Path

95%

tipo_?vivienda tenencia_?(de_?)(la_?)?vivienda situacion_?(habitacional|vivienda)
vivienda_?(propia|arrendada|cedida) allegad[oa]s? allegamiento hacinamiento campamento
toma_?terreno subsidio_?(habitacional|ds1|ds49|ds19|arriendo|vivienda) ds_?49 ds_?1
comite_?vivienda deficit_?habitacional material_?vivienda housing_?(type|tenure|status)
dividendo_?hipotecario

KNOWN VALUES CL_L3_SOCIOEC_VIVIENDA - List

LIST	VALUES	STRENGTH	FIRST VALUES
------	--------	----------	--------------

cl-detectar-vivienda.txt	19	60%	Propia pagada, Propia pagándose, Propia pagandose, Arrendada con contrato, Arrendada sin contrato, Cedida por familiar
--------------------------	----	-----	--

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced from the list of housing situations.

CL_VIVIENDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_VIVIENDA_LISTA .**CL_BANDERA** **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

CL_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

CL_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

CL_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CL_VIVIENDA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 10 values in `cl-vivienda.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
-------	--------

Allegado	→ Arrendada sin contrato
----------	---------------------------------

10.12 Student aid

CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS

COLUMN NAME**KNOWN VALUES****REGEX DECOMPOSE****WHAT IT IS**

Gratuidad, scholarships, the Crédito con Aval del Estado and the Fondo Solidario.

HOW IT IS FOUND**COLUMN NAME** CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS - Path**90%**

```
beca[a-z]*  gratuidad  credito?(cae|aval?del?estado|universitario|fscu|corfo)  cae
fscu  fuas  beneficio?estudiantil  arancel?(diferenciado|referencia)  tne  beneficio?
(mineduc|arancel)  scholarship  student?loan  financiamiento?(de?)?estudios  deuda?
(cae|universitaria)
```

KNOWN VALUES CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS - List

LIST	VALUES	STRENGTH	FIRST VALUES
cl-detectar-financiamiento-estudios.txt	28	70%	Gratuidad, Beca Bicentenario, Beca Juan Gómez Millas, Beca Juan Gomez Millas, Beca Nuevo Milenio, Beca Excelencia Académica

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced from the list of student aid.

CL_FINANCIAMIENTO_ESTUDIOS **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_FINANCIAMIENTO_ESTUDIOS_LISTA .

CL_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

CL_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

CL_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

CL_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

CL_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CL_FINANCIAMIENTO_ESTUDIOS_LISTA **SECURE LOOKUP**

Replaces the value with one of the 12 values in `cl-financiamiento-estudios.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
CAE	→ BECA PRESIDENTE DE LA REPÚBLICA

Criminal records

Data on criminal offenses, convictions and court cases, handled with the same care as sensitive data.

11.1 Criminal records

CL_L3_PENAL_ANTECEDENTES

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Convictions, offenses, criminal records, disqualifications, precautionary measures, domestic violence.

HOW IT IS FOUND

COLUMN NAME

CL_L3_PENAL_ANTECEDENTES – Path

95%

antecedentes(_?(penales|judiciales|policiales|criminales))? *(except when followed by list E9)*
certificado?antecedentes condenas? condenad[oa] delitos? tipo?delito prontuario
reincidente reincidencia imputad[oa] formalizad[oa] sentencia(_?condenatoria)? pena
privacion?(de_)?libertad libertad?condicional inhabilidad(es)? registro?(de_)?
inhabilidades inhabilitad[oa] criminal?record conviction offen[cs]e detenid[oa]
detencion orden?(de_)?detencion medida?cautelar violencia?intrafamiliar vif
causa?penal

HOW IT IS MASKED

Replaced by a generic status (Sin antecedentes , Con antecedentes); flags keep their shape.

CL_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_ANTECEDENTES_LISTA .

CL_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-si-no.txt , chosen by a keyed hash.

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-true-false.txt , chosen by a keyed hash.

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-s-n.txt , chosen by a keyed hash.

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-y-n.txt , chosen by a keyed hash.

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cl-bandera-0-1.txt , chosen by a keyed hash.

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CL_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 3 values in cl-antecedentes.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Condenado por robo

→ Sin información

11.2 Court case numbers

CL_L3_PENAL_CAUSA

COLUMN NAME	VALUE FORMAT	CHARACTER MAPPING
-------------	--------------	-------------------

WHAT IT IS

RIT and RUC case numbers, police reports and complaint numbers.

HOW IT IS FOUND

COLUMN NAME	CL_L3_PENAL_CAUSA – Path	
90%	rol_?causa rit ruc rol?(tribunal judicial) n(ro um umero)?causa causa?rol rol? unico?(de_)?causa parte?policial n(ro um)?parte folio?(parte denuncia) n(ro um umero)?denuncia expediente(_?(judicial penal))? case?number	
VALUE FORMAT	CL_L3_PENAL_CAUSA – Regex	
PATTERN	STRENGTH	NOTES
[A-Za-z]{1,3}-\d{1,6}-\d{4}		80%
\d{10}-[\dkK]		80%
A value that matches none counts 30% against the domain.		

HOW IT IS MASKED

Characters are mapped within their kind, keeping the format.

CL_CM_ALFANUM	CHARACTER MAPPING
---------------	-------------------

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
0-1234-2023	→ M-3791-2227

The RUT check digit

The RUT check digit is computed modulo 11 with weights 2 to 7 from the right, and a result of 10 is written `K`. The Check Digit framework writes 10 as `0`, so masking a RUT with it alone leaves about one result in eleven invalid.

The algorithm `CL_RUT` takes two passes:

- The first masks the body and writes, in the check digit's place, an auxiliary digit computed with every weight doubled modulo 11. That digit is `9` exactly when the real check digit is `K`.
- The second writes `K` where the auxiliary digit is `9`; anywhere else it recomputes the real check digit without touching the body.

Every masked RUT is valid, `K` appears in its natural proportion, and the mapping stays one-to-one — a RUT used as a key cannot collide. Bodies of 6, 7 and 8 digits keep their format, with or without dots and hyphen, with an upper- or lower-case `k`.

Limits

- **Binary columns** — scanned identity cards, fingerprint images, clinical PDFs stored in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A RUT split in two columns** keeps its masked body consistent, but the check digit column cannot see the body, so the pair is no longer valid.
- **Comunas** spelled in a way the list does not know pass unchanged. Names with and without accents and ñ are both recognized.
- **Free text** is redacted word by word: a phone number written with spaces (`+56 9 8765 4321`) is not found there, and a name that is also a common word (`Rosa , Paz`) is redacted wherever it appears.
- **Minors** — a birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, number and comuna kept in separate columns are masked independently of one another.

Verification

Before publication the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 129 columns with the whole set at its assignment threshold — well named, badly named, and 21 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The algorithms, run with the Delphix algorithm plugin, masked 184 sample values and 204 placeholders such as `S/I`, checking that each masked value comes from the right vocabulary, and 60 random RUTs for a valid check digit. Each of the 101 algorithms also masked its own sample input.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

15

Sources

- Ley 21.719 — Biblioteca del Congreso Nacional de Chile.
- Bill postponing the entry into force, Boletín 18.623-07 (31 August 2026).
- Comunas, provinces, regions and Censo 2024 population — Wikipedia, *Anexo:Comunas de Chile*.
- Most registered surnames, 2014–2023 — Servicio de Registro Civil e Identificación.
- Legally constituted political parties — Servicio Electoral (Servel).
- Pension fund administrators — Superintendencia de Pensiones. ISAPREs — Superintendencia de Salud.
- Registro Social de Hogares tiers — Ministerio de Desarrollo Social y Familia.
- Indigenous peoples — Ley 19.253 and its amendments; Chilean Afro-descendant tribal people — Ley 21.151.
- Vehicle plate formats — Registro Civil. Telephone numbering — Subsecretaría de Telecomunicaciones.
- Religion categories — Instituto Nacional de Estadísticas, Censo 2024.

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

CL_AFP REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_AFP_LISTA .

Used by: CL_L3_SOCIOEC_PREVISION_AFP

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_AFP_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_AFP_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in cl-afp.txt , chosen by a keyed hash.

Used by: CL_AFP

CONFIGURATION

lookupFile	cl-afp.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CL_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER

(\d{3})(\d)	keep · CL_CM_ALFANUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_ANTECEDENTES_LISTA .

Used by: CL_L3_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_ANTECEDENTES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_ANTECEDENTES_LISTA **SECURE LOOKUP**

Replaces the value with one of the 3 values in `cl-antecedentes.txt` , chosen by a keyed hash.

Used by: `CL_ANTECEDENTES`

CONFIGURATION

lookupFile	cl-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_APELLIDO **NAME**

Replaces the name with one of the 194 names in `cl-apellidos.txt` .

Used by: `CL_APELLIDOS` , `CL_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	cl-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

CL_APELLIDOS **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

Used by: `CL_L1_APELLIDO` , `CL_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

(\S+)	CL_APELLIDO
(\S+)\s+(\S+)	CL_APELLIDO · CL_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	CL_APELLIDO · CL_APELLIDO · CL_APELLIDO
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CL_CATEGORIA_SUPRIMIDA` , `CL_PUEBLO_ORIGINARIO` , `CL_DIAGNOSTICO` , `CL_MEDICAMENTO` , `CL_DISCAPACIDAD` , `CL_ORIENTACION_SEXUAL` , `CL_IDENTIDAD_GENERO` , `CL_RELIGION` , `CL_IDEOLOGIA` , `CL_PARTIDO_POLITICO` , `CL_PREVISION_SALUD` ,

CL_RSH , CL_BENEFICIO_SOCIAL , CL_MOROSIDAD , CL_AFP , CL_VIVIENDA , CL_FINANCIAMIENTO_ESTUDIOS , CL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	CL_BANDERA_SI_NO
(?i)(true false)	CL_BANDERA_TRUE_FALSE
(?i)([sn])	CL_BANDERA_S_N
(?i)(y)	CL_BANDERA_Y_N
([01])	CL_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-0-1.txt` , chosen by a keyed hash.

Used by: CL_BANDERA

CONFIGURATION

lookupFile	cl-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-s-n.txt` , chosen by a keyed hash.

Used by: CL_BANDERA

CONFIGURATION

lookupFile	cl-bandera-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-si-no.txt` , chosen by a keyed hash.

Used by: CL_BANDERA

CONFIGURATION

lookupFile	cl-bandera-si-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

CL_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-true-false.txt` , chosen by a keyed hash.

Used by: `CL_BANDERA`

CONFIGURATION

lookupFile	<code>cl-bandera-true-false.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

CL_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-bandera-y-n.txt` , chosen by a keyed hash.

Used by: `CL_BANDERA`

CONFIGURATION

lookupFile	<code>cl-bandera-y-n.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

CL_BENEFICIO_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CL_BENEFICIO_SOCIAL_LISTA` .

Used by: `CL_L3_SOCIOEC_BENEFICIO_SOCIAL`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>CL_BANDERA</code>
<code>(\d{1,6})</code>	<code>CL_CM_ALFANUM</code>
otherwise	<code>CL_BENEFICIO_SOCIAL_LISTA</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

CL_BENEFICIO_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 21 values in `cl-beneficios-sociales.txt` , chosen by a keyed hash.

Used by: `CL_BENEFICIO_SOCIAL`

CONFIGURATION

lookupFile	<code>cl-beneficios-sociales.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_CANTIDAD_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CL_L2_CARGAS_FAMILIARES

PATTERNS, TRIED IN ORDER

([0-5])	keep
(\d+)	replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_SUPRIMIR .

Used by: CL_L3_SALUD_SEXUAL_REPRODUCTIVA , CL_L3_SALUD_MENTAL_ADICCIONES , CL_L3_VIDA_SEXUAL , CL_L3_AFILIACION_SINDICAL , CL_L3_AFILIACION_GREMIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_SUPRIMIR

CONFIGURATION

trimInput	yes
requireMask	no

CL_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in cl-cie10.txt , chosen by a keyed hash.

Used by: CL_DIAGNOSTICO

CONFIGURATION

lookupFile	cl-cie10.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in cl-cie10-decimal.txt , chosen by a keyed hash.

Used by: CL_DIAGNOSTICO

CONFIGURATION

lookupFile	cl-cie10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: CL_L1_RUT_CUERPO , CL_L1_DIRECCION_COMPLEMENTO , CL_L1_NUMERO_DOCUMENTO , CL_L1_PASAPORTE , CL_L1_DOCUMENTO_EXTRANJERO , CL_L1_CUENTA_BANCARIA , CL_L1_DISPOSITIVO , CL_L1_VEHICULO_ID , CL_L1_NUMERO_CONTRATO , CL_L1_USUARIO_RRSS , CL_L3_SALUD_IDENTIFICADOR , CL_L3_SALUD_RESULTADO_EXAMEN , CL_L3_SOCIOEC_PLAN_SALUD , CL_L3_PENAL_CAUSA , CL_CATEGORIA_SUPRIMIDA , CL_RUT_CUERPO_8 , CL_RUT_CUERPO_7 , CL_RUT_CUERPO_6 , CL_RUT_PASO_1 , CL_NOMBRES , CL_APELLIDOS , CL_NOMBRE_COMPLETO , CL_EMAIL , CL_TELEFONO , CL_IP , CL_COORDENADA , CL_ANIO , CL_EDAD , CL_CODIGO_POSTAL , CL_PUEBLO_ORIGINARIO , CL_MEDICAMENTO , CL_DISCAPACIDAD , CL_ORIENTACION_SEXUAL , CL_IDENTIDAD_GENERO , CL_RELIGION , CL_IDEOLOGIA , CL_PARTIDO_POLITICO , CL_BENEFICIO_SOCIAL , CL_MOROSIDAD , CL_AFP , CL_VIVIENDA , CL_FINANCIAMIENTO_ESTUDIOS , CL_ANTECEDENTES

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnñopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ áéíóúü ÁÉÍÓÚÜ
caseSensitive	yes
minMaskedPositions	0

CL_CODIGO_COMUNA DATA CLEANSING

Replaces each value found in cl-codigo-comuna-generalizado.txt (552 pairs) by its counterpart; values not in the file stay as they are.

Used by: CL_L2_CODIGO_COMUNA

CONFIGURATION

lookupFile	cl-codigo-comuna-generalizado.txt
delimiter	,
caseSensitive	no
trimWhitespace	yes

CL_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

Used by: CL_L2_CODIGO_POSTAL

PATTERNS, TRIED IN ORDER

(\d{3})-(\d{4})	keep · replace with 0000
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_COMUNA DATA CLEANSING

Replaces each value found in cl-comuna-generalizada.txt (428 pairs) by its counterpart; values not in the file stay as they are.

Used by: CL_L2_COMUNA

CONFIGURATION

lookupFile	cl-comuna-generalizada.txt
delimiter	,

caseSensitive	no
trimWhitespace	yes

CL_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CL_L1_GEOLOCALIZACION

PATTERNS, TRIED IN ORDER

(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)	keep · CL_CM_ALFANUM · keep · CL_CM_ALFANUM
(-?\d{1,3}\.\d)(\d+)	keep · CL_CM_ALFANUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CL_DIAGNOSTICO_TEXTO .

Used by: CL_L3_SALUD_DIAGNOSTICO

PATTERNS, TRIED IN ORDER

([A-TV-Za-tv-z]\d{2}\.\d{1,2})	CL_CIE10_DECIMAL
([A-TV-Za-tv-z]\d{2,3})	CL_CIE10
(?i)(s[ií] no true false [sny01])	CL_BANDERA
otherwise	CL_DIAGNOSTICO_TEXTO

CONFIGURATION

trimInput	yes
requireMask	no

CL_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in cl-diagnostics.txt , chosen by a keyed hash.

Used by: CL_DIAGNOSTICO

CONFIGURATION

lookupFile	cl-diagnostics.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_DIRECCION SECURE LOOKUP

Replaces the value with one of the 3,000 values in cl-direcciones.txt , chosen by a keyed hash.

Used by: CL_L1_DIRECCION

CONFIGURATION

lookupFile	cl-direcciones.txt
------------	--------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_DISCAPACIDAD_LISTA .

Used by: CL_L3_SALUD_DISCAPACIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_DISCAPACIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in cl-discapacidad.txt , chosen by a keyed hash.

Used by: CL_DISCAPACIDAD

CONFIGURATION

lookupFile	cl-discapacidad.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CL_L2_EDAD

PATTERNS, TRIED IN ORDER

(\d{3,})	replace with 90
([1-9])(\d)(\.\d+)	keep · CL_CM_ALFANUM · keep
([1-9])(\d)	keep · CL_CM_ALFANUM
(\d)	CL_CM_ALFANUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

Used by: `CL_L1_EMAIL`

PATTERNS, TRIED IN ORDER

<code>([^\s]+)@ ([^\s]+) \. ([A-Za-z]{2,24})</code>	<code>CL_CM_ALFANUM</code> · <code>CL_CM_ALFANUM</code> · replace with <code>test</code>
otherwise	<code>CL_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CL_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 25 values in `cl-empleadores.txt` , chosen by a keyed hash.

Used by: `CL_L2_EMPLEADOR`

CONFIGURATION

lookupFile	<code>cl-empleadores.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_ESTABLECIMIENTO SECURE LOOKUP

Replaces the value with one of the 15 values in `cl-establecimientos.txt` , chosen by a keyed hash.

Used by: `CL_L2_ESTABLECIMIENTO_EDUCACIONAL`

CONFIGURATION

lookupFile	<code>cl-establecimientos.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_ESTADO_CIVIL SECURE LOOKUP

Replaces the value with one of the 6 values in `cl-estado-civil.txt` , chosen by a keyed hash.

Used by: `CL_L2_ESTADO_CIVIL`

CONFIGURATION

lookupFile	<code>cl-estado-civil.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `CL_L2_FECHA_EVENTO`

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

CL_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: CL_L2_FECHA_NACIMIENTO

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS
roll	no

CL_FINANCIAMIENTO_ESTUDIOS REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_FINANCIAMIENTO_ESTUDIOS_LISTA .

Used by: CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_FINANCIAMIENTO_ESTUDIOS_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_FINANCIAMIENTO_ESTUDIOS_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in cl-financiamiento-estudios.txt , chosen by a keyed hash.

Used by: CL_FINANCIAMIENTO_ESTUDIOS

CONFIGURATION

lookupFile	cl-financiamiento-estudios.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in cl-grupo-sanguineo.txt , chosen by a keyed hash.

Used by: CL_L3_SALUD_GRUPO_SANGUINEO

CONFIGURATION

lookupFile	cl-grupo-sanguineo.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_GSE SECURE LOOKUP

Replaces the value with one of the 7 values in `cl-gse.txt` , chosen by a keyed hash.

Used by: `CL_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	cl-gse.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CL_IDENTIDAD_GENERO_LISTA` .

Used by: `CL_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	CL_BANDERA
<code>(\d{1,6})</code>	CL_CM_ALFANUM
otherwise	CL_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-identidad-genero.txt` , chosen by a keyed hash.

Used by: `CL_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	cl-identidad-genero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_IDEOLOGIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CL_IDEOLOGIA_LISTA` .

Used by: `CL_L3_CONVICCION_IDEOLOGICA`

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_IDEOLOGIA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_IDEOLOGIA_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `cl-ideologias.txt` , chosen by a keyed hash.

Used by: `CL_IDEOLOGIA`

CONFIGURATION

lookupFile	cl-ideologias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

Used by: `CL_L1_IP`

PATTERNS, TRIED IN ORDER

(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3})	CL_OCTETO · CL_OCTETO · CL_OCTETO · CL_OCTETO
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CL_MEDICAMENTO_LISTA` .

Used by: `CL_L3_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_MEDICAMENTO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 26 values in `cl-medicamentos.txt` , chosen by a keyed hash.

Used by: `CL_MEDICAMENTO`

CONFIGURATION

lookupFile	cl-medicamentos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_MONTO_DEUDA NUMERIC MAPPING

Maps the number to another between 10,000 and 50,000,000.

Used by: CL_L3_SOCIOEC_MONTO_DEUDA

CONFIGURATION

minValue	10000
maxValue	50000000

CL_MONTO_INGRESO NUMERIC MAPPING

Maps the number to another between 450,000 and 8,000,000.

Used by: CL_L3_SOCIOEC_INGRESOS

CONFIGURATION

minValue	450000
maxValue	8000000

CL_MONTO_PREVISIONAL NUMERIC MAPPING

Maps the number to another between 100,000 and 250,000,000.

Used by: CL_L3_SOCIOEC_SALDO_PREVISIONAL

CONFIGURATION

minValue	100000
maxValue	250000000

CL_MOROSIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_MOROSIDAD_LISTA .

Used by: CL_L3_SOCIOEC_MOROSIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_MOROSIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_MOROSIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in cl-estado-credificio.txt , chosen by a keyed hash.

Used by: CL_MOROSIDAD

CONFIGURATION

lookupFile	cl-estado-credificio.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 17 values in cl-nacionalidades.txt , chosen by a keyed hash.

Used by: CL_L2_NACIONALIDAD

CONFIGURATION

lookupFile	cl-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_NIVEL_EDUCACIONAL SECURE LOOKUP

Replaces the value with one of the 10 values in cl-nivel-educacional.txt , chosen by a keyed hash.

Used by: CL_L2_NIVEL_EDUCACIONAL

CONFIGURATION

lookupFile	cl-nivel-educacional.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CL_GSE .

Used by: CL_L3_SOCIOEC_NIVEL

PATTERNS, TRIED IN ORDER

(\d{1,2})	CL_QUINTIL
otherwise	CL_GSE

CONFIGURATION

trimInput	yes
requireMask	no

CL_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

Used by: CL_L1_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

([^\,]+),\s*(.+)	CL_APELLIDOS · CL_NOMBRES
(\S+)	CL_NOMBRE_PILA
(\S+)\s+(\S+)	CL_NOMBRE_PILA · CL_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	CL_NOMBRE_PILA · CL_APELLIDO · CL_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_APELLIDO · CL_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_APELLIDO · CL_APELLIDO
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_NOMBRE_PILA NAME

Replaces the name with one of the 189 names in `cl-nombres.txt` .

Used by: `CL_NOMBRES` , `CL_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	cl-nombres.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

CL_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CL_CM_ALFANUM` .

Used by: `CL_L1_NOMBRE` , `CL_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

(\S+)	CL_NOMBRE_PILA
(\S+)\s+(\S+)	CL_NOMBRE_PILA · CL_NOMBRE_PILA
(\S+)\s+(\S+)\s+(\S+)	CL_NOMBRE_PILA · CL_NOMBRE_PILA · CL_NOMBRE_PILA
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `CL_IP`

CONFIGURATION

minValue	1
maxValue	254

CL_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in `cl-ocupaciones.txt` , chosen by a keyed hash.

Used by: `CL_L2_OCUPACION`

CONFIGURATION

lookupFile	cl-ocupaciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_ORIENTACION_SEXUAL_LISTA .

Used by: CL_L3_ORIENTACION_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_ORIENTACION_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in cl-orientacion-sexual.txt , chosen by a keyed hash.

Used by: CL_ORIENTACION_SEXUAL

CONFIGURATION

lookupFile	cl-orientacion-sexual.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_PARTIDO_POLITICO_LISTA .

Used by: CL_L3_AFILIACION_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_PARTIDO_POLITICO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 15 values in `cl-partidos.txt` , chosen by a keyed hash.

Used by: `CL_PARTIDO_POLITICO`

CONFIGURATION

lookupFile	cl-partidos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_PATENTE CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `CL_L1_PATENTE`

CONFIGURATION

characterGroups	BCDFGHJKLPRSTVWXYZ AEIMNOQU bcdfghjklprstvwxyz aeimnoqu 0123456789
caseSensitive	yes

CL_PREVISION_SALUD REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

`CL_PREVISION_SALUD_LISTA` .

Used by: `CL_L3_SOCIOEC_PREVISION_SALUD`

PATTERNS, TRIED IN ORDER

<code>([A-Da-d])</code>	<code>CL_TRAMO_FONASA</code>
<code>(?i)(fonasa\s*[\-:]?\s*(?:tramo\s*))?([A-D])</code>	keep · <code>CL_TRAMO_FONASA</code>
<code>(?i)(s[ií] no true false [sny01])</code>	<code>CL_BANDERA</code>
otherwise	<code>CL_PREVISION_SALUD_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CL_PREVISION_SALUD_LISTA SECURE LOOKUP

Replaces the value with one of the 18 values in `cl-prevision-salud.txt` , chosen by a keyed hash.

Used by: `CL_PREVISION_SALUD`

CONFIGURATION

lookupFile	cl-prevision-salud.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_PUEBLO_ORIGINARIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CL_PUEBLO_ORIGINARIO_LISTA .

Used by: CL_L3_ETNIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_PUEBLO_ORIGINARIO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_PUEBLO_ORIGINARIO_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in cl-pueblos.txt , chosen by a keyed hash.

Used by: CL_PUEBLO_ORIGINARIO

CONFIGURATION

lookupFile	cl-pueblos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in cl-quintil.txt , chosen by a keyed hash.

Used by: CL_NIVEL_SOCIOECONOMICO

CONFIGURATION

lookupFile	cl-quintil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CL_L1_CREDENCIAL , CL_L3_BIOMETRICO , CL_L3_PERFIL_GENETICO

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

CL_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_RELIGION_LISTA .

Used by: CL_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	CL_BANDERA
(\d{1,6})	CL_CM_ALFANUM
otherwise	CL_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CL_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in cl-religiones.txt , chosen by a keyed hash.

Used by: CL_RELIGION

CONFIGURATION

lookupFile	cl-religiones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_RSH REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

CL_RSH_TRAMO_TEXT0 .

Used by: CL_L3_SOCIOEC_RSH

PATTERNS, TRIED IN ORDER

(\d{1,3})(\s*%)	CL_RSH_TRAMO_NUMERO · keep
(?i)(tramo\s*)(\d{1,3})(.*)	keep · CL_RSH_TRAMO_NUMERO · keep
(\d{1,3})	CL_RSH_TRAMO_NUMERO
(?i)(s[ií] no true false [sny01])	CL_BANDERA
otherwise	CL_RSH_TRAMO_TEXT0

CONFIGURATION

trimInput	yes
requireMask	no

CL_RSH_TRAMO_NUMERO SECURE LOOKUP

Replaces the value with one of the 7 values in cl-rsh-tramo-numero.txt , chosen by a keyed hash.

Used by: CL_RSH

CONFIGURATION

lookupFile	cl-rsh-tramo-numero.txt
------------	-------------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_RSH_TRAMO_TEXTO SECURE LOOKUP

Replaces the value with one of the 7 values in `cl-rsh-tramo-texto.txt`, chosen by a keyed hash.

Used by: `CL_RSH`

CONFIGURATION

lookupFile	cl-rsh-tramo-texto.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_RUT STRING ALGORITHM CHAIN

Applies `CL_RUT_PASO_1` → `CL_RUT_PASO_2`, in this order.

Used by: `CL_L1_RUT`

CONFIGURATION

algorithmReferences[1]	CL_RUT_PASO_1
algorithmReferences[2]	CL_RUT_PASO_2

CL_RUT_CUERPO_6 CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3` from the right.

Used by: `CL_RUT_PASO_1`

CONFIGURATION

weightList	4 6 8 10 1 3
modulusNumber	11
checkDigitIndex	6
calculateChecksumRightToLeft	yes
numDigitsForCheckdigitCalculation	6
numericAlgorithm	CL_CM_ALFANUM
preserveRegex	[.\-]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CL_RUT_CUERPO_7 CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights `4 6 8 10 1 3 4` from the right.

Used by: `CL_RUT_PASO_1`

CONFIGURATION

weightList	4 6 8 10 1 3 4
modulusNumber	11
checkDigitIndex	7
calculateChecksumRightToLeft	yes
numDigitsForCheckdigitCalculation	7
numericAlgorithm	CL_CM_ALFANUM
preserveRegex	[.\-]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CL_RUT_CUERPO_8 CHECK DIGIT

Masks the digits with `CL_CM_ALFANUM` and recomputes a modulus 11 check digit with weights 4 6 8 10 1 3 4 6 from the right.

Used by: `CL_RUT_PASO_1`

CONFIGURATION

weightList	4 6 8 10 1 3 4 6
modulusNumber	11
checkDigitIndex	8
calculateChecksumRightToLeft	yes
numDigitsForCheckdigitCalculation	8
numericAlgorithm	CL_CM_ALFANUM
preserveRegex	[.\-]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CL_RUT_DV SECURE LOOKUP

Replaces the value with one of the 11 values in `cl-digito-verificador.txt` , chosen by a keyed hash.

Used by: `CL_L1_RUT_DV`

CONFIGURATION

lookupFile	cl-digito-verificador.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_RUT_DV_6 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 from the right.

Used by: CL_RUT_PASO_2

CONFIGURATION

weightList	2 3 4 5 6 7
modulusNumber	11
checkDigitIndex	6
calculateChecksumRightToLeft	yes
numDigitsForCheckdigitCalculation	6
numericAlgorithm	CL_SIN_CAMBIO
preserveRegex	[.\-]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CL_RUT_DV_7 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 from the right.

Used by: CL_RUT_PASO_2

CONFIGURATION

weightList	2 3 4 5 6 7 2
modulusNumber	11
checkDigitIndex	7
calculateChecksumRightToLeft	yes
numDigitsForCheckdigitCalculation	7
numericAlgorithm	CL_SIN_CAMBIO
preserveRegex	[.\-]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CL_RUT_DV_8 CHECK DIGIT

Masks the digits with CL_SIN_CAMBIO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 from the right.

Used by: CL_RUT_PASO_2

CONFIGURATION

weightList	2 3 4 5 6 7 2 3
modulusNumber	11
checkDigitIndex	8
calculateChecksumRightToLeft	yes

numDigitsForCheckdigitCalculation	8
numericAlgorithm	CL_SIN_CAMBIO
preserveRegex	[.\-]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CL_RUT_PASO_1 REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

Used by: CL_RUT

PATTERNS, TRIED IN ORDER

(\d{2}\.?\d{3}\.?\d{3}-?[0-9kK])	CL_RUT_CUERPO_8
(\d\.\d{3}\.\d{3}-?[0-9kK])	CL_RUT_CUERPO_7
(\d{3}\.\d{3}-?[0-9kK])	CL_RUT_CUERPO_6
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_RUT_PASO_2 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CL_RUT

PATTERNS, TRIED IN ORDER

(\d{2}\.?\d{3}\.?\d{3}-?)(9)	keep · replace with K
(\d\.\d{3}\.\d{3}-?)(9)	keep · replace with K
(\d{3}\.\d{3}-?)(9)	keep · replace with K
(\d{2}\.?\d{3}\.?\d{3}-?[0-9])	CL_RUT_DV_8
(\d\.\d{3}\.\d{3}-?[0-9])	CL_RUT_DV_7
(\d{3}\.\d{3}-?[0-9])	CL_RUT_DV_6
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_SEX0 REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CL_L2_SEX0

PATTERNS, TRIED IN ORDER

(?i)(femenino masculino)	CL_SEX0_PALABRA
(?i)(mujer hombre)	CL_SEX0_MUJER_HOMBRE
(?i)(female male)	CL_SEX0_INGLES

(?i)([fm])	CL_SEX0_F_M
(?i)(h)	CL_SEX0_H_M
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_SEX0_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-f-m.txt` , chosen by a keyed hash.

Used by: `CL_SEX0`

CONFIGURATION

lookupFile	cl-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_SEX0_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-h-m.txt` , chosen by a keyed hash.

Used by: `CL_SEX0`

CONFIGURATION

lookupFile	cl-sexo-h-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_SEX0_INGLES SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-ingles.txt` , chosen by a keyed hash.

Used by: `CL_SEX0`

CONFIGURATION

lookupFile	cl-sexo-ingles.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_SEX0_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `CL_SEX0`

CONFIGURATION

lookupFile	cl-sexo-mujer-hombre.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_SEXO_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in `cl-sexo-palabra.txt` , chosen by a keyed hash.

Used by: `CL_SEXO`

CONFIGURATION

lookupFile	cl-sexo-palabra.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_SIN_CAMBIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_RUT_DV_8` , `CL_RUT_DV_7` , `CL_RUT_DV_6`

PATTERNS, TRIED IN ORDER

<code>(.*)</code>	keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cl-sin-informacion.txt` , chosen by a keyed hash.

Used by: `CL_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	cl-sin-informacion.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CL_L1_TARJETA`

PATTERNS, TRIED IN ORDER

(\d[\d\s\~]{11,22}\d)	CL_TARJETA_LUHN
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CL_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: CL_TARJETA

CONFIGURATION

minMaskedPositions	6
preserve	0

CL_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CL_CM_ALFANUM .

Used by: CL_L1_TELEFONO

PATTERNS, TRIED IN ORDER

(\+?56[\s\~]?)?(\(?9\)?[\s\~]?)\d{4})	keep · keep · CL_CM_ALFANUM · keep · CL_CM_ALFANUM
([\s\~]?)\d{4})	
(\+?56[\s\~]?)?(\(?(:2 [3-7]\d)\)?[\s\~]?)\d{3,4})([\s\~]?)\d{4})	keep · keep · CL_CM_ALFANUM · keep · CL_CM_ALFANUM
otherwise	CL_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CL_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with [DATO] , and the 948 terms of cl-texto-nombres.txt with [NOMBRE] .

Used by: CL_L1_TEXTO_LIBRE , CL_L3_SALUD_TEXTO_CLINICO

PATTERNS, TRIED IN ORDER

\d{1,2}\.\d{3}\.\d{3}-[\dkk]	
\d{7,8}-[\dkk]	
[\w.+\~]+@[~\w\~]+(\. [\w\~]+)+	
\+?56\d{9}	
(?<!\d)9\d{8}(?!~\d)	
(?<![A-Za-z]) [BCDFGHJKLPRSTVWXYZ]{4}-?\d{2}(?!~\d)	
(?<!\d)\d{13,19}(?!~\d)	
(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!~\d)	

CONFIGURATION

regExRedactValue	[DATO]
lookupFile	cl-texto-nombres.txt
lookupFileRedactValue	[NOMBRE]

isDenyList	yes
------------	-----

CL_TRAMO_FONASA SECURE LOOKUP

Replaces the value with one of the 4 values in `cl-tramo-fonasa.txt` , chosen by a keyed hash.

Used by: `CL_PREVISION_SALUD`

CONFIGURATION

lookupFile	<code>cl-tramo-fonasa.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CL_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CL_VIVIENDA_LISTA` .

Used by: `CL_L3_SOCIOEC_VIVIENDA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>CL_BANDERA</code>
<code>(\d{1,6})</code>	<code>CL_CM_ALFANUM</code>
otherwise	<code>CL_VIVIENDA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CL_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cl-vivienda.txt` , chosen by a keyed hash.

Used by: `CL_VIVIENDA`

CONFIGURATION

lookupFile	<code>cl-vivienda.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
cl-afp.txt	11	CL_AFP_LISTA	AFP Capital · AFP Cuprum · AFP Habitat · AFP Modelo
cl-antecedentes.txt	3	CL_ANTECEDENTES_LISTA	Sin antecedentes · Con antecedentes · Sin información
cl-apellidos.txt	194	CL_APELLIDO	González · Muñoz · Rojas · Díaz
cl-bandera-0-1.txt	2	CL_BANDERA_0_1	0 · 1
cl-bandera-s-n.txt	2	CL_BANDERA_S_N	S · N
cl-bandera-si-no.txt	2	CL_BANDERA_SI_NO	Si · No
cl-bandera-true-false.txt	2	CL_BANDERA_TRUE_FALSE	true · false
cl-bandera-y-n.txt	2	CL_BANDERA_Y_N	Y · N
cl-beneficios-sociales.txt	21	CL_BENEFICIO_SOCIAL_LISTA	Pensión Garantizada Universal · Subsidio Único Familiar · Asignación Familiar · Aporte Familiar Permanente
cl-cie10-decimal.txt	33	CL_CIE10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
cl-cie10.txt	37	CL_CIE10	I10 · E11 · E78 · J45
cl-codigo-comuna-generalizado.txt	552	CL_CODIGO_COMUNA	15101,15101 · 15102,15101 · 15201,15101 · 15202,15101
cl-comuna-generalizada.txt	428	CL_COMUNA	Arica,Arica · Camarones,Arica · Putre,Arica · General Lagos,Arica
cl-detectar-afp.txt	24	CL_L3_SOCIOEC_PREVISION_AFP – List	AFP Capital · AFP Cuprum · AFP Habitat · AFP Modelo
cl-detectar-apellidos.txt	245	CL_L1_APELLIDO – List CL_L1_NOMBRE_COMPLETO – List	González · Gonzalez · Muñoz · Munoz
cl-detectar-beneficios.txt	45	CL_L3_SOCIOEC_BENEFICIO_SOCIAL – List	Pensión Garantizada Universal · Pension Garantizada Universal · Subsidio Único Familiar · Subsidio Unico Familiar
cl-detectar-codigo-comuna.txt	552	CL_L2_CODIGO_COMUNA – List	15101 · 15102 · 15201 · 15202
cl-detectar-comunas.txt	428	CL_L2_COMUNA – List	Arica · Camarones · Putre · General Lagos
cl-detectar-discapacidad.txt	20	CL_L3_SALUD_DISCAPACIDAD – List	Física · Fisica · Visual · Auditiva
cl-detectar-estado-civil.txt	22	CL_L2_ESTADO_CIVIL – List	soltero · soltera · casado · casada
cl-detectar-financiamiento-estudios.txt	28	CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS – List	Gratuidad · Beca Bicentenario · Beca Juan Gómez Millas · Beca Juan Gomez Millas
cl-detectar-grupo-sanguineo.txt	28	CL_L3_SALUD_GRUPO_SANGUINEO – List	A+ · A- · B+ · B- · 0 – List

FILE	LINES	USED BY	FIRST LINES
cl-detectar-gse.txt	9	CL_L3_SOCIOEC_NIVEL – List	abc1 · c1 · c1a · c1b
cl-detectar-identidad-genero.txt	18	CL_L3_IDENTIDAD_GENERO – List	Mujer · Hombre · Mujer trans · Hombre trans
cl-detectar-ideologias.txt	15	CL_L3_CONVICCION_IDEOLOGICA – List	Izquierda · Centroizquierda · Centro · Centroderecha
cl-detectar-medicamentos.txt	50	CL_L3_SALUD_MEDICAMENTO – List	Paracetamol · Ibuprofeno · Losartán · Losartan
cl-detectar-nacionalidades.txt	48	CL_L2_NACIONALIDAD – List	Chilena · Venezolana · Peruana · Haitiana
cl-detectar-nivel-educacional.txt	28	CL_L2_NIVEL_EDUCACIONAL – List	Sin estudios · Básica incompleta · Basica incompleta · Básica completa
cl-detectar-nombres.txt	229	CL_L1_NOMBRE – List CL_L1_NOMBRE_COMPLETO – List	María · Maria · José · Jose
cl-detectar-orientacion-sexual.txt	15	CL_L3_ORIENTACION_SEXUAL – List	Heterosexual · Homosexual · Lesbiana · Gay
cl-detectar-partidos.txt	52	CL_L3_AFILIACION_POLITICA – List	Partido Demócrata Cristiano · Partido Democrata Cristiano · Partido por la Democracia · Partido Radical de Chile
cl-detectar-prevision-salud.txt	44	CL_L3_SOCIOEC_PREVISION_SALUD – List	FONASA A · FONASA B · FONASA C · FONASA D
cl-detectar-pueblos.txt	44	CL_L3_ETNIA – List	Mapuche · Aymara · Rapa Nui · Lickanantay
cl-detectar-religiones.txt	50	CL_L3_RELIGION – List	Católica · Catolica · Evangélica o protestante · Evangelica o protestante
cl-detectar-sexo.txt	11	CL_L2_SEXO – List	f · m · h · femenino
cl-detectar-tramo-fonasa.txt	4	CL_L3_SOCIOEC_PREVISION_SALUD – List	a · b · c · d
cl-detectar-vivienda.txt	19	CL_L3_SOCIOEC_VIVIENDA – List	Propia pagada · Propia pagándose · Propia pagandose · Arrendada con contrato
cl-diagnosticos.txt	30	CL_DIAGNOSTICO_TEXTO	Hipertensión arterial esencial · Diabetes mellitus tipo 2 · Asma bronquial · Lumbago
cl-digito-verificador.txt	11	CL_RUT_DV	0 · 1 · 2 · 3
cl-direcciones.txt	3,000	CL_DIRECCION	El Peumo 762 · Calle Los Robles 1026 · Avenida España 873, depto 1909 · Avenida Matta 1445
cl-discapacidad.txt	8	CL_DISCAPACIDAD_LISTA	Física · Visual · Auditiva · Intelectual
cl-empleadores.txt	25	CL_EMPLEADOR	Comercial Los Andes SpA · Servicios Integrales del Sur Ltda. · Constructora Cordillera S.A. · Transportes Pacífico Norte SpA
cl-establecimientos.txt	15	CL_ESTABLECIMIENTO	Escuela Básica N° 12 · Escuela Rural Los Aromos · Liceo Bicentenario A-45 · Liceo Técnico Profesional B-23
cl-estado-civil.txt	6	CL_ESTADO_CIVIL	Soltero · Casado · Viudo · Divorciado
cl-estado-credificio.txt	8	CL_MOROSIDAD_LISTA	Al día · Mora 1 a 30 días · Mora 31 a 90 días · Mora sobre 90 días

FILE	LINES	USED BY	FIRST LINES
cl-financiamiento-estudios.txt	12	CL_FINANCIAMIENTO_ESTUDIOS_LISTA	Gratuidad · Beca Bicentenario · Beca Juan Gómez Millas · Beca Nuevo Milenio
cl-grupo-sanguineo.txt	8	CL_GRUPO_SANGUINEO	A+ · A- · B+ · B-
cl-gse.txt	7	CL_GSE	ABC1 · C1a · C1b · C2
cl-identidad-genero.txt	8	CL_IDENTIDAD_GENERO_LISTA	Mujer · Hombre · Mujer trans · Hombre trans
cl-ideologias.txt	8	CL_IDEOLOGIA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
cl-medicamentos.txt	26	CL_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Losartán · Enalapril
cl-nacionalidades.txt	17	CL_NACIONALIDAD	Chilena · Venezolana · Peruana · Haitiana
cl-nivel-educacional.txt	10	CL_NIVEL_EDUCACIONAL	Sin estudios · Básica incompleta · Básica completa · Media incompleta
cl-nombres.txt	189	CL_NOMBRE_PILA	María · José · Juan · Luis
cl-ocupaciones.txt	40	CL_OCUPACION	Administrativo · Vendedor · Técnico en mantención · Contador
cl-orientacion-sexual.txt	9	CL_ORIENTACION_SEXUAL_LISTA	Heterosexual · Homosexual · Lesbiana · Gay
cl-partidos.txt	15	CL_PARTIDO_POLITICO_LISTA	Partido Demócrata Cristiano · Partido por la Democracia · Partido Radical de Chile · Partido Socialista de Chile
cl-prevision-salud.txt	18	CL_PREVISION_SALUD_LISTA	FONASA A · FONASA B · FONASA C · FONASA D
cl-pueblos.txt	13	CL_PUEBLO_ORIGINARIO_LISTA	Mapuche · Aymara · Rapa Nui · Lickanantay
cl-quintil.txt	5	CL_QUINTIL	1 · 2 · 3 · 4
cl-religiones.txt	12	CL_RELIGION_LISTA	Católica · Evangélica o protestante · Testigo de Jehová · Santos de los Últimos Días
cl-rsh-tramo-numero.txt	7	CL_RSH_TRAMO_NUMERO	40 · 50 · 60 · 70
cl-rsh-tramo-texto.txt	7	CL_RSH_TRAMO_TEXTO	Tramo 40% · Tramo 50% · Tramo 60% · Tramo 70%
cl-sexo-f-m.txt	2	CL_SEXO_F_M	F · M
cl-sexo-h-m.txt	2	CL_SEXO_H_M	H · M
cl-sexo-ingles.txt	2	CL_SEXO_INGLES	Female · Male
cl-sexo-mujer-hombre.txt	2	CL_SEXO_MUJER_HOMBRE	Mujer · Hombre
cl-sexo-palabra.txt	2	CL_SEXO_PALABRA	Femenino · Masculino
cl-sin-informacion.txt	1	CL_SUPRIMIR	Sin información
cl-texto-nombres.txt	948	CL_TEXTO_LIBRE	María · MARÍA · Maria · MARIA
cl-tramo-fonasa.txt	4	CL_TRAMO_FONASA	A · B · C · D
cl-vivienda.txt	10	CL_VIVIENDA_LISTA	Propia pagada · Propia pagándose · Arrendada con contrato · Arrendada sin contrato

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

-
- E1** producto prod articulo item empresa emp compania razon fantasia archivo arch file calle via comuna region provincia ciudad pais banco sucursal plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo estado colegio establecimiento institucion isapre afp curso carrera asignatura documento doc centro unidad area depto departamento cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico examen programa beneficio partido sindicato religion etnia pueblo lugar local tienda bodega proveedor convenio contrato poliza seguro org organizacion entidad parametro variable metodo funcion indice job script cola recurso red equipo dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso cliente cli paciente pac trabajador trab funcionario func alumno estudiante afiliado beneficiario titular madre padre tutor apoderado conyuge pareja medico doctor profesional responsable contacto emergencia aval codeudor deudor remitente destinatario receptor firmante testigo representante propietario arrendatario asegurado contratante victima denunciante imputado socio donante heredero causante persona pers conductor chofer vendedor ejecutivo agente empleado colaborador completos? y_? apellidos? apellidos?
-
- E2** producto prod articulo item empresa emp compania razon fantasia archivo arch file calle via comuna region provincia ciudad pais banco sucursal plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo estado colegio establecimiento institucion isapre afp curso carrera asignatura documento doc centro unidad area depto departamento cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico examen programa beneficio partido sindicato religion etnia pueblo lugar local tienda bodega proveedor convenio contrato poliza seguro org organizacion entidad parametro variable metodo funcion indice job script cola recurso red equipo dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso cliente cli paciente pac trabajador trab funcionario func alumno estudiante afiliado beneficiario titular madre padre tutor apoderado conyuge pareja medico doctor profesional responsable contacto emergencia aval codeudor deudor remitente destinatario receptor firmante testigo representante propietario arrendatario asegurado contratante victima denunciante imputado socio donante heredero causante persona pers conductor chofer vendedor ejecutivo agente empleado colaborador completo compl full y_?apellidos? apellidos?
-
- E3** producto prod articulo item empresa emp compania razon fantasia archivo arch file calle via comuna region provincia ciudad pais banco sucursal plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo estado colegio establecimiento institucion isapre afp curso carrera asignatura documento doc centro unidad area depto departamento cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico examen programa beneficio partido sindicato religion etnia pueblo lugar local tienda bodega proveedor convenio contrato poliza seguro org organizacion entidad parametro variable metodo funcion indice job script cola recurso red equipo dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso completo
-

E4 producto prod articulo item empresa emp compania razon fantasia archivo arch file calle via comuna region provincia ciudad pais banco sucursal plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo estado colegio establecimiento institucion isapre afp curso carrera asignatura documento doc centro unidad area depto departamento cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico examen programa beneficio partido sindicato religion etnia pueblo lugar local tienda bodega proveedor convenio contrato poliza seguro org organizacion entidad parametro variable metodo funcion indice job script cola recurso red equipo dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso

E5 ip mac web url correo mail electronica email

E6 producto articulo sucursal interna tipo registro primaria foranea elector

E7 fijo variable monto adicional servicio tarifa valor cuenta extra

E8 produccion desempeno anual gestion termino vacaciones trabajador colacion movilizacion

E9 medicos morbosos m[oó]rbidos familiares clinicos academicos laborales comerciales generales

APPENDIX D

Profile set and classifiers

The profile set `CL - Ley 21.719 - v3` runs these 132 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores y datos sensibles (art. 2 g) de la Ley 21.719.

CLASSIFIER	KIND	DOMAIN
CL_L1_RUT - Path	COLUMN NAME	CL_L1_RUT
CL_L1_RUT - Type	DATA TYPE	CL_L1_RUT
CL_L1_RUT - Regex	VALUE FORMAT	CL_L1_RUT
CL_L1_RUT_CUERPO - Path	COLUMN NAME	CL_L1_RUT_CUERPO
CL_L1_RUT_CUERPO - Type	DATA TYPE	CL_L1_RUT_CUERPO
CL_L1_RUT_CUERPO - Regex	VALUE FORMAT	CL_L1_RUT_CUERPO
CL_L1_RUT_DV - Path	COLUMN NAME	CL_L1_RUT_DV
CL_L1_RUT_DV - Type	DATA TYPE	CL_L1_RUT_DV
CL_L1_RUT_DV - Regex	VALUE FORMAT	CL_L1_RUT_DV
CL_L1_NOMBRE - Path	COLUMN NAME	CL_L1_NOMBRE
CL_L1_NOMBRE - List	KNOWN VALUES	CL_L1_NOMBRE
CL_L1_APELLIDO - Path	COLUMN NAME	CL_L1_APELLIDO
CL_L1_APELLIDO - List	KNOWN VALUES	CL_L1_APELLIDO
CL_L1_NOMBRE_COMPLETO - Path	COLUMN NAME	CL_L1_NOMBRE_COMPLETO
CL_L1_NOMBRE_COMPLETO - List	KNOWN VALUES	CL_L1_NOMBRE_COMPLETO
CL_L1_EMAIL - Path	COLUMN NAME	CL_L1_EMAIL
CL_L1_EMAIL - Type	DATA TYPE	CL_L1_EMAIL
CL_L1_EMAIL - Regex	VALUE FORMAT	CL_L1_EMAIL
CL_L1_TELEFONO - Path	COLUMN NAME	CL_L1_TELEFONO
CL_L1_TELEFONO - Regex	VALUE FORMAT	CL_L1_TELEFONO
CL_L1_DIRECCION - Path	COLUMN NAME	CL_L1_DIRECCION
CL_L1_DIRECCION - Type	DATA TYPE	CL_L1_DIRECCION
CL_L1_DIRECCION - Regex	VALUE FORMAT	CL_L1_DIRECCION
CL_L1_DIRECCION_COMPLEMENTO - Path	COLUMN NAME	CL_L1_DIRECCION_COMPLEMENTO
CL_L1_NUMERO_DOCUMENTO - Path	COLUMN NAME	CL_L1_NUMERO_DOCUMENTO
CL_L1_NUMERO_DOCUMENTO - Regex	VALUE FORMAT	CL_L1_NUMERO_DOCUMENTO
CL_L1_PASAPORTE - Path	COLUMN NAME	CL_L1_PASAPORTE
CL_L1_PASAPORTE - Regex	VALUE FORMAT	CL_L1_PASAPORTE
CL_L1_DOCUMENTO_EXTRANJERO - Path	COLUMN NAME	CL_L1_DOCUMENTO_EXTRANJERO
CL_L1_CUENTA_BANCARIA - Path	COLUMN NAME	CL_L1_CUENTA_BANCARIA
CL_L1_TARJETA - Path	COLUMN NAME	CL_L1_TARJETA
CL_L1_TARJETA - Regex	VALUE FORMAT	CL_L1_TARJETA

CLASSIFIER	KIND	DOMAIN
CL_L1_IP – Path	COLUMN NAME	CL_L1_IP
CL_L1_IP – Regex	VALUE FORMAT	CL_L1_IP
CL_L1_DISPOSITIVO – Path	COLUMN NAME	CL_L1_DISPOSITIVO
CL_L1_DISPOSITIVO – Regex	VALUE FORMAT	CL_L1_DISPOSITIVO
CL_L1_PATENTE – Path	COLUMN NAME	CL_L1_PATENTE
CL_L1_PATENTE – Regex	VALUE FORMAT	CL_L1_PATENTE
CL_L1_VEHICULO_ID – Path	COLUMN NAME	CL_L1_VEHICULO_ID
CL_L1_VEHICULO_ID – Regex	VALUE FORMAT	CL_L1_VEHICULO_ID
CL_L1_NUMERO_CONTRATO – Path	COLUMN NAME	CL_L1_NUMERO_CONTRATO
CL_L1_USUARIO_RRSS – Path	COLUMN NAME	CL_L1_USUARIO_RRSS
CL_L1_CREDENCIAL – Path	COLUMN NAME	CL_L1_CREDENCIAL
CL_L1_GEOLOCALIZACION – Path	COLUMN NAME	CL_L1_GEOLOCALIZACION
CL_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	CL_L1_GEOLOCALIZACION
CL_L1_TEXTO_LIBRE – Path	COLUMN NAME	CL_L1_TEXTO_LIBRE
CL_L1_TEXTO_LIBRE – Type	DATA TYPE	CL_L1_TEXTO_LIBRE
CL_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	CL_L1_TEXTO_LIBRE
CL_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	CL_L2_FECHA_NACIMIENTO
CL_L2_FECHA_NACIMIENTO – Type	DATA TYPE	CL_L2_FECHA_NACIMIENTO
CL_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	CL_L2_ANIO_NACIMIENTO
CL_L2_ANIO_NACIMIENTO – Type	DATA TYPE	CL_L2_ANIO_NACIMIENTO
CL_L2_EDAD – Path	COLUMN NAME	CL_L2_EDAD
CL_L2_EDAD – Type	DATA TYPE	CL_L2_EDAD
CL_L2_FECHA_EVENTO – Path	COLUMN NAME	CL_L2_FECHA_EVENTO
CL_L2_FECHA_EVENTO – Type	DATA TYPE	CL_L2_FECHA_EVENTO
CL_L2_SEX0 – Path	COLUMN NAME	CL_L2_SEX0
CL_L2_SEX0 – List	KNOWN VALUES	CL_L2_SEX0
CL_L2_COMUNA – Path	COLUMN NAME	CL_L2_COMUNA
CL_L2_COMUNA – List	KNOWN VALUES	CL_L2_COMUNA
CL_L2_CODIGO_COMUNA – Path	COLUMN NAME	CL_L2_CODIGO_COMUNA
CL_L2_CODIGO_COMUNA – Type	DATA TYPE	CL_L2_CODIGO_COMUNA
CL_L2_CODIGO_COMUNA – List	KNOWN VALUES	CL_L2_CODIGO_COMUNA
CL_L2_CODIGO_POSTAL – Path	COLUMN NAME	CL_L2_CODIGO_POSTAL
CL_L2_CODIGO_POSTAL – Regex	VALUE FORMAT	CL_L2_CODIGO_POSTAL
CL_L2_NACIONALIDAD – Path	COLUMN NAME	CL_L2_NACIONALIDAD
CL_L2_NACIONALIDAD – List	KNOWN VALUES	CL_L2_NACIONALIDAD
CL_L2_ESTADO_CIVIL – Path	COLUMN NAME	CL_L2_ESTADO_CIVIL
CL_L2_ESTADO_CIVIL – List	KNOWN VALUES	CL_L2_ESTADO_CIVIL

CLASSIFIER	KIND	DOMAIN
CL_L2_OCUPACION – Path	COLUMN NAME	CL_L2_OCUPACION
CL_L2_EMPLEADOR – Path	COLUMN NAME	CL_L2_EMPLEADOR
CL_L2_NIVEL_EDUCACIONAL – Path	COLUMN NAME	CL_L2_NIVEL_EDUCACIONAL
CL_L2_NIVEL_EDUCACIONAL – List	KNOWN VALUES	CL_L2_NIVEL_EDUCACIONAL
CL_L2_ESTABLECIMIENTO_EDUCACIONAL – Path	COLUMN NAME	CL_L2_ESTABLECIMIENTO_EDUCACIONAL
CL_L2_CARGAS_FAMILIARES – Path	COLUMN NAME	CL_L2_CARGAS_FAMILIARES
CL_L2_CARGAS_FAMILIARES – Type	DATA TYPE	CL_L2_CARGAS_FAMILIARES
CL_L3_ETNIA – Path	COLUMN NAME	CL_L3_ETNIA
CL_L3_ETNIA – List	KNOWN VALUES	CL_L3_ETNIA
CL_L3_SALUD_DIAGNOSTICO – Path	COLUMN NAME	CL_L3_SALUD_DIAGNOSTICO
CL_L3_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	CL_L3_SALUD_DIAGNOSTICO
CL_L3_SALUD_MEDICAMENTO – Path	COLUMN NAME	CL_L3_SALUD_MEDICAMENTO
CL_L3_SALUD_MEDICAMENTO – List	KNOWN VALUES	CL_L3_SALUD_MEDICAMENTO
CL_L3_SALUD_IDENTIFICADOR – Path	COLUMN NAME	CL_L3_SALUD_IDENTIFICADOR
CL_L3_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	CL_L3_SALUD_TEXTO_CLINICO
CL_L3_SALUD_TEXTO_CLINICO – Type	DATA TYPE	CL_L3_SALUD_TEXTO_CLINICO
CL_L3_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	CL_L3_SALUD_RESULTADO_EXAMEN
CL_L3_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	CL_L3_SALUD_GRUPO_SANGUINEO
CL_L3_SALUD_GRUPO_SANGUINEO – List	KNOWN VALUES	CL_L3_SALUD_GRUPO_SANGUINEO
CL_L3_SALUD_DISCAPACIDAD – Path	COLUMN NAME	CL_L3_SALUD_DISCAPACIDAD
CL_L3_SALUD_DISCAPACIDAD – List	KNOWN VALUES	CL_L3_SALUD_DISCAPACIDAD
CL_L3_SALUD_SEXUAL_REPRODUCTIVA – Path	COLUMN NAME	CL_L3_SALUD_SEXUAL_REPRODUCTIVA
CL_L3_SALUD_MENTAL_ADICCIONES – Path	COLUMN NAME	CL_L3_SALUD_MENTAL_ADICCIONES
CL_L3_BIOMETRICO – Path	COLUMN NAME	CL_L3_BIOMETRICO
CL_L3_BIOMETRICO – Type	DATA TYPE	CL_L3_BIOMETRICO
CL_L3_PERFIL_GENETICO – Path	COLUMN NAME	CL_L3_PERFIL_GENETICO
CL_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	CL_L3_ORIENTACION_SEXUAL
CL_L3_ORIENTACION_SEXUAL – List	KNOWN VALUES	CL_L3_ORIENTACION_SEXUAL
CL_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	CL_L3_IDENTIDAD_GENERO
CL_L3_IDENTIDAD_GENERO – List	KNOWN VALUES	CL_L3_IDENTIDAD_GENERO
CL_L3_VIDA_SEXUAL – Path	COLUMN NAME	CL_L3_VIDA_SEXUAL
CL_L3_RELIGION – Path	COLUMN NAME	CL_L3_RELIGION
CL_L3_RELIGION – List	KNOWN VALUES	CL_L3_RELIGION
CL_L3_CONVICCION_IDEOLOGICA – Path	COLUMN NAME	CL_L3_CONVICCION_IDEOLOGICA
CL_L3_CONVICCION_IDEOLOGICA – List	KNOWN VALUES	CL_L3_CONVICCION_IDEOLOGICA
CL_L3_AFILIACION_POLITICA – Path	COLUMN NAME	CL_L3_AFILIACION_POLITICA
CL_L3_AFILIACION_POLITICA – List	KNOWN VALUES	CL_L3_AFILIACION_POLITICA

CLASSIFIER	KIND	DOMAIN
CL_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	CL_L3_AFILIACION_SINDICAL
CL_L3_AFILIACION_GREMIAL – Path	COLUMN NAME	CL_L3_AFILIACION_GREMIAL
CL_L3_SOCIOEC_PREVISION_SALUD – Path	COLUMN NAME	CL_L3_SOCIOEC_PREVISION_SALUD
CL_L3_SOCIOEC_PREVISION_SALUD – List	KNOWN VALUES	CL_L3_SOCIOEC_PREVISION_SALUD
CL_L3_SOCIOEC_PLAN_SALUD – Path	COLUMN NAME	CL_L3_SOCIOEC_PLAN_SALUD
CL_L3_SOCIOEC_RSH – Path	COLUMN NAME	CL_L3_SOCIOEC_RSH
CL_L3_SOCIOEC_NIVEL – Path	COLUMN NAME	CL_L3_SOCIOEC_NIVEL
CL_L3_SOCIOEC_NIVEL – List	KNOWN VALUES	CL_L3_SOCIOEC_NIVEL
CL_L3_SOCIOEC_BENEFICIO_SOCIAL – Path	COLUMN NAME	CL_L3_SOCIOEC_BENEFICIO_SOCIAL
CL_L3_SOCIOEC_BENEFICIO_SOCIAL – List	KNOWN VALUES	CL_L3_SOCIOEC_BENEFICIO_SOCIAL
CL_L3_SOCIOEC_MOROSIDAD – Path	COLUMN NAME	CL_L3_SOCIOEC_MOROSIDAD
CL_L3_SOCIOEC_MONTO_DEUDA – Path	COLUMN NAME	CL_L3_SOCIOEC_MONTO_DEUDA
CL_L3_SOCIOEC_MONTO_DEUDA – Type	DATA TYPE	CL_L3_SOCIOEC_MONTO_DEUDA
CL_L3_SOCIOEC_INGRESOS – Path	COLUMN NAME	CL_L3_SOCIOEC_INGRESOS
CL_L3_SOCIOEC_INGRESOS – Type	DATA TYPE	CL_L3_SOCIOEC_INGRESOS
CL_L3_SOCIOEC_PREVISION_AFP – Path	COLUMN NAME	CL_L3_SOCIOEC_PREVISION_AFP
CL_L3_SOCIOEC_PREVISION_AFP – List	KNOWN VALUES	CL_L3_SOCIOEC_PREVISION_AFP
CL_L3_SOCIOEC_SALDO_PREVISIONAL – Path	COLUMN NAME	CL_L3_SOCIOEC_SALDO_PREVISIONAL
CL_L3_SOCIOEC_SALDO_PREVISIONAL – Type	DATA TYPE	CL_L3_SOCIOEC_SALDO_PREVISIONAL
CL_L3_SOCIOEC_VIVIENDA – Path	COLUMN NAME	CL_L3_SOCIOEC_VIVIENDA
CL_L3_SOCIOEC_VIVIENDA – List	KNOWN VALUES	CL_L3_SOCIOEC_VIVIENDA
CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS – Path	COLUMN NAME	CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS
CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS – List	KNOWN VALUES	CL_L3_SOCIOEC_FINANCIAMIENTO_ESTUDIOS
CL_L3_PENAL_ANTECEDENTES – Path	COLUMN NAME	CL_L3_PENAL_ANTECEDENTES
CL_L3_PENAL_CAUSA – Path	COLUMN NAME	CL_L3_PENAL_CAUSA
CL_L3_PENAL_CAUSA – Regex	VALUE FORMAT	CL_L3_PENAL_CAUSA