

Colombia — Ley 1581 de 2012

Discovery and masking of Colombian personal data: cédula and NIT with a valid check digit, quasi-identifiers, the sensitive data of article 5, victims of the armed conflict, financial data under Law 1266 of 2008 and criminal records.

82

DOMAINS

143

CLASSIFIERS

144

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	Ley 1581 de 2012 in brief
3	Anonymization, pseudonymization and non-production copies
4	How sensitive data is discovered
5	How data is masked
6	Essential and extended packs
7	Domains at a glance

PART 8 · DIRECT IDENTIFIERS

8.1	Cédula and identity document	CO_L1_CEDULA
8.2	NIT	CO_L1_NIT
8.3	Foreigner documents	CO_L1_DOCUMENTO_EXTRANJERO
8.4	Passport	CO_L1_PASAPORTE
8.5	Civil registry	CO_L1_REGISTRO_CIVIL
8.6	Professional card	CO_L1_TARJETA_PROFESIONAL
8.7	Given name	CO_L1_NOMBRE
8.8	Surname	CO_L1_APELLIDO
8.9	Full name	CO_L1_NOMBRE_COMPLETO
8.10	E-mail	CO_L1_EMAIL
8.11	Phone	CO_L1_TELEFONO
8.12	Address	CO_L1_DIRECCION
8.13	Address complement	CO_L1_DIRECCION_COMPLEMENTO
8.14	Bank account	CO_L1_CUENTA_BANCARIA
8.15	Payment card	CO_L1_TARJETA
8.16	Bre-B key	CO_L1_LLAVE_BREB
8.17	IP address	CO_L1_IP
8.18	Device identifier	CO_L1_DISPOSITIVO
8.19	Licence plate	CO_L1_PLACA
8.20	Vehicle	CO_L1_VEHICULO
8.21	Real estate	CO_L1_INMUEBLE
8.22	Contract and enrolment numbers	CO_L1_CONTRATO
8.23	User and social media	CO_L1_USUARIO
8.24	Credentials	CO_L1_CREDENCIAL

8.25	Geolocation	CO_L1_GEOLOCALIZACION
8.26	Free text	CO_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	CO_L2_FECHA_NACIMIENTO
9.2	Birth year	CO_L2_ANIO_NACIMIENTO
9.3	Age	CO_L2_EDAD
9.4	Personal event dates	CO_L2_FECHA_EVENTO
9.5	Sex	CO_L2_SEXO
9.6	Municipality	CO_L2_MUNICIPIO
9.7	Municipality code (DIVIPOLA)	CO_L2_CODIGO_MUNICIPIO
9.8	Postal code	CO_L2_CODIGO_POSTAL
9.9	Neighbourhood, locality and commune	CO_L2_BARRIO
9.10	Vereda and corregimiento	CO_L2_VEREDA
9.11	Nationality	CO_L2_NACIONALIDAD
9.12	Marital status	CO_L2_ESTADO_CIVIL
9.13	Occupation	CO_L2_OCUPACION
9.14	Employer	CO_L2_EMPLEADOR
9.15	Education	CO_L2_ESCOLARIDAD
9.16	Educational institution	CO_L2_INSTITUCION_EDUCATIVA
9.17	Dependants and children	CO_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA

10.1	Ethnic self-recognition	CO_L3_GRUPO_ETNICO
10.2	Indigenous people and ethnic community	CO_L3_PUEBLO_INDIGENA
10.3	Native language	CO_L3_LENGUA_NATIVA
10.4	Religion	CO_L3_RELIGION
10.5	Philosophical convictions	CO_L3_CONVICCION_FILOSOFICA
10.6	Political orientation	CO_L3_ORIENTACION_POLITICA
10.7	Party membership	CO_L3_AFILIACION_PARTIDO
10.8	Trade union membership	CO_L3_SINDICATO
10.9	Social and human rights organizations	CO_L3_ORGANIZACION_SOCIAL
10.10	Biometric data	CO_L3_BIOMETRICO
10.11	Genetic data	CO_L3_GENETICO
10.12	Sexual orientation	CO_L3_ORIENTACION_SEXUAL
10.13	Sexual life	CO_L3_VIDA_SEXUAL
10.14	Gender identity	CO_L3_IDENTIDAD_GENERO
10.15	Victim of the armed conflict	CO_L3_VICTIMA_CONFLICTO

PART 11 · HEALTH DATA

11.1	Health identifiers	CO_SALUD_IDENTIFICADOR
11.2	Health system affiliation	CO_SALUD_AFILIACION
11.3	Diagnosis and ICD-10	CO_SALUD_DIAGNOSTICO
11.4	Procedures (CUPS)	CO_SALUD_PROCEDIMIENTO
11.5	Medicines	CO_SALUD_MEDICAMENTO
11.6	Clinical text	CO_SALUD_TEXTO_CLINICO
11.7	Test results	CO_SALUD_RESULTADO_EXAMEN
11.8	Blood group and Rh	CO_SALUD_GRUPO_SANGUINEO
11.9	Disability	CO_SALUD_DISCAPACIDAD
11.10	Occupational health	CO_SALUD_OCUPACIONAL
11.11	Sexual and reproductive health	CO_SALUD_REPRODUCTIVA
11.12	Mental health	CO_SALUD_MENTAL

PART 12 · FINANCIAL AND SOCIOECONOMIC DATA

12.1	Credit bureaus	CO_FIN_CREDITO
12.2	Debt	CO_FIN_DEUDA
12.3	Income and salary	CO_FIN_INGRESOS
12.4	Assets	CO_FIN_PATRIMONIO
12.5	Pension and subsidies	CO_FIN_PENSION
12.6	Socioeconomic stratum	CO_FIN ESTRATO
12.7	Sisbén	CO_FIN SISBEN
12.8	Social programmes	CO_FIN_PROGRAMA_SOCIAL
12.9	Housing tenure	CO_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS AND PROCEEDINGS

13.1	Records	CO_PENAL_ANTECEDENTES
13.2	Case file number	CO_PENAL_RADICADO
14	The NIT check digit	
15	Where people live: municipalities, veredas and postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	

About this profile set

This profile set finds the personal data in a Colombian database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and cédulas alone is not enough: a birth date, a sex and a small municipality already point at one person. The set works in the layers where the risk is:

- **Direct identifiers** — cédula, identity card and NUIP, NIT, foreigner documents (cédula de extranjería, PPT, PEP), passport, civil registry, professional card, names, contact, address, accounts, cards and Bre-B key, devices, vehicles, real estate, free text.
- **Quasi-identifiers** — birth date, age, sex, municipality and DIVIPOLA code, postal code, neighbourhood, vereda, nationality, marital status, occupation, employer, education.
- **Sensitive data** — those of article 5: racial or ethnic origin, political orientation, religious or philosophical convictions, membership of trade unions, of social and human rights organizations and of parties, sexual life and biometric data — and, since the list is illustrative, genetic data, gender identity, being a victim of the armed conflict and being in the reincorporation process.
- **Health data** — sensitive under article 5 too, in a group of its own: medical record, health system affiliation, ICD-10, CUPS procedures, medicines, tests, blood group, disability, occupational, reproductive and mental health.
- **Financial data** — those of Law 1266 of 2008: credit bureau reports, debt, income, assets, pension; and those that reveal the socioeconomic situation: stratum, Sisbén IV, social programmes, housing tenure.
- **Criminal records and proceedings** — judicial, disciplinary and fiscal records, corrective measures, legal situation and case file numbers.

On a Masking Engine, the set is a profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those lean on — and the lookup files they read. The appendices list each of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it on its own; an ambiguous one — `NOMBRE` , `DOCUMENTO` , `CARGO` , `PROCESO` — needs the values to agree. A column whose name means nothing (`CAMP01` , `OBS`) is still found when the values have a recognizable format or vocabulary: a cédula with dots, a NIT, an address in the street grid notation, a plate, a municipality.

Column names are recognized in Spanish, in the abbreviations of Colombian systems (`NRO_DOCUMENTO` , `CC_CLIENTE` , `FEC_NAC` , `COD_MPIO` , `DX_PRINCIPAL` , `ESTRATO` , `GRUPO_SISBEN`) and in English.

Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often store a photo of the cédula — with the fingerprint and blood group — and a biometric validation selfie. Report those columns as residual risk.

Ley 1581 de 2012 in brief

Statutory Law 1581 of 17 October 2012 — Diario Oficial 48.587 — sets the general rules for personal data protection and develops the habeas data right of article 15 of the Constitution. It went through prior constitutional review (judgment C-748 of 2011) and is regulated by Decree 1377 of 2013, compiled in the Single Regulatory Decree 1074 of 2015. The authority is the **Superintendencia de Industria y Comercio (SIC)**, through its Delegation for Personal Data Protection.

What matters for a copy of production data:

- **Personal data** is any information linked or that can be associated with one or more determined or determinable natural persons (art. 3, c). Data that can no longer be associated with anyone ceases to be personal data.
- **Sensitive data** is data that affects the privacy of the data subject or whose misuse can lead to discrimination, *such as* data revealing racial or ethnic origin, political orientation, religious or philosophical convictions, membership of trade unions, social or human rights organizations or organizations promoting the interests of any political party or guaranteeing the rights of opposition parties, and data concerning health, sexual life and biometric data (art. 5). Processing it is **prohibited** save for the exceptions of article 6; for historical, statistical or scientific purposes the **suppression of the data subjects' identity** is required (art. 6, e).
- **Children and adolescents.** Processing their data is proscribed except for data of a public nature (art. 7); the Constitutional Court allowed it when it serves their best interest and respects their rights (C-748 of 2011), and Decree 1377 sets the requirements.
- **Principles.** Purpose, freedom, restricted access and circulation, **security** and **confidentiality** (art. 4): whoever takes part in the processing must prevent unauthorized or fraudulent consultation, use or access, and keep it confidential even after their work ends. A test database with real data, open to developers and vendors, hardly meets either.
- **Security incidents.** The controller informs the SIC of breaches of security codes (art. 17, n); the SIC sets a term of fifteen business days from detection, through the National Database Registry.
- **Sanctions.** Personal and institutional fines of up to 2,000 monthly minimum wages — in 2026, about 3.5 billion pesos —, suspension of processing for up to six months, temporary closure and **immediate and definitive closure** of any operation involving sensitive data (art. 23). Obtaining, compiling, selling or disclosing personal data without authorization is also a crime: article 269F of the Criminal Code (Law 1273 of 2009) punishes it with 48 to 96 months in prison.

Financial data. Databases governed by Law 1266 of 2008 — financial, credit and commercial habeas data — are outside Law 1581, but its principles apply to them (art. 2, e and paragraph). Law 2157 of 2021 limits how long negative data stays to twice the time in arrears, four years at most.

Archived reform. In August 2025 statutory bills 214 and 274 of 2025, merged, were filed in the House of Representatives to update Law 1581 (definitions of genetic and biometric data, profiling, automated decisions, higher fines). The bill passed its first debate in October 2025, and in September 2026 it is listed as **archived** on the House website: a statutory law must be passed within a single legislative term (art. 153 of the Constitution). This set follows the law in force.

Anonymization, pseudonymization and non-production copies

Law 1581 has no anonymization clause: the consequence follows from the definition of personal data. If data can no longer be associated with a determined or determinable person, it is not personal data. The **Guide to the Anonymization of Structured Data** of the Archivo General de la Nación (2020), written with the ICT Ministry, the SIC, the Civil Service Department, the National Planning Department and DANE, draws the line: **pseudonymization** replaces one attribute with another, does not produce completely anonymous records and *cannot be said to be an anonymization method*, although it reduces the risk of identification.

The algorithms of this set are deterministic for the key of the Masking Engine: the same cédula masks the same way in every table, which keeps joins working. So for whoever holds the key **and** production, the

masked copy can be linked back — it is pseudonymized and still personal data. For whoever holds only the copy, direct identifiers were replaced and quasi-identifiers generalized.

- Keep the engine key out of reach of the users of the masked copy.
- Do not hand the copy to people who also access production without need.
- Review quasi-identifiers the set does not know. The AGN guide and the DANE guide (2024) recommend measuring the re-identification risk before publishing or sharing.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters:

`rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	25	36	5
Extended	82	143	144	89

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- Cédula and identity document — CO_L1_CEDULA
- NIT — CO_L1_NIT
- Foreigner documents — CO_L1_DOCUMENTO_EXTRANJERO
- Passport — CO_L1_PASAPORTE
- Given name — CO_L1_NOMBRE
- Surname — CO_L1_APELLIDO
- Full name — CO_L1_NOMBRE_COMPLETO
- E-mail — CO_L1_EMAIL
- Phone — CO_L1_TELEFONO
- Address — CO_L1_DIRECCION
- Address complement — CO_L1_DIRECCION_COMPLEMENTO
- Birth date — CO_L2_FECHA_NACIMIENTO

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM	
DIRECT IDENTIFIERS					
Cédula and identity document	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	CO_DOCUMENTO
CO_L1_CEDULA					
NIT	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CO_NIT
CO_L1_NIT					
Foreigner documents	ESSENTIAL	COLUMN NAME			CO_CM_ALFANUM
CO_L1_DOCUMENTO_EXTRANJERO					
Passport	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CO_CM_ALFANUM
CO_L1_PASAPORTE					
Civil registry		COLUMN NAME			CO_CM_ALFANUM
CO_L1_REGISTRO_CIVIL					
Professional card		COLUMN NAME			CO_CM_ALFANUM
CO_L1_TARJETA_PROFESIONAL					
Given name	ESSENTIAL	COLUMN NAME	KNOWN VALUES		CO_NOMBRES
CO_L1_NOMBRE					
Surname	ESSENTIAL	COLUMN NAME	KNOWN VALUES		CO_APELLIDOS
CO_L1_APELLIDO					
Full name	ESSENTIAL	COLUMN NAME	KNOWN VALUES		CO_NOMBRE_COMPLETO
CO_L1_NOMBRE_COMPLETO					
E-mail	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	CO_EMAIL
CO_L1_EMAIL					
Phone	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CO_TELEFONO
CO_L1_TELEFONO					
Address	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	CO_DIRECCION
CO_L1_DIRECCION					
Address complement	ESSENTIAL	COLUMN NAME			CO_CM_ALFANUM
CO_L1_DIRECCION_COMPLEMENTO					
Bank account		COLUMN NAME			CO_CM_DIGITOS
CO_L1_CUENTA_BANCARIA					
Payment card		COLUMN NAME	VALUE FORMAT		CO_TARJETA
CO_L1_TARJETA					
Bre-B key		COLUMN NAME	VALUE FORMAT		CO_LLAVE_BREB
CO_L1_LLAVE_BREB					
IP address		COLUMN NAME	VALUE FORMAT		CO_IP
CO_L1_IP					
Device identifier		COLUMN NAME	VALUE FORMAT		CO_CM_HEX
CO_L1_DISPOSITIVO					
Licence plate		COLUMN NAME	VALUE FORMAT		CO_PLACA
CO_L1_PLACA					

DOMAIN	FOUND BY	ALGORITHM
Vehicle CO_L1_VEHICULO	COLUMN NAMEVALUE FORMAT	CO_CM_ALFANUM
Real estate CO_L1_INMUEBLE	COLUMN NAMEVALUE FORMAT	CO_INMUEBLE
Contract and enrolment numbers CO_L1_CONTRATO	COLUMN NAME	CO_CM_ALFANUM
User and social media CO_L1_USUARIO	COLUMN NAME	CO_CM_ALFANUM
Credentials CO_L1_CREDENCIAL	COLUMN NAME	CO_REDACTAR
Geolocation CO_L1_GEOLOCALIZACION	COLUMN NAMEVALUE FORMAT	CO_COORDENADA
Free text CO_L1_TEXTO_LIBRE	COLUMN NAMEDATA TYPEVALUE FORMAT	CO_TEXTO_LIBRE
QUASI-IDENTIFIERS		
Birth date ESSENTIAL CO_L2_FECHA_NACIMIENTO	COLUMN NAMEDATA TYPE	CO_FECHA_NACIMIENTO
Birth year CO_L2_ANIO_NACIMIENTO	COLUMN NAMEDATA TYPE	CO_ANIO
Age CO_L2_EDAD	COLUMN NAMEDATA TYPE	CO_EDAD
Personal event dates CO_L2_FECHA_EVENTO	COLUMN NAMEDATA TYPE	CO_FECHA_EVENTO
Sex CO_L2_SEXO	COLUMN NAMEKNOWN VALUES	CO_SEXO
Municipality CO_L2_MUNICIPIO	COLUMN NAMEKNOWN VALUES	CO_MUNICIPIO
Municipality code (DIVIPOLA) CO_L2_CODIGO_MUNICIPIO	COLUMN NAMEVALUE FORMAT	CO_CODIGO_MUNICIPIO
Postal code CO_L2_CODIGO_POSTAL	COLUMN NAMEDATA TYPE	CO_CODIGO_POSTAL
Neighbourhood, locality and commune CO_L2_BARRIO	COLUMN NAME	CO_BARRIO
Vereda and corregimiento CO_L2_VEREDA	COLUMN NAME	CO_ZONA_RURAL
Nationality CO_L2_NACIONALIDAD	COLUMN NAMEKNOWN VALUES	CO_NACIONALIDAD
Marital status CO_L2_ESTADO_CIVIL	COLUMN NAMEKNOWN VALUES	CO_ESTADO_CIVIL
Occupation CO_L2_OCUPACION	COLUMN NAME	CO_OCUPACION_O_CIUO
Employer CO_L2_EMPLEADOR	COLUMN NAME	CO_EMPLEADOR
Education CO_L2_ESCOLARIDAD	COLUMN NAMEKNOWN VALUES	CO_ESCOLARIDAD

DOMAIN	FOUND BY		ALGORITHM
Educational institution CO_L2_INSTITUCION_EDUCATIVA	COLUMN NAME		CO_INSTITUCION_EDUCATIVA
Dependants and children CO_L2_PERSONAS_A_CARGO	COLUMN NAME	DATA TYPE	CO_CONTEO_LIMITADO
SENSITIVE DATA			
Ethnic self-recognition CO_L3_GRUPO_ETNICO	COLUMN NAME	KNOWN VALUES	CO_GRUPO_ETNICO
Indigenous people and ethnic community CO_L3_PUEBLO_INDIGENA	COLUMN NAME	KNOWN VALUES	CO_PUEBLO_INDIGENA
Native language CO_L3_LENGUA_NATIVA	COLUMN NAME	KNOWN VALUES	CO_LENGUA
Religion CO_L3_RELIGION	COLUMN NAME	KNOWN VALUES	CO_RELIGION
Philosophical convictions CO_L3_CONVICCION_FILOSOFICA	COLUMN NAME		CO_CATEGORIA_SUPRIMIDA
Political orientation CO_L3_ORIENTACION_POLITICA	COLUMN NAME	KNOWN VALUES	CO_ORIENTACION_POLITICA
Party membership CO_L3_AFILIACION_PARTIDO	COLUMN NAME	KNOWN VALUES	CO_PARTIDO
Trade union membership CO_L3_SINDICATO	COLUMN NAME	KNOWN VALUES	CO_CATEGORIA_SUPRIMIDA
Social and human rights organizations CO_L3_ORGANIZACION_SOCIAL	COLUMN NAME		CO_CATEGORIA_SUPRIMIDA
Biometric data CO_L3_BIOMETRICO	COLUMN NAME	DATA TYPE	CO_REDACTAR
Genetic data CO_L3_GENETICO	COLUMN NAME		CO_REDACTAR
Sexual orientation CO_L3_ORIENTACION_SEXUAL	COLUMN NAME	KNOWN VALUES	CO_ORIENTACION_SEXUAL
Sexual life CO_L3_VIDA_SEXUAL	COLUMN NAME		CO_CATEGORIA_SUPRIMIDA
Gender identity CO_L3_IDENTIDAD_GENERO	COLUMN NAME	KNOWN VALUES	CO_IDENTIDAD_GENERO
Victim of the armed conflict CO_L3_VICTIMA_CONFLICTO	COLUMN NAME	KNOWN VALUES	CO_VICTIMA
Reincorporation CO_L3_REINCORPORACION	COLUMN NAME		CO_CATEGORIA_SUPRIMIDA
HEALTH DATA			
Health identifiers CO_SALUD_IDENTIFICADOR	COLUMN NAME		CO_CM_ALFANUM
Health system affiliation CO_SALUD_AFILIACION	COLUMN NAME	KNOWN VALUES	CO_AFILIACION_SALUD
Diagnosis and ICD-10 CO_SALUD_DIAGNOSTICO	COLUMN NAME	VALUE FORMAT	CO_DIAGNOSTICO

DOMAIN	FOUND BY	ALGORITHM
Procedures (CUPS) CO_SALUD_PROCEDIMIENTO	COLUMN NAME	CO_PROCEDIMIENTO
Medicines CO_SALUD_MEDICAMENTO	COLUMN NAME KNOWN VALUES	CO_MEDICAMENTO
Clinical text CO_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	CO_TEXTO_LIBRE
Test results CO_SALUD_RESULTADO_EXAMEN	COLUMN NAME	CO_CM_ALFANUM
Blood group and Rh CO_SALUD_GRUPO_SANGUINEO	COLUMN NAME KNOWN VALUES	CO_GRUPO_SANGUINEO
Disability CO_SALUD_DISCAPACIDAD	COLUMN NAME KNOWN VALUES	CO_DISCAPACIDAD
Occupational health CO_SALUD_OCUPACIONAL	COLUMN NAME KNOWN VALUES	CO_SALUD_LABORAL
Sexual and reproductive health CO_SALUD_REPRODUCTIVA	COLUMN NAME	CO_CATEGORIA_SUPRIMIDA
Mental health CO_SALUD_MENTAL	COLUMN NAME	CO_CATEGORIA_SUPRIMIDA
FINANCIAL AND SOCIOECONOMIC DATA		
Credit bureaus CO_FIN_CREDITO	COLUMN NAME	CO_CREDITO
Debt CO_FIN_DEUDA	COLUMN NAME DATA TYPE	CO_VALOR_DEUDA
Income and salary CO_FIN_INGRESOS	COLUMN NAME DATA TYPE	CO_INGRESOS
Assets CO_FIN_PATRIMONIO	COLUMN NAME DATA TYPE	CO_PATRIMONIO
Pension and subsidies CO_FIN_PENSION	COLUMN NAME DATA TYPE	CO_VALOR_PENSION
Socioeconomic stratum CO_FIN ESTRATO	COLUMN NAME KNOWN VALUES	CO_ESTRATO
Sisbén CO_FIN_SISBEN	COLUMN NAME VALUE FORMAT	CO_SISBEN
Social programmes CO_FIN_PROGRAMA_SOCIAL	COLUMN NAME KNOWN VALUES	CO_PROGRAMA_SOCIAL
Housing tenure CO_FIN_VIVIENDA	COLUMN NAME KNOWN VALUES	CO_TENENCIA_VIVIENDA
CRIMINAL RECORDS AND PROCEEDINGS		
Records CO_PENAL_ANTECEDENTES	COLUMN NAME	CO_ANTECEDENTES
Case file number CO_PENAL_RADICADO	COLUMN NAME VALUE FORMAT	CO_RADICADO

Direct identifiers

Data that identifies a person on its own. The cédula is the key of almost every Colombian record, and the same number follows a person through life: the NUIP of the civil registry is that of the identity card and then of the cédula, the driving licence and the military service card, and with a check digit it is their NIT. It is masked the same way everywhere, and the NIT comes out with a valid check digit, because applications validate it.

8.1 Cédula and identity document

CO_L1_CEDULA

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The number of the cédula de ciudadanía issued by the National Civil Registry — 3 to 10 digits, written with thousands dots, 79.456.123 , 1.023.456.789 —, and those that share its number: the identity card and NUIP of minors, the driving licence and the military service card.

NUMERO_DOCUMENTO columns often mix cédulas, identity cards, NITs with their digit and passports: each value is masked by its shape.

HOW IT IS FOUND

COLUMN NAME CO_L1_CEDULA – Path

90% c[eé]dula(_?(de_)?ciudadan[íí]a)? cc c_c n(o|ro|um|umero|u)?
(cc|c[eé]dula|documento|doc|identificaci[oó]n|id(ent)?) documento?(de_)?identidad doc_
identidad identificaci[oó]n(_?
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|f
uncionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|pr
opietario|arrendatario|conductor|acudiente|responsable|representante|persona|ciudadano|votante
|contribuyente|proveedor|tercero|cotizante))?
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|
funcionario|trabajador|contratista|estudiante|alumno|deudor|codeudor|fiador|avalista|tomador|p
ropietario|arrendatario|conductor|acudiente|responsable|representante|persona|ciudadano|votant
e|contribuyente|proveedor|tercero|cotizante)?(cc|c[eé]dula|documento|doc|identificaci[oó]n)
tarjeta?(de_)?identidad nuip numero?unico?identificacion?personal licencia?(de_)?
conducci[oó]n(_?(n(o|ro|um|umero)))? pase?(de_)?conducci[oó]n libreta?militar(_?
(n(o|ro|um|umero)))? n(o|ro|um|umero)?libreta

60% documento doc_?id id_?documento nit_?cc cc_?nit

DATA TYPE CO_L1_CEDULA – Type

Accepts text (length 3 or more) or number (length 3 or more); any other type rules the domain out.

VALUE FORMAT CO_L1_CEDULA – Regex

PATTERN	STRENGTH	NOTES
\d{1,3}(\.\d{3}){1,3}		80%
1\d{9}		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, keeping the length and the dots. The mapping is one-to-one: a cédula used as a key does not collide, and the same number masks the same way on the identity card, the licence and the military card. A value with a check digit is masked as a NIT; one with letters, character by character.

CO_DOCUMENTO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CO_NIT_6 STRING ALGORITHM CHAIN

Applies CO_NIT_6_AUX → CO_NIT_6_AJUSTE , in this order.

CO_NIT_6_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 from the right.

CO_NIT_6_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_6_DV .

CO_NIT_6_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 from the right.

CO_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CO_NIT_7 STRING ALGORITHM CHAIN

Applies CO_NIT_7_AUX → CO_NIT_7_AJUSTE , in this order.

CO_NIT_7_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 from the right.

CO_NIT_7_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_7_DV .

CO_NIT_7_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 from the right.

CO_NIT_8 STRING ALGORITHM CHAIN

Applies CO_NIT_8_AUX → CO_NIT_8_AJUSTE , in this order.

CO_NIT_8_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 from the right.

CO_NIT_8_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_8_DV .

CO_NIT_8_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 from the right.

CO_NIT_9 STRING ALGORITHM CHAIN

Applies CO_NIT_9_AUX → CO_NIT_9_AJUSTE , in this order.

CO_NIT_9_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 82 from the right.

CO_NIT_9_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_9_DV .

CO_NIT_9_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 41 from the right.

CO_NIT_10 STRING ALGORITHM CHAIN

Applies `CO_NIT_10_AUX` → `CO_NIT_10_AJUSTE`, in this order.

`CO_NIT_10_AUX` **CHECK DIGIT**

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 82 86 from the right.

`CO_NIT_10_AJUSTE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_10_DV`.

`CO_NIT_10_DV` **CHECK DIGIT**

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 41 43 from the right.

`CO_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
79.456.123	→	69.583.619
1023456789	→	2556091343
800197268-4	→	265590357-6

8.2

NIT

`CO_L1_NIT`

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The tax identification number of the DIAN's RUT with its check digit, `800.197.268-4`. A natural person's is their cédula plus the digit; a legal entity's has nine digits and starts with 8 or 9.

The digit uses the weights 3, 7, 13, 17, 19, 23, 29, 37, 41, 43, 47, 53, 59, 67 and 71 from the right, modulus 11: when the remainder is 0 or 1 the digit is the remainder, otherwise eleven minus the remainder.

HOW IT IS FOUND

COLUMN NAME

`CO_L1_NIT` - Path

90%

`nit[a-z0-9]* n(o|ro|um|umero)?nit nit_?`

`(proveedor|cliente|empresa|tercero|emisor|adquiriente|receptor|contribuyente|empleador)`

`(proveedor|cliente|empresa|tercero|emisor|adquiriente|receptor|empleador)?nit rut`

`registro?unico?tributario n(o|ro|um|umero)?identificacion?tributaria`

VALUE FORMAT

`CO_L1_NIT` - Regex

PATTERN

STRENGTH

NOTES

`\d{3}\.?\d{3}\.?\d{3}-\d`

90%

`\d{1,3}(\.\d{3}){1,3}-\d`

80%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The body is mapped digit by digit — with the same algorithm as the cédula, so a person's NIT still matches their cédula — and the check digit is recomputed. Every masked NIT is valid and the mapping is one-to-one. See *The NIT check digit*.

`CO_NIT` **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.

`CO_NIT_6` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_6_AUX` → `CO_NIT_6_AJUSTE` , in this order.

`CO_NIT_6_AUX` **CHECK DIGIT**

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 from the right.

`CO_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

`CO_NIT_6_AJUSTE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_6_DV` .

`CO_NIT_6_DV` **CHECK DIGIT**

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 from the right.

`CO_IDENTIDAD` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`CO_NIT_7` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_7_AUX` → `CO_NIT_7_AJUSTE` , in this order.

`CO_NIT_7_AUX` **CHECK DIGIT**

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 from the right.

`CO_NIT_7_AJUSTE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_7_DV` .

`CO_NIT_7_DV` **CHECK DIGIT**

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 from the right.

`CO_NIT_8` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_8_AUX` → `CO_NIT_8_AJUSTE` , in this order.

`CO_NIT_8_AUX` **CHECK DIGIT**

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 from the right.

`CO_NIT_8_AJUSTE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_8_DV` .

`CO_NIT_8_DV` **CHECK DIGIT**

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 from the right.

`CO_NIT_9` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_9_AUX` → `CO_NIT_9_AJUSTE` , in this order.

`CO_NIT_9_AUX` **CHECK DIGIT**

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 82 from the right.

`CO_NIT_9_AJUSTE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_9_DV` .

`CO_NIT_9_DV` **CHECK DIGIT**

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 41 from the right.

`CO_NIT_10` **STRING ALGORITHM CHAIN**

Applies `CO_NIT_10_AUX` → `CO_NIT_10_AJUSTE` , in this order.

`CO_NIT_10_AUX` **CHECK DIGIT**

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 82 86 from the right.

`CO_NIT_10_AJUSTE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_10_DV` .

`CO_NIT_10_DV` **CHECK DIGIT**

Masks the digits with `CO_IDENTIDAD` and recomputes a modulus 11 check digit with weights `3 7 13 17 19 23 29 37 41 43` from the right.

EXAMPLES

VALUE		MASKED
800.197.268-4	→	265.590.357-6
79456123-7	→	69583619-0

8.3 Foreigner documents

CO_L1_DOCUMENTO_EXTRANJERO

ESSENTIAL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The cédula de extranjería, the Temporary Protection Permit (PPT) of Venezuelan migrants, the Special Stay Permit (PEP), the safe-conduct and the visa number.

HOW IT IS FOUND

COLUMN NAME

CO_L1_DOCUMENTO_EXTRANJERO - Path

85%

`c[eé]dula?(de_)?extranjer[ií]a` `ce` `c_e` `ppt` `permiso?(por_)?protecci[oó]n?temporal`
`pep` `permiso?especial?(de_)?permanencia` `salvoconducto` `visa(_?(n(o|ro|um|umero)))?`
`n(o|ro|um|umero)?(ce|ppt|pep|visa)` `documento?migratorio` `carne?diplom[aá]tico`

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PEP 123456789	→	BAK 712017988

8.4 Passport

CO_L1_PASAPORTE

ESSENTIAL

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

Colombian passport numbers — two letters and six or seven digits, `AB123456` — and foreign ones.

HOW IT IS FOUND

COLUMN NAME

CO_L1_PASAPORTE - Path

90%

`pasaporte[a-z0-9]*` `n(o|ro|um|umero)?pasaporte` `passport[a-z0-9]*`

VALUE FORMAT

CO_L1_PASAPORTE - Regex

PATTERN

STRENGTH

NOTES

`[A-Z]{2}\d{6,7}`

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AB123456	→	0X623407

8.5 Civil registry

CO_L1_REGISTRO_CIVIL

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The serial indicator of birth, marriage and death records, and the number of the live birth or death certificate.

HOW IT IS FOUND

COLUMN NAME CO_L1_REGISTRO_CIVIL – Path

85% registro_?civil(_?(de_)?(nacimiento|matrimonio|defunci[oó]n))?(_?
(serial|indicativo|n(o|ro|um|umero)))? _?indicativo_?serial _?registro _?certificado_?
(de_)?(nacido_?vivo|defunci[oó]n) _?n(o|ro|um|umero)_?(registro_?civil|certificado_?
defuncion)

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
52345678	→	11443774

8.6 Professional card

CO_L1_TARJETA_PROFESIONAL

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The number of the professional card or registration and of the ReTHUS health workforce registry. Professional councils publish these registers with the person's name.

HOW IT IS FOUND

COLUMN NAME CO_L1_TARJETA_PROFESIONAL – Path

85% tarjeta_?profesional(_?(n(o|ro|um|umero)))? _?t_?p _?n(o|ro|um|umero)_?tarjeta_?profesional
matr[ií]cula_?profesional _?registro_?(m[eé]dico|profesional) _?rethus _?registro_?rethus

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

123456-T

→

111512-X

8.7 Given name

CO_L1_NOMBRE

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The given name, one or two: Luz , Juan Carlos , María del Pilar .

HOW IT IS FOUND

COLUMN NAME

CO_L1_NOMBRE - Path

85%

primer_?nombre segundo_?nombre nombres?_?(de_?)?pila pri(mer)?_?nom seg(undo)?_?nom
nombre_?1 nombre_?2 first_?names? given_?names? fname middle_?names? nombres (except
when followed by completos? , y_?apellidos? , apellidos?)

50%

nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)

KNOWN VALUES

CO_L1_NOMBRE - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-nombres.txt

280

70%

María, Maria, José, Jose, Luis, Carlos

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, each name replaced with one from the list. de , del and la stay in place. More than three words are masked character by character.

CO_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NOMBRE .

CO_NOMBRE NAME

Replaces the name with one of the 232 names in co-nombres.txt .

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

María del Pilar

→

Elizabeth del Blanca

JUAN CARLOS

→

NATALIA ORLANDO

8.8 Surname

CO_L1_APELLIDO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The surnames — the first, the father's, and the second, the mother's —, in separate columns or together, and the married name: López de Gómez .

HOW IT IS FOUND

COLUMN NAME

CO_L1_APELLIDO - Path

85%

apellidos?

primer_?apellido

segundo_?apellido

pri(mer)?_?ape

seg(undo)?_?ape

apellido_?(1|2|paterno|materno|casada)

ape_?(1|2)

last_?names?

surnames?

family_?

names?

lname

KNOWN VALUES

CO_L1_APELLIDO - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-apellidos.txt	328	70%	Rodríguez, Rodriguez, Gómez, Gomez, González, Gonzalez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, each surname replaced with one from the list; particles stay in place.

CO_APELLIDOS

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

CO_CM_ALFANUM

 .

CO_PALABRA_APELLIDO

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

CO_APELLIDO

 .

CO_APELLIDO

NAME

Replaces the name with one of the 255 names in

co-apellidos.txt

 .

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
López de Gómez	→ Rengifo de Pinzón

8.9 Full name

CO_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column:

Juan Carlos Rodríguez Gómez

 . Also those of the mother, father, guardian, spouse, personal or family reference, and the identity name of a trans person.

A column called just

NOMBRE

 may hold given names or full names: the values decide between the two domains.

HOW IT IS FOUND

COLUMN NAME CO_L1_NOMBRE_COMPLETO - Path

90%	nombres?_(completos? y_apellidos? apellidos?) nombre_?razon_?social nombre_?(del_ de_la_)? (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado funcionario trabajador contratista estudiante alumno deudor codeudor fiador avalista tomador propietario arrendatario arrendador conductor acudiente responsable representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto referencia victima denunciante sindicado imputado procesado testigo medico docente socio accionista heredero causante donante tutor curador cotizante customer patient employee member holder mother father spouse contact person student driver owner) (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado funcionario trabajador contratista estudiante alumno deudor codeudor fiador avalista tomador propietario arrendatario arrendador conductor acudiente responsable representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto referencia victima denunciante sindicado imputado procesado testigo medico docente socio accionista heredero causante donante tutor curador cotizante customer patient employee member holder mother father spouse contact person student driver owner)?(nombre nom) nom_? (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado funcionario trabajador contratista estudiante alumno deudor codeudor fiador avalista tomador propietario arrendatario arrendador conductor acudiente responsable representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto referencia victima denunciante sindicado imputado procesado testigo medico docente socio accionista heredero causante donante tutor curador cotizante customer patient employee member holder mother father spouse contact person student driver owner) nombre_?(madre padre acudiente conyuge contacto_?emergencia referencia) full_?name person_?name
60%	madre padre acudiente conyuge companero_?permanente representante_?legal apoderado codeudor fiador beneficiario heredero titular referencia_?(personal familiar)
50%	nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)

KNOWN VALUES CO_L1_NOMBRE_COMPLETO - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-nombres.txt	280	60%	María, Maria, José, Jose, Luis, Carlos
co-detectar-apellidos.txt	328	60%	Rodríguez, Rodriguez, Gómez, Gomez, González, Gonzalez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

In Colombian order: two words are a given name and a surname; three, a given name and two surnames; four, two and two; five, two given names and three words of surnames. SURNAMES, GIVEN NAMES with a comma, as in lists, is recognized too. The result is a plausible name, never the original.

CO_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_APELLIDO .

CO_APELLIDO NAME

Replaces the name with one of the 255 names in co-apellidos.txt .

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NOMBRE .

CO_NOMBRE NAME

Replaces the name with one of the 232 names in co-nombres.txt .

EXAMPLES

VALUE		MASKED
Juan Carlos Rodríguez Gómez	→	Natalia Orlando Lara Pinzón
Luz Rodríguez	→	Maximiliano Lara
RODRÍGUEZ GÓMEZ, JUAN CARLOS	→	LARA PINZÓN, NATALIA ORLANDO

8.10 E-mail

CO_L1_EMAIL

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Personal and corporate e-mail addresses.

HOW IT IS FOUND

COLUMN NAME CO_L1_EMAIL - Path

85% e_?mail[a-z0-9_]* mail[a-z0-9_]* correo(?:electr[oó]nico)?[a-z0-9_]* dir_?correo
direcci[oó]n_?(de_)?correo direcci[oó]n_?electr[oó]nica

DATA TYPE CO_L1_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT CO_L1_EMAIL - Regex

PATTERN	STRENGTH	NOTES
[A-Za-z0-9._%+'\-\-]+@[A-Za-z0-9.\-\-]+\.[A-Za-z]{2,24}	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

User and domain are mapped character by character, and the top-level domain — .com , .com.co — becomes .test , reserved for testing: a masked address never delivers a message.

CO_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

luz.rodriguez@gmail.com

→

vim.seskotuuk@pgoeb.test

8.11 Phone

CO_L1_TELEFONO

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Ten-digit numbers since the 2021 numbering plan: mobiles starting with 3 (310 456 7890) and landlines starting with 60 and the regional digit (601 345 6789 in Bogotá, 604 in Antioquia), with or without +57 . Also seven-digit landlines from before 2021.

HOW IT IS FOUND

COLUMN NAME

CO_L1_TELEFONO - Path

85%

```
tel tel[eé]fono[a-z0-9]* tel_?(fijo|movil|m[ó]vil|celular|casa|oficina|contacto)
celular[a-z0-9]* cel m[ó]vil whats_app n(o|ro|um|umero)?
(tel|tel[eé]fono|celular|cel|contacto|movil) fax ext(ension)?_?tel phone[a-z0-9]*
mobile[a-z0-9]*
```

VALUE FORMAT

CO_L1_TELEFONO - Regex

PATTERN

STRENGTH

NOTES

```
(\+?57[\s\-\]?)?3[0-2]\d[\s\-\]?\d{3}[\s\-\]?\d{4}
```

100%

```
(\+?57[\s\-\]?)?\(?60[1-8]\)?[\s\-\]?\d{3}[\s\-\]?\d{4}
```

90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The +57 , the first three digits — the operator's range or the region — and the separators stay; the other seven digits are mapped.

CO_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_CM_DIGITOS .

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

+57 310 456 7890

→

+57 310 047 9607

601 345 6789

→

601 203 7290

8.12 Address

CO_L1_DIRECCION

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

SECURE LOOKUP

WHAT IT IS

The address in the urban grid notation — the street, its number, the crossing street and the distance to it: Carrera 7 # 32-16 , Cl 100 No. 19-54 Apto 802 —, which places a door on a block, and rural addresses with a vereda, farm or kilometre.

HOW IT IS FOUND

COLUMN NAME CO_L1_DIRECCION - Path

80% `direcci[oó]n[a-z0-9]*` (except when preceded by `mac`, `ip`, `e_mail`, `web`, `url`, `correo`; except when followed by `list E4`) `dir_?`
`(residencia|domicilio|correspondencia|notificaci[oó]n|entrega|cobro|oficina|trabajo|cliente|paciente)?` (except when preceded by `mac`, `ip`, `e_mail`, `web`, `url`; except when followed by `ip`, `mac`, `correo`, `email`)
`domicilio[a-z0-9]*` `residencia` `lugar_?(de_)?residencia` `address[a-z0-9]*` (except when preceded by `mac`, `ip`, `e_mail`, `web`, `url`; except when followed by `list E5`)

DATA TYPE CO_L1_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT CO_L1_DIRECCION - Regex

PATTERN	STRENGTH	NOTES
<code>(?i)((av avenida)\.?\s+)?(calle cll? carrera cra crr kra? cr avenida av ak ac diagonal dg transversal tv tr circular cq autopista aut)\.? \s*\d+\s*[a-z]?(\s*(bis sur este))?\s*(# no\.? n[º]) num\.)?\s*\d+\s*[a-z]?(\s* \s*\d+.*</code>	90%	
<code>(?i).*\b(vereda finca corregimiento kil[oó]metro km)\b.*</code>	40%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced with a fictitious Colombian address in the same notation. Neighbourhood, vereda, municipality and postal code in their own columns are handled by their domains.

CO_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `co-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Carrera 7 # 32-16 Oficina 1203	→ Carrera 52 # 100-66

8.13 Address complement

CO_L1_DIRECCION_COMPLEMENTO

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

Apartment, interior, tower, block, lot, floor or office in their own columns.

HOW IT IS FOUND

COLUMN NAME CO_L1_DIRECCION_COMPLEMENTO - Path

70% `complemento(_?direcci[oó]n)?` `apto` `apartamento` `interior` `int` `torre` `bloque` `casa_?`
`(n(o|ro|um|umero))?` `manzana` `mz` `lote` `piso` `oficina` `local` `conjunto(_?residencial)?`
`edificio`

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Torre 3 Apto 502

→

Hablu 6 Ihye 654

8.14 Bank account

CO_L1_CUENTA_BANCARIA

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Savings and current account numbers, low-value deposits and wallets. The bank code is not personal data and has no domain.

HOW IT IS FOUND

COLUMN NAME

CO_L1_CUENTA_BANCARIA – Path

85%

cuenta_?(bancaria|banco|ahorros?

|corriente|n[oó]mina|deposito|dep[oó]sito|abono|pago|destino|origen) n(o|ro|um|umero)?

cuenta nro_?cta num_?cta cta_?(bancaria|ahorros|corriente) tipo_?y_?n(o|ro|um|umero)?

cuenta iban account_?(no|num|number) bank_?account dep[oó]sito_?electr[oó]nico

billetera

HOW IT IS MASKED

Digits are mapped; separators stay.

CO_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

123-456789-01

→

061-766269-22

8.15 Payment card

CO_L1_TARJETA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, recognized by the Luhn algorithm.

HOW IT IS FOUND

COLUMN NAME

CO_L1_TARJETA – Path

85%

tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))? n(o|ro|um|umero)?tarjeta pan card_?

(no|num|number) credit_?card tc_?(numero|num)

VALUE FORMAT

CO_L1_TARJETA – Regex

PATTERN

STRENGTH

NOTES

\d{13,19}

90%

LUHN check digit; after removing [\s\~]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Payment Card: another number that passes the Luhn check. Only values shaped like a card reach it.

CO_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CO_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE		MASKED
4539 5787 6362 1486	→	1912 8421 0957 2974

8.16 Bre-B key

CO_L1_LLAVE_BREB

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The key of Bre-B, the instant payment system of the Banco de la República: an identity document number, a mobile number, an e-mail or an alphanumeric key starting with @.

HOW IT IS FOUND

COLUMN NAME

CO_L1_LLAVE_BREB - Path

90%

llave(?:bre_b|breb|pago|transferencia)? bre_b(?:llave)? breb llave?alfanum[eé]rica

VALUE FORMAT

CO_L1_LLAVE_BREB - Regex

PATTERN

STRENGTH

NOTES

@[A-Za-z0-9]{3,20}

60%

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Each kind of key is masked as its own domain: the document digit by digit, the mobile keeping its range, the e-mail with .test, the alphanumeric key character by character keeping the @. A key holding the cédula and the same person's cédula still agree.

CO_LLAVE_BREB REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM.

CO_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_ALFANUM.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_CM_DIGITOS.

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
@luzrodriguez83	→	@tofbetxutiib61
3104567890	→	3100479607

8.17 IP address

CO_L1_IP

- COLUMN NAME
- VALUE FORMAT
- REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses from access and transaction logs.

HOW IT IS FOUND

COLUMN NAME

CO_L1_IP - Path

85%

ipip?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)direcci[ó]n?ipdir?ipipv[46]remote?addr(ess)?client?iphost?ip

VALUE FORMAT

CO_L1_IP - Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)	100%	
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to 1-254; an IPv6 is mapped keeping its hexadecimal characters.

CO_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_HEX .

- CO_OCTETO

NUMERIC MAPPING
Maps the number to another between 1 and 254.
- CO_CM_HEX

CHARACTER MAPPING
Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
190.85.46.120	→ 164.54.50.254

8.18 Device identifier

CO_L1_DISPOSITIVO

- COLUMN NAME
- VALUE FORMAT
- CHARACTER MAPPING

WHAT IT IS

IMEI — which in Colombia is registered with the operators against theft —, IMSI, ICCID, MAC address, advertising identifiers, cookies and sessions.

HOW IT IS FOUND

COLUMN NAME

CO_L1_DISPOSITIVO - Path

80%

imeiimsiiccidmacmac?addressdirecci[ó]n?macdevice?(id|uuid|serial)id?(dispositivo|equipo|celular)serial?(equipo|celular|dispositivo)advertising?ididfa
gaidcookie(_?id)?session?idid?sesi[ó]n

VALUE FORMAT CO_L1_DISPOSITIVO – Regex

PATTERN	STRENGTH	NOTES
<code>([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}</code>	100%	
<code>\d{15}</code>	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, with hexadecimal digits kept hexadecimal: a MAC stays a MAC.

CO_CM_HEX **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
3c:22:fb:9a:10:e4	→ 5e:83:bb:3c:31:f9

8.19 Licence plate

CO_L1_PLACA

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

Car plates, three letters and three digits (KDZ123), and motorcycle plates, three letters, two digits and a letter (XYZ12D). The RUNT leads from the plate to the owner.

HOW IT IS FOUND

COLUMN NAME CO_L1_PLACA – Path

85% `placa(_?(veh[ií]culo|carro|moto|automotor))?` `n(o|ro|um|umero)?placa` `license_?plate`
`plate(_?(no|number))?`

VALUE FORMAT CO_L1_PLACA – Regex

PATTERN	STRENGTH	NOTES
<code>[A-Z]{3}[\s\~]?d{3}</code>		80%
<code>[A-Z]{3}[\s\~]?d{2}[A-Z]</code>		80%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters become letters and digits become digits, position by position, with the hyphen: the plate format stays.

CO_PLACA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

CO_CM_DIGITOS_LETRAS **CHARACTER MAPPING**

Maps each character to another of its group (2 groups), keeping length and format.

CO_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
KDZ123	→	RR1957
XYZ12D	→	H0U58K

8.20 Vehicle

CO_L1_VEHICULO

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The VIN or chassis number, the engine number and the vehicle registration (licencia de tránsito) number.

HOW IT IS FOUND

COLUMN NAME CO_L1_VEHICULO - Path

85% vin chasis n(o|ro|um|umero)?(chasis|motor|serie|vin) serie_?veh[ií]culo motor_?
n(o|ro|um|umero) licencia_?(de_)?tr[aá]nsito(_?(n(o|ro|um|umero)))? tarjeta_?(de_)?
propiedad runt

VALUE FORMAT CO_L1_VEHICULO - Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NPR-Z0-9]{17}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
9FBHS41A1YM123456	→	0PQRZ7700SS723598

8.21 Real estate

CO_L1_INMUEBLE

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The folio de matrícula inmobiliaria — the registry office code and a number, 50C-1234567 —, the 30-digit national cadastral number, which starts with the DIVIPOLA code, and the cadastral code. Title certificates are public and lead to the owner.

HOW IT IS FOUND

COLUMN NAME CO_L1_INMUEBLE - Path

85% folio_?(de_)?matr[ií]cula(_?inmobiliaria)? matr[ií]cula_?inmobiliaria fmi c[eé]dula_?
catastral n(o|ro|um|umero)?predial(_?nacional)? c[oó]digo_?catastral chip(_?predio)?
referencia_?catastral predio_?(n(o|ro|um|umero)|codigo|id)

VALUE FORMAT CO_L1_INMUEBLE – Regex

PATTERN	STRENGTH	NOTES
\d{2,3}[A-Z]?-\d{3,9}		60%
\d{30}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The registry office and the municipality stay; the rest is mapped digit by digit.

CO_INMUEBLE **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: **CO_CM_DIGITOS**.

CO_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
50C-1234567	→ 50C-5649285

8.22 Contract and enrolment numbers

CO_L1_CONTRATO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Contract, policy, obligation, loan, subscriber or utility account (NIC, NIU) numbers, student enrolment and customer or employee codes.

HOW IT IS FOUND

COLUMN NAME CO_L1_CONTRATO – Path

70% `n(o|ro|um|umero)?(contrato|p[ó]liza|obligaci[ó]n|cr[eé]dito|pr[eé]stamo|radicado?
(pqr|solicitud)|solicitud|afiliaci[ó]n|matr[ií]cula|carn[eé]|suscriptor|contador|medidor|clie
nte|cuenta_?contrato|factura_?servicio) contrato?(n(o|ro|um|umero)) matr[ií]cula(_?
(estudiante|alumno))? (except when followed by inmobiliaria, profesional, mercantil) c[ó]digo_
(estudiante|empleado|cliente|afiliado|suscriptor) id_
(cliente|empleado|afiliado|estudiante) n(o|ro|um|umero)?suscriptor nic niu cuenta_
contrato carne`

HOW IT IS MASKED

Character by character, keeping length and format. The mapping is deterministic, so joins keep working.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
CT-123456	→ NG-557411

8.23 User and social media

CO_L1_USUARIO

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Login, alias and social media profiles.

HOW IT IS FOUND

COLUMN NAME CO_L1_USUARIO – Path

70% usuario user_?name username login alias apodo nick(_?name)? perfil_?
(instagram|facebook|twitter|tiktok|linkedin|x) instagram facebook twitter tiktok
linkedin red_?social handle

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
@luz_rodriguez	→ @vim_seskotuuk

8.24 Credentials

CO_L1_CREDENCIAL

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Passwords and their hashes, PINs, security codes and OTPs, CVV, tokens, API keys and secret answers.

HOW IT IS FOUND

COLUMN NAME CO_L1_CREDENCIAL – Path

90% contrase[nñ]a clave *(except when followed by producto, catastral, primaria, for[aá]nea, valor, dian)* password passwd pwd pass hash_?(clave|contrasena|password) pin c[ó]digo_?
(seguridad|verificaci[ó]n|acceso|otp) cvv cvc token(_?(acceso|refresh|api))? access_?
token refresh_?token api_?key llave_?api secreto secret otp pregunta_?secreta
respuesta_?secreta

HOW IT IS MASKED

Every character becomes X. A credential has no use in a test copy, and a hash masked character by character could still be attacked.

CO_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
Clave#2024	→ XXXXXXXXXX

8.25 Geolocation

CO_L1_GEOLOCALIZACION

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns, from apps, visits, deliveries and property georeferencing.

HOW IT IS FOUND

COLUMN NAME

CO_L1_GEOLOCALIZACION - Path

85%

lat latitud lon lng longitud coordenadas? coord_{xy} geo_
(lat|lon|lng|loc|localizacion|posicion) georreferenciaci[oó]n geolocalizaci[oó]n gps(_?
(ubicaci[oó]n|posici[oó]n|coordenadas))? ubicaci[oó]n?gps

50%

long

VALUE FORMAT

CO_L1_GEOLOCALIZACION - Regex

PATTERN

STRENGTH

NOTES

-(?([0-9]|1[0-3])\.\d{3,}\s*,\s*-(6[6-9]|7\d|8[01])\.\d{3,})

90%

-(6[6-9]|7\d|8[01])\.\d{4,}

60%

-(?([0-9]|1[0-3])\.\d{4,})

30%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and the first decimal stay — about 11 km — and the other decimals are mapped: the place is generalized, not moved far away.

CO_COORDENADA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

4.609710,-74.081750

→ 4.608875,-74.088248

8.26 Free text

CO_L1_TEXTO_LIBRE

COLUMN NAME

DATA TYPE

VALUE FORMAT

FREE TEXT REDACTION

WHAT IT IS

Remarks, complaint (PQRS) descriptions, accounts of events, justifications and messages where anything gets written — cédula, mobile and name included.

HOW IT IS FOUND

COLUMN NAME CO_L1_TEXT0_LIBRE – Path

60% observaci[oó]n(es)? obs comentarios? notas? anotaci[oó]n(es)? descripci[oó]n_
(pqr|pqrs|pqrsd|queja|reclamo|solicitud|caso|hechos|novedad|atenci[oó]n) detalle_
(pqr|solicitud|caso|atenci[oó]n) hechos relato justificaci[oó]n mensaje (except when preceded by
list E6; except when followed by list E7) texto(_?libre)? resumen?(caso|atenci[oó]n) queja reclamo
pqrs?d? remarks? comments? notes? free_?text memo

DATA TYPE CO_L1_TEXT0_LIBRE – Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT CO_L1_TEXT0_LIBRE – Regex

PATTERN	STRENGTH	NOTES
\d{1,3}(\.\d{3}){2,3}	60%	anywhere in the value
[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}	70%	anywhere in the value
3\d{2}\\s?\\d{3}\\s?\\d{4}	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: cédulas with dots, NITs, numbers of 6 to 11 digits, e-mail, mobiles, cards, plates and IPs become [DATO] ; given names and surnames from the list become [NOMBRE] . The rest of the text stays.

CO_TEXT0_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with [DATO] , and the 1,188 terms of co-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE	MASKED
Cliente Rodríguez, CC 79.456.123, correo l.rodriguez@gmail.com, cel 3104567890.	→ Cliente [NOMBRE], CC [DATO], correo [DATO], cel [DATO].

Quasi-identifiers

Data that identifies no one on its own, but does in combination. DIVIPOLA has 1,102 municipalities, Bogotá and 20 non-municipalized areas; 694 of those 1,122 units have fewer than 20,000 inhabitants in the DANE projection for 2026, and a few hundred people live in the smallest. A birth date, a sex and one of those municipalities point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

9.1 Birth date

CO_L2_FECHA_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The birth date, as a date, timestamp or text.

HOW IT IS FOUND

COLUMN NAME CO_L2_FECHA_NACIMIENTO - Path

90% (fecha|fec|fch|f)?(de_?)?nac(imiento)? fnac fechanac(imiento)? cumplea[nños] dob
date_of_birth birth_date birthday

DATA TYPE CO_L2_FECHA_NACIMIENTO - Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days either way. Ages and school years change for few people; the date stays plausible and the same birth shifts the same way in every table.

CO_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

9.2 Birth year

CO_L2_ANIO_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The birth year in a column of its own.

HOW IT IS FOUND

COLUMN NAME CO_L2_ANIO_NACIMIENTO - Path

90% a[nñ]o?(de_?)?nac(imiento)? anio?nac(imiento)? year_of_birth birth_year yob

DATA TYPE CO_L2_ANIO_NACIMIENTO - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: 1985 becomes a year from 1980 to 1989.

CO_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

9.3

Age

CO_L2_EDAD

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Age in years, also age group.

HOW IT IS FOUND

COLUMN NAME

CO_L2_EDAD - Path

85%

```
edad(_?(actual|a[ñ]os|anios|paciente|afiliado|cliente|al_?
(ingreso|diagn[ó]stico|fallecimiento)))? grupo_?etario rango_?(de_?)?edad quinquenio
age(_?(years|group))?
```

DATA TYPE

CO_L2_EDAD - Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the unit is mapped (37 becomes 30 to 39). A hundred or more becomes 90: rare ages identify.

CO_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

9.4

Personal event dates

CO_L2_FECHA_EVENTO

COLUMN NAME

DATA TYPE

DATE SHIFT

WHAT IT IS

Dates that say something about the person: death, marriage, hiring and leaving, pension, hospitalization and discharge, diagnosis, childbirth, arrest, conviction, issue of the cédula, displacement, sick leave.

HOW IT IS FOUND

COLUMN NAME CO_L2_FECHA_EVENTO – Path

80% (fecha|fec|fch|f)?(de_?)?
(defunci[oó]n|fallecimiento|muerte|matrimonio|divorcio|ingreso|retiro|vinculaci[oó]n|desvinculaci[oó]n|contrataci[oó]n|terminaci[oó]n|_?
contrato|pensi[oó]n|hospitalizaci[oó]n|egreso|diagn[oó]stico|atenci[oó]n|consulta|parto|captur
a|condena|expedici[oó]n(_?(documento|c[eé]dula|cc))?)|desplazamiento|declaraci[oó]n|hecho_
victimizante|vacunaci[oó]n|cirug[ií]a|accidente|incapacidad) fec_
(exp|expedicion|defuncion|ingreso|retiro) date_?of_
(death|marriage|hire|admission|discharge)

DATA TYPE CO_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days either way. The cédula's issue date is asked as an identity check: masked, it can no longer be used to impersonate.

CO_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE

MASKED

2021-03-15

→

2021-03-05T00:00

9.5

Sex

CO_L2_SEX0

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Sex as the record holds it: F / M , Femenino / Masculino , Mujer / Hombre or the codes 1 and 2.

HOW IT IS FOUND

COLUMN NAME CO_L2_SEX0 – Path

85% sexo(_?(biol[oó]gico|al_?nacer|paciente|afiliado|cliente))?(tp|tipo|cod|cd|id)?sexo
g[eé]nero (except when followed by *identidad* , *autopercebido*) sex gender (except when followed by
identity)

KNOWN VALUES CO_L2_SEX0 – List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-sexo.txt

9

50%

f, m, h, femenino, masculino, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: F stays F or M , 1 stays 1 or 2 .

CO_SEX0 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_SEX0_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in co-sexo-femenino-masculino.txt , chosen by a keyed hash.

CO_SEX0_MUJER_HOMBRE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-sexo-mujer-hombre.txt`, chosen by a keyed hash.

CO_SEX0_FEMALE_MALE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-sexo-female-male.txt`, chosen by a keyed hash.

CO_SEX0_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-sexo-f-m.txt`, chosen by a keyed hash.

CO_SEX0_H_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-sexo-h-m.txt`, chosen by a keyed hash.

CO_SEX0_1_2 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	M
Masculino	→	Femenino

9.6 Municipality

CO_L2_MUNICIPIO

COLUMN NAME

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

The municipality of residence, birth, document issue or occurrence, by name — on its own or with the department, `La Unión – Sucre`, `La Unión (Sucre)`.

HOW IT IS FOUND

COLUMN NAME CO_L2_MUNICIPIO – Path

85% `municipio(_?`
`(residencia|nacimiento|expedici[oó]n|domicilio|paciente|cliente|ocurrencia|atenci[oó]n|notific`
`aci[oó]n))?` *(except when followed by `dane`, `cod`, `codigo`, `id`)* `mpio(_?`
`(res|nac|residencia|nacimiento))?` `ciudad(_?`
`(residencia|nacimiento|expedici[oó]n|domicilio|cliente|origen))?` `(nom|nombre|desc)_?`
`(municipio|mpio|ciudad)` `lugar_?(de_?)?(nacimiento|expedici[oó]n)` `municipio_?expedici[oó]n`
`city` `town` `localidad_?residencia`

KNOWN VALUES CO_L2_MUNICIPIO – List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>co-detectar-municipios.txt</code>	1,369	80%	Medellín, Medellin, Abejorral, Abriaquí, Abriaqui, Alejandría

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A municipality with fewer than 20,000 inhabitants becomes the nearest municipality of the same department with at least 20,000; larger ones stay. See *Where people live*.

CO_MUNICIPIO **DATA CLEANSING**

Replaces each value found in `co-municipios-generalizados.txt` (12,622 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE

MASKED

Jardín

→

Andes

La Unión – Sucre

→

San Marcos – Sucre

Medellín

→

Medellín

9.7 Municipality code (DIVIPOLA)

CO_L2_CODIGO_MUNICIPIO

COLUMN NAME

VALUE FORMAT

DATA CLEANSING

WHAT IT IS

The DANE DIVIPOLA code, five digits: two for the department and three for the municipality, 05001 for Medellín.

HOW IT IS FOUND

COLUMN NAME

CO_L2_CODIGO_MUNICIPIO – Path

85%

```
(cod|codigo|cd|id)?(municipio|mpio|ciudad|mun)(_?
(dane|res|residencia|nac|nacimiento|ocurrencia|divipola))? (cod|codigo)?dane(_?
(municipio|mpio))? divipola cod_?mpio codmpio dane_?mpio
```

VALUE FORMAT

CO_L2_CODIGO_MUNICIPIO – Regex

PATTERN

STRENGTH NOTES

```
(05|08|11|13|15|17|18|19|20|23|25|27|41|44|47|50|52|54|63|66|68|70|73|76|81|85|86|
88|91|94|95|97|99)\d{3}
```

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same generalization as the name: a small municipality's code becomes that of the municipality replacing its name. The two still agree.

CO_CODIGO_MUNICIPIO DATA CLEANSING

Replaces each value found in co-codigos-municipio-generalizados.txt (694 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE

MASKED

05364

→

05034

9.8 Postal code

CO_L2_CODIGO_POSTAL

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

The six-digit 4-72 postal code: two for the department, two for the postal zone and two for the postal district.

HOW IT IS FOUND

COLUMN NAME

CO_L2_CODIGO_POSTAL – Path

85%

```
c[oó]digo_?postal cod_?postal codpostal zip(_?code)? postal_?code cp
```

DATA TYPE CO_L2_CODIGO_POSTAL – Type

Accepts text (length 6 to 6) or number (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The two department digits stay and the others become zero: 110231 becomes 110000.

CO_CODIGO_POSTAL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
110231	→	110000

9.9 Neighbourhood, locality and commune

CO_L2_BARRIO

COLUMN NAME **SECURE LOOKUP**

WHAT IT IS

The neighbourhood, housing estate or residential complex, locality or commune of residence.

HOW IT IS FOUND

COLUMN NAME CO_L2_BARRIO – Path

80% `barrio(_?(residencia|domicilio|cliente))? (nom|nombre)?barrio` `urbanizaci[oó]n` `conjunto_?`
`residencial` `localidad` *(except when followed by* `c[oó]digo` *,* `cod`*)* `comuna` `upz` `neighbou?rhood`

HOW IT IS MASKED

Replaced with a neighbourhood name common in Colombia — Centro, La Esperanza, San José —, unrelated to the original.

CO_BARRIO **SECURE LOOKUP**

Replaces the value with one of the 35 values in `co-barrios.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Chapinero Alto	→	Santa Mónica

9.10 Vereda and corregimiento

CO_L2_VEREDA

COLUMN NAME **SECURE LOOKUP**

WHAT IT IS

The vereda, corregimiento, populated centre, indigenous reserve or farm of a rural address: communities of a few dozen families.

HOW IT IS FOUND

COLUMN NAME CO_L2_VEREDA – Path

85% `vereda(_?(residencia|nombre))?` `corregimiento` `centro_?poblado` `inspecci[oó]n_?(de_)?`
`polic[ií]a` `resguardo(_?ind[ií]gena)?` `caser[ií]o` `finca` `parcela`

HOW IT IS MASKED

Replaced with `Zona rural`.

CO_ZONA_RURAL SECURE LOOKUP

Replaces the value with one of the 1 values in `co-zona-rural.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Vereda La Esperanza

MASKED

→ Zona rural

9.11 Nationality

CO_L2_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. Venezuelans are by far the largest foreign community.

HOW IT IS FOUND

COLUMN NAME

CO_L2_NACIONALIDAD - Path

80%

nacionalidad pa[ií]s_?(de_?)(nacimient|origen|nacionalidad) ciudadan[ií]la nationality
citizenship country_of_birth

KNOWN VALUES

CO_L2_NACIONALIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

VALUES	STRENGTH	FIRST VALUES
co-detectar-nacionalidades.txt	52	70% Colombiana, Venezolana, Ecuatoriana, Peruana, Estadounidense, Española

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a nationality from the list: Colombian and the largest foreign communities.

CO_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 16 values in `co-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Haitiana

MASKED

→ Mexicana

9.12 Marital status

CO_L2_ESTADO_CIVIL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Single, married, de facto marital union, separated, divorced or widowed, in words or as a code.

HOW IT IS FOUND

COLUMN NAME

CO_L2_ESTADO_CIVIL - Path

85%

estado_civil est_civil (cod|tipo|id)_estado_civil situaci[ó]n_conyugal marital_
status civil_status

KNOWN VALUES CO_L2_ESTADO_CIVIL – List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-estado-civil.txt	21	70%	Soltero(a), Casado(a), Unión marital de hecho, Union marital de hecho, Separado(a), Divorciado(a)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another status from the list; a code stays a code.

CO_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ESTADO_CIVIL_LISTA .**CO_BANDERA REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in co-estado-civil-codigos.txt , chosen by a keyed hash.

CO_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in co-estado-civil.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Unión libre	→ Divorciado(a)

9.13 Occupation

CO_L2_OCUPACION

COLUMN NAME **REGEX DECOMPOSE****WHAT IT IS**

Occupation, profession or trade, in words or by the CIUO-08 code adapted for Colombia. A rare occupation in a small municipality identifies.

HOW IT IS FOUND**COLUMN NAME** CO_L2_OCUPACION – Path

80%	ocupaci[oó]n profesi[oó]n oficio ciuo (cod codigo)?(ocupacion ciuo profesion) actividad?econ[oó]mica?(persona afiliado) cargo?(actual empleado trabajador) occupation profession job?title
50%	cargo

HOW IT IS MASKED

A text is replaced with a common occupation; a code is mapped digit by digit.

CO_OCUPACION_0_CIU0 **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **CO_OCUPACION**.

CO_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

CO_OCUPACION **SECURE LOOKUP**

Replaces the value with one of the 39 values in **co-ocupaciones.txt**, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Gerente de operaciones regionales

→

Modista

9.14 Employer

CO_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The name of the company or body the person works for.

HOW IT IS FOUND

COLUMN NAME

CO_L2_EMPLEADOR – Path

80%

empleador(_?(nombre|raz[oó]n?social))? (nombre|nom)?(empleador|empresa?donde?
trabaja|empresa?labora) empresa?(donde?)?(trabaja|labora) lugar?(de_)?trabajo
empresa?empleadora patrono employer(_?name)? workplace

HOW IT IS MASKED

Replaced with a fictitious company.

CO_EMPLEADOR **SECURE LOOKUP**

Replaces the value with one of the 24 values in **co-empleadores.txt**, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Ecopetrol S.A.

→

Droguería El Buen Vecino

9.15 Education

CO_L2_ESCOLARIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The highest education level — from none to doctorate —, in words or as a code.

HOW IT IS FOUND

COLUMN NAME

CO_L2_ESCOLARIDAD – Path

80%

escolaridad nivel?(educativo|de?estudios|acad[eé]mico|escolaridad|formaci[oó]n) grado?
(de_)?(instrucci[oó]n|escolaridad) máximo?nivel formaci[oó]n?acad[eé]mica
education(_?level)?

KNOWN VALUES CO_L2_ESCOLARIDAD – List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-escolaridad.txt	33	60%	Ninguno, Preescolar, Básica primaria, Basica primaria, Básica secundaria, Basica secundaria

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another level from the list; a code stays a code.

CO_ESCOLARIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ESCOLARIDAD_LISTA .**CO_BANDERA REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

CO_ESCOLARIDAD_CODIGO SECURE LOOKUP

Replaces the value with one of the 11 values in `co-escolaridad-codigos.txt`, chosen by a keyed hash.

CO_ESCOLARIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `co-escolaridad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Posdoctorado	→ Preescolar

9.16 Educational institution

CO_L2_INSTITUCION_EDUCATIVA

COLUMN NAME **SECURE LOOKUP****WHAT IT IS**

The school, educational institution or university, by name or by the DANE code of the establishment.

HOW IT IS FOUND**COLUMN NAME** CO_L2_INSTITUCION_EDUCATIVA – Path

75% `colegio(_?(nombre|egreso))? (nombre|nom)?(colegio|instituci[oó]n? educativa|universidad|establecimiento?educativo) instituci[oó]n?educativa establecimiento?educativo universidad (cod|codigo)?dane?(colegio|establecimiento|sede) school(_?name)? university`

HOW IT IS MASKED

Replaced with a fictitious institution.

CO_INSTITUCION_EDUCATIVA **SECURE LOOKUP**

Replaces the value with one of the 12 values in `co-instituciones-educativas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Colegio Mayor de San Bartolomé	→	Corporación Universitaria del Valle

9.17

Dependants and children

CO_L2_PERSONAS_A_CARGO

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Number of dependants, children or household members.

HOW IT IS FOUND

COLUMN NAME CO_L2_PERSONAS_A_CARGO – Path

80% `personas_?a_?cargo   n(o|ro|um|umero)_?(de_)?(hijos|dependientes|personas_?a_?cargo) cant(idad)?_?(hijos|dependientes|personas_?hogar)   hijos   dependientes   personas_?(en_? e\_)?hogar   tama[nñ]o_?hogar   number_?of_?children   dependents`

DATA TYPE CO_L2_PERSONAS_A_CARGO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values from 0 to 5 stay; above 5 they become 5. Very large families are rare, and a rare count identifies.

CO_CONTEO_LIMITADO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

Sensitive data

The categories of article 5 that are not health data — which has a group of its own: racial or ethnic origin, political orientation, religious or philosophical convictions, membership of trade unions, of social and human rights organizations and of parties, sexual life and biometric data. The list is illustrative (*such as*): the set includes genetic data, sexual orientation and gender identity, and two categories that in Colombia expose people to discrimination and violence — being a **victim of the armed conflict**, whose information is confidential (Law 1448 of 2011, arts. 29 and 156), and being a **person in the reincorporation process**.

Categorical columns keep their shape: an S/N flag stays a flag, a code is replaced by another code of the same catalog and any other value by one from the list of its category. Where the values share no vocabulary, they are suppressed to Sin información .

10.1 Ethnic self-recognition

CO_L3_GRUPO_ETNICO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The ethnic group a person recognizes themselves in, in the categories of the 2018 census: indigenous (1,905,617 people, 4.4%), Gypsy or Rrom, Raizal of the San Andrés, Providencia and Santa Catalina Archipelago, Palenquero of San Basilio, Black, mulatto, Afro-descendant or Afro-Colombian, or none; in words, as a code or as a flag.

HOW IT IS FOUND

COLUMN NAME CO_L3_GRUPO_ETNICO – Path

95% etnia grupo_?[eé]tnico pertenencia_?[eé]tnica autorreconocimiento(_?[eé]tnico)? auto_?reconocimiento (cod|codigo|tipo|id)?(etnia|pertenencia_?etnica) raza origen_?[eé]tnico afrocolombiano afrodescendiente raizal palenquero rrom gitano ethnicity race

KNOWN VALUES CO_L3_GRUPO_ETNICO – List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-grupos-etnicos.txt	24	90%	Indígena, Indígena, Gitano(a) o Rrom, Raizal del Archipiélago de San Andrés, Providencia y Santa Catalina, Raizal del Archipiélago de San Andres, Providencia y Santa Catalina, Palenquero(a) de San Basilio
co-detectar-codigos-banderas.txt	11	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag, a code is replaced by another code of the catalog and any other value by a census category.

CO_GRUPO_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_GRUPO_ETNICO_LISTA .

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

CO_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.

CO_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

CO_GRUPO_ETNICO_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 6 values in `co-grupos-etnicos-codigos.txt` , chosen by a keyed hash.

CO_GRUPO_ETNICO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 6 values in `co-grupos-etnicos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afrocolombiana	→	Raizal del Archipiélago de San Andrés, Providencia y Santa Catalina
5	→	3

10.2 Indigenous people and ethnic community

CO_L3_PUEBLO_INDIGENA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The indigenous people — the 2018 census identified 115; the Wayuu (380,460), Zenú (307,091), Nasa (243,176) and Pastos (163,873) make up 58.1% of the indigenous population —, the reserve or council, the Afro-descendant community council and the Rrom kumpania.

HOW IT IS FOUND

COLUMN NAME CO_L3_PUEBLO_INDIGENA - Path

90% `pueblo(?:ind[ií]gena)? (cod|codigo|nombre|nom)?pueblo resguardo(?:ind[ií]gena cabildo(?:ind[ií]gena)? comunidad?(ind[ií]gena|negra|afro) consejo?comunitario parcialidad kumpania indigenous?people`

KNOWN VALUES CO_L3_PUEBLO_INDIGENA - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-pueblos-indigenas.txt	137	90%	Achagua, Amorúa, Amorua, Andoke, Arhuaco, Awá

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A people code is replaced with another code; a name with one of the most numerous peoples.

CO_PUEBLO_INDIGENA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_PUEBLO_INDIGENA_LISTA .

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

CO_PUEBLO_INDIGENA_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `co-pueblos-indigenas-codigos.txt`, chosen by a keyed hash.

CO_PUEBLO_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 20 values in `co-pueblos-indigenas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Kuna

→

Muisca

10.3 Native language

CO_L3 LENGUA NATIVA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The language a person speaks: Colombia has 65 indigenous languages, besides the San Andrés creole, the Palenquero language and Romani. Speaking Wayuunaiki or Nasa Yuwe reveals the people of origin.

HOW IT IS FOUND

COLUMN NAME

CO_L3 LENGUA NATIVA - Path

90%

`lengua_?(nativa|materna|ind[ií]gena|propia)` `idioma_?(nativo|materno|ind[ií]gena)` `habla_?`
`lengua` `lengua` (except when followed by `extranjera`, `codigo`, `cod`) `mother_?tongue` `native_?language`

KNOWN VALUES

CO_L3 LENGUA NATIVA - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-lenguas.txt

39

80%

Español, Espanol, Wayuunaiki, Nasa Yuwe, Emberá, Embera

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a language from the list; a flag stays a flag.

CO LENGUA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO LENGUA LISTA`.

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.

CO_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CO LENGUA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 12 values in `co-lenguas.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Tikuna

→ Ninguna lengua nativa

10.4

Religion

CO_L3_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The religion, church or congregation a person belongs to.

HOW IT IS FOUND

COLUMN NAME

CO_L3_RELIGION - Path

95%

religi[oó]n creencia_?religiosa convicci[oó]n_?religiosa credo confesi[oó]n_?religiosa
culto iglesia(_?(a_?la_?que_?pertenece|nombre))? denominaci[oó]n_?religiosa
(cod|codigo|tipo)_?religion religion church

KNOWN VALUES

CO_L3_RELIGION - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-
religiones.txt

41

90%

Católica, Catolica, Cristiana evangélica, Cristiana evangelica, Pentecostal,
Adventista del Séptimo Día

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a religion from the list.

CO_RELIGION **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_RELIGION_LISTA .

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

CO_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

CO_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CO_RELIGION_LISTA **SECURE LOOKUP**

Replaces the value with one of the 12 values in `co-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Anglicana

→

Musulmana

10.5 Philosophical convictions

CO_L3_CONVICCION_FILOSOFICA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Philosophical and moral convictions, conscientious objection — invoked in Colombia, for instance, against military service — and membership of lodges.

HOW IT IS FOUND

COLUMN NAME

CO_L3_CONVICCION_FILOSOFICA - Path

90%

convicci[oó]n(es)?_?(filos[oó]fica|moral|personal) creencias?_?(filos[oó]ficas?
|personales) objeci[oó]n_(de_)?conciencia objetor_(de_)?conciencia masoner[ií]a
logia beliefs? philosophical_beliefs?

HOW IT IS MASKED

The values share no vocabulary: they are suppressed to `Sin información`. Flags and codes keep their shape.

CO_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

CO_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

CO_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

CO_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Se niega a transfusiones

→ Sin información

10.6 Political orientation

CO_L3_ORIENTACION_POLITICA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Political leaning, ideology, sympathy and voting intention, from surveys and registers.

HOW IT IS FOUND

COLUMN NAME

CO_L3_ORIENTACION_POLITICA - Path

90%

orientaci[oó]n_?pol[ií]tica opini[oó]n_?pol[ií]tica tendencia_?pol[ií]tica
ideolog[ií]a(_?pol[ií]tica)? preferencia_?(pol[ií]tica|partidista|electoral)
intenci[oó]n_?(de_)?voto simpat[ií]a_?pol[ií]tica political_?(opinion|orientation|view)
voting_?intention

KNOWN VALUES

CO_L3_ORIENTACION_POLITICA - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-orientaciones-politicas.txt	19	70%	Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente
---	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a position from the list — left to right, independent.

CO_ORIENTACION_POLITICA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ORIENTACION_POLITICA_LISTA .

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_ORIENTACION_POLITICA_LISTA

SECURE LOOKUP

Replaces the value with one of the 7 values in co-orientaciones-politicas.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Uribista

→ **Centroderecha**

10.7 Party membership

CO_L3_AFILIACION_PARTIDO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The party or political movement a person is a member of, and belonging to the opposition. The National Electoral Council certified 28 political organizations with legal personality in September 2026.

HOW IT IS FOUND

COLUMN NAME

CO_L3_AFILIACION_PARTIDO - Path

95%

partido(_?pol[í]tico)?(_?(afiliaci[oó]n|nombre|militerancia))? movimiento_?pol[í]tico
afiliaci[oó]n_?(pol[í]tica|partidista|partido) militancia(_?pol[í]tica)? militante
(cod|codigo|nombre|nom)_?partido colectividad bancada oposici[oó]n political_?party
party_?membership

KNOWN VALUES

CO_L3_AFILIACION_PARTIDO - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-
detectar-
partidos.tx
t

68

80%

Partido Liberal Colombiano, Partido Conservador Colombiano, Partido Cambio Radical,
Partido Alianza Verde, Movimiento Autoridades Indígenas de Colombia (AICO),
Movimiento Autoridades Indigenas de Colombia (AICO)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another organization from the list of those with legal personality; a flag stays a flag.

CO_PARTIDO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_PARTIDO_LISTA .

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_PARTIDO_LISTA

SECURE LOOKUP

Replaces the value with one of the 29 values in `co-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Polo Democrático Alternativo

→

Partido Colombia Renaciente

10.8 Trade union membership

CO_L3_SINDICATO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The union, being unionized, the union fee deducted from payroll, union immunity and the confederation — CUT, CGT, CTC.

HOW IT IS FOUND

COLUMN NAME

CO_L3_SINDICATO – Path

95%

```
sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))? sindicalizado afiliado_?sindicato
afiliaci[oó]n_?sindical cuota_?sindical descuento_?sindical aporte_?sindical
asociaci[oó]n_?sindical fuero_?sindical directivo_?sindical central_?obrero
convenci[oó]n_?colectiva pacto_?colectivo trade_?union union_?member(ship)?
```

KNOWN VALUES

CO_L3_SINDICATO – List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-sindicatos.txt

23

60%

CUT, CGT, CTC, FECODE, USO, SINTRAINAL

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

CO_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR`.

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in `co-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

SINTRAINAL

→

Sin información

S

→

S

10.9 Social and human rights organizations

CO_L3_ORGANIZACION_SOCIAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Membership of social, community and human rights organizations, the community action board, and being a social leader or human rights defender — in Colombia, among the conditions most exposed to violence.

HOW IT IS FOUND

COLUMN NAME

CO_L3_ORGANIZACION_SOCIAL - Path

90%

```
organizaci[oó]n?(social|comunitaria|de_?base|de_?derechos_?humanos|defensora)
l[ií]der(esa)??(social|comunal|comunitario) liderazgo_?social defensor(a)??(de_)?
derechos_?humanos ddhh junta_(de_)?acci[oó]n_?comunal jac movimiento_?social
asociaci[oó]n?(de_)?(v[ií]ctimas|campesinos|mujeres) colectivo_?social ong_?
(afiliado|miembro) human_?rights_?defender
```

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

CO_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_SUPRIMIR .

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in co-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Junta de Acción Comunal vereda El Salitre

→

Sin información

10.10 Biometric data

CO_L3_BIOMETRICO

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Fingerprint templates — biometric validation against the Registry is common in banks and notaries —, face, iris, voice and digitized signature.

HOW IT IS FOUND

COLUMN NAME CO_L3_BIOMETRICO – Path

90% biometr[ií]a[a-z]* biom[eé]trico[a-z]* huella(?:dactilar)?(?:
(template|plantilla|imagen|hash))? huellas dactilar template?(facial|huella|biometrico)
plantilla?(facial|biom[eé]trica) rostro?(hash|template) reconocimiento?facial firma?
(biom[eé]trica|digitalizada|manuscrita) iris voz?(biom[eé]trica|template) fingerprints?
face?(template|hash|encoding) biometric[a-z]*

DATA TYPE CO_L3_BIOMETRICO – Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes X . A masked template authenticates no one.

CO_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

A1B2C3D4E5F6

→ XXXXXXXXXXXX

10.11 Genetic data

CO_L3_GENETICO

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Genetic and DNA test results, paternity tests, genetic profiles, mutations, karyotype, newborn screening. Not on the list of article 5, but they reveal health and origin.

HOW IT IS FOUND

COLUMN NAME CO_L3_GENETICO – Path

90% adn dna gen[eé]tic[oa]s? datos?_?gen[eé]ticos? genoma genotip[a-z]* prueba?
(gen[eé]tica|de?adn|de?paternidad) perfil?gen[eé]tico mutaci[oó]n brca[12]?
cariotipo tamizaje?neonatal genetic[a-z]*

HOW IT IS MASKED

Every character becomes X .

CO_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

BRCA1 positivo

→ XXXXXXXXXXXXX

10.12 Sexual orientation

CO_L3_ORIENTACION_SEXUAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Self-declared sexual orientation, in health and diversity registers. It is data concerning sexual life.

HOW IT IS FOUND

COLUMN NAME

CO_L3_ORIENTACION_SEXUAL - Path

95%

orientaci[oó]n?sexual orient?sexual (cod|codigo|tipo)?orientacion?sexual
preferencia?sexual sexual?orientation

KNOWN VALUES

CO_L3_ORIENTACION_SEXUAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-orientaciones-
sexuales.txt

13

80%

Heterosexual, Gay, Lesbiana, Bisexual, Pansexual,
Asexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a category from the list.

CO_ORIENTACION_SEXUAL

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ORIENTACION_SEXUAL_LISTA .

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_ORIENTACION_SEXUAL_LISTA

SECURE LOOKUP

Replaces the value with one of the 8 values in co-orientaciones-sexuales.txt , chosen by a keyed hash.

EXAMPLES

VALUE

Homosexual

MASKED

→ **Pansexual**

10.13 Sexual life

CO_L3_VIDA_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Sexual activity and behaviour, number of partners, sexual debut.

HOW IT IS FOUND

COLUMN NAME

CO_L3_VIDA_SEXUAL - Path

90%

vida_?sexual actividad_?sexual conducta_?sexual pr[aá]cticas?_?sexuales? parejas?_? sexuales? n(o|ro|um|umero)_?parejas sexualmente_?activ[oa] inicio_?(de_?)(la_?)?vida_? sexual relaciones_?sexuales sex(ual)?_?life sexual?(activity|behavio(u)?r|partners)

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

CO_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_SUPRIMIR .

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in co-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

Activa

MASKED

→ **Sin información**

10.14 Gender identity

CO_L3_IDENTIDAD_GENERO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Self-declared gender identity. Not on the list of article 5, but it exposes people to the same discrimination. The identity name falls under the full-name domain.

HOW IT IS FOUND

COLUMN NAME

CO_L3_IDENTIDAD_GENERO - Path

95%

identidad?(de_)?g[eé]nero (cod|codigo|tipo)?identidad?genero g[eé]nero?(autopercebido|identitario) transg[eé]nero persona?trans nombre?identitario pronombres? gender?identity

KNOWN VALUES

CO_L3_IDENTIDAD_GENERO - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-identidades-genero.txt	21	70%	Mujer cisgénero, Mujer cisgenero, Hombre cisgénero, Hombre cisgenero, Mujer trans, Hombre trans

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with a category from the list.

CO_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_IDENTIDAD_GENERO_LISTA .

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in co-identidades-genero.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Transgénero	→ Hombre trans

10.15 Victim of the armed conflict

CO_L3_VICTIMA_CONFLICTO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Being a victim and the victimizing event of the Single Victims Registry — forced displacement, homicide, threat, enforced disappearance, kidnapping, crimes against sexual freedom, landmines, recruitment —, often as a flag. The information a victim provides is confidential (Law 1448 of 2011, arts. 29 and 156).

HOW IT IS FOUND

COLUMN NAME

CO_L3_VICTIMA_CONFLICTO - Path

95%

```
v[íi]ctima(_?(del_)?(conflicto(_?armado)?|ruv))? hecho_?victimizante (cod|codigo|tipo)?  
hecho(_?victimizante)? ruv registro_?[uú]nico?(de_)?v[íi]ctimas desplazad[oa](?  
(forzad[oa]))? condici[oó]n?(de_)?(v[íi]ctima|desplazado) poblaci[oó]n?desplazada  
estado?ruv sujeto?(de_)?reparaci[oó]n victim?of?conflict
```

KNOWN VALUES

CO_L3_VICTIMA_CONFLICTO - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-hechos-
victimizantes.txt

30

80%

Desplazamiento forzado, Homicidio, Amenaza, Desaparición forzada,
Desaparicion forzada, Pérdida de bienes muebles o inmuebles

co-detectar-codigos-
banderas.txt

11

30%

s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a victimizing event from the list.

CO_VICTIMA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_VICTIMA_LISTA .

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_VICTIMA_LISTA SECURE LOOKUP

Replaces the value with one of the 15 values in co-hechos-victimizantes.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Masacre	→	Confinamiento
S	→	S

10.16 Reincorporation

CO_L3_REINCORPORACION

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Being in the reincorporation or reintegration process of the Agency for Reincorporation and Normalization (ARN): ex-combatants and peace signatories.

HOW IT IS FOUND

COLUMN NAME

CO_L3_REINCORPORACION - Path

95%

```
reincorporad[oa] reincorporaci[oó]n reintegrad[oa] reintegraci[oó]n desmovilizad[oa]
desmovilizaci[oó]n excombatiente ex_?combatiente firmante_?(de_)?paz arn
poblaci[oó]n?(en_?proceso_?de_)?(reincorporaci[oó]n|reintegraci[oó]n) ex_?farc ex_?
guerriller[oa]
```

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

CO_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_SUPRIMIR .

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in co-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Excombatiente FARC-EP	→	Sin información
-----------------------	---	-----------------

Health data

Data concerning health is sensitive (art. 5), and the medical record is also a confidential document that can only be accessed with the patient's authorization or in the cases the law provides. The group covers what hospitals and clinics (IPS), health insurers (EPS), laboratories, occupational risk insurers (ARL) and occupational health teams keep: identifiers, affiliation, diagnoses, procedures, medicines, tests, blood group, disability, occupational, reproductive and mental health.

11.1 Health identifiers

CO_SALUD_IDENTIFICADOR

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Medical record, admission, visit, service authorization, prescription, sick-leave and MIPRES numbers. The medical record is identified by the patient's document number, which falls under the cédula domain.

HOW IT IS FOUND

COLUMN NAME

CO_SALUD_IDENTIFICADOR - Path

85% n(o|ro|um|umero)?(historia?(cl[ií]nica)?|hc|ingreso|atenci[oó]n|autorizaci[oó]n|orden_?
m[eé]dica|f[oó]rmula|incapacidad|carn[eé]?(eps|salud)|afiliaci[oó]n?
eps|mipres|prescripci[oó]n) historia?cl[ií]nica hc?(n(o|ro|um|umero))? autorizaci[oó]n?
(servicio|eps) mipres c[oó]digo?(paciente|afiliado) id?paciente n(o|ro)?rips

55% atenci[oó]n ingreso autorizaci[oó]n episodio

HOW IT IS MASKED

Character by character, keeping length and format.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

HC-2024-00123

→

TW-3389-01317

11.2 Health system affiliation

CO_SALUD_AFILIACION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The regime – contributory, subsidized, special or exception – and the health insurer (EPS). Being in the subsidized regime says the person cannot pay contributions.

HOW IT IS FOUND

COLUMN NAME

CO_SALUD_AFILIACION - Path

85% r[eé]gimen?(de?)?(salud|afiliaci[oó]n)? tipo?(de?)?(regimen|afiliado|afiliaci[oó]n)
eps?(afiliado|actual|nombre|codigo)? (cod|codigo|nombre|nom)?eps entidad?promotora(?
(de?)?salud)? aseguradora?salud administradora?(de?)?salud eapb prepagada
medicina?prepagada plan?complementario

KNOWN VALUES CO_SALUD_AFILIACION – List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-afiliacion-salud.txt	41	80%	Contributivo, Subsidiado, Especial, De excepción, De excepcion, No afiliado

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A regime is replaced with another regime and an EPS with another EPS from the list; a flag stays a flag.

CO_AFILIACION_SALUD REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_EPS .

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_REGIMEN_SALUD SECURE LOOKUP

Replaces the value with one of the 5 values in co-regimenes-salud.txt , chosen by a keyed hash.

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CO_EPS SECURE LOOKUP

Replaces the value with one of the 18 values in co-eps.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Subsidiado	→	Contributivo
Medimás EPS	→	Famisanar EPS

11.3 Diagnosis and ICD-10

CO_SALUD_DIAGNOSTICO

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE****WHAT IT IS**

Diagnoses in words or by ICD-10 code, with the dot (F33.1) or without it, as in the RIPS (F331 , I10X); causes of death, sick leave and hospitalization, history and allergies.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_DIAGNOSTICO - Path

85% `diagn[oó]stico[a-z]*   dx(?:principal|relacionado|ingreso|egreso)[0-9]?   cie_?10   cie(?:`
`(10|11|principal))   (cod|codigo)_?(diagnostico|dx|cie)   impresi[oó]n_?diagn[oó]stica`
`enfermedad(es)?[a-z]*   patolog[ií]a   comorbilidad(es)?   antecedentes?_?`
`(m[eé]dicos|patol[oó]gicos|familiares|personales)   causa_?(de_)?`
`(muerte|defunci[oó]n|incapacidad|hospitalizaci[oó]n|consulta)   motivo_?(de_)?`
`(consulta|incapacidad|hospitalizaci[oó]n)   alergias?   diagnos(is|es)   icd_?(10|11)?`

VALUE FORMAT CO_SALUD_DIAGNOSTICO - Regex

PATTERN	STRENGTH	NOTES
[A-TV-Za-tv-z]\d{2}(\.\d{1,2} \d X)?		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another common code in the same format, and a text a common diagnosis: an HIV or mental disorder diagnosis does not survive as a category.

CO_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CO_DIAGNOSTICO_TEXT0 .

CO_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `co-cie10-decimal.txt` , chosen by a keyed hash.

CO_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `co-cie10.txt` , chosen by a keyed hash.

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

CO_DIAGNOSTICO_TEXT0 SECURE LOOKUP

Replaces the value with one of the 30 values in `co-diagnostics.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	K21.9
B24X	→	R51

11.4 Procedures (CUPS)

CO_SALUD_PROCEDIMIENTO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Procedures, tests and surgeries, in words or by the code of the Single Classification of Health Procedures. A viral load or a voluntary termination of pregnancy reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_PROCEDIMIENTO - Path

85% cups (cod|codigo)?(cups|procedimiento|servicio_salud) procedimiento(?(m[eé]dico|quir[uú]rgico|realizado|autorizado))? servicio?(de_)?salud?(prestado|autorizado) examen?(ordenado|realizado) cirug[ií]a(_?realizada)? intervenci[oó]n?quir[uú]rgica medical_procedure

HOW IT IS MASKED

A CUPS code is replaced with another common code; a text with a common procedure.

CO_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

CO_PROCEDIMIENTO_TEXTO .

CO_CUPS SECURE LOOKUP

Replaces the value with one of the 10 values in co-cups.txt , chosen by a keyed hash.

CO_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in co-procedimientos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
906249	→ 903815

11.5 Medicines

CO_SALUD_MEDICAMENTO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Medicines prescribed, dispensed or taken continuously, by name or by CUM code. An antiretroviral, an antipsychotic or a contraceptive reveals a diagnosis.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_MEDICAMENTO - Path

85% medicamentos?(?(formulado|prescrito|entregado|dispensado|nombre|uso))? f[aá]rmacos? principio_active cum (cod|codigo)?(cum|medicamento) f[oó]rmula_m[eé]dica prescripci[oó]n?(medicamento)? posolog[ií]a tratamiento_farmacol[oó]gico medications? drugs?_prescribed

KNOWN VALUES CO_SALUD_MEDICAMENTO - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar- medicamentos.txt	53	70%	Acetaminofén, Acetaminofen, Ibuprofeno, Naproxeno, Diclofenaco, Metformina

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced with a common medicine from the list; a flag stays a flag.

CO_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_MEDICAMENTO_LISTA .

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 24 values in co-medicamentos.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Sertralina 50 mg

→ Ibuprofeno

11.6 Clinical text

CO_SALUD_TEXT0_CLINICO

COLUMN NAME

DATA TYPE

FREE TEXT REDACTION

WHAT IT IS

Medical history, current illness, progress notes, physical examination, management plan, discharge summary and nursing notes.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_TEXT0_CLINICO - Path

85%

anamnesis evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))? enfermedad_?actual
examen_?f[ií]sico an[aá]lisis_?(y_)?plan plan_?(de_)?manejo conducta(_?m[eé]dica)?
epicrisis resumen_?(de_)?(egreso|atenci[oó]n) nota_?(m[eé]dica|de_?
enfermer[ií]a|cl[ií]nica) notas?_?(m[eé]dicas|cl[ií]nicas) triage(_?texto)? motivo_?
consulta_?texto interpretaci[oó]n_?(resultado|examen) informe_?
(patolog[ií]a|radiolog[ií]a) clinical_?notes? discharge_?summary

DATA TYPE CO_SALUD_TEXT0_CLINICO - Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same Free Text Redaction as free text: documents, contacts and names from the list are redacted. The clinical content stays — if it must not be in the copy, suppress the column.

CO_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with [DAT0], and the 1,188 terms of co-texto-nombres.txt with [NOMBRE].

EXAMPLES

VALUE

Paciente Rodríguez, CC 79.456.123, consulta por cefalea.

MASKED

→ Paciente [NOMBRE], CC [DAT0], consulta por cefalea.

11.7 Test results

CO_SALUD_RESULTADO_EXAMEN

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Laboratory and test results — HIV, viral load, blood glucose, pregnancy, drug test, blood alcohol —, also as numeric values.

HOW IT IS FOUND

COLUMN NAME

CO_SALUD_RESULTADO_EXAMEN - Path

80%

resultado?(del_)?

(examen|prueba|laboratorio|vih|covid|pcr|serolog[ií]a|biopsia|glicemia|citolog[ií]a|patolog[ií]a) (examen|prueba)?(resultado|laboratorio) vih(_?(estado|resultado|prueba))? carga_? viral cd4 glicemia glucosa hemoglobina?glicosilada hba1c colesterol imc presi[oó]n?arterial tensi[oó]n?arterial prueba?(de_)?embarazo toxicol[oó]gico alcoholemia lab_?results? test_?results?

50%

resultado prueba

HOW IT IS MASKED

Character by character, keeping the format: a number stays a number.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

Reactivo

MASKED

→ Quilqaju

11.8 Blood group and Rh

CO_SALUD_GRUPO_SANGUINEO

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor — printed on the cédula and asked by almost every employer.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_GRUPO_SANGUINEO - Path

90% grupo_?sangu[ií]neo tipo_?(de_)?sangre rh factor_?rh gs_?rh grupo_?rh
hemoclasificaci[ó]n abo(_?rh)? blood_?(type|group)

KNOWN VALUES CO_SALUD_GRUPO_SANGUINEO - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-grupos-sanguineos.txt	18	90%	A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced with another group from the list.

CO_GRUPO_SANGUINEO **SECURE LOOKUP**

Replaces the value with one of the 8 values in co-grupos-sanguineos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
O+	→ A-

11.9 Disability

CO_SALUD_DISCAPACIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Disability and its category in the Ministry of Health certification — physical, hearing, visual, deafblindness, intellectual, psychosocial, multiple — and the Registry for the Location and Characterization of Persons with Disabilities.

HOW IT IS FOUND

COLUMN NAME CO_SALUD_DISCAPACIDAD - Path

90% discapacidad[a-z]* (tipo|cod|codigo|categoria)?discapacidad persona_?con_?discapacidad
pcd condici[ó]n_?(de_)?discapacidad certificado_?(de_)?discapacidad rlcpd
necesidades_?(educativas_)?especiales movilidad_?reducida disabilit(y|ies)

KNOWN VALUES CO_SALUD_DISCAPACIDAD - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-discapacidades.txt	29	60%	Física, Física, Auditiva, Visual, Sordoceguera, Intelectual

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a category from the list.

CO_DISCAPACIDAD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_DISCAPACIDAD_LISTA .

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-discapacidades.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno del espectro autista

→ Ninguna

11.10 Occupational health

CO_SALUD_OCUPACIONAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The fitness result of occupational medical exams, work accident (FURAT) and occupational disease (FUREL) reports, sick leaves, the assessment of loss of working capacity and medical restrictions.

HOW IT IS FOUND

COLUMN NAME

CO_SALUD_OCUPACIONAL - Path

85%

```
concepto_(de_)?aptitud  aptitud_(laboral|m[eé]dica)  examen_(m[eé]dico_)?
(ocupacional|de_ingreso|de_retiro|peri[oó]dico)  resultado_examen_ocupacional
accidente_(de_)?trabajo  at_(tipo|reporte)  furat  enfermedad_laboral  furel
incapacidad_(?(m[eé]dica|laboral|tipo|motivo|d[ií]as))?  d[ií]as_(de_)?incapacidad
licencia_(de_)?(maternidad|paternidad)  calificaci[oó]n_(de_)?(p[eé]rdida|origen)
p[eé]rdida_(de_)?capacidad_laboral  pcl  restricciones_m[eé]dicas  recomendaciones_
m[eé]dicas  reintegro_laboral
```

KNOWN VALUES

CO_SALUD_OCUPACIONAL - List

LIST

VALUES STRENGTH FIRST VALUES

VALUES	STRENGTH	FIRST VALUES
co-detectar-aptitud-laboral.txt	5	60%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A result is replaced with another from the list — fit, unfit —; a flag stays a flag; the diagnosis of the sick leave falls under its domain.

CO_SALUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_SALUD_LABORAL_LISTA .

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in **co-bandera-si-no.txt** , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in **co-bandera-true-false.txt** , chosen by a keyed hash.

CO_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in **co-bandera-yes-no.txt** , chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in **co-bandera-s-n.txt** , chosen by a keyed hash.

CO_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in **co-bandera-y-n.txt** , chosen by a keyed hash.

CO_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in **co-bandera-0-1.txt** , chosen by a keyed hash.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CO_SALUD_LABORAL_LISTA **SECURE LOOKUP**

Replaces the value with one of the 4 values in **co-aptitud-laboral.txt** , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

No apto temporalmente

→ **Aplazado**

11.11 Sexual and reproductive health

CO_SALUD_REPRODUCTIVA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Pregnancy, last menstrual period, prenatal care, childbirth, voluntary termination of pregnancy, family planning, fertility, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME

CO_SALUD_REPRODUCTIVA - Path

90%

gestante embarazo embarazada gestaci[ó]n edad_?gestacional semanas_?(de_)?
gestaci[ó]n fum fecha_?[ú]ltima_?menstruaci[ó]n control_?prenatal prenatal parto(_?
tipo)? ces[á]rea aborto ive interrupci[ó]n_?voluntaria(_?del_?embarazo)? m[eé]todo_?
(de_)?planificaci[ó]n planificaci[ó]n_?familiar anticoncepci[ó]n anticonceptivo
fertilidad infertilidad its ets infecci[ó]n(es)?_?(de_)?transmisi[ó]n_?sexual
pregnan(t|cy) contracepti(on|ve)

HOW IT IS MASKED

Flags keep their shape; any other value becomes Sin información .

CO_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: **CO_SUPRIMIR** .

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

CO_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.

CO_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `co-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
12 semanas de gestación	→	Sin información
S	→	S

11.12 Mental health

CO_SALUD_MENTAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Mental disorders, psychiatric or psychological care, suicide attempts, use of psychoactive substances.

HOW IT IS FOUND

COLUMN NAME

CO_SALUD_MENTAL – Path

90%

```
salud_?mental  trastorno[a-z]*  psiqui[aá]tri[a-z]*  psicol[oó]gi[a-z]*  depresi[oón]
ansiedad  suicid[a-z]*  intento_?(de_)?suicidio  autolesi[oón]  consumo_?(de_)?
(sustancias|spa|alcohol|drogas)  spa  sustancias_?psicoactivas  adicci[oón](es)?
farmacodependencia  alcoholismo  tabaquismo  mental_?health
```

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información` .

CO_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_SUPRIMIR` .

CO_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

CO_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt` , chosen by a keyed hash.

CO_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt` , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `co-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno bipolar

→

Sin información

Financial and socioeconomic data

Financial, credit and commercial information has its own habeas data regime (Law 1266 of 2008, amended by Law 2157 of 2021), and a negative report is among the data with the heaviest consequences for a person. Colombia adds two indicators that say a lot about whoever lives in a dwelling: the **socioeconomic stratum** from 1 to 6 and the **Sisbén IV** group, which decides access to the subsidized health regime and to social programmes. Categories are replaced within their own notation; amounts are mapped into a plausible range unrelated to the real value.

12.1 Credit bureaus

CO_FIN_CREDITO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The credit score (in DataCrédito, 150 to 950), the negative report, days and level of arrears, the status of the obligation and portfolio written off or in legal collection.

HOW IT IS FOUND

COLUMN NAME

CO_FIN_CREDITO – Path

90%

```
score(?:cr[eé]dito|datacr[eé]dito|cifin|transunion|experian|interno))? puntaje?(de_)?
cr[eé]dito calificaci[oó]n?(de_)?(riesgo|cr[eé]dito|cartera) centrales?(de_)?riesgo
reporte?(negativo|centrales|datacr[eé]dito|cifin) reportado dato?negativo
datacr[eé]dito cifin transunion d[ií]as?(de_)?mora altura?(de_)?mora edad?(de_)?
mora estado?(de_)?(cartera|obligaci[oó]n|cr[eé]dito) morosidad moroso carter_?
castigada cobro?jur[ií]dico credit?score credit?rating
```

HOW IT IS MASKED

A score gets other digits of the same length; a flag stays a flag; a status is replaced with another from the list.

CO_CREDITO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ESTADO_CREDITO .

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt`, chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt`, chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-yes-no.txt`, chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt`, chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-y-n.txt`, chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt`, chosen by a keyed hash.

CO_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in `co-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Reportado en DataCrédito	→	Reportado negativamente
745	→	471

12.2 Debt

CO_FIN_DEUDA

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Loan and portfolio balances, overdue amounts, instalments, disbursed amounts and credit limits.

HOW IT IS FOUND

COLUMN NAME CO_FIN_DEUDA – Path

85% saldo_?(deuda|cr[eé]dito|capital|obligaci[oó]n|cartera|en_?mora|adeudado) valor_?(de_?la_?)?
(deuda|cuota|obligaci[oó]n|cr[eé]dito|pr[eé]stamo|mora|en_?mora) vr_
(cuota|deuda|mora|saldo) deuda(_?total)? cupo_?(de_?)?(cr[eé]dito|tarjeta) cupo_
aprobado monto_?(cr[eé]dito|pr[eé]stamo|desembolsado) cuota_?mensual loan_
(amount|balance) outstanding_?balance debt

DATA TYPE CO_FIN_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 100,000 and 1,000,000,000 pesos, unrelated to the real value.

CO_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 100,000 and 1,000,000,000.

EXAMPLES

VALUE		MASKED
8500000	→	9340619

12.3 Income and salary

CO_FIN_INGRESOS

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Salary, monthly or household income, fees and contribution base income (IBC).

HOW IT IS FOUND

COLUMN NAME CO_FIN_INGRESOS – Path

85% salario(_?(b[aá]sico|integral|mensual|devengado))? sueldo(_?(b[aá]sico|mensual))?
ingresos?(_?(mensuales?|totales?|familiares?|laborales?|declarados?))? ibc ingreso_?base_
(de_?)?cotizaci[oó]n devengado asignaci[oó]n_?b[aá]sica honorarios remuneraci[oó]n vr_
(salario|ingreso) valor_?(salario|ingresos?) salary income wages?

DATA TYPE CO_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 1,000,000 and 60,000,000 pesos.

CO_INGRESOS **NUMERIC MAPPING**

Maps the number to another between 1,000,000 and 60,000,000.

EXAMPLES

VALUE		MASKED
3200000	→	9018715

12.4 Assets

CO_FIN_PATRIMONIO

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Net worth, assets, cadastral and market valuations, account balances, term deposits and investments, severance funds.

HOW IT IS FOUND

COLUMN NAME CO_FIN_PATRIMONIO – Path

85% patrimonio(_?(l[ií]quido|bruto))? activos?_?(totales?))? valor_?(de|_)?)
(inmueble|veh[ií]culo|bienes|aval[uú]o|comercial|catastral|inversi[oó]n) aval[uú]o(_?
catastral)? saldo_?(cuenta|ahorros|cdt|inversi[oó]n|cesant[ií]as|pensi[oó]n?voluntaria)
cdt(_?valor)? cesant[ií]as net_?worth account_?balance

DATA TYPE CO_FIN_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 10,000,000 and 2,000,000,000 pesos.

CO_PATRIMONIO **NUMERIC MAPPING**

Maps the number to another between 10,000,000 and 2,000,000,000.

EXAMPLES

VALUE		MASKED
185000000	→	233522319

12.5 Pension and subsidies

CO_FIN_PENSION

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

The amount of the monthly pension, subsidies and allowances, and child support.

HOW IT IS FOUND

COLUMN NAME CO_FIN_PENSION – Path

90% `mesada(_?pensional)? valor?(de_?la_?)(pensi[oó]n|mesada|subsidio|auxilio|beneficio)`
`pensi[oó]n?(valor|mensual|monto) vr?(pension|subsidio) cuota_?alimentaria pension_?`
`amount`

DATA TYPE CO_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between one 2026 minimum wage (1,750,905 pesos) and 30,000,000 pesos.

CO_VALOR_PENSION **NUMERIC MAPPING**

Maps the number to another between 1,750,905 and 30,000,000.

EXAMPLES

VALUE		MASKED
2400000	→	7834212

12.6 Socioeconomic stratum

CO_FIN ESTRATO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The stratum from 1 to 6 that classifies a dwelling for utility tariffs (Law 142 of 1994). It says, roughly, how much whoever lives there earns, and in which part of town.

HOW IT IS FOUND

COLUMN NAME CO_FIN ESTRATO – Path

90% `estrato(_?(socioecon[oó]mico|vivienda|residencia))?` `estr nivel_?socioecon[oó]mico`
`stratum`

KNOWN VALUES CO_FIN ESTRATO – List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-estratos.txt	12	40%	1, 2, 3, 4, 5, 6

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within its band — low (1-2), middle (3-4), high (5-6) —, so analysis by band keeps its shape.

Estrato 4 stays written the same way.

CO ESTRATO **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

CO ESTRATO_BAJO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-estrato-bajo.txt`, chosen by a keyed hash.

CO ESTRATO_MEDIO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-estrato-medio.txt`, chosen by a keyed hash.

CO ESTRATO_ALTO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `co-estrato-alto.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
2	→	2
Estrato 5	→	Estrato 5

12.7 Sisbén

CO_FIN_SISBEN

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The Sisbén IV group — A1-A5 extreme poverty, B1-B7 moderate poverty, C1-C18 vulnerable, D1-D21 neither poor nor vulnerable —, which decides access to the subsidized regime and to social programmes, and the Sisbén III score.

HOW IT IS FOUND

COLUMN NAME

CO_FIN_SISBEN - Path

95%

sisb[eé]n(?:iv|4|iii|grupo|puntaje|clasificaci[oó]n|nivel|categor[ií]a)? grupo_?

sisb[eé]n puntaje_?sisb[eé]n clasificaci[oó]n_?sisb[eé]n nivel_?sisb[eé]n ficha_?

sisb[eé]n

VALUE FORMAT

CO_FIN_SISBEN - Regex

PATTERN

STRENGTH

NOTES

[A-D]\s?\d{1,2}

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The group letter stays and the subgroup is replaced with another of the same group; a score is mapped digit by digit.

CO_SISBEN

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: CO_SISBEN_GRUPO .

CO_SISBEN_A SECURE LOOKUP

Replaces the value with one of the 5 values in co-sisben-a.txt , chosen by a keyed hash.

CO_SISBEN_B SECURE LOOKUP

Replaces the value with one of the 7 values in co-sisben-b.txt , chosen by a keyed hash.

CO_SISBEN_C SECURE LOOKUP

Replaces the value with one of the 18 values in co-sisben-c.txt , chosen by a keyed hash.

CO_SISBEN_D SECURE LOOKUP

Replaces the value with one of the 21 values in co-sisben-d.txt , chosen by a keyed hash.

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CO_SISBEN_GRUPO SECURE LOOKUP

Replaces the value with one of the 4 values in co-sisben-grupos.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
A3	→	A3
C15	→	C17

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Taking part in social programmes — Renta Ciudadana, Renta Joven, Colombia Mayor, VAT refund — and in housing and unemployment subsidies, often as a flag.

HOW IT IS FOUND

COLUMN NAME CO_FIN_PROGRAMA_SOCIAL - Path

90% programa_?(social|beneficiario|de_?gobierno|prosperidad) beneficiario_?
(programa|subsidio|renta|familias|colombia_?mayor) renta_?(ciudadana|joven|b[aá]sica)
familias_?en_?acci[oó]n j[oó]venes_?en_?acci[oó]n colombia_?mayor ingreso_?solidario
devoluci[oó]n_?(del_?)?iva subsidio(_?(familiar|vivienda|desempleo|tipo))? mi_?casa_?ya
transferencia_?monetaria social_?programme

KNOWN VALUES CO_FIN_PROGRAMA_SOCIAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
co-detectar-programas-sociales.txt	20	80%	Renta Ciudadana, Renta Joven, Colombia Mayor, Devolución del IVA, Devolucion del IVA, Mi Casa Ya
co-detectar-codigos-banderas.txt	11	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced with a programme from the list.

CO_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_PROGRAMA_SOCIAL_LISTA .

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in co-programas-sociales.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Familias en Acción

→ Mi Casa Ya

12.9 Housing tenure

CO_FIN_VIVIENDA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Tenure of the dwelling — owned outright or being paid, rented, usufruct, possession without title, collective property.

HOW IT IS FOUND

COLUMN NAME

CO_FIN_VIVIENDA - Path

90%

tenencia_?(de_?)(la_?)?vivienda tipo_?(de_?)?tenencia vivienda_?(propia|arrendada|tipo_?tenencia) condici[oó]n_?(de_?)(la_?)?vivienda ocupaci[oó]n_?vivienda housing_?tenure

KNOWN VALUES

CO_FIN_VIVIENDA - List

LIST

VALUES

STRENGTH

FIRST VALUES

co-detectar-
tenencia-
vivienda.txt

19

60%

Propia, totalmente pagada, Propia, la están pagando, Propia, la estan pagando, En arriendo o subarriendo, En usufructo, Posesión sin título

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced with another tenure from the list.

CO_TENENCIA_VIVIENDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_TENENCIA_VIVIENDA_LISTA

CO_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CO_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-si-no.txt , chosen by a keyed hash.

CO_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-true-false.txt , chosen by a keyed hash.

CO_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

CO_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-s-n.txt , chosen by a keyed hash.

CO_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

CO_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-0-1.txt , chosen by a keyed hash.

CO_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_TENENCIA_VIVIENDA_LISTA

SECURE LOOKUP

Replaces the value with one of the 7 values in co-tenencia-vivienda.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Invasión



Posesión sin título

Criminal records and proceedings

Not on the list of article 5, but for the Constitutional Court criminal records are *the negative data par excellence* (SU-458 of 2012): their circulation must be restricted to those with a legitimate interest. They get the same care as sensitive data.

13.1 Records

CO_PENAL_ANTECEDENTES

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Judicial records of the Police, disciplinary records of the Procuraduría and fiscal records of the Contraloría, the National Registry of Corrective Measures, type of crime, legal situation, pre-trial detention, being an INPEC inmate and arrest warrants.

HOW IT IS FOUND

COLUMN NAME	CO_PENAL_ANTECEDENTES – Path
95%	<code>antecedentes?(?(\judiciales penales disciplinarios fiscales))?</code> <code>certificado?(de_)?</code> <code>antecedentes</code> <code>medidas_?correctivas</code> <code>rnmc</code> <code>registro_?nacional_?(de_)?medidas_?correctivas</code> <code>condena(_?(penal tipo))?</code> <code>delito(_?(tipo cometido))?</code> <code>tipo_?(de_)?delito</code> <code>conducta_?</code> <code>punible</code> <code>situaci[oó]n_?jur[ií]dica</code> <code>medida_?(de_)?aseguramiento</code> <code>detenci[oó]n_?</code> <code>domiciliaria</code> <code>privad[oa]_?(de_)?(la_)?libertad</code> <code>recluso</code> <code>interno_?inpec</code> <code>td_?inpec</code> <code>reincidente</code> <code>orden_?(de_)?captura</code> <code>inhabilidad(es)?</code> <code>sanciones_?disciplinarias</code> <code>criminal_?</code> <code>record</code>
55%	<code>estado_(del_)?proceso</code> <code>sentido_(del_)?fallo</code> <code>fallo</code>

HOW IT IS MASKED

Replaced with a generic status from the list — nothing pending, convicted, acquitted —, whatever the outcome; a flag stays a flag.

CO_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ANTECEDENTES_LISTA .

CO_BANDERA REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
CO_BANDERA_SI_NO SECURE LOOKUP Replaces the value with one of the 2 values in <code>co-bandera-si-no.txt</code> , chosen by a keyed hash.
CO_BANDERA_TRUE_FALSE SECURE LOOKUP Replaces the value with one of the 2 values in <code>co-bandera-true-false.txt</code> , chosen by a keyed hash.
CO_BANDERA_YES_NO SECURE LOOKUP Replaces the value with one of the 2 values in <code>co-bandera-yes-no.txt</code> , chosen by a keyed hash.
CO_BANDERA_S_N SECURE LOOKUP Replaces the value with one of the 2 values in <code>co-bandera-s-n.txt</code> , chosen by a keyed hash.
CO_BANDERA_Y_N SECURE LOOKUP Replaces the value with one of the 2 values in <code>co-bandera-y-n.txt</code> , chosen by a keyed hash.
CO_BANDERA_0_1 SECURE LOOKUP Replaces the value with one of the 2 values in <code>co-bandera-0-1.txt</code> , chosen by a keyed hash.
CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CO_ANTECEDENTES_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `co-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Condenado por hurto en 2019

→

No tiene asuntos pendientes con las autoridades judiciales

13.2 Case file number

CO_PENAL_RADICADO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The file number of a Judiciary proceeding — 23 digits: DIVIPOLA code, court corporation, specialty, office, year, consecutive and appeal, `11001310300120200012300` — and SPOA criminal complaint numbers.

Proceedings can be looked up online and lead to the parties.

HOW IT IS FOUND

COLUMN NAME

CO_PENAL_RADICADO – Path

90%

```
n(o|ro|um|umero)?(de_)?(radicado|radicaci[oó]n|proceso|expediente|noticia_?
criminal|spoa|cui|denuncia|tutela|acci[oó]n_de_?tutela)(_(judicial|penal))? radicado_?
(judicial|proceso|penal|tutela)? radicaci[oó]n_proceso c[oó]ldigo_?[uú]nico?(de_)?
investigaci[oó]n cui spoa noticia_criminal
```

50%

proceso expediente

VALUE FORMAT

CO_PENAL_RADICADO – Regex

PATTERN

STRENGTH

NOTES

`\d{23}`

80%

`\d{21}`

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The consecutive is mapped digit by digit; city, corporation, specialty, office, year and appeal stay. Other numbers are masked character by character.

CO_RADICADO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

CO_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

CO_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

11001310300120200012300

→

11001310300120204791600

The NIT check digit

The Check Digit algorithm of the Masking Engine computes a modulus 11 digit as *eleven minus the remainder* and writes 10 as 0. For the NIT that is right for ten of the eleven possible remainders: when the remainder is 1, the DIAN writes 1 and Check Digit would write 0. One masked NIT in eleven would be invalid.

The set solves it in two steps, without tables:

- A Check Digit with **doubled weights** maps the body and writes an auxiliary digit where the check digit goes. Since $2 \times 1 \equiv 2$ modulus 11, the auxiliary digit is 9 exactly when the remainder of the masked body with the true weights is 1.
- A Regex Decompose turns a final 9 into 1, and otherwise applies a Check Digit with the true weights over the body, which it leaves as it is, and recomputes the digit.

Check Digit needs as many weights as digits, so there is one pair of steps per body length, from 6 to 10 digits, and a Regex Decompose that picks by the shape of the value, with or without dots and hyphen. The body is mapped with the same Character Mapping as the cédula: a natural person's NIT still matches their masked cédula.

Where people live: municipalities, veredas and postal code

With DANE's municipal population projection for 2026 (based on the 2018 census, post COVID-19 update) and the location of each seat in DIVIPOLA, the set knows the size, department and position of 1,122 municipalities and non-municipalized areas.

- A **municipality** with fewer than 20,000 inhabitants becomes the nearest municipality of the same department with at least 20,000. There are 694 of them, with 6.4 million inhabitants — 12% of the population. Jardín (Antioquia) becomes Andes; Providencia, San Andrés; the non-municipalized areas of Guainía, Inírida.
- The **department** stays. Every one has at least one municipality of 20,000 inhabitants.
- Distance is measured between the coordinates of the seats, in a straight line.
- Some names repeat — four La Unión, four Villanueva, four Buenavista — and others differ only in an accent. A name on its own is generalized only when every municipality bearing it is small, and then it follows the largest of them. With the department (La Unión – Sucre , La Unión (Sucre) , La Unión, Sucre) there is no ambiguity, and the municipality is always generalized.
- The **DIVIPOLA code** follows the same table, and a person's name and code still agree.
- Names are also recognized as people write them: Cartagena , Cúcuta , Mompox , Bogotá .
- The **vereda** and the **corregimiento** become Zona rural , and the **postal code** keeps only the department.

Municipality names that are also given names or surnames, and department names, are left out of the detection list, so that a column of surnames is not taken for municipalities.

Limits

- **Binary columns** — cédula photos, biometric validation selfies, fingerprints, medical record PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A NIT whose body has 5 digits or fewer, or more than 10**, is masked digit by digit, without recomputing the digit. A NIT with neither hyphen nor dots is read as body and digit: 8001972684 is 800197268–4 .
- **A check digit in a column of its own** is not recomputed: it is masked and no longer matches the masked NIT.
- **The department, the bank code and the phone prefix stay.**
- **Data Cleansing lets through what it does not know:** a municipality written in a way the table does not have — abbreviated, misspelled — passes unchanged.
- **Free text** is redacted word by word: a mobile written with spaces is not found, and a name that is also a common word (Luz , Rosa , León) is redacted wherever it appears.
- **Children and adolescents** — a birth date moves at most 60 days, so few people cross their 14th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, neighbourhood, municipality and postal code in separate columns are masked independently and no longer form a coherent address.
- **The engine key** links masked values back to production for whoever holds both: in that case the result is pseudonymized data, still personal data. Keep the key away from the users of the copy.

17

Verification

Before publication, the set was checked outside a Masking Engine:

- The check-digit rule was checked against the DIAN's own NIT, 800.197.268–4 .
- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 151 columns with the whole set at its assignment threshold — well named, badly named and 31 columns that are not personal data — and again with only the classifiers of the essential pack.
- The table that generalizes municipalities was audited for all 1,122 DIVIPOLA units: by name, by name with the department and by code.
- The algorithms, run with the Delphix algorithm plugin, masked each domain's sample values and placeholders such as N/A , checking every output against its vocabulary; 200 NITs of every length — remainder 1 included — for validity and collisions; 150 cédulas for collisions; and 20 people whose cédula and NIT must still agree. Every algorithm also masked its own sample value.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

18

Sources

- Statutory Law 1581 of 2012 (Senate Secretariat, text in force). Constitutional Court, judgments C-748 of 2011 and SU-458 of 2012. Decree 1377 of 2013, compiled in Decree 1074 of 2015. Political Constitution, arts. 15 and 153.

- Superintendencia de Industria y Comercio: security incident reporting in the National Database Registry; reform of Law 1581 (bills 214 and 274 of 2025, House of Representatives).
- Law 1266 of 2008 and Law 2157 of 2021 (financial habeas data). Law 1273 of 2009 (art. 269F). Law 1448 of 2011 (victims). Law 142 of 1994 (stratification). Decree 1469 of 2025 (2026 minimum wage).
- Archivo General de la Nación, Guide to the Anonymization of Structured Data (2020). DANE, Data anonymization guide (2024).
- DANE: municipal population projections 2020–2035 (post COVID-19 update); DIVIPOLA (datos.gov.co); 2018 census, ethnic self-recognition and indigenous peoples.
- National Electoral Council: political organizations with legal personality (16 September 2026). DIAN: NIT check digit. Banco de la República: Bre-B keys. National Planning Department: Sisbén IV. Communications Regulation Commission: numbering plan. Judiciary: case file numbering.

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

CO_AFILIACION_SALUD REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_EPS .

Used by: CO_SALUD_AFILIACION

PATTERNS, TRIED IN ORDER	
(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(?i) (contributivo subsidiado especial de\s+excepti[ó]n excepti[ó]n no\s+afiliado)	CO_REGIMEN_SALUD
(\d{1,6})	CO_CM_DIGITOS
otherwise	CO_EPS
CONFIGURATION	
trimInput	yes
requireMask	no

CO_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CO_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER	
(\d{3})(\d)	keep · CO_CM_DIGITOS
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

CO_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ANTECEDENTES_LISTA .

Used by: CO_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER	
(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_ANTECEDENTES_LISTA
CONFIGURATION	
trimInput	yes
requireMask	no

CO_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-antecedentes.txt` , chosen by a keyed hash.

Used by: CO_ANTECEDENTES

CONFIGURATION

lookupFile	co-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_APELLIDO NAME

Replaces the name with one of the 255 names in `co-apellidos.txt` .

Used by: CO_PALABRA_APELLIDO

CONFIGURATION

lookupFile	co-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

CO_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

Used by: CO_L1_APELLIDO , CO_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	CO_PALABRA_APELLIDO
(\S+)\s+(\S+)	CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO
otherwise	CO_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CO_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CO_CATEGORIA_SUPRIMIDA , CO_ESTADO_CIVIL , CO_ESCOLARIDAD , CO_GRUPO_ETNICO , CO_PUEBLO_INDIGENA , CO LENGUA , CO_RELIGION , CO_ORIENTACION_POLITICA , CO_PARTIDO , CO_ORIENTACION_SEXUAL , CO_IDENTIDAD_GENERO , CO_VICTIMA , CO_AFILIACION_SALUD , CO_DIAGNOSTICO , CO_MEDICAMENTO , CO_DISCAPACIDAD , CO_SALUD_LABORAL , CO_CREDITO , CO_PROGRAMA_SOCIAL , CO_TENENCIA_VIVIENDA , CO_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	CO_BANDERA_SI_NO
(?i)(true false)	CO_BANDERA_TRUE_FALSE
(?i)(yes)	CO_BANDERA_YES_NO
(?i)([sn])	CO_BANDERA_S_N

(?i)([yx])	CO_BANDERA_Y_N
([01])	CO_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-0-1.txt` , chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	co-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-s-n.txt` , chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	co-bandera-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-si-no.txt` , chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	co-bandera-si-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-bandera-true-false.txt` , chosen by a keyed hash.

Used by: `CO_BANDERA`

CONFIGURATION

lookupFile	co-bandera-true-false.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-y-n.txt , chosen by a keyed hash.

Used by: CO_BANDERA

CONFIGURATION

lookupFile	co-bandera-y-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in co-bandera-yes-no.txt , chosen by a keyed hash.

Used by: CO_BANDERA

CONFIGURATION

lookupFile	co-bandera-yes-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_BARRIO SECURE LOOKUP

Replaces the value with one of the 35 values in co-barrrios.txt , chosen by a keyed hash.

Used by: CO_L2_BARRIO

CONFIGURATION

lookupFile	co-barrrios.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_SUPRIMIR .

Used by: CO_L3_CONVICCION_FILOSOFICA , CO_L3_SINDICATO , CO_L3_ORGANIZACION_SOCIAL , CO_L3_VIDA_SEXUAL , CO_L3_REINCORPORACION , CO_SALUD_REPRODUCTIVA , CO_SALUD_MENTAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_SUPRIMIR

CONFIGURATION

trimInput	yes
requireMask	no

CO_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in co-cie10.txt , chosen by a keyed hash.

Used by: CO_DIAGNOSTICO

CONFIGURATION

lookupFile	co-cie10.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in co-cie10-decimal.txt , chosen by a keyed hash.

Used by: CO_DIAGNOSTICO

CONFIGURATION

lookupFile	co-cie10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: CO_L1_DOCUMENTO_EXTRANJERO , CO_L1_PASAPORTE , CO_L1_REGISTRO_CIVIL , CO_L1_TARJETA_PROFESIONAL , CO_L1_DIRECCION_COMPLEMENTO , CO_L1_VEHICULO , CO_L1_CONTRATO , CO_L1_USUARIO , CO_SALUD_IDENTIFICADOR , CO_SALUD_RESULTADO_EXAMEN , CO_CATEGORIA_SUPRIMIDA , CO_DOCUMENTO , CO_NOMBRES , CO_APELLIDOS , CO_NOMBRE_COMPLETO , CO_EMAIL , CO_LLAVE_BREB , CO_PLACA , CO LENGUA , CO_RELIGION , CO_ORIENTACION_POLITICA , CO_PARTIDO , CO_ORIENTACION_SEXUAL , CO_IDENTIDAD_GENERO , CO_VICTIMA , CO_MEDICAMENTO , CO_DISCAPACIDAD , CO_SALUD_LABORAL , CO_PROGRAMA_SOCIAL , CO_TENENCIA_VIVIENDA , CO_ANTECEDENTES , CO_RADICADO

CONFIGURATION

characterGroups	0123456789 AEIOU BCFGHJKLMNPQRSTUVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚÚ áéíóúú
caseSensitive	yes
minMaskedPositions	0

CO_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: CO_L1_CUENTA_BANCARIA , CO_NIT_6_AUX , CO_NIT_7_AUX , CO_NIT_8_AUX , CO_NIT_9_AUX , CO_NIT_10_AUX , CO_NIT , CO_DOCUMENTO , CO_TELEFONO , CO_LLAVE_BREB , CO_PLACA , CO_INMUEBLE , CO_COORDENADA , CO_ANIO , CO_EDAD , CO_OCUPACION_O_CIUO , CO_AFILIACION_SALUD , CO_CREDITO , CO_SISBEN , CO_RADICADO

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0

CO_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: CO_PLACA

CONFIGURATION

characterGroups	0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

CO_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: CO_L1_DISPOSITIVO , CO_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

CO_CODIGO_MUNICIPIO DATA CLEANSING

Replaces each value found in co-codigos-municipio-generalizados.txt (694 pairs) by its counterpart; values not in the file stay as they are.

Used by: CO_L2_CODIGO_MUNICIPIO

CONFIGURATION

lookupFile	co-codigos-municipio-generalizados.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

CO_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CO_L2_CODIGO_POSTAL

PATTERNS, TRIED IN ORDER

(\d{2})(\d{4})	keep · replace with 0000
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CO_L2_PERSONAS_A_CARGO

PATTERNS, TRIED IN ORDER

([0-5])	keep
(\d+)	replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CO_L1_GEOLOCALIZACION

PATTERNS, TRIED IN ORDER

(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)	keep · CO_CM_DIGITOS · keep · keep · CO_CM_DIGITOS
(-?\d{1,3}[.,]\d)(\d+)	keep · CO_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_CREDITO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_ESTADO_CREDITO .

Used by: CO_FIN_CREDITO

PATTERNS, TRIED IN ORDER

(\d{1,4})	CO_CM_DIGITOS
(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
otherwise	CO_ESTADO_CREDITO

CONFIGURATION

trimInput	yes
requireMask	no

CO_CUPS SECURE LOOKUP

Replaces the value with one of the 10 values in co-cups.txt , chosen by a keyed hash.

Used by: CO_PROCEDIMIENTO

CONFIGURATION

lookupFile	co-cups.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

CO_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CO_DIAGNOSTICO_TEXT0 .

Used by: CO_SALUD_DIAGNOSTICO

PATTERNS, TRIED IN ORDER

([A-TV-Za-tv-z]\d{2}\.\d{1,2})	CO_CIE10_DECIMAL
([A-TV-Za-tv-z]\d{2,3}X?)	CO_CIE10
(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
otherwise	CO_DIAGNOSTICO_TEXT0

CONFIGURATION

trimInput	yes
requireMask	no

CO_DIAGNOSTICO_TEXT0 SECURE LOOKUP

Replaces the value with one of the 30 values in co-diagnostics.txt , chosen by a keyed hash.

Used by: CO_DIAGNOSTICO

CONFIGURATION

lookupFile	co-diagnostics.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in co-direcciones.txt , chosen by a keyed hash.

Used by: CO_L1_DIRECCION

CONFIGURATION

lookupFile	co-direcciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_DISCAPACIDAD_LISTA .

Used by: CO_SALUD_DISCAPACIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM

otherwise	CO_DISCAPACIDAD_LISTA
-----------	-----------------------

CONFIGURATION

trimInput	yes
requireMask	no

CO_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-discapacidades.txt` , chosen by a keyed hash.

Used by: `CO_DISCAPACIDAD`

CONFIGURATION

lookupFile	co-discapacidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_DOCUMENTO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM` .

Used by: `CO_L1_CEDULA`

PATTERNS, TRIED IN ORDER

<code>(\d{1,3}(?:\.\d{3})+ \d{3,11})</code>	<code>CO_CM_DIGITOS</code>
<code>(\d{3}\.\d{3}\s?-\s?\d)</code>	<code>CO_NIT_6</code>
<code>(\d{1}\.\d{3}\.\d{3}\s?-\s?\d)</code>	<code>CO_NIT_7</code>
<code>(\d{2}\.\d{3}\.\d{3}\s?-\s?\d)</code>	<code>CO_NIT_8</code>
<code>(\d{3}\.\d{3}\.\d{3}\s?-\s?\d)</code>	<code>CO_NIT_9</code>
<code>(\d{1}\.\d{3}\.\d{3}\.\d{3}\s?-\s?\d)</code>	<code>CO_NIT_10</code>
otherwise	<code>CO_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `keep`.

Used by: `CO_L2_EDAD`

PATTERNS, TRIED IN ORDER

<code>(\d{3,})</code>	replace with <code>90</code>
<code>([1-9])(\d)([.,]\d+)</code>	keep · <code>CO_CM_DIGITOS</code> · keep
<code>([1-9])(\d)</code>	keep · <code>CO_CM_DIGITOS</code>
<code>(\d)</code>	<code>CO_CM_DIGITOS</code>
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

CO_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

Used by: CO_L1_EMAIL , CO_LLAVE_BREB

PATTERNS, TRIED IN ORDER

(([^@\\s]+)) @ (([^@\\s]+)) \\ . ([A-Za-z]{2,24}) (? : \\ . [A-Za-z]{2}) ?)	CO_CM_ALFANUM · CO_CM_ALFANUM · replace with test
--	---

otherwise	CO_CM_ALFANUM
-----------	---------------

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

CO_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in co-empleadores.txt , chosen by a keyed hash.

Used by: CO_L2_EMPLEADOR

CONFIGURATION

lookupFile	co-empleadores.txt
------------	--------------------

hashMethod	SHA256
------------	--------

maskedValueCase	PRESERVE_INPUT
-----------------	----------------

inputCaseSensitive	no
--------------------	----

trimWhitespaceFromInput	yes
-------------------------	-----

trimWhitespaceInLookupFile	yes
----------------------------	-----

CO_EPS SECURE LOOKUP

Replaces the value with one of the 18 values in co-eps.txt , chosen by a keyed hash.

Used by: CO_AFILIACION_SALUD

CONFIGURATION

lookupFile	co-eps.txt
------------	------------

hashMethod	SHA256
------------	--------

maskedValueCase	PRESERVE_LOOKUP_FILE
-----------------	----------------------

inputCaseSensitive	no
--------------------	----

trimWhitespaceFromInput	yes
-------------------------	-----

trimWhitespaceInLookupFile	yes
----------------------------	-----

CO_ESCOLARIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ESCOLARIDAD_LISTA .

Used by: CO_L2_ESCOLARIDAD

PATTERNS, TRIED IN ORDER

(? i) (s [i í] n o t r u e f a l s e y e s [s n y x 0 1])	CO_BANDERA
---	------------

(\ d { 1 , 6 })	CO_ESCOLARIDAD_CODIGO
-------------------	-----------------------

otherwise	CO_ESCOLARIDAD_LISTA
-----------	----------------------

CONFIGURATION

trimInput	yes
requireMask	no

CO_ESCOLARIDAD_CODIGO SECURE LOOKUP

Replaces the value with one of the 11 values in co-escolaridad-codigos.txt , chosen by a keyed hash.

Used by: CO_ESCOLARIDAD

CONFIGURATION

lookupFile	co-escolaridad-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESCOLARIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in co-escolaridad.txt , chosen by a keyed hash.

Used by: CO_ESCOLARIDAD

CONFIGURATION

lookupFile	co-escolaridad.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ESTADO_CIVIL_LISTA .

Used by: CO_L2_ESTADO_CIVIL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_ESTADO_CIVIL_CODIGO
otherwise	CO_ESTADO_CIVIL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in co-estado-civil-codigos.txt , chosen by a keyed hash.

Used by: CO_ESTADO_CIVIL

CONFIGURATION

lookupFile	co-estado-civil-codigos.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `co-estado-civil.txt` , chosen by a keyed hash.

Used by: `CO_ESTADO_CIVIL`

CONFIGURATION

lookupFile	co-estado-civil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in `co-estados-credito.txt` , chosen by a keyed hash.

Used by: `CO_CREDITO`

CONFIGURATION

lookupFile	co-estados-credito.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTRATO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CO_FIN_ESTRATO`

PATTERNS, TRIED IN ORDER

<code>(?i)(estrato\s*)([12])</code>	keep · <code>CO_ESTRATO_BAJO</code>
<code>(?i)(estrato\s*)([34])</code>	keep · <code>CO_ESTRATO_MEDIO</code>
<code>(?i)(estrato\s*)([56])</code>	keep · <code>CO_ESTRATO_ALTO</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_ESTRATO_ALTO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-estrato-alto.txt` , chosen by a keyed hash.

Used by: `CO_ESTRATO`

CONFIGURATION

lookupFile	co-estrato-alto.txt
------------	---------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTRATO_BAJO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-estrato-bajo.txt` , chosen by a keyed hash.

Used by: `CO_ESTRATO`

CONFIGURATION

lookupFile	co-estrato-bajo.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ESTRATO_MEDIO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-estrato-medio.txt` , chosen by a keyed hash.

Used by: `CO_ESTRATO`

CONFIGURATION

lookupFile	co-estrato-medio.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `CO_L2_FECHA_EVENTO`

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

CO_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `CO_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS

roll	no
------	----

CO_GRUPO_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_GRUPO_ETNICO_LISTA .

Used by: CO_L3_GRUPO_ETNICO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snx01])	CO_BANDERA
(\d{1,6})	CO_GRUPO_ETNICO_CODIGO
otherwise	CO_GRUPO_ETNICO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_GRUPO_ETNICO_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in co-grupos-etnicos-codigos.txt , chosen by a keyed hash.

Used by: CO_GRUPO_ETNICO

CONFIGURATION

lookupFile	co-grupos-etnicos-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_GRUPO_ETNICO_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in co-grupos-etnicos.txt , chosen by a keyed hash.

Used by: CO_GRUPO_ETNICO

CONFIGURATION

lookupFile	co-grupos-etnicos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in co-grupos-sanguineos.txt , chosen by a keyed hash.

Used by: CO_SALUD_GRUPO_SANGUINEO

CONFIGURATION

lookupFile	co-grupos-sanguineos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CO_NIT_6_DV , CO_NIT_7_DV , CO_NIT_8_DV , CO_NIT_9_DV , CO_NIT_10_DV

PATTERNS, TRIED IN ORDER

(.*)	keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_IDENTIDAD_GENERO_LISTA .

Used by: CO_L3_IDENTIDAD_GENERO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in co-identidades-genero.txt , chosen by a keyed hash.

Used by: CO_IDENTIDAD_GENERO

CONFIGURATION

lookupFile	co-identidades-genero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_INGRESOS NUMERIC MAPPING

Maps the number to another between 1,000,000 and 60,000,000.

Used by: CO_FIN_INGRESOS

CONFIGURATION

minValue	1000000
maxValue	60000000

CO_INMUEBLE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_CM_DIGITOS .

Used by: CO_L1_INMUEBLE

PATTERNS, TRIED IN ORDER

(\d{2,3}[A-Za-z]?)([\s\~+](\d{3,9})	keep · keep · CO_CM_DIGITOS
(\d{5})(\d{25})	keep · CO_CM_DIGITOS
otherwise	CO_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

CO_INSTITUCION_EDUCATIVA SECURE LOOKUP

Replaces the value with one of the 12 values in co-instituciones-educativas.txt , chosen by a keyed hash.

Used by: CO_L2_INSTITUCION_EDUCATIVA

CONFIGURATION

lookupFile	co-instituciones-educativas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_HEX .

Used by: CO_L1_IP

PATTERNS, TRIED IN ORDER

(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3})	CO_OCTETO · CO_OCTETO · CO_OCTETO · CO_OCTETO
otherwise	CO_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

CO LENGUA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO LENGUA_LISTA .

Used by: CO_L3_LENGUA_NATIVA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO LENGUA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_LENGUA_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `co-lenguas.txt` , chosen by a keyed hash.

Used by: `CO_LENGUA`

CONFIGURATION

lookupFile	co-lenguas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_LLAVE_BREB REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM` .

Used by: `CO_L1_LLAVE_BREB`

PATTERNS, TRIED IN ORDER

<code>([^\s]+@[^\s]+)</code>	<code>CO_EMAIL</code>
<code>(@)(\S+)</code>	keep · <code>CO_CM_ALFANUM</code>
<code>(3\d{9})</code>	<code>CO_TELEFONO</code>
<code>(\d{3,11})</code>	<code>CO_CM_DIGITOS</code>
otherwise	<code>CO_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CO_MEDICAMENTO_LISTA` .

Used by: `CO_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CO_BANDERA</code>
<code>(\d{1,6})</code>	<code>CO_CM_ALFANUM</code>
otherwise	<code>CO_MEDICAMENTO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 24 values in `co-medicamentos.txt` , chosen by a keyed hash.

Used by: `CO_MEDICAMENTO`

CONFIGURATION

lookupFile	co-medicamentos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_MUNICIPIO DATA CLEANSING

Replaces each value found in `co-municipios-generalizados.txt` (12,622 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CO_L2_MUNICIPIO`

CONFIGURATION

lookupFile	<code>co-municipios-generalizados.txt</code>
delimiter	
caseSensitive	yes
trimWhitespace	yes

CO_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 16 values in `co-nacionalidades.txt`, chosen by a keyed hash.

Used by: `CO_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	<code>co-nacionalidades.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_NIT REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_DIGITOS`.

Used by: `CO_L1_NIT`

PATTERNS, TRIED IN ORDER

<code>(\d{3}\.?\d{3}\s?-\s?\d)</code>	<code>CO_NIT_6</code>
<code>(\d{1}\.?\d{3}\.?\d{3}\s?-\s?\d)</code>	<code>CO_NIT_7</code>
<code>(\d{2}\.?\d{3}\.?\d{3}\s?-\s?\d)</code>	<code>CO_NIT_8</code>
<code>(\d{3}\.?\d{3}\.?\d{3}\s?-\s?\d)</code>	<code>CO_NIT_9</code>
<code>(\d{1}\.?\d{3}\.?\d{3}\.?\d{3}\s?-\s?\d)</code>	<code>CO_NIT_10</code>
otherwise	<code>CO_CM_DIGITOS</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_10 STRING ALGORITHM CHAIN

Applies `CO_NIT_10_AUX` → `CO_NIT_10_AJUSTE`, in this order.

Used by: `CO_NIT`, `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	<code>CO_NIT_10_AUX</code>
------------------------	----------------------------

algorithmReferences[2]	CO_NIT_10_AJUSTE
------------------------	------------------

CO_NIT_10_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_10_DV .

Used by: CO_NIT_10

PATTERNS, TRIED IN ORDER

(.*) (9)	keep · replace with 1
otherwise	CO_NIT_10_DV

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_10_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 82 86 from the right.

Used by: CO_NIT_10

CONFIGURATION

weightList	6 14 26 34 38 46 58 74 82 86
modulusNumber	11
checkDigitIndex	10
numDigitsForCheckdigitCalculation	10
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_CM_DIGITOS
alphaNumericAlgorithm	CO_CM_DIGITOS
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_10_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 41 43 from the right.

Used by: CO_NIT_10_AJUSTE

CONFIGURATION

weightList	3 7 13 17 19 23 29 37 41 43
modulusNumber	11
checkDigitIndex	10
numDigitsForCheckdigitCalculation	10
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_IDENTIDAD
alphaNumericAlgorithm	CO_IDENTIDAD
preserveRegex	[.\-\\s]

inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_6 STRING ALGORITHM CHAIN

Applies CO_NIT_6_AUX → CO_NIT_6_AJUSTE , in this order.

Used by: CO_NIT , CO_DOCUMENTO

CONFIGURATION

algorithmReferences[1]	CO_NIT_6_AUX
algorithmReferences[2]	CO_NIT_6_AJUSTE

CO_NIT_6_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_6_DV .

Used by: CO_NIT_6

PATTERNS, TRIED IN ORDER

(.*) (9)	keep · replace with 1
otherwise	CO_NIT_6_DV

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_6_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 from the right.

Used by: CO_NIT_6

CONFIGURATION

weightList	6 14 26 34 38 46
modulusNumber	11
checkDigitIndex	6
numDigitsForCheckdigitCalculation	6
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_CM_DIGITOS
alphaNumericAlgorithm	CO_CM_DIGITOS
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_6_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 from the right.

Used by: `CO_NIT_6_AJUSTE`

CONFIGURATION

weightList	3 7 13 17 19 23
modulusNumber	11
checkDigitIndex	6
numDigitsForCheckdigitCalculation	6
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_IDENTIDAD
alphaNumericAlgorithm	CO_IDENTIDAD
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_7 STRING ALGORITHM CHAIN

Applies `CO_NIT_7_AUX` → `CO_NIT_7_AJUSTE` , in this order.

Used by: `CO_NIT` , `CO_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	CO_NIT_7_AUX
algorithmReferences[2]	CO_NIT_7_AJUSTE

CO_NIT_7_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CO_NIT_7_DV` .

Used by: `CO_NIT_7`

PATTERNS, TRIED IN ORDER

<code>(.*) (9)</code>	keep · replace with 1
otherwise	CO_NIT_7_DV

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_7_AUX CHECK DIGIT

Masks the digits with `CO_CM_DIGITOS` and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 from the right.

Used by: `CO_NIT_7`

CONFIGURATION

weightList	6 14 26 34 38 46 58
modulusNumber	11
checkDigitIndex	7
numDigitsForCheckdigitCalculation	7
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_CM_DIGITOS

alphaNumericAlgorithm	CO_CM_DIGITOS
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_7_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 from the right.

Used by: CO_NIT_7_AJUSTE

CONFIGURATION

weightList	3 7 13 17 19 23 29
modulusNumber	11
checkDigitIndex	7
numDigitsForCheckdigitCalculation	7
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_IDENTIDAD
alphaNumericAlgorithm	CO_IDENTIDAD
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_8 STRING ALGORITHM CHAIN

Applies CO_NIT_8_AUX → CO_NIT_8_AJUSTE , in this order.

Used by: CO_NIT , CO_DOCUMENTO

CONFIGURATION

algorithmReferences[1]	CO_NIT_8_AUX
algorithmReferences[2]	CO_NIT_8_AJUSTE

CO_NIT_8_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_8_DV .

Used by: CO_NIT_8

PATTERNS, TRIED IN ORDER

(.*) (9)	keep · replace with 1
otherwise	CO_NIT_8_DV

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_8_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 from the right.

Used by: CO_NIT_8

CONFIGURATION

weightList	6 14 26 34 38 46 58 74
modulusNumber	11
checkDigitIndex	8
numDigitsForCheckdigitCalculation	8
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_CM_DIGITOS
alphaNumericAlgorithm	CO_CM_DIGITOS
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_8_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 from the right.

Used by: CO_NIT_8_AJUSTE

CONFIGURATION

weightList	3 7 13 17 19 23 29 37
modulusNumber	11
checkDigitIndex	8
numDigitsForCheckdigitCalculation	8
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_IDENTIDAD
alphaNumericAlgorithm	CO_IDENTIDAD
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_9 STRING ALGORITHM CHAIN

Applies CO_NIT_9_AUX → CO_NIT_9_AJUSTE , in this order.

Used by: CO_NIT , CO_DOCUMENTO

CONFIGURATION

algorithmReferences[1]	CO_NIT_9_AUX
algorithmReferences[2]	CO_NIT_9_AJUSTE

CO_NIT_9_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NIT_9_DV .

Used by: CO_NIT_9

PATTERNS, TRIED IN ORDER

(.*) (9)	keep · replace with 1
otherwise	CO_NIT_9_DV

CONFIGURATION

trimInput	yes
requireMask	no

CO_NIT_9_AUX CHECK DIGIT

Masks the digits with CO_CM_DIGITOS and recomputes a modulus 11 check digit with weights 6 14 26 34 38 46 58 74 82 from the right.

Used by: CO_NIT_9

CONFIGURATION

weightList	6 14 26 34 38 46 58 74 82
modulusNumber	11
checkDigitIndex	9
numDigitsForCheckdigitCalculation	9
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_CM_DIGITOS
alphaNumericAlgorithm	CO_CM_DIGITOS
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NIT_9_DV CHECK DIGIT

Masks the digits with CO_IDENTIDAD and recomputes a modulus 11 check digit with weights 3 7 13 17 19 23 29 37 41 from the right.

Used by: CO_NIT_9_AJUSTE

CONFIGURATION

weightList	3 7 13 17 19 23 29 37 41
modulusNumber	11
checkDigitIndex	9
numDigitsForCheckdigitCalculation	9
calculateChecksumRightToLeft	yes
numericAlgorithm	CO_IDENTIDAD
alphaNumericAlgorithm	CO_IDENTIDAD
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR

inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

CO_NOMBRE NAME

Replaces the name with one of the 232 names in `co-nombres.txt`.

Used by: `CO_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	co-nombres.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

CO_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

<code>([^\,]+),\s*(.+)</code>	<code>CO_APELLIDOS · CO_NOMBRES</code>
<code>(\S+)</code>	<code>CO_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO · CO_PALABRA_APELLIDO</code>
otherwise	<code>CO_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM`.

Used by: `CO_L1_NOMBRE`, `CO_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

<code>(\S+)</code>	<code>CO_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)\s+(\S+)</code>	<code>CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE · CO_PALABRA_NOMBRE</code>
otherwise	<code>CO_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: CO_IP

CONFIGURATION

minValue	1
maxValue	254

CO_OCUPACION SECURE LOOKUP

Replaces the value with one of the 39 values in co-ocupaciones.txt , chosen by a keyed hash.

Used by: CO_OCUPACION_0_CIUO

CONFIGURATION

lookupFile	co-ocupaciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_OCUPACION_0_CIUO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_OCUPACION .

Used by: CO_L2_OCUPACION

PATTERNS, TRIED IN ORDER

(\d{4,5})	CO_CM_DIGITOS
otherwise	CO_OCUPACION

CONFIGURATION

trimInput	yes
requireMask	no

CO_ORIENTACION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ORIENTACION_POLITICA_LISTA .

Used by: CO_L3_ORIENTACION_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [sn]yx01))	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_ORIENTACION_POLITICA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_ORIENTACION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in co-orientaciones-politicas.txt , chosen by a keyed hash.

Used by: CO_ORIENTACION_POLITICA

CONFIGURATION

lookupFile	co-orientaciones-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_ORIENTACION_SEXUAL_LISTA .

Used by: CO_L3_ORIENTACION_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_ORIENTACION_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in co-orientaciones-sexuales.txt , chosen by a keyed hash.

Used by: CO_ORIENTACION_SEXUAL

CONFIGURATION

lookupFile	co-orientaciones-sexuales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_APELLIDO .

Used by: CO_APELLIDOS , CO_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i)	keep
(de del la las los y e san santa van von di)	
otherwise	CO_APELLIDO

CONFIGURATION

trimInput	yes
requireMask	no

CO_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_NOMBRE .

Used by: `CO_NOMBRES` , `CO_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

<code>(?i)</code>	keep
<code>(de del la las los y e san santa van von di)</code>	
otherwise	<code>CO_NOMBRE</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_PARTIDO_LISTA` .

Used by: `CO_L3_AFILIACION_PARTIDO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CO_BANDERA</code>
<code>(\d{1,6})</code>	<code>CO_CM_ALFANUM</code>
otherwise	<code>CO_PARTIDO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 29 values in `co-partidos.txt` , chosen by a keyed hash.

Used by: `CO_PARTIDO`

CONFIGURATION

lookupFile	<code>co-partidos.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 10,000,000 and 2,000,000,000.

Used by: `CO_FIN_PATRIMONIO`

CONFIGURATION

minValue	<code>10000000</code>
maxValue	<code>2000000000</code>

CO_PLACA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CO_CM_ALFANUM` .

Used by: `CO_L1_PLACA`

PATTERNS, TRIED IN ORDER

<code>([A-Za-z]{3})([\s-]?)(\d{3})</code>	<code>CO_CM_DIGITOS_LETRAS</code> · keep · <code>CO_CM_DIGITOS</code>
---	---

<code>([A-Za-z]{3})([\s\~?](\d{2}))([A-Za-z]?)</code>	<code>CO_CM_DIGITOS_LETRAS</code> · keep · <code>CO_CM_DIGITOS</code> · <code>CO_CM_DIGITOS_LETRAS</code>
otherwise	<code>CO_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

`CO_PROCEDIMIENTO_TEXTO` .

Used by: `CO_SALUD_PROCEDIMIENTO`

PATTERNS, TRIED IN ORDER

<code>(\d{6} \d{2}\.\d{2}\.\d{2})</code>	<code>CO_CUPS</code>
otherwise	<code>CO_PROCEDIMIENTO_TEXTO</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in `co-procedimientos.txt` , chosen by a keyed hash.

Used by: `CO_PROCEDIMIENTO`

CONFIGURATION

lookupFile	<code>co-procedimientos.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CO_PROGRAMA_SOCIAL_LISTA` .

Used by: `CO_FIN_PROGRAMA_SOCIAL`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CO_BANDERA</code>
<code>(\d{1,6})</code>	<code>CO_CM_ALFANUM</code>
otherwise	<code>CO_PROGRAMA_SOCIAL_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CO_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `co-programas-sociales.txt` , chosen by a keyed hash.

Used by: `CO_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	co-programas-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PUEBLO_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_PUEBLO_INDIGENA_LISTA .

Used by: CO_L3_PUEBLO_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_PUEBLO_INDIGENA_CODIGO
otherwise	CO_PUEBLO_INDIGENA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_PUEBLO_INDIGENA_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in co-pueblos-indigenas-codigos.txt , chosen by a keyed hash.

Used by: CO_PUEBLO_INDIGENA

CONFIGURATION

lookupFile	co-pueblos-indigenas-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_PUEBLO_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 20 values in co-pueblos-indigenas.txt , chosen by a keyed hash.

Used by: CO_PUEBLO_INDIGENA

CONFIGURATION

lookupFile	co-pueblos-indigenas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_RADICADO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CO_CM_ALFANUM .

Used by: CO_PENAL_RADICADO

PATTERNS, TRIED IN ORDER

(\d{5}[\s-]?[d{2}[\s-]?[d{2}[\s-]?[d{3}[\s-]?[d{4}[\s-]?)(\d{5})([\s-]?[d{2})	keep · CO_CM_DIGITOS · keep
otherwise	CO_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CO_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CO_L1_CREDENCIAL , CO_L3_BIOMETRICO , CO_L3_GENETICO

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_REGIMEN_SALUD SECURE LOOKUP

Replaces the value with one of the 5 values in co-regimenes-salud.txt , chosen by a keyed hash.

Used by: CO_AFILIACION_SALUD

CONFIGURATION

lookupFile	co-regimenes-salud.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_RELIGION_LISTA .

Used by: CO_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in co-religiones.txt , chosen by a keyed hash.

Used by: CO_RELIGION

CONFIGURATION

lookupFile	co-religiones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SALUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_SALUD_LABORAL_LISTA .

Used by: CO_SALUD_OCUPACIONAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_SALUD_LABORAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_SALUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in co-aptitud-laboral.txt , chosen by a keyed hash.

Used by: CO_SALUD_LABORAL

CONFIGURATION

lookupFile	co-aptitud-laboral.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEXO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CO_L2_SEXO

PATTERNS, TRIED IN ORDER

(?i)(femenino masculino)	CO_SEXO_FEMENINO_MASCULINO
(?i)(mujer hombre)	CO_SEXO_MUJER_HOMBRE
(?i)(female male)	CO_SEXO_FEMALE_MALE
(?i)([fm])	CO_SEXO_F_M
(?i)([hm])	CO_SEXO_H_M
([12])	CO_SEXO_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

CO_SEX0_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-1-2.txt` , chosen by a keyed hash.

Used by: `CO_SEX0`

CONFIGURATION

lookupFile	<code>co-sexo-1-2.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEX0_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-f-m.txt` , chosen by a keyed hash.

Used by: `CO_SEX0`

CONFIGURATION

lookupFile	<code>co-sexo-f-m.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEX0_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-female-male.txt` , chosen by a keyed hash.

Used by: `CO_SEX0`

CONFIGURATION

lookupFile	<code>co-sexo-female-male.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SEX0_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-femenino-masculino.txt` , chosen by a keyed hash.

Used by: `CO_SEX0`

CONFIGURATION

lookupFile	<code>co-sexo-femenino-masculino.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

CO_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-h-m.txt` , chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	<code>co-sexo-h-m.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

CO_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `co-sexo-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `CO_SEXO`

CONFIGURATION

lookupFile	<code>co-sexo-mujer-hombre.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

CO_SISBEN REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `CO_SISBEN_GRUPO` .

Used by: `CO_FIN_SISBEN`

PATTERNS, TRIED IN ORDER

<code>(?i)(A\s?)([1-5])</code>	<code>keep · CO_SISBEN_A</code>
<code>(?i)(B\s?)([1-7])</code>	<code>keep · CO_SISBEN_B</code>
<code>(?i)(C\s?)([0-8] [1-9])</code>	<code>keep · CO_SISBEN_C</code>
<code>(?i)(D\s?)(2[01] 1\d [1-9])</code>	<code>keep · CO_SISBEN_D</code>
<code>(\d{1,3})([.,]\d+)?</code>	<code>CO_CM_DIGITOS · keep</code>
<code>otherwise</code>	<code>CO_SISBEN_GRUPO</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

CO_SISBEN_A SECURE LOOKUP

Replaces the value with one of the 5 values in `co-sisben-a.txt` , chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	<code>co-sisben-a.txt</code>
hashMethod	<code>SHA256</code>

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_B SECURE LOOKUP

Replaces the value with one of the 7 values in `co-sisben-b.txt` , chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	co-sisben-b.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_C SECURE LOOKUP

Replaces the value with one of the 18 values in `co-sisben-c.txt` , chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	co-sisben-c.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_D SECURE LOOKUP

Replaces the value with one of the 21 values in `co-sisben-d.txt` , chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	co-sisben-d.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SISBEN_GRUPO SECURE LOOKUP

Replaces the value with one of the 4 values in `co-sisben-grupos.txt` , chosen by a keyed hash.

Used by: `CO_SISBEN`

CONFIGURATION

lookupFile	co-sisben-grupos.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in co-sin-informacion.txt , chosen by a keyed hash.

Used by: CO_CATEGORIA_SUPRIMIDA

CONFIGURATION

lookupFile	co-sin-informacion.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CO_L1_TARJETA

PATTERNS, TRIED IN ORDER

(\d[\d\s\~]{11,22}\d)	CO_TARJETA_LUHN
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CO_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: CO_TARJETA

CONFIGURATION

minMaskedPositions	6
preserve	0

CO_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CO_CM_DIGITOS .

Used by: CO_L1_TELEFONO , CO_LLAVE_BREB

PATTERNS, TRIED IN ORDER

(\+?57[\s\~]?)?(\(?3\d{2}\))? ([\s\~]?) (\d{3}) ([\s\~]?) (\d{4})	keep · keep · keep · CO_CM_DIGITOS · keep · CO_CM_DIGITOS
(\+?57[\s\~]?)?(\(?60[1-8]\))? ([\s\~]?) (\d{3}) ([\s\~]?) (\d{4})	keep · keep · keep · CO_CM_DIGITOS · keep · CO_CM_DIGITOS
([2-8]\d{2}) ([\s\~]?) (\d{4})	CO_CM_DIGITOS · keep · CO_CM_DIGITOS
otherwise	CO_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

CO_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CO_TENENCIA_VIVIENDA_LISTA .

Used by: CO_FIN_VIVIENDA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_TENENCIA_VIVIENDA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in co-tenencia-vivienda.txt , chosen by a keyed hash.

Used by: CO_TENENCIA_VIVIENDA

CONFIGURATION

lookupFile	co-tenencia-vivienda.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with [DATO] , and the 1,188 terms of co-texto-nombres.txt with [NOMBRE] .

Used by: CO_L1_TEXTO_LIBRE , CO_SALUD_TEXTO_CLINICO

PATTERNS, TRIED IN ORDER

(?<![\d.])\d{1,3}(\.\d{3}){1,3}(-\d)?(?![\d.])
(?<!\d)\d{6,10}-\d(?:\d)
(?<!\d)\d{6,11}(?:\d)
[\w.+\\-]+@[\\w\\-]+(\\. [\\w\\-]+)+
(?<![\\d\\-])(\\+?57)?3\\d{2}[\\-]?\\d{3}[\\-]?\\d{4}(?![\\d\\-])
(?<!\d)\d{13,19}(?:\d)
(?<![A-Za-z])([A-Z]{3}-?\\d{2}[A-Z\\d])(?![A-Za-z\\d])
(?<!\d)(\\d{1,3}\\.){3}\\d{1,3}(?:\d)

CONFIGURATION

regExRedactValue	[DATO]
lookupFile	co-texto-nombres.txt
lookupFileRedactValue	[NOMBRE]

isDenyList	yes
------------	-----

CO_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 100,000 and 1,000,000,000.

Used by: CO_FIN_DEUDA

CONFIGURATION

minValue	100000
maxValue	1000000000

CO_VALOR_PENSION NUMERIC MAPPING

Maps the number to another between 1,750,905 and 30,000,000.

Used by: CO_FIN_PENSION

CONFIGURATION

minValue	1750905
maxValue	30000000

CO_VICTIMA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CO_VICTIMA_LISTA .

Used by: CO_L3_VICTIMA_CONFLICTO

PATTERNS, TRIED IN ORDER

(?i)(s[ii] no true false yes [snx01])	CO_BANDERA
(\d{1,6})	CO_CM_ALFANUM
otherwise	CO_VICTIMA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CO_VICTIMA_LISTA SECURE LOOKUP

Replaces the value with one of the 15 values in co-hechos-victimizantes.txt , chosen by a keyed hash.

Used by: CO_VICTIMA

CONFIGURATION

lookupFile	co-hechos-victimizantes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CO_ZONA_RURAL SECURE LOOKUP

Replaces the value with one of the 1 values in co-zona-rural.txt , chosen by a keyed hash.

Used by: CO_L2_VEREDA

CONFIGURATION

lookupFile	co-zona-rural.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
co- antecedentes.txt	8	CO_ANTECEDENTES_LISTA	No tiene asuntos pendientes con las autoridades judiciales · Registra antecedentes · Imputado · Acusado
co- apellidos.txt	255	CO_APELLIDO	Rodríguez · Gómez · González · Martínez
co-aptitud- laboral.txt	4	CO_SALUD_LABORAL_LISTA	Apto · Apto con restricciones · No apto · Aplazado
co-bandera-0- 1.txt	2	CO_BANDERA_0_1	0 · 1
co-bandera-s- n.txt	2	CO_BANDERA_S_N	S · N
co-bandera-si- no.txt	2	CO_BANDERA_SI_NO	Sí · No
co-bandera- true-false.txt	2	CO_BANDERA_TRUE_FALSE	true · false
co-bandera-y- n.txt	2	CO_BANDERA_Y_N	Y · N
co-bandera- yes-no.txt	2	CO_BANDERA_YES_NO	Yes · No
co-barrios.txt	35	CO_BARRIO	Centro · La Esperanza · San José · El Prado
co-cie10- decimal.txt	33	CO_CIE10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
co-cie10.txt	37	CO_CIE10	I10 · E11 · E78 · J45
co-codigos- municipio- generalizados.t xt	694	CO_CODIGO_MUNICIPIO	05004,05284 · 05021,05670 · 05036,05030 · 05038,05887
co-cups.txt	10	CO_CUPS	890201 · 890301 · 890701 · 902210
co-detectar- afiliacion- salud.txt	41	CO_SALUD_AFILIACION – List	Contributivo · Subsidiado · Especial · De excepción
co-detectar- apellidos.txt	328	CO_L1_APELLIDO – List CO_L1_NOMBRE_COMPLETO – List	Rodríguez · Rodriguez · Gómez · Gomez
co-detectar- aptitud- laboral.txt	5	CO_SALUD_OCUPACIONAL – List	apto · no apto · apto con restricciones · aplazado
co-detectar- codigos- banderas.txt	11	CO_L3_GRUPO_ETNICO – List CO_L3_VICTIMA_CONFLICTO – List CO_FIN_PROGRAMA_SOCIAL – List	s · n · sí · si

FILE	LINES	USED BY	FIRST LINES
co-detectar-discapacidades.txt	29	CO_SALUD_DISCAPACIDAD – List	Física · Física · Auditiva · Visual
co-detectar-escolaridad.txt	33	CO_L2_ESCOLARIDAD – List	Ninguno · Preescolar · Básica primaria · Basica primaria
co-detectar-estado-civil.txt	21	CO_L2_ESTADO_CIVIL – List	Soltero(a) · Casado(a) · Unión marital de hecho · Union marital de hecho
co-detectar-estratos.txt	12	CO_FIN ESTRATO – List	1 · 2 · 3 · 4
co-detectar-grupos-etnicos.txt	24	CO_L3_GRUPO_ETNICO – List	Indígena · Indígena · Gitano(a) o Rrom · Raizal del Archipiélago de San Andrés, Providencia y Santa Catalina
co-detectar-grupos-sanguineos.txt	18	CO_SALUD_GRUPO_SANGUINEO – List	A+ · A- · B+ · B-
co-detectar-hechos-victimizantes.txt	30	CO_L3_VICTIMA_CONFLICTO – List	Desplazamiento forzado · Homicidio · Amenaza · Desaparición forzada
co-detectar-identidades-genero.txt	21	CO_L3_IDENTIDAD_GENERO – List	Mujer cisgénero · Mujer cisgenero · Hombre cisgénero · Hombre cisgenero
co-detectar-lenguas.txt	39	CO_L3 LENGUA NATIVA – List	Español · Espanol · Wayuunaiki · Nasa Yuwe
co-detectar-medicamentos.txt	53	CO_SALUD_MEDICAMENTO – List	Acetaminofén · Acetaminofen · Ibuprofeno · Naproxeno
co-detectar-municipios.txt	1,369	CO_L2_MUNICIPIO – List	Medellín · Medellin · Abejorral · Abriaquí
co-detectar-nacionalidades.txt	52	CO_L2_NACIONALIDAD – List	Colombiana · Venezolana · Ecuatoriana · Peruana
co-detectar-nombres.txt	280	CO_L1_NOMBRE – List CO_L1_NOMBRE_COMPLETO – List	María · Maria · José · Jose
co-detectar-orientaciones-politicas.txt	19	CO_L3_ORIENTACION_POLITICA – List	Izquierda · Centroizquierda · Centro · Centroderecha
co-detectar-orientaciones-sexuales.txt	13	CO_L3_ORIENTACION_SEXUAL – List	Heterosexual · Gay · Lesbiana · Bisexual
co-detectar-partidos.txt	68	CO_L3_AFILIACION_PARTIDO – List	Partido Liberal Colombiano · Partido Conservador Colombiano · Partido Cambio Radical · Partido Alianza Verde
co-detectar-programas-sociales.txt	20	CO_FIN_PROGRAMA_SOCIAL – List	Renta Ciudadana · Renta Joven · Colombia Mayor · Devolución del IVA

FILE	LINES	USED BY	FIRST LINES
co-detectar-pueblos-indigenas.txt	137	CO_L3_PUEBLO_INDIGENA - List	Achagua · Amorúa · Amorua · Andoke
co-detectar-religiones.txt	41	CO_L3_RELIGION - List	Católica · Catolica · Cristiana evangélica · Cristiana evangelica
co-detectar-sexo.txt	9	CO_L2_SEX0 - List	f · m · h · femenino
co-detectar-sindicatos.txt	23	CO_L3_SINDICATO - List	CUT · CGT · CTC · FECODE
co-detectar-tenencia-vivienda.txt	19	CO_FIN_VIVIENDA - List	Propia, totalmente pagada · Propia, la están pagando · Propia, la estan pagando · En arriendo o subarriendo
co-diagnosticos.txt	30	CO_DIAGNOSTICO_TEXTO	Hipertensión esencial · Diabetes mellitus tipo 2 · Asma · Lumbago
co-direcciones.txt	4,000	CO_DIRECCION	Calle 27 # 53-56 · Avenida Calle 40 # 38A-81 Torre 8 Apto 2406 · Carrera 76 Bis # 3-56 Torre 6 Apto 605 · Calle 49 # 53-57
co-discapacidades.txt	8	CO_DISCAPACIDAD_LISTA	Física · Auditiva · Visual · Sordoceguera
co-empleadores.txt	24	CO_EMPLEADOR	Comercializadora El Progreso S.A.S. · Construcciones Andinas S.A.S. · Transportes La Sabana S.A.S. · Supermercados La Económica S.A.S.
co-eps.txt	18	CO_EPS	Nueva EPS · EPS Sura · EPS Sanitas · Salud Total EPS
co-escolaridad-codigos.txt	11	CO_ESCOLARIDAD_CODIGO	1 · 2 · 3 · 4
co-escolaridad.txt	11	CO_ESCOLARIDAD_LISTA	Ninguno · Preescolar · Básica primaria · Básica secundaria
co-estado-civil-codigos.txt	6	CO_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
co-estado-civil.txt	6	CO_ESTADO_CIVIL_LISTA	Soltero(a) · Casado(a) · Unión marital de hecho · Separado(a)
co-estados-credito.txt	10	CO_ESTADO_CREDITO	Al día · Mora de 30 días · Mora de 60 días · Mora de 90 días
co-estrato-alto.txt	2	CO ESTRATO_ALTO	5 · 6
co-estrato-bajo.txt	2	CO ESTRATO_BAJ0	1 · 2
co-estrato-medio.txt	2	CO ESTRATO_MEDIO	3 · 4
co-grupos-etnicos-codigos.txt	6	CO_GRUPO_ETNICO_CODIGO	1 · 2 · 3 · 4

FILE	LINES	USED BY	FIRST LINES
co-grupos-etnicos.txt	6	CO_GRUPO_ETNICO_LISTA	Indígena · Gitano(a) o Rrom · Raizal del Archipiélago de San Andrés, Providencia y Santa Catalina · Palenquero(a) de San Basilio
co-grupos-sanguineos.txt	8	CO_GRUPO_SANGUINEO	A+ · A- · B+ · B-
co-hechos-victimizantes.txt	15	CO_VICTIMA_LISTA	Desplazamiento forzado · Homicidio · Amenaza · Desaparición forzada
co-identidades-genero.txt	7	CO_IDENTIDAD_GENERO_LISTA	Mujer cisgénero · Hombre cisgénero · Mujer trans · Hombre trans
co-instituciones-educativas.txt	12	CO_INSTITUCION_EDUCATIVA	Institución Educativa San José · Colegio Nuestra Señora del Rosario · Institución Educativa Técnica Agropecuaria · Colegio Departamental La Esperanza
co-lenguas.txt	12	CO LENGUA_LISTA	Español · Wayuunaiki · Nasa Yuwe · Emberá
co-medicamentos.txt	24	CO_MEDICAMENTO_LISTA	Acetaminofén · Ibuprofeno · Naproxeno · Diclofenaco
co-municipios-generalizados.txt	12,622	CO_MUNICIPIO	Abriaquí Frontino · ABRIAQUÍ FRONTINO · Abriaquí Frontino · ABRIAQUÍ FRONTINO
co-nacionalidades.txt	16	CO_NACIONALIDAD	Colombiana · Venezolana · Ecuatoriana · Peruana
co-nombres.txt	232	CO_NOMBRE	María · José · Luis · Carlos
co-ocupaciones.txt	39	CO_OCUPACION	Auxiliar administrativo · Asistente administrativo · Vendedor · Cajero
co-orientaciones-politicas.txt	7	CO_ORIENTACION_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
co-orientaciones-sexuales.txt	8	CO_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
co-partidos.txt	29	CO_PARTIDO_LISTA	Partido Liberal Colombiano · Partido Conservador Colombiano · Partido Cambio Radical · Partido Alianza Verde
co-procedimientos.txt	10	CO_PROCEDIMIENTO_TEXTO	Consulta de primera vez por medicina general · Consulta de control o de seguimiento por medicina general · Consulta de urgencias por medicina general · Hemograma
co-programas-sociales.txt	8	CO_PROGRAMA_SOCIAL_LISTA	Renta Ciudadana · Renta Joven · Colombia Mayor · Devolución del IVA
co-pueblos-indigenas-codigos.txt	10	CO_PUEBLO_INDIGENA_CODIGO	720 · 800 · 500 · 560
co-pueblos-indigenas.txt	20	CO_PUEBLO_INDIGENA_LISTA	Wayuu · Zenú · Nasa · Pastos
co-regimenes-salud.txt	5	CO_REGIMEN_SALUD	Contributivo · Subsidiado · Especial · De excepción

FILE	LINES	USED BY	FIRST LINES
co-religiones.txt	12	CO_RELIGION_LISTA	Católica · Cristiana evangélica · Pentecostal · Adventista del Séptimo Día
co-sexo-1-2.txt	2	CO_SEXO_1_2	1 · 2
co-sexo-f-m.txt	2	CO_SEXO_F_M	F · M
co-sexo-female-male.txt	2	CO_SEXO_FEMALE_MALE	Female · Male
co-sexo-femenino-masculino.txt	2	CO_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
co-sexo-h-m.txt	2	CO_SEXO_H_M	H · M
co-sexo-mujer-hombre.txt	2	CO_SEXO_MUJER_HOMBRE	Mujer · Hombre
co-sin-informacion.txt	1	CO_SUPRIMIR	Sin información
co-sisben-a.txt	5	CO_SISBEN_A	1 · 2 · 3 · 4
co-sisben-b.txt	7	CO_SISBEN_B	1 · 2 · 3 · 4
co-sisben-c.txt	18	CO_SISBEN_C	1 · 2 · 3 · 4
co-sisben-d.txt	21	CO_SISBEN_D	1 · 2 · 3 · 4
co-sisben-grupos.txt	4	CO_SISBEN_GRUPO	Pobreza extrema · Pobreza moderada · Vulnerable · No pobre, no vulnerable
co-tenencia-vivienda.txt	7	CO_TENENCIA_VIVIENDA_LISTA	Propia, totalmente pagada · Propia, la están pagando · En arriendo o subarriendo · En usufructo
co-texto-nombres.txt	1,188	CO_TEXTO_LIBRE	María · MARÍA · Maria · MARIA
co-zona-rural.txt	1	CO_ZONA_RURAL	Zona rural

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 producto prod item articulo empresa emp razon social comercial archivo calle via barrio municipio
 mpio ciudad departamento depto dpto pais banco sucursal plan campana proyecto servicio tabla
 columna campo usuario host servidor dominio marca modelo categoria tipo colegio escuela institucion
 curso materia documento doc centro unidad clinica hospital ips eps area dependencia cargo sistema
 app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta
 medicamento diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua
 lugar sede tienda almacen bodega proveedor convenio contrato poliza seguro aseguradora entidad
 organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo
 plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda
 emisor factura pago forma zona ruta linea actividad sector vereda corregimiento localidad comuna
 file table column field user server product company category type school document department
 system group report role account place store supplier contract device image page module action key
 label code project city country street bank cliente cli paciente pac usuario afiliado asegurado
 beneficiario benef titular empleado funcionario trabajador contratista estudiante alumno deudor
 codeudor fiador avalista tomador propietario arrendatario arrendador conductor acudiente responsable
 representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto
 referencia victima denunciante sindicato imputado procesado testigo medico docente socio accionista
 heredero causante donante tutor curador cotizante customer patient employee member holder mother
 father spouse contact person student driver owner completo apellidos? usuario corto largo

E2 producto prod item articulo empresa emp razon social comercial archivo calle via barrio municipio
 mpio ciudad departamento depto dpto pais banco sucursal plan campana proyecto servicio tabla
 columna campo usuario host servidor dominio marca modelo categoria tipo colegio escuela institucion
 curso materia documento doc centro unidad clinica hospital ips eps area dependencia cargo sistema
 app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta
 medicamento diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua
 lugar sede tienda almacen bodega proveedor convenio contrato poliza seguro aseguradora entidad
 organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo
 plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda
 emisor factura pago forma zona ruta linea actividad sector vereda corregimiento localidad comuna
 file table column field user server product company category type school document department
 system group report role account place store supplier contract device image page module action key
 label code project city country street bank cliente cli paciente pac usuario afiliado asegurado
 beneficiario benef titular empleado funcionario trabajador contratista estudiante alumno deudor
 codeudor fiador avalista tomador propietario arrendatario arrendador conductor acudiente responsable
 representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto
 referencia victima denunciante sindicato imputado procesado testigo medico docente socio accionista
 heredero causante donante tutor curador cotizante customer patient employee member holder mother
 father spouse contact person student driver owner

E3 producto prod item articulo empresa emp razon social comercial archivo calle via barrio municipio
mpio ciudad departamento depto dpto pais banco sucursal plan campana proyecto servicio tabla
columna campo usuario host servidor dominio marca modelo categoria tipo colegio escuela institucion
curso materia documento doc centro unidad clinica hospital ips eps area dependencia cargo sistema
app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta
medicamento diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua
lugar sede tienda almacen bodega proveedor convenio contrato poliza seguro aseguradora entidad
organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo
plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda
emisor factura pago forma zona ruta linea actividad sector vereda corregimiento localidad comuna
file table column field user server product company category type school document department
system group report role account place store supplier contract device image page module action key
label code project city country street bank cliente cli paciente pac usuario afiliado asegurado
beneficiario benef titular empleado funcionario trabajador contratista estudiante alumno deudor
codeudor fiador avalista tomador propietario arrendatario arrendador conductor acudiente responsable
representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto
referencia victima denunciante sindicato imputado procesado testigo medico docente socio accionista
heredero causante donante tutor curador cotizante customer patient employee member holder mother
father spouse contact person student driver owner full complete last first

E4 ip mac email e_?mail correo electr[ó]nica web url tipo id general t[e]cnica seccional regional

E5 ip mac email e_?mail web url type id

E6 id cd cod codigo tipo fecha estado num nro

E7 id tipo codigo fecha estado cola log

APPENDIX D

Profile set and classifiers

The profile set `CO - Ley 1581 de 2012 - v1` runs these 143 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, datos sensibles (art. 5), víctimas del conflicto armado, datos de salud, datos financieros (Ley 1266 de 2008) y antecedentes penales, conforme a la Ley Estatutaria 1581 de 2012 de protección de datos personales.

CLASSIFIER	KIND	DOMAIN
CO_L1_CEDULA - Path	COLUMN NAME	CO_L1_CEDULA
CO_L1_CEDULA - Type	DATA TYPE	CO_L1_CEDULA
CO_L1_CEDULA - Regex	VALUE FORMAT	CO_L1_CEDULA
CO_L1_NIT - Path	COLUMN NAME	CO_L1_NIT
CO_L1_NIT - Regex	VALUE FORMAT	CO_L1_NIT
CO_L1_DOCUMENTO_EXTRANJERO - Path	COLUMN NAME	CO_L1_DOCUMENTO_EXTRANJERO
CO_L1_PASAPORTE - Path	COLUMN NAME	CO_L1_PASAPORTE
CO_L1_PASAPORTE - Regex	VALUE FORMAT	CO_L1_PASAPORTE
CO_L1_REGISTRO_CIVIL - Path	COLUMN NAME	CO_L1_REGISTRO_CIVIL
CO_L1_TARJETA_PROFESIONAL - Path	COLUMN NAME	CO_L1_TARJETA_PROFESIONAL
CO_L1_NOMBRE - Path	COLUMN NAME	CO_L1_NOMBRE
CO_L1_NOMBRE - List	KNOWN VALUES	CO_L1_NOMBRE
CO_L1_APELLIDO - Path	COLUMN NAME	CO_L1_APELLIDO
CO_L1_APELLIDO - List	KNOWN VALUES	CO_L1_APELLIDO
CO_L1_NOMBRE_COMPLETO - Path	COLUMN NAME	CO_L1_NOMBRE_COMPLETO
CO_L1_NOMBRE_COMPLETO - List	KNOWN VALUES	CO_L1_NOMBRE_COMPLETO
CO_L1_EMAIL - Path	COLUMN NAME	CO_L1_EMAIL
CO_L1_EMAIL - Type	DATA TYPE	CO_L1_EMAIL
CO_L1_EMAIL - Regex	VALUE FORMAT	CO_L1_EMAIL
CO_L1_TELEFONO - Path	COLUMN NAME	CO_L1_TELEFONO
CO_L1_TELEFONO - Regex	VALUE FORMAT	CO_L1_TELEFONO
CO_L1_DIRECCION - Path	COLUMN NAME	CO_L1_DIRECCION
CO_L1_DIRECCION - Type	DATA TYPE	CO_L1_DIRECCION
CO_L1_DIRECCION - Regex	VALUE FORMAT	CO_L1_DIRECCION
CO_L1_DIRECCION_COMPLEMENTO - Path	COLUMN NAME	CO_L1_DIRECCION_COMPLEMENTO
CO_L1_CUENTA_BANCARIA - Path	COLUMN NAME	CO_L1_CUENTA_BANCARIA
CO_L1_TARJETA - Path	COLUMN NAME	CO_L1_TARJETA
CO_L1_TARJETA - Regex	VALUE FORMAT	CO_L1_TARJETA
CO_L1_LLAVE_BREB - Path	COLUMN NAME	CO_L1_LLAVE_BREB

CLASSIFIER	KIND	DOMAIN
CO_L1_LLAVE_BREB – Regex	VALUE FORMAT	CO_L1_LLAVE_BREB
CO_L1_IP – Path	COLUMN NAME	CO_L1_IP
CO_L1_IP – Regex	VALUE FORMAT	CO_L1_IP
CO_L1_DISPOSITIVO – Path	COLUMN NAME	CO_L1_DISPOSITIVO
CO_L1_DISPOSITIVO – Regex	VALUE FORMAT	CO_L1_DISPOSITIVO
CO_L1_PLACA – Path	COLUMN NAME	CO_L1_PLACA
CO_L1_PLACA – Regex	VALUE FORMAT	CO_L1_PLACA
CO_L1_VEHICULO – Path	COLUMN NAME	CO_L1_VEHICULO
CO_L1_VEHICULO – Regex	VALUE FORMAT	CO_L1_VEHICULO
CO_L1_INMUEBLE – Path	COLUMN NAME	CO_L1_INMUEBLE
CO_L1_INMUEBLE – Regex	VALUE FORMAT	CO_L1_INMUEBLE
CO_L1_CONTRATO – Path	COLUMN NAME	CO_L1_CONTRATO
CO_L1_USUARIO – Path	COLUMN NAME	CO_L1_USUARIO
CO_L1_CREDENCIAL – Path	COLUMN NAME	CO_L1_CREDENCIAL
CO_L1_GEOLOCALIZACION – Path	COLUMN NAME	CO_L1_GEOLOCALIZACION
CO_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	CO_L1_GEOLOCALIZACION
CO_L1_TEXTO_LIBRE – Path	COLUMN NAME	CO_L1_TEXTO_LIBRE
CO_L1_TEXTO_LIBRE – Type	DATA TYPE	CO_L1_TEXTO_LIBRE
CO_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	CO_L1_TEXTO_LIBRE
CO_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	CO_L2_FECHA_NACIMIENTO
CO_L2_FECHA_NACIMIENTO – Type	DATA TYPE	CO_L2_FECHA_NACIMIENTO
CO_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	CO_L2_ANIO_NACIMIENTO
CO_L2_ANIO_NACIMIENTO – Type	DATA TYPE	CO_L2_ANIO_NACIMIENTO
CO_L2_EDAD – Path	COLUMN NAME	CO_L2_EDAD
CO_L2_EDAD – Type	DATA TYPE	CO_L2_EDAD
CO_L2_FECHA_EVENTO – Path	COLUMN NAME	CO_L2_FECHA_EVENTO
CO_L2_FECHA_EVENTO – Type	DATA TYPE	CO_L2_FECHA_EVENTO
CO_L2_SEX0 – Path	COLUMN NAME	CO_L2_SEX0
CO_L2_SEX0 – List	KNOWN VALUES	CO_L2_SEX0
CO_L2_MUNICIPIO – Path	COLUMN NAME	CO_L2_MUNICIPIO
CO_L2_MUNICIPIO – List	KNOWN VALUES	CO_L2_MUNICIPIO
CO_L2_CODIGO_MUNICIPIO – Path	COLUMN NAME	CO_L2_CODIGO_MUNICIPIO
CO_L2_CODIGO_MUNICIPIO – Regex	VALUE FORMAT	CO_L2_CODIGO_MUNICIPIO
CO_L2_CODIGO_POSTAL – Path	COLUMN NAME	CO_L2_CODIGO_POSTAL
CO_L2_CODIGO_POSTAL – Type	DATA TYPE	CO_L2_CODIGO_POSTAL
CO_L2_BARRIO – Path	COLUMN NAME	CO_L2_BARRIO
CO_L2_VEREDA – Path	COLUMN NAME	CO_L2_VEREDA

CLASSIFIER	KIND	DOMAIN
CO_L2_NACIONALIDAD – Path	COLUMN NAME	CO_L2_NACIONALIDAD
CO_L2_NACIONALIDAD – List	KNOWN VALUES	CO_L2_NACIONALIDAD
CO_L2_ESTADO_CIVIL – Path	COLUMN NAME	CO_L2_ESTADO_CIVIL
CO_L2_ESTADO_CIVIL – List	KNOWN VALUES	CO_L2_ESTADO_CIVIL
CO_L2_OCUPACION – Path	COLUMN NAME	CO_L2_OCUPACION
CO_L2_EMPLEADOR – Path	COLUMN NAME	CO_L2_EMPLEADOR
CO_L2_ESCOLARIDAD – Path	COLUMN NAME	CO_L2_ESCOLARIDAD
CO_L2_ESCOLARIDAD – List	KNOWN VALUES	CO_L2_ESCOLARIDAD
CO_L2_INSTITUCION_EDUCATIVA – Path	COLUMN NAME	CO_L2_INSTITUCION_EDUCATIVA
CO_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	CO_L2_PERSONAS_A_CARGO
CO_L2_PERSONAS_A_CARGO – Type	DATA TYPE	CO_L2_PERSONAS_A_CARGO
CO_L3_GRUPO_ETNICO – Path	COLUMN NAME	CO_L3_GRUPO_ETNICO
CO_L3_GRUPO_ETNICO – List	KNOWN VALUES	CO_L3_GRUPO_ETNICO
CO_L3_PUEBLO_INDIGENA – Path	COLUMN NAME	CO_L3_PUEBLO_INDIGENA
CO_L3_PUEBLO_INDIGENA – List	KNOWN VALUES	CO_L3_PUEBLO_INDIGENA
CO_L3_LENGUA_NATIVA – Path	COLUMN NAME	CO_L3_LENGUA_NATIVA
CO_L3_LENGUA_NATIVA – List	KNOWN VALUES	CO_L3_LENGUA_NATIVA
CO_L3_RELIGION – Path	COLUMN NAME	CO_L3_RELIGION
CO_L3_RELIGION – List	KNOWN VALUES	CO_L3_RELIGION
CO_L3_CONVICCION_FILOSOFICA – Path	COLUMN NAME	CO_L3_CONVICCION_FILOSOFICA
CO_L3_ORIENTACION_POLITICA – Path	COLUMN NAME	CO_L3_ORIENTACION_POLITICA
CO_L3_ORIENTACION_POLITICA – List	KNOWN VALUES	CO_L3_ORIENTACION_POLITICA
CO_L3_AFILIACION_PARTIDO – Path	COLUMN NAME	CO_L3_AFILIACION_PARTIDO
CO_L3_AFILIACION_PARTIDO – List	KNOWN VALUES	CO_L3_AFILIACION_PARTIDO
CO_L3_SINDICATO – Path	COLUMN NAME	CO_L3_SINDICATO
CO_L3_SINDICATO – List	KNOWN VALUES	CO_L3_SINDICATO
CO_L3_ORGANIZACION_SOCIAL – Path	COLUMN NAME	CO_L3_ORGANIZACION_SOCIAL
CO_L3_BIOMETRICO – Path	COLUMN NAME	CO_L3_BIOMETRICO
CO_L3_BIOMETRICO – Type	DATA TYPE	CO_L3_BIOMETRICO
CO_L3_GENETICO – Path	COLUMN NAME	CO_L3_GENETICO
CO_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	CO_L3_ORIENTACION_SEXUAL
CO_L3_ORIENTACION_SEXUAL – List	KNOWN VALUES	CO_L3_ORIENTACION_SEXUAL
CO_L3_VIDA_SEXUAL – Path	COLUMN NAME	CO_L3_VIDA_SEXUAL
CO_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	CO_L3_IDENTIDAD_GENERO
CO_L3_IDENTIDAD_GENERO – List	KNOWN VALUES	CO_L3_IDENTIDAD_GENERO
CO_L3_VICTIMA_CONFLICTO – Path	COLUMN NAME	CO_L3_VICTIMA_CONFLICTO
CO_L3_VICTIMA_CONFLICTO – List	KNOWN VALUES	CO_L3_VICTIMA_CONFLICTO

CLASSIFIER	KIND	DOMAIN
CO_L3_REINCORPORACION – Path	COLUMN NAME	CO_L3_REINCORPORACION
CO_SALUD_IDENTIFICADOR – Path	COLUMN NAME	CO_SALUD_IDENTIFICADOR
CO_SALUD_AFILIACION – Path	COLUMN NAME	CO_SALUD_AFILIACION
CO_SALUD_AFILIACION – List	KNOWN VALUES	CO_SALUD_AFILIACION
CO_SALUD_DIAGNOSTICO – Path	COLUMN NAME	CO_SALUD_DIAGNOSTICO
CO_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	CO_SALUD_DIAGNOSTICO
CO_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	CO_SALUD_PROCEDIMIENTO
CO_SALUD_MEDICAMENTO – Path	COLUMN NAME	CO_SALUD_MEDICAMENTO
CO_SALUD_MEDICAMENTO – List	KNOWN VALUES	CO_SALUD_MEDICAMENTO
CO_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	CO_SALUD_TEXTO_CLINICO
CO_SALUD_TEXTO_CLINICO – Type	DATA TYPE	CO_SALUD_TEXTO_CLINICO
CO_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	CO_SALUD_RESULTADO_EXAMEN
CO_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	CO_SALUD_GRUPO_SANGUINEO
CO_SALUD_GRUPO_SANGUINEO – List	KNOWN VALUES	CO_SALUD_GRUPO_SANGUINEO
CO_SALUD_DISCAPACIDAD – Path	COLUMN NAME	CO_SALUD_DISCAPACIDAD
CO_SALUD_DISCAPACIDAD – List	KNOWN VALUES	CO_SALUD_DISCAPACIDAD
CO_SALUD_OCUPACIONAL – Path	COLUMN NAME	CO_SALUD_OCUPACIONAL
CO_SALUD_OCUPACIONAL – List	KNOWN VALUES	CO_SALUD_OCUPACIONAL
CO_SALUD_REPRODUCTIVA – Path	COLUMN NAME	CO_SALUD_REPRODUCTIVA
CO_SALUD_MENTAL – Path	COLUMN NAME	CO_SALUD_MENTAL
CO_FIN_CREDITO – Path	COLUMN NAME	CO_FIN_CREDITO
CO_FIN_DEUDA – Path	COLUMN NAME	CO_FIN_DEUDA
CO_FIN_DEUDA – Type	DATA TYPE	CO_FIN_DEUDA
CO_FIN_INGRESOS – Path	COLUMN NAME	CO_FIN_INGRESOS
CO_FIN_INGRESOS – Type	DATA TYPE	CO_FIN_INGRESOS
CO_FIN_PATRIMONIO – Path	COLUMN NAME	CO_FIN_PATRIMONIO
CO_FIN_PATRIMONIO – Type	DATA TYPE	CO_FIN_PATRIMONIO
CO_FIN_PENSION – Path	COLUMN NAME	CO_FIN_PENSION
CO_FIN_PENSION – Type	DATA TYPE	CO_FIN_PENSION
CO_FIN_ESTRATO – Path	COLUMN NAME	CO_FIN_ESTRATO
CO_FIN_ESTRATO – List	KNOWN VALUES	CO_FIN_ESTRATO
CO_FIN_SISBEN – Path	COLUMN NAME	CO_FIN_SISBEN
CO_FIN_SISBEN – Regex	VALUE FORMAT	CO_FIN_SISBEN
CO_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	CO_FIN_PROGRAMA_SOCIAL
CO_FIN_PROGRAMA_SOCIAL – List	KNOWN VALUES	CO_FIN_PROGRAMA_SOCIAL
CO_FIN_VIVIENDA – Path	COLUMN NAME	CO_FIN_VIVIENDA
CO_FIN_VIVIENDA – List	KNOWN VALUES	CO_FIN_VIVIENDA

CLASSIFIER	KIND	DOMAIN
CO_PENAL_ANTECEDENTES – Path	COLUMN NAME	CO_PENAL_ANTECEDENTES
CO_PENAL_RADICADO – Path	COLUMN NAME	CO_PENAL_RADICADO
CO_PENAL_RADICADO – Regex	VALUE FORMAT	CO_PENAL_RADICADO