

Costa Rica — Ley 8968 de Protección de la Persona frente al Tratamiento de sus Datos Personales

Discovery and masking of Costa Rican personal data: cédula de identidad, DIMEX and NITE, the IBAN with valid check digits, the address written as directions from a landmark, quasi-identifiers, the sensitive data article 9.1 forbids a private party to process, health data, the condición socioeconómica article 3 e) calls sensitive, and criminal records.

81

DOMAINS

141

CLASSIFIERS

172

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	Ley 8968 in brief
3	Desasociación, pseudonymization and non-production copies
4	How sensitive data is discovered
5	How data is masked
6	Essential and extended packs
7	Domains at a glance

PART 8 · DIRECT IDENTIFIERS

8.1	Cédula de identidad	CR_L1_CEDULA
8.2	DIMEX	CR_L1_DIMEX
8.3	NITE	CR_L1_NITE
8.4	Passport	CR_L1_PASAPORTE
8.5	Social security number	CR_L1_SEGURO_SOCIAL
8.6	Student code	CR_L1_CODIGO_ESTUDIANTE
8.7	Professional registration	CR_L1_MATRICULA_PROFESIONAL
8.8	Given name	CR_L1_NOMBRE
8.9	Surname	CR_L1_APELLIDO
8.10	Full name	CR_L1_NOMBRE_COMPLETO
8.11	E-mail address	CR_L1_EMAIL
8.12	Telephone number	CR_L1_TELEFONO
8.13	Address and señas	CR_L1_DIRECCION
8.14	Address detail	CR_L1_DIRECCION_COMPLEMENTO
8.15	Bank account (IBAN)	CR_L1_CUENTA_BANCARIA
8.16	Payment card	CR_L1_TARJETA
8.17	Digital wallet	CR_L1_BILLETERA
8.18	IP address	CR_L1_IP
8.19	Device identifier	CR_L1_DISPOSITIVO
8.20	Cookie and tracking identifier	CR_L1_COOKIE
8.21	Vehicle plate	CR_L1_PLACA
8.22	Vehicle identifiers	CR_L1_VEHICULO
8.23	Property identifiers	CR_L1_INMUEBLE
8.24	Contract and case numbers	CR_L1_CONTRATO

8.25	Username and social handle	CR_L1_USUARIO
8.26	Credentials and secrets	CR_L1_CREDENCIAL
8.27	Photograph and recordings	CR_L1_IMAGEN
8.28	Geolocation	CR_L1_GEOLOCALIZACION
8.29	Free text	CR_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Date of birth	CR_L2_FECHA_NACIMIENTO
9.2	Year of birth	CR_L2_ANIO_NACIMIENTO
9.3	Age	CR_L2_EDAD
9.4	Other dates about the person	CR_L2_FECHA_EVENTO
9.5	Sex	CR_L2_SEXO
9.6	Distrito and cantón	CR_L2_DISTRITO
9.7	DTA code and postal code	CR_L2_CODIGO_DTA
9.8	Barrio	CR_L2_BARRIO
9.9	Marital status	CR_L2_ESTADO_CIVIL
9.10	Occupation	CR_L2_OCUPACION
9.11	Employer	CR_L2_EMPLEADOR
9.12	Level of education	CR_L2_NIVEL_EDUCATIVO
9.13	Educational institution	CR_L2_INSTITUCION_EDUCATIVA
9.14	Dependants	CR_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA (ART. 3 E AND ART. 9.1)

10.1	Racial or ethnic origin	CR_L3_ETNIA
10.2	Indigenous people and territory	CR_L3_PUEBLO_INDIGENA
10.3	Nationality	CR_L3_NACIONALIDAD
10.4	Migratory condition	CR_L3_CONDICION_MIGRATORIA
10.5	Religion	CR_L3_RELIGION
10.6	Philosophical convictions	CR_L3_CONVICCION_FILOSOFICA
10.7	Political opinion	CR_L3_OPINION_POLITICA
10.8	Party membership	CR_L3_AFILIACION_PARTIDARIA
10.9	Trade union membership	CR_L3_AFILIACION_SINDICAL
10.10	Biometric data	CR_L3_BIOMETRICO
10.11	Genetic data	CR_L3_GENETICO
10.12	Sexual orientation	CR_L3_ORIENTACION_SEXUAL
10.13	Sexual life	CR_L3_VIDA_SEXUAL
10.14	Gender identity	CR_L3_IDENTIDAD_GENERO
10.15	Victim of violence	CR_L3_VICTIMA

PART 11 · HEALTH DATA (ART. 9.1 D)

11.1	Clinical record number	CR_SALUD_IDENTIFICADOR
11.2	Health coverage	CR_SALUD_COBERTURA
11.3	Diagnosis	CR_SALUD_DIAGNOSTICO
11.4	Procedure	CR_SALUD_PROCEDIMIENTO
11.5	Medicine	CR_SALUD_MEDICAMENTO
11.6	Clinical notes	CR_SALUD_TEXTO_CLINICO
11.7	Test result	CR_SALUD_RESULTADO_EXAMEN
11.8	HIV and sexually transmitted infections	CR_SALUD_VIH
11.9	Blood group	CR_SALUD_GRUPO_SANGUINEO
11.10	Disability	CR_SALUD_DISCAPACIDAD
11.11	Occupational health	CR_SALUD_OCUPACIONAL
11.12	Reproductive health	CR_SALUD_REPRODUCTIVA
11.13	Mental health	CR_SALUD_MENTAL

PART 12 · ECONOMIC DATA (ART. 3 E, ART. 1 AND ART. 9.4)

12.1	Credit standing	CR_FIN_HISTORIAL_CREDITICIO
12.2	Debt	CR_FIN_DEUDA
12.3	Income	CR_FIN_INGRESOS
12.4	Assets	CR_FIN_PATRIMONIO
12.5	Pension	CR_FIN_PENSION
12.6	Social programme	CR_FIN_PROGRAMA_SOCIAL
12.7	Condición socioeconómica	CR_FIN_CONDICION_SOCIOECONOMICA
12.8	Housing tenure	CR_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS (ART. 8 C AND LEY 6723)

13.1	Criminal record	CR_PENAL_ANTECEDENTES
13.2	Judicial file number	CR_PENAL_EXPEDIENTE
14	The IBAN check digits	
15	Where people live: distritos, cantones and the code that is also the postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Profile set and classifiers	

About this profile set

This profile set finds the personal data in a Costa Rican database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and cédulas alone is not enough: a birth date, a sex and one small distrito already point at a handful of people, and most of the 492 distritos of Costa Rica are small. The set works in the layers where the risk is:

- **Direct identifiers** — cédula de identidad, DIMEX, NITE, passport, social-security and student numbers, professional registration, names, contact, address and señas, bank accounts, cards, devices, cookies, plates, property, photographs, free text.
- **Quasi-identifiers** — birth date, year of birth, age, sex, distrito and cantón, the code of the División Territorial Administrativa that doubles as the postal code, barrio, marital status, occupation, employer, education, dependants.
- **Sensitive data** — the categories of article 3 e) and article 9.1: racial or ethnic origin, political opinions, religious, spiritual or philosophical convictions, biomedical and genetic information, sexual life and orientation; and the attributes the anti-discrimination clause of article 4 reaches: indigenous people, nationality, migratory condition, gender identity, trade union membership.
- **Health data**, which article 9.1 lets only health care itself process, and only under professional secrecy.
- **Economic data** — income, debts, assets, credit standing and social programmes. Article 3 e) names the **condición socioeconómica** among the sensitive data, and article 1 extends the law to the data of a person's **bienes**.
- **Criminal records**, whose entries the Registro Judicial cancels on a scale of its own.

Each group below says what each domain is, how it is masked and why. The discovery is a profile set of 141 classifiers at a threshold of 60; the masking is 81 domains with their algorithms.

Ley 8968 in brief

Costa Rica has had a data protection law since 2011: the **Ley 8968 de Protección de la Persona frente al Tratamiento de sus Datos Personales**, in force since 5 September 2011 and **never amended**. Its regulation, Decreto Ejecutivo 37554-JP, was amended twice, by Decreto 40008-JP in 2016 and by Decreto 41582 in 2019, both on the registry of databases rather than on the principles. The authority is the **Agencia de Protección de Datos de los Habitantes (Prodhab)**, created by article 15.

Two features of the law shape this set. First, article 1 states its reach over the data of a person **o bienes** — the assets as well as the person — which puts property, income and patrimony squarely inside it. Second, only a **persona física** is a titular: article 3 b) defines a personal datum as any datum relating to an identified or identifiable natural person, and article 3 g) and article 2 v) of the regulation define the interesado the same way. A company is not a data subject in Costa Rica, so a cédula jurídica is left exactly as it is.

On sensitive data the law is unusually strict. Article 3 e) defines it as "información relativa al **fuero íntimo** de la persona, como por ejemplo los que revelen origen racial, opiniones políticas, convicciones religiosas o espirituales, **condición socioeconómica**, información **biomédica o genética**, vida y orientación sexual, **entre otros**" — an open list, and the only one in the region that names the socio-economic condition. Article 9.1 then **prohibits** processing it, with five narrow exceptions, and article 31 a) makes processing it a **falta**

gravísima for a private party: fifteen to thirty base salaries and the suspension of the fichero for up to six months.

Article 9.3 is worth reading beside it. It lists what is **not** a datum of unrestricted access even when it sits in a public register: "la dirección exacta de la residencia", "la fotografía", "los números de teléfono privados y otros de igual naturaleza cuyo tratamiento pueda afectar los derechos y los intereses de la persona titular". Three domains of this set exist because that paragraph names them.

3 Desasociación, pseudonymization and non-production copies

Costa Rica writes the technique into the law itself. Article 6.1 says that personal data which may affect its holder shall in no case be kept beyond ten years from the facts recorded, and that "en caso de que sea necesaria su conservación, más allá del plazo estipulado, deberán ser **desasociados de su titular**". Article 2 r) of the regulation defines the procedure: "acción y efecto de **disociar** los datos personales, de modo que la información que se obtenga no pueda asociarse o vincularse a persona determinada o determinable". No other law of the region orders the technique in the body of the statute.

Be precise about what masking achieves against that definition. The engine masks with a key, and whoever holds the key can reproduce the mapping: the result is a **pseudonymized** copy, not a dissociated one in the strict sense of article 2 r), and it is still personal data. What it is, squarely, is the "medida de índole técnica" article 10 requires and the "medida de seguridad lógica" articles 34 to 37 of the regulation ask the responsible to choose by risk — including the **riesgo residual** article 36 f) asks to be computed. To reach desasociación the key has to be discarded, and nothing in a masked copy should be read as anonymous while it exists.

Two more provisions make the risk-based reading explicit. Article 2 q) of the regulation says a natural person is identifiable when the identity can be determined "directa o **indirectamente**, mediante cualquier información referida a su identidad anatómica, fisiológica, psíquica, económica, cultural o social", and adds that "una persona física **no se considerará identificable** si dicha identificación requiere plazos o actividades desproporcionadas". Article 8 d) of the law limits its principles for databases used for statistical, historical or scientific purposes "cuando **no exista riesgo** de que las personas sean identificadas". Both put the question where this set answers it: how much work it would take to point at one person again.

4 How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	26	19	5
Extended	81	141	172	81

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- Cédula de identidad — `CR_L1_CEDULA`
- DIMEX — `CR_L1_DIMEX`
- NITE — `CR_L1_NITE`
- Passport — `CR_L1_PASAPORTE`
- Given name — `CR_L1_NOMBRE`
- Surname — `CR_L1_APELLIDO`
- Full name — `CR_L1_NOMBRE_COMPLETO`
- E-mail address — `CR_L1_EMAIL`
- Telephone number — `CR_L1_TELEFONO`

- Address and señas — CR_L1_DIRECCION
- Address detail — CR_L1_DIRECCION_COMPLEMENTO
- Date of birth — CR_L2_FECHA_NACIMIENTO

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM	
DIRECT IDENTIFIERS					
Cédula de identidad CR_L1_CEDULA	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	CR_DOCUMENTO
DIMEX CR_L1_DIMEX	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CR_DIMEX
NITE CR_L1_NITE	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CR_NITE
Passport CR_L1_PASAPORTE	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CR_CM_DIGITOS_LETRAS
Social security number CR_L1_SEGURO_SOCIAL		COLUMN NAME			CR_CM_ALFANUM
Student code CR_L1_CODIGO_ESTUDIANTE		COLUMN NAME			CR_CM_ALFANUM
Professional registration CR_L1_MATRICULA_PROFESIONAL		COLUMN NAME			CR_CM_ALFANUM
Given name CR_L1_NOMBRE	ESSENTIAL	COLUMN NAME	KNOWN VALUES		CR_NOMBRES
Surname CR_L1_APELLIDO	ESSENTIAL	COLUMN NAME	KNOWN VALUES		CR_APELLIDOS
Full name CR_L1_NOMBRE_COMPLETO	ESSENTIAL	COLUMN NAME	KNOWN VALUES		CR_NOMBRE_COMPLETO
E-mail address CR_L1_EMAIL	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	CR_EMAIL
Telephone number CR_L1_TELEFONO	ESSENTIAL	COLUMN NAME	VALUE FORMAT		CR_TELEFONO
Address and señas CR_L1_DIRECCION	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	CR_DIRECCION
Address detail CR_L1_DIRECCION_COMPLEMENTO	ESSENTIAL	COLUMN NAME			CR_CM_ALFANUM
Bank account (IBAN) CR_L1_CUENTA_BANCARIA		COLUMN NAME	VALUE FORMAT		CR_CUENTA
Payment card CR_L1_TARJETA		COLUMN NAME	VALUE FORMAT		CR_TARJETA
Digital wallet CR_L1_BILLETERA		COLUMN NAME	VALUE FORMAT		CR_CM_ALFANUM
IP address CR_L1_IP		COLUMN NAME	VALUE FORMAT		CR_IP
Device identifier CR_L1_DISPOSITIVO		COLUMN NAME	VALUE FORMAT		CR_CM_HEX

DOMAIN	FOUND BY			ALGORITHM
Cookie and tracking identifier CR_L1_COOKIE	COLUMN NAME			CR_CM_ALFANUM
Vehicle plate CR_L1_PLACA	COLUMN NAME	VALUE FORMAT		CR_PLACA
Vehicle identifiers CR_L1_VEHICULO	COLUMN NAME	VALUE FORMAT		CR_CM_ALFANUM
Property identifiers CR_L1_INMUEBLE	COLUMN NAME	VALUE FORMAT		CR_INMUEBLE
Contract and case numbers CR_L1_CONTRATO	COLUMN NAME			CR_CM_ALFANUM
Username and social handle CR_L1_USUARIO	COLUMN NAME			CR_CM_ALFANUM
Credentials and secrets CR_L1_CREDENCIAL	COLUMN NAME			CR_REDACTAR
Photograph and recordings CR_L1_IMAGEN	COLUMN NAME			CR_REDACTAR
Geolocation CR_L1_GEOLOCALIZACION	COLUMN NAME	VALUE FORMAT		CR_COORDENADA
Free text CR_L1_TEXTO_LIBRE	COLUMN NAME	DATA TYPE	VALUE FORMAT	CR_TEXTO_LIBRE
QUASI-IDENTIFIERS				
Date of birth ESSENTIAL CR_L2_FECHA_NACIMIENTO	COLUMN NAME	DATA TYPE		CR_FECHA_NACIMIENTO
Year of birth CR_L2_ANIO_NACIMIENTO	COLUMN NAME	DATA TYPE		CR_ANIO
Age CR_L2_EDAD	COLUMN NAME	DATA TYPE		CR_EDAD
Other dates about the person CR_L2_FECHA_EVENTO	COLUMN NAME	DATA TYPE		CR_FECHA_EVENTO
Sex CR_L2_SEXO	COLUMN NAME	KNOWN VALUES		CR_SEXO
Distrito and cantón CR_L2_DISTRITO	COLUMN NAME	KNOWN VALUES		CR_DISTRITO
DTA code and postal code CR_L2_CODIGO_DTA	COLUMN NAME	VALUE FORMAT		CR_CODIGO_DTA
Barrio CR_L2_BARRIO	COLUMN NAME			CR_BARRIO
Marital status CR_L2_ESTADO_CIVIL	COLUMN NAME	KNOWN VALUES		CR_ESTADO_CIVIL
Occupation CR_L2_OCUPACION	COLUMN NAME			CR_OCUPACION_O_CODIGO
Employer CR_L2_EMPLEADOR	COLUMN NAME			CR_EMPLEADOR
Level of education CR_L2_NIVEL_EDUCATIVO	COLUMN NAME	KNOWN VALUES		CR_NIVEL_EDUCATIVO

DOMAIN	FOUND BY		ALGORITHM
Educational institution CR_L2_INSTITUCION_EDUCATIVA	COLUMN NAME		CR_INSTITUCION_EDUCATIVA
Dependants CR_L2_PERSONAS_A_CARGO	COLUMN NAME	DATA TYPE	CR_CONTEO_LIMITADO
SENSITIVE DATA (ART. 3 E AND ART. 9.1)			
Racial or ethnic origin CR_L3_ETNIA	COLUMN NAME	KNOWN VALUES	CR_ETNIA
Indigenous people and territory CR_L3_PUEBLO_INDIGENA	COLUMN NAME	KNOWN VALUES	CR_PUEBLO
Nationality CR_L3_NACIONALIDAD	COLUMN NAME	KNOWN VALUES	CR_NACIONALIDAD
Migratory condition CR_L3_CONDICION_MIGRATORIA	COLUMN NAME	KNOWN VALUES	CR_CONDICION_MIGRATORIA
Religion CR_L3_RELIGION	COLUMN NAME	KNOWN VALUES	CR_RELIGION
Philosophical convictions CR_L3_CONVICCION_FILOSOFICA	COLUMN NAME		CR_CATEGORIA_SUPRIMIDA
Political opinion CR_L3_OPINION_POLITICA	COLUMN NAME	KNOWN VALUES	CR_PREFERENCIA_POLITICA
Party membership CR_L3_AFILIACION_PARTIDARIA	COLUMN NAME	KNOWN VALUES	CR_PARTIDO
Trade union membership CR_L3_AFILIACION_SINDICAL	COLUMN NAME	KNOWN VALUES	CR_CATEGORIA_SUPRIMIDA
Biometric data CR_L3_BIOMETRICO	COLUMN NAME	DATA TYPE	CR_REDACTAR
Genetic data CR_L3_GENETICO	COLUMN NAME		CR_REDACTAR
Sexual orientation CR_L3_ORIENTACION_SEXUAL	COLUMN NAME	KNOWN VALUES	CR_ORIENTACION_SEXUAL
Sexual life CR_L3_VIDA_SEXUAL	COLUMN NAME		CR_CATEGORIA_SUPRIMIDA
Gender identity CR_L3_IDENTIDAD_GENERO	COLUMN NAME	KNOWN VALUES	CR_IDENTIDAD_GENERO
Victim of violence CR_L3_VICTIMA	COLUMN NAME		CR_CATEGORIA_SUPRIMIDA
HEALTH DATA (ART. 9.1 D)			
Clinical record number CR_SALUD_IDENTIFICADOR	COLUMN NAME		CR_CM_ALFANUM
Health coverage CR_SALUD_COBERTURA	COLUMN NAME	KNOWN VALUES	CR_COBERTURA_SALUD
Diagnosis CR_SALUD_DIAGNOSTICO	COLUMN NAME	VALUE FORMAT	CR_DIAGNOSTICO
Procedure CR_SALUD_PROCEDIMIENTO	COLUMN NAME		CR_PROCEDIMIENTO

DOMAIN	FOUND BY		ALGORITHM
Medicine CR_SALUD_MEDICAMENTO	COLUMN NAME	KNOWN VALUES	CR_MEDICAMENTO
Clinical notes CR_SALUD_TEXTO_CLINICO	COLUMN NAME	DATA TYPE	CR_TEXTO_LIBRE
Test result CR_SALUD_RESULTADO_EXAMEN	COLUMN NAME		CR_CM_ALFANUM
HIV and sexually transmitted infections CR_SALUD_VIH	COLUMN NAME		CR_CATEGORIA_SUPRIMIDA
Blood group CR_SALUD_GRUPO_SANGUINEO	COLUMN NAME	KNOWN VALUES	CR_GRUPO_SANGUINEO
Disability CR_SALUD_DISCAPACIDAD	COLUMN NAME	KNOWN VALUES	CR_DISCAPACIDAD
Occupational health CR_SALUD_OCUPACIONAL	COLUMN NAME	KNOWN VALUES	CR_APTITUD_LABORAL
Reproductive health CR_SALUD_REPRODUCTIVA	COLUMN NAME		CR_CATEGORIA_SUPRIMIDA
Mental health CR_SALUD_MENTAL	COLUMN NAME		CR_CATEGORIA_SUPRIMIDA
ECONOMIC DATA (ART. 3 E, ART. 1 AND ART. 9.4)			
Credit standing CR_FIN_HISTORIAL_CREDITICIO	COLUMN NAME		CR_HISTORIAL_CREDITICIO
Debt CR_FIN_DEUDA	COLUMN NAME	DATA TYPE	CR_VALOR_DEUDA
Income CR_FIN_INGRESOS	COLUMN NAME	DATA TYPE	CR_INGRESOS
Assets CR_FIN_PATRIMONIO	COLUMN NAME	DATA TYPE	CR_PATRIMONIO
Pension CR_FIN_PENSION	COLUMN NAME	DATA TYPE	CR_VALOR_PENSION
Social programme CR_FIN_PROGRAMA_SOCIAL	COLUMN NAME	KNOWN VALUES	CR_PROGRAMA_SOCIAL
Condición socioeconómica CR_FIN_CONDICION_SOCIOECONOMICA	COLUMN NAME	KNOWN VALUES	CR_CONDICION_SOCIOECONOMICA
Housing tenure CR_FIN_VIVIENDA	COLUMN NAME	KNOWN VALUES	CR_TENENCIA_VIVIENDA
CRIMINAL RECORDS (ART. 8 C AND LEY 6723)			
Criminal record CR_PENAL_ANTECEDENTES	COLUMN NAME		CR_ANTECEDENTES
Judicial file number CR_PENAL_EXPEDIENTE	COLUMN NAME	VALUE FORMAT	CR_EXPEDIENTE_JUDICIAL

Direct identifiers

Data that identifies a person on its own. The *cédula de identidad* is the key of every Costa Rican record and carries no check digit, so nothing has to be recomputed and the whole number changes, the provincia digit included. The IBAN is the exception: it does carry check digits, and it comes out with valid ones. Only a **persona física** is a titular in Costa Rica, so a *cédula jurídica* passes through untouched.

8.1 Cédula de identidad

CR_L1_CEDULA

ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	REGEX DECOMPOSE
-----------	-------------	-----------	--------------	-----------------

WHAT IT IS

The number of the Tribunal Supremo de Elecciones, the key of every Costa Rican record. Its canonical form is ten digits, 0P-TTTT-AAAA — a provincia, the tomo and the asiento of the birth entry — and the leading zeroes are usually dropped, so it is written 1-0234-0567 or 102340567 .

The same domain takes the other numbers a document column holds: a DIMEX of eleven or twelve digits, a NITE of the 3-120 series, and the *cédula jurídica* of a company. A driving licence carries the *cédula* of its holder, so a licence column lands here too.

HOW IT IS FOUND

COLUMN NAME	CR_L1_CEDULA – Path
90%	<code>c[eé]dula(_?(de_)?identidad)?</code> <i>(except when followed by jur[ií]dica)</i> <code>ced</code> <code>n(o ro um umero)_?</code> <code>(c[eé]dula documento doc identificaci[oó]n id(ent)?)</code> <code>doc_?identidad</code> <code>nro_?doc</code> <code>num_?doc</code> <code>identificaci[oó]n</code> <i>(except when preceded by (tipo cod codigo desc clase)_ ; except when followed by tipo ,</i> <i>clase , juridica , jur[ií]dica)</i> <code>identificaci[oó]n_?f[ií]sica</code> <code>licencia(_?(de_)?conducir)?(_?</code> <code>n(o ro um umero))?</code> <code>n(o ro um umero)_?licencia</code> <code>licencia_?cosevi</code> <code>driver_?licen[cs]e</code> <code>(cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado emp </code> <code>trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitant</code> <code>e propietario arrendatario inquilino conductor responsable representante apoderado persona ciu</code> <code>dadano elector votante contribuyente proveedor socio conyuge padre madre hijo familiar pension</code> <code>ado jubilado aportante patrono)_?(cedula ced doc documento)</code> <code>cedula_?</code> <code>(cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado emp t</code> <code>rabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante</code> <code> propietario arrendatario inquilino conductor responsable representante apoderado persona ciud</code> <code>adano elector votante contribuyente proveedor socio conyuge padre madre hijo familiar pension</code> <code>ado jubilado aportante patrono)</code>
60%	<code>documento</code> <code>doc</code>
DATA TYPE	CR_L1_CEDULA – Type
Accepts text (length 6 or more) or number (length 6 or more); any other type rules the domain out.	

PATTERN	STRENGTH	NOTES
\d-\d{4}-\d{4}		95%
0\d-\d{4}-\d{4}		90%
\d-\d{3}-\d{3}		70%
[1-9]\d{8}		40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, keeping the hyphens. The cédula carries **no check digit** — the Dirección General de Tributación validates it against the Registro Civil itself — so nothing has to be recomputed and the whole number changes, **the provincia digit included**: it is the provincia of the birth entry and would otherwise survive into the copy. The first digit is mapped inside 1 to 9, never to a zero, so the result is still a well-formed cédula.

A **cédula jurídica** is left exactly as it is: article 3 b) and g) reach only a natural person, so a company is no titular and its number is nobody's personal datum. From the fourth quarter of 2026 that number may be alphanumeric, 3-101-A00001, under Decreto 44648-MJ; both forms pass through.

CR_DOCUMENTO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_NITE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_DIMEX REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

CR_CEDULA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

CR_CM_DIGITO_1_9 CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1-0234-0567	→	9-2975-1730
102340567	→	977261849
155812345678	→	211863565214
3-120-123456	→	3-120-904292
3-101-123456	→	3-101-123456

8.2 DIMEX

CR_L1_DIMEX

ESSENTIAL COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The Documento de Identidad Migratorio para Extranjeros, the identity number of a foreign resident: eleven or twelve digits, no separators, and the identifier the Dirección General de Tributación uses for them.

HOW IT IS FOUND

COLUMN NAME CR_L1_DIMEX - Path

90% dimex c[eé]dula_(de_)?residencia documento_(de_)?identidad_migratorio
n(o|ro|um|umero)_(dimex|residencia|extranjer[ií]a|refugiado) carn[eé]_(de_)?
(residencia|refugiado) id_migratorio
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|
trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|fiador|garante|solicitant
e|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciu
dadano|elector|votante|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|pension
ado|jubilado|aportante|patrono)_?dimex

VALUE FORMAT CR_L1_DIMEX - Regex

PATTERN	STRENGTH	NOTES
\d{11,12}		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every digit changes and the length stays, because the length is what tells a DIMEX from a cédula in a mixed column. The DIMEX has no check digit either.

CR_DIMEX REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
155812345678	→ 211863565214
12345678901	→ 06176626922

8.3 NITE

CR_L1_NITE

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The Número de Identificación Tributaria Especial, for a person with no cédula and no DIMEX. The **3-120** series belongs to a foreign natural person and the **3-130** series to a foreign company.

HOW IT IS FOUND

COLUMN NAME CR_L1_NITE - Path

90% nite n(o|ro|um|umero)_(de_)?identificaci[oó]n_(tributaria_)?especial identificacion_
tributaria_especial

VALUE FORMAT CR_L1_NITE - Regex

PATTERN	STRENGTH	NOTES
3[\s\~]?120[\s\~]?[0-9]{6}		90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

This is where the law draws its sharpest line: the six digits of a **3-120** number are masked, because that number belongs to a natural person, and a **3-130** number is left alone, because it belongs to a company and a company is no titular. The two look alike and are treated opposite ways.

CR_NITE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3-120-123456	→	3-120-904292
3130ABC123	→	3130ABC123

8.4 Passport

CR_L1_PASAPORTE

ESSENTIAL

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The passport number, Costa Rican or foreign: a letter or two and six to eight digits.

HOW IT IS FOUND

COLUMN NAME CR_L1_PASAPORTE - Path

90%

`pasaporte[a-z0-9]* n(o|ro|um|umero)?pasaporte passport[a-z0-9]*`

VALUE FORMAT CR_L1_PASAPORTE - Regex

PATTERN	STRENGTH	NOTES
<code>[A-Z]{1,2}\d{6,8}</code>		40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters become letters and digits become digits, so the number keeps the shape the issuing country gives it.

CR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BLM123	→	ZJQ771

8.5 Social security number

CR_L1_SEGURO_SOCIAL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The numbers of the Caja Costarricense de Seguro Social: the número de asegurado, the número patronal of an employer, the planilla and the SICERE codes.

HOW IT IS FOUND

COLUMN NAME CR_L1_SEGURO_SOCIAL – Path

85% n(o|ro|um|umero)?(asegurado|seguro?social|patronal|patrono|afiliado|afiliaci[oó]n)
c[oó]digo?(asegurado|patrono|patronal) asegurado[a-z0-9]* ccss[a-z0-9]* n[uú]mero?
ccss carn[eé]?(ccss|asegurado) planilla?(ccss|n(o|ro|um|umero)) sincere

HOW IT IS MASKED

Character by character, keeping the shape and any separators. These numbers are built from the cédula, so they are as identifying as it is.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

A1234567

→ **U2438404**

8.6 Student code

CR_L1_CODIGO_ESTUDIANTE

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

The identifier a school, a colegio or a university gives a student, and the cédula escolar.

HOW IT IS FOUND

COLUMN NAME CR_L1_CODIGO_ESTUDIANTE – Path

80% c[oó]digo?(de_)?(estudiante|alumno|matr[ií]cula) cod?(alumno|estudiante)
n(o|ro|um|umero)?(de_)?(matr[ií]cula|estudiante) carn[eé]?(de_)?
(estudiante|universitario) id?(alumno|estudiante) c[eé]dula?escolar identificaci[oó]n?
estudiantil

HOW IT IS MASKED

Character by character. It is a direct identifier inside its own institution, which is where the roster lives.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

A1234567

→ **U2438404**

8.7 Professional registration

CR_L1_MATRICULA_PROFESIONAL

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

The number of a colegio profesional — the código médico, the número de colegiado, the carné — and the título number.

HOW IT IS FOUND

COLUMN NAME CR_L1_MATRICULA_PROFESIONAL – Path

85% `c[oó]digo?(profesional|m[eé]dico) n(o|ro|um|umero)?(de_)??`
`(colegiado|incorporaci[oó]n|registro?profesional) colegiado incorporaci[oó]n?(al_)??`
`colegio carn[eé]?profesional n(o|ro|um|umero)?(de_)??t[ií]tulo`

HOW IT IS MASKED

Character by character. The registers are public, which is exactly what makes the number a key back to a named professional.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
A1234567	→ U2438404

8.8 Given name

CR_L1_NOMBRE

ESSENTIAL **COLUMN NAME** **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

A given name on its own: the first, the second, or a column that holds both.

HOW IT IS FOUND

COLUMN NAME CR_L1_NOMBRE – Path

85% `primer?nombre segundo?nombre nombres?(de_)?pila pri(mer)??nom seg(undo)??nom`
`nombre_?1 nombre_?2 first?names? given?names? fname middle?names? nombres (except`
`when followed by completos?, y?apellidos?, apellidos? )`

50% `nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)`

KNOWN VALUES CR_L1_NOMBRE – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-nombres.txt	449	70%	Adolfo, Adrián, Adrian, Adriana, Aída, Aida

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word becomes another Costa Rican given name, from a list of 400 taken from the frequency of names in the country — Xinia, Yorleny, Olger and Keylor among them. The particles of a compound name stay where they are, so "María de los Ángeles" keeps its shape.

CR_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_NOMBRE .

CR_NOMBRE NAME

Replaces the name with one of the 400 names in cr-nombres.txt .

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

María de los Ángeles

→

Hugo de los Álvaro

JOSÉ PABLO

→

ELIZABETH DORA

8.9

Surname

CR_L1_APELLIDO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The first or the second surname, or a column with both.

HOW IT IS FOUND

COLUMN NAME

CR_L1_APELLIDO - Path

85%

apellidos? primer_apellido segundo_apellido apellido?(1|2|paterno|materno) ape_?
(1|2|pat|mat) ap?(paterno|materno) last_names? surnames? family_names? lname

KNOWN VALUES

CR_L1_APELLIDO - List

LIST

VALUES

STRENGTH

FIRST VALUES

cr-detectar-apellidos.txt

539

70%

Abarca, Acevedo, Acosta, Acuña, Acuna, Agüero

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word becomes another Costa Rican surname, from a list of 420 — Oconitrillo, Cartín, Garbanzo, Jirón and the English surnames of the Caribbean coast among them. "De la Cruz" keeps its particles.

CR_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_APELLIDO .

CR_APELLIDO NAME

Replaces the name with one of the 420 names in cr-apellidos.txt .

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Jiménez Oconitrillo

→

Guadamuz Moreira

8.10

Full name

CR_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The whole name in one column, and the name of a third party — the mother, the father, a guardian, an emergency contact, a fiador.

HOW IT IS FOUND

COLUMN NAME CR_L1_NOMBRE_COMPLETO – Path

90%	nombres?_?(completos? y_apellidos? apellidos?) apellidos?_?(y_?)?nombres? nombre?(del_ de_la_?)? (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante imputado testigo medico docente socio heredero donante tutor pensionado jubilado customer patient employee member holder mother father spouse contact person student driver owner) (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante imputado testigo medico docente socio heredero donante tutor pensionado jubilado customer patient employee member holder mother father spouse contact person student driver owner)?(nombre nom) nom_? (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante imputado testigo medico docente socio heredero donante tutor pensionado jubilado customer patient employee member holder mother father spouse contact person student driver owner) nombre_? (madre padre tutor conyuge contacto_emergencia referencia) full_name person_name
60%	madre padre tutor conyuge representante_legal apoderado fiador garante beneficiario heredero titular referencia_(personal familiar)
50%	nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)

KNOWN VALUES CR_L1_NOMBRE_COMPLETO – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-nombres.txt	449	65%	Adolfo, Adrián, Adrian, Adriana, Aída, Aida
cr-detectar-apellidos.txt	539	65%	Abarca, Acevedo, Acosta, Acuña, Acuna, Agüero

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Read in the Costa Rican order — one or two given names, the father's surname, the mother's surname — and each word replaced by one of its own kind, so a masked name is still plausibly a person. "Jiménez Oconitrillo, José Pablo" is read the other way round.

CR_NOMBRE_COMPLETO **REGEX DECOMPOSE**

Tries 7 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_APELLIDOS **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_PALABRA_APELLIDO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: CR_APELLIDO .

CR_APELLIDO	NAME
Replaces the name with one of the 420 names in <code>cr-apellidos.txt</code> .	
CR_CM_ALFANUM	CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.	
CR_NOMBRES	REGEX DECOMPOSE
Tries 4 patterns in order and gives each part of the value its own action; when none matches: <code>CR_CM_ALFANUM</code> .	
CR_PALABRA_NOMBRE	REGEX DECOMPOSE
Matches one pattern and gives each part of the value its own action; when none matches: <code>CR_NOMBRE</code> .	
CR_NOMBRE	NAME
Replaces the name with one of the 400 names in <code>cr-nombres.txt</code> .	

EXAMPLES

VALUE		MASKED
José Pablo Jiménez Oconitrillo	→	Elizabeth Dora Guadamuz Moreira
Xinia Jiménez	→	Kevin Guadamuz
JIMÉNEZ OCONITRILLO, JOSÉ PABLO	→	GUADAMUZ MOREIRA, ELIZABETH DORA

8.11 E-mail address

CR_L1_EMAIL

ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	REGEX DECOMPOSE
-----------	-------------	-----------	--------------	-----------------

WHAT IT IS

Any address column, personal or at work.

HOW IT IS FOUND

COLUMN NAME

CR_L1_EMAIL - Path

85%

e_?mail[a-z0-9_]*

mail[a-z0-9_]*

correo(_?electr[oó]nico)?[a-z0-9_]*

dir_?correo

direcci[oó]n_?(de_)?correo

direcci[oó]n_?electr[oó]nica

DATA TYPE

CR_L1_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT

CR_L1_EMAIL - Regex

PATTERN	STRENGTH	NOTES
[A-Za-z0-9._%+ '\-]+@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The local part and the domain are masked and the top-level domain becomes `.test`, the suffix reserved for testing: a masked address can never deliver, so a test run cannot mail a real person.

CR_EMAIL	REGEX DECOMPOSE
Matches one pattern and gives each part of the value its own action; when none matches: <code>CR_CM_ALFANUM</code> .	
CR_CM_ALFANUM	CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.	

EXAMPLES

VALUE		MASKED
jose.jimenez@gmail.com	→	sexu.lewebax@pgoeb.test

8.12 Telephone number

CR_L1_TELEFONO

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Every Costa Rican number has eight digits and no area code: 2 for a landline, 4 for IP telephony, 5 to 8 for a mobile. Article 9.3 keeps the **números de teléfono privados** out of the data of unrestricted access by name, and SINPE Móvil makes a mobile number a payment address as well.

HOW IT IS FOUND

COLUMN NAME

CR_L1_TELEFONO - Path

85%

```
tel tel[eé]fono[a-z0-9]* tel_?
(fijo|casa|habitaci[oó]n|oficina|trabajo|contacto|celular|m[oó]vil) celular[a-z0-9]* cel
m[oó]vil whats_?app sinpe_?m[oó]vil n(o|ro|um|umero)_?
(tel|tel[eé]fono|celular|cel|contacto) fax phone[a-z0-9]* mobile[a-z0-9]*
```

VALUE FORMAT

CR_L1_TELEFONO - Regex

PATTERN

STRENGTH

NOTES

(\+?506[\s-]?)?[5-8]\d{3}[\s-]?\d{4}

80%

(\+?506[\s-]?)?[24]\d{3}[\s-]?\d{4}

60%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The country code and the first digit stay, so a masked number still says landline or mobile; the other seven change and the spacing is kept.

CR_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

CR_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

+506 8312 4567

→

+506 8725 6415

83124567

→

87256415

2222 1234

→

2727 2351

8.13 Address and señas

CR_L1_DIRECCION

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

SECURE LOOKUP

WHAT IT IS

Costa Rica has almost no street addresses: an address is a distance and a direction from a landmark — "200 metros norte de la iglesia católica, casa esquinera color verde" — sometimes a residencial and a house number, sometimes the avenue-and-calle grid of central San José. The **dirección exacta de la residencia** is the first thing article 9.3 takes out of the data of unrestricted access.

HOW IT IS FOUND

COLUMN NAME CR_L1_DIRECCION - Path

80% direcci[oó]n[a-z0-9_]* (except when preceded by mac , ip , e_?mail , web , url , correo ; except when followed by list E4) domicilio[a-z0-9_]* dom_?(residencia|particular|laboral|cliente|fiscal|exacto) residencia lugar_?(de_?)?residencia se[nñ]as(_?(exactas|adicionales|particulares))? otras_?se[nñ]as address[a-z0-9_]* (except when preceded by mac , ip , e_?mail , web , url ; except when followed by list E5)

DATA TYPE CR_L1_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT CR_L1_DIRECCION - Regex

PATTERN	STRENGTH	NOTES
(?i).*\d{2,3}\s*(m mts metros)\.?\s+(norte sur este oeste noreste noroeste sureste suroeste).*	90%	
(?i)(urbanizaci[oó]n residencial condominio barrio caser[ií]o)\s+[a-záéíóúñ0-9.']{2,40}.*	70%	
(?i).*(avenida calle)\s*\d{1,3}.*(calle avenida)\s*\d{1,3}.*	70%	
(?i).*\b(contiguo frente diagonal costado detr[áá]s)\b.*	60%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced by a fictitious one from a list of four thousand built in the Costa Rican way: metres and a direction from a landmark, a residencial and a house, or an avenue and a calle. The same input always gives the same output, so a row keeps its neighbours.

CR_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in cr-direcciones.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
200 metros norte de la iglesia católica, casa esquinera color verde	→	250 metros oeste y 600 norte de el colegio técnico
Urbanización Los Laureles, casa 12	→	150 metros suroeste de la cancha de fútbol, casa de dos plantas

8.14 Address detail

CR_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

What comes beside the address: the apartment, the floor, the tower, the house number, the lote, the etapa, the apartado postal.

HOW IT IS FOUND

COLUMN NAME CR_L1_DIRECCION_COMPLEMENTO - Path

70% apartamento apto apto_?n(o|ro|um|umero) piso torre bloque block casa_?
n(o|ro|um|umero) n(o|ro|um|umero)?(casa|apto|apartamento|local|oficina) lote etapa
filial condominio complemento(_?direcci[oó]n)? referencia_?(de_)?
(direcci[oó]n|domicilio) apartado(_?postal)? apdo p_?o_?box

HOW IT IS MASKED

Character by character, keeping the shape: a detail that narrows a building to one door identifies as much as the address.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
A1234567	→ U2438404

8.15 Bank account (IBAN)

CR_L1_CUENTA_BANCARIA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Since 2017 every Costa Rican account is an IBAN of 22 characters: CR , two check digits, a reserved zero, three digits for the bank and fourteen for the account — the 17-digit Cuenta Cliente of SINPE with five characters in front. It is written compact, CR05015202001026284066 , and printed in groups of four, CR05 0152 0200 1026 2840 66 .

HOW IT IS FOUND

COLUMN NAME CR_L1_CUENTA_BANCARIA - Path

90% cuenta_?(bancaria|banco|corriente|ahorros?
|cliente|salario|planilla|abono|dep[oó]sito|destino|origen|iban) n(o|ro|um|umero)?(de_)?
(cuenta|cta) nro_?cta num_?cta cta_?(cte|corriente|ahorros?|bancaria|cliente) iban[a-z0-
9_]* cuenta_?iban account_?(no|num|number) bank_?account

VALUE FORMAT CR_L1_CUENTA_BANCARIA - Regex

PATTERN	STRENGTH	NOTES
CR\d{20}		95%
CR\d{2}(\s\d{4}){4}\s\d{2}		95%
\d{17}		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The fourteen digits of the account change and the **two check digits are recomputed**, so the masked IBAN passes the ISO 13616 remainder that every library and every Costa Rican system checks. The bank stays — it is not personal data, and keeping it keeps a test account inside a real bank. The last section of this document explains how the remainder is computed.

CR_CUENTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

CR_IBAN STRING ALGORITHM CHAIN

Applies CR_IBAN_1 → CR_IBAN_2 → CR_IBAN_3 → CR_IBAN_4 → CR_IBAN_5 → CR_IBAN_6 → CR_IBAN_RESTAURAR , in this order. It is made of 59 algorithms that repeat the same step position by position; each one is in Appendix A.

EXAMPLES

VALUE		MASKED
CR05015202001026284066	→	CR06015246852985710469
CR05 0152 0200 1026 2840 66	→	CR29 0152 3258 2781 0212 23
15202001026284066	→	15246852985710469

8.16 Payment card

CR_L1_TARJETA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The card number, credit or debit, with or without spaces.

HOW IT IS FOUND

COLUMN NAME

CR_L1_TARJETA – Path

85%

tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))? n(o|ro|um|umero)?tarjeta pan card_?
(no|num|number) credit_card tc_(numero|num|nro)

VALUE FORMAT

CR_L1_TARJETA – Regex

PATTERN

STRENGTH

NOTES

\d{13,19}

90%

LUHN check digit; after removing [\s-]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The Payment Card algorithm keeps the Luhn digit valid and the first digits in place, so the brand and the issuer survive and a payment form still accepts the value in a test.

CR_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CR_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE		MASKED
4532 0000 0000 0001	→	1913 8236 1564 8970

8.17 Digital wallet

CR_L1_BILLETERA

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The identifier of a wallet or of a crypto address.

HOW IT IS FOUND

COLUMN NAME CR_L1_BILLETERA - Path

85% billetera(_?(digital|electr[oó]nica|m[oó]vil))? wallet(_?(id|address|direccion))? kash
tapp monedero_?(digital|electr[oó]nico) dinero_?electr[oó]nico c[oó]digo_?qr qr_
(id|codigo) direcci[oó]n_?(bitcoin|btc|wallet) btc_?(address|direccion)

VALUE FORMAT CR_L1_BILLETERA - Regex

PATTERN	STRENGTH	NOTES
(bc1 [13])[a-zA-HJ-NP-Z0-9]{25,59}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the shape so that a format check still passes.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
A1234567	→ U2438404

8.18 IP address

CR_L1_IP

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The address of the device from which a person connected, logged in or filed something.

HOW IT IS FOUND

COLUMN NAME CR_L1_IP - Path

85% ip ip_?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)
direcci[oó]n_?ip dir_?ip ipv[46] remote_?addr(ess)? client_?ip host_?ip

VALUE FORMAT CR_L1_IP - Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)		100%
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}		90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each octet becomes another number between 1 and 254, so the address stays routable-looking; an IPv6 keeps valid hexadecimal.

CR_IP **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **CR_CM_HEX**.

CR_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

CR_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

201.196.45.12

→

133.244.51.94

8.19 Device identifier

CR_L1_DISPOSITIVO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC, advertising and session identifiers: numbers that follow one device, and so one person.

HOW IT IS FOUND

COLUMN NAME

CR_L1_DISPOSITIVO - Path

80%

imei imsi iccid mac mac_address direccion_mac device_(id|uuid|serial) id_(dispositivo|equipo|celular) serial_(equipo|celular|dispositivo) advertising_id idfa gaid session_id id_session

VALUE FORMAT

CR_L1_DISPOSITIVO - Regex

PATTERN

STRENGTH

NOTES

([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}

100%

\d{15}

80%

LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Hexadecimal stays hexadecimal and a MAC keeps its colons; an IMEI keeps its fifteen digits.

CR_CM_HEX

CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

3c:22:fb:9a:10:e4

→

5e:83:bb:3c:31:f9

8.20 Cookie and tracking identifier

CR_L1_COOKIE

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The identifier a site or a campaign writes into a browser, and the UTM parameters that came with it.

HOW IT IS FOUND

COLUMN NAME

CR_L1_COOKIE - Path

80%

cookie_(? (id|value|valor|nombre)) cookies _ga _gid fbp fbclid utm_(source|medium|campaign|term|content) id_(navegador|browser|visitante) visitor_id tracking_id client_id

HOW IT IS MASKED

Character by character. It names no one by itself and follows one browsing history, which is why it is a direct identifier here.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	U2438404

8.21 Vehicle plate

CR_L1_PLACA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Digits for a private car, three letters and three digits in the alphanumeric series the Registro Nacional opened, and a class prefix for the rest — MOT a motorcycle, CL light cargo, AB a bus, TSJ or TA a taxi.

HOW IT IS FOUND

COLUMN NAME	CR_L1_PLACA - Path		
85%	placa(_?(veh[ií]culo auto moto n(o ro um umero)))? n(o ro um umero)?placa matr[ií]cula(_?(veh[ií]culo auto moto))? (except when followed by profesional, m[eé]dica, estudiante, consular) license_?plate plate(_?(no number))?		
VALUE FORMAT	CR_L1_PLACA - Regex		
PATTERN	STRENGTH	NOTES	
(?i)(MOT CL TSJ AB SJB) [\s-]? \d{3,6}		80%	
[A-Z]{3} [\s-]? \d{3}		50%	
\d{6}		35%	
A value that matches none counts 30% against the domain.			

HOW IT IS MASKED

The class prefix stays and the digits change, so the fleet still looks like a fleet and the plate still points at no owner.

CR_PLACA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CR_CM_DIGITOS_LETRAS

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BLM123	→	PNX957
123456	→	904292
MOT123456	→	MOT904292

8.22 Vehicle identifiers

CR_L1_VEHICULO

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number, the marchamo and the revisión técnica record.

HOW IT IS FOUND

COLUMN NAME CR_L1_VEHICULO - Path

85% vin chasis n(o|ro|um|umero)?(chasis|motor|serie|vin) motor_?n(o|ro|um|umero) t[ií]tulo?(de_)?propiedad?veh[ií]culo riteve dekra n(o|ro|um|umero)?(de_)? revisi[oó]n_?t[eé]cnica marchamo

VALUE FORMAT CR_L1_VEHICULO - Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NPR-Z0-9]{17}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the seventeen positions of a VIN so that a format check still passes.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
A1234567	→ U2438404

8.23 Property identifiers

CR_L1_INMUEBLE

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The folio real of the Registro Inmobiliario, 1-234567-000, the plano catastrado of the Catastro, SJ-1234567-2010, and the meter numbers of the utilities. Article 1 of the law reaches the data of a person "o bienes", and article 12 of the regulation repeats it.

HOW IT IS FOUND

COLUMN NAME CR_L1_INMUEBLE - Path

85% folio_?real n(o|ro|um|umero)?(de_)?(finca|folio|folio_?real|plano|plano_? catastrado|matr[ií]cula_?inmueble|derecho) finca(_?(n(o|ro|um|umero)|filial))? plano_? catastrado matr[ií]cula_?(inmobiliaria|catastral) c[oó]digo_?catastral n(o|ro|um|umero)?(de_)?(medidor|nis|servicio_?el[eé]ctrico) nis(_?(ice|cnfl|aya))?

VALUE FORMAT CR_L1_INMUEBLE - Regex

PATTERN	STRENGTH	NOTES
[1-7]-\d{6}-\d{3}		80%
(?i)(SJ A C H G P L)-\d{6,7}-\d{4}		80%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The digits change and the separators and the provincia letters stay, so the reference keeps its shape. The registers are public and searchable by number, which is what makes a folio real a route back to an owner.

CR_INMUEBLE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_CM_DIGITO_1_9 CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1-234567-000	→	9-172434-991
SJ-1234567-2010	→	SJ-5649285-2010

8.24 Contract and case numbers

CR_L1_CONTRATO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The internal numbers that stand for one person: contract, policy, loan, application, claim, ticket, customer or employee code.

HOW IT IS FOUND

COLUMN NAME

CR_L1_CONTRATO - Path

70%

```
n(o|ro|um|umero)?(contrato|p[ó]liza|cr[eé]dito|pr[eé]stamo|solicitud|expediente_?
(administrativo|interno)|tr[aá]mite|referencia|cliente|socio|suscriptor|suministro|servicio|ca
so|ticket|beneficio|sinistro|reclamo) contrato?(n(o|ro|um|umero)) c[ó]digo_?
(cliente|socio|empleado|afiliado|suministro) id?(cliente|socio|empleado|afiliado)
n(o|ro)?(empleado|funcionario) c[ó]digo?(de_)?(empleado|funcionario|puesto)
```

HOW IT IS MASKED

Character by character, keeping prefixes and separators so that joins by format still work. The number is a pseudonym, and a pseudonym that survives the copy links it back.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A1234567	→	U2438404

8.25 Username and social handle

CR_L1_USUARIO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The login, the alias, the nickname and the handle of a social network.

HOW IT IS FOUND

COLUMN NAME CR_L1_USUARIO – Path

70% usuario user_?name username login alias apodo nick(_?name)? perfil_?
(instagram|facebook|twitter|tiktok|linkedin|x) instagram facebook twitter tiktok
linkedin red_?social handle

HOW IT IS MASKED

Character by character. A handle is searchable, so it names a person as surely as the name does.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
A1234567	→ U2438404

8.26 Credentials and secrets

CR_L1_CREDENCIAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PINs, CVVs, tokens, API keys, seed phrases, security questions and answers.

HOW IT IS FOUND

COLUMN NAME CR_L1_CREDENCIAL – Path

90% contrase[nñ]a clave (except when followed by catastral, primaria, for[aá]nea, valor, producto)
password passwd pwd pass hash_?(clave|contrasena|password) pin c[oó]digo_
(seguridad|verificaci[oó]n|acceso|otp) cvv cvc token(_?(acceso|refresh|api))? access_
token refresh_?token api_?key llave_?(api|privada) secreto secret otp firma_
(electr[oó]nica|digital)_?(clave|pin) pregunta_?secreta respuesta_?secreta frase_
semilla seed_?phrase

HOW IT IS MASKED

Replaced by X characters. These are not masked to de-identify but to stop a copy from carrying working credentials: article 29 b) makes it a falta leve to store or transmit third-party data "por medio de mecanismos inseguros", and a dump with live passwords is that.

CR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
clave123	→ XXXXXXXX

8.27 Photograph and recordings

CR_L1_IMAGEN

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The path or the URL of a photograph, a selfie, a scanned cédula, a video or a call recording. Article 9.3 names **la fotografía** among the things that are not of unrestricted access even when they sit in a public register.

HOW IT IS FOUND

COLUMN NAME

CR_L1_IMAGEN - Path

85%

foto(graf[ií]a)?[a-z0-9]* imagen?(persona|rostro|perfil|c[eé]dula|documento) avatar
selfie retrato video?(persona|entrevista) audio?(voz|llamada) grabaci[oó]n(_?
(llamada|voz))? url?foto ruta?(foto|imagen) photo[a-z0-9]* picture image_
(url|path|person)

HOW IT IS MASKED

Replaced by X characters: the reference is cut, because a path that still resolves hands over the face itself.

CR_REDACTAR

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

clave123

→

XXXXXXXX

8.28 Geolocation

CR_L1_GEOLOCALIZACION

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in columns of their own, and the CRTM05 coordinates the national grid uses.

HOW IT IS FOUND

COLUMN NAME

CR_L1_GEOLOCALIZACION - Path

85%

lat latitud lon lng longitud coordenadas? coord?[xy] geo?
(lat|lon|lng|loc|localizacion|posicion) georreferenciaci[oó]n geolocalizaci[oó]n gps(_?
(ubicaci[oó]n|posici[oó]n|coordenadas))? ubicaci[oó]n?gps crt05 lambert

50%

long

VALUE FORMAT

CR_L1_GEOLOCALIZACION - Regex

PATTERN

STRENGTH

NOTES

(8|9|10|11)\.\d{3,}\s*,\s*-8[2-6]\.\d{3,}

90%

-8[2-6]\.\d{4,}

50%

(8|9|10|11)\.\d{4,}

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and the first decimal stay — about eleven kilometres — and the rest changes: the place is generalized, not moved to another country.

CR_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
9.935800	→	9.948145
9.935800,-84.092059	→	9.948145,-84.075771

8.29 Free text

CR_L1_TEXT0_LIBRE

COLUMN NAME

DATA TYPE

VALUE FORMAT

FREE TEXT REDACTION

WHAT IT IS

Observations, comments, notes, the account of a complaint: the columns where people write whatever they like, and where cédulas, phones and names end up.

HOW IT IS FOUND

COLUMN NAME

CR_L1_TEXT0_LIBRE - Path

60%

observaci[oó]n(es)? obs comentarios? notas? anotaci[oó]n(es)? glosa descripci[oó]n_
(queja|reclamo|solicitud|caso|hechos|novedad|atenci[oó]n|denuncia) detalle_
(reclamo|solicitud|caso|atenci[oó]n) hechos relato justificaci[oó]n mensaje *(except when
preceded by list E6; except when followed by list E7)* texto(?:libre)? resumen?(caso|atenci[oó]n) queja
reclamo denuncia_?texto remarks? comments? notes? free_?text memo

DATA TYPE

CR_L1_TEXT0_LIBRE - Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT

CR_L1_TEXT0_LIBRE - Regex

PATTERN

STRENGTH

NOTES

\d-\d{4}-\d{4}

80% anywhere in the value

[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}

70% anywhere in the value

[5-8]\\d{3}[\\s\\-]?\\d{4}

60% anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

The text is kept and what identifies inside it is redacted: a cédula, a DIMEX, a NITE, an e-mail address, a phone number, a card, an IBAN and an IP become [DAT0], and a name from the lists of the set becomes [NOMBRE].

CR_TEXT0_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with [DAT0], and the 1,944 terms of cr-texto-nombres.txt with [NOMBRE].

EXAMPLES

VALUE		MASKED
Cliente Jiménez, cédula 1-0234-0567, correo j.jimenez@gmail.com, cel 83124567	→	Cliente [NOMBRE], cédula [DAT0], correo [DAT0], cel [DAT0]

Quasi-identifiers

Data that identifies nobody alone and identifies almost anybody together. Article 2 q) of the regulation says the identity may be determined **indirectly**, by any information about a person's anatomical, physiological, psychic, economic, cultural or social identity. These columns are not emptied — a test needs ages and places that behave — they are coarsened until a combination stops pointing at one person.

9.1 Date of birth

CR_L2_FECHA_NACIMIENTO

ESSENTIAL **COLUMN NAME** **DATA TYPE** **DATE SHIFT**

WHAT IT IS

The date of birth, in a date column or written as text.

HOW IT IS FOUND

COLUMN NAME CR_L2_FECHA_NACIMIENTO – Path

90% (fecha|fec|fch|f)?(de_?)?nac(imiento)? fnac fechanac(imiento)? cumplea[nñ]os dob
date_of_birth birth_date birthday

DATA TYPE CR_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Moved by up to sixty days either way. The age and the generation survive, the exact date does not — and the exact date with a sex and a distrito is what points at one person.

CR_FECHA_NACIMIENTO **DATE SHIFT**

Moves the date by -60 to 60 days.

EXAMPLES

VALUE	MASKED
1985-07-20	→ 1985-08-05T00:00

9.2 Year of birth

CR_L2_ANIO_NACIMIENTO

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

The year alone, when the system keeps no full date.

HOW IT IS FOUND

COLUMN NAME CR_L2_ANIO_NACIMIENTO – Path

90% a[nñ]o?(de_?)?nac(imiento)? anio?nac(imiento)? year_of_birth birth_year yob

DATA TYPE CR_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit changes, so a cohort analysis still works within ten years.

CR_ANIO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

CR_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

1985

→

1980

9.3

Age

CR_L2_EDAD

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

The age in years, or the band it falls in.

HOW IT IS FOUND

COLUMN NAME

CR_L2_EDAD – Path

85%

edad(_?(actual|a[nños|anios|paciente|afiliado|cliente|al_?

(ingreso|diagn[ó]stico|fallecimiento)))? grupo_?etario tramo_?(de_)?edad rango_?(de_)?

edad quinquenio age(_?(years|group))?

DATA TYPE

CR_L2_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the units change, so 37 becomes some other thirty-something; from 100 on the value becomes 90, because a very old age is rare enough to identify.

CR_EDAD **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

37

→

35

104

→

90

9.4

Other dates about the person

CR_L2_FECHA_EVENTO

COLUMN NAME

DATA TYPE

DATE SHIFT

WHAT IT IS

Death, marriage, hiring, dismissal, admission, discharge, diagnosis, consultation, pension, arrest, sentence, the issue of the cédula.

HOW IT IS FOUND

COLUMN NAME CR_L2_FECHA_EVENTO – Path

80% (fecha|fec|fch|f)_?(de_?)?
(defunci[oó]n|fallecimiento|muerte|matrimonio|divorcio|ingreso|egreso|alta|baja|cese|retiro|con
ntrataci[oó]n|despido|pensi[oó]n|jubilaci[oó]n|internamiento|hospitalizaci[oó]n|diagn[oó]stico
|atenci[oó]n|consulta|parto|detenci[oó]n|sentencia|emisi[oó]n(_?(cedula|documento))?
|vencimiento_?c[eé]dula|vacunaci[oó]n|cirug[ií]a|accidente|incapacidad) fec_?
(emi|emision|defuncion|ingreso|egreso|baja) date_?of_?
(death|marriage|hire|admission|discharge)

DATA TYPE CR_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Moved by up to thirty days. Sequences hold — the admission still comes before the discharge — and the exact day stops being a key into a public record.

CR_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	2021-03-05T00:00

9.5

Sex

CR_L2_SEX0

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

The sex as the system records it: F/M, Femenino/Masculino, Mujer/Hombre, 1/2.

HOW IT IS FOUND

COLUMN NAME CR_L2_SEX0 – Path

85% sexo(_?(biol[oó]gico|al_?nacer|paciente|afiliado|cliente))? (tp|tipo|cod|cd|id)_?sexo
g[eé]nero (except when followed by identidad , autopercebido) sex gender (except when followed by
identity)

KNOWN VALUES CR_L2_SEX0 – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-sexo.txt		9	50% f, m, h, femenino, masculino, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced inside its own vocabulary, so an F stays an F or an M and a CHAR(1) column still fits. The distribution survives; the row no longer says which.

CR_SEX0 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_SEX0_FEMENINO_MASculINO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-sexo-femenino-masculino.txt , chosen by a keyed hash.

CR_SEX0_MUJER_HOMBRE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-sexo-mujer-hombre.txt`, chosen by a keyed hash.

CR_SEX0_FEMALE_MALE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-sexo-female-male.txt`, chosen by a keyed hash.

CR_SEX0_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-sexo-f-m.txt`, chosen by a keyed hash.

CR_SEX0_H_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-sexo-h-m.txt`, chosen by a keyed hash.

CR_SEX0_1_2 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

F

→

M

9.6

Distrito and cantón

CR_L2_DISTRITO

COLUMN NAME

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

The distrito or the cantón of residence, birth or care, by name — alone or with its cantón or provincia beside it, Matambú – Hojancha .

HOW IT IS FOUND

COLUMN NAME

CR_L2_DISTRITO – Path

85%

`distrito(_?(residencia|nacimiento|domicilio))?` *(except when followed by list E8)* `cant[oó]n(_?(residencia|nacimiento|domicilio))?` *(except when followed by cod, codigo, id)* `canton` *(except when followed by cod, codigo, id)* `ciudad(_?(residencia|nacimiento|domicilio|cliente))?` `poblado` `caser[ií]o` `(nom|nombre|desc)_?(distrito|canton|ciudad)` `lugar_?(de_)?nacimiento` `city` `town`

KNOWN VALUES

CR_L2_DISTRITO – List

LIST

VALUES

STRENGTH

FIRST VALUES

`cr-detectar-`
`distritos.txt`

496

80%

Merced, Hospital, Catedral, Zapote, San Francisco de Dos Ríos, San Francisco de Dos Rios

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A distrito of fewer than 20,000 inhabitants becomes the nearest distrito of at least 20,000 in the same cantón, or in the same provincia when the cantón has none. The cantones follow the same rule one level up, and the seven provincias stay. A name shared by several places is generalized only when every bearer is small, so a large distrito and a provincia keep their own name.

CR_DISTRITO **DATA CLEANSING**

Replaces each value found in `cr-distritos-generalizados.txt` (11,582 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Quitirrisí	→	Pozos
Matambú – Hojancha	→	Nicoya – Nicoya
San José	→	San José

9.7 DTA code and postal code

CR_L2_CODIGO_DTA

COLUMN NAME VALUE FORMAT DATA CLEANSING

WHAT IT IS

The code of the División Territorial Administrativa — one digit for the provincia, two for the cantón, two for the distrito — which in Costa Rica **is also the postal code**: Correos de Costa Rica assigns 10101 to the distrito 101 01.

HOW IT IS FOUND

COLUMN NAME CR_L2_CODIGO_DTA – Path

85% (cod|codigo|cd|id)_(dta|distrito|canton|cant|provincia|ciudad|lugar|geogr[aá]fico)(_?(inec|censo|res|residencia|nac|nacimienta)?)? c[oó]digo_(de_)? (distrito|canton|divisi[oó]n_?territorial) coddistrito codcanton c[oó]digo_postal cod_postal codpostal zip(_?code)? postal_?code

VALUE FORMAT CR_L2_CODIGO_DTA – Regex

PATTERN	STRENGTH	NOTES
[1-7]\d{4}		40%
[1-7]\d{2}		30%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same table that generalizes the names generalizes the codes, so a masked postal code still agrees with the masked distrito beside it and no row says one place in words and another in digits.

CR_CODIGO_DTA DATA CLEANSING

Replaces each value found in cr-codigos-generalizados.txt (428 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
10707	→	10903
10110	→	10110
107	→	107

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The barrio, the urbanización, the residencial or the condominio — the level below the distrito. The 2025 decree of the División Territorial Administrativa names 1,276 of them.

HOW IT IS FOUND

COLUMN NAME

CR_L2_BARRIO – Path

80%

barrio(_?(residencia|domicilio|nombre))?

urbanizaci[oó]n

urb

residencial

condominio_?

(nombre)?

zona(_?(residencia|domicilio))?

asentamiento

precario

(nom|nombre)_?

(barrio|urbanizacion|residencial)

neighbou?rhood

HOW IT IS MASKED

Replaced by another real barrio of the country, always the same one for the same input. Generalizing upwards would say nothing a masked distrito does not already say, and a barrio column is often all the geography a table has.

CR_BARRIO

SECURE LOOKUP

Replaces the value with one of the 1,276 values in `cr-barrios.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Barrio Escalante	→ Ponderosa

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The marital status, as text or as a code.

HOW IT IS FOUND

COLUMN NAME

CR_L2_ESTADO_CIVIL – Path

85%

estado_?civil

est_?civil

(cod|tipo|id)_?estado_?civil

situaci[oó]n_?conyugal

uni[oó]n_?

(libre|de_?hecho)

marital_?status

civil_?status

KNOWN VALUES

CR_L2_ESTADO_CIVIL – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-estado-civil.txt	21	70%	Soltero/a, Casado/a, Unión libre o de hecho, Union libre o de hecho, Separado/a, Divorciado/a

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another status of the same list, and a numeric code by another code. A flag column keeps its S/N.

CR_ESTADO_CIVIL

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_ESTADO_CIVIL_LISTA .

CR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`CR_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

`CR_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

`CR_BANDERA_YES_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

`CR_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

`CR_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

`CR_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

`CR_ESTADO_CIVIL_CODIGO` **SECURE LOOKUP**

Replaces the value with one of the 6 values in `cr-estado-civil-codigos.txt`, chosen by a keyed hash.

`CR_ESTADO_CIVIL_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 6 values in `cr-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Unión de hecho	→ Soltero/a

9.10 Occupation

CR_L2_OCUPACION

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The occupation, the profession or the post, as text or as a code of the national classification.

HOW IT IS FOUND

COLUMN NAME	CR_L2_OCUPACION - Path
80%	<code>ocupaci[oó]n profesi[oó]n oficio cocr ciuo (cod codigo)?</code> <code>(ocupacion profesion cocr ciuo) puesto_?(de_)?trabajo categor[ií]a_?ocupacional cargo_?</code> <code>(actual empleado) occupation profession job_?title</code>
50%	<code>cargo puesto</code>

HOW IT IS MASKED

Replaced by another occupation, and a code by another code of the same length. A rare occupation in a small place names a person, which is why this is not left alone.

`CR_OCUPACION_O_CODIGO` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `CR_OCUPACION`.

`CR_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

`CR_OCUPACION` **SECURE LOOKUP**

Replaces the value with one of the 37 values in `cr-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Gerente de operaciones

→ **Teleoperador**

9.11 Employer

CR_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The name of the employer or the patrono, and the place of work.

HOW IT IS FOUND

COLUMN NAME

CR_L2_EMPLEADOR – Path

90%

empleador(_?(nombre|raz[oó]n_?social|cedula))? (nombre|nom)_?(empleador|empresa_?donde_?trabaja|patrono) empresa_?(donde_?)(trabaja|labora) lugar_?(de_?)?trabajo centro_?(de_?)?trabajo patrono(_?nombre)? entidad_?empleadora employer(_?name)? workplace

HOW IT IS MASKED

Replaced by a fictitious Costa Rican company. The employer is not a titular, but it narrows a person to a payroll, which is why the column is masked.

CR_EMPLEADOR

SECURE LOOKUP

Replaces the value with one of the 24 values in `cr-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Corporación Comercial Centroamericana S.A.

→ **Transportes La Meseta S.A.**

9.12 Level of education

CR_L2_NIVEL_EDUCATIVO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The highest level reached, as text or as a code.

HOW IT IS FOUND

COLUMN NAME

CR_L2_NIVEL_EDUCATIVO – Path

80%

escolaridad nivel_?(educativo|de_?estudios|acad[eé]mico|alcanzado|de_?instrucci[oó]n) instrucci[oó]n(_?formal)? grado_?(de_?)(estudio|instrucci[oó]n|escolaridad) m[aá]ximo_? nivel a[ññ]os_?(de_?)?estudio education(_?level)?

KNOWN VALUES

CR_L2_NIVEL_EDUCATIVO – List

LIST

VALUES

STRENGTH

FIRST VALUES

cr-detectar-nivel-
educativo.txt

27

60%

Sin instrucción, Sin instruccin, Preescolar, Primaria incompleta, Primaria completa, Secundaria incompleta

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level of the same list, and a code by another code.

CR_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_NIVEL_EDUCATIVO_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-nivel-educativo-codigos.txt` , chosen by a keyed hash.

CR_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-nivel-educativo.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Educación universitaria en curso

→

Preescolar

9.13 Educational institution

CR_L2_INSTITUCION_EDUCATIVA

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The school, the colegio, the instituto or the university a person attends or attended.

HOW IT IS FOUND

COLUMN NAME

CR_L2_INSTITUCION_EDUCATIVA - Path

75%

`instituci[oó]n_educativa` `centro_?(educativo|de_?estudios)` `escuela` `colegio` `liceo`
`instituto` `universidad` `ina` `(nombre|nom)_?(escuela|colegio|liceo|universidad|institucion_?`
`educativa)` `c[oó]digo_?(de_?)?(escuela|colegio|centro)` `school(_?name)?` `university`

HOW IT IS MASKED

Replaced by another Costa Rican institution. A rural unidocente school has a handful of pupils, so naming it narrows the person almost completely.

CR_INSTITUCION_EDUCATIVA SECURE LOOKUP

Replaces the value with one of the 12 values in `cr-instituciones-educativas.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Universidad de Costa Rica

→

Instituto Nacional de Aprendizaje

9.14 Dependants

CR_L2_PERSONAS_A_CARGO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The number of children, dependants or members of the household.

HOW IT IS FOUND

COLUMN NAME

CR_L2_PERSONAS_A_CARGO - Path

80%

personas_a_cargo n(or|ro|um|umero)_?(de_)?(hijos|dependientes|personas_a_cargo|beneficiarios) cant(idad)?_(hijos|dependientes|personas_hogar|integrantes|miembros) hijos dependientes integrantes_(del_)?hogar personas_(en_el)?hogar tamaño_(del_)?hogar number_of_children dependents

DATA TYPE

CR_L2_PERSONAS_A_CARGO - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Capped at five: a household of eleven is rare enough to identify, and five is enough for any arithmetic a test needs.

CR_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

Sensitive data (art. 3 e and art. 9.1)

Article 9.1 does not regulate these data, it **prohibits** them: "se prohíbe el tratamiento de datos de carácter personal que revelen el origen racial o étnico, opiniones políticas, convicciones religiosas, espirituales o filosóficas, así como los relativos a la salud, la vida y la orientación sexual, entre otros", with five narrow exceptions, and article 31 a) makes processing them a falta gravísima for a private party. A test copy is none of those exceptions, so these columns are replaced within their own vocabulary or suppressed outright. Article 4, second paragraph, adds the reason the attributes the list does not name are here as well: informational self-determination exists "evitando que se propicien **acciones discriminatorias**".

10.1 Racial or ethnic origin

CR_L3_ETNIA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The self-identification the census asks for: indígena, afrodescendiente o negra, mulata, china, blanca o mestiza.

HOW IT IS FOUND

COLUMN NAME CR_L3_ETNIA – Path

95% etnia origen_?([eé]tnico|racial) grupo_?[eé]tnico pertenencia_?[eé]tnica autoidentificaci[oó]n(_?[eé]tnica)? autodefinici[oó]n (cod|codigo|tipo|id)_?etnia raza afrodescendiente afrocostarricense ind[ií]gena ethnicity race

KNOWN VALUES CR_L3_ETNIA – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-etnias.txt	22	90%	Indígena, Indigena, Afrodescendiente o negra, Mulata, China, Blanca o mestiza
cr-detectar-codigos-banderas.txt	12	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside the list, a code by another code and a flag by a flag. Article 3 e) names the **origen racial** and article 9.1 prohibits processing the **origen racial o étnico** outright.

CR_ETNIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_ETNIA_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_ETNIA_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cr-etnias-codigos.txt` , chosen by a keyed hash.

CR_ETNIA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cr-etnias.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Afrodescendiente

→ Ninguna

10.2 Indigenous people and territory

CR_L3_PUEBLO_INDIGENA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The people a person belongs to – bribri, cabécar, maleku, chorotega, huetar, brunca, ngäbe, buglé, teribe – the territorio indígena and the mother tongue. Costa Rica has eight peoples and 24 territorios.

HOW IT IS FOUND

COLUMN NAME CR_L3_PUEBLO_INDIGENA – Path

90%

pueblo_?(ind[ií]gena|originario) territorio_?ind[ií]gena comunidad_?ind[ií]gena adi_
ind[ií]gena lengua_?(ind[ií]gena|materna) idioma_?ind[ií]gena bribri cab[eé]car ngäbe
ngabe maleku chorotega huetar br[uú]nca boruca teribe t[eé]rraba indigenous_
people

KNOWN VALUES CR_L3_PUEBLO_INDIGENA – List

LIST

VALUES

STRENGTH

FIRST VALUES

cr-detectar-pueblos.txt

52

85%

Bribri, Cabécar, Cabecar, Maleku, Chorotega, Huetar

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside its own list. A people counts a few thousand members and a territorio a few hundred, so the two are the sharpest quasi-identifiers in the country and sensitive besides.

CR_PUEBLO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_PUEBLO_LISTA` .

CR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CR_PUEBLO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 11 values in `cr-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Pueblo indígena	→	Cabécar

10.3 Nationality

CR_L3_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

The nationality, the country of birth or of origin, the citizenship.

HOW IT IS FOUND

COLUMN NAME

CR_L3_NACIONALIDAD - Path

85%

`nacionalidad pa[ií]s_?(de_?)(nacimient|origen|nacionalidad|procedencia) ciudadan[ií]a`
`nationality citizenship country_of_birth`

KNOWN VALUES

CR_L3_NACIONALIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

<code>cr-detectar-nacionalidades.txt</code>	47	70%	Costarricense, Nicaragüense, Nicaraguense, Panameña, Panamena, Colombiana
---	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another nationality of the list. The law does not name it, but it sits beside the racial and ethnic origin it does name, and in Costa Rica it separates the nationals from the Nicaraguan community – the attribute on which the "acciones discriminatorias" of article 4 most often turn.

CR_NACIONALIDAD **SECURE LOOKUP**

Replaces the value with one of the 14 values in `cr-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Peruana	→	Costarricense

10.4 Migratory condition

CR_L3_CONDICION_MIGRATORIA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The migratory category the Dirección General de Migración records: residence, special category, refugee, applicant for refuge, work permit, irregular condition.

HOW IT IS FOUND

COLUMN NAME CR_L3_CONDICION_MIGRATORIA - Path

90% `condici[oó]n_?migratoria    estatus_?migratorio    categor[ii]a_?migratoria    situaci[oó]n_?`
`migratoria    tipo_?(de_?)?residencia    residencia_?(permanente|temporal|categoria)    permiso_?`
`(de_?)?(trabajo|residencia|laboral)    refugiad[oa]    solicitante_?(de_?)?refugio    asilo`
`apatrida    visa(_?(n(o|ro|um|umero)|tipo|categoria))?` `migration_?status    immigration_?`
`status`

KNOWN VALUES CR_L3_CONDICION_MIGRATORIA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar- condicion- migratoria.txt	21	70%	Residente permanente, Residente temporal, Categoría especial, Categoría especial, Persona refugiada, Solicitante de refugio

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. Of all the attributes in a Costa Rican database this is the one whose disclosure can cost a person their stay.

CR_CONDICION_MIGRATORIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_CONDICION_MIGRATORIA_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_CONDICION_MIGRATORIA_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `cr-condicion-migratoria.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Residencia en trámite	→ Persona refugiada

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The religion, the creed, the church, the religious or spiritual conviction.

HOW IT IS FOUND

COLUMN NAME CR_L3_RELIGION – Path

95% religi[oó]n creencia_?(religiosa|espiritual) convicci[oó]n(es)?_?(religiosa|espiritual) credo confesi[oó]n_?religiosa culto iglesia(_?(a_?la_?que_?pertenece|nombre))? denominaci[oó]n_?religiosa (cod|codigo|tipo)_?religion religion church

KNOWN VALUES CR_L3_RELIGION – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-religiones.txt	46	90%	Católica, Catolica, Evangélica o protestante, Evangelica o protestante, Testigo de Jehová, Testigo de Jehova

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside the list. Article 3 e) names the **convicciones religiosas o espirituales** and article 9.1 prohibits processing them.

CR_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_RELIGION_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-religiones.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Ortodoxa	→ Otra

10.6 Philosophical convictions

CR_L3_CONVICCION_FILOSOFICA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

A philosophical, moral or ethical conviction, an objection of conscience, membership of a lodge.

HOW IT IS FOUND

COLUMN NAME CR_L3_CONVICCION_FILOSOFICA – Path

90% convicci[oó]n(es)?_?(filos[oó]ficas?|morales?|personales?|[eé]ticas?) creencias?_?
(filos[oó]ficas?|morales?|personales?) objeci[oó]n?(de_)?conciencia objetor?(de_)?
conciencia masoner[ií]a logia beliefs? philosophical_?beliefs?

HOW IT IS MASKED

Suppressed: replaced by "Sin información". Article 9.1 names the **convicciones filosóficas** that article 3 e) leaves out, and its exception b) lets a foundation or association of a philosophical purpose keep the data of its own members – which is the database this domain protects everywhere else.

CR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in cr-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno depresivo recurrente	→	Sin información

10.7 Political opinion

CR_L3_OPINION_POLITICA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The political opinion, the ideology, the leaning, the voting intention.

HOW IT IS FOUND

COLUMN NAME	CR_L3_OPINION_POLITICA - Path		
95%	opini[oó]n?pol[ií]tica preferencias?(pol[ií]tica partidaria electoral) ideolog[ií]a(pol[ií]tica)? orientaci[oó]n?pol[ií]tica tendencia?pol[ií]tica intenci[oó]n?(de_)? voto simpat[ií]a?pol[ií]tica political?(opinion orientation view preference) voting? intention		
KNOWN VALUES	CR_L3_OPINION_POLITICA - List		
LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-preferencias-politicas.txt	16	70%	Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside the list. Article 3 e) and article 9.1 both name the **opiniones políticas**, with no exception that covers a survey kept in a CRM.

CR_PREFERENCIA_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_PREFERENCIA_POLITICA_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_PREFERENCIA_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in cr-preferencias-politicas.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Oficialista	→ Centro

10.8 Party membership

CR_L3_AFILIACION_PARTIDARIA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The party a person adheres to, the militancy, the divisa política. The Tribunal Supremo de Elecciones keeps the register of adhesiones.

HOW IT IS FOUND

COLUMN NAME

CR_L3_AFILIACION_PARTIDARIA - Path

95%

partido(_?pol[ii]tico)?(_?(afiliaci[oó]n|nombre))?

adhesi[oó]n?(partidaria|al_?partido)

afiliaci[oó]n?(pol[ii]tica|partidaria|partido)

militancia(_?pol[ii]tica)?

militante

(cod|codigo|nombre|nom)_?partido

divisa_?pol[ii]tica

political_?party

party_?membership

KNOWN VALUES

CR_L3_AFILIACION_PARTIDARIA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-partidos.txt	26	80%	Liberación Nacional, Liberacion Nacional, Unidad Social Cristiana, Progreso Social Democrático, Progreso Social Democratico, Nueva República

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another party of the register, and a flag kept as a flag. Membership reveals the opinión política, which is what makes it sensitive.

CR_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_PARTIDO_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in cr-partidos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Partido Republicano Social Cristiano	→ Liberal Progresista

10.9 Trade union membership

CR_L3_AFILIACION_SINDICAL

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

The union, the dues deducted from the payroll, the asociación solidarista, the gremio.

HOW IT IS FOUND

COLUMN NAME CR_L3_AFILIACION_SINDICAL – Path

95% `sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))?` `sindicalizado` `afiliado_?sindicato`
`afiliaci[oó]n_?sindical` `cuota_?sindical` `rebajo_?sindical` `aporte_?sindical`
`asociaci[oó]n_?(sindical|solidarista|de_?empleados)` `solidarismo` `gremio` `fuero_?sindical`
`dirigente_?sindical` `trade_?union` `union_?member(ship)?`

KNOWN VALUES CR_L3_AFILIACION_SINDICAL – List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-sindicatos.txt	17	60%	ANEP, APSE, SEC, ANDE, UNDECA, SINAE

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. Article 9.1 b) lets an organization of a **sindical** purpose keep the data of its own members "con tal de que los datos no se comuniquen a terceros sin el consentimiento de las personas interesadas" – which is exactly what a copy sent to a development team does.

CR_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Trastorno depresivo recurrente	→ Sin información

10.10 Biometric data

CR_L3_BIOMETRICO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

A fingerprint and its template, a facial encoding, an iris, a voiceprint, a digitalized signature.

HOW IT IS FOUND

COLUMN NAME CR_L3_BIOMETRICO - Path

90% biometr[ií]a[a-z]* biom[eé]trico[a-z]* huella(_?(dactilar|digital))?(_?(template|plantilla|imagen|hash))? huellas dactilar dactilosc[oó]pic[oa] template_(facial|huella|biometrico) plantilla_?(facial|biom[eé]trica) rostro_(hash|template) reconocimiento_?(facial|de_?voz) firma_?(biom[eé]trica|digitalizada) iris voz_(biom[eé]trica|template) fingerprints? face_(template|hash|encoding) biometric[a-z]*

DATA TYPE CR_L3_BIOMETRICO - Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Replaced by X characters. Article 3 e) names the **información biomédica**, and no exception of article 9.1 covers a template kept for convenience — a biometric cannot be reissued when it leaks.

CR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
clave123	→ XXXXXXXX

10.11 Genetic data

CR_L3_GENETICO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

DNA, a genetic profile, a paternity or filiation test, a mutation, the neonatal screening.

HOW IT IS FOUND

COLUMN NAME CR_L3_GENETICO - Path

90% adn dna gen[eé]tic[oa]s? datos_?gen[eé]ticos? genoma genotip[a-z]* prueba_(gen[eé]tica|de_?adn|de_?paternidad|de_?filiaci[oó]n) perfil_?gen[eé]tico mutaci[oó]n brca[12]? cariotipo tamizaje_?neonatal genetic[a-z]*

HOW IT IS MASKED

Replaced by X characters. Article 3 e) names **información biomédica o genética** in one breath, and a genetic datum identifies relatives who were never asked.

CR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

clave123

→

XXXXXXXX

10.12 Sexual orientation

CR_L3_ORIENTACION_SEXUAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The sexual orientation as the system records it.

HOW IT IS FOUND

COLUMN NAME

CR_L3_ORIENTACION_SEXUAL - Path

95%

orientaci[oó]n?sexual preferencias?_?sexuales? (cod|codigo|tipo)?orientacion?sexual sexual?orientation

KNOWN VALUES

CR_L3_ORIENTACION_SEXUAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

cr-detectar-orientaciones-sexuales.txt

14

80%

Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside the list. Article 3 e) and article 9.1 both name the **orientación sexual**.

CR_ORIENTACION_SEXUAL

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_ORIENTACION_SEXUAL_LISTA .

CR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_ORIENTACION_SEXUAL_LISTA

SECURE LOOKUP

Replaces the value with one of the 8 values in cr-orientaciones-sexuales.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Homosexual

→ Pansexual

10.13 Sexual life

CR_L3_VIDA_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Sexual activity, conduct, practices, number of partners, the age at which sexual life began.

HOW IT IS FOUND

COLUMN NAME

CR_L3_VIDA_SEXUAL – Path

90%

vida_?sexual actividad_?sexual conducta_?sexual pr[aá]cticas?_?sexuales? parejas?_? sexuales? n(o|ro|um|umero)_?parejas sexualmente_?activ[oa] inicio_?(de_?)(la_?)?vida_? sexual relaciones_?sexuales sex(ual)?_?life sexual?(activity|behavio(u)?r|partners)

HOW IT IS MASKED

Suppressed. Article 3 e) names the **vida** as well as the **orientación sexual**, and article 9.1 repeats it.

CR_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in cr-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno depresivo recurrente

→ Sin información

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The gender identity, the social name, the pronouns. Since 2018 a person may change the name and the sex marker of the cédula, so this is a real column in Costa Rican systems.

HOW IT IS FOUND

COLUMN NAME

CR_L3_IDENTIDAD_GENERO - Path

95% identidad?(de_)?g[eé]nero (cod|codigo|tipo)?identidad?genero g[eé]nero? (autopercibido|identitario) expresi[oó]n?de?g[eé]nero transg[eé]nero persona?trans nombre?social pronombres? gender?identity

KNOWN VALUES

CR_L3_IDENTIDAD_GENERO - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-identidades-genero.txt	19	70%	Mujer cisgénero, Mujer cisgenero, Hombre cisgénero, Hombre cisgenero, Mujer trans, Hombre trans

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside its own list. The list of article 3 e) is open — "entre otros" — and article 4 asks that the data not propitiate discriminatory actions.

CR_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_IDENTIDAD_GENERO_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in cr-identidades-genero.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Transgénero	→ Hombre trans

10.15 Victim of violence

CR_L3_VICTIMA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The condition of victim, the kind of violence, a protection measure, a PANI case.

HOW IT IS FOUND

COLUMN NAME CR_L3_VICTIMA – Path

90%
v[ií]ctima(_?(de_)?(violencia(_?(de_)?
g[eé]nero|dom[eé]stica|intrafamiliar|sexual|psicol[oó]gica|patrimonial))?
|delito|trata|abuso|desaparici[oó]n)? violencia_?(de_)?g[eé]nero violencia_
(dom[eé]stica|intrafamiliar|sexual|psicol[oó]gica) tipo_?(de_)?violencia medida_?(de_)?
protecci[oó]n boleta_?(de_)?violencia trata_?(de_)?personas denunciante_?violencia
pani_?(caso|expediente)

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. The Ley 8589 de penalización de la violencia contra las mujeres and the Ley 9095 against the trafficking of persons both protect the identity of the victim.

CR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR SECURE LOOKUP
Replaces the value with one of the 1 values in cr-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno depresivo recurrente	→	Sin información

Health data (art. 9.1 d)

Health is among the data article 9.1 prohibits, and its exception d) draws the only door: processing is allowed when it is necessary for prevention, medical diagnosis, health care or the management of health services, and then only by a health worker bound to professional secrecy "o por otra persona sujeta, asimismo, a una obligación equivalente de secreto". A test environment is nobody's health care, and whoever restores the dump is under no such obligation. Article 2 c) of the Ley 8239 de derechos de las personas usuarias de los servicios de salud guarantees the confidentiality of the expediente, which the CCSS keeps for the whole country in the EDUS.

11.1 Clinical record number

CR_SALUD_IDENTIFICADOR

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The number of the expediente clínico, of the EDUS record, of an episode, an admission, a consultation or a prescription.

HOW IT IS FOUND

COLUMN NAME	CR_SALUD_IDENTIFICADOR – Path
85%	<code>n(o ro um umero)?(expediente?(cl[ií]nico de_salud m[eé]dico) hc ficha(_?cl[ií]nica)? episodio ingreso atenci[oó]n consulta cita receta) expediente?(cl[ií]nico digital [uú]nico m[eé]dico salud) edus[a-z0-9_]* arca sics id_paciente c[ó]digo?(paciente expediente atenci[oó]n)</code>
55%	<code>expediente atenci[oó]n ingreso consulta episodio</code>

HOW IT IS MASKED

Character by character, keeping the shape. The number is a pseudonym for a patient, and it is usually built from the cédula.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
A1234567	→ U2438404

11.2 Health coverage

CR_SALUD_COBERTURA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

How a person is insured: asegurado directo asalariado or cuenta propia, voluntario, por el Estado, pensionado of the IVM or of the RNC, familiar, a private policy, or not insured at all.

HOW IT IS FOUND

COLUMN NAME	CR_SALUD_COBERTURA - Path		
85%	cobertura(_?(m[eé]dica de_?salud asistencial))? seguro_?(m[eé]dico salud sem) r[eé]gimen(_?(de_?)?(aseguramiento salud pensiones ivm rnc))? tipo_?(de_?)? (seguro cobertura asegurado) modalidad_?(de_?)?aseguramiento ccss_?(regimen cobertura) aseguradora_?(m[eé]dica salud) plan_?(m[eé]dico de_?salud) ins_?(poliza seguro)		
KNOWN VALUES	CR_SALUD_COBERTURA - List		
LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-cobertura.txt	21	80%	Asegurado directo asalariado, Asegurado directo cuenta propia, Asegurado voluntario, Asegurado por el Estado, Pensionado (IVM), Pensionado (RNC)
A value that matches none counts 40% against the domain.			

HOW IT IS MASKED

Replaced inside its own list, and a numeric code by another code. The régimen says more than it looks: "asegurado por el Estado" is a statement about the person's **condición socioeconómica**, which article 3 e) calls sensitive.

CR_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_COBERTURA .

CR_BANDERA	REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.	
CR_BANDERA_SI_NO	SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.	
CR_BANDERA_TRUE_FALSE	SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.	
CR_BANDERA_YES_NO	SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.	
CR_BANDERA_S_N	SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.	
CR_BANDERA_Y_N	SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.	
CR_BANDERA_0_1	SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.	
CR_CM_DIGITOS	CHARACTER MAPPING
Maps each character to another of its group (1 groups), keeping length and format.	
CR_COBERTURA	SECURE LOOKUP
Replaces the value with one of the 10 values in cr-cobertura-salud.txt , chosen by a keyed hash.	

EXAMPLES

VALUE	MASKED
Asegurado por el Estado	→ Seguro privado

11.3 Diagnosis

CR_SALUD_DIAGNOSTICO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The diagnosis as an ICD-10 code or as text, the cause of death, the reason for a consultation or an incapacidad, allergies and comorbidities.

HOW IT IS FOUND

COLUMN NAME

CR_SALUD_DIAGNOSTICO - Path

85%

```
diagn[oó]stico[a-z_]* dx(?:principal|secundario|ingreso|egreso)[0-9]? cie_?10 cie(?:
(10|11|principal))? (cod|codigo)?(diagnostico|dx|cie) impresi[oó]n?diagn[oó]stica
enfermedad(es)?[a-z_]* patolog[ií]a comorbilidad(es)? antecedentes?_?
(m[eé]dicos|patol[oó]gicos|cl[ií]nicos|personales) causa?(de_)?
(muerte|defunci[oó]n|incapacidad|internamiento|consulta) motivo?(de_)?
(consulta|incapacidad|internamiento) alergias? diagnos(is|es) icd?(10|11)?
```

VALUE FORMAT

CR_SALUD_DIAGNOSTICO - Regex

PATTERN

STRENGTH

NOTES

[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d|X)?

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another code of the same shape and a text diagnosis another common diagnosis. The column still looks like a diagnosis column and no longer says what a person has.

CR_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CR_DIAGNOSTICO_TEXT0 .

CR_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 34 values in cr-cie10-decimal.txt , chosen by a keyed hash.

CR_CIE10 SECURE LOOKUP

Replaces the value with one of the 38 values in cr-cie10.txt , chosen by a keyed hash.

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_DIAGNOSTICO_TEXT0 SECURE LOOKUP

Replaces the value with one of the 31 values in cr-diagnosticos.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

F33.1

→

N39.0

Depresión mayor

→

Obesidad

11.4 Procedure

CR_SALUD_PROCEDIMIENTO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The procedure, the prestación, the surgery or the examination ordered, as a code or as text.

HOW IT IS FOUND

COLUMN NAME

CR_SALUD_PROCEDIMIENTO - Path

85%

```
procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado))? (cod|codigo)?
(procedimiento|prestaci[oó]n|servicio_?salud) prestaci[oó]n?(m[eé]dica|de_?salud) examen_?
(ordenado|realizado) cirug[ií]a(_?realizada)? intervenci[oó]n?quir[uú]rgica t[eé]cnica_?
(diagn[oó]stica|quir[uú]rgica) medical_?procedure
```

HOW IT IS MASKED

A code gets other digits of the same length and text becomes another common procedure. Some procedures name a diagnosis on their own, which is why they are not left alone.

CR_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

CR_PROCEDIMIENTO_TEXTO

CR_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_PROCEDIMIENTO_TEXTO

SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-procedimientos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Prueba de carga viral para VIH

→

Hemograma completo

11.5 Medicine

CR_SALUD_MEDICAMENTO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The medicine prescribed or dispensed, the active ingredient, the LOM code, the posology.

HOW IT IS FOUND

COLUMN NAME

CR_SALUD_MEDICAMENTO - Path

85%

```
medicamentos?(_?(recetado|prescrito|entregado|despachado|nombre|uso))? f[aá]rmacos?
principio_?activo denominaci[oó]n_?com[uú]n_?internacional dci receta(_?m[eé]dica)?
prescripci[oó]n(_?medicamento)? posolog[ií]a tratamiento_?farmacol[oó]gico (cod|codigo)?
medicamento lista_?oficial_?de_?medicamentos lom medications? drugs?_?prescribed
```

KNOWN VALUES CR_SALUD_MEDICAMENTO - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar- medicamentos.txt	52	70%	Acetaminofén, Acetaminofen, Ibuprofeno, Diclofenaco, Metformina, Glibenclamida

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another medicine of the list. A medicine is a diagnosis written backwards: an antiretroviral or an antipsychotic says what the diagnosis column was masked for.

CR_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_MEDICAMENTO_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 22 values in `cr-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Sertralina 50 mg	→ Complejo B

11.6 Clinical notes

CR_SALUD_TEXTO_CLINICO

COLUMN NAME DATA TYPE FREE TEXT REDACTION

WHAT IT IS

The anamnesis, the evolución, the physical examination, the plan, the epicrisis, a radiology or pathology report.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_TEXTO_CLINICO - Path

85% anamnesis evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))? enfermedad_?actual
examen_?f[ií]sico plan_?(de_)?(manejo|tratamiento) indicaciones_?m[eé]dicas conducta(_?
m[eé]dica)? epicrisis resumen_?(de_)?(alta|egreso|atenci[oó]n) nota_?(m[eé]dica|de_?
enfermer[ií]a|cl[ií]nica) notas_?(m[eé]dicas|cl[ií]nicas) triaje(_?texto)? informe_?
(patolog[ií]a|radiolog[ií]a|m[eé]dico) clinical_?notes? discharge_?summary

DATA TYPE CR_SALUD_TEXTO_CLINICO - Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The prose is kept and the identifiers inside it are redacted, the same way as any free text: the clinical reasoning survives for a test, the patient does not.

CR_TEXTO_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with [DATO], and the 1,944 terms of cr-texto-nombres.txt with [NOMBRE].

EXAMPLES

VALUE

MASKED

Cliente Jiménez, cédula 1-0234-0567, correo
j.jimenez@gmail.com, cel 83124567

→ Cliente [NOMBRE], cédula [DATO], correo
[DATO], cel [DATO]

11.7 Test result

CR_SALUD_RESULTADO_EXAMEN

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

The result of a laboratory test, a serology, a biopsy, a glycaemia, a blood pressure, an alcoholiaemia.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_RESULTADO_EXAMEN - Path

80% resultado_?(del_)?
(examen|prueba|an[aá]lisis|laboratorio|pcr|serolog[ií]a|biopsia|glicemia|citolog[ií]a|papanico
laou|vdrl) (examen|prueba|an[aá]lisis)_?(resultado|laboratorio) glicemia hemoglobina(_?
glicosilada)? hba1c colesterol imc presi[oó]n_?arterial test_?(de_)?embarazo
espirometr[ií]a alcoholemia lab_?results? test_?results?

50% resultado prueba analisis

HOW IT IS MASKED

Character by character, keeping the shape so that units and ranges still parse. A single reactive result is a diagnosis.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

A1234567

→ U2438404

11.8 HIV and sexually transmitted infections

CR_SALUD_VIH

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The serological status, the viral load, the CD4 count, the antiretroviral treatment, syphilis, hepatitis, tuberculosis.

HOW IT IS FOUND

COLUMN NAME

CR_SALUD_VIH - Path

90%

vih(_?(estado|resultado|prueba|diagn[ó]stico|positivo))? hiv sida aids serolog[ií]a?
(vih|hiv) estado_?serol[ó]gico carga_?viral cd4 tar antirretroviral(es)? its ets
infecci[ó]n(es)?_?(de_)?transmisi[ó]n_?sexual s[ií]filis hepatitis_?[bc] tuberculosis
tbc

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. The **Ley 7771 General sobre el VIH-SIDA** makes the condition confidential and its disclosure an offence of its own, beyond article 9.1.

CR_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in cr-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno depresivo recurrente

→ Sin información

11.9 Blood group

CR_SALUD_GRUPO_SANGUINEO

COLUMN NAME KNOWN VALUES SECURE LOOKUP

WHAT IT IS

The ABO group and the Rh factor.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_GRUPO_SANGUINEO - Path

90% grupo_?sangu[ií]neo tipo_?(de_)?sangre rh factor_?rh gs_?rh grupo_?rh abo(_?rh)?
blood_?(type|group)

KNOWN VALUES CR_SALUD_GRUPO_SANGUINEO - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-grupos-sanguineos.txt	18	90%	A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another group. It is a weak identifier on its own and a health datum all the same, and a rare group in a small place narrows a person.

CR_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in cr-grupos-sanguineos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
0+	→ A-

11.10 Disability

CR_SALUD_DISCAPACIDAD

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The kind, the degree or the certificate of a disability. The Ley 7600 de igualdad de oportunidades and the Ley 9379 that created CONAPDIS both build registers of it.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_DISCAPACIDAD - Path

90% discapacidad[a-z_]* (tipo|cod|codigo|categoria|porcentaje|grado)?discapacidad persona_?
con_?discapacidad pcd certificado_?(de_)?discapacidad conapdis condici[oó]n_?(de_)?
discapacidad necesidades_?(educativas_)?especiales movilidad_?reducida ley_?7600
disabilit(y|ies)

KNOWN VALUES CR_SALUD_DISCAPACIDAD - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-discapacidades.txt	24	60%	Física o motora, Física o motora, Auditiva, Visual, Intelectual, Psicosocial

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. A rare disability in a small distrito names the person as surely as the cédula.

CR_DISCAPACIDAD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_DISCAPACIDAD_LISTA .

CR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CR_DISCAPACIDAD_LISTA **SECURE LOOKUP**

Replaces the value with one of the 7 values in `cr-discapacidades.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno del espectro autista

→ **Psicosocial**

11.11 Occupational health

CR_SALUD_OCUPACIONAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Fitness for work, the pre-employment or periodic examination, an accident at work, an occupational disease, an incapacidad and its days.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_OCUPACIONAL - Path

85%

```
aptitud_?(laboral|m[eé]dica) certificado_?(de_?)?aptitud examen_?(m[eé]dico_?)?
(ocupacional|preocupacional|de_?ingreso|de_?egreso|peri[ód]dico) accidente_?(de_?)?trabajo
riesgos?_?(del_?)?trabajo enfermedad_?(laboral|profesional|ocupacional) incapacidad(_?
(m[eé]dica|laboral|d[ií]as))? boleta_?(de_?)?incapacidad d[ií]as_?(de_?)?incapacidad
licencia_?(m[eé]dica|por_?maternidad) ausentismo
```

KNOWN VALUES CR_SALUD_OCUPACIONAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-aptitud-laboral.txt	5	60%	apto, no apto, apto con restricciones, pendiente, apto con recomendaciones

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced inside its own list. The boleta de incapacidad of the CCSS travels with a diagnosis, which is why a personnel table holds health data without meaning to.

CR_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_APTITUD_LABORAL_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in cr-aptitud-laboral.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
No apto temporalmente	→ Pendiente

11.12 Reproductive health

CR_SALUD_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy and its weeks, the prenatal control, the delivery, the interruption, contraception, fertility.

HOW IT IS FOUND

COLUMN NAME	CR_SALUD_REPRODUCTIVA – Path
90%	<code>embarazo</code> <code>embarazada</code> <code>gestante</code> <code>gestaci[oó]n</code> <code>edad_?gestacional</code> <code>semanas_?(de_)?</code> <code>gestaci[oó]n</code> <code>fum</code> <code>fecha_?[uú]ltima_?(regla menstruaci[oó]n)</code> <code>control_?</code> <code>(prenatal obst[eé]trico)</code> <code>prenatal</code> <code>parto(_?tipo)?</code> <code>ces[aá]rea</code> <code>interrupci[oó]n_?(del_)?</code> <code>embarazo</code> <code>aborto</code> <code>m[eé]todo_?(de_)?anticoncepci[oó]n</code> <code>planificaci[oó]n_?familiar</code> <code>anticoncepci[oó]n</code> <code>anticonceptivo</code> <code>fertilidad</code> <code>fecundaci[oó]n_?in_?vitro</code> <code>salud_?</code> <code>(sexual reproductiva)</code> <code>pregnan(t cy)</code> <code>contracepti(on ve)</code>

HOW IT IS MASKED

Suppressed, and a flag kept as a flag. It is health data under article 9.1 and it sits next to the vida sexual of article 3 e).

CR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt` , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt` , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt` , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt` , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt` , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt` , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Trastorno depresivo recurrente	→ Sin información

11.13 Mental health

CR_SALUD_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

A mental health diagnosis or follow-up, a suicide attempt, self-harm, the consumption of substances, an addiction, an IAFA record.

HOW IT IS FOUND

COLUMN NAME CR_SALUD_MENTAL – Path

90% salud_?mental trastorno[a-z]* psiqui[aá]tri[a-z]* psicol[oó]gi[a-z]* depresi[oó]n
ansiedad suicid[a-z]* intento_?(de_)?suicidio autolesi[oó]n consumo_?(de_)?
(sustancias|alcohol|drogas) adicci[oó]n(es)? alcoholismo tabaquismo iaafa mental_
health

HOW IT IS MASKED

Suppressed. It is health data, and of all health data it is the one whose disclosure costs a person a job, a custody or a policy.

CR_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

CR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

CR_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in cr-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno depresivo recurrente

→ Sin información

Economic data (art. 3 e, art. 1 and art. 9.4)

Costa Rica is the only country of the region whose law names the **condición socioeconómica** among the sensitive data of article 3 e), beside racial origin and religious convictions. Article 1 extends the law to the data of a person's **bienes**, and article 9.4 sends credit behaviour to the rules of the Sistema Financiero Nacional — where the SUGEF keeps the Centro de Información Crediticia — "sin impedir el pleno ejercicio del derecho a la autodeterminación informativa ni exceder los límites de esta ley". Amounts keep their order of magnitude so that totals and ratios still behave; what they stop doing is naming a salary.

12.1 Credit standing

CR_FIN_HISTORIAL_CREDITICIO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The SUGEF category — A1, A2, B1, B2, C1, C2, D, E —, the CIC record, a score, the days in arrears, the state of a collection.

HOW IT IS FOUND

COLUMN NAME

CR_FIN_HISTORIAL_CREDITICIO – Path

90%

```
historial_?(crediticio|de_?cr[eé]dito)  cic(_?sugef)?  centro_?(de_?)?informaci[oó]n_?
crediticia  sugef(_?(categoria|calificacion))?  central_?(de_?)?riesgos?  bur[oó]_(de_?)?
cr[eé]dito  protectora_?(de_?)?cr[eé]dito  score(_?(crediticio|interno))?  puntaje_?(de_?)?
cr[eé]dito  calificaci[oó]n_?(de_?)?(riesgo|cr[eé]dito|cartera|deudor)  categor[ií]a_?
(sugef|de_?riesgo)  d[ií]as_?(de_?)?(mora|atraso)  estado_?(de_?)?
(cr[eé]dito|cartera|obligaci[oó]n)  morosidad  moroso  cobro_?judicial  credit_?score
credit_?rating
```

HOW IT IS MASKED

A category becomes another category, a score other digits and a flag a flag. Article 9.4 sends this data to the rules of the Sistema Financiero Nacional without taking it out of the law.

CR_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CR_ESTADO_CREDITO .

CR_CATEGORIA_SUGEF SECURE LOOKUP

Replaces the value with one of the 8 values in `cr-categorias-sugef.txt`, chosen by a keyed hash.

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-si-no.txt`, chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-true-false.txt`, chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-yes-no.txt`, chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-s-n.txt`, chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-bandera-y-n.txt`, chosen by a keyed hash.

CR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `cr-bandera-0-1.txt`, chosen by a keyed hash.

CR_ESTADO_CREDITO **SECURE LOOKUP**

Replaces the value with one of the 13 values in `cr-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
En cobro judicial	→	Categoría A2 – riesgo normal
A1	→	A2

12.2

Debt

CR_FIN_DEUDA

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

The balance of a debt, a loan or a card, the instalment, the credit limit.

HOW IT IS FOUND

COLUMN NAME

CR_FIN_DEUDA – Path

85%

`saldo_?(deuda|cr[eé]dito|capital|obligaci[oó]n|cartera|en_?mora|adeudado) monto_?(de_?la_?)?`
`(deuda|cuota|obligaci[oó]n|cr[eé]dito|pr[eé]stamo|mora|otorgado) deuda(_?total)?`
`l[ií]mite_?(de_?)?(cr[eé]dito|tarjeta) l[ií]nea_?(de_?)?cr[eé]dito cuota_?mensual loan_?`
`(amount|balance) outstanding_?balance debt`

DATA TYPE

CR_FIN_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Another amount of the same order of magnitude, from fifty thousand to sixty million colones, so totals and ratios still behave.

CR_VALOR_DEUDA

NUMERIC MAPPING

Maps the number to another between 50,000 and 60,000,000.

EXAMPLES

VALUE		MASKED
2400000	→	7834212

12.3

Income

CR_FIN_INGRESOS

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

The salary, gross or net, the fees, the declared income, the income per person of the household.

HOW IT IS FOUND

COLUMN NAME CR_FIN_INGRESOS – Path

85% sueldo(_?(bruto|neto|mensual|base|ordinario))? salario(_?(bruto|neto|mensual|base|m[ií]nimo|escolar))? remuneraci[ó]n(_?mensual)? ingresos?(_?(mensuales?|totales?|familiares?|declarados?|netos?|brutos?))? haberes honorarios renta(_?(bruta|neta|mensual|anual))? ingreso?(_?(base|familiar|per_?capita) salary income wages?

DATA TYPE CR_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Another amount between the minimum wage and six million colones a month. This is where Costa Rica differs from its neighbours: article 3 e) names the **condición socioeconómica** among the sensitive data, so an income column is not merely commercial.

CR_INGRESOS **NUMERIC MAPPING**

Maps the number to another between 360,000 and 6,000,000.

EXAMPLES

VALUE	MASKED
780000	→ 693756

12.4 Assets

CR_FIN_PATRIMONIO

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

The patrimony, the assets, the fiscal or commercial value of a property or a vehicle, the balance of an account or an investment, a sworn declaration of assets.

HOW IT IS FOUND

COLUMN NAME CR_FIN_PATRIMONIO – Path

85% patrimonio(_?(neto|l[ií]quido|fiscal))? activos?(_?(totales?))? valor?(_?(del_?))?(inmueble|finca|veh[ií]culo|bienes|tasaci[ó]n|fiscal|comercial) tasaci[ó]n valor?(fiscal|catastral) saldo?(cuenta|ahorro|dep[ó]sito|inversi[ó]n|fondo) certificado?(de_)?dep[ó]sito inversiones declaraci[ó]n?(jurada_)?(de_)?(bienes|patrimonio) net? worth account_?balance

DATA TYPE CR_FIN_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Another amount of the same order of magnitude. Article 1 of the law reaches the data of a person "o **bienes**", which puts this column inside it by the plain words of the statute.

CR_PATRIMONIO **NUMERIC MAPPING**

Maps the number to another between 1,000,000 and 500,000,000.

EXAMPLES

VALUE

MASKED

48000000

→

91760294

12.5 Pension

CR_FIN_PENSION

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

The amount of a pension or a subsidy: the IVM, the Régimen No Contributivo, an alimony, a disability pension.

HOW IT IS FOUND

COLUMN NAME

CR_FIN_PENSION – Path

90%

```
jubilaci[oó]n(_?(monto|mensual|valor))? pensi[oó]n(_?
(monto|mensual|valor|alimentaria|alimenticia|por_?invalides|por_?vejez))? monto_?
(jubilaci[oó]n|pensi[oó]n|beneficio|subsidio) valor_?(pensi[oó]n|subsidio|beneficio) rnc(_?
monto)? ivm(_?monto)? r[eé]gimen_?no_?contributivo pension_?amount
```

DATA TYPE

CR_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Another amount of the same order. A pension of the Régimen No Contributivo says the person is poor, a pension by disability says the person has one.

CR_VALOR_PENSION

NUMERIC MAPPING

Maps the number to another between 150,000 and 2,500,000.

EXAMPLES

VALUE

MASKED

420000

→

646464

12.6 Social programme

CR_FIN_PROGRAMA_SOCIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Membership of a programme: Avancemos, Crecemos, the bono de vivienda of the BANHVI, the Red de Cuido, a FONABE scholarship, an IMAS benefit, the Régimen No Contributivo.

HOW IT IS FOUND

COLUMN NAME

CR_FIN_PROGRAMA_SOCIAL – Path

90%

```
programa_?social beneficiario_(programa|subsidiobeca|bono|prestaci[oó]n) avancemos
crecemos bono_(de_)?vivienda banhvi fonabe beca_(fonabe|mep|estudiantil) red_?
(de_)?cuido comedor_?escolar imas[a-z0-9]* sinirube transferencia_?monetaria ayuda_?
(social|estatal) subsidio(_?estatal)? social_?programme
```

KNOWN VALUES CR_FIN_PROGRAMA_SOCIAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-programas-sociales.txt	20	80%	Avancemos, Crecemos, Bono de vivienda (BANHVI), Red de Cuido, Pensión del Régimen No Contributivo, Pension del Regimen No Contributivo
cr-detectar-codigos-banderas.txt	12	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. The SINIRUBE joins the registers of every programme, so a single row of it states the condición socioeconómica of a household.

CR_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_PROGRAMA_SOCIAL_LISTA

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt, chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt, chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt, chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt, chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt, chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt, chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in cr-programas-sociales.txt, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Subsidio estatal	→ Beca FONABE

12.7 Condición socioeconómica

CR_FIN_CONDICION_SOCIOECONOMICA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The classification of the IMAS or the SINIRUBE — pobreza extrema, pobreza básica, vulnerabilidad, no pobre —, the score of the ficha de información social, the quintile, the índice de desarrollo social.

HOW IT IS FOUND

COLUMN NAME

CR_FIN_CONDICION_SOCIOECONOMICA - Path

90%

condici[oó]n?socioecon[oó]mica

nivel?socioecon[oó]mico

nse

estrato?socioecon[oó]mico

clasificaci[oó]n?(socioecon[oó]mica|imas|sinirube)

puntaje?(imas|sinirube|ficha)

ficha_?

(de_)?informaci[oó]n?social

fis

l[ií]nea?(de_)?pobreza

condici[oó]n?(de_)?pobreza

pobreza(_?extrema)?

vulnerabilidad

quintil(_?(de_)?(ingreso|riqueza))?

decil

[ií]ndice?(de_)?desarrollo?social

KNOWN VALUES

CR_FIN_CONDICION_SOCIOECONOMICA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-condicion-socioeconomica.txt	24	60%	Pobreza extrema, Pobreza básica, Pobreza basica, Vulnerabilidad, No pobre, Quintil 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced inside its own list, a code by another code. This domain carries the law’s own phrase: article 3 e) lists the **condición socioeconómica** as a sensitive datum, in the same sentence as racial origin and religious conviction, which no other law of the region does.

CR_CONDICION_SOCIOECONOMICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_CONDICION_SOCIOECONOMICA_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CONDICION_SOCIOECONOMICA_CODIGO SECURE LOOKUP

Replaces the value with one of the 5 values in cr-condicion-socioeconomica-codigos.txt , chosen by a keyed hash.

CR_CONDICION_SOCIOECONOMICA_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in cr-condicion-socioeconomica.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Pobreza extrema	→ Pobreza básica

12.8 Housing tenure

CR_FIN_VIVIENDA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

How the household holds the dwelling: owned, paying in instalments, rented, in precario, lent.

HOW IT IS FOUND

COLUMN NAME

CR_FIN_VIVIENDA - Path

90%

tenencia_(de_)?(la_)?vivienda tipo_(de_)?tenencia vivienda_(propia|alquilada|tipo_?tenencia) condici[ó]n_(de_)?(la_)?vivienda ocupaci[ó]n_vivienda r[eé]gimen_(de_)?tenencia tugurio precario housing_tenure

KNOWN VALUES

CR_FIN_VIVIENDA - List

LIST	VALUES	STRENGTH	FIRST VALUES
cr-detectar-tenencia-vivienda.txt	13	60%	Propia totalmente pagada, Propia pagando a plazos, Alquilada, En precario, Cedida o prestada, Otra

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced inside its own list. "En precario" is a statement about poverty, which article 3 e) calls sensitive.

CR_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_TENENCIA_VIVIENDA_LISTA .

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in cr-tenencia-vivienda.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Vivienda en precario	→ Propia totalmente pagada

Criminal records (art. 8 c and Ley 6723)

Article 8 c) lets the principles of the law be limited for "la prevención, persecución, investigación, detención y represión de las infracciones penales" — a limit written for the authorities, not for whoever copies their tables. Article 11 of the **Ley 6723 del Registro y Archivos Judiciales**, as reformed by the **Ley 10453 of 4 March 2024**, cancels an entry on a scale that runs from the end of the sentence to ten years after it, and a certification issued for employment shows only what is still current. A non-production copy keeps the entry for as long as the copy lives, which is longer than any of those terms.

13.1 Criminal record

CR_PENAL_ANTECEDENTES

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The hoja de delincuencia, the juzgamientos of the Registro Judicial, a conviction, a kind of offence, a precautionary measure, deprivation of liberty.

HOW IT IS FOUND

COLUMN NAME	CR_PENAL_ANTECEDENTES – Path
95%	antecedentes?(_(penales policiales judiciales))? hoja_(de_)?delincuencia certificado_(de_)?antecedentes?(penales)? registro?judicial juzgamientos? reincidencia condena(?(penal tipo))? delito(?(tipo cometido))? tipo?(de_)?delito situaci[ó]n? (jur[ii]dica procesal) medida?cautelar privad[oa]_(de_)?libertad centro?penal adaptaci[ó]n?social criminal?record
55%	estado?(del_)?proceso sentencia fallo

HOW IT IS MASKED

Replaced inside its own list, and a flag kept as a flag. Article 11 of the Ley 6723, reformed by the Ley 10453 of 2024, cancels an entry on a scale from the end of the sentence to ten years after it; a copy that lives longer than that keeps an entry the register itself has erased.

CR_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_ANTECEDENTES_LISTA .

CR_BANDERA REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
CR_BANDERA_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.
CR_BANDERA_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.
CR_BANDERA_YES_NO SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.
CR_BANDERA_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.
CR_BANDERA_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.
CR_BANDERA_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

CR_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Condenado por hurto en 2019

→

Sentencia absolutoria

13.2 Judicial file number

CR_PENAL_EXPEDIENTE

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The number the Poder Judicial gives a case: the year, a correlative, the office and the matter, `24-001234-0007-PE`.

HOW IT IS FOUND

COLUMN NAME

CR_PENAL_EXPEDIENTE - Path

90%

```
n(o|ro|um|umero)?(de_)?(expediente?(judicial|penal|fiscal)|causa|proceso?(judicial|penal)|denuncia|sumaria) expediente?(judicial|penal|fiscal) causa?penal
n(o|ro|um|umero)?(de_)?(carpeta|legajo)?(fiscal|judicial) n(o|ro|um|umero)?[uú]nico?(de_)?expediente oij?(caso|expediente)
```

50%

expediente causa proceso sumaria

VALUE FORMAT

CR_PENAL_EXPEDIENTE - Regex

PATTERN

STRENGTH

NOTES

`\d{2}-\d{6}-\d{4}-[A-Z]{2,4}`

90%

`\d{2}-\d{6}-\d{4}`

70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The correlative changes and the year, the office and the matter stay, so the file still looks like a file and no longer opens a public record. The file is searchable by number, which is what makes it an identifier.

CR_EXPEDIENTE_JUDICIAL REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

24-001234-0007-PE

→

24-029817-0007-PE

12-000456-0164-CI

→

12-459518-0164-CI

The IBAN check digits

Costa Rica is unusual in that **none of its identity numbers carries a check digit**: the cédula de identidad, the DIMEX, the NITE and the cédula jurídica are all validated against a register rather than by arithmetic. The Dirección General de Tributación checks a cédula against the Registro Civil in real time. So nothing in this set has to recompute an identity digit — and the whole number can change, which is why even the provincia digit of a cédula is masked.

The **IBAN** is the one place where arithmetic matters, and it matters everywhere: since 2017 every Costa Rican account is an IBAN, SINPE moves on it, and any library that touches one validates it. The rule is ISO 13616: move the first four characters to the end, read **C** as 12 and **R** as 27, and the resulting number must leave a remainder of **1 modulo 97**. The BCCR's own example, CR05 0152 0200 1026 2840 66, does.

No masking framework computes a remainder modulo 97, and the Check Digit algorithm writes one character where these are two. So the set computes it with lookup tables. A **two-digit state** — the remainder so far — is put where the old check digits were, and travels right through the number one character at a time; each step is a Data Cleansing that turns "state + character" into "character + new state", from a table of 1,067 lines, one for every pair of a remainder and a digit. At the right end a table of 97 lines turns the remainder into the check digits, by the formula $98 - (r \cdot 10^6 + 1227 \cdot 100) \bmod 97$. A second traveller then carries the two digits back to the front.

CR and the spaces of the printed form wait as one-character markers while this happens, and are written back at the end, so the compact form and the form printed in groups of four both come out as they went in — valid, with their bank, and with an account that belongs to nobody.

Where people live: distritos, cantones and the code that is also the postal code

Costa Rica is divided into 7 provincias, 84 cantones and 492 distritos, and the distritos are small: **413 of the 492 hold fewer than 20,000 inhabitants**, some 2.68 million people — more than half the country — and the smallest hold a few hundred. A birth date, a sex and one of those distritos point at a handful of people.

So a distrito below the threshold becomes the nearest distrito of at least 20,000 **in the same cantón**, measured between their centres; when the cantón has none, the nearest one in the same provincia. The cantones follow the same rule one level up — 15 of the 84 are below the threshold — and the 7 provincias stay, so a generalized value never leaves its provincia and a provincia column is never rewritten.

Costa Rica is full of homonyms: 179 of the 492 distritos share a name with another place, and there are distritos called San Rafael, San Isidro and San José in province after province. A name is generalized only when **every** place that bears it is small, to the fate of the most populous; 91 small distritos keep their own name because a homonym of theirs is large. Written with the cantón or the provincia beside it — Matambú — Hojancha, in any of five ways systems write that — the same rule applies inside the qualifier, which is how a small distrito is reached even when its bare name has to be left alone.

The codes follow the names, and here Costa Rica gives something no other country in the region does: the code of the División Territorial Administrativa — one digit for the provincia, two for the cantón, two for the distrito — **is the postal code**. Correos de Costa Rica assigns 10101 to the distrito 101 01. So one table of 428 lines generalizes the district code, the cantón code and the postal code at once, and a masked postal code always agrees with the masked distrito in the next column.

Below the distrito, the 2025 decree of the División Territorial Administrativa names 1,276 barrios. A barrio is far below any threshold, so it is not generalized upwards — that would say nothing a masked distrito does not already say — but replaced by another real barrio of the country, always the same one for the same input.

16

Limits

- **Masking with a key is pseudonymization, not desasociación.** Article 2 r) of the regulation asks that the result cannot be associated or linked to a determined or determinable person; whoever holds the key can reproduce the mapping, so a masked copy is still personal data and still needs the measures of article 10. To reach desasociación the key has to be discarded.
 - **The population figures are estimates.** The distrito populations are the Instituto Nacional de Estadística y Censos estimate for 2022, projected from the 2011 census; they total some 5.20 million, about 3% above the 5,044,197 the 2022 census counted. A distrito within a few hundred of the 20,000 threshold may fall on the other side of it under the census figures, and that is worth checking for the few that sit there.
 - **Sixteen distritos have no published figure of their own.** They were created after the distribution the estimate comes from — among them the three of the Río Cuarto cantón, Monteverde, Puerto Jiménez, Puente Salas, and the indigenous territories of Quitirisí and Matambú — and Isla del Coco is uninhabited. The set treats all sixteen as small, which generalizes them: the conservative choice, at the cost of some utility.
 - **The bank of an IBAN is preserved.** It is not personal data, and keeping it keeps a test account inside a real bank; but a bank with few clients in a small place narrows a person a little. The two check digits are recomputed from the masked account, so they leak nothing about the original.
 - **A birth date is shifted, not replaced.** Sixty days either way break the link to a public record and leave the age and the generation in place. Where a child's age decides something — a school year, a programme — a shift across a birthday moves a few rows; where that matters, shift the date the same way in every table that holds it.
 - **Binary columns and attachments are out of reach.** A scanned cédula, a photograph, a PDF of a hoja de delincuencia or a clinical image keeps everything the columns beside it no longer say. The set masks the path, not the file.
 - **Discovery is a proposal, not a verdict.** The classifiers read column names and values; a column with a name nobody recognizes and few values may be missed, and one named like a person may be caught by mistake. Review the inventory before running a masking job, which is what the inventory is for.
-

17

Verification

The set is checked on every build. The 141 classifier configurations are reviewed one by one, and a battery of 146 columns — well named, badly named, and 30 that are not personal data at all, among them a cédula jurídica — is profiled with the whole set at its threshold of 60 and again with the essential pack alone: every column lands where it should, and none of the 30 is claimed.

The generalization is audited offline: all 492 distritos, all 84 cantones and all 7 provincias are checked against the rule, and every one of the 11,582 replacements the table writes is checked to name a place of at least 20,000 — in the right provincia, by name, with the cantón, with the provincia and by code.

The masking is run for real: 572 values across every domain, every one checked against what it should become. Two hundred cédulas give two hundred distinct outputs, all well formed, with the provincia digit

masked and never a zero. Two hundred IBANs — one hundred compact and one hundred printed in groups of four — give two hundred distinct outputs, **all of them valid under ISO 13616**, all keeping their bank and their written form.

Sources

- Ley 8968, Protección de la Persona frente al Tratamiento de sus Datos Personales, of 7 July 2011 (La Gaceta 170 of 5 September 2011).
- Reglamento a la Ley 8968, Decreto Ejecutivo 37554-JP, as amended by Decreto 40008-JP of 19 July 2016 and Decreto 41582 of 21 February 2019.
- Ley 6723 del Registro y Archivos Judiciales, article 11 as reformed by Ley 10453 of 4 March 2024.
- Ley 8239 de derechos y deberes de las personas usuarias de los servicios de salud; Ley 7771 General sobre el VIH-SIDA; Ley 7600 de igualdad de oportunidades para las personas con discapacidad and Ley 9379; Ley 8589 and Ley 9095 on violence and trafficking.
- División Territorial Administrativa de la República, Decreto Ejecutivo 44882-MGP (Alcance 12 to La Gaceta 17 of 28 January 2025): the 7 provincias, 84 cantones, 492 distritos and their barrios.
- Instituto Nacional de Estadística y Censos: the estimate of population by distrito for 2022, projected from the 2011 census, and the 2022 census totals. Postal codes from Correos de Costa Rica. District centres from the subnational boundary set of the Instituto Geográfico Nacional.
- Banco Central de Costa Rica, the IBAN of 22 characters and the Cuenta Cliente of SINPE; ISO 13616 for the check digits. Decreto 44648-MJ for the alphanumeric cédula jurídica of 2026.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

CR_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER

(\d{3})(\d)	keep · CR_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_ANTECEDENTES_LISTA .

Used by: CR_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_ANTECEDENTES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in cr-antecedentes.txt , chosen by a keyed hash.

Used by: CR_ANTECEDENTES

CONFIGURATION

lookupFile	cr-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_APELLIDO NAME

Replaces the name with one of the 420 names in cr-apellidos.txt .

Used by: CR_PALABRA_APELLIDO

CONFIGURATION

lookupFile	cr-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

CR_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

Used by: CR_L1_APELLIDO , CR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	CR_PALABRA_APELLIDO
(\S+)\s+(\S+)	CR_PALABRA_APELLIDO · CR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	CR_PALABRA_APELLIDO · CR_PALABRA_APELLIDO · CR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	CR_PALABRA_APELLIDO · CR_PALABRA_APELLIDO · CR_PALABRA_APELLIDO · CR_PALABRA_APELLIDO
otherwise	CR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CR_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_APTITUD_LABORAL_LISTA .

Used by: CR_SALUD_OCUPACIONAL

PATTERNS, TRIED IN ORDER

(?i)(s i j no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_APTITUD_LABORAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in cr-aptitud-laboral.txt , chosen by a keyed hash.

Used by: CR_APTITUD_LABORAL

CONFIGURATION

lookupFile	cr-aptitud-laboral.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_CATEGORIA_SUPRIMIDA , CR_ESTADO_CIVIL , CR_NIVEL_EDUCATIVO , CR_ETNIA , CR_PUEBLO , CR_CONDICION_MIGRATORIA , CR_RELIGION , CR_PREFERENCIA_POLITICA , CR_PARTIDO , CR_ORIENTACION_SEXUAL , CR_IDENTIDAD_GENERO , CR_COBERTURA_SALUD , CR_DIAGNOSTICO , CR_MEDICAMENTO , CR_DISCAPACIDAD , CR_APTITUD_LABORAL , CR_HISTORIAL_CREDITICIO , CR_PROGRAMA_SOCIAL , CR_CONDICION_SOCIOECONOMICA , CR_TENENCIA_VIVIENDA , CR_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	CR_BANDERA_SI_NO
(?i)(true false)	CR_BANDERA_TRUE_FALSE
(?i)(yes)	CR_BANDERA_YES_NO
(?i)([sn])	CR_BANDERA_S_N
(?i)([yx])	CR_BANDERA_Y_N
([01])	CR_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-0-1.txt , chosen by a keyed hash.

Used by: CR_BANDERA

CONFIGURATION

lookupFile	cr-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-s-n.txt , chosen by a keyed hash.

Used by: CR_BANDERA

CONFIGURATION

lookupFile	cr-bandera-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-si-no.txt , chosen by a keyed hash.

Used by: CR_BANDERA

CONFIGURATION

lookupFile	cr-bandera-si-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-true-false.txt , chosen by a keyed hash.

Used by: CR_BANDERA

CONFIGURATION

lookupFile	cr-bandera-true-false.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-y-n.txt , chosen by a keyed hash.

Used by: CR_BANDERA

CONFIGURATION

lookupFile	cr-bandera-y-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in cr-bandera-yes-no.txt , chosen by a keyed hash.

Used by: CR_BANDERA

CONFIGURATION

lookupFile	cr-bandera-yes-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_BARRIO SECURE LOOKUP

Replaces the value with one of the 1,276 values in cr-barrrios.txt , chosen by a keyed hash.

Used by: CR_L2_BARRIO

CONFIGURATION

lookupFile	cr-barrios.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CATEGORIA_SUGEF SECURE LOOKUP

Replaces the value with one of the 8 values in cr-categorias-sugef.txt , chosen by a keyed hash.

Used by: CR_HISTORIAL_CREDITICIO

CONFIGURATION

lookupFile	cr-categorias-sugef.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_SUPRIMIR .

Used by: CR_L3_CONVICCION_FILOSOFICA , CR_L3_AFILIACION_SINDICAL , CR_L3_VIDA_SEXUAL , CR_L3_VICTIMA , CR_SALUD_VIH , CR_SALUD_REPRODUCTIVA , CR_SALUD_MENTAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_SUPRIMIR

CONFIGURATION

trimInput	yes
requireMask	no

CR_CEDULA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

Used by: CR_DOCUMENTO

PATTERNS, TRIED IN ORDER

(0)(\d)[s\-]?(\d{4})[s\-]?(\d{4})	keep · CR_CM_DIGITO_1_9 · CR_CM_DIGITOS · CR_CM_DIGITOS
(\d)[s\-](\d{3,4})[s\-](\d{3,4})	CR_CM_DIGITO_1_9 · CR_CM_DIGITOS · CR_CM_DIGITOS
(\d)(\d{8})	CR_CM_DIGITO_1_9 · CR_CM_DIGITOS
otherwise	CR_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

CR_CIE10 SECURE LOOKUP

Replaces the value with one of the 38 values in `cr-cie10.txt`, chosen by a keyed hash.

Used by: `CR_DIAGNOSTICO`

CONFIGURATION

lookupFile	<code>cr-cie10.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 34 values in `cr-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `CR_DIAGNOSTICO`

CONFIGURATION

lookupFile	<code>cr-cie10-decimal.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `CR_L1_SEGURO_SOCIAL`, `CR_L1_CODIGO_ESTUDIANTE`, `CR_L1_MATRICULA_PROFESIONAL`, `CR_L1_DIRECCION_COMPLEMENTO`, `CR_L1_BILLETERA`, `CR_L1_COOKIE`, `CR_L1_VEHICULO`, `CR_L1_CONTRATO`, `CR_L1_USUARIO`, `CR_SALUD_IDENTIFICADOR`, `CR_SALUD_RESULTADO_EXAMEN`, `CR_CATEGORIA_SUPRIMIDA`, `CR_NITE`, `CR_DOCUMENTO`, `CR_NOMBRES`, `CR_APELLIDOS`, `CR_NOMBRE_COMPLETO`, `CR_EMAIL`, `CR_INMUEBLE`, `CR_PUEBLO`, `CR_CONDICION_MIGRATORIA`, `CR_RELIGION`, `CR_PREFERENCIA_POLITICA`, `CR_PARTIDO`, `CR_ORIENTACION_SEXUAL`, `CR_IDENTIDAD_GENERO`, `CR_MEDICAMENTO`, `CR_DISCAPACIDAD`, `CR_APTITUD_LABORAL`, `CR_PROGRAMA_SOCIAL`, `CR_TENENCIA_VIVIENDA`, `CR_ANTECEDENTES`, `CR_EXPEDIENTE_JUDICIAL`

CONFIGURATION

characterGroups	<code>0123456789 AEIOU BCDFGHJKLMNPQRSTUVWXYZ aeiou bcd fghjklmnpqrstvwxyz ÁÉÍÓÚú áéíóúü</code>
caseSensitive	yes
minMaskedPositions	0

CR_CM_DIGITO_1_9 CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `CR_CEDULA`, `CR_INMUEBLE`

CONFIGURATION

characterGroups	<code>123456789</code>
caseSensitive	yes
minMaskedPositions	0

CR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: CR_CEDULA , CR_DIMEX , CR_NITE , CR_TELEFONO , CR_IBAN_PREPARAR , CR_CUENTA , CR_PLACA , CR_INMUEBLE , CR_COORDENADA , CR_ANIO , CR_EDAD , CR_OCUPACION_O_CODIGO , CR_COBERTURA_SALUD , CR_PROCEDIMIENTO , CR_HISTORIAL_CREDITICIO , CR_EXPEDIENTE_JUDICIAL

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0

CR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: CR_L1_PASAPORTE , CR_PLACA

CONFIGURATION

characterGroups	0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

CR_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: CR_L1_DISPPOSITIVO , CR_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

CR_COBERTURA SECURE LOOKUP

Replaces the value with one of the 10 values in cr-cobertura-salud.txt , chosen by a keyed hash.

Used by: CR_COBERTURA_SALUD

CONFIGURATION

lookupFile	cr-cobertura-salud.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_COBERTURA .

Used by: CR_SALUD_COBERTURA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,8})	CR_CM_DIGITOS
otherwise	CR_COBERTURA

CONFIGURATION

trimInput	yes
requireMask	no

CR_CODIGO_DTA DATA CLEANSING

Replaces each value found in `cr-codigos-generalizados.txt` (428 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CR_L2_CODIGO_DTA`

CONFIGURATION

lookupFile	<code>cr-codigos-generalizados.txt</code>
delimiter	
caseSensitive	yes
trimWhitespace	yes

CR_CONDICION_MIGRATORIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CR_CONDICION_MIGRATORIA_LISTA`.

Used by: `CR_L3_CONDICION_MIGRATORIA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CR_BANDERA</code>
<code>(\d{1,6})</code>	<code>CR_CM_ALFANUM</code>
otherwise	<code>CR_CONDICION_MIGRATORIA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_CONDICION_MIGRATORIA_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `cr-condicion-migratoria.txt`, chosen by a keyed hash.

Used by: `CR_CONDICION_MIGRATORIA`

CONFIGURATION

lookupFile	<code>cr-condicion-migratoria.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CONDICION_SOCIOECONOMICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CR_CONDICION_SOCIOECONOMICA_LISTA`.

Used by: `CR_FIN_CONDICION_SOCIOECONOMICA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CR_BANDERA</code>
<code>(\d{1,6})</code>	<code>CR_CONDICION_SOCIOECONOMICA_CODIGO</code>
otherwise	<code>CR_CONDICION_SOCIOECONOMICA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_CONDICION_SOCIOECONOMICA_CODIGO SECURE LOOKUP

Replaces the value with one of the 5 values in `cr-condicion-socioeconomica-codigos.txt` , chosen by a keyed hash.

Used by: `CR_CONDICION_SOCIOECONOMICA`

CONFIGURATION

lookupFile	<code>cr-condicion-socioeconomica-codigos.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CONDICION_SOCIOECONOMICA_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `cr-condicion-socioeconomica.txt` , chosen by a keyed hash.

Used by: `CR_CONDICION_SOCIOECONOMICA`

CONFIGURATION

lookupFile	<code>cr-condicion-socioeconomica.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L2_PERSONAS_A_CARGO`

PATTERNS, TRIED IN ORDER

<code>([0-5])</code>	keep
<code>(\d+)</code>	replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

<code>(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)</code>	keep · <code>CR_CM_DIGITOS</code> · keep · keep · <code>CR_CM_DIGITOS</code>
---	--

(-?\d{1,3}[.,]\d)(\d+)	keep · CR_CM_DIGITOS
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

CR_CUENTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

Used by: CR_L1_CUENTA_BANCARIA

PATTERNS, TRIED IN ORDER	
(?i)(CR\d{2}[\s]?d{4}[\s]?d{4}[\s]?d{4}[\s]?d{2})	CR_IBAN
(?i)(CR\d{20})	CR_IBAN
(\d{3})(\d{14})	keep · CR_CM_DIGITOS
otherwise	CR_CM_DIGITOS
CONFIGURATION	
trimInput	yes
requireMask	no

CR_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CR_DIAGNOSTICO_TEXTO .

Used by: CR_SALUD_DIAGNOSTICO

PATTERNS, TRIED IN ORDER	
([A-TV-Za-tv-z]\d{2}\.\d{1,2})	CR_CIE10_DECIMAL
([A-TV-Za-tv-z]\d{2,3}X?)	CR_CIE10
(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
otherwise	CR_DIAGNOSTICO_TEXTO
CONFIGURATION	
trimInput	yes
requireMask	no

CR_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 31 values in cr-diagnostics.txt , chosen by a keyed hash.

Used by: CR_DIAGNOSTICO

CONFIGURATION	
lookupFile	cr-diagnostics.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_DIMEX REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

Used by: CR_L1_DIMEX , CR_DOCUMENTO

PATTERNS, TRIED IN ORDER

(\d{11,12})	CR_CM_DIGITOS
otherwise	CR_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

CR_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in cr-direcciones.txt , chosen by a keyed hash.

Used by: CR_L1_DIRECCION

CONFIGURATION

lookupFile	cr-direcciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_DISCAPACIDAD_LISTA .

Used by: CR_SALUD_DISCAPACIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_DISCAPACIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in cr-discapacidades.txt , chosen by a keyed hash.

Used by: CR_DISCAPACIDAD

CONFIGURATION

lookupFile	cr-discapacidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

CR_DISTRITO DATA CLEANSING

Replaces each value found in `cr-distritos-generalizados.txt` (11,582 pairs) by its counterpart; values not in the file stay as they are.

Used by: `CR_L2_DISTRITO`

CONFIGURATION

lookupFile	<code>cr-distritos-generalizados.txt</code>
delimiter	<code> </code>
caseSensitive	yes
trimWhitespace	yes

CR_DOCUMENTO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_CEDULA`

PATTERNS, TRIED IN ORDER

<code>(3[\s\~]?120[\s\~]?[0-9]{6})</code>	<code>CR_NITE</code>
<code>(3[\s\~]?[0-9]{3}[\s\~]?[A-Za-z]{6})</code>	keep
<code>([0-9]{11,12})</code>	<code>CR_DIMEX</code>
<code>(0?[0-9][\s\~]?[0-9]{3,4}[\s\~]?[0-9]{3,4})</code>	<code>CR_CEDULA</code>
otherwise	<code>CR_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `CR_L2_EDAD`

PATTERNS, TRIED IN ORDER

<code>([0-9]{3,})</code>	replace with <code>90</code>
<code>([0-9])([.,][0-9]+)</code>	keep · <code>CR_CM_DIGITOS</code> · keep
<code>([0-9])([0-9])</code>	keep · <code>CR_CM_DIGITOS</code>
<code>([0-9])</code>	<code>CR_CM_DIGITOS</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_EMAIL`

PATTERNS, TRIED IN ORDER

<code>([^\s@]+)@([^\s@]+)\.([A-Za-z]{2,24})(?:\.[A-Za-z]{2})?)</code>	<code>CR_CM_ALFANUM</code> · <code>CR_CM_ALFANUM</code> · replace with <code>test</code>
---	--

otherwise	CR_CM_ALFANUM
-----------	---------------

CONFIGURATION

trimInput	yes
requireMask	no

CR_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in `cr-empleadores.txt`, chosen by a keyed hash.

Used by: `CR_L2_EMPLEADOR`

CONFIGURATION

lookupFile	<code>cr-empleadores.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CR_ESTADO_CIVIL_LISTA`.

Used by: `CR_L2_ESTADO_CIVIL`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CR_BANDERA</code>
<code>(\d{1,6})</code>	<code>CR_ESTADO_CIVIL_CODIGO</code>
otherwise	<code>CR_ESTADO_CIVIL_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-estado-civil-codigos.txt`, chosen by a keyed hash.

Used by: `CR_ESTADO_CIVIL`

CONFIGURATION

lookupFile	<code>cr-estado-civil-codigos.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-estado-civil.txt`, chosen by a keyed hash.

Used by: `CR_ESTADO_CIVIL`

CONFIGURATION

lookupFile	cr-estado-civil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 13 values in cr-estados-credito.txt , chosen by a keyed hash.

Used by: CR_HISTORIAL_CREDITICIO

CONFIGURATION

lookupFile	cr-estados-credito.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ETNIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_ETNIA_LISTA .

Used by: CR_L3_ETNIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_ETNIA_CODIGO
otherwise	CR_ETNIA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_ETNIA_CODIGO SECURE LOOKUP

Replaces the value with one of the 7 values in cr-etnias-codigos.txt , chosen by a keyed hash.

Used by: CR_ETNIA

CONFIGURATION

lookupFile	cr-etnias-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_ETNIA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in cr-etnias.txt , chosen by a keyed hash.

Used by: CR_ETNIA

CONFIGURATION

lookupFile	cr-etnias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_EXPEDIENTE_JUDICIAL REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

Used by: CR_PENAL_EXPEDIENTE

PATTERNS, TRIED IN ORDER

(\d{2})(-)(\d{6})(-)(\d{4})(-)([A-Za-z]{2,4})	keep · keep · CR_CM_DIGITOS · keep · keep · keep · keep
(\d{2})(-)(\d{6})(-)(\d{4})	keep · keep · CR_CM_DIGITOS · keep · keep
(\d{1,6})([\s\-/])([A-Za-z]{2,10})([\s\-/])(\d{4})	CR_CM_DIGITOS · keep · keep · keep · keep
(\d{1,6})([\s\-/])(\d{4})	CR_CM_DIGITOS · keep · keep
otherwise	CR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CR_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: CR_L2_FECHA_EVENTO

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

CR_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: CR_L2_FECHA_NACIMIENTO

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS
roll	no

CR_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in cr-grupos-sanguineos.txt , chosen by a keyed hash.

Used by: CR_SALUD_GRUPO_SANGUINEO

CONFIGURATION

lookupFile	cr-grupos-sanguineos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_ESTADO_CREDITO .

Used by: CR_FIN_HISTORIAL_CREDITICIO

PATTERNS, TRIED IN ORDER

(?i)([A-E][12]?)	CR_CATEGORIA_SUGEF
(\d{1,4})	CR_CM_DIGITOS
(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
otherwise	CR_ESTADO_CREDITO

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN STRING ALGORITHM CHAIN

Applies CR_IBAN_1 → CR_IBAN_2 → CR_IBAN_3 → CR_IBAN_4 → CR_IBAN_5 → CR_IBAN_6 → CR_IBAN_RESTAURAR , in this order.

Used by: CR_CUENTA

CONFIGURATION

algorithmReferences[1]	CR_IBAN_1
algorithmReferences[2]	CR_IBAN_2
algorithmReferences[3]	CR_IBAN_3
algorithmReferences[4]	CR_IBAN_4
algorithmReferences[5]	CR_IBAN_5
algorithmReferences[6]	CR_IBAN_6
algorithmReferences[7]	CR_IBAN_RESTAURAR

CR_IBAN_1 STRING ALGORITHM CHAIN

Applies CR_IBAN_PREPARAR → CR_IBAN_IDA_01 → CR_IBAN_IDA_02 → CR_IBAN_IDA_03 → CR_IBAN_IDA_04 → CR_IBAN_IDA_05 → CR_IBAN_IDA_06 → CR_IBAN_IDA_07 , in this order.

Used by: CR_IBAN

CONFIGURATION

algorithmReferences[1]	CR_IBAN_PREPARAR
algorithmReferences[2]	CR_IBAN_IDA_01
algorithmReferences[3]	CR_IBAN_IDA_02
algorithmReferences[4]	CR_IBAN_IDA_03
algorithmReferences[5]	CR_IBAN_IDA_04
algorithmReferences[6]	CR_IBAN_IDA_05

algorithmReferences[7]	CR_IBAN_IDA_06
algorithmReferences[8]	CR_IBAN_IDA_07

CR_IBAN_2 STRING ALGORITHM CHAIN

Applies CR_IBAN_IDA_08 → CR_IBAN_IDA_09 → CR_IBAN_IDA_10 → CR_IBAN_IDA_11 → CR_IBAN_IDA_12 → CR_IBAN_IDA_13 → CR_IBAN_IDA_14 → CR_IBAN_IDA_15 , in this order.

Used by: CR_IBAN

CONFIGURATION

algorithmReferences[1]	CR_IBAN_IDA_08
algorithmReferences[2]	CR_IBAN_IDA_09
algorithmReferences[3]	CR_IBAN_IDA_10
algorithmReferences[4]	CR_IBAN_IDA_11
algorithmReferences[5]	CR_IBAN_IDA_12
algorithmReferences[6]	CR_IBAN_IDA_13
algorithmReferences[7]	CR_IBAN_IDA_14
algorithmReferences[8]	CR_IBAN_IDA_15

CR_IBAN_3 STRING ALGORITHM CHAIN

Applies CR_IBAN_IDA_16 → CR_IBAN_IDA_17 → CR_IBAN_IDA_18 → CR_IBAN_IDA_19 → CR_IBAN_IDA_20 → CR_IBAN_IDA_21 → CR_IBAN_IDA_22 → CR_IBAN_IDA_23 , in this order.

Used by: CR_IBAN

CONFIGURATION

algorithmReferences[1]	CR_IBAN_IDA_16
algorithmReferences[2]	CR_IBAN_IDA_17
algorithmReferences[3]	CR_IBAN_IDA_18
algorithmReferences[4]	CR_IBAN_IDA_19
algorithmReferences[5]	CR_IBAN_IDA_20
algorithmReferences[6]	CR_IBAN_IDA_21
algorithmReferences[7]	CR_IBAN_IDA_22
algorithmReferences[8]	CR_IBAN_IDA_23

CR_IBAN_4 STRING ALGORITHM CHAIN

Applies CR_IBAN_CALCULAR → CR_IBAN_VUELTA_23 → CR_IBAN_VUELTA_22 → CR_IBAN_VUELTA_21 → CR_IBAN_VUELTA_20 → CR_IBAN_VUELTA_19 → CR_IBAN_VUELTA_18 → CR_IBAN_VUELTA_17 , in this order.

Used by: CR_IBAN

CONFIGURATION

algorithmReferences[1]	CR_IBAN_CALCULAR
algorithmReferences[2]	CR_IBAN_VUELTA_23
algorithmReferences[3]	CR_IBAN_VUELTA_22
algorithmReferences[4]	CR_IBAN_VUELTA_21
algorithmReferences[5]	CR_IBAN_VUELTA_20
algorithmReferences[6]	CR_IBAN_VUELTA_19
algorithmReferences[7]	CR_IBAN_VUELTA_18
algorithmReferences[8]	CR_IBAN_VUELTA_17

CR_IBAN_5 STRING ALGORITHM CHAIN

Applies CR_IBAN_VUELTA_16 → CR_IBAN_VUELTA_15 → CR_IBAN_VUELTA_14 → CR_IBAN_VUELTA_13 → CR_IBAN_VUELTA_12 → CR_IBAN_VUELTA_11 → CR_IBAN_VUELTA_10 → CR_IBAN_VUELTA_09 , in this order.

Used by: CR_IBAN

CONFIGURATION

algorithmReferences[1]	CR_IBAN_VUELTA_16
algorithmReferences[2]	CR_IBAN_VUELTA_15
algorithmReferences[3]	CR_IBAN_VUELTA_14
algorithmReferences[4]	CR_IBAN_VUELTA_13
algorithmReferences[5]	CR_IBAN_VUELTA_12
algorithmReferences[6]	CR_IBAN_VUELTA_11
algorithmReferences[7]	CR_IBAN_VUELTA_10
algorithmReferences[8]	CR_IBAN_VUELTA_09

CR_IBAN_6 STRING ALGORITHM CHAIN

Applies CR_IBAN_VUELTA_08 → CR_IBAN_VUELTA_07 → CR_IBAN_VUELTA_06 → CR_IBAN_VUELTA_05 → CR_IBAN_VUELTA_04 → CR_IBAN_VUELTA_03 → CR_IBAN_VUELTA_02 → CR_IBAN_VUELTA_01 , in this order.

Used by: CR_IBAN

CONFIGURATION

algorithmReferences[1]	CR_IBAN_VUELTA_08
algorithmReferences[2]	CR_IBAN_VUELTA_07
algorithmReferences[3]	CR_IBAN_VUELTA_06
algorithmReferences[4]	CR_IBAN_VUELTA_05
algorithmReferences[5]	CR_IBAN_VUELTA_04
algorithmReferences[6]	CR_IBAN_VUELTA_03
algorithmReferences[7]	CR_IBAN_VUELTA_02
algorithmReferences[8]	CR_IBAN_VUELTA_01

CR_IBAN_CALCULAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.*)({2})	keep · CR_IBAN_RESULTADO
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{1})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
CR_IBAN_IDA_06 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: CR_IBAN_1	
PATTERNS, TRIED IN ORDER	
(.{6})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
CR_IBAN_IDA_07 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: CR_IBAN_1	
PATTERNS, TRIED IN ORDER	
(.{7})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
CR_IBAN_IDA_08 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: CR_IBAN_2	
PATTERNS, TRIED IN ORDER	
(.{8})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
CR_IBAN_IDA_09 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: CR_IBAN_2	
PATTERNS, TRIED IN ORDER	
(.{9})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

CR_IBAN_IDA_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_2

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_2

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_2

PATTERNS, TRIED IN ORDER

(.{12})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_2

PATTERNS, TRIED IN ORDER

(.{13})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_2

PATTERNS, TRIED IN ORDER

(.{14})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_2

PATTERNS, TRIED IN ORDER

(.{15})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

(.{16})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

(.{17})(.{3})(.*)	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

<code>(.{18})(.{3})(.*)</code>	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

<code>(.{19})(.{3})(.*)</code>	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

<code>(.{20})(.{3})(.*)</code>	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

<code>(.{21})(.{3})(.*)</code>	keep · CR_IBAN_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_22 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

<code>(.{22})(.{3})(.*)</code>	keep · CR_IBAN_PAS0 · keep
--------------------------------	----------------------------

otherwise	keep
-----------	------

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_IDA_23 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_3

PATTERNS, TRIED IN ORDER

(.{23})(.{3})(.*)	keep · CR_IBAN_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_PASO DATA CLEANSING

Replaces each value found in cr-iban-paso.txt (1,067 pairs) by its counterpart; values not in the file stay as they are.

Used by: CR_IBAN_IDA_01 , CR_IBAN_IDA_02 , CR_IBAN_IDA_03 , CR_IBAN_IDA_04 , CR_IBAN_IDA_05 , CR_IBAN_IDA_06 , CR_IBAN_IDA_07 , CR_IBAN_IDA_08 , CR_IBAN_IDA_09 , CR_IBAN_IDA_10 , CR_IBAN_IDA_11 , CR_IBAN_IDA_12 , CR_IBAN_IDA_13 , CR_IBAN_IDA_14 , CR_IBAN_IDA_15 , CR_IBAN_IDA_16 , CR_IBAN_IDA_17 , CR_IBAN_IDA_18 , CR_IBAN_IDA_19 , CR_IBAN_IDA_20 , CR_IBAN_IDA_21 , CR_IBAN_IDA_22 , CR_IBAN_IDA_23

CONFIGURATION

lookupFile	cr-iban-paso.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

CR_IBAN_PREPARAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_1

PATTERNS, TRIED IN ORDER

(?i)(CR)(\d{2})()(\d{4})()(\d{4})()(\d{4})()(\d{4})()(\d{2})	replace with ~ · replace with 00 · replace with _ · keep · replace with _ · CR_CM_DIGITOS · replace with _ · CR_CM_DIGITOS · replace with _ · CR_CM_DIGITOS · replace with _ · CR_CM_DIGITOS
(?i)(CR)(\d{2})(\d{4})(\d{14})	replace with ~ · replace with 00 · keep · CR_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_RESTAURAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN

PATTERNS, TRIED IN ORDER

(~)(\d{2})(_)(\d{4})(_)(\d{4})(_)(\d{4})(_)(\d{4})(_)(\d{2})	replace with CR · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
(~)(\d{2})(\d{18})	replace with CR · keep · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_RESULTADO DATA CLEANSING

Replaces each value found in cr-iban-resultado.txt (97 pairs) by its counterpart; values not in the file stay as they are.

Used by: CR_IBAN_CALCULAR

CONFIGURATION

lookupFile	cr-iban-resultado.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

CR_IBAN TRASLADO DATA CLEANSING

Replaces each value found in cr-iban-traslado.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: CR_IBAN_VUELTA_23 , CR_IBAN_VUELTA_22 , CR_IBAN_VUELTA_21 , CR_IBAN_VUELTA_20 , CR_IBAN_VUELTA_19 , CR_IBAN_VUELTA_18 , CR_IBAN_VUELTA_17 , CR_IBAN_VUELTA_16 , CR_IBAN_VUELTA_15 , CR_IBAN_VUELTA_14 , CR_IBAN_VUELTA_13 , CR_IBAN_VUELTA_12 , CR_IBAN_VUELTA_11 , CR_IBAN_VUELTA_10 , CR_IBAN_VUELTA_09 , CR_IBAN_VUELTA_08 , CR_IBAN_VUELTA_07 , CR_IBAN_VUELTA_06 , CR_IBAN_VUELTA_05 , CR_IBAN_VUELTA_04 , CR_IBAN_VUELTA_03 , CR_IBAN_VUELTA_02 , CR_IBAN_VUELTA_01

CONFIGURATION

lookupFile	cr-iban-traslado.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

CR_IBAN_VUELTA_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_6

PATTERNS, TRIED IN ORDER

(.{1})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_6

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_6

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_6

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_6

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_6

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
------------------	--------------------------------

otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

CR_IBAN_VUELTA_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: **CR_IBAN_6**

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: **CR_IBAN_6**

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: **CR_IBAN_5**

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: **CR_IBAN_5**

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_5

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_5

PATTERNS, TRIED IN ORDER

(.{12})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_5

PATTERNS, TRIED IN ORDER

(.{13})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_5

PATTERNS, TRIED IN ORDER

(.{14})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

CR_IBAN_VUELTA_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_5

PATTERNS, TRIED IN ORDER

(.{15})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_5

PATTERNS, TRIED IN ORDER

(.{16})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.{17})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.{18})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.{19})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.{20})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.{21})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_22 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_IBAN_4

PATTERNS, TRIED IN ORDER

(.{22})(.{3})(.*)	keep · CR_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_IBAN_VUELTA_23 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `CR_IBAN_4`

PATTERNS, TRIED IN ORDER

<code>(.{23})(.{3})(.*)</code>	<code>keep · CR_IBAN TRASLADO · keep</code>
otherwise	<code>keep</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CR_IDENTIDAD_GENERO_LISTA` .

Used by: `CR_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CR_BANDERA</code>
<code>(\d{1,6})</code>	<code>CR_CM_ALFANUM</code>
otherwise	<code>CR_IDENTIDAD_GENERO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `cr-identidades-genero.txt` , chosen by a keyed hash.

Used by: `CR_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	<code>cr-identidades-genero.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_INGRESOS NUMERIC MAPPING

Maps the number to another between 360,000 and 6,000,000.

Used by: `CR_FIN_INGRESOS`

CONFIGURATION

minValue	<code>360000</code>
maxValue	<code>6000000</code>

CR_INMUEBLE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM` .

Used by: `CR_L1_INMUEBLE`

PATTERNS, TRIED IN ORDER

<code>(?i)([A-Z]{1,2})([\s-])(\d{6,7})([\s-])(\d{4})</code>	<code>keep · keep · CR_CM_DIGITOS · keep · keep</code>
---	--

(\d)([\s-])(\d{6})([\s-])(\d{3})	CR_CM_DIGITO_1_9 · keep · CR_CM_DIGITOS · keep · CR_CM_DIGITOS
(\d)([\s-])(\d{6})	CR_CM_DIGITO_1_9 · keep · CR_CM_DIGITOS
otherwise	CR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CR_INSTITUCION_EDUCATIVA SECURE LOOKUP

Replaces the value with one of the 12 values in cr-instituciones-educativas.txt , chosen by a keyed hash.

Used by: CR_L2_INSTITUCION_EDUCATIVA

CONFIGURATION

lookupFile	cr-instituciones-educativas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_CM_HEX .

Used by: CR_L1_IP

PATTERNS, TRIED IN ORDER

(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3})	CR_OCTETO · CR_OCTETO · CR_OCTETO · CR_OCTETO
otherwise	CR_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

CR_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_MEDICAMENTO_LISTA .

Used by: CR_SALUD_MEDICAMENTO

PATTERNS, TRIED IN ORDER

(?i)(s[ii] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_MEDICAMENTO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 22 values in cr-medicamentos.txt , chosen by a keyed hash.

Used by: CR_MEDICAMENTO

CONFIGURATION

lookupFile	cr-medicamentos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in `cr-nacionalidades.txt`, chosen by a keyed hash.

Used by: `CR_L3_NACIONALIDAD`

CONFIGURATION

lookupFile	cr-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NITE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM`.

Used by: `CR_L1_NITE`, `CR_DOCUMENTO`

PATTERNS, TRIED IN ORDER

<code>(3[\s\~]?120[\s\~]?)(\d{6})</code>	keep · <code>CR_CM_DIGITOS</code>
<code>(3[\s\~]?130[\s\~]?[\dA-Za-z]{6})</code>	keep
otherwise	<code>CR_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`CR_NIVEL_EDUCATIVO_LISTA`.

Used by: `CR_L2_NIVEL_EDUCATIVO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>CR_BANDERA</code>
<code>(\d{1,6})</code>	<code>CR_NIVEL_EDUCATIVO_CODIGO</code>
otherwise	<code>CR_NIVEL_EDUCATIVO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-nivel-educativo-codigos.txt`, chosen by a keyed hash.

Used by: `CR_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	cr-nivel-educativo-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `cr-nivel-educativo.txt` , chosen by a keyed hash.

Used by: `CR_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	cr-nivel-educativo.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_NOMBRE NAME

Replaces the name with one of the 400 names in `cr-nombres.txt` .

Used by: `CR_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	cr-nombres.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

CR_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `CR_CM_ALFANUM` .

Used by: `CR_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

<code>([^,]+), \s*(. +)</code>	<code>CR_APELLIDOS</code> · <code>CR_NOMBRES</code>
<code>(\S+)</code>	<code>CR_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)</code>	<code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)</code>	<code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_APELLIDO</code> · <code>CR_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_APELLIDO</code> · <code>CR_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_APELLIDO</code> · <code>CR_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_NOMBRE</code> · <code>CR_PALABRA_APELLIDO</code> · <code>CR_PALABRA_APELLIDO</code>
otherwise	<code>CR_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

CR_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: CR_CM_ALFANUM .

Used by: CR_L1_NOMBRE , CR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	CR_PALABRA_NOMBRE
(\S+)\s+(\S+)	CR_PALABRA_NOMBRE · CR_PALABRA_NOMBRE
(\S+)\s+(\S+)\s+(\S+)	CR_PALABRA_NOMBRE · CR_PALABRA_NOMBRE · CR_PALABRA_NOMBRE
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	CR_PALABRA_NOMBRE · CR_PALABRA_NOMBRE · CR_PALABRA_NOMBRE · CR_PALABRA_NOMBRE
otherwise	CR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

CR_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: CR_IP

CONFIGURATION

minValue	1
maxValue	254

CR_OCUPACION SECURE LOOKUP

Replaces the value with one of the 37 values in cr-ocupaciones.txt , chosen by a keyed hash.

Used by: CR_OCUPACION_O_CODIGO

CONFIGURATION

lookupFile	cr-ocupaciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_OCUPACION_O_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_OCUPACION .

Used by: CR_L2_OCUPACION

PATTERNS, TRIED IN ORDER

(\d{2,5})	CR_CM_DIGITOS
otherwise	CR_OCUPACION

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

CR_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_ORIENTACION_SEXUAL_LISTA .

Used by: CR_L3_ORIENTACION_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_ORIENTACION_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in cr-orientaciones-sexuales.txt , chosen by a keyed hash.

Used by: CR_ORIENTACION_SEXUAL

CONFIGURATION

lookupFile	cr-orientaciones-sexuales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_APELLIDO .

Used by: CR_APELLIDOS , CR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i)	keep
(de del la las los y e da do dos san santa vo n van di le)	
otherwise	CR_APELLIDO

CONFIGURATION

trimInput	yes
requireMask	no

CR_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: CR_NOMBRE .

Used by: CR_NOMBRES , CR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i)	keep
(de del la las los y e da do dos san santa vo n van di le)	
otherwise	CR_NOMBRE

CONFIGURATION

trimInput	yes
requireMask	no

CR_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_PARTIDO_LISTA .

Used by: CR_L3_AFILIACION_PARTIDARIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_PARTIDO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in cr-partidos.txt , chosen by a keyed hash.

Used by: CR_PARTIDO

CONFIGURATION

lookupFile	cr-partidos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 1,000,000 and 500,000,000.

Used by: CR_FIN_PATRIMONIO

CONFIGURATION

minValue	1000000
maxValue	500000000

CR_PLACA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

CR_CM_DIGITOS_LETRAS .

Used by: CR_L1_PLACA

PATTERNS, TRIED IN ORDER

(?i)	keep · keep · CR_CM_DIGITOS
(MOT CL TSJ TA TB TC TG TH TL TP AB SJB PE CD C M)([s\-\]?) (\d{3,6})	
([A-Za-z]{3})([s\-\]?) (\d{3})	CR_CM_DIGITOS_LETRAS · keep · CR_CM_DIGITOS
(\d{3,6})	CR_CM_DIGITOS
otherwise	CR_CM_DIGITOS_LETRAS

CONFIGURATION

trimInput	yes
requireMask	no

CR_PREFERENCIA_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_PREFERENCIA_POLITICA_LISTA .

Used by: CR_L3_OPINION_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[íí] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_PREFERENCIA_POLITICA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_PREFERENCIA_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in cr-preferencias-politicas.txt , chosen by a keyed hash.

Used by: CR_PREFERENCIA_POLITICA

CONFIGURATION

lookupFile	cr-preferencias-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

CR_PROCEDIMIENTO_TEXTO .

Used by: CR_SALUD_PROCEDIMIENTO

PATTERNS, TRIED IN ORDER

(\d{4,6})	CR_CM_DIGITOS
otherwise	CR_PROCEDIMIENTO_TEXTO

CONFIGURATION

trimInput	yes
requireMask	no

CR_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in cr-procedimientos.txt , chosen by a keyed hash.

Used by: CR_PROCEDIMIENTO

CONFIGURATION

lookupFile	cr-procedimientos.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_PROGRAMA_SOCIAL_LISTA .

Used by: CR_FIN_PROGRAMA_SOCIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_PROGRAMA_SOCIAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in cr-programas-sociales.txt , chosen by a keyed hash.

Used by: CR_PROGRAMA_SOCIAL

CONFIGURATION

lookupFile	cr-programas-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_PUEBLO_LISTA .

Used by: CR_L3_PUEBLO_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_PUEBLO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_PUEBLO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in cr-pueblos.txt , chosen by a keyed hash.

Used by: CR_PUEBLO

CONFIGURATION

lookupFile	cr-pueblos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_L1_CREDENCIAL , CR_L1_IMAGEN , CR_L3_BIOMETRICO , CR_L3_GENETICO

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: CR_RELIGION_LISTA .

Used by: CR_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [sn]yx01))	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in cr-religiones.txt , chosen by a keyed hash.

Used by: CR_RELIGION

CONFIGURATION

lookupFile	cr-religiones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEXO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: CR_L2_SEX0

PATTERNS, TRIED IN ORDER

(?i)(femenino masculino)	CR_SEX0_FEMENINO_MASCULINO
(?i)(mujer hombre)	CR_SEX0_MUJER_HOMBRE
(?i)(female male)	CR_SEX0_FEMALE_MALE
(?i)([fm])	CR_SEX0_F_M
(?i)([hm])	CR_SEX0_H_M
([12])	CR_SEX0_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_SEX0_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-1-2.txt` , chosen by a keyed hash.

Used by: `CR_SEX0`

CONFIGURATION

lookupFile	cr-sexo-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEX0_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-f-m.txt` , chosen by a keyed hash.

Used by: `CR_SEX0`

CONFIGURATION

lookupFile	cr-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEX0_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-female-male.txt` , chosen by a keyed hash.

Used by: `CR_SEX0`

CONFIGURATION

lookupFile	cr-sexo-female-male.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

CR_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-femenino-masculino.txt` , chosen by a keyed hash.

Used by: `CR_SEX0`

CONFIGURATION

lookupFile	<code>cr-sexo-femenino-masculino.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEX0_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-h-m.txt` , chosen by a keyed hash.

Used by: `CR_SEX0`

CONFIGURATION

lookupFile	<code>cr-sexo-h-m.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SEX0_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `cr-sexo-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `CR_SEX0`

CONFIGURATION

lookupFile	<code>cr-sexo-mujer-hombre.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

CR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `cr-sin-informacion.txt` , chosen by a keyed hash.

Used by: `CR_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	<code>cr-sin-informacion.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

CR_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: CR_L1_TARJETA

PATTERNS, TRIED IN ORDER

(\d[\d\s-]{11,22}\d)	CR_TARJETA_LUHN
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

CR_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: CR_TARJETA

CONFIGURATION

minMaskedPositions	6
preserve	0

CR_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: CR_CM_DIGITOS .

Used by: CR_L1_TELEFONO

PATTERNS, TRIED IN ORDER

(\+?506[\s-]?)([2458-9])([\d\s-]{7,10})	keep · keep · CR_CM_DIGITOS
(\(?\+?506\)?[\s-]?)([2458-9])([\d\s-]{7,10})	keep · keep · CR_CM_DIGITOS
([2458-9])([\d\s-]{7,9})	keep · CR_CM_DIGITOS
otherwise	CR_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

CR_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

CR_TENENCIA_VIVIENDA_LISTA .

Used by: CR_FIN_VIVIENDA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	CR_BANDERA
(\d{1,6})	CR_CM_ALFANUM
otherwise	CR_TENENCIA_VIVIENDA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

CR_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `cr-tenencia-vivienda.txt` , chosen by a keyed hash.

Used by: `CR_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	<code>cr-tenencia-vivienda.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

CR_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DATO]` , and the 1,944 terms of `cr-texto-nombres.txt` with `[NOMBRE]` .

Used by: `CR_L1_TEXTO_LIBRE` , `CR_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

<code>(?<!\d)\d-\d{4}-\d{4}(?!\\d)</code>
<code>(?<!\d)[1-9]\d{8}(?!\\d)</code>
<code>(?<!\d)\d{11,12}(?!\\d)</code>
<code>3-1[23]0-\d{6}</code>
<code>[\w.+\\-]+@[\\w\\-]+(\\. [\\w\\-]+)+</code>
<code>(?<![\\d\\-])(\\+?506\\-)?[2458-9]\\d{3}\\-?\\d{4}(?! [\\d\\-])</code>
<code>(?<!\d)\d{13,19}(?!\\d)</code>
<code>CR\d{20}</code>
<code>(?<!\d)(\\d{1,3}\\. .){3}\\d{1,3}(?!\\d)</code>

CONFIGURATION

regExRedactValue	<code>[DATO]</code>
lookupFile	<code>cr-texto-nombres.txt</code>
lookupFileRedactValue	<code>[NOMBRE]</code>
isDenyList	<code>yes</code>

CR_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 50,000 and 60,000,000.

Used by: `CR_FIN_DEUDA`

CONFIGURATION

minValue	<code>50000</code>
maxValue	<code>60000000</code>

CR_VALOR_PENSION NUMERIC MAPPING

Maps the number to another between 150,000 and 2,500,000.

Used by: `CR_FIN_PENSION`

CONFIGURATION

minValue	<code>150000</code>
----------	---------------------

maxValue	2500000
----------	---------

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
cr-antecedentes.txt	7	CR_ANTECEDENTES_LISTA	No registra antecedentes penales · Registra antecedentes · Con causa pendiente · Sentencia condenatoria
cr-apellidos.txt	420	CR_APELLIDO	Abarca · Acevedo · Acosta · Acuña
cr-aptitud-laboral.txt	4	CR_APTITUD_LABORAL_LISTA	Apto · Apto con restricciones · No apto · Pendiente
cr-bandera-0-1.txt	2	CR_BANDERA_0_1	0 · 1
cr-bandera-s-n.txt	2	CR_BANDERA_S_N	S · N
cr-bandera-si-no.txt	2	CR_BANDERA_SI_NO	Sí · No
cr-bandera-true-false.txt	2	CR_BANDERA_TRUE_FALSE	true · false
cr-bandera-y-n.txt	2	CR_BANDERA_Y_N	Y · N
cr-bandera-yes-no.txt	2	CR_BANDERA_YES_NO	Yes · No
cr-barrios.txt	1,276	CR_BARRIO	Abarca · Acacias · Acapulco · Acequia Grande
cr-categorias-sugef.txt	8	CR_CATEGORIA_SUGEf	A1 · A2 · B1 · B2
cr-cie10-decimal.txt	34	CR_CIE10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
cr-cie10.txt	38	CR_CIE10	I10 · E11 · E78 · J45
cr-cobertura-salud.txt	10	CR_COBERTURA	Asegurado directo asalariado · Asegurado directo cuenta propia · Asegurado voluntario · Asegurado por el Estado
cr-codigos-generalizados.txt	428	CR_CODIGO_DTA	10101 10105 · 10102 10103 · 10104 10105 · 10108 10110
cr-condicion-migratoria.txt	9	CR_CONDICION_MIGRATORIA_LISTA	Residente permanente · Residente temporal · Categoría especial · Persona refugiada
cr-condicion-socioeconomica-codigos.txt	5	CR_CONDICION_SOCIOECONOMICA_CODIGO	1 · 2 · 3 · 4
cr-condicion-socioeconomica.txt	10	CR_CONDICION_SOCIOECONOMICA_LISTA	Pobreza extrema · Pobreza básica · Vulnerabilidad · No pobre

FILE	LINES	USED BY	FIRST LINES
cr-detectar-apellidos.txt	539	CR_L1_APELLIDO – List CR_L1_NOMBRE_COMPLET 0 – List	Abarca · Acevedo · Acosta · Acuña
cr-detectar-aptitud-laboral.txt	5	CR_SALUD_OCUPACIONAL – List	apto · no apto · apto con restricciones · pendiente
cr-detectar-cobertura.txt	21	CR_SALUD_COBERTURA – List	Asegurado directo asalariado · Asegurado directo cuenta propia · Asegurado voluntario · Asegurado por el Estado
cr-detectar-codigos-banderas.txt	12	CR_L3_ETNIA – List CR_FIN_PROGRAMA_SOCIAL – List	s · n · sí · si
cr-detectar-condicion-migratoria.txt	21	CR_L3_CONDICION_MIGRATORIA – List	Residente permanente · Residente temporal · Categoría especial · Categoría especial
cr-detectar-condicion-socioeconomica.txt	24	CR_FIN_CONDICION_SOCIOECONOMICA – List	Pobreza extrema · Pobreza básica · Pobreza basica · Vulnerabilidad
cr-detectar-discapacidades.txt	24	CR_SALUD_DISCAPACIDAD – List	Física o motora · Fisica o motora · Auditiva · Visual
cr-detectar-distritos.txt	496	CR_L2_DISTRITO – List	Merced · Hospital · Catedral · Zapote
cr-detectar-estado-civil.txt	21	CR_L2_ESTADO_CIVIL – List	Soltero/a · Casado/a · Unión libre o de hecho · Union libre o de hecho
cr-detectar-etnias.txt	22	CR_L3_ETNIA – List	Indígena · Indigena · Afrodescendiente o negra · Mulata
cr-detectar-grupos-sanguineos.txt	18	CR_SALUD_GRUPO_SANGUINEO – List	A+ · A- · B+ · B-
cr-detectar-identidades-genero.txt	19	CR_L3_IDENTIDAD_GENERO – List	Mujer cisgénero · Mujer cisgenero · Hombre cisgénero · Hombre cisgenero
cr-detectar-medicamentos.txt	52	CR_SALUD_MEDICAMENTO – List	Acetaminofén · Acetaminofen · Ibuprofeno · Diclofenaco
cr-detectar-nacionalidades.txt	47	CR_L3_NACIONALIDAD – List	Costarricense · Nicaragüense · Nicaraguense · Panameña
cr-detectar-nivel-educativo.txt	27	CR_L2_NIVEL_EDUCATIVO – List	Sin instrucción · Sin instruccion · Preescolar · Primaria incompleta
cr-detectar-nombres.txt	449	CR_L1_NOMBRE – List CR_L1_NOMBRE_COMPLET 0 – List	Adolfo · Adrián · Adrian · Adriana

FILE	LINES	USED BY	FIRST LINES
cr-detectar-orientaciones-sexuales.txt	14	CR_L3_ORIENTACION_SEXUAL – List	Heterosexual · Gay · Lesbiana · Bisexual
cr-detectar-partidos.txt	26	CR_L3_AFILIACION_PARTIDARIA – List	Liberación Nacional · Liberacion Nacional · Unidad Social Cristiana · Progreso Social Democrático
cr-detectar-preferencias-politicas.txt	16	CR_L3_OPINION_POLITICA – List	Izquierda · Centroizquierda · Centro · Centroderecha
cr-detectar-programas-sociales.txt	20	CR_FIN_PROGRAMA_SOCIAL – List	Avancemos · Creemos · Bono de vivienda (BANHVI) · Red de Cuido
cr-detectar-pueblos.txt	52	CR_L3_PUEBLO_INDIGENA – List	Bribri · Cabécar · Cabecar · Maleku
cr-detectar-religiones.txt	46	CR_L3_RELIGION – List	Católica · Catolica · Evangélica o protestante · Evangelica o protestante
cr-detectar-sexo.txt	9	CR_L2_SEX0 – List	f · m · h · femenino
cr-detectar-sindicatos.txt	17	CR_L3_AFILIACION_SINDICAL – List	ANEP · APSE · SEC · ANDE
cr-detectar-tenencia-vivienda.txt	13	CR_FIN_VIVIENDA – List	Propia totalmente pagada · Propia pagando a plazos · Alquilada · En precario
cr-diagnosticos.txt	31	CR_DIAGNOSTICO_TEXT0	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
cr-direcciones.txt	4,000	CR_DIRECCION	125 metros sur de el puente, casa esquinera color verde · 75 metros sureste de el EBAIS, apartamento 3 · 500 metros este de la entrada principal, última casa a mano derecha · Urbanización La Paz, casa 101
cr-discapacidades.txt	7	CR_DISCAPACIDAD_LISTA	Física o motora · Auditiva · Visual · Intelectual
cr-distritos-generalizados.txt	11,582	CR_DISTRITO	Carmen San Nicolás · Carmen - San José Zapote - San José · Carmen, San José Zapote, San José · Carmen (San José) Zapote (San José)
cr-empleadores.txt	24	CR_EMPLEADOR	Distribuidora Central S.A. · Constructora del Valle S.A. · Transportes La Meseta S.A. · Supermercados El Ahorro S.A.
cr-estado-civil-codigos.txt	6	CR_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
cr-estado-civil.txt	6	CR_ESTADO_CIVIL_LISTA	Soltero/a · Casado/a · Unión libre o de hecho · Separado/a
cr-estados-credito.txt	13	CR_ESTADO_CREDITO	Categoría A1 — riesgo normal · Categoría A2 — riesgo normal · Categoría B1 — riesgo bajo · Categoría B2 — riesgo bajo
cr-etnias-codigos.txt	7	CR_ETNIA_CODIGO	1 · 2 · 3 · 4
cr-etnias.txt	7	CR_ETNIA_LISTA	Indígena · Afrodescendiente o negra · Mulata · China

FILE	LINES	USED BY	FIRST LINES
cr-grupos-sanguineos.txt	8	CR_GRUPO_SANGUINEO	A+ · A- · B+ · B-
cr-iban-paso.txt	1,067	CR_IBAN_PASO	000 000 · 001 101 · 002 202 · 003 303
cr-iban-resultado.txt	97	CR_IBAN_RESULTADO	00 06 · 01 76 · 02 49 · 03 22
cr-iban-traslado.txt	1,100	CR_IBAN TRASLADO	000 000 · 100 001 · 200 002 · 300 003
cr-identidades-genero.txt	7	CR_IDENTIDAD_GENERO_LISTA	Mujer cisgénero · Hombre cisgénero · Mujer trans · Hombre trans
cr-instituciones-educativas.txt	12	CR_INSTITUCION_EDUCATIVA	Escuela Juan Rafael Mora · Escuela República de Francia · Liceo de Costa Rica · Liceo del Sur
cr-medicamentos.txt	22	CR_MEDICAMENTO_LISTA	Acetaminofén · Ibuprofeno · Diclofenaco · Metformina
cr-nacionalidades.txt	14	CR_NACIONALIDAD	Costarricense · Nicaragüense · Panameña · Colombiana
cr-nivel-educativo-codigos.txt	11	CR_NIVEL_EDUCATIVO_CODIGO	1 · 2 · 3 · 4
cr-nivel-educativo.txt	11	CR_NIVEL_EDUCATIVO_LISTA	Sin instrucción · Preescolar · Primaria incompleta · Primaria completa
cr-nombres.txt	400	CR_NOMBRE	Adolfo · Adrián · Adriana · Aída
cr-ocupaciones.txt	37	CR_OCUPACION	Empleado administrativo · Dependiente de tienda · Cajero · Chofer
cr-orientaciones-sexuales.txt	8	CR_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
cr-partidos.txt	13	CR_PARTIDO_LISTA	Liberación Nacional · Unidad Social Cristiana · Progreso Social Democrático · Nueva República
cr-preferencias-politicas.txt	7	CR_PREFERENCIA POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
cr-procedimientos.txt	10	CR_PROCEDIMIENTO_TEXTO	Consulta de medicina general · Consulta de urgencias · Hemograma completo · Glicemia en ayunas
cr-programas-sociales.txt	10	CR_PROGRAMA_SOCIAL_LISTA	Avancemos · Crecemos · Bono de vivienda (BANHVI) · Red de Cuido
cr-pueblos.txt	11	CR_PUEBLO_LISTA	Bribri · Cabécar · Maleku · Chorotega
cr-religiones.txt	10	CR_RELIGION_LISTA	Católica · Evangélica o protestante · Testigo de Jehová · Adventista del Séptimo Día
cr-sexo-1-2.txt	2	CR_SEXO_1_2	1 · 2
cr-sexo-f-m.txt	2	CR_SEXO_F_M	F · M

FILE	LINES	USED BY	FIRST LINES
cr-sexo-female-male.txt	2	CR_SEXO_FEMALE_MALE	Female · Male
cr-sexo-femenino-masculino.txt	2	CR_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
cr-sexo-h-m.txt	2	CR_SEXO_H_M	H · M
cr-sexo-mujer-hombre.txt	2	CR_SEXO_MUJER_HOMBRE	Mujer · Hombre
cr-sin-informacion.txt	1	CR_SUPRIMIR	Sin información
cr-tenencia-vivienda.txt	6	CR_TENENCIA_VIVIENDA_LISTA	Propia totalmente pagada · Propia pagando a plazos · Alquilada · En precario
cr-texto-nombres.txt	1,944	CR_TEXTO_LIBRE	Adolfo · ADOLFO · Adrián · ADRIÁN

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

- E1** producto prod item articulo empresa emp razon social comercial fantasia archivo calle avenida camino carretera ruta barrio caserio poblado distrito canton provincia pais banco sucursal agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo escuela colegio liceo institucion universidad curso materia documento doc unidad clinica hospital ebais seguro area dependencia cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio partido sindicato religion lengua idioma lugar sede local tienda deposito bodega proveedor convenio contrato poliza aseguradora entidad organismo organizacion institucional parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona linea actividad rubro sector finca plano file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante imputado testigo medico docente socio heredero donante tutor pensionado jubilado customer patient employee member holder mother father spouse contact person student driver owner completo apellidos? usuario corto largo
- E2** producto prod item articulo empresa emp razon social comercial fantasia archivo calle avenida camino carretera ruta barrio caserio poblado distrito canton provincia pais banco sucursal agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo escuela colegio liceo institucion universidad curso materia documento doc unidad clinica hospital ebais seguro area dependencia cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio partido sindicato religion lengua idioma lugar sede local tienda deposito bodega proveedor convenio contrato poliza aseguradora entidad organismo organizacion institucional parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona linea actividad rubro sector finca plano file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante imputado testigo medico docente socio heredero donante tutor pensionado jubilado customer patient employee member holder mother father spouse contact person student driver owner

E3	producto prod item articulo empresa emp razon social comercial fantasia archivo calle avenida camino carretera ruta barrio caserio poblado distrito canton provincia pais banco sucursal agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo escuela colegio liceo institucion universidad curso materia documento doc unidad clinica hospital ebais seguro area dependencia cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio partido sindicato religion lengua idioma lugar sede local tienda deposito bodega proveedor convenio contrato poliza aseguradora entidad organismo organizacion institucional parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona linea actividad rubro sector finca plano file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario colaborador alumno estudiante deudor codeudor fiador garante solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante imputado testigo medico docente socio heredero donante tutor pensionado jubilado customer patient employee member holder mother father spouse contact person student driver owner full complete last first
E4	ip mac email e_?mail correo electr[ó]nica web url tipo id general regional
E5	ip mac email e_?mail web url type id
E6	id cd cod codigo tipo fecha estado num nro
E7	id tipo codigo fecha estado cola log
E8	cod codigo id electoral judicial escolar riego

APPENDIX D

Profile set and classifiers

The profile set `CR - Ley 8968 - v1` runs these 141 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, datos sensibles (art. 3 e y art. 9.1), datos de salud, condición socioeconómica y datos de bienes (art. 3 e y art. 1) y antecedentes penales, conforme a la Ley 8968 de Protección de la Persona frente al Tratamiento de sus Datos Personales de Costa Rica y su reglamento.

CLASSIFIER	KIND	DOMAIN
CR_L1_CEDULA - Path	COLUMN NAME	CR_L1_CEDULA
CR_L1_CEDULA - Type	DATA TYPE	CR_L1_CEDULA
CR_L1_CEDULA - Regex	VALUE FORMAT	CR_L1_CEDULA
CR_L1_DIMEX - Path	COLUMN NAME	CR_L1_DIMEX
CR_L1_DIMEX - Regex	VALUE FORMAT	CR_L1_DIMEX
CR_L1_NITE - Path	COLUMN NAME	CR_L1_NITE
CR_L1_NITE - Regex	VALUE FORMAT	CR_L1_NITE
CR_L1_PASAPORTE - Path	COLUMN NAME	CR_L1_PASAPORTE
CR_L1_PASAPORTE - Regex	VALUE FORMAT	CR_L1_PASAPORTE
CR_L1_SEGURO_SOCIAL - Path	COLUMN NAME	CR_L1_SEGURO_SOCIAL
CR_L1_CODIGO_ESTUDIANTE - Path	COLUMN NAME	CR_L1_CODIGO_ESTUDIANTE
CR_L1_MATRICULA_PROFESIONAL - Path	COLUMN NAME	CR_L1_MATRICULA_PROFESIONAL
CR_L1_NOMBRE - Path	COLUMN NAME	CR_L1_NOMBRE
CR_L1_NOMBRE - List	KNOWN VALUES	CR_L1_NOMBRE
CR_L1_APELLIDO - Path	COLUMN NAME	CR_L1_APELLIDO
CR_L1_APELLIDO - List	KNOWN VALUES	CR_L1_APELLIDO
CR_L1_NOMBRE_COMPLETO - Path	COLUMN NAME	CR_L1_NOMBRE_COMPLETO
CR_L1_NOMBRE_COMPLETO - List	KNOWN VALUES	CR_L1_NOMBRE_COMPLETO
CR_L1_EMAIL - Path	COLUMN NAME	CR_L1_EMAIL
CR_L1_EMAIL - Type	DATA TYPE	CR_L1_EMAIL
CR_L1_EMAIL - Regex	VALUE FORMAT	CR_L1_EMAIL
CR_L1_TELEFONO - Path	COLUMN NAME	CR_L1_TELEFONO
CR_L1_TELEFONO - Regex	VALUE FORMAT	CR_L1_TELEFONO
CR_L1_DIRECCION - Path	COLUMN NAME	CR_L1_DIRECCION
CR_L1_DIRECCION - Type	DATA TYPE	CR_L1_DIRECCION
CR_L1_DIRECCION - Regex	VALUE FORMAT	CR_L1_DIRECCION
CR_L1_DIRECCION_COMPLEMENTO - Path	COLUMN NAME	CR_L1_DIRECCION_COMPLEMENTO
CR_L1_CUENTA_BANCARIA - Path	COLUMN NAME	CR_L1_CUENTA_BANCARIA
CR_L1_CUENTA_BANCARIA - Regex	VALUE FORMAT	CR_L1_CUENTA_BANCARIA
CR_L1_TARJETA - Path	COLUMN NAME	CR_L1_TARJETA

CLASSIFIER	KIND	DOMAIN
CR_L1_TARJETA - Regex	VALUE FORMAT	CR_L1_TARJETA
CR_L1_BILLETERA - Path	COLUMN NAME	CR_L1_BILLETERA
CR_L1_BILLETERA - Regex	VALUE FORMAT	CR_L1_BILLETERA
CR_L1_IP - Path	COLUMN NAME	CR_L1_IP
CR_L1_IP - Regex	VALUE FORMAT	CR_L1_IP
CR_L1_DISPOSITIVO - Path	COLUMN NAME	CR_L1_DISPOSITIVO
CR_L1_DISPOSITIVO - Regex	VALUE FORMAT	CR_L1_DISPOSITIVO
CR_L1_COOKIE - Path	COLUMN NAME	CR_L1_COOKIE
CR_L1_PLACA - Path	COLUMN NAME	CR_L1_PLACA
CR_L1_PLACA - Regex	VALUE FORMAT	CR_L1_PLACA
CR_L1_VEHICULO - Path	COLUMN NAME	CR_L1_VEHICULO
CR_L1_VEHICULO - Regex	VALUE FORMAT	CR_L1_VEHICULO
CR_L1_INMUEBLE - Path	COLUMN NAME	CR_L1_INMUEBLE
CR_L1_INMUEBLE - Regex	VALUE FORMAT	CR_L1_INMUEBLE
CR_L1_CONTRATO - Path	COLUMN NAME	CR_L1_CONTRATO
CR_L1_USUARIO - Path	COLUMN NAME	CR_L1_USUARIO
CR_L1_CREDENCIAL - Path	COLUMN NAME	CR_L1_CREDENCIAL
CR_L1_IMAGEN - Path	COLUMN NAME	CR_L1_IMAGEN
CR_L1_GEOLOCALIZACION - Path	COLUMN NAME	CR_L1_GEOLOCALIZACION
CR_L1_GEOLOCALIZACION - Regex	VALUE FORMAT	CR_L1_GEOLOCALIZACION
CR_L1_TEXTO_LIBRE - Path	COLUMN NAME	CR_L1_TEXTO_LIBRE
CR_L1_TEXTO_LIBRE - Type	DATA TYPE	CR_L1_TEXTO_LIBRE
CR_L1_TEXTO_LIBRE - Regex	VALUE FORMAT	CR_L1_TEXTO_LIBRE
CR_L2_FECHA_NACIMIENTO - Path	COLUMN NAME	CR_L2_FECHA_NACIMIENTO
CR_L2_FECHA_NACIMIENTO - Type	DATA TYPE	CR_L2_FECHA_NACIMIENTO
CR_L2_ANIO_NACIMIENTO - Path	COLUMN NAME	CR_L2_ANIO_NACIMIENTO
CR_L2_ANIO_NACIMIENTO - Type	DATA TYPE	CR_L2_ANIO_NACIMIENTO
CR_L2_EDAD - Path	COLUMN NAME	CR_L2_EDAD
CR_L2_EDAD - Type	DATA TYPE	CR_L2_EDAD
CR_L2_FECHA_EVENTO - Path	COLUMN NAME	CR_L2_FECHA_EVENTO
CR_L2_FECHA_EVENTO - Type	DATA TYPE	CR_L2_FECHA_EVENTO
CR_L2_SEX0 - Path	COLUMN NAME	CR_L2_SEX0
CR_L2_SEX0 - List	KNOWN VALUES	CR_L2_SEX0
CR_L2_DISTRITO - Path	COLUMN NAME	CR_L2_DISTRITO
CR_L2_DISTRITO - List	KNOWN VALUES	CR_L2_DISTRITO
CR_L2_CODIGO_DTA - Path	COLUMN NAME	CR_L2_CODIGO_DTA
CR_L2_CODIGO_DTA - Regex	VALUE FORMAT	CR_L2_CODIGO_DTA

CLASSIFIER	KIND	DOMAIN
CR_L2_BARRIO – Path	COLUMN NAME	CR_L2_BARRIO
CR_L2_ESTADO_CIVIL – Path	COLUMN NAME	CR_L2_ESTADO_CIVIL
CR_L2_ESTADO_CIVIL – List	KNOWN VALUES	CR_L2_ESTADO_CIVIL
CR_L2_OCUPACION – Path	COLUMN NAME	CR_L2_OCUPACION
CR_L2_EMPLEADOR – Path	COLUMN NAME	CR_L2_EMPLEADOR
CR_L2_NIVEL_EDUCATIVO – Path	COLUMN NAME	CR_L2_NIVEL_EDUCATIVO
CR_L2_NIVEL_EDUCATIVO – List	KNOWN VALUES	CR_L2_NIVEL_EDUCATIVO
CR_L2_INSTITUCION_EDUCATIVA – Path	COLUMN NAME	CR_L2_INSTITUCION_EDUCATIVA
CR_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	CR_L2_PERSONAS_A_CARGO
CR_L2_PERSONAS_A_CARGO – Type	DATA TYPE	CR_L2_PERSONAS_A_CARGO
CR_L3_ETNIA – Path	COLUMN NAME	CR_L3_ETNIA
CR_L3_ETNIA – List	KNOWN VALUES	CR_L3_ETNIA
CR_L3_PUEBLO_INDIGENA – Path	COLUMN NAME	CR_L3_PUEBLO_INDIGENA
CR_L3_PUEBLO_INDIGENA – List	KNOWN VALUES	CR_L3_PUEBLO_INDIGENA
CR_L3_NACIONALIDAD – Path	COLUMN NAME	CR_L3_NACIONALIDAD
CR_L3_NACIONALIDAD – List	KNOWN VALUES	CR_L3_NACIONALIDAD
CR_L3_CONDICION_MIGRATORIA – Path	COLUMN NAME	CR_L3_CONDICION_MIGRATORIA
CR_L3_CONDICION_MIGRATORIA – List	KNOWN VALUES	CR_L3_CONDICION_MIGRATORIA
CR_L3_RELIGION – Path	COLUMN NAME	CR_L3_RELIGION
CR_L3_RELIGION – List	KNOWN VALUES	CR_L3_RELIGION
CR_L3_CONVICCION_FILOSOFICA – Path	COLUMN NAME	CR_L3_CONVICCION_FILOSOFICA
CR_L3_OPINION_POLITICA – Path	COLUMN NAME	CR_L3_OPINION_POLITICA
CR_L3_OPINION_POLITICA – List	KNOWN VALUES	CR_L3_OPINION_POLITICA
CR_L3_AFILIACION_PARTIDARIA – Path	COLUMN NAME	CR_L3_AFILIACION_PARTIDARIA
CR_L3_AFILIACION_PARTIDARIA – List	KNOWN VALUES	CR_L3_AFILIACION_PARTIDARIA
CR_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	CR_L3_AFILIACION_SINDICAL
CR_L3_AFILIACION_SINDICAL – List	KNOWN VALUES	CR_L3_AFILIACION_SINDICAL
CR_L3_BIOMETRICO – Path	COLUMN NAME	CR_L3_BIOMETRICO
CR_L3_BIOMETRICO – Type	DATA TYPE	CR_L3_BIOMETRICO
CR_L3_GENETICO – Path	COLUMN NAME	CR_L3_GENETICO
CR_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	CR_L3_ORIENTACION_SEXUAL
CR_L3_ORIENTACION_SEXUAL – List	KNOWN VALUES	CR_L3_ORIENTACION_SEXUAL
CR_L3_VIDA_SEXUAL – Path	COLUMN NAME	CR_L3_VIDA_SEXUAL
CR_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	CR_L3_IDENTIDAD_GENERO
CR_L3_IDENTIDAD_GENERO – List	KNOWN VALUES	CR_L3_IDENTIDAD_GENERO
CR_L3_VICTIMA – Path	COLUMN NAME	CR_L3_VICTIMA
CR_SALUD_IDENTIFICADOR – Path	COLUMN NAME	CR_SALUD_IDENTIFICADOR

CLASSIFIER	KIND	DOMAIN
CR_SALUD_COBERTURA – Path	COLUMN NAME	CR_SALUD_COBERTURA
CR_SALUD_COBERTURA – List	KNOWN VALUES	CR_SALUD_COBERTURA
CR_SALUD_DIAGNOSTICO – Path	COLUMN NAME	CR_SALUD_DIAGNOSTICO
CR_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	CR_SALUD_DIAGNOSTICO
CR_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	CR_SALUD_PROCEDIMIENTO
CR_SALUD_MEDICAMENTO – Path	COLUMN NAME	CR_SALUD_MEDICAMENTO
CR_SALUD_MEDICAMENTO – List	KNOWN VALUES	CR_SALUD_MEDICAMENTO
CR_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	CR_SALUD_TEXTO_CLINICO
CR_SALUD_TEXTO_CLINICO – Type	DATA TYPE	CR_SALUD_TEXTO_CLINICO
CR_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	CR_SALUD_RESULTADO_EXAMEN
CR_SALUD_VIH – Path	COLUMN NAME	CR_SALUD_VIH
CR_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	CR_SALUD_GRUPO_SANGUINEO
CR_SALUD_GRUPO_SANGUINEO – List	KNOWN VALUES	CR_SALUD_GRUPO_SANGUINEO
CR_SALUD_DISCAPACIDAD – Path	COLUMN NAME	CR_SALUD_DISCAPACIDAD
CR_SALUD_DISCAPACIDAD – List	KNOWN VALUES	CR_SALUD_DISCAPACIDAD
CR_SALUD_OCUPACIONAL – Path	COLUMN NAME	CR_SALUD_OCUPACIONAL
CR_SALUD_OCUPACIONAL – List	KNOWN VALUES	CR_SALUD_OCUPACIONAL
CR_SALUD_REPRODUCTIVA – Path	COLUMN NAME	CR_SALUD_REPRODUCTIVA
CR_SALUD_MENTAL – Path	COLUMN NAME	CR_SALUD_MENTAL
CR_FIN_HISTORIAL_CREDITICIO – Path	COLUMN NAME	CR_FIN_HISTORIAL_CREDITICIO
CR_FIN_DEUDA – Path	COLUMN NAME	CR_FIN_DEUDA
CR_FIN_DEUDA – Type	DATA TYPE	CR_FIN_DEUDA
CR_FIN_INGRESOS – Path	COLUMN NAME	CR_FIN_INGRESOS
CR_FIN_INGRESOS – Type	DATA TYPE	CR_FIN_INGRESOS
CR_FIN_PATRIMONIO – Path	COLUMN NAME	CR_FIN_PATRIMONIO
CR_FIN_PATRIMONIO – Type	DATA TYPE	CR_FIN_PATRIMONIO
CR_FIN_PENSION – Path	COLUMN NAME	CR_FIN_PENSION
CR_FIN_PENSION – Type	DATA TYPE	CR_FIN_PENSION
CR_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	CR_FIN_PROGRAMA_SOCIAL
CR_FIN_PROGRAMA_SOCIAL – List	KNOWN VALUES	CR_FIN_PROGRAMA_SOCIAL
CR_FIN_CONDICION_SOCIOECONOMICA – Path	COLUMN NAME	CR_FIN_CONDICION_SOCIOECONOMICA
CR_FIN_CONDICION_SOCIOECONOMICA – List	KNOWN VALUES	CR_FIN_CONDICION_SOCIOECONOMICA
CR_FIN_VIVIENDA – Path	COLUMN NAME	CR_FIN_VIVIENDA
CR_FIN_VIVIENDA – List	KNOWN VALUES	CR_FIN_VIVIENDA
CR_PENAL_ANTECEDENTES – Path	COLUMN NAME	CR_PENAL_ANTECEDENTES
CR_PENAL_EXPEDIENTE – Path	COLUMN NAME	CR_PENAL_EXPEDIENTE
CR_PENAL_EXPEDIENTE – Regex	VALUE FORMAT	CR_PENAL_EXPEDIENTE