

# Mexico — LFPDPPP

Discovering and masking Mexican personal data: direct identifiers with valid check digits, quasi-identifiers, the sensitive data of article 2 and the financial and patrimonial data of article 7.

---

83

DOMAINS

153

CLASSIFIERS

154

ALGORITHMS

# Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

|          |                                         |
|----------|-----------------------------------------|
| <b>1</b> | <b>About this profile set</b>           |
| <b>2</b> | <b>The LFPDPPP in brief</b>             |
| <b>3</b> | <b>How sensitive data is discovered</b> |
| <b>4</b> | <b>How data is masked</b>               |
| <b>5</b> | <b>Essential and extended packs</b>     |
| <b>6</b> | <b>Domains at a glance</b>              |

## PART 7 · DIRECT IDENTIFIERS

|             |                                      |                             |
|-------------|--------------------------------------|-----------------------------|
| <b>7.1</b>  | <b>CURP</b>                          | MX_L1_CURP                  |
| <b>7.2</b>  | <b>RFC</b>                           | MX_L1_RFC                   |
| <b>7.3</b>  | <b>Social security number (NSS)</b>  | MX_L1_NSS                   |
| <b>7.4</b>  | <b>INE voter key</b>                 | MX_L1_CLAVE_ELECTOR         |
| <b>7.5</b>  | <b>INE credential numbers</b>        | MX_L1_CREDENCIAL_INE        |
| <b>7.6</b>  | <b>Given names</b>                   | MX_L1_NOMBRE                |
| <b>7.7</b>  | <b>Surnames</b>                      | MX_L1_APELLIDO              |
| <b>7.8</b>  | <b>Full name</b>                     | MX_L1_NOMBRE_COMPLETO       |
| <b>7.9</b>  | <b>E-mail</b>                        | MX_L1_EMAIL                 |
| <b>7.10</b> | <b>Phone number</b>                  | MX_L1_TELEFONO              |
| <b>7.11</b> | <b>Address</b>                       | MX_L1_DIRECCION             |
| <b>7.12</b> | <b>Address details</b>               | MX_L1_DIRECCION_COMPLEMENTO |
| <b>7.13</b> | <b>CLABE</b>                         | MX_L1_CLABE                 |
| <b>7.14</b> | <b>Bank account</b>                  | MX_L1_CUENTA_BANCARIA       |
| <b>7.15</b> | <b>Payment card</b>                  | MX_L1_TARJETA               |
| <b>7.16</b> | <b>Passport</b>                      | MX_L1_PASAPORTE             |
| <b>7.17</b> | <b>Immigration document</b>          | MX_L1_DOCUMENTO_MIGRATORIO  |
| <b>7.18</b> | <b>Professional license</b>          | MX_L1_CEDULA_PROFESIONAL    |
| <b>7.19</b> | <b>Driver's license</b>              | MX_L1_LICENCIA_CONDUCCIR    |
| <b>7.20</b> | <b>e.firma certificate</b>           | MX_L1_EFIRMA                |
| <b>7.21</b> | <b>IP address</b>                    | MX_L1_IP                    |
| <b>7.22</b> | <b>Device identifier</b>             | MX_L1_DISPOSITIVO           |
| <b>7.23</b> | <b>License plate</b>                 | MX_L1_PLACA                 |
| <b>7.24</b> | <b>Vehicle identification number</b> | MX_L1_NIV                   |
| <b>7.25</b> | <b>Contract and customer numbers</b> | MX_L1_NUMERO_CONTRATO       |

|      |                           |                       |
|------|---------------------------|-----------------------|
| 7.26 | Username and social media | MX_L1_USUARIO_RRSS    |
| 7.27 | Credentials               | MX_L1_CREDENCIAL      |
| 7.28 | Geolocation               | MX_L1_GEOLOCALIZACION |
| 7.29 | Free text                 | MX_L1_TEXTO_LIBRE     |

#### PART 8 · QUASI-IDENTIFIERS

|      |                         |                        |
|------|-------------------------|------------------------|
| 8.1  | Birth date              | MX_L2_FECHA_NACIMIENTO |
| 8.2  | Birth year              | MX_L2_ANIO_NACIMIENTO  |
| 8.3  | Age                     | MX_L2_EDAD             |
| 8.4  | Life event dates        | MX_L2_FECHA_EVENTO     |
| 8.5  | Sex                     | MX_L2_SEXO             |
| 8.6  | Municipality            | MX_L2_MUNICIPIO        |
| 8.7  | Municipality code       | MX_L2_CLAVE_MUNICIPIO  |
| 8.8  | Locality                | MX_L2_LOCALIDAD        |
| 8.9  | Colonia                 | MX_L2_COLONIA          |
| 8.10 | Postal code             | MX_L2_CODIGO_POSTAL    |
| 8.11 | Nationality             | MX_L2_NACIONALIDAD     |
| 8.12 | Marital status          | MX_L2_ESTADO_CIVIL     |
| 8.13 | Occupation              | MX_L2_OCUPACION        |
| 8.14 | Employer                | MX_L2_EMPLEADOR        |
| 8.15 | Schooling               | MX_L2_ESCOLARIDAD      |
| 8.16 | School                  | MX_L2_ESCUELA          |
| 8.17 | School code (CCT)       | MX_L2_CCT              |
| 8.18 | Dependents and children | MX_L2_DEPENDIENTES     |

#### PART 9 · SENSITIVE DATA

|      |                                |                                 |
|------|--------------------------------|---------------------------------|
| 9.1  | Ethnic origin                  | MX_L3_ETNIA                     |
| 9.2  | Indigenous language            | MX_L3 LENGUA_INDIGENA           |
| 9.3  | Diagnosis                      | MX_L3_SALUD_DIAGNOSTICO         |
| 9.4  | Medication                     | MX_L3_SALUD_MEDICAMENTO         |
| 9.5  | Health record identifiers      | MX_L3_SALUD_IDENTIFICADOR       |
| 9.6  | Clinical notes                 | MX_L3_SALUD_TEXTO_CLINICO       |
| 9.7  | Test results                   | MX_L3_SALUD_RESULTADO_EXAMEN    |
| 9.8  | Blood type                     | MX_L3_SALUD_GRUPO_SANGUINEO     |
| 9.9  | Disability                     | MX_L3_SALUD_DISCAPACIDAD        |
| 9.10 | Sexual and reproductive health | MX_L3_SALUD_SEXUAL_REPRODUCTIVA |
| 9.11 | Mental health and addictions   | MX_L3_SALUD_MENTAL_ADICCIONES   |
| 9.12 | Biometric data                 | MX_L3_BIOMETRICO                |

|      |                                 |                                 |
|------|---------------------------------|---------------------------------|
| 9.13 | Genetic information             | MX_L3_INFORMACION_GENETICA      |
| 9.14 | Sexual preference               | MX_L3_PREFERENCIA_SEXUAL        |
| 9.15 | Gender identity                 | MX_L3_IDENTIDAD_GENERO          |
| 9.16 | Sexual life                     | MX_L3_VIDA_SEXUAL               |
| 9.17 | Religion                        | MX_L3_RELIGION                  |
| 9.18 | Philosophical and moral beliefs | MX_L3_CREENCIA_FILOSOFICA_MORAL |
| 9.19 | Political opinions              | MX_L3_OPINION_POLITICA          |
| 9.20 | Party membership                | MX_L3_AFILIACION_POLITICA       |
| 9.21 | Union membership                | MX_L3_AFILIACION_SINDICAL       |

#### PART 10 · FINANCIAL AND PATRIMONIAL DATA

|       |                                |                             |
|-------|--------------------------------|-----------------------------|
| 10.1  | Credit bureau record           | MX_FIN_BURO_CREDITO         |
| 10.2  | Debt amount                    | MX_FIN_MONTO_DEUDA          |
| 10.3  | Monthly income                 | MX_FIN_INGRESO_MENSUAL      |
| 10.4  | Daily wage (SDI, SBC)          | MX_FIN_SALARIO_DIARIO       |
| 10.5  | Assets                         | MX_FIN_PATRIMONIO           |
| 10.6  | AFORE                          | MX_FIN_AFORE                |
| 10.7  | Retirement and housing savings | MX_FIN_SALDO_RETIRO         |
| 10.8  | Housing credit                 | MX_FIN_CREDITO_VIVIENDA     |
| 10.9  | Social security coverage       | MX_FIN_SEGURIDAD_SOCIAL     |
| 10.10 | Social programs                | MX_FIN_PROGRAMA_SOCIAL      |
| 10.11 | Socioeconomic level            | MX_FIN_NIVEL_SOCIOECONOMICO |
| 10.12 | Housing tenure                 | MX_FIN_VIVIENDA             |
| 10.13 | Tax regime                     | MX_FIN_REGIMEN_FISCAL       |

#### PART 11 · CRIMINAL RECORDS

|      |                                  |                       |
|------|----------------------------------|-----------------------|
| 11.1 | Criminal records                 | MX_PENAL_ANTECEDENTES |
| 11.2 | Case numbers                     | MX_PENAL_CAUSA        |
| 12   | Check digits computed by the set |                       |
| 13   | Dates inside keys                |                       |
| 14   | Limits                           |                       |
| 15   | Verification                     |                       |
| 16   | Sources                          |                       |
| A    | Algorithms                       |                       |
| B    | Files                            |                       |
| C    | Exclusion lists                  |                       |
| D    | Profile set and classifiers      |                       |

# About this profile set

This profile set finds the personal data in a Mexican database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and CURPs does not achieve that: a birth date, a sex and a small municipality single people out on their own. The set works in the same layers the risk does:

- **Direct identifiers** — CURP, RFC, NSS, INE voter key, names, contact details, CLABE and cards, documents, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, municipality, locality, colonia, postal code, occupation, employer, schooling.
- **Sensitive data** — ethnic origin and indigenous language, health, genetic information, religious, philosophical and moral beliefs, political opinions, sexual preference, and union membership.
- **Financial and patrimonial data** — credit bureau records, debts, income, assets, retirement savings, housing credit, social security, social programs, socioeconomic level, tax regime.
- **Criminal records** — records and case numbers.

On a Masking Engine the set is one profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — NOMBRE , RESULTADO , CIUDAD — needs the values to agree. A column with a meaningless name ( CAMP01 , OBS ) is still found when its values have a recognizable shape or vocabulary: a CURP, an RFC, an INE voter key, a CLABE, a plate, a municipality.

Column names are recognized in Spanish, in the abbreviations of Mexican systems ( AP\_PATERN0 , FEC\_NAC , NUM\_EXT , CVE\_MUN , SDI ), in the attribute names of CFDI 4.0 invoices ( RfcReceptor , DomicilioFiscalReceptor , RegimenFiscalReceptor ) and in English.

Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often store photos of the INE credential: the CURP and the voter key stay readable in the image. Report those columns as residual risk.

# The LFPDPPP in brief

The Ley Federal de Protección de Datos Personales en Posesión de los Particulares was published in the Diario Oficial de la Federación on 20 March 2025 and took effect the next day, repealing the law of 2010. Its last amendment (14 November 2025) touched only its supplementary procedural rules. The INAI was dissolved: the authority is now the **Secretaría Anticorrupción y Buen Gobierno**. The public sector has its own law, the Ley General de Protección de Datos Personales en Posesión de Sujetos Obligados, issued the same day.

What matters for a copy of production data:

- **Personal data** is any information about an identified or identifiable person — identifiable directly or indirectly, through any information (art. 2, V).
- **Sensitive data** are those that touch the most intimate sphere of a person or whose misuse may lead to discrimination or serious risk. The law names, as examples and not as a closed list, data that may reveal racial or ethnic origin, present or future health, genetic information, religious, philosophical and moral

beliefs, political opinions and sexual preference (art. 2, VI). They need express written consent, and databases of sensitive data may only be created for legitimate, specific purposes (art. 8).

- **Financial and patrimonial data** need express consent (art. 7).
- **Purpose.** Data may only be processed for the purposes of the privacy notice; a different purpose needs new consent (art. 11). Development and testing are rarely among the purposes a customer agreed to.
- **Dissociation** — a procedure after which data can no longer be associated with the person nor, by their structure, content or level of detail, identify them (art. 2, IX). Consent is not required for data subjected to prior dissociation (art. 9, III).
- **Security.** Administrative, technical and physical measures proportional to the sensitivity of the data (art. 18); breaches that significantly affect people must be reported to them (art. 19); everyone involved keeps confidentiality (art. 20).
- **Sanctions.** Fines up to 320,000 times the UMA, which may be doubled for sensitive data (art. 59); prison of three months to five years for the crimes of chapter XII, doubled for sensitive data (arts. 62 to 64).

A test environment filled with production data is processing for a purpose the privacy notice does not cover, and holds sensitive and financial data outside the controls built for them. A dissociated copy is the route the law itself provides: that is what this set is for.

Two notes on the categories. The 2010 law listed **union membership** as sensitive; the 2025 text no longer names it. Its list is not exhaustive and union membership still exposes people to discrimination, so the set keeps it. **Biometric data** are not named either; they identify a person by definition and are treated as sensitive here.

This document describes technical controls. Whether a copy counts as dissociated is a legal assessment of the whole environment — its access, its retention, what else is joined to it — and not of the profile set alone.

---

3

## How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters:

`rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

## How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

## Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

| PACK             | DOMAINS | CLASSIFIERS | ALGORITHMS | FILES |
|------------------|---------|-------------|------------|-------|
| <b>Essential</b> | 13      | 31          | 63         | 25    |
| <b>Extended</b>  | 83      | 153         | 154        | 97    |

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- CURP — `MX_L1_CURP`
- RFC — `MX_L1_RFC`
- Social security number (NSS) — `MX_L1_NSS`
- INE voter key — `MX_L1_CLAVE_ELECTOR`
- Given names — `MX_L1_NOMBRE`
- Surnames — `MX_L1_APELLIDO`
- Full name — `MX_L1_NOMBRE_COMPLETO`
- E-mail — `MX_L1_EMAIL`
- Phone number — `MX_L1_TELEFONO`
- Address — `MX_L1_DIRECCION`
- Address details — `MX_L1_DIRECCION_COMPLEMENTO`
- Passport — `MX_L1_PASAPORTE`
- Birth date — `MX_L2_FECHA_NACIMIENTO`

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

# Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

| DOMAIN                                                                       | FOUND BY                           | ALGORITHM          |
|------------------------------------------------------------------------------|------------------------------------|--------------------|
| DIRECT IDENTIFIERS                                                           |                                    |                    |
| <b>CURP</b> <span>ESSENTIAL</span><br>MX_L1_CURP                             | COLUMN NAME DATA TYPE VALUE FORMAT | MX_CURP            |
| <b>RFC</b> <span>ESSENTIAL</span><br>MX_L1_RFC                               | COLUMN NAME DATA TYPE VALUE FORMAT | MX_RFC             |
| <b>Social security number (NSS)</b> <span>ESSENTIAL</span><br>MX_L1_NSS      | COLUMN NAME DATA TYPE VALUE FORMAT | MX_NSS             |
| <b>INE voter key</b> <span>ESSENTIAL</span><br>MX_L1_CLAVE_ELECTOR           | COLUMN NAME DATA TYPE VALUE FORMAT | MX_CLAVE_ELECTOR   |
| <b>INE credential numbers</b><br>MX_L1_CREDENCIAL_INE                        | COLUMN NAME VALUE FORMAT           | MX_CM_ALFANUM      |
| <b>Given names</b> <span>ESSENTIAL</span><br>MX_L1_NOMBRE                    | COLUMN NAME KNOWN VALUES           | MX_NOMBRES         |
| <b>Surnames</b> <span>ESSENTIAL</span><br>MX_L1_APELLIDO                     | COLUMN NAME KNOWN VALUES           | MX_APELLIDOS       |
| <b>Full name</b> <span>ESSENTIAL</span><br>MX_L1_NOMBRE_COMPLETO             | COLUMN NAME KNOWN VALUES           | MX_NOMBRE_COMPLETO |
| <b>E-mail</b> <span>ESSENTIAL</span><br>MX_L1_EMAIL                          | COLUMN NAME DATA TYPE VALUE FORMAT | MX_EMAIL           |
| <b>Phone number</b> <span>ESSENTIAL</span><br>MX_L1_TELEFONO                 | COLUMN NAME VALUE FORMAT           | MX_TELEFONO        |
| <b>Address</b> <span>ESSENTIAL</span><br>MX_L1_DIRECCION                     | COLUMN NAME DATA TYPE VALUE FORMAT | MX_DIRECCION       |
| <b>Address details</b> <span>ESSENTIAL</span><br>MX_L1_DIRECCION_COMPLEMENTO | COLUMN NAME                        | MX_CM_ALFANUM      |
| <b>CLABE</b><br>MX_L1_CLABE                                                  | COLUMN NAME DATA TYPE VALUE FORMAT | MX_CLABE           |
| <b>Bank account</b><br>MX_L1_CUENTA_BANCARIA                                 | COLUMN NAME                        | MX_CM_ALFANUM      |
| <b>Payment card</b><br>MX_L1_TARJETA                                         | COLUMN NAME VALUE FORMAT           | MX_TARJETA         |
| <b>Passport</b> <span>ESSENTIAL</span><br>MX_L1_PASAPORTE                    | COLUMN NAME VALUE FORMAT           | MX_CM_ALFANUM      |
| <b>Immigration document</b><br>MX_L1_DOCUMENTO_MIGRATORIO                    | COLUMN NAME                        | MX_CM_ALFANUM      |
| <b>Professional license</b><br>MX_L1_CEDULA_PROFESIONAL                      | COLUMN NAME VALUE FORMAT           | MX_CM_ALFANUM      |
| <b>Driver's license</b><br>MX_L1_LICENCIA_CONDU CIR                          | COLUMN NAME                        | MX_CM_ALFANUM      |

| DOMAIN                                                        | FOUND BY    |              |              | ALGORITHM           |
|---------------------------------------------------------------|-------------|--------------|--------------|---------------------|
| <b>e.firma certificate</b><br>MX_L1_EFIRMA                    | COLUMN NAME | VALUE FORMAT |              | MX_CM_ALFANUM       |
| <b>IP address</b><br>MX_L1_IP                                 | COLUMN NAME | VALUE FORMAT |              | MX_IP               |
| <b>Device identifier</b><br>MX_L1_DISPOSITIVO                 | COLUMN NAME | VALUE FORMAT |              | MX_CM_HEX           |
| <b>License plate</b><br>MX_L1_PLACA                           | COLUMN NAME | VALUE FORMAT |              | MX_PLACA            |
| <b>Vehicle identification number</b><br>MX_L1_NIV             | COLUMN NAME | VALUE FORMAT |              | MX_CM_ALFANUM       |
| <b>Contract and customer numbers</b><br>MX_L1_NUMERO_CONTRATO | COLUMN NAME |              |              | MX_CM_ALFANUM       |
| <b>Username and social media</b><br>MX_L1_USUARIO_RRSS        | COLUMN NAME |              |              | MX_CM_ALFANUM       |
| <b>Credentials</b><br>MX_L1_CREDENCIAL                        | COLUMN NAME |              |              | MX_REDACTAR         |
| <b>Geolocation</b><br>MX_L1_GEOLOCALIZACION                   | COLUMN NAME | VALUE FORMAT |              | MX_COORDENADA       |
| <b>Free text</b><br>MX_L1_TEXTO_LIBRE                         | COLUMN NAME | DATA TYPE    | VALUE FORMAT | MX_TEXTO_LIBRE      |
| QUASI-IDENTIFIERS                                             |             |              |              |                     |
| <b>Birth date</b> ESSENTIAL<br>MX_L2_FECHA_NACIMIENTO         | COLUMN NAME | DATA TYPE    |              | MX_FECHA_NACIMIENTO |
| <b>Birth year</b><br>MX_L2_ANIO_NACIMIENTO                    | COLUMN NAME | DATA TYPE    |              | MX_ANIO             |
| <b>Age</b><br>MX_L2_EDAD                                      | COLUMN NAME | DATA TYPE    |              | MX_EDAD             |
| <b>Life event dates</b><br>MX_L2_FECHA_EVENTO                 | COLUMN NAME | DATA TYPE    |              | MX_FECHA_EVENTO     |
| <b>Sex</b><br>MX_L2_SEXO                                      | COLUMN NAME | KNOWN VALUES |              | MX_SEXO             |
| <b>Municipality</b><br>MX_L2_MUNICIPIO                        | COLUMN NAME | KNOWN VALUES |              | MX_MUNICIPIO        |
| <b>Municipality code</b><br>MX_L2_CLAVE_MUNICIPIO             | COLUMN NAME | DATA TYPE    | KNOWN VALUES | MX_CLAVE_MUNICIPIO  |
| <b>Locality</b><br>MX_L2_LOCALIDAD                            | COLUMN NAME |              |              | MX_LOCALIDAD        |
| <b>Colonia</b><br>MX_L2_COLONIA                               | COLUMN NAME |              |              | MX_COLONIA          |
| <b>Postal code</b><br>MX_L2_CODIGO_POSTAL                     | COLUMN NAME | VALUE FORMAT |              | MX_CODIGO_POSTAL    |
| <b>Nationality</b><br>MX_L2_NACIONALIDAD                      | COLUMN NAME | KNOWN VALUES |              | MX_NACIONALIDAD     |
| <b>Marital status</b><br>MX_L2_ESTADO_CIVIL                   | COLUMN NAME | KNOWN VALUES |              | MX_ESTADO_CIVIL     |

| DOMAIN                                                                   | FOUND BY                    | ALGORITHM              |
|--------------------------------------------------------------------------|-----------------------------|------------------------|
| <b>Occupation</b><br>MX_L2_OCUPACION                                     | COLUMN NAME                 | MX_OCUPACION           |
| <b>Employer</b><br>MX_L2_EMPLEADOR                                       | COLUMN NAME                 | MX_EMPLEADOR           |
| <b>Schooling</b><br>MX_L2_ESCOLARIDAD                                    | COLUMN NAME<br>KNOWN VALUES | MX_ESCOLARIDAD         |
| <b>School</b><br>MX_L2_ESCUELA                                           | COLUMN NAME                 | MX_ESCUELA             |
| <b>School code (CCT)</b><br>MX_L2_CCT                                    | COLUMN NAME<br>VALUE FORMAT | MX_CM_ALFANUM          |
| <b>Dependents and children</b><br>MX_L2_DEPENDIENTES                     | COLUMN NAME<br>DATA TYPE    | MX_CANTIDAD_ACOTADA    |
| SENSITIVE DATA                                                           |                             |                        |
| <b>Ethnic origin</b><br>MX_L3_ETNIA                                      | COLUMN NAME<br>KNOWN VALUES | MX_PUEBLO              |
| <b>Indigenous language</b><br>MX_L3_LENGUA_INDIGENA                      | COLUMN NAME<br>KNOWN VALUES | MX_LENGUA_INDIGENA     |
| <b>Diagnosis</b><br>MX_L3_SALUD_DIAGNOSTICO                              | COLUMN NAME<br>VALUE FORMAT | MX_DIAGNOSTICO         |
| <b>Medication</b><br>MX_L3_SALUD_MEDICAMENTO                             | COLUMN NAME<br>KNOWN VALUES | MX_MEDICAMENTO         |
| <b>Health record identifiers</b><br>MX_L3_SALUD_IDENTIFICADOR            | COLUMN NAME                 | MX_CM_ALFANUM          |
| <b>Clinical notes</b><br>MX_L3_SALUD_TEXTO_CLINICO                       | COLUMN NAME<br>DATA TYPE    | MX_TEXTO_LIBRE         |
| <b>Test results</b><br>MX_L3_SALUD_RESULTADO_EXAMEN                      | COLUMN NAME                 | MX_CM_ALFANUM          |
| <b>Blood type</b><br>MX_L3_SALUD_GRUPO_SANGUINEO                         | COLUMN NAME<br>KNOWN VALUES | MX_GRUPO_SANGUINEO     |
| <b>Disability</b><br>MX_L3_SALUD_DISCAPACIDAD                            | COLUMN NAME<br>KNOWN VALUES | MX_DISCAPACIDAD        |
| <b>Sexual and reproductive health</b><br>MX_L3_SALUD_SEXUAL_REPRODUCTIVA | COLUMN NAME                 | MX_CATEGORIA_SUPRIMIDA |
| <b>Mental health and addictions</b><br>MX_L3_SALUD_MENTAL_ADICCIONES     | COLUMN NAME                 | MX_CATEGORIA_SUPRIMIDA |
| <b>Biometric data</b><br>MX_L3_BIOMETRICO                                | COLUMN NAME<br>DATA TYPE    | MX_REDACTAR            |
| <b>Genetic information</b><br>MX_L3_INFORMACION_GENETICA                 | COLUMN NAME                 | MX_REDACTAR            |
| <b>Sexual preference</b><br>MX_L3_PREFERENCIA_SEXUAL                     | COLUMN NAME<br>KNOWN VALUES | MX_PREFERENCIA_SEXUAL  |
| <b>Gender identity</b><br>MX_L3_IDENTIDAD_GENERO                         | COLUMN NAME<br>KNOWN VALUES | MX_IDENTIDAD_GENERO    |
| <b>Sexual life</b><br>MX_L3_VIDA_SEXUAL                                  | COLUMN NAME                 | MX_CATEGORIA_SUPRIMIDA |

| DOMAIN                                                                    | FOUND BY    |              | ALGORITHM               |
|---------------------------------------------------------------------------|-------------|--------------|-------------------------|
| <b>Religion</b><br>MX_L3_RELIGION                                         | COLUMN NAME | KNOWN VALUES | MX_RELIGION             |
| <b>Philosophical and moral beliefs</b><br>MX_L3_CREENCIA_FILOSOFICA_MORAL | COLUMN NAME |              | MX_CATEGORIA_SUPRIMIDA  |
| <b>Political opinions</b><br>MX_L3_OPINION_POLITICA                       | COLUMN NAME | KNOWN VALUES | MX_OPINION_POLITICA     |
| <b>Party membership</b><br>MX_L3_AFILIACION_POLITICA                      | COLUMN NAME | KNOWN VALUES | MX_PARTIDO_POLITICO     |
| <b>Union membership</b><br>MX_L3_AFILIACION_SINDICAL                      | COLUMN NAME | KNOWN VALUES | MX_CATEGORIA_SUPRIMIDA  |
| FINANCIAL AND PATRIMONIAL DATA                                            |             |              |                         |
| <b>Credit bureau record</b><br>MX_FIN_BURO_CREDITO                        | COLUMN NAME |              | MX_BURO_CREDITO         |
| <b>Debt amount</b><br>MX_FIN_MONTO_DEUDA                                  | COLUMN NAME | DATA TYPE    | MX_MONTO_DEUDA          |
| <b>Monthly income</b><br>MX_FIN_INGRESO_MENSUAL                           | COLUMN NAME | DATA TYPE    | MX_INGRESO_MENSUAL      |
| <b>Daily wage (SDI, SBC)</b><br>MX_FIN_SALARIO_DIARIO                     | COLUMN NAME | DATA TYPE    | MX_SALARIO_DIARIO       |
| <b>Assets</b><br>MX_FIN_PATRIMONIO                                        | COLUMN NAME | DATA TYPE    | MX_PATRIMONIO           |
| <b>AFORE</b><br>MX_FIN_AFORE                                              | COLUMN NAME | KNOWN VALUES | MX_AFORE                |
| <b>Retirement and housing savings</b><br>MX_FIN_SALDO_RETIRO              | COLUMN NAME | DATA TYPE    | MX_SALDO_RETIRO         |
| <b>Housing credit</b><br>MX_FIN_CREDITO_VIVIENDA                          | COLUMN NAME | KNOWN VALUES | MX_CREDITO_VIVIENDA     |
| <b>Social security coverage</b><br>MX_FIN_SEGURIDAD_SOCIAL                | COLUMN NAME | KNOWN VALUES | MX_SEGURIDAD_SOCIAL     |
| <b>Social programs</b><br>MX_FIN_PROGRAMA_SOCIAL                          | COLUMN NAME | KNOWN VALUES | MX_PROGRAMA_SOCIAL      |
| <b>Socioeconomic level</b><br>MX_FIN_NIVEL_SOCIOECONOMICO                 | COLUMN NAME | KNOWN VALUES | MX_NIVEL_SOCIOECONOMICO |
| <b>Housing tenure</b><br>MX_FIN_VIVIENDA                                  | COLUMN NAME | KNOWN VALUES | MX_VIVIENDA             |
| <b>Tax regime</b><br>MX_FIN_REGIMEN_FISCAL                                | COLUMN NAME |              | MX_REGIMEN_FISCAL       |
| CRIMINAL RECORDS                                                          |             |              |                         |
| <b>Criminal records</b><br>MX_PENAL_ANTECEDENTES                          | COLUMN NAME |              | MX_ANTECEDENTES         |
| <b>Case numbers</b><br>MX_PENAL_CAUSA                                     | COLUMN NAME | VALUE FORMAT | MX_CM_ALFANUM           |

# Direct identifiers

Data that identify a person on their own. The national keys — CURP, RFC, NSS, CLABE — keep a valid check digit after masking, because applications validate them and a test environment where they fail validation tests nothing.

## 7.1 CURP

MX\_L1\_CURP

- ESSENTIAL
- COLUMN NAME
- DATA TYPE
- VALUE FORMAT
- REGEX DECOMPOSE

WHAT IT IS

The Clave Única de Registro de Población: 18 characters built from the names (4 letters), the birth date, the sex, the state of birth, three internal consonants, a differentiator — a digit for people born before 2000, a letter after — and a check digit. HEGA850720MDFRRL04 . The key of almost every Mexican record, and a quasi-identifier in itself: it carries the birth date, sex and state.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_CURP - Path

90%

curp[a-z0-9\_]\*

c\_?u\_?r\_?p

clave\_?unica(\_?de\_?registro)?(\_?de\_?poblacion)?

curp\_?

(cte|cliente|emp|empleado|trab|trabajador|pac|paciente|alumno|benef|beneficiario|titular|asegu

rado|afiliado|derechohabiente|receptor|usuario|persona)

(cte|cliente|emp|trab|pac|alumno|benef|titular|asegurado)\_?curp

DATA TYPE

MX\_L1\_CURP - Type

Accepts text (length 18 or more); any other type rules the domain out.

VALUE FORMAT

MX\_L1\_CURP - Regex

| PATTERN                                                                                                                                                                                                      | STRENGTH | NOTES |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------|
| [A-Z][AEIOUX][A-Z]{2}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d 3[01])[HMX]<br>(AS BC BS CC CL CM CS CH DF DG GT GR HG JC MC MN MS NT NL OC PL QT QR SP SL SR TC <br>TS TL VZ YN ZS NE)[B-DF-HJ-NP-TV-Z]{3}[0-9A-Z]\d | 100%     |       |
| [A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d                                                                                                                                                                         | 90%      |       |

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Letters become other letters (vowel for vowel, consonant for consonant), the birth date another valid date of the same decade, the sex and state other values, the consonants and differentiator other ones of their kind — and the check digit is recomputed, so every masked CURP passes validation. The mapping is one-to-one: a CURP used as a key cannot collide. See *Check digits computed by the set*.

MX\_CURP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

MX\_CURP\_VALIDA

STRING ALGORITHM CHAIN

Applies MX\_CURP\_CUERPO → MX\_CURP\_DV , in this order.

MX\_CURP\_CUERPO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_CM\_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_FECHA\_AAMDD

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

**MX\_CM\_ALFANUM**

**MX\_MES NUMERIC MAPPING**  
Maps the number to another between 1 and 12.

**MX\_DIA\_1\_28 NUMERIC MAPPING**  
Maps the number to another between 1 and 28.

**MX\_MES\_30\_DIAS SECURE LOOKUP**  
Replaces the value with one of the 11 values in `mx-meses-30-dias.txt`, chosen by a keyed hash.

**MX\_DIA\_29\_30 NUMERIC MAPPING**  
Maps the number to another between 29 and 30.

**MX\_MES\_31\_DIAS SECURE LOOKUP**  
Replaces the value with one of the 7 values in `mx-meses-31-dias.txt`, chosen by a keyed hash.

**MX\_SEXO\_H\_M SECURE LOOKUP**  
Replaces the value with one of the 2 values in `mx-sexo-h-m.txt`, chosen by a keyed hash.

**MX\_ENTIDAD\_CURP SECURE LOOKUP**  
Replaces the value with one of the 33 values in `mx-entidad-curp.txt`, chosen by a keyed hash.

**MX\_CURP\_DV STRING ALGORITHM CHAIN**  
Applies `MX_CURP_DV_P1 → MX_CURP_DV_P2 → MX_CURP_DV_P3 → MX_CURP_DV_P4 → MX_CURP_DV_P5 → MX_CURP_DV_P6 → MX_CURP_DV_P7 → MX_CURP_DV_P8`, in this order. It is made of 16 algorithms that repeat the same step position by position; each one is in Appendix A.

EXAMPLES

| VALUE              |   | MASKED             |
|--------------------|---|--------------------|
| HEGA850720MDFRRL04 | → | WUVU800428HTLBZD88 |
| L0PM030215HJCPRRA8 | → | GIFW090514HTLHDLE3 |

7.2

RFC

MX\_L1\_RFC

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The Registro Federal de Contribuyentes: 13 characters for a person (4 letters, birth date, 2-character differentiator, check digit), 12 for a company. HEGA850720ABA . Appears in payroll, supplier and CFDI invoice tables.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_RFC - Path

90%

rfc[a-z0-9]\*

r\_?f\_?c

registro\_?federal(?!de)(?!contribuyentes)?

rfc\_?

(cte|cliente|emp|empleado|trab|trabajador|prov|proveedor|receptor|emisor|titular|contribuyente|persona|pf|fisica)

(cte|cliente|emp|trab|prov|receptor|emisor|titular)?rfc

tax\_?id

id\_?

fiscal

DATA TYPE

MX\_L1\_RFC - Type

Accepts text (length 10 or more); any other type rules the domain out.

**VALUE FORMAT** MX\_L1\_RFC – Regex

| PATTERN                                                             | STRENGTH | NOTES |
|---------------------------------------------------------------------|----------|-------|
| [A-ZÑ&]{4}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d{3}(01)[A-Z0-9]{2}[0-9A] | 100%     |       |
| [A-ZÑ&]{3}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d{3}(01)[A-Z0-9]{2}[0-9A] | 90%      |       |
| [A-ZÑ&]{4}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d{3}(01)                  | 60%      |       |

A value that matches none counts 20% against the domain.

**HOW IT IS MASKED**

Same treatment as the CURP, with the SAT's modulo 11 check digit, A included. A person's RFC shares its first ten characters with their CURP, and both are masked with the same algorithms: after masking they still share them. Company RFCs are masked too – a column mixes both, and the incorporation date of a small company can point to its owner. An RFC without differentiator (10 characters) keeps its shape.

**MX\_RFC REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

**MX\_RFC\_FISICA STRING ALGORITHM CHAIN**

Applies MX\_RFC\_CUERPO\_FISICA → MX\_RFC\_DV , in this order.

**MX\_RFC\_CUERPO\_FISICA REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

**MX\_CM\_ALFANUM CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

**MX\_FECHA\_AAMDD REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

MX\_CM\_ALFANUM .

**MX\_MES NUMERIC MAPPING**

Maps the number to another between 1 and 12.

**MX\_DIA\_1\_28 NUMERIC MAPPING**

Maps the number to another between 1 and 28.

**MX\_MES\_30\_DIAS SECURE LOOKUP**

Replaces the value with one of the 11 values in mx-meses-30-dias.txt , chosen by a keyed hash.

**MX\_DIA\_29\_30 NUMERIC MAPPING**

Maps the number to another between 29 and 30.

**MX\_MES\_31\_DIAS SECURE LOOKUP**

Replaces the value with one of the 7 values in mx-meses-31-dias.txt , chosen by a keyed hash.

**MX\_RFC\_DV STRING ALGORITHM CHAIN**

Applies MX\_RFC\_DV\_P1 → MX\_RFC\_DV\_P2 → MX\_RFC\_DV\_P3 → MX\_RFC\_DV\_P4 → MX\_RFC\_DV\_P5 → MX\_RFC\_DV\_P6 , in this order. It is made of 12 algorithms that repeat the same step position by position; each one is in Appendix A.

**MX\_RFC\_MORAL STRING ALGORITHM CHAIN**

Applies MX\_RFC\_CUERPO\_MORAL → MX\_RFC\_RELLENO → MX\_RFC\_DV → MX\_RFC\_SIN\_RELLENO , in this order.

**MX\_RFC\_CUERPO\_MORAL REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

**MX\_RFC\_RELLENO REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

**MX\_RFC\_RELLENO\_TABLA DATA CLEANSING**

Replaces each value found in mx-rfc-relleno.txt (38 pairs) by its counterpart; values not in the file stay as they are.

**MX\_RFC\_SIN\_RELLENO REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

## EXAMPLES

### VALUE

### MASKED

HEGA850720ABA

→

WUVU800428EX5

WMT970714R10

→

DHL950413V22

## 7.3 Social security number (NSS)

MX\_L1\_NSS

### ESSENTIAL

### COLUMN NAME

### DATA TYPE

### VALUE FORMAT

### REGEX DECOMPOSE

### WHAT IT IS

The IMSS number: 11 digits holding the subdelegation, registration year, birth year, a sequence and a check digit. Present in every payroll and HR system.

### HOW IT IS FOUND

#### COLUMN NAME

MX\_L1\_NSS - Path

90%

nss[a-z0-9]\* n?s?s num(ero)??(de\_)?seguro?social n(o|um|ro)?(seg|seguro)?  
soc(ial)? num(ero)??(de\_)?seguridad?social numero?imss n(o|um|ro)?imss imss?  
(num|nss|no) afiliacion?imss nss?  
(trab|trabajador|emp|empleado|asegurado|derechohabiente)

#### DATA TYPE

MX\_L1\_NSS - Type

Accepts text (length 11 to 13) or number (length 10 to 11); any other type rules the domain out.

#### VALUE FORMAT

MX\_L1\_NSS - Regex

#### PATTERN

#### STRENGTH

#### NOTES

\d{11}

70% LUHN check digit

\d{2}-?\d{2}-?\d{2}-?\d{4}-?\d

40%

A value that matches none counts 30% against the domain.

### HOW IT IS MASKED

Replaced by another NSS that passes the same Luhn check — the check of payment cards, which the Payment Card framework keeps valid. The mapping is one-to-one. Written with dashes, it is masked digit by digit, without a valid check digit.

### MX\_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

#### MX\_NSS\_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

#### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

## EXAMPLES

### VALUE

### MASKED

12345678903

→

68774252859

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The clave de elector of the INE credential: 6 consonants from the names, birth date, state number, sex and a 3-digit differentiator. GRHRAL85072009M100 . The INE credential is the most used identity document in Mexico.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_CLAVE\_ELECTOR – Path

90%

clave\_(de\_)?elector

cve\_?elector

clave\_?electoral

clave\_?ine

clave\_?ife

elector\_?

(clave|key)

voter\_?key

DATA TYPE

MX\_L1\_CLAVE\_ELECTOR – Type

Accepts text (length 18 or more); any other type rules the domain out.

VALUE FORMAT

MX\_L1\_CLAVE\_ELECTOR – Regex

| PATTERN                | STRENGTH | NOTES |
|------------------------|----------|-------|
| [A-Z]{6}\d{8}[HM]\d{3} |          | 100%  |

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Consonants mapped, birth date through the same algorithm as in the CURP (so a person's CURP and voter key keep the same masked date), state and sex replaced, differentiator mapped. The key has no check digit.

MX\_CLAVE\_ELECTOR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

MX\_CM\_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_FECHA\_AAMDD

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

MX\_MES

NUMERIC MAPPING

Maps the number to another between 1 and 12.

MX\_DIA\_1\_28

NUMERIC MAPPING

Maps the number to another between 1 and 28.

MX\_MES\_30\_DIAS

SECURE LOOKUP

Replaces the value with one of the 11 values in mx-meses-30-dias.txt , chosen by a keyed hash.

MX\_DIA\_29\_30

NUMERIC MAPPING

Maps the number to another between 29 and 30.

MX\_MES\_31\_DIAS

SECURE LOOKUP

Replaces the value with one of the 7 values in mx-meses-31-dias.txt , chosen by a keyed hash.

MX\_ENTIDAD\_NUMERO

SECURE LOOKUP

Replaces the value with one of the 32 values in mx-entidad-numero.txt , chosen by a keyed hash.

MX\_SEXO\_H\_M

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-sexo-h-m.txt , chosen by a keyed hash.

EXAMPLES

| VALUE              |   | MASKED             |
|--------------------|---|--------------------|
| GRHRAL85072009M100 | → | WVBMIF80042822H896 |

## 7.5 INE credential numbers

MX\_L1\_CREDENCIAL\_INE

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

### WHAT IT IS

The numbers that identify the physical credential: OCR (13 digits), CIC (9 digits), the citizen identifier and the issue number.

### HOW IT IS FOUND

| COLUMN NAME                                              | MX_L1_CREDENCIAL_INE – Path                                                                                                                                                                                                                                                                                 |       |  |
|----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--|
| 85%                                                      | ocr(_?(ine ife credencial))? cic(_?(ine ife credencial))? id_?ciudadano identificador_?ciudadano folio_?(ine ife credencial credencial_?elector) n(o um ro)_?(credencial_?(de_)?elector ine ife) num(ero)?_?(de_)?(ine ife) credencial_?(ine ife elector para_?votar) ine ife numero_?vertical num_?emision |       |  |
| 55%                                                      | credencial identificacion_?oficial n(o um ro)_?identificacion                                                                                                                                                                                                                                               |       |  |
| VALUE FORMAT                                             | MX_L1_CREDENCIAL_INE – Regex                                                                                                                                                                                                                                                                                |       |  |
| PATTERN                                                  | STRENGTH                                                                                                                                                                                                                                                                                                    | NOTES |  |
| \d{13}                                                   |                                                                                                                                                                                                                                                                                                             | 30%   |  |
| \d{9}                                                    |                                                                                                                                                                                                                                                                                                             | 20%   |  |
| A value that matches none counts 30% against the domain. |                                                                                                                                                                                                                                                                                                             |       |  |

### HOW IT IS MASKED

Character by character, keeping length and format.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE         | MASKED          |
|---------------|-----------------|
| 1234567890123 | → 4957065550289 |

## 7.6 Given names

MX\_L1\_NOMBRE

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

### WHAT IT IS

First and middle names ( NOMBRES , PRIMER\_NOMBRE ), including compound names such as María Guadalupe or José Luis .

### HOW IT IS FOUND

| COLUMN NAME | MX_L1_NOMBRE – Path                                                                                                                                                                                   |  |  |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| 85%         | primer_?nombre segundo_?nombre nombres?_?(de_)?pila nombre_?social first_?name given_?names? fname name_?first middle_?name nombre[12] nombres (except when followed by list E1) nom_?(pila trab emp) |  |  |
| 50%         | nombre (except when followed by list E2) nomb? (except when followed by list E3) name (except when followed by list E4)                                                                               |  |  |

**KNOWN VALUES** MX\_L1\_NOMBRE - List

| LIST                    | VALUES | STRENGTH | FIRST VALUES                         |
|-------------------------|--------|----------|--------------------------------------|
| mx-detectar-nombres.txt | 301    | 70%      | María, Maria, José, Jose, Juan, Luis |

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

Each word is replaced by a Mexican given name from a list of 255, keeping the number of words and the case.

More than three words are masked character by character.

**MX\_NOMBRES** **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

**MX\_NOMBRE\_PILA** **NAME**

Replaces the name with one of the 255 names in mx-nombres.txt .

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

#### EXAMPLES

| VALUE           |   | MASKED          |
|-----------------|---|-----------------|
| María Guadalupe | → | Gloria Pedro    |
| JOSÉ LUIS       | → | ROSARIO RODOLFO |

## 7.7 Surnames

MX\_L1\_APELLIDO

**ESSENTIAL** **COLUMN NAME** **KNOWN VALUES** **REGEX DECOMPOSE**

#### WHAT IT IS

Paternal and maternal surnames, in one column or two.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_APELLIDO - Path

85% apellidos? apellido\_(paterno|materno|pat|mat|uno|dos|[12]) ape\_(pat|mat|paterno|materno|[12]) aepat apemat appat apmat ap\_(pat|mat|paterno|materno) a\_?paterno a\_?materno paterno materno primer\_?apellido segundo\_?apellido last\_?name surname lname family\_?name second\_?last\_?name mother\_?last\_?name

**KNOWN VALUES** MX\_L1\_APELLIDO - List

| LIST                      | VALUES | STRENGTH | FIRST VALUES                                             |
|---------------------------|--------|----------|----------------------------------------------------------|
| mx-detectar-apellidos.txt | 423    | 70%      | Hernández, Hernandez, García, Garcia, Martínez, Martinez |

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

Each word is replaced by one of the 337 most frequent Mexican surnames, keeping the number of words and the case.

**MX\_APELLIDOS** **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

**MX\_APELLIDO** **NAME**

Replaces the name with one of the 337 names in mx-apellidos.txt .

## MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

#### VALUE

Hernández López

#### MASKED

→

Lozano Salazar

## 7.8 Full name

MX\_L1\_NOMBRE\_COMPLETO

### ESSENTIAL

### COLUMN NAME

### KNOWN VALUES

### REGEX DECOMPOSE

#### WHAT IT IS

Given names and both surnames in one column, in Mexican order, or as `SURNAMES`, `NAMES`. Also the name of a titular, beneficiary, insured person or invoice receiver.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_NOMBRE\_COMPLETO - Path

|     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 90% | <code>nombre_?(completo compl full)</code> <code>nombres?_?y_?apellidos?</code> <code>nombres?_?apellidos?</code><br><code>nombreakellido</code> <code>nom_?completo</code> <code>nomcompleto</code> <code>nombrecompleto</code> <code>full_?name</code> <code>fullname</code> <code>person_?</code><br><code>name</code> <code>customer_?name</code> <code>employee_?name</code> <code>patient_?name</code> <code>nombre_?</code><br><code>(cliente cte cli paciente pac trabajador trab empleado colaborador alumno estudiante afiliado </code><br><code>asegurado derechohabiente beneficiario benef titular madre padre tutor conyuge pareja medico d</code><br><code>otor profesional responsable contacto emergencia aval obligado coacreditado deudor acreditado</code><br><code> remitente destinatario receptor firmante testigo representante apoderado propietario arrendat</code><br><code>ario contratante victima denunciante imputado socio donante heredero persona pers conductor ch</code><br><code>ofer vendedor ejecutivo agente solicitante usuario_?</code><br><code>final ciudadano elector votante contribuyente jefe_?(de_)?</code><br><code>familia hijo hija familiar dependiente)</code> <code>nombre_?razon_?social_?receptor</code> |
| 60% | <code>titular</code> <code>beneficiario</code> <code>contacto_?emergencia</code> <code>conyuge</code> <code>tutor_?legal</code> <code>representante_?legal</code><br><code>apoderado_?legal</code> <code>paciente</code> <code>victima</code> <code>asegurado</code> <code>contratante</code> <code>derechohabiente</code> <code>acreditado</code><br><code>obligado_?solidario</code> <code>aval</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 50% | <code>nombre</code> (except when followed by <a href="#">list E2</a> ) <code>name</code> (except when followed by <a href="#">list E4</a> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

**KNOWN VALUES** MX\_L1\_NOMBRE\_COMPLETO - List

| LIST                                   | VALUES | STRENGTH | FIRST VALUES                                             |
|----------------------------------------|--------|----------|----------------------------------------------------------|
| <code>mx-detectar-nombres.txt</code>   | 301    | 60%      | María, Maria, José, Jose, Juan, Luis                     |
| <code>mx-detectar-apellidos.txt</code> | 423    | 60%      | Hernández, Hernandez, García, Garcia, Martínez, Martinez |

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

Given names become given names and surnames become surnames, by position: one word is a name, two are name and surname, three are name and two surnames, four are two names and two surnames. A comma separates surnames from names.

MX\_NOMBRE\_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

#### MX\_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

##### MX\_APELLIDO NAME

Replaces the name with one of the 337 names in mx-apellidos.txt .

##### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

#### MX\_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

##### MX\_NOMBRE\_PILA NAME

Replaces the name with one of the 255 names in mx-nombres.txt .

#### EXAMPLES

| VALUE                           |   | MASKED                          |
|---------------------------------|---|---------------------------------|
| María Guadalupe Hernández López | → | Gloria Pedro Lozano Salazar     |
| HERNÁNDEZ LÓPEZ, JUAN CARLOS    | → | LOZANO SALAZAR, CECILIA GERARDO |

## 7.9 E-mail

MX\_L1\_EMAIL

#### ESSENTIAL

#### COLUMN NAME

#### DATA TYPE

#### VALUE FORMAT

#### REGEX DECOMPOSE

#### WHAT IT IS

Personal and work e-mail addresses.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L1\_EMAIL - Path

85%

e\_?mail[a-z0-9]\* mail[a-z0-9]\* correo(?:electronico)?[a-z0-9]\* email\_?address  
correo\_?(personal|laboral|contacto|receptor|cliente)

##### DATA TYPE

MX\_L1\_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

##### VALUE FORMAT

MX\_L1\_EMAIL - Regex

##### PATTERN

[A-Za-z0-9.\_%+'\"-]+@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}

##### STRENGTH

100%

##### NOTES

A value that matches none counts 20% against the domain.

#### HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes .test , reserved for tests: a masked address can never receive mail.

#### MX\_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

##### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

#### EXAMPLES

| VALUE                         |   | MASKED                         |
|-------------------------------|---|--------------------------------|
| guadalupe.hernandez@gmail.com | → | koepupoqe.vadvamdul@pgoeb.test |

7.10 Phone number

MX\_L1\_TELEFONO

- ESSENTIAL
- COLUMN NAME
- VALUE FORMAT
- REGEX DECOMPOSE

WHAT IT IS

Landlines and mobiles. Since August 2019 every Mexican number has 10 digits: a 2-digit area code for Mexico City, Guadalajara and Monterrey (55, 56, 33, 81), 3 digits elsewhere.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_TELEFONO - Path

85%

tel   telefono[a-z0-9]\*   tel[eé]fono   tel\_?  
(cel|casa|particular|oficina|trabajo|movil|contacto|fijo|recados)   celular[a-z0-9]\*   cel  
movil   m[oó]vil   whatsapp   wa   fax   phone[a-z0-9]\*   mobile   cellphone   n(o|um|ro)?  
tel(efono)?   telef   tlf   lada   extension

VALUE FORMAT

MX\_L1\_TELEFONO - Regex

| PATTERN                                                              | STRENGTH | NOTES |
|----------------------------------------------------------------------|----------|-------|
| (\+?52[\s-]?)?(1[\s-]?)?\((? (55 56 33 81)\) ?[\s-]?\d{4}[\s-]?\d{4} | 90%      |       |
| (\+?52[\s-]?)?(1[\s-]?)?\((? [2-9]\d{2}\) ?[\s-]?\d{3}[\s-]?\d{4}    | 80%      |       |
| \+?\d[\d\s()\-]{7,15}                                                | 30%      |       |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The subscriber digits are masked; +52 , the old mobile 1 , the area code and the separators stay. A number that does not have the shape of a Mexican number is masked digit by digit.

MX\_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

MX\_CM\_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE            |   | MASKED           |
|------------------|---|------------------|
| +52 55 1234 5678 | → | +52 55 9707 7565 |
| (222) 123 4567   | → | (222) 957 9910   |

7.11 Address

MX\_L1\_DIRECCION

- ESSENTIAL
- COLUMN NAME
- DATA TYPE
- VALUE FORMAT
- SECURE LOOKUP

WHAT IT IS

The street line of an address: street, exterior and interior number, or block and lot ( Mz. 12 Lt. 5 ).

## HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_DIRECCION - Path

**80%** direccion[a-z]\* (except when followed by list E5) direcci[oó]n dir domicilio[a-z]\* (except when followed by fiscal) calle(\_?y?numero)? avenida address (except when preceded by mac, ip, e?mail, web, url) street addr (except when preceded by mac, ip, e?mail, web, url) dir\_? (particular|comercial|laboral|envio|entrega|facturacion|cliente|paciente|trabajo) entre\_? calles y\_calle residencia lugar?(de\_)?residencia home\_address

**DATA TYPE** MX\_L1\_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

**VALUE FORMAT** MX\_L1\_DIRECCION - Regex

| PATTERN                                                                                                                                                               | STRENGTH | NOTES |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------|
| (?i)(av(enida)?\. calle c\. privada priv\. andador cerrada calzada calz\. blvd\. boulevard bulevar prolongaci[oó]n prol\. carretera camino circuito retorno)\s+.\d+.* | 80%      |       |
| [A-Za-zÁÉÍÓÚÑáéíóúñ'\.]{4,}\s(\# no\.\s)?\d{1,5}(\s*(int interior depto dpto local)\.\s*\w+)?                                                                         | 40%      |       |
| (?i).\s(mz mza manzana)\.\s*\d+\s*(lt lte lote)\.\s*\d+                                                                                                               | 70%      |       |

A value that matches none counts 20% against the domain.

## HOW IT IS MASKED

Replaced by one of 3,000 fictitious Mexican addresses on common street names, with interior numbers and blocks and lots in realistic proportions.

**MX\_DIRECCION** **SECURE LOOKUP**

Replaces the value with one of the 3,000 values in mx-direcciones.txt, chosen by a keyed hash.

## EXAMPLES

| VALUE                           | MASKED               |
|---------------------------------|----------------------|
| Av. Insurgentes Sur 1602 Int. 4 | → Calle Abasolo 7005 |

## 7.12 Address details

MX\_L1\_DIRECCION\_COMPLEMENTO

**ESSENTIAL**

**COLUMN NAME**

**CHARACTER MAPPING**

## WHAT IT IS

Exterior and interior numbers, block, lot, building or tower kept in their own columns.

## HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_DIRECCION\_COMPLEMENTO - Path

**70%** n(o|um|ro|umero)?(ext|exterior|int|interior) num\_ext num\_int no\_ext no\_int numext numint exterior interior depto dpto manzana mza mz lote lt lte edificio torre casa?(num|no|numero) house\_number apartment apt unit\_number

## HOW IT IS MASKED

Character by character, keeping length and format.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

## EXAMPLES

| VALUE      | MASKED       |
|------------|--------------|
| Mz 12 Lt 5 | → Jj 37 Jp 7 |

## 7.13 CLABE

MX\_L1\_CLABE

| COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE |
|-------------|-----------|--------------|-----------------|
|-------------|-----------|--------------|-----------------|

## WHAT IT IS

The 18-digit standardized bank key: bank (3), plaza (3), account (11) and check digit. Used in every SPEI transfer and payroll deposit.

## HOW IT IS FOUND

| <div>COLUMN NAME</div> <div>MX_L1_CLABE - Path</div>                                                 |                                                                                                                                                                                                                                                                                             |       |
|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| 90%                                                                                                  | <div> <div>clabe[a-z0-9]*</div> <div>cta_?clabe</div> <div>cuenta_?clabe</div> <div>clabe_?interbancaria</div> <div>clave_?bancaria_?</div> <div>estandarizada</div> <div>cuenta_?interbancaria</div> <div>clabe_?</div> <div>(deposito pago cliente beneficiario trab nomina)</div> </div> |       |
| <div>DATA TYPE</div> <div>MX_L1_CLABE - Type</div>                                                   |                                                                                                                                                                                                                                                                                             |       |
| Accepts text (length 18 or more) or number (length 18 or more); any other type rules the domain out. |                                                                                                                                                                                                                                                                                             |       |
| <div>VALUE FORMAT</div> <div>MX_L1_CLABE - Regex</div>                                               |                                                                                                                                                                                                                                                                                             |       |
| PATTERN                                                                                              | STRENGTH                                                                                                                                                                                                                                                                                    | NOTES |
| \d{18}                                                                                               |                                                                                                                                                                                                                                                                                             | 70%   |
| A value that matches none counts 30% against the domain.                                             |                                                                                                                                                                                                                                                                                             |       |

## HOW IT IS MASKED

The bank code stays, so reports by bank still add up; plaza and account are masked and the check digit (weights 3, 7, 1, modulo 10) recomputed. Every masked CLABE is valid and the mapping is one-to-one.

MX CLABE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

**MX\_CLABE\_VALIDA CHECK DIGIT**

Masks the digits with **MX\_CLABE\_CUERPO** and recomputes a modulus 10 check digit with weights 3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7.

**MX\_CLABE\_CUERPO REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

**MX\_CM\_ALFANUM CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

## EXAMPLES

| VALUE              |   | MASKED             |
|--------------------|---|--------------------|
| 002180700545678911 | → | 002141726834346236 |

### 7.14 Bank account

MX L1 CUENTA BANCARIA

[illegible]

## WHAT IT IS

Account numbers other than the CLABE: checking, savings, payroll.

HOW IT IS FOUND

| COLUMN NAME | MX_L1_CUENTA_BANCARIA – Path                                                                                                                                                                                                                                                                |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 85%         | cuenta_?<br>(bancaria banco cheques ahorro deposito abono pago destino origen nomina debito inversion)<br>cta_?(bancaria banco cheques ahorro nomina) n(o um ro umero)?_(de_)?cuenta(_?<br>(banco bancaria cheques nomina))? account_?(number no num nbr) bank_?account num_?cta<br>no_?cta |

HOW IT IS MASKED

Character by character, keeping length and format.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE      | MASKED       |
|------------|--------------|
| 0123456789 | → 8947251356 |

7.15 Payment card

MX\_L1\_TARJETA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_TARJETA - Path

85%

tarjeta(\_?(credito|debito|cred|deb|num|no|numero|bancaria))?

n(o|um|ro|umero)?tarjeta

pan

card\_?(number|no|num)

credit\_?card

cc\_?(number|num)

tdc

tdd

num\_?tdc

plastico

VALUE FORMAT

MX\_L1\_TARJETA - Regex

| PATTERN              | STRENGTH | NOTES                                   |
|----------------------|----------|-----------------------------------------|
| <div>\d{13,19}</div> | 90%      | LUHN check digit; after removing [\s\~] |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another card number that still passes the Luhn check. Values that do not look like a card pass unchanged instead of failing the row.

MX\_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX\_TARJETA\_LUHN PAYMENT CARD  
Replaces the card number with another that passes the Luhn check.

EXAMPLES

| VALUE               | MASKED                |
|---------------------|-----------------------|
| 4152 3131 2345 6780 | → 1544 7874 9862 8904 |

## 7.16 Passport

MX\_L1\_PASAPORTE

**ESSENTIAL** **COLUMN NAME** **VALUE FORMAT** **CHARACTER MAPPING**

### WHAT IT IS

Mexican and foreign passport numbers.

### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_PASAPORTE – Path

**85%** pasaporte[a-z]\* passport[a-z]\* n(o|um|ro|umero)?pasaporte pasap

**VALUE FORMAT** MX\_L1\_PASAPORTE – Regex

| PATTERN    | STRENGTH | NOTES |
|------------|----------|-------|
| [A-Z]\d{8} |          | 30%   |

A value that matches none counts 30% against the domain.

### HOW IT IS MASKED

Character by character, keeping length and format.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE     | MASKED      |
|-----------|-------------|
| G12345678 | → G27909346 |

## 7.17 Immigration document

MX\_L1\_DOCUMENTO\_MIGRATORIO

**COLUMN NAME** **CHARACTER MAPPING**

### WHAT IT IS

Temporary and permanent resident cards, immigration forms, visas and foreign identity numbers.

### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_DOCUMENTO\_MIGRATORIO – Path

**80%** tarjeta?(de\_)?residente residente?(temporal|permanente) documento?migratorio doc?  
migratorio forma?migratoria fm?[23] fmm n(o|um|ro)?(documento)?migratorio id?  
extranjero documento?extranjero identificacion?extranjera dni visa n(o|um|ro)?visa  
national?id

### HOW IT IS MASKED

Character by character, keeping length and format.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE     | MASKED      |
|-----------|-------------|
| 123456789 | → 110858568 |

## 7.18 Professional license

MX\_L1\_CEDULA\_PROFESIONAL

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

### WHAT IT IS

The number of the cédula profesional issued by the SEP. The registry is public: the number leads straight to the person's name.

### HOW IT IS FOUND

| COLUMN NAME                                              | MX_L1_CEDULA_PROFESIONAL - Path  |           |                                                                 |
|----------------------------------------------------------|----------------------------------|-----------|-----------------------------------------------------------------|
| 85%                                                      | cedula_?profesional              | ced_?prof | cedula_?(prof medica especialidad) n(o um ro)_?cedula<br>cedula |
| VALUE FORMAT                                             | MX_L1_CEDULA_PROFESIONAL - Regex |           |                                                                 |
| PATTERN                                                  | STRENGTH                         |           | NOTES                                                           |
| \d{7,8}                                                  |                                  |           | 30%                                                             |
| A value that matches none counts 30% against the domain. |                                  |           |                                                                 |

### HOW IT IS MASKED

Character by character, keeping length.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE    | MASKED |          |
|----------|--------|----------|
| 12345678 | →      | 46916122 |

## 7.19 Driver's license

MX\_L1\_LICENCIA\_CONducIR

COLUMN NAME CHARACTER MAPPING

### WHAT IT IS

State and federal driver's license numbers.

### HOW IT IS FOUND

| COLUMN NAME | MX_L1_LICENCIA_CONducIR - Path                                               |              |                                  |
|-------------|------------------------------------------------------------------------------|--------------|----------------------------------|
| 80%         | licencia_?(de_?)?(conducir manejo chofer automovilista motociclista federal) | n(o um ro)_? |                                  |
|             | licencia                                                                     | licencia     | driver_?license drivers_?license |

### HOW IT IS MASKED

Character by character, keeping length and format.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE     | MASKED |           |
|-----------|--------|-----------|
| A12345678 | →      | A67558943 |

## 7.20 e.firma certificate

MX\_L1\_EFIRMA

**COLUMN NAME** **VALUE FORMAT** **CHARACTER MAPPING**

### WHAT IT IS

The 20-digit serial number of an e.firma (FIEL) or digital seal certificate issued by the SAT.

### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_EFIRMA - Path

**85%** e\_?firma efirma fiel firma\_?electronica(\_?avanzada)? n(o|um|ro)\_?certificado(\_?  
(sat|fiel|efirma|csd))? certificado\_?(sat|fiel|efirma|digital) no\_?certificado serial\_?  
certificado csd

**VALUE FORMAT** MX\_L1\_EFIRMA - Regex

| PATTERN       | STRENGTH | NOTES |
|---------------|----------|-------|
| 0000[0-9]{16} |          | 80%   |

A value that matches none counts 30% against the domain.

### HOW IT IS MASKED

Character by character, keeping length.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

| VALUE                | MASKED                 |
|----------------------|------------------------|
| 00001000000504465028 | → 24028511323899248367 |

## 7.21 IP address

MX\_L1\_IP

**COLUMN NAME** **VALUE FORMAT** **REGEX DECOMPOSE**

### WHAT IT IS

IPv4 and IPv6 addresses of users and devices.

### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_IP - Path

**85%** ip ip\_  
(address|addr|origen|destino|cliente|usuario|remota|publica|privada|acceso|conexion|login)  
direccion\_?ip dir\_?ip ipv[46] remote\_?addr client\_?ip host\_?ip

**VALUE FORMAT** MX\_L1\_IP - Regex

| PATTERN                                                     | STRENGTH | NOTES |
|-------------------------------------------------------------|----------|-------|
| ((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d) | 100%     |       |
| [0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}                    | 90%      |       |

A value that matches none counts 30% against the domain.

### HOW IT IS MASKED

Each IPv4 octet is mapped to a number from 1 to 254; an IPv6 address is mapped as hexadecimal.

**MX\_IP** **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_HEX` .

`MX_OCTETO` **NUMERIC MAPPING**

Maps the number to another between 1 and 254.

`MX_CM_HEX` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

| VALUE        |   | MASKED       |
|--------------|---|--------------|
| 189.203.4.10 | → | 160.148.8.16 |

7.22 Device identifier

MX\_L1\_DISPOSITIVO

COLUMN NAME   VALUE FORMAT   CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, advertising and session identifiers, device serial numbers.

HOW IT IS FOUND

COLUMN NAME   MX\_L1\_DISPOSITIVO – Path

80%   imei   imsi   iccid   mac   mac?address   direccion?mac   device?id   id?dispositivo  
dispositivo?id   uuid?dispositivo   advertising?id   idfa   gaid   cookie(?id)?   session?  
id   id?sesion   serie?equipo   n(o|um|ro)?serie?(equipo|celular|telefono)

VALUE FORMAT   MX\_L1\_DISPOSITIVO – Regex

| PATTERN                                | STRENGTH | NOTES            |
|----------------------------------------|----------|------------------|
| ([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2} | 100%     |                  |
| \d{15}                                 | 80%      | LUHN check digit |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Hexadecimal stays hexadecimal and digits stay digits, so the value keeps its format.

`MX_CM_HEX` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

| VALUE             |   | MASKED            |
|-------------------|---|-------------------|
| 3c:22:fb:9a:10:e4 | → | 5e:83:bb:3c:31:f9 |

7.23 License plate

MX\_L1\_PLACA

COLUMN NAME   VALUE FORMAT   CHARACTER MAPPING

WHAT IT IS

Vehicle plates in the formats of NOM-001-SCT-2-2016 ( URU-197-A ), Mexico City ( A-12-BCD ) and older series.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_PLACA – Path

85%

placas?(\_(vehiculo|auto|circulacion|vehicular|num|no|numero))?

n(o|um|ro)\_?placas?

matricula(\_(vehiculo|auto|vehicular))?

license\_?plate

plate(\_?number)?

tarjeta?(de\_)?

circulacion

VALUE FORMAT

MX\_L1\_PLACA – Regex

| PATTERN                                                               | STRENGTH | NOTES |
|-----------------------------------------------------------------------|----------|-------|
| [ABCDEFGHJKLMNPRSTUVWXYZ]{3}[\s-]?d{3}[\s-]?[ABCDEFGHJKLMNPRSTUVWXYZ] | 100%     |       |
| [ABCDEFGHJKLMNPRSTUVWXYZ][\s-]?d{2}[\s-]?[ABCDEFGHJKLMNPRSTUVWXYZ]{3} | 80%      |       |
| [ABCDEFGHJKLMNPRSTUVWXYZ]{3}[\s-]?d{2}[\s-]?d{2}                      | 80%      |       |
| d{3}[\s-]?[ABCDEFGHJKLMNPRSTUVWXYZ]{3}                                | 60%      |       |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters map among the letters plates use — never **I**, **0** or **Q** — and digits among digits: the masked plate is still a valid plate. The state series is not preserved.

MX\_PLACA CHARACTER MAPPING

Maps each character to another of its group (3 groups), keeping length and format.

EXAMPLES

| VALUE     | MASKED      |
|-----------|-------------|
| URU-197-A | → SGK-611-T |

7.24 Vehicle identification number

MX\_L1\_NIV

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The NIV (VIN), engine and chassis numbers and the REPUVE registration.

HOW IT IS FOUND

COLUMN NAME

MX\_L1\_NIV – Path

80%

niv

vin

n(o|um|ro|umero)\_?(de\_)?(serie|identificacion)\_?(vehicular|vehiculo)

serie?

vehicul(o|ar)

n(o|um|ro)\_?serie

numero\_?serie

n(o|um|ro)\_?motor

chasis

repuve

folio?

repuve

constancia\_?repuve

vin\_?number

VALUE FORMAT

MX\_L1\_NIV – Regex

HOW IT IS MASKED

Character by character, keeping length and format. The check digit of North American VINs is not recomputed.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

## EXAMPLES

### VALUE

### MASKED

3VWFE21C04M000001

→

7VVCU97M86J091175

## 7.25 Contract and customer numbers

MX\_L1\_NUMERO\_CONTRATO

### COLUMN NAME

### CHARACTER MAPPING

#### WHAT IT IS

Contract, policy, credit, customer, member, employee and payroll numbers — internal keys that lead to a person in the source system.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L1\_NUMERO\_CONTRATO - Path

70%

contrato n(o|u|m|r|o|u|m|e|r|o|\_)?contrato p[ó]liza n(o|u|m|r|o|u|m|e|r|o|\_)?poliza n(o|u|m|r|o|\_)?  
(de\_)?credito(\_?(infonavit|fovissste))? credito(\_?(infonavit|fovissste)) n(o|u|m|r|o|\_)?  
operacion n(o|u|m|r|o|u|m|e|r|o|\_)?(de\_)?socio n(o|u|m|r|o|u|m|e|r|o|\_)?(de\_)?cliente id\_cliente  
cve\_cliente clave\_cliente n(o|u|m|r|o|u|m|e|r|o|\_)?(de\_)?empleado num\_emp no\_emp  
n(o|u|m|r|o|\_)?nomina n(o|u|m|r|o|\_)?afiliado n(o|u|m|r|o|\_)?sinistro n(o|u|m|r|o|\_)?(de\_)?  
matricula matricula\_(alumno|estudiante) n(o|u|m|r|o|\_)?expediente\_  
(cliente|laboral|personal) folio\_(contrato|poliza|credito|cliente)

#### HOW IT IS MASKED

Character by character, keeping length and format, so the same number masks the same way in every table.

##### MX\_CM\_ALFANUM

##### CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

## EXAMPLES

### VALUE

### MASKED

POL-123456

→

MIF-194239

## 7.26 Username and social media

MX\_L1\_USUARIO\_RRSS

### COLUMN NAME

### CHARACTER MAPPING

#### WHAT IT IS

Username, logins, aliases and social media handles.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L1\_USUARIO\_RRSS - Path

70%

usuario username user\_name login nick(name)? alias cuenta\_usuario usr facebook  
instagram twitter tiktok linkedin red\_social perfil\_  
(facebook|instagram|twitter|linkedin|tiktok) telegram handle

#### HOW IT IS MASKED

Character by character, keeping length and format.

##### MX\_CM\_ALFANUM

##### CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE       |   | MASKED      |
|-------------|---|-------------|
| @lupita_hdz | → | @numaje_hws |

7.27 Credentials

MX\_L1\_CREDENTIAL

COLUMN NAME    REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PINs, tokens, API keys, the SAT CIEC password and security questions.

HOW IT IS FOUND

| COLUMN NAME | MX_L1_CREDENTIAL – Path                                                                                                                                                                                                                                                                                                          |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 90%         | password   passwd   pwd   pass   contrasen[aa]   contraseña   clave[a-z]* <i>(except when followed by list E6)</i><br>pin   nip   ciec   contrasena?(sat efirma fiel)   hash_?password   password_?hash   secret<br>token_?acceso   access_?token   refresh_?token   api_?key   otp   respuesta_?secreta   pregunta_?<br>secreta |

HOW IT IS MASKED

Every character becomes X . A credential has no place in a test environment.

MX\_REDACTAR    REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

| VALUE        |   | MASKED       |
|--------------|---|--------------|
| Secreta#2024 | → | XXXXXXXXXXXX |

7.28 Geolocation

MX\_L1\_GEOLOCALIZACION

COLUMN NAME    VALUE FORMAT    REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude of homes, deliveries or devices.

HOW IT IS FOUND

| COLUMN NAME | MX_L1_GEOLOCALIZACION – Path                                                                                                                                                                  |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 85%         | lat   latitud   latitude   lon   lng   longitude   coordenadas?   coord_?[xy]   geo_?<br>(lat lon lng loc localizacion posicion)   geolocalizacion   ubicacion_?gps   gps   posicion_?<br>gps |
| 50%         | longitud   long                                                                                                                                                                               |

**VALUE FORMAT** MX\_L1\_GEOLOCALIZACION - Regex

| PATTERN                                                        | STRENGTH | NOTES |
|----------------------------------------------------------------|----------|-------|
| (1[4-9] 2\d 3[0-3])\.\d{3,}\s*-\s*(8[6-9] 9\d 1[01]\d)\.\d{3,} | 90%      |       |
| (1[4-9] 2\d 3[0-3])\.\d{3,}                                    | 60%      |       |
| -(8[6-9] 9\d 1[01]\d)\.\d{3,}                                  | 70%      |       |

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved to another region.

**MX\_COORDENADA** **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

#### EXAMPLES

| VALUE                | MASKED                 |
|----------------------|------------------------|
| 19.432608,-99.133209 | → 19.463593,-99.198278 |

## 7.29 Free text

MX\_L1\_TEXTO\_LIBRE

**COLUMN NAME** **DATA TYPE** **VALUE FORMAT** **FREE TEXT REDACTION**

#### WHAT IT IS

Observations, comments, complaints, address references and notes where people write identifiers in the middle of a sentence.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L1\_TEXTO\_LIBRE - Path

**60%** observaciones? obs comentarios? notas? detalle descripcion\_  
(caso|queja|reclamo|incidente|solicitud|problema|atencion|hechos) texto\_?libre mensaje  
queja reclamo referencias?(?domicilio)? motivo?(texto|detalle) narrativa relato  
resumen?caso remarks comments? notes? free\_?text memo bitacora

**DATA TYPE** MX\_L1\_TEXTO\_LIBRE - Type

Accepts text (length 30 or more); any other type rules the domain out.

**VALUE FORMAT** MX\_L1\_TEXTO\_LIBRE - Regex

| PATTERN                                     | STRENGTH | NOTES                 |
|---------------------------------------------|----------|-----------------------|
| [A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d        | 70%      | anywhere in the value |
| [\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}        | 70%      | anywhere in the value |
| [A-ZÑ&]{4}\d{6}[A-Z0-9]{3}                  | 60%      | anywhere in the value |
| (\\+?52\\s?)?\\d{2,3}\\s?\\d{3,4}\\s?\\d{4} | 50%      | anywhere in the value |

A value that matches none does not count against the domain.

#### HOW IT IS MASKED

CURPs, RFCs, INE voter keys, e-mails, 10-digit phones, NSS, card and CLABE numbers, plates and IPs are replaced by [DAT0] ; given names and surnames from the lists by [NOMBRE] .

**MX\_TEXT0\_LIBRE** **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with `[DAT0]` , and the 1,436 terms of `mx-texto-nombres.txt` with `[NOMBRE]` .

**EXAMPLES**

| VALUE                                                                                        |   | MASKED                                                       |
|----------------------------------------------------------------------------------------------|---|--------------------------------------------------------------|
| Cliente Hernández, CURP HEGA850720MDFRRL04,<br>correo g.hernandez@gmail.com, tel 5512345678. | → | Cliente [NOMBRE], CURP [DAT0], correo [DAT0],<br>tel [DAT0]. |

# Quasi-identifiers

Data that identify no one alone but do in combination. Mexico has 2,469 municipalities, and 1,505 of them had fewer than 20,000 inhabitants in 2020: a birth date, a sex and one of those municipalities point to a handful of people. These attributes are generalized or shifted rather than replaced, so the data keep their analytical value.

## 8.1 Birth date

MX\_L2\_FECHA\_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The strongest quasi-identifier: with sex and municipality it singles out most people.

HOW IT IS FOUND

COLUMN NAME MX\_L2\_FECHA\_NACIMIENTO - Path

90% fecha?(de\_)?nac(imiento)? fec?nac(imiento)? fch?nac f?nac(imiento|im)? fnac  
fechanac(imiento)? fecnac nacimiento dob birth\_date date\_of\_birth birthdate  
birthday cumplea(n|ñ)os

DATA TYPE MX\_L2\_FECHA\_NACIMIENTO - Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days, the same way in every table for the same date.

MX\_FECHA\_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

| VALUE      |   | MASKED           |
|------------|---|------------------|
| 1985-07-20 | → | 1985-08-05T00:00 |

## 8.2 Birth year

MX\_L2\_ANIO\_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The year of birth stored on its own.

HOW IT IS FOUND

COLUMN NAME MX\_L2\_ANIO\_NACIMIENTO - Path

90% an(i)?o?(de\_)?nac(imiento)? año?(de\_)?nac(imiento)? birth\_year year\_of\_birth  
ano\_nacim

DATA TYPE MX\_L2\_ANIO\_NACIMIENTO - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

#### HOW IT IS MASKED

The decade stays and the last digit is masked — with the same mapping as the year inside a CURP, RFC or voter key.

**MX\_ANIO** **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

#### EXAMPLES

| VALUE |   | MASKED |
|-------|---|--------|
| 1985  | → | 1980   |

### 8.3

## Age

MX\_L2\_EDAD

**COLUMN NAME** **DATA TYPE** **REGEX DECOMPOSE**

#### WHAT IT IS

Age in years.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_EDAD – Path

**85%** edad(\_?  
(actual|paciente|cliente|afiliado|asegurado|derechohabiente|beneficiario|ingreso|anos|años|cum  
plida))? age anos?cumplidos rango?(de\_)?edad grupo?(de\_)?edad edad?en?anos

**DATA TYPE** MX\_L2\_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

#### HOW IT IS MASKED

The decade stays and the unit is masked (37 → 3x); 100 and over becomes 90, because very old ages are rare enough to identify.

**MX\_EDAD** **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

#### EXAMPLES

| VALUE |   | MASKED |
|-------|---|--------|
| 37    | → | 35     |
| 104   | → | 90     |

### 8.4

## Life event dates

MX\_L2\_FECHA\_EVENTO

**COLUMN NAME** **DATA TYPE** **DATE SHIFT**

#### WHAT IT IS

Dates of death, marriage, hiring and dismissal, IMSS registration, disability leave, hospitalization, diagnosis, childbirth, arrest.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_FECHA\_EVENTO – Path

**80%** fecha\_?(de\_)?(defuncion|fallecimiento|muerte|matrimonio|divorcio|ingreso|alta\_?  
(imss|patronal|laboral)|baja(\_?(imss|laboral)))?  
|contratacion|contrato|egreso|despido|renuncia|jubilacion|pension|incapacidad|hospitalizacion|  
alta\_?  
medica|diagnostico|atencion|consulta|parto|embarazo|detencion|sentencia|vacunacion|cirugia|est  
udio|reingreso|antiguedad) fec\_?  
(defuncion|ingreso|alta|baja|egreso|contrato|atencion|diagnostico|incapacidad) fch\_?  
(ingreso|alta|baja|egreso) death\_?date hire\_?date termination\_?date date\_?of\_?death  
admission\_?date discharge\_?date

**DATA TYPE** MX\_L2\_FECHA\_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

#### HOW IT IS MASKED

Shifted up to 30 days.

**MX\_FECHA\_EVENTO DATE SHIFT**

Moves the date by -30 to 30 days.

#### EXAMPLES

**VALUE**

**MASKED**

2021-03-15

→

2021-03-05T00:00

## 8.5 Sex

MX\_L2\_SEX0

**COLUMN NAME**

**KNOWN VALUES**

**REGEX DECOMPOSE**

#### WHAT IT IS

Sex or gender as recorded: H / M , F / M , Hombre / Mujer , Masculino / Femenino .

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_SEX0 – Path

**85%** sexo(\_?(biologico|registral|paciente|cliente|asegurado|trabajador))? sex g[eé]nero (except  
when followed by *identidad* , *social* , *autopercebido* ) gender cve\_?sexo cod\_?sexo

**KNOWN VALUES** MX\_L2\_SEX0 – List

**LIST**

**VALUES**

**STRENGTH**

**FIRST VALUES**

mx-detectar-sexo.txt

12

50%

h, m, f, x, hombre, mujer

A value that matches none counts 50% against the domain.

#### HOW IT IS MASKED

Replaced within its own vocabulary. H / M uses the same lookup as the sex inside a CURP or voter key, so the three stay consistent.

**MX\_SEX0 REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_SEX0\_PALABRA SECURE LOOKUP**

Replaces the value with one of the 2 values in mx-sexo-palabra.txt , chosen by a keyed hash.

#### MX\_SEX0\_MUJER\_HOMBRE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-mujer-hombre.txt`, chosen by a keyed hash.

#### MX\_SEX0\_INGLES **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-ingles.txt`, chosen by a keyed hash.

#### MX\_SEX0\_H\_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-h-m.txt`, chosen by a keyed hash.

#### MX\_SEX0\_F\_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-f-m.txt`, chosen by a keyed hash.

#### EXAMPLES

| VALUE     |   | MASKED   |
|-----------|---|----------|
| M         | → | H        |
| Masculino | → | Femenino |

## 8.6 Municipality

MX\_L2\_MUNICIPIO

### COLUMN NAME

### KNOWN VALUES

### DATA CLEANSING

#### WHAT IT IS

Municipality or Mexico City borough. 1,505 of the 2,469 municipalities had fewer than 20,000 inhabitants in the 2020 census.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L2\_MUNICIPIO - Path

85%

`municipio[a-z]* nom(bre)??(mun|mpio|municipio) mpio mun d?mpio mpio alcaldia delegacion (except when followed by list E7) demarcacion(_?territorial)? municipio? (residencia|nacimiento|domicilio)`

60%

`ciudad[a-z]* city town d?ciudad`

##### KNOWN VALUES

MX\_L2\_MUNICIPIO - List

##### LIST

##### VALUES

##### STRENGTH

##### FIRST VALUES

|                            |       |     |                                                               |
|----------------------------|-------|-----|---------------------------------------------------------------|
| mx-detectar-municipios.txt | 3,090 | 90% | Aguascalientes, Asientos, Calvillo, Cosío, Cosio, Jesús María |
|----------------------------|-------|-----|---------------------------------------------------------------|

A value that matches none counts 40% against the domain.

#### HOW IT IS MASKED

A municipality under 20,000 inhabitants becomes the nearest municipality of the same state that has at least 20,000; larger ones stay. The result is a real, nearby municipality. Names without accents and in capitals are recognized. A name shared by several municipalities is generalized only when all of them are small.

#### MX\_MUNICIPIO **DATA CLEANSING**

Replaces each value found in `mx-municipio-generalizado.txt` (6,547 pairs) by its counterpart; values not in the file stay as they are.

#### EXAMPLES

| VALUE                      |   | MASKED                 |
|----------------------------|---|------------------------|
| Santa María Tlahuitoltepec | → | Santa Lucía del Camino |
| Guadalajara                | → | Guadalajara            |

COLUMN NAME

DATA TYPE

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

The 5-digit INEGI geostatistical code of a municipality (state + municipality), with or without the leading zero.

HOW IT IS FOUND

COLUMN NAME

MX\_L2\_CLAVE\_MUNICIPIO – Path

85%

cve\_?(geo|mun|mpio|municipio|inegi)clave\_?(geo(estadistica)?|mun|mpio|municipio|inegi)(\_?(inegi|municipal))?cod(igo)??(mun|mpio|municipio|inegi)id\_?(mun|mpio|municipio)c\_?mnpio municipio\_?(cve|clave|id|cod|inegi)cvegeo

DATA TYPE

MX\_L2\_CLAVE\_MUNICIPIO – Type

Accepts number (length up to 5) or text (length up to 5); any other type rules the domain out.

KNOWN VALUES

MX\_L2\_CLAVE\_MUNICIPIO – List

| LIST                            | VALUES | STRENGTH | FIRST VALUES                          |
|---------------------------------|--------|----------|---------------------------------------|
| mx-detector-clave-municipio.txt | 2,758  | 50%      | 01001, 1001, 01002, 1002, 01003, 1003 |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Generalized exactly like the municipality name, without the ambiguity of homonyms.

MX\_CLAVE\_MUNICIPIO

DATA CLEANSING

Replaces each value found in `mx-clave-municipio-generalizada.txt` (2,758 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

| VALUE | MASKED  |
|-------|---------|
| 20426 | → 20006 |

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Locality, town, ejido, rancho or community — often a few hundred inhabitants — and place of birth.

HOW IT IS FOUND

COLUMN NAME

MX\_L2\_LOCALIDAD – Path

80%

localidad[a-z]\*nom(bre)?\_?loc(alidad)?poblado ranch[oe]ria ejido comunidad (except when followed by indigena, religiosa)pueblo\_?(residencia|origen)lugar\_?(de\_)?nacimiento origen\_(localidad|poblacion)

HOW IT IS MASKED

Replaced by the name of a municipality of over 100,000 inhabitants: still a place, no longer theirs.

MX\_LOCALIDAD

SECURE LOOKUP

Replaces the value with one of the 229 values in `mx-localidades.txt`, chosen by a keyed hash.

## EXAMPLES

### VALUE

San Isidro Buenavista

→

### MASKED

Cuautla

## 8.9

# Colonia

MX\_L2\_COLONIA

### COLUMN NAME

### SECURE LOOKUP

#### WHAT IT IS

Colonia, fraccionamiento, barrio or housing unit: with the postal code, it narrows an address down to a few blocks.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L2\_COLONIA – Path

85%

colonia[a-z]\* nom(bre)?\_?colonia fraccionamiento fracc barrio asentamiento d\_? asenta nom\_?asentamiento tipo\_?asentamiento unidad\_?habitacional conjunto\_?habitacional ageb manzana\_?inegi

#### HOW IT IS MASKED

Replaced by a common colonia name ( Centro , Del Valle , Las Flores ).

### MX\_COLONIA SECURE LOOKUP

Replaces the value with one of the 60 values in mx-colonias.txt , chosen by a keyed hash.

## EXAMPLES

### VALUE

Santa María la Ribera

→

### MASKED

Las Flores

## 8.10

# Postal code

MX\_L2\_CODIGO\_POSTAL

### COLUMN NAME

### VALUE FORMAT

### REGEX DECOMPOSE

#### WHAT IT IS

Five digits: the first two are the state or Mexico City borough. Also the fiscal address of CFDI invoices.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L2\_CODIGO\_POSTAL – Path

90%

cod(igo)?\_?postal cp c\_?p zip(\_?code)? postal\_?code codpostal d\_?codigo domicilio\_? fiscal(\_?receptor)? lugar\_?expedicion cp\_?(fiscal|domicilio|receptor|emisor)

##### VALUE FORMAT

MX\_L2\_CODIGO\_POSTAL – Regex

##### PATTERN

##### STRENGTH

##### NOTES

\d{5}

20%

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

The first three digits stay and the last two become 00 ( 06760 → 06700 ).

### MX\_CODIGO\_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

## MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

VALUE

MASKED

06760

→

06700

## 8.11 Nationality

MX\_L2\_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

### WHAT IT IS

Nationality or country of birth. A foreign nationality is rare in most tables, and rarity identifies.

### HOW IT IS FOUND

COLUMN NAME

MX\_L2\_NACIONALIDAD - Path

80%

nacionalidad nationality pais\_?(de\_)?(nacimiento|origen) ciudadania citizenship  
country\_of\_birth extranjero

KNOWN VALUES

MX\_L2\_NACIONALIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detectar-

64

70%

nacionalidades.txt

Mexicana, Estadounidense, Guatemalteca, Hondureña, Hondurena, Salvadoreña

A value that matches none counts 40% against the domain.

### HOW IT IS MASKED

Replaced by a nationality from a list of the most frequent in Mexico.

MX\_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 20 values in mx-nacionalidades.txt, chosen by a keyed hash.

### EXAMPLES

VALUE

MASKED

Guatemalteca

→

Hondureña

## 8.12 Marital status

MX\_L2\_ESTADO\_CIVIL

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

### WHAT IT IS

Single, married, free union, separated, divorced, widowed.

### HOW IT IS FOUND

COLUMN NAME

MX\_L2\_ESTADO\_CIVIL - Path

85%

estado\_civil edo\_civil est\_civil ecivil situacion\_conyugal marital\_status  
civil\_status

**KNOWN VALUES** MX\_L2\_ESTADO\_CIVIL – List

| LIST                         | VALUES | STRENGTH | FIRST VALUES                                               |
|------------------------------|--------|----------|------------------------------------------------------------|
| mx-detectar-estado-civil.txt | 19     | 70%      | soltero, soltera, casado, casada, unión libre, union libre |

A value that matches none counts 40% against the domain.

#### HOW IT IS MASKED

Replaced by another marital status.

**MX\_ESTADO\_CIVIL** **SECURE LOOKUP**

Replaces the value with one of the 6 values in `mx-estado-civil.txt`, chosen by a keyed hash.

#### EXAMPLES

| VALUE       | MASKED              |
|-------------|---------------------|
| Unión libre | → <b>Divorciado</b> |

## 8.13 Occupation

MX\_L2\_OCUPACION

**COLUMN NAME** **SECURE LOOKUP**

#### WHAT IT IS

Occupation, profession or position. A rare position identifies on its own.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_OCUPACION – Path

**80%** `ocupaci[oó]n` `profesi[oó]n` `oficio` `puesto(_?(trabajo|laboral|actual))?` *(except when followed by*  
*votacion, venta, trabajo\_?id)* `cargo` *(except when followed by list E8)* `job_?title` `occupation`  
`actividad_?(laboral|economica_?persona)` `categoria_?laboral`

#### HOW IT IS MASKED

Replaced by one of 40 common occupations.

**MX\_OCUPACION** **SECURE LOOKUP**

Replaces the value with one of the 40 values in `mx-ocupaciones.txt`, chosen by a keyed hash.

#### EXAMPLES

| VALUE                                   | MASKED              |
|-----------------------------------------|---------------------|
| Gerente Regional Zona Sierra Tarahumara | → <b>Repartidor</b> |

## 8.14 Employer

MX\_L2\_EMPLEADOR

**COLUMN NAME** **SECURE LOOKUP**

#### WHAT IT IS

Employer name or workplace.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_EMPLEADOR – Path

**80%** empleador patron (except when followed by *busqueda*, *regex*, *expresion*) nombre\_?patron razon\_?social\_?(patron|empleador) registro\_?patronal?nombre empresa?(empleadora|trabajo|laboral) lugar\_?(de\_)?trabajo centro\_?(de\_)?trabajo employer dependencia\_?laboral

#### HOW IT IS MASKED

Replaced by a fictitious Mexican company.

**MX\_EMPLEADOR** **SECURE LOOKUP**

Replaces the value with one of the 25 values in `mx-empleadores.txt`, chosen by a keyed hash.

#### EXAMPLES

**VALUE**

**MASKED**

Petróleos Mexicanos

→

Ayuntamiento de Villa Nueva

## 8.15 Schooling

MX\_L2\_ESCOLARIDAD

**COLUMN NAME**

**KNOWN VALUES**

**SECURE LOOKUP**

#### WHAT IT IS

Highest level of schooling, in INEGI's categories.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_ESCOLARIDAD – Path

**80%** escolaridad nivel\_?(educativo|educacional|escolar|de\_?estudios|academico) grado\_?(de\_)??estudios grado\_?academico ultimo\_?grado education\_?level anos\_?(de\_)?escolaridad

**KNOWN VALUES** MX\_L2\_ESCOLARIDAD – List

| LIST | VALUES | STRENGTH | FIRST VALUES |
|------|--------|----------|--------------|
|------|--------|----------|--------------|

|                             |    |     |                                                                                                                 |
|-----------------------------|----|-----|-----------------------------------------------------------------------------------------------------------------|
| mx-detectar-escolaridad.txt | 27 | 60% | Sin escolaridad, Preescolar, Primaria incompleta, Primaria completa, Secundaria incompleta, Secundaria completa |
|-----------------------------|----|-----|-----------------------------------------------------------------------------------------------------------------|

A value that matches none counts 40% against the domain.

#### HOW IT IS MASKED

Replaced by another level of the same scale.

**MX\_ESCOLARIDAD** **SECURE LOOKUP**

Replaces the value with one of the 12 values in `mx-escolaridad.txt`, chosen by a keyed hash.

#### EXAMPLES

**VALUE**

**MASKED**

Secundaria completa

→

Preparatoria o bachillerato

## 8.16 School

MX\_L2\_ESCUELA

**COLUMN NAME** **SECURE LOOKUP**

### WHAT IT IS

Name of a school, high school or university.

### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_ESCUELA – Path

75%

escuela colegio plantel nombre?(escuela|plantel|colegio|institucion?educativa)  
institucion?educativa universidad preparatoria secundaria primaria bachillerato  
school(\_?name)? jardin?de?ninos guarderia estancia?infantil

### HOW IT IS MASKED

Replaced by a generic school name.

**MX\_ESCUELA** **SECURE LOOKUP**

Replaces the value with one of the 15 values in `mx-escuelas.txt`, chosen by a keyed hash.

### EXAMPLES

**VALUE**

**MASKED**

Instituto Cultural Tampico

→

Universidad Autónoma del Centro

## 8.17 School code (CCT)

MX\_L2\_CCT

**COLUMN NAME** **VALUE FORMAT** **CHARACTER MAPPING**

### WHAT IT IS

The Clave de Centro de Trabajo of a school: state, type, number and a letter ( 09DPR1234X ).

### HOW IT IS FOUND

**COLUMN NAME** MX\_L2\_CCT – Path

85%

cct clave?(de?)(centro?de?trabajo|escuela|plantel) cve?(cct|escuela|plantel)  
centro?de?trabajo?clave

**VALUE FORMAT** MX\_L2\_CCT – Regex

**PATTERN**

**STRENGTH**

**NOTES**

`\d{2}[A-Z]{3}\d{4}[A-Z]`

90%

A value that matches none counts 30% against the domain.

### HOW IT IS MASKED

Character by character, keeping the format.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

### EXAMPLES

**VALUE**

**MASKED**

09DPR1234X

→

79TPS0988Z

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Number of economic dependents, children or household members.

HOW IT IS FOUND

COLUMN NAME

MX\_L2\_DEPENDIENTES – Path

80%

dependientes(\_?economicos)?

n(o|um|ro)?\_dependientes

num\_?hijos

n(o|um|ro)?\_hijos

cant\_?hijos

hijos

integrantes\_(del\_)?(hogar|familia)

n(o|um|ro)\_?integrantes

tamano\_?

(del\_)?hogar

personas\_(en\_)?(el\_)?hogar

hijos\_?nacidos\_?vivos

DATA TYPE

MX\_L2\_DEPENDIENTES – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values up to 5 stay; larger ones become 5, because large households are rare.

MX\_CANTIDAD\_ACOTADA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

| VALUE |   | MASKED |
|-------|---|--------|
| 9     | → | 5      |

# Sensitive data

The categories of article 2, section VI — ethnic origin, health, genetic information, beliefs, political opinions, sexual preference — together with gender identity, sexual life, biometrics and union membership. A categorical value is replaced by another of the same category, so the column keeps a realistic content; where the values share no vocabulary, they are suppressed.

## 9.1 Ethnic origin

MX\_L3\_ETNIA

COLUMN NAME    KNOWN VALUES    REGEX DECOMPOSE

WHAT IT IS

Indigenous people, Afro-Mexican self-identification or ethnic group. Named first in the sensitive data of article 2.

HOW IT IS FOUND

COLUMN NAME    MX\_L3\_ETNIA - Path

90%    etnia    [eé]tnico    origen\_[eé]tnico    grupo\_[eé]tnico    pueblo\_?(indigena|originario|orig)    autoadscripcion(\_?(indigena|afromexicana|afro))?    se\_?considera\_?    (indigena|afromexican[oa]|afro)    indigena    ind[ií]gena    afromexican[oa]    afrodescendiente    afro    raza    race    ethnicity    ethnic\_?group    comunidad\_?indigena    pertenencia\_?    (etnica|indigena)

KNOWN VALUES    MX\_L3\_ETNIA - List

| LIST                    | VALUES | STRENGTH | FIRST VALUES                                 |
|-------------------------|--------|----------|----------------------------------------------|
| mx-detectar-pueblos.txt | 103    | 90%      | Nahua, Maya, Zapoteco, Mixteco, Otomí, Otomi |
| mx-detectar-bandera.txt | 8      | 30%      | s, n, sí, si, no, y                          |

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A yes/no flag stays a flag; a people becomes another from a list of the most numerous indigenous peoples and the Afro-Mexican people, including unlisted ones such as Kumiai .

MX\_PUEBLO    REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_PUEBLO\_LISTA .

MX\_BANDERA    REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX\_CM\_ALFANUM    CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

**MX\_PUEBLO\_LISTA** **SECURE LOOKUP**

Replaces the value with one of the 31 values in `mx-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

| VALUE  |   | MASKED    |
|--------|---|-----------|
| Kumiai | → | Tlapaneco |
| S      | → | S         |

9.2 Indigenous language

MX\_L3 LENGUA INDIGENA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Whether a person speaks an indigenous language, and which. It reveals ethnic origin as surely as self-identification, and INEGI asks it in every census.

HOW IT IS FOUND

COLUMN NAME

MX\_L3 LENGUA INDIGENA - Path

90%

lengua(\_?(indigena|materna|originaria))? habla\_(lengua\_?)(indigena|originaria) hli  
hablante\_(de\_?)?lengua\_?indigena idioma\_(indigena|materno|originario) lengua\_?que\_  
habla language\_?indigenous native\_?language

KNOWN VALUES

MX\_L3 LENGUA INDIGENA - List

LIST

VALUES

STRENGTH

FIRST VALUES

|                         |    |     |                                                   |
|-------------------------|----|-----|---------------------------------------------------|
| mx-detectar-lenguas.txt | 57 | 80% | Náhuatl, Nahuatl, Maya, Tseltal, Tsotsil, Mixteco |
|-------------------------|----|-----|---------------------------------------------------|

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag; a language becomes another from a list of the most spoken.

MX LENGUA INDIGENA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX LENGUA INDIGENA LISTA .

MX BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX BANDERA SI NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX BANDERA TRUE FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX BANDERA S N

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX BANDERA Y N

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

MX BANDERA 0 1

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

MX CM ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX LENGUA INDIGENA LISTA

SECURE LOOKUP

Replaces the value with one of the 27 values in `mx-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Chocholteco

→ Cora

9.3 Diagnosis

MX\_L3\_SALUD\_DIAGNOSTICO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Diagnoses, ICD-10 codes, conditions, allergies and pathological history.

HOW IT IS FOUND

COLUMN NAME

MX\_L3\_SALUD\_DIAGNOSTICO - Path

85%

diagn[oó]stico[a-z]\* diag dx cie\_?10 cie\_?11 cod(igo)?\_?cie cie icd\_?10 icd  
patolog[ií]a[a-z]\* padecimiento[a-z]\* enfermedad(es)?[a-z]\* morbilidad condicion\_  
(medica|de\_?salud|cronica) problema\_?(de\_?)?salud impresion\_?diagnostica causa\_  
(incapacidad|muerte|defuncion|hospitalizacion|consulta) motivo\_?(de\_?)?  
(consulta|hospitalizacion|incapacidad) comorbilidad(es)? antecedentes\_  
(medicos|patologicos|personales\_?patologicos|heredofamiliares|clinicos) alergias?  
enfermedad\_?preexistente preexistencias? enfermedad\_?cronica riesgo\_?de\_?trabajo

VALUE FORMAT

MX\_L3\_SALUD\_DIAGNOSTICO - Regex

PATTERN

STRENGTH

NOTES

[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes a common code in the same format ( F32.9 → J45.9 ), a description a common diagnosis. The mapping hides the sensitive conditions — HIV, mental health, addictions — among ordinary ones.

MX\_DIAGNOSTICO

REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

MX\_DIAGNOSTICO\_TEXTO .

MX\_CIE10\_DECIMAL

SECURE LOOKUP

Replaces the value with one of the 33 values in mx-cie10-decimal.txt , chosen by a keyed hash.

MX\_CIE10

SECURE LOOKUP

Replaces the value with one of the 37 values in mx-cie10.txt , chosen by a keyed hash.

MX\_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

`MX_DIAGNOSTICO_TEXTO` **SECURE LOOKUP**

Replaces the value with one of the 30 values in `mx-diagnosticos.txt` , chosen by a keyed hash.

EXAMPLES

| VALUE           |   | MASKED            |
|-----------------|---|-------------------|
| F32.9           | → | <b>J02.9</b>      |
| Depresión mayor | → | <b>Tendinitis</b> |

9.4 Medication

`MX_L3_SALUD_MEDICAMENTO`

**COLUMN NAME**

**KNOWN VALUES**

**REGEX DECOMPOSE**

WHAT IT IS

Prescribed medicines. An antiretroviral or an antipsychotic reveals the diagnosis.

HOW IT IS FOUND

**COLUMN NAME**

`MX_L3_SALUD_MEDICAMENTO` - Path

85% medicamentos? f[aá]rmacos? sustancia\_?activa principio\_?activo prescripci[oó]n  
receta(\_?medica)? tratamiento(\_?farmacologico)? medication drug(\_?name)? posologia  
clave\_?cuadro\_?basico cuadro\_?basico

**KNOWN VALUES**

`MX_L3_SALUD_MEDICAMENTO` - List

| LIST                             | VALUES | STRENGTH | FIRST VALUES                                                              |
|----------------------------------|--------|----------|---------------------------------------------------------------------------|
| mx-detectar-<br>medicamentos.txt | 57     | 70%      | Paracetamol, Ibuprofeno, Naproxeno, Metamizol, Ketorolaco,<br>Diclofenaco |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine.

`MX_MEDICAMENTO`

**REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_MEDICAMENTO_LISTA` .

`MX_BANDERA` **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

`MX_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

`MX_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

`MX_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

`MX_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`MX_MEDICAMENTO_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 26 values in `mx-medicamentos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Sertralina 50 mg

→

Bezafibrato

9.5 Health record identifiers

MX\_L3\_SALUD\_IDENTIFICADOR

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Clinical file numbers (NOM-004-SSA3-2012), episode, prescription, bed and disability certificate numbers.

HOW IT IS FOUND

COLUMN NAME

MX\_L3\_SALUD\_IDENTIFICADOR - Path

85%

expediente\_?clinico n(o|um|ro|umero)\_?expediente(\_?clinico)? historia\_?clinica  
n(o|um|ro)\_?historia nhc n(o|um|ro)\_?episodio folio\_?  
(atencion|urgencias|receta|incapacidad|certificado\_?(de\_)?defuncion) n(o|um|ro)\_?  
incapacidad certificado\_?(de\_)?incapacidad serie\_?folio\_?incapacidad n(o|um|ro)\_?(de\_)?  
cama n(o|um|ro)\_?interconsulta n(o|um|ro)\_?(de\_)?receta agregado\_?medico n(o|um|ro)\_?  
biopsia medical\_?record\_?number mrn

55%

expediente episodio cama

HOW IT IS MASKED

Character by character, keeping length and format.

MX\_CM\_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

EXP-2024-00123

→

IRH-7843-85225

9.6 Clinical notes

MX\_L3\_SALUD\_TEXTO\_CLINICO

COLUMN NAME

DATA TYPE

FREE TEXT REDACTION

WHAT IT IS

Medical, progress, admission and discharge notes, current illness, physical examination — free text where names and CURPs appear.

HOW IT IS FOUND

COLUMN NAME

MX\_L3\_SALUD\_TEXTO\_CLINICO - Path

85%

nota\_?(medica|de\_?evolucion|evolucion|de\_?ingreso|ingreso|de\_?egreso|egreso|de\_?  
urgencias|urgencias|postoperatoria|preoperatoria|de\_?enfermeria|clinica)s? notas\_?  
clinicas? padecimiento\_?actual interrogatorio exploracion\_?fisica evoluci[oó]n(\_?  
(medica|clinica))? epicrisis indicaciones(\_?medicas)? resumen\_?clinico resumen\_?(de\_)?  
egreso historia\_?(de\_?la\_)?enfermedad plan\_?(de\_)?tratamiento pronostico hallazgos  
interpretacion clinical\_?notes? progress\_?notes?

**DATA TYPE** MX\_L3\_SALUD\_TEXTO\_CLINICO – Type

Accepts text (length 30 or more); any other type rules the domain out.

#### HOW IT IS MASKED

The same free text redaction as other text: identifiers become [DATO] , names [NOMBRE] . The clinical content stays.

**MX\_TEXTO\_LIBRE** **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with [DATO] , and the 1,436 terms of `mx-texto-nombres.txt` with [NOMBRE] .

#### EXAMPLES

| VALUE                                                       |   | MASKED                                             |
|-------------------------------------------------------------|---|----------------------------------------------------|
| Paciente López, CURP HEGA850720MDFRRL04, acude por cefalea. | → | Paciente [NOMBRE], CURP [DATO], acude por cefalea. |

## 9.7 Test results

MX\_L3\_SALUD\_RESULTADO\_EXAMEN

**COLUMN NAME** **CHARACTER MAPPING**

#### WHAT IT IS

Laboratory and imaging results: HIV, viral load, glucose, HbA1c, pregnancy and drug tests.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L3\_SALUD\_RESULTADO\_EXAMEN – Path

|     |                                                                                                                                                                                                                                                                                                                                                                                    |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 80% | resultado?<br>(estudio examen laboratorio lab prueba pcr antigeno biopsia imagen vih covid papanicolaou mast<br>ografia) estudios?_(de_)?laboratorio vih hiv carga_viral cd4 glucosa glicemia<br>hemoglobina(_glucosilada)? hba1c colesterol trigliceridos presion_arterial tension_<br>arterial imc prueba?(covid embarazo vih antidoping toxicologica) antidoping lab_<br>result |
| 50% | resultado estudio                                                                                                                                                                                                                                                                                                                                                                  |

#### HOW IT IS MASKED

Character by character, keeping length and format.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

#### EXAMPLES

| VALUE    |   | MASKED   |
|----------|---|----------|
| Reactivo | → | Quilqaju |

## 9.8 Blood type

MX\_L3\_SALUD\_GRUPO\_SANGUINEO

**COLUMN NAME** **KNOWN VALUES** **SECURE LOOKUP**

#### WHAT IT IS

ABO group and Rh factor.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L3\_SALUD\_GRUPO\_SANGUINEO - Path

**90%** grupo\_?sangu[ií]neo grupo\_?sang tipo\_?(de\_)??sangre tipo\_?sanguineo factor\_?rh rh  
blood\_?type blood\_?group

**KNOWN VALUES** MX\_L3\_SALUD\_GRUPO\_SANGUINEO - List

| LIST                            | VALUES | STRENGTH | FIRST VALUES             |
|---------------------------------|--------|----------|--------------------------|
| mx-detectar-grupo-sanguineo.txt | 26     | 90%      | A+, A-, B+, B-, AB+, AB- |

A value that matches none counts 40% against the domain.

#### HOW IT IS MASKED

Replaced by another blood type.

**MX\_GRUPO\_SANGUINEO** **SECURE LOOKUP**

Replaces the value with one of the 8 values in `mx-grupo-sanguineo.txt`, chosen by a keyed hash.

#### EXAMPLES

| VALUE | MASKED |
|-------|--------|
| 0+    | → A-   |

## 9.9 Disability

MX\_L3\_SALUD\_DISCAPACIDAD

**COLUMN NAME**

**KNOWN VALUES**

**REGEX DECOMPOSE**

#### WHAT IT IS

Type or degree of disability, in the categories of the 2020 census.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_L3\_SALUD\_DISCAPACIDAD - Path

**90%** discapacidad[a-z]\* tipo\_?(de\_)??discapacidad grado\_?(de\_)??discapacidad certificado\_?  
(de\_)?discapacidad persona\_?con\_?discapacidad pcd invalidez porcentaje\_?(de\_)?  
invalidez pension\_?(de\_)?invalidez limitacion(\_?(fisica|actividad))? disability  
dependencia\_?funcional nee necesidades\_?educativas\_?especiales condicion\_?mental

**KNOWN VALUES** MX\_L3\_SALUD\_DISCAPACIDAD - List

| LIST                         | VALUES | STRENGTH | FIRST VALUES                                                                                                                                                      |
|------------------------------|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mx-detectar-discapacidad.txt | 26     | 60%      | Caminar, subir o bajar, Ver, aun usando lentes, Oír, aun usando aparato auditivo, Oír, aun usando aparato auditivo, Hablar o comunicarse, Recordar o concentrarse |

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

A flag stays a flag; a type becomes another census category.

**MX\_DISCAPACIDAD** **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

**MX\_DISCAPACIDAD\_LISTA**.

**MX\_BANDERA** **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_BANDERA\_SI\_NO** **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

#### MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

#### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

#### MX\_DISCAPACIDAD\_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `mx-discapacidad.txt` , chosen by a keyed hash.

#### EXAMPLES

##### VALUE

##### MASKED

Discapacidad psicosocial severa

→

Oír, aun usando aparato auditivo

## 9.10 Sexual and reproductive health

MX\_L3\_SALUD\_SEXUAL\_REPRODUCTIVA

#### COLUMN NAME

#### REGEX DECOMPOSE

#### WHAT IT IS

Pregnancy, gestational age, legal interruption of pregnancy, contraception, fertility, sexually transmitted infections.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L3\_SALUD\_SEXUAL\_REPRODUCTIVA - Path

90%

```
embarazo embarazada gestaci[oó]n semanas_?(de_)?gestacion edad?gestacional fum
fecha?ultima?menstruacion aborto ile ive interrupcion_?(legal_|voluntaria_)?(del_)?
embarazo anticonceptivos? metodo_?(de_)?planificacion(_?familiar)? planificacion?
familiar fertilidad infertilidad reproduccion?asistida gestas partos cesareas?
puerperio its ets infeccion_?(de_)?transmision?sexual prep pregnan[a-z]*
contracepti[a-z]*
```

#### HOW IT IS MASKED

A flag stays a flag and a number gets other digits; anything else becomes Sin información .

#### MX\_CATEGORIA\_SUPRIMIDA

#### REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_SUPRIMIR .

#### MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

#### MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

#### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

#### MX\_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt` , chosen by a keyed hash.

#### EXAMPLES

| VALUE                  |   | MASKED          |
|------------------------|---|-----------------|
| Embarazo de 12 semanas | → | Sin información |
| S                      | → | S               |

## 9.11 Mental health and addictions

MX\_L3\_SALUD\_MENTAL\_ADICCIONES

#### COLUMN NAME

#### REGEX DECOMPOSE

#### WHAT IT IS

Psychiatric and psychological care, disorders, suicide risk, substance use and treatment.

#### HOW IT IS FOUND

#### COLUMN NAME

MX\_L3\_SALUD\_MENTAL\_ADICCIONES - Path

90%

```
salud_?mental  psiquiatri[a-z]*  psicologi[a-z]*  trastorno[a-z_]*  depresi[oó]n  ansiedad
suicid[a-z]*  autolesi[oó]n  adicci[oó]n(es)?  consumo_?(de_)?
(drogas|alcohol|sustancias|tabaco)  alcoholismo  farmacodependencia  drogadiccion
toxicomania  dependencia?(alcohol|drogas|sustancias)  cij  conadic  tratamiento_?
(adicciones|drogas|alcohol)  anexo?(rehabilitacion)?  mental_?health  substance_?
(use|abuse)
```

#### HOW IT IS MASKED

Suppressed to `Sin información` ; flags and codes keep their shape.

#### MX\_CATEGORIA\_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR` .

#### MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `keep`.

#### MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

#### MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

#### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

#### MX\_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt` , chosen by a keyed hash.

## EXAMPLES

### VALUE

### MASKED

Trastorno bipolar

→

Sin información

## 9.12 Biometric data

MX\_L3\_BIOMETRICO

### COLUMN NAME

### DATA TYPE

### REGEX DECOMPOSE

#### WHAT IT IS

Fingerprint and facial templates, iris, voice and digitized signatures stored as text.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L3\_BIOMETRICO - Path

90%

huella(\_?(dactilar|digital))? huellas dactilar biometri[a-z]\* template\_?  
(facial|biometrico|huella) rostro reconocimiento\_?facial facial\_?(template|id) iris  
retina voz\_?(huella|biometrica) firma\_?(digitalizada|biometrica|autografa\_?digital)  
fingerprint face\_?(id|template|encoding) palm\_?print minucias

##### DATA TYPE

MX\_L3\_BIOMETRICO - Type

Accepts text; any other type rules the domain out.

#### HOW IT IS MASKED

Every character becomes X. Binary columns cannot be masked by the set; see *Limits*.

### MX\_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

## EXAMPLES

### VALUE

### MASKED

A1B2C3D4E5F6

→

XXXXXXXXXXXX

## 9.13 Genetic information

MX\_L3\_INFORMACION\_GENETICA

### COLUMN NAME

### REGEX DECOMPOSE

#### WHAT IT IS

DNA profiles, genotypes, mutations, genetic screening and paternity tests — named by article 2.

#### HOW IT IS FOUND

##### COLUMN NAME

MX\_L3\_INFORMACION\_GENETICA - Path

90%

adn dna genoma genotipo genetic[a-z]\* gen[eé]tic[ao] informacion\_?genetica  
secuencia\_?genetica marcador\_?genetico perfil\_?(genetico|biologico) mutacion(\_?  
genetica)? snp brca haplotipo cariotipo tamiz\_?(genetico|metabolico) prueba\_?(de\_?)?  
paternidad

#### HOW IT IS MASKED

Every character becomes X.

### MX\_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

BRCA1 positivo

→ XXXXXXXXXXXXXXXX

9.14 Sexual preference

MX\_L3\_PREFERENCIA\_SEXUAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Sexual orientation — *preferencia sexual* in the words of the law.

HOW IT IS FOUND

COLUMN NAME

MX\_L3\_PREFERENCIA\_SEXUAL - Path

95%

preferencia\_?sexual orientaci[oó]n\_?sexual sexual\_?(orientation|preference) orient\_?  
sexual pref\_?sexual

KNOWN VALUES

MX\_L3\_PREFERENCIA\_SEXUAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

|                                    |    |     |                                                              |
|------------------------------------|----|-----|--------------------------------------------------------------|
| mx-detector-preferencia-sexual.txt | 17 | 80% | Heterosexual, Homosexual, Lesbiana, Gay, Bisexual, Pansexual |
|------------------------------------|----|-----|--------------------------------------------------------------|

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the same scale.

MX\_PREFERENCIA\_SEXUAL

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_PREFERENCIA\_SEXUAL\_LISTA .

MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_PREFERENCIA\_SEXUAL\_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in mx-preferencia-sexual.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Bisexual

→ Lesbiana

9.15 Gender identity

MX\_L3\_IDENTIDAD\_GENERO

COLUMN NAME    KNOWN VALUES    REGEX DECOMPOSE

WHAT IT IS

Self-perceived gender identity and legal gender recognition.

HOW IT IS FOUND

**COLUMN NAME**    MX\_L3\_IDENTIDAD\_GENERO - Path

**95%**    identidad?(de\_)?g[eé]nero    gender?identity    g[eé]nero?(identidad|social|autopercibido)    transg[eé]nero    transexual    persona?trans    reconocimiento?(de\_)?identidad    cambio?(de\_)?(sexo|genero)    pronombres?

**KNOWN VALUES**    MX\_L3\_IDENTIDAD\_GENERO - List

| LIST                             | VALUES | STRENGTH | FIRST VALUES                                                        |
|----------------------------------|--------|----------|---------------------------------------------------------------------|
| mx-detectar-identidad-genero.txt | 19     | 70%      | Mujer, Hombre, Mujer trans, Hombre trans, No binario, Género fluido |

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the same scale.

MX\_IDENTIDAD\_GENERO    REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_IDENTIDAD\_GENERO\_LISTA .

**MX\_BANDERA    REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_BANDERA\_SI\_NO    SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

**MX\_BANDERA\_TRUE\_FALSE    SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

**MX\_BANDERA\_S\_N    SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

**MX\_BANDERA\_Y\_N    SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

**MX\_BANDERA\_0\_1    SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

**MX\_CM\_ALFANUM    CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

**MX\_IDENTIDAD\_GENERO\_LISTA    SECURE LOOKUP**

Replaces the value with one of the 8 values in `mx-identidad-genero.txt` , chosen by a keyed hash.

EXAMPLES

| VALUE        | MASKED       |
|--------------|--------------|
| Hombre trans | → No binario |

## 9.16 Sexual life

MX\_L3\_VIDA\_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

### WHAT IT IS

Sexual activity, behavior and history.

### HOW IT IS FOUND

COLUMN NAME

MX\_L3\_VIDA\_SEXUAL – Path

90%

vida\_?sexual conducta\_?sexual actividad\_?sexual parejas?\_?sexuales? practicas\_?  
sexuales inicio\_?(de\_)??vida\_?sexual ivsa sexual\_?(activity|behavior|history) historia\_  
sexual comportamiento\_?sexual

### HOW IT IS MASKED

Suppressed to Sin información .

MX\_CATEGORIA\_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_SUPRIMIR .

MX\_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in mx-sin-informacion.txt , chosen by a keyed hash.

### EXAMPLES

VALUE

MASKED

Activa

→

Sin información

## 9.17 Religion

MX\_L3\_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

### WHAT IT IS

Religious affiliation — religious beliefs are named by article 2.

## HOW IT IS FOUND

**COLUMN NAME** MX\_L3\_RELIGION – Path

95%    religi[oó]n[a-z]\*    credo    culto    iglesia    creencia\_?religiosa    confesion\_?religiosa  
denominacion\_?religiosa    asociacion\_?religiosa    religious\_?affiliation    comunidad\_?  
religiosa

**KNOWN VALUES** MX\_L3\_RELIGION - List

| LIST                       | VALUES | STRENGTH | FIRST VALUES                                                                                                               |
|----------------------------|--------|----------|----------------------------------------------------------------------------------------------------------------------------|
| mx-detectar-religiones.txt | 56     | 90%      | Católica, Catolica, Protestante o cristiana evangélica, Protestante o cristiana evangelica, Pentecostal, Testigo de Jehová |

A value that matches none counts 40% against the domain.

## HOW IT IS MASKED

Replaced by a religion group of the 2020 census, including unlisted churches such as Luz del Mundo.

MX RFI TGT ON REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action: when none matches:

MX RELIGION LISTA.

## MX BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX BANDERA SI NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX BANDERA TRUE FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX BANDERA S N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX BANDERA Y N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX BANDERA 0 1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

## MX CM ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX RELIGION LISTA **SECURE LOOKUP**

Replaces the value with one of the 13 values in `mx-religiones.txt`, chosen by a keyed hash.

## EXAMPLES

| VALUE         | MASKED     |
|---------------|------------|
| Luz del Mundo | → Católica |

### 9.18 Philosophical and moral beliefs

MX L3 CREENCIA FILOSOFICA MORAL

COLUMN NAME      REGEX DECOMPOSE

## WHAT IT IS

Convictions, conscientious objection, ethical positions — the article 2 wording for beliefs that are not religious.

HOW IT IS FOUND

| COLUMN NAME | MX_L3_CREENCIA_FILOSOFICA_MORAL – Path                                                                                                                                                                                |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 90%         | creencias?_(filosoficas? morales? personales) convicci[oó]n(es)?(_?(filosoficas? morales? eticas? personales))? objeccion?(de_)?conciencia postura?(etica moral) valores_?personales filosofia?(de_)?vida cosmovision |

HOW IT IS MASKED

Suppressed to Sin información .

MX\_CATEGORIA\_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_SUPRIMIR .

|                                                                                                     |                   |
|-----------------------------------------------------------------------------------------------------|-------------------|
| MX_BANDERA                                                                                          | REGEX DECOMPOSE   |
| Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep. |                   |
| MX_BANDERA_SI_NO                                                                                    | SECURE LOOKUP     |
| Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.       |                   |
| MX_BANDERA_TRUE_FALSE                                                                               | SECURE LOOKUP     |
| Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.  |                   |
| MX_BANDERA_S_N                                                                                      | SECURE LOOKUP     |
| Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.         |                   |
| MX_BANDERA_Y_N                                                                                      | SECURE LOOKUP     |
| Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.         |                   |
| MX_BANDERA_0_1                                                                                      | SECURE LOOKUP     |
| Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.         |                   |
| MX_CM_ALFANUM                                                                                       | CHARACTER MAPPING |
| Maps each character to another of its group (7 groups), keeping length and format.                  |                   |
| MX_SUPRIMIR                                                                                         | SECURE LOOKUP     |
| Replaces the value with one of the 1 values in mx-sin-informacion.txt , chosen by a keyed hash.     |                   |

EXAMPLES

| VALUE                 | MASKED            |
|-----------------------|-------------------|
| Rechaza transfusiones | → Sin información |

9.19 Political opinions

MX\_L3\_OPINION\_POLITICA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Ideology, political position, voting intention and electoral preference.

HOW IT IS FOUND

| COLUMN NAME | MX_L3_OPINION_POLITICA – Path                                                                                                                                                                                                                                            |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 90%         | opini[oó]n(es)?_?pol[ií]ticas? ideolog[ií]a(_?politica)? posicion?politica postura?politica tendencia?politica orientacion?politica preferencia?(politica electoral partidista) intencion?(de_)?voto simpatia?(politica partidista) political?(view orientation opinion) |

## KNOWN VALUES MX\_L3\_OPINION\_POLITICA - List

| LIST                                | VALUES | STRENGTH | FIRST VALUES                                                                  |
|-------------------------------------|--------|----------|-------------------------------------------------------------------------------|
| mx-detectar-opiniones-politicas.txt | 14     | 70%      | Izquierda, Centro izquierda, Centro, Centro derecha, Derecha, Sin preferencia |

A value that matches none counts 40% against the domain.

### HOW IT IS MASKED

Replaced by another position of the same scale.

## MX\_OPINION\_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

### MX\_OPINION\_POLITICA\_LISTA .

#### MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

##### MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

##### MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

##### MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

##### MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

##### MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

#### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

#### MX\_OPINION\_POLITICA\_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in mx-opiniones-politicas.txt , chosen by a keyed hash.

### EXAMPLES

| VALUE          | MASKED   |
|----------------|----------|
| Centro derecha | → Centro |

## 9.20 Party membership

MX\_L3\_AFILIACION\_POLITICA

### COLUMN NAME

### KNOWN VALUES

### REGEX DECOMPOSE

### WHAT IT IS

Party membership or sympathy. A party list reveals political opinion.

### HOW IT IS FOUND

#### COLUMN NAME MX\_L3\_AFILIACION\_POLITICA - Path

95% partido(?:pol[í]tico)? militancia militante afiliaci[ó]n?  
(politica|partidista|partido) afiliado?(a\_)?partido padron?(de\_)?militantes  
political\_?party party\_?affiliation coalici[ó]n simpatizante

KNOWN VALUES MX\_L3\_AFILIACION\_POLITICA – List

| LIST                     | VALUES | STRENGTH | FIRST VALUES                                                                                                                                            |
|--------------------------|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| mx-detectar-partidos.txt | 35     | 80%      | Morena, Partido Acción Nacional, Partido Accion Nacional, Partido Revolucionario Institucional, Partido del Trabajo, Partido Verde Ecologista de México |

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the national parties registered in 2026, including those that lost registration ( PRD ).

MX\_PARTIDO\_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_PARTIDO\_POLITICO\_LISTA .

MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_PARTIDO\_POLITICO\_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in mx-partidos.txt , chosen by a keyed hash.

EXAMPLES

| VALUE                                |   | MASKED       |
|--------------------------------------|---|--------------|
| Partido de la Revolución Democrática | → | Somos México |

9.21 Union membership

MX\_L3\_AFILIACION\_SINDICAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Union membership, union dues, section and unionized or trust worker status.

HOW IT IS FOUND

COLUMN NAME MX\_L3\_AFILIACION\_SINDICAL – Path

95%    sindicato[a-z]\*    sindical    sindicalizado    afiliaci[oó]n?sindical    agremiado    cuota?  
sindical    delegado?sindical    seccion?sindical    trabajador?(de\_?)?confianza    tipo?(de\_?)?  
trabajador?(sindicalizado|confianza)    union?member(ship)?    trade?union    contrato?  
colectivo

#### KNOWN VALUES

MX\_L3\_AFILIACION\_SINDICAL - List

| LIST                       | VALUES | STRENGTH | FIRST VALUES                         |
|----------------------------|--------|----------|--------------------------------------|
| mx-detectar-sindicatos.txt | 16     | 60%      | SNTE, CNTE, STPRM, SUTERM, CTM, CROC |

A value that matches none counts 30% against the domain.

#### HOW IT IS MASKED

A flag stays a flag; anything else becomes Sin información .

#### MX\_CATEGORIA\_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_SUPRIMIR .

##### MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

##### MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

##### MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

##### MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

##### MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

##### MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

##### MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

##### MX\_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in mx-sin-informacion.txt , chosen by a keyed hash.

#### EXAMPLES

| VALUE           |   | MASKED          |
|-----------------|---|-----------------|
| SNTE Sección 22 | → | Sin información |
| S               | → | S               |

# Financial and patrimonial data

Article 7 requires express consent for financial and patrimonial data — a regime of its own, between ordinary and sensitive data, that GDPR-based templates do not have. It covers more than bank accounts: a credit bureau record, a daily wage, a housing credit, a social program or a tax regime tell as much about a person's economic situation as an income. Categories are replaced within their own notation; amounts are mapped into a plausible range with no link to the real value.

## 10.1 Credit bureau record

MX\_FIN\_BURO\_CREDITO

COLUMN NAME

REGEX DECOMPOSE

### WHAT IT IS

Buró de Crédito and Círculo de Crédito data: payment behaviour codes (MOP), score, arrears status, write-offs.

### HOW IT IS FOUND

COLUMN NAME

MX\_FIN\_BURO\_CREDITO - Path

90%

```
buro(_?(de_)?credito)? bur[oó] circulo_?(de_)?credito historial_?crediticio score(_?
(buro|crediticio|credito|riesgo|bc))? bc_?score puntaje_?(crediticio|buro|riesgo|credito)
calificacion_?(crediticia|buro|riesgo) mop forma_?de_?pago_?buro clave_?(de_)?
observacion morosidad moroso morosa atraso dias_?(de_)?atraso dias_?(de_)?mora
cartera_?vencida quebranto estatus_?(credito|crediticio|cartera) estado_?(de_)?
(cuenta_)?(credito|crediticio|cartera) credit_?score delinquen[a-z]* reestructura
insolvencia concurso_?mercantil
```

### HOW IT IS MASKED

A MOP code becomes another MOP code, a 3-digit score other digits, a status another status.

MX\_BURO\_CREDITO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

MX\_ESTADO\_CREDITICIO .

MX\_MOP SECURE LOOKUP

Replaces the value with one of the 9 values in `mx-mop.txt`, chosen by a keyed hash.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

#### MX\_ESTADO\_CREDITICIO **SECURE LOOKUP**

Replaces the value with one of the 10 values in `mx-estado-crediticio.txt`, chosen by a keyed hash.

#### EXAMPLES

| VALUE  |   | MASKED |
|--------|---|--------|
| MOP 05 | → | MOP 04 |
| 650    | → | 807    |

## 10.2 Debt amount

MX\_FIN\_MONTO\_DEUDA

**COLUMN NAME** **DATA TYPE** **NUMERIC MAPPING**

#### WHAT IT IS

Outstanding balance, amount owed, credit limit, minimum payment.

#### HOW IT IS FOUND

**COLUMN NAME** MX\_FIN\_MONTO\_DEUDA – Path

85% `monto_?(deuda|adeudo|adeudado|vencido|quebranto|credito|prestamo|financiado) adeudo(_?(total|vigente|vencido))? deuda(_?(total|vigente|vencida))? saldo_?(deudor|insoluto|vencido|credito|prestamo|tarjeta|adeudo) limite_?(de_)?credito linea_?(de_)?credito pago_?minimo debt(_?amount)? outstanding_?balance`

**DATA TYPE** MX\_FIN\_MONTO\_DEUDA – Type

Accepts number; any other type rules the domain out.

#### HOW IT IS MASKED

Mapped to an amount between 1,000 and 5,000,000.

**MX\_MONTO\_DEUDA** **NUMERIC MAPPING**

Maps the number to another between 1,000 and 5,000,000.

#### EXAMPLES

| VALUE |   | MASKED |
|-------|---|--------|
| 85000 | → | 78007  |

## 10.3 Monthly income

MX\_FIN\_INGRESO\_MENSUAL

**COLUMN NAME** **DATA TYPE** **NUMERIC MAPPING**

#### WHAT IT IS

Salary, perceptions, net pay, household income.

HOW IT IS FOUND

**COLUMN NAME** MX\_FIN\_INGRESO\_MENSUAL – Path

**85%**    `suel``do[a-z]*` (except when followed by `diario`, `base_?cotizacion`)    `salario[a-z]*` (except when followed by `diario`, `base_?(de_)?cotizacion`, `minimo_?(general|profesional|zona)`)    `remuneraci``oó``n[a-z]*`  
`ingreso_?(mensual|neto|bruto|familiar|del_?hogar|hogar|per_?`  
`capita|total|promedio|declarado|laboral|comprobable|anual)`    `ingresos(_?[a-z]+)?`  
`percepciones?(_?(totales|gravadas|exentas))?`    `total_?percepciones`    `neto_?a_?pagar`    `nomina_?`  
`(neta|bruta)`    `gasto_?(mensual|familiar)`    `capacidad_?(de_)?pago`    `salary`    `wage`    `income`  
`gross_?pay`    `net_?pay`

**DATA TYPE** MX\_FIN\_INGRESO\_MENSUAL – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 8,000 and 250,000.

**MX\_INGRESO\_MENSUAL**    **NUMERIC MAPPING**

Maps the number to another between 8,000 and 250,000.

EXAMPLES

| VALUE |   | MASKED |
|-------|---|--------|
| 18500 | → | 10882  |

10.4    Daily wage (SDI, SBC)

MX\_FIN\_SALARIO\_DIARIO

**COLUMN NAME**    **DATA TYPE**    **NUMERIC MAPPING**

WHAT IT IS

The integrated daily wage and the contribution base wage used by the IMSS — the way Mexican payrolls store pay.

HOW IT IS FOUND

**COLUMN NAME** MX\_FIN\_SALARIO\_DIARIO – Path

**90%**    `sdi`    `sbc`    `salario_?diario(_?integrado)?`    `suel``do_?diario`    `salario_?base_?(de_)?cotizacion`  
`sal_?(diario|base|integrado)`    `sd_?integrado`    `cuota_?diaria`    `daily_?wage`

**DATA TYPE** MX\_FIN\_SALARIO\_DIARIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 280 and 3,000.

**MX\_SALARIO\_DIARIO**    **NUMERIC MAPPING**

Maps the number to another between 280 and 3,000.

EXAMPLES

| VALUE |   | MASKED |
|-------|---|--------|
| 452   | → | 586    |

# 10.5 Assets

MX\_FIN\_PATRIMONIO

| COLUMN NAME | DATA TYPE | NUMERIC MAPPING |
|-------------|-----------|-----------------|
|-------------|-----------|-----------------|

## WHAT IT IS

Net worth, cadastral and appraisal values, investments and savings.

## HOW IT IS FOUND

**COLUMN NAME** MX\_FIN\_PATRIMONIO – Path

85% patrimonio(\_?(neto|total))? valor\_?  
(catastral|comercial|avaluo|inmueble|propiedad|vivienda|vehiculo|de\_?la\_?garantia) avaluo  
bienes?(inmuebles|muebles) valor\_?bienes activos?(personales|totales) saldo\_  
(inversion|ahorro|cuenta) monto?(inversion|ahorro) net\_?worth assets

**DATA TYPE** MX\_FIN\_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

## HOW IT IS MASKED

Mapped to an amount between 200,000 and 30,000,000.

MX\_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 200,000 and 30,000,000.

## EXAMPLES

| VALUE   | MASKED    |
|---------|-----------|
| 1850000 | → 4398071 |

# 10.6 AFORE

MX\_FIN\_AFORE

| COLUMN NAME | KNOWN VALUES | REGEX DECOMPOSE |
|-------------|--------------|-----------------|
|-------------|--------------|-----------------|

## WHAT IT IS

The retirement fund administrator, and the pension regime.

## HOW IT IS FOUND

**COLUMN NAME** MX\_FIN\_AFORE – Path

95% afore nombre?afore cve?afore clave?afore administradora?(de\_)?fondos?(para\_el\_)?  
retiro sar siefore cuenta?individual?(afore|retiro) regimen?(de\_)?pension(\_?(ley\_?  
73|ley\_97)))? pension\_fund

**KNOWN VALUES** MX\_FIN\_AFORE – List

| LIST                   | VALUES | STRENGTH | FIRST VALUES                                                                            |
|------------------------|--------|----------|-----------------------------------------------------------------------------------------|
| mx-detectar-afores.txt | 27     | 90%      | Afore Azteca, Afore Banamex, Afore Coppel, Afore Inbursa, Afore Invercap, PensionISSSTE |

A value that matches none counts 40% against the domain.

## HOW IT IS MASKED

Replaced by one of the ten AFORES authorized by CONSAR in 2026.

MX\_AFORE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_AFORE\_LISTA .

MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_BANDERA\_SI\_NO** **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

**MX\_BANDERA\_TRUE\_FALSE** **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

**MX\_BANDERA\_S\_N** **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

**MX\_BANDERA\_Y\_N** **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

**MX\_BANDERA\_0\_1** **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

**MX\_CM\_ALFANUM** **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

**MX\_AFORE\_LISTA** **SECURE LOOKUP**

Replaces the value with one of the 11 values in `mx-afores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Afore Coppel

→ **Afore Principal**

10.7 Retirement and housing savings

MX\_FIN\_SALDO\_RETIRO

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Balances of the retirement and housing subaccounts, voluntary savings, pension amounts.

HOW IT IS FOUND

COLUMN NAME

MX\_FIN\_SALDO\_RETIRO - Path

90%

`saldo_?(afore|retiro|rcv|subcuenta|vivienda|infonavit|fovissste|sar|cuenta?  
individual|voluntario) subcuenta_?(de_?)(retiro|vivienda|rcv) aportaciones?_  
(voluntarias|patronales|infonavit) monto_?pension pension_?(mensual|monto) retiro_  
cesantia_?vejez rcv ahorro_?voluntario retirement_?balance`

DATA TYPE

MX\_FIN\_SALDO\_RETIRO - Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 5,000 and 5,000,000.

**MX\_SALDO\_RETIRO** **NUMERIC MAPPING**

Maps the number to another between 5,000 and 5,000,000.

EXAMPLES

VALUE

MASKED

385000

→ **797256**

COLUMN NAME    KNOWN VALUES    REGEX DECOMPOSE

WHAT IT IS

Infonavit, Fovissste, Cofinavit or bank mortgage, and payroll discount notices.

HOW IT IS FOUND

**COLUMN NAME**    MX\_FIN\_CREDITO\_VIVIENDA – Path

**90%**    tipo\_?(de\_)?credito\_?(vivienda|hipotecario)    credito\_?(vivienda|hipotecario)    hipoteca

infonavit    fovissste    cofinavit    mejoravit    descuento\_?infonavit    factor\_?(de\_)?descuento

aviso\_?(de\_)?retencion    mortgage

**KNOWN VALUES**    MX\_FIN\_CREDITO\_VIVIENDA – List

| LIST                             | VALUES | STRENGTH | FIRST VALUES                                                                                                        |
|----------------------------------|--------|----------|---------------------------------------------------------------------------------------------------------------------|
| mx-detectar-credito-vivienda.txt | 20     | 80%      | Crédito Infonavit, Credito Infonavit, Crédito Fovissste, Credito Fovissste, Cofinavit, Crédito hipotecario bancario |

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another type of housing credit.

MX\_CREDITO\_VIVIENDA    REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_CREDITO\_VIVIENDA\_LISTA .

**MX\_BANDERA    REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

**MX\_BANDERA\_SI\_NO    SECURE LOOKUP**

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

**MX\_BANDERA\_TRUE\_FALSE    SECURE LOOKUP**

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

**MX\_BANDERA\_S\_N    SECURE LOOKUP**

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

**MX\_BANDERA\_Y\_N    SECURE LOOKUP**

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

**MX\_BANDERA\_0\_1    SECURE LOOKUP**

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

**MX\_CM\_ALFANUM    CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

**MX\_CREDITO\_VIVIENDA\_LISTA    SECURE LOOKUP**

Replaces the value with one of the 6 values in mx-credito-vivienda.txt , chosen by a keyed hash.

EXAMPLES

| VALUE     | MASKED      |
|-----------|-------------|
| Mejoravit | → Cofinavit |

# 10.9 Social security coverage

MX\_FIN\_SEGURIDAD\_SOCIAL

COLUMN NAME    KNOWN VALUES    REGEX DECOMPOSE

## WHAT IT IS

Derechohabiencia: IMSS, ISSSTE, IMSS-Bienestar, Pemex, armed forces, private insurance, none. It reveals formal or informal work.

## HOW IT IS FOUND

COLUMN NAME

MX\_FIN\_SEGURIDAD\_SOCIAL - Path

90%

derechohabiencia

derecho\_?habiencia

afiliacion\_?(a\_?)(servicios\_?de\_?salud|seguridad\_?social)

institucion\_?(de\_?)(seguridad\_?social|salud)

servicio\_?medico

seguridad\_?social

regimen\_?(de\_?)?seguridad\_?social

seguro\_?(medico|de\_?salud|popular)

imss\_?bienestar

insabi

umf

unidad\_?medica\_?familiar

health\_?insurance

KNOWN VALUES

MX\_FIN\_SEGURIDAD\_SOCIAL - List

| LIST                             | VALUES | STRENGTH | FIRST VALUES                                                |
|----------------------------------|--------|----------|-------------------------------------------------------------|
| mx-detectar-seguridad-social.txt | 22     | 80%      | IMSS, ISSSTE, ISSSTE estatal, IMSS-Bienestar, Pemex, Sedena |

A value that matches none counts 40% against the domain.

## HOW IT IS MASKED

Replaced by another institution of the same list.

MX\_SEGURIDAD\_SOCIAL    REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_SEGURIDAD\_SOCIAL\_LISTA .

MX\_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX\_BANDERA\_S\_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX\_BANDERA\_Y\_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX\_BANDERA\_0\_1

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX\_CM\_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_SEGURIDAD\_SOCIAL\_LISTA

SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-seguridad-social.txt` , chosen by a keyed hash.

## EXAMPLES

| VALUE  |   | MASKED         |
|--------|---|----------------|
| ISSSTE | → | ISSSTE estatal |

## 10.10 Social programs

MX\_FIN\_PROGRAMA\_SOCIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

### WHAT IT IS

Beneficiaries of the Programas para el Bienestar and their predecessors: pensions, scholarships, Sembrando Vida, Jóvenes Construyendo el Futuro.

### HOW IT IS FOUND

COLUMN NAME

MX\_FIN\_PROGRAMA\_SOCIAL - Path

90%

```
programa_?(social|del_?bienestar|bienestar|federal|de_?apoyo|gobierno) programas_?sociales
beneficiario_?(de_?)?(programa|pension|beca|apoyo) apoyo_?
(social|gubernamental|bienestar|economico) pension_?(bienestar|adultos_?
mayores|mujeres|discapacidad|65) beca_?(bienestar|benito_?juarez|rita_?cetina) becas_?
bienestar jovenes_?construyendo jcf sembrando_?vida prospera oportunidades progresa
padron_?(de_?)?beneficiarios tarjeta_?bienestar social_?program
```

KNOWN VALUES

MX\_FIN\_PROGRAMA\_SOCIAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

|           |    |     |                                                                                                                                                                             |
|-----------|----|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mx-       | 37 | 80% | Pensión para el Bienestar de las Personas Adultas Mayores, Pension para el Bienestar de las Personas Adultas Mayores, Pensión Mujeres Bienestar, Pension Mujeres Bienestar, |
| detectar- |    |     | Pensión para el Bienestar de las Personas con Discapacidad, Pension para el Bienestar de las Personas con Discapacidad                                                      |
| programas |    |     |                                                                                                                                                                             |
| .txt      |    |     |                                                                                                                                                                             |

A value that matches none counts 40% against the domain.

### HOW IT IS MASKED

A flag stays a flag; a program becomes another program of 2026.

MX\_PROGRAMA\_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_PROGRAMA\_SOCIAL\_LISTA .

MX\_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX\_CM\_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_PROGRAMA\_SOCIAL\_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in mx-programas-sociales.txt , chosen by a keyed hash.

## EXAMPLES

## VALUE

## MASKED

Prospera

→

Jóvenes Escribiendo el Futuro

## 10.11 Socioeconomic level

MX\_FIN\_NIVEL\_SOCIOECONOMICO

## COLUMN NAME

## KNOWN VALUES

## REGEX DECOMPOSE

## WHAT IT IS

AMAI socioeconomic level ( A/B to E ), income decile or quintile, marginalization and poverty indicators.

## HOW IT IS FOUND

## COLUMN NAME

MX\_FIN\_NIVEL\_SOCIOECONOMICO - Path

90%

```
nse nivel_?socioeconomico nivel_?socio_?economico estrato(_?socioeconomico)? clase_?
social decil(_?(de_?)?ingresos?)? quintil(_?(de_?)?ingresos?)? grado_?(de_?)?marginacion
indice_?(de_?)?marginacion marginacion rezago_?social pobreza(_?
(extrema|moderada|multidimensional))? carencias_?sociales? vulnerabilidad(_?(por_?
ingresos|social))? socioeconomic_?level
```

## KNOWN VALUES

MX\_FIN\_NIVEL\_SOCIOECONOMICO - List

## LIST

## VALUES

## STRENGTH

## FIRST VALUES

mx-detectar-nse.txt

13

40%

a/b, ab, c+, c, c-, d+

A value that matches none counts 30% against the domain.

## HOW IT IS MASKED

An AMAI level becomes another, a quintile another quintile, a decile another decile.

## MX\_NIVEL\_SOCIOECONOMICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_NSE .

## MX\_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in mx-quintil.txt , chosen by a keyed hash.

## MX\_DECIL\_ALTO SECURE LOOKUP

Replaces the value with one of the 5 values in mx-decil-alto.txt , chosen by a keyed hash.

## MX\_DECIL SECURE LOOKUP

Replaces the value with one of the 10 values in mx-decil.txt , chosen by a keyed hash.

## MX\_NSE SECURE LOOKUP

Replaces the value with one of the 7 values in mx-nse.txt , chosen by a keyed hash.

## EXAMPLES

## VALUE

## MASKED

C-

→

E

Decil 8

→

Decil 10

## 10.12 Housing tenure

MX\_FIN\_VIVIENDA

## COLUMN NAME

## KNOWN VALUES

## REGEX DECOMPOSE

## WHAT IT IS

Whether the home is owned, being paid, rented, lent or in litigation, and its conditions.

HOW IT IS FOUND

COLUMN NAME    MX\_FIN\_VIVIENDA – Path

95%    `tenencia_?(de_?)(la_?)?vivienda`    `tipo_?(de_?)?vivienda`    `situacion_?(de_?la_?)?vivienda`  
`vivienda_?(propia|rentada|prestada)`    `condicion_?(de_?)(la_?)?vivienda`    `material_?(de_?)?`  
`(la_?)?vivienda`    `piso_?de_?tierra`    `hacinamiento`    `asentamiento_?irregular`    `housing_?`  
`(type|tenure|status)`

KNOWN VALUES    MX\_FIN\_VIVIENDA – List

| LIST                     | VALUES | STRENGTH | FIRST VALUES                                                                                             |
|--------------------------|--------|----------|----------------------------------------------------------------------------------------------------------|
| mx-detectar-vivienda.txt | 15     | 60%      | Propia, Propia en proceso de pago, Rentada o alquilada, Prestada, Intestada o en litigio, Otra situación |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure of the census scale.

MX\_VIVIENDA    REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_VIVIENDA\_LISTA .

MX\_BANDERA    REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO    SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE    SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX\_BANDERA\_S\_N    SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX\_BANDERA\_Y\_N    SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX\_BANDERA\_0\_1    SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX\_CM\_ALFANUM    CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_VIVIENDA\_LISTA    SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-vivienda.txt` , chosen by a keyed hash.

EXAMPLES

| VALUE                  | MASKED   |
|------------------------|----------|
| Asentamiento irregular | → Propia |

10.13 Tax regime

MX\_FIN\_REGIMEN\_FISCAL

COLUMN NAME    REGEX DECOMPOSE

WHAT IT IS

The SAT tax regime of an individual (CFDI catalog `c_RegimenFiscal` ): wages, rent, business activity, RESICO. It reveals the source of a person's income.

HOW IT IS FOUND

| COLUMN NAME | MX_FIN_REGIMEN_FISCAL - Path                                                                                                    |
|-------------|---------------------------------------------------------------------------------------------------------------------------------|
| 90%         | regimen_?fiscal(_?receptor)? c_?regimen_?fiscal cve_?regimen clave_?regimen(_?fiscal)?<br>regimen_?(sat tributario) tax_?regime |

HOW IT IS MASKED

A code becomes another individual regime code, a description another description; 626 - ... keeps both parts.

MX\_REGIMEN\_FISCAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_REGIMEN\_FISCAL\_NOMBRE .

MX\_REGIMEN\_FISCAL\_CLAVE SECURE LOOKUP

Replaces the value with one of the 13 values in mx-regimen-fiscal-clave.txt , chosen by a keyed hash.

MX\_REGIMEN\_FISCAL\_NOMBRE SECURE LOOKUP

Replaces the value with one of the 13 values in mx-regimen-fiscal-nombre.txt , chosen by a keyed hash.

EXAMPLES

| VALUE                                   |   | MASKED                          |
|-----------------------------------------|---|---------------------------------|
| 626 - Régimen Simplificado de Confianza | → | 612 - Sin obligaciones fiscales |

# Criminal records

Not named by the LFPDPPP, but among the data most likely to lead to discrimination, which is what article 2 describes as sensitive. They are handled with the same care.

## 11.1 Criminal records

MX\_PENAL\_ANTECEDENTES

COLUMN NAME    REGEX DECOMPOSE

WHAT IT IS

Criminal records, sentences, offenses, pretrial detention, arrest warrants.

HOW IT IS FOUND

COLUMN NAME    MX\_PENAL\_ANTECEDENTES – Path

95%    antecedentes(\_?(penales|judiciales|policiacos|criminales|no?penales))? *(except when followed by list E9)* carta?(de\_?)?no?antecedentes    constancia?(de\_?)?(no\_?)?antecedentes    sentencia(\_?condenatoria)?    sentenciad[oa]    condena(do|da)?    delitos?    tipo?(de\_?)?delito    reincidente    reincidencia    imputad[oa]    vinculado?a?proceso    vinculacion?a?proceso    prision?    preventiva    pena    reclusion    interno    centro?penitenciario    cereso    libertad?condicional    criminal?record    conviction    offen[cs]e    detenid[oa]    orden?de?aprehension    medida?    cautelar    violencia?familiar

HOW IT IS MASKED

A flag stays a flag; anything else becomes a generic status.

MX\_ANTECEDENTES    REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_ANTECEDENTES\_LISTA .

MX\_BANDERA    REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX\_BANDERA\_SI\_NO    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX\_BANDERA\_TRUE\_FALSE    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX\_BANDERA\_S\_N    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX\_BANDERA\_Y\_N    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX\_BANDERA\_0\_1    SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX\_CM\_ALFANUM    CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX\_ANTECEDENTES\_LISTA    SECURE LOOKUP

Replaces the value with one of the 3 values in mx-antecedentes.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Sentenciado por robo

→ Sin información

11.2 Case numbers

MX\_PENAL\_CAUSA

| COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING |
|-------------|--------------|-------------------|
|-------------|--------------|-------------------|

WHAT IT IS

Investigation folders, preliminary inquiries, criminal case and appeal numbers ( 123/2024 ).

HOW IT IS FOUND

| COLUMN NAME                                             | MX_PENAL_CAUSA - Path                                                                                                                                                                                                                                                                                                  |       |  |
|---------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--|
| 90%                                                     | carpeta_(de_)?investigacion n(o um ro)_?carpeta averiguacion_?previa n(o um ro)_?averiguacion causa_?penal n(o um ro umero)_?(de_)?causa expediente_(judicial penal) n(o um ro)_?expediente_(judicial penal) toca_?penal n(o um ro)_?toca amparo_(n(o um ro))? n(o um ro)_?(de_)?denuncia folio_?denuncia case_?number |       |  |
| VALUE FORMAT                                            | MX_PENAL_CAUSA - Regex                                                                                                                                                                                                                                                                                                 |       |  |
| PATTERN                                                 | STRENGTH                                                                                                                                                                                                                                                                                                               | NOTES |  |
| [A-Z]{2,6}(/[A-Z0-9\-\]{1,12}){2,}/\d{2,6}[/\-\]\d{2,4} | 80%                                                                                                                                                                                                                                                                                                                    |       |  |
| \d{1,5}/\d{4}                                           | 50%                                                                                                                                                                                                                                                                                                                    |       |  |

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the format.

| MX_CM_ALFANUM | CHARACTER MAPPING |
|---------------|-------------------|
|---------------|-------------------|

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

| VALUE    | MASKED     |
|----------|------------|
| 123/2024 | → 845/5120 |

## Check digits computed by the set

Mexican applications validate their keys, and a masked key that fails validation breaks the test it was meant for. Two keys are covered by the plugin's own frameworks: the CLABE by Check Digit (weights 3, 7, 1, modulo 10), and the NSS by Payment Card, since its check digit is Luhn — the check of payment cards. The CURP and the RFC need more:

- **CURP** — every character counts, letters included (0–9, A–N → 10–23, Ñ 24, 0–Z → 25–36), with weights 18 down to 2, modulo 10. Check Digit reads letters in base 36, where 0–Z are worth one less.
- **RFC** — the SAT table (& 24, space 37, Ñ 38), weights 13 down to 2, modulo 11, with 10 written A. A company RFC counts as if preceded by a space. Check Digit writes a result of 10 as 0 and does not accept & or Ñ.

For these two the set computes the check digit itself. After the body is masked, a running sum travels through the value two characters at a time: a lookup table turns *sum + next two characters* into *those characters + new sum*, and the last table writes the check digit in place. Each table lists only what its positions can hold — digits for the date, letters for the names — so the CURP takes 8 steps and the RFC 6, each a Regex Decompose and a Data Cleansing file generated with the set, in a single String Algorithm Chain.

Every masked CURP, RFC and NSS is valid, and the mapping stays one-to-one — a key cannot collide with another. The cost is paid per value, per step, not per algorithm configured. Measured with the plugin outside the engine, on a laptop, a CURP masks in about 11 µs, an RFC in about 9 and an NSS in about 3, against about 2 for a Character Mapping: some 90,000 CURPs per second per thread. Half of the CURP's cost is its body — the date, and the keyed lookups for sex and state; the check digit is the other half. An engine's throughput depends on its hardware and job settings.

## Dates inside keys

CURP, RFC and the INE voter key carry the birth date as YYMMDD. Leaving it would leave the strongest quasi-identifier in the key; changing its digits freely would produce dates that do not exist.

The decade stays and the unit of the year is masked, as in a birth year column. The month goes through a one-to-one mapping of 1–12, the day through one of 1–28, 29–30 among themselves, and a 31st keeps a 31-day month. The result is always a real date, and two different dates never become the same.

The same algorithm masks the date in the three keys, so a person's CURP, RFC and voter key keep agreeing with each other. They do not agree with the birth date column, which moves by up to 60 days: no algorithm can see two columns at once.

## Limits

- **Binary columns** — photos of INE credentials, fingerprint images, clinical PDFs stored in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **Keys and the columns they derive from.** The letters of a masked CURP or RFC no longer come from the masked name, and its date is not the masked birth date. Where an application recomputes the CURP from the name, it will not match.

- **Inconvenient words.** RENAPO replaces some offensive letter combinations at the start of a CURP; a masked CURP may form one. It still passes the check digit.
  - **Lowercase or formatted keys** — a CURP in lower case, an NSS with dashes — are masked character by character, without a valid check digit.
  - **Municipalities** spelled in a way the list does not know pass unchanged. A name shared by a large and a small municipality stays as it is; the 5-digit code has no such ambiguity. A 3-digit municipality code without its state is not generalized.
  - **Free text** is redacted word by word: a phone number written with spaces ( 55 1234 5678 ) is not found there, and a given name that is also a common word ( Luz , Paz , Rosa ) is redacted wherever it appears.
  - **Minors** — a birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
  - **Addresses** are replaced as a whole line. Street, colonia, postal code and municipality in separate columns are masked independently and no longer form a coherent address.
  - **Plates and VINs** keep their format but not the state series or the VIN check digit.
- 

15

## Verification

Before publication the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 151 columns with the whole set at its assignment threshold — well named, badly named, and 26 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The algorithms, run with the Delphix algorithm plugin, masked 350 sample values and 228 placeholders such as S/D . Random CURPs, RFCs, NSS and CLABEs were checked for a valid check digit and a valid date, 150 of each for collisions, and pairs of CURP and RFC of the same person for agreement.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

---

16

## Sources

- Ley Federal de Protección de Datos Personales en Posesión de los Particulares — DOF 20 March 2025, last amendment DOF 14 November 2025 (Cámara de Diputados). The 2010 law, DOF 5 July 2010, for comparison.
- CURP structure and check digit — Registro Nacional de Población (RENAPO).
- RFC check digit — Servicio de Administración Tributaria (SAT). Tax regime catalog `c_RegimenFiscal` — SAT, CFDI 4.0.
- NSS structure — Instituto Mexicano del Seguro Social (IMSS). CLABE — Banco de México and the Asociación de Bancos de México.
- INE voter key — Instituto Nacional Electoral. National political parties, including the registration of Partido Paz and Somos México on 1 July 2026 — INE.
- Municipalities, geostatistical codes, coordinates and population — INEGI, Censo de Población y Vivienda 2020. Religion, disability, schooling and housing categories — the same census.

- Most frequent surnames — INE and RENAPO registers. Given names — INEGI and name frequency registers.
- Indigenous peoples — Instituto Nacional de los Pueblos Indígenas, Catálogo Nacional de Pueblos y Comunidades Indígenas y Afromexicanas (2024).
- AFOREs — Comisión Nacional del Sistema de Ahorro para el Retiro (CONSAR), 2026. Social programs — Programas para el Bienestar, Government of Mexico, 2026.
- Socioeconomic levels — Asociación Mexicana de Agencias de Inteligencia de Mercado y Opinión (AMAI).
- Ten-digit dialing — Instituto Federal de Telecomunicaciones, 3 August 2019. Postal codes — Correos de México (SEPOMEX). License plates — NOM-001-SCT-2-2016.

# Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

## MX\_AFORE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_AFORE\_LISTA .

Used by: MX\_FIN\_AFORE

### PATTERNS, TRIED IN ORDER

|                                   |                |
|-----------------------------------|----------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA     |
| (\d{1,6})                         | MX_CM_ALFANUM  |
| otherwise                         | MX_AFORE_LISTA |

### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

## MX\_AFORE\_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in mx-afores.txt , chosen by a keyed hash.

Used by: MX\_AFORE

### CONFIGURATION

|                            |                |
|----------------------------|----------------|
| lookupFile                 | mx-afores.txt  |
| hashMethod                 | SHA256         |
| maskedValueCase            | PRESERVE_INPUT |
| inputCaseSensitive         | no             |
| trimWhitespaceFromInput    | yes            |
| trimWhitespaceInLookupFile | yes            |

## MX\_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_L2\_ANIO\_NACIMIENTO

### PATTERNS, TRIED IN ORDER

|             |                      |
|-------------|----------------------|
| (\d{3})(\d) | keep · MX_CM_ALFANUM |
| otherwise   | keep                 |

### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

## MX\_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_ANTECEDENTES\_LISTA .

Used by: MX\_PENAL\_ANTECEDENTES

**PATTERNS, TRIED IN ORDER**

|                                   |                       |
|-----------------------------------|-----------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA            |
| (\d{1,6})                         | MX_CM_ALFANUM         |
| otherwise                         | MX_ANTECEDENTES_LISTA |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_ANTECEDENTES\_LISTA** SECURE LOOKUP

Replaces the value with one of the 3 values in `mx-antecedentes.txt` , chosen by a keyed hash.

Used by: `MX_ANTECEDENTES`

**CONFIGURATION**

|                            |                     |
|----------------------------|---------------------|
| lookupFile                 | mx-antecedentes.txt |
| hashMethod                 | SHA256              |
| maskedValueCase            | PRESERVE_INPUT      |
| inputCaseSensitive         | no                  |
| trimWhitespaceFromInput    | yes                 |
| trimWhitespaceInLookupFile | yes                 |

**MX\_APELLIDO** NAME

Replaces the name with one of the 337 names in `mx-apellidos.txt` .

Used by: `MX_APELLIDOS` , `MX_NOMBRE_COMPLETO`

**CONFIGURATION**

|                    |                  |
|--------------------|------------------|
| lookupFile         | mx-apellidos.txt |
| maskedValueCase    | PRESERVE_INPUT   |
| filterAccent       | yes              |
| inputCaseSensitive | no               |

**MX\_APELLIDOS** REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_APELLIDO` , `MX_NOMBRE_COMPLETO`

**PATTERNS, TRIED IN ORDER**

|                       |                                         |
|-----------------------|-----------------------------------------|
| (\S+)                 | MX_APELLIDO                             |
| (\S+)\s+(\S+)         | MX_APELLIDO · MX_APELLIDO               |
| (\S+)\s+(\S+)\s+(\S+) | MX_APELLIDO · MX_APELLIDO · MX_APELLIDO |
| otherwise             | MX_CM_ALFANUM                           |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_BANDERA** REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CATEGORIA_SUPRIMIDA` , `MX_PUEBLO` , `MX LENGUA INDIGENA` , `MX_DIAGNOSTICO` , `MX_MEDICAMENTO` , `MX_DISCAPACIDAD` , `MX_PREFERENCIA_SEXUAL` , `MX_IDENTIDAD_GENERO` , `MX_RELIGION` , `MX_OPINION_POLITICA` , `MX_PARTIDO_POLITICO` ,

MX\_BURO\_CREDITO , MX\_AFORE , MX\_CREDITO\_VIVIENDA , MX\_SEGURIDAD\_SOCIAL , MX\_PROGRAMA\_SOCIAL , MX\_VIVIENDA , MX\_ANTECEDENTES

#### PATTERNS, TRIED IN ORDER

|                  |                       |
|------------------|-----------------------|
| (?i)(s[ií] no)   | MX_BANDERA_SI_NO      |
| (?i)(true false) | MX_BANDERA_TRUE_FALSE |
| (?i)([sn])       | MX_BANDERA_S_N        |
| (?i)(y)          | MX_BANDERA_Y_N        |
| ([01])           | MX_BANDERA_0_1        |
| otherwise        | keep                  |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### MX\_BANDERA\_0\_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

#### CONFIGURATION

|                            |                                 |
|----------------------------|---------------------------------|
| lookupFile                 | <code>mx-bandera-0-1.txt</code> |
| hashMethod                 | SHA256                          |
| maskedValueCase            | PRESERVE_INPUT                  |
| inputCaseSensitive         | no                              |
| trimWhitespaceFromInput    | yes                             |
| trimWhitespaceInLookupFile | yes                             |

#### MX\_BANDERA\_S\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

#### CONFIGURATION

|                            |                                 |
|----------------------------|---------------------------------|
| lookupFile                 | <code>mx-bandera-s-n.txt</code> |
| hashMethod                 | SHA256                          |
| maskedValueCase            | PRESERVE_INPUT                  |
| inputCaseSensitive         | no                              |
| trimWhitespaceFromInput    | yes                             |
| trimWhitespaceInLookupFile | yes                             |

#### MX\_BANDERA\_SI\_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

#### CONFIGURATION

|                         |                                   |
|-------------------------|-----------------------------------|
| lookupFile              | <code>mx-bandera-si-no.txt</code> |
| hashMethod              | SHA256                            |
| maskedValueCase         | PRESERVE_INPUT                    |
| inputCaseSensitive      | no                                |
| trimWhitespaceFromInput | yes                               |

|                            |     |
|----------------------------|-----|
| trimWhitespaceInLookupFile | yes |
|----------------------------|-----|

#### MX\_BANDERA\_TRUE\_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

##### CONFIGURATION

|                            |                                        |
|----------------------------|----------------------------------------|
| lookupFile                 | <code>mx-bandera-true-false.txt</code> |
| hashMethod                 | <code>SHA256</code>                    |
| maskedValueCase            | <code>PRESERVE_INPUT</code>            |
| inputCaseSensitive         | <code>no</code>                        |
| trimWhitespaceFromInput    | <code>yes</code>                       |
| trimWhitespaceInLookupFile | <code>yes</code>                       |

#### MX\_BANDERA\_Y\_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

##### CONFIGURATION

|                            |                                 |
|----------------------------|---------------------------------|
| lookupFile                 | <code>mx-bandera-y-n.txt</code> |
| hashMethod                 | <code>SHA256</code>             |
| maskedValueCase            | <code>PRESERVE_INPUT</code>     |
| inputCaseSensitive         | <code>no</code>                 |
| trimWhitespaceFromInput    | <code>yes</code>                |
| trimWhitespaceInLookupFile | <code>yes</code>                |

#### MX\_BURO\_CREDITO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

`MX_ESTADO_CREDITICIO` .

Used by: `MX_FIN_BURO_CREDITO`

##### PATTERNS, TRIED IN ORDER

|                                                |                                   |
|------------------------------------------------|-----------------------------------|
| <code>(0[0-7] 9[679])</code>                   | <code>MX_MOP</code>               |
| <code>(?i)(mop\s*)(0[0-7] 9[679])</code>       | <code>keep · MX_MOP</code>        |
| <code>(\d{3})</code>                           | <code>MX_CM_ALFANUM</code>        |
| <code>(?i)(s[ií] no true false [sny01])</code> | <code>MX_BANDERA</code>           |
| <code>otherwise</code>                         | <code>MX_ESTADO_CREDITICIO</code> |

##### CONFIGURATION

|             |                  |
|-------------|------------------|
| trimInput   | <code>yes</code> |
| requireMask | <code>no</code>  |

#### MX\_CANTIDAD\_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `keep`.

Used by: `MX_L2_DEPENDIENTES`

##### PATTERNS, TRIED IN ORDER

|                      |                             |
|----------------------|-----------------------------|
| <code>([0-5])</code> | <code>keep</code>           |
| <code>(\d+)</code>   | <code>replace with 5</code> |

|           |      |
|-----------|------|
| otherwise | keep |
|-----------|------|

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### **MX\_CATEGORIA\_SUPRIMIDA** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR` .

Used by: `MX_L3_SALUD_SEXUAL_REPRODUCTIVA` , `MX_L3_SALUD_MENTAL_ADICCIONES` , `MX_L3_VIDA_SEXUAL` , `MX_L3_CREENCIA_FILOSOFICA_MORAL` , `MX_L3_AFILIACION_SINDICAL`

#### **PATTERNS, TRIED IN ORDER**

|                                                |                            |
|------------------------------------------------|----------------------------|
| <code>(?i)(s[ií] no true false [sny01])</code> | <code>MX_BANDERA</code>    |
| <code>(\d{1,6})</code>                         | <code>MX_CM_ALFANUM</code> |
| otherwise                                      | <code>MX_SUPRIMIR</code>   |

#### **CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### **MX\_CIE10** SECURE LOOKUP

Replaces the value with one of the 37 values in `mx-cie10.txt` , chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

#### **CONFIGURATION**

|                            |                                   |
|----------------------------|-----------------------------------|
| lookupFile                 | <code>mx-cie10.txt</code>         |
| hashMethod                 | <code>SHA256</code>               |
| maskedValueCase            | <code>PRESERVE_LOOKUP_FILE</code> |
| inputCaseSensitive         | no                                |
| trimWhitespaceFromInput    | yes                               |
| trimWhitespaceInLookupFile | yes                               |

#### **MX\_CIE10\_DECIMAL** SECURE LOOKUP

Replaces the value with one of the 33 values in `mx-cie10-decimal.txt` , chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

#### **CONFIGURATION**

|                            |                                   |
|----------------------------|-----------------------------------|
| lookupFile                 | <code>mx-cie10-decimal.txt</code> |
| hashMethod                 | <code>SHA256</code>               |
| maskedValueCase            | <code>PRESERVE_LOOKUP_FILE</code> |
| inputCaseSensitive         | no                                |
| trimWhitespaceFromInput    | yes                               |
| trimWhitespaceInLookupFile | yes                               |

#### **MX\_CLABE** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_CLABE`

#### **PATTERNS, TRIED IN ORDER**

|                       |                              |
|-----------------------|------------------------------|
| <code>(\d{18})</code> | <code>MX_CLABE_VALIDA</code> |
|-----------------------|------------------------------|

|                      |               |
|----------------------|---------------|
| otherwise            | MX_CM_ALFANUM |
| <b>CONFIGURATION</b> |               |
| trimInput            | yes           |
| requireMask          | no            |

**MX\_CLABE\_CUERPO** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CLABE\_VALIDA

**PATTERNS, TRIED IN ORDER**

|                 |                      |
|-----------------|----------------------|
| (\d{3})(\d{14}) | keep · MX_CM_ALFANUM |
| otherwise       | keep                 |

|                      |     |
|----------------------|-----|
| <b>CONFIGURATION</b> |     |
| trimInput            | yes |
| requireMask          | no  |

**MX\_CLABE\_VALIDA** CHECK DIGIT

Masks the digits with MX\_CLABE\_CUERPO and recomputes a modulus 10 check digit with weights 3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7 .

Used by: MX\_CLABE

|                                          |                                   |
|------------------------------------------|-----------------------------------|
| <b>CONFIGURATION</b>                     |                                   |
| weightList                               | 3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7 |
| modulusNumber                            | 10                                |
| checkDigitIndex                          | 17                                |
| calculateChecksumRightToLeft             | no                                |
| numDigitsForCheckdigitCalculation        | 17                                |
| numericAlgorithm                         | MX_CLABE_CUERPO                   |
| inputHandlingConfig.characterHandling    | STANDARD                          |
| inputHandlingConfig.invalidInputHandling | ERROR                             |
| inputHandlingConfig.shortInputHandling   | FALLBACK                          |
| inputHandlingConfig.padCharacter         | 0                                 |
| inputHandlingConfig.trimWhitespace       | yes                               |

**MX\_CLAVE\_ELECTOR** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

Used by: MX\_L1\_CLAVE\_ELECTOR

**PATTERNS, TRIED IN ORDER**

|                                       |                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------|
| ([A-Z]{6})(\d{6})(\d{2})([HM])(\d{3}) | MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_ENTIDAD_NUMERO · MX_SEXO_H_M · MX_CM_ALFANUM |
| otherwise                             | MX_CM_ALFANUM                                                                     |

|                      |     |
|----------------------|-----|
| <b>CONFIGURATION</b> |     |
| trimInput            | yes |
| requireMask          | no  |

**MX\_CLAVE\_MUNICIPIO** DATA CLEANSING

Replaces each value found in `mx-clave-municipio-generalizada.txt` (2,758 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_L2_CLAVE_MUNICIPIO`

**CONFIGURATION**

|                |                                                  |
|----------------|--------------------------------------------------|
| lookupFile     | <code>mx-clave-municipio-generalizada.txt</code> |
| delimiter      | <code>,</code>                                   |
| caseSensitive  | <code>yes</code>                                 |
| trimWhitespace | <code>yes</code>                                 |

**MX\_CM\_ALFANUM** CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `MX_L1_CREDENCIAL_INE`, `MX_L1_DIRECCION_COMPLEMENTO`, `MX_L1_CUENTA_BANCARIA`, `MX_L1_PASAPORTE`, `MX_L1_DOCUMENTO_MIGRATORIO`, `MX_L1_CEDULA_PROFESIONAL`, `MX_L1_LICENCIA_CONducir`, `MX_L1_EFIRMA`, `MX_L1_NIV`, `MX_L1_NUMERO_CONTRATO`, `MX_L1_USUARIO_RRSS`, `MX_L2_CCT`, `MX_L3_SALUD_IDENTIFICADOR`, `MX_L3_SALUD_RESULTADO_EXAMEN`, `MX_PENAL_CAUSA`, `MX_CATEGORIA_SUPRIMIDA`, `MX_FECHA_AAMMDD`, `MX_CURP_CUERPO`, `MX_CURP`, `MX_RFC_CUERPO_FISICA`, `MX_RFC_CUERPO_MORAL`, `MX_RFC`, `MX_NSS`, `MX_CLAVE_ELECTOR`, `MX_NOMBRES`, `MX_APELLIDOS`, `MX_NOMBRE_COMPLETO`, `MX_EMAIL`, `MX_TELEFONO`, `MX_CLABE_CUERPO`, `MX_CLABE`, `MX_COORDENADA`, `MX_ANIO`, `MX_EDAD`, `MX_CODIGO_POSTAL`, `MX_PUEBLO`, `MX LENGUA_INDIGENA`, `MX_MEDICAMENTO`, `MX_DISCAPACIDAD`, `MX_PREFERENCIA_SEXUAL`, `MX_IDENTIDAD_GENERO`, `MX_RELIGION`, `MX_OPINION_POLITICA`, `MX_PARTIDO_POLITICO`, `MX_BURO_CREDITO`, `MX_AFORE`, `MX_CREDITO_VIVIENDA`, `MX_SEGURIDAD_SOCIAL`, `MX_PROGRAMA_SOCIAL`, `MX_VIVIENDA`, `MX_ANTECEDENTES`

**CONFIGURATION**

|                    |                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------|
| characterGroups    | <code>0123456789 AEIOU BCDFGHIJKLMNOPQRSTUVWXYZ aeiou<br/>bcdfghijklmnopqrstuvwxyz ÁÉÍÓÚÚ áéíóúü</code> |
| caseSensitive      | <code>yes</code>                                                                                        |
| minMaskedPositions | <code>0</code>                                                                                          |

**MX\_CM\_HEX** CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `MX_L1_DISPOSITIVO`, `MX_IP`

**CONFIGURATION**

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| characterGroups    | <code>0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz<br/>GHIJKLMNOPQRSTUVWXYZ</code> |
| caseSensitive      | <code>yes</code>                                                                    |
| minMaskedPositions | <code>0</code>                                                                      |

**MX\_CODIGO\_POSTAL** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L2_CODIGO_POSTAL`

**PATTERNS, TRIED IN ORDER**

|                             |                                     |
|-----------------------------|-------------------------------------|
| <code>(\d{3})(\d{2})</code> | <code>keep · replace with 00</code> |
| otherwise                   | <code>MX_CM_ALFANUM</code>          |

**CONFIGURATION**

|             |                  |
|-------------|------------------|
| trimInput   | <code>yes</code> |
| requireMask | <code>no</code>  |

**MX\_COLONIA** SECURE LOOKUP

Replaces the value with one of the 60 values in `mx-colonias.txt` , chosen by a keyed hash.

Used by: `MX_L2_COLONIA`

CONFIGURATION

|                            |                      |
|----------------------------|----------------------|
| lookupFile                 | mx-colonias.txt      |
| hashMethod                 | SHA256               |
| maskedValueCase            | PRESERVE_LOOKUP_FILE |
| inputCaseSensitive         | no                   |
| trimWhitespaceFromInput    | yes                  |
| trimWhitespaceInLookupFile | yes                  |

**MX\_COORDENADA** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

|                                                 |                                             |
|-------------------------------------------------|---------------------------------------------|
| (-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+) | keep · MX_CM_ALFANUM · keep · MX_CM_ALFANUM |
| (-?\d{1,3}\.\d)(\d+)                            | keep · MX_CM_ALFANUM                        |
| otherwise                                       | keep                                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CREDITO\_VIVIENDA** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_CREDITO_VIVIENDA_LISTA` .

Used by: `MX_FIN_CREDITO_VIVIENDA`

PATTERNS, TRIED IN ORDER

|                                   |                           |
|-----------------------------------|---------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA                |
| (\d{1,6})                         | MX_CM_ALFANUM             |
| otherwise                         | MX_CREDITO_VIVIENDA_LISTA |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CREDITO\_VIVIENDA\_LISTA** SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-credito-vivienda.txt` , chosen by a keyed hash.

Used by: `MX_CREDITO_VIVIENDA`

CONFIGURATION

|                    |                         |
|--------------------|-------------------------|
| lookupFile         | mx-credito-vivienda.txt |
| hashMethod         | SHA256                  |
| maskedValueCase    | PRESERVE_INPUT          |
| inputCaseSensitive | no                      |

|                            |     |
|----------------------------|-----|
| trimWhitespaceFromInput    | yes |
| trimWhitespaceInLookupFile | yes |

**MX\_CURP** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

Used by: MX\_L1\_CURP

**PATTERNS, TRIED IN ORDER**

|                                             |                |
|---------------------------------------------|----------------|
| ( [A-Z]{4}\d{6} [HMX] [A-Z]{5} [0-9A-Z]\d ) | MX_CURP_VALIDA |
| otherwise                                   | MX_CM_ALFANUM  |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_CUERPO** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_VALIDA

**PATTERNS, TRIED IN ORDER**

|                                                                                                   |                                                                                                                                                  |
|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| ( [A-Z] ) ( [A-Z] ) ( [A-Z]{2} ) ( \d{6} ) ( [HM] ) ( [A-Z]{2} ) ( [A-Z]{3} ) ( [0-9A-Z] ) ( \d ) | MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_SEXO_H_M · MX_ENTIDAD_CURP · MX_CM_ALFANUM · MX_CM_ALFANUM · replace with 0 |
| ( [A-Z] ) ( [A-Z] ) ( [A-Z]{2} ) ( \d{6} ) ( X ) ( [A-Z]{2} ) ( [A-Z]{3} ) ( [0-9A-Z] ) ( \d )    | MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD · keep · MX_ENTIDAD_CURP · MX_CM_ALFANUM · MX_CM_ALFANUM · replace with 0        |
| otherwise                                                                                         | keep                                                                                                                                             |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV** STRING ALGORITHM CHAIN

Applies MX\_CURP\_DV\_P1 → MX\_CURP\_DV\_P2 → MX\_CURP\_DV\_P3 → MX\_CURP\_DV\_P4 → MX\_CURP\_DV\_P5 → MX\_CURP\_DV\_P6 → MX\_CURP\_DV\_P7 → MX\_CURP\_DV\_P8 , in this order.

Used by: MX\_CURP\_VALIDA

**CONFIGURATION**

|                        |               |
|------------------------|---------------|
| algorithmReferences[1] | MX_CURP_DV_P1 |
| algorithmReferences[2] | MX_CURP_DV_P2 |
| algorithmReferences[3] | MX_CURP_DV_P3 |
| algorithmReferences[4] | MX_CURP_DV_P4 |
| algorithmReferences[5] | MX_CURP_DV_P5 |
| algorithmReferences[6] | MX_CURP_DV_P6 |
| algorithmReferences[7] | MX_CURP_DV_P7 |
| algorithmReferences[8] | MX_CURP_DV_P8 |

**MX\_CURP\_DV\_P1** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                  |                             |
|------------------|-----------------------------|
| (.{0})(.{2})(.*) | keep · MX_CURP_DV_T1 · keep |
| otherwise        | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P2** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                  |                             |
|------------------|-----------------------------|
| (.{2})(.{3})(.*) | keep · MX_CURP_DV_T2 · keep |
| otherwise        | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P3** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                  |                             |
|------------------|-----------------------------|
| (.{4})(.{3})(.*) | keep · MX_CURP_DV_T3 · keep |
| otherwise        | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P4** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                  |                             |
|------------------|-----------------------------|
| (.{6})(.{3})(.*) | keep · MX_CURP_DV_T4 · keep |
| otherwise        | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P5** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                  |                             |
|------------------|-----------------------------|
| (.{8})(.{3})(.*) | keep · MX_CURP_DV_T5 · keep |
|------------------|-----------------------------|

|           |      |
|-----------|------|
| otherwise | keep |
|-----------|------|

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P6** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                                |                             |
|--------------------------------|-----------------------------|
| <code>(.{10})(.{4})(.*)</code> | keep · MX_CURP_DV_T6 · keep |
| otherwise                      | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P7** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                                |                             |
|--------------------------------|-----------------------------|
| <code>(.{13})(.{3})(.*)</code> | keep · MX_CURP_DV_T7 · keep |
| otherwise                      | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_P8** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_CURP\_DV

PATTERNS, TRIED IN ORDER

|                                |                             |
|--------------------------------|-----------------------------|
| <code>(.{15})(.{4})(.*)</code> | keep · MX_CURP_DV_T8 · keep |
| otherwise                      | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_CURP\_DV\_T1** DATA CLEANSING

Replaces each value found in `mx-curp-dv-1.txt` (676 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_CURP\_DV\_P1

CONFIGURATION

|            |                               |
|------------|-------------------------------|
| lookupFile | <code>mx-curp-dv-1.txt</code> |
| delimiter  | <code>,</code>                |

|                |     |
|----------------|-----|
| caseSensitive  | yes |
| trimWhitespace | yes |

#### **MX\_CURP\_DV\_T2** DATA CLEANSING

Replaces each value found in `mx-curp-dv-2.txt` (6,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P2`

##### **CONFIGURATION**

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-2.txt</code> |
| delimiter      | ,                             |
| caseSensitive  | yes                           |
| trimWhitespace | yes                           |

#### **MX\_CURP\_DV\_T3** DATA CLEANSING

Replaces each value found in `mx-curp-dv-3.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P3`

##### **CONFIGURATION**

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-3.txt</code> |
| delimiter      | ,                             |
| caseSensitive  | yes                           |
| trimWhitespace | yes                           |

#### **MX\_CURP\_DV\_T4** DATA CLEANSING

Replaces each value found in `mx-curp-dv-4.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P4`

##### **CONFIGURATION**

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-4.txt</code> |
| delimiter      | ,                             |
| caseSensitive  | yes                           |
| trimWhitespace | yes                           |

#### **MX\_CURP\_DV\_T5** DATA CLEANSING

Replaces each value found in `mx-curp-dv-5.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P5`

##### **CONFIGURATION**

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-5.txt</code> |
| delimiter      | ,                             |
| caseSensitive  | yes                           |
| trimWhitespace | yes                           |

#### **MX\_CURP\_DV\_T6** DATA CLEANSING

Replaces each value found in `mx-curp-dv-6.txt` (20,280 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P6`

#### CONFIGURATION

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-6.txt</code> |
| delimiter      | <code>,</code>                |
| caseSensitive  | <code>yes</code>              |
| trimWhitespace | <code>yes</code>              |

#### MX\_CURP\_DV\_T7 DATA CLEANSING

Replaces each value found in `mx-curp-dv-7.txt` (6,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P7`

#### CONFIGURATION

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-7.txt</code> |
| delimiter      | <code>,</code>                |
| caseSensitive  | <code>yes</code>              |
| trimWhitespace | <code>yes</code>              |

#### MX\_CURP\_DV\_T8 DATA CLEANSING

Replaces each value found in `mx-curp-dv-8.txt` (9,360 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P8`

#### CONFIGURATION

|                |                               |
|----------------|-------------------------------|
| lookupFile     | <code>mx-curp-dv-8.txt</code> |
| delimiter      | <code>,</code>                |
| caseSensitive  | <code>yes</code>              |
| trimWhitespace | <code>yes</code>              |

#### MX\_CURP\_VALIDA STRING ALGORITHM CHAIN

Applies `MX_CURP_CUERPO` → `MX_CURP_DV`, in this order.

Used by: `MX_CURP`

#### CONFIGURATION

|                        |                             |
|------------------------|-----------------------------|
| algorithmReferences[1] | <code>MX_CURP_CUERPO</code> |
| algorithmReferences[2] | <code>MX_CURP_DV</code>     |

#### MX\_DECIL SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-decil.txt`, chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

#### CONFIGURATION

|                            |                             |
|----------------------------|-----------------------------|
| lookupFile                 | <code>mx-decil.txt</code>   |
| hashMethod                 | <code>SHA256</code>         |
| maskedValueCase            | <code>PRESERVE_INPUT</code> |
| inputCaseSensitive         | <code>no</code>             |
| trimWhitespaceFromInput    | <code>yes</code>            |
| trimWhitespaceInLookupFile | <code>yes</code>            |

### MX\_DECIL\_ALTO SECURE LOOKUP

Replaces the value with one of the 5 values in `mx-decil-alto.txt` , chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

#### CONFIGURATION

|                            |                   |
|----------------------------|-------------------|
| lookupFile                 | mx-decil-alto.txt |
| hashMethod                 | SHA256            |
| maskedValueCase            | PRESERVE_INPUT    |
| inputCaseSensitive         | no                |
| trimWhitespaceFromInput    | yes               |
| trimWhitespaceInLookupFile | yes               |

### MX\_DIA\_1\_28 NUMERIC MAPPING

Maps the number to another between 1 and 28.

Used by: `MX_FECHA_AAMDD`

#### CONFIGURATION

|          |    |
|----------|----|
| minValue | 1  |
| maxValue | 28 |

### MX\_DIA\_29\_30 NUMERIC MAPPING

Maps the number to another between 29 and 30.

Used by: `MX_FECHA_AAMDD`

#### CONFIGURATION

|          |    |
|----------|----|
| minValue | 29 |
| maxValue | 30 |

### MX\_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

`MX_DIAGNOSTICO_TEXTO` .

Used by: `MX_L3_SALUD_DIAGNOSTICO`

#### PATTERNS, TRIED IN ORDER

|                                                |                                   |
|------------------------------------------------|-----------------------------------|
| <code>([A-TV-Za-tv-z]\d{2}\.\d{1,2})</code>    | <code>MX_CIE10_DECIMAL</code>     |
| <code>([A-TV-Za-tv-z]\d{2,3})</code>           | <code>MX_CIE10</code>             |
| <code>(?i)(s[ií] no true false [sny01])</code> | <code>MX_BANDERA</code>           |
| otherwise                                      | <code>MX_DIAGNOSTICO_TEXTO</code> |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

### MX\_DIAGNOSTICO\_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `mx-diagnostics.txt` , chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

#### CONFIGURATION

|            |                    |
|------------|--------------------|
| lookupFile | mx-diagnostics.txt |
|------------|--------------------|

|                            |                |
|----------------------------|----------------|
| hashMethod                 | SHA256         |
| maskedValueCase            | PRESERVE_INPUT |
| inputCaseSensitive         | no             |
| trimWhitespaceFromInput    | yes            |
| trimWhitespaceInLookupFile | yes            |

#### **MX\_DIRECCION** SECURE LOOKUP

Replaces the value with one of the 3,000 values in `mx-direcciones.txt` , chosen by a keyed hash.

Used by: `MX_L1_DIRECCION`

##### **CONFIGURATION**

|                            |                                 |
|----------------------------|---------------------------------|
| lookupFile                 | <code>mx-direcciones.txt</code> |
| hashMethod                 | SHA256                          |
| maskedValueCase            | PRESERVE_LOOKUP_FILE            |
| inputCaseSensitive         | no                              |
| trimWhitespaceFromInput    | yes                             |
| trimWhitespaceInLookupFile | yes                             |

#### **MX\_DISCAPACIDAD** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_DISCAPACIDAD_LISTA` .

Used by: `MX_L3_SALUD_DISCAPACIDAD`

##### **PATTERNS, TRIED IN ORDER**

|                                                |                                    |
|------------------------------------------------|------------------------------------|
| <code>(?i)(s[ií] no true false [sny01])</code> | <code>MX_BANDERA</code>            |
| <code>(\d{1,6})</code>                         | <code>MX_CM_ALFANUM</code>         |
| otherwise                                      | <code>MX_DISCAPACIDAD_LISTA</code> |

##### **CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### **MX\_DISCAPACIDAD\_LISTA** SECURE LOOKUP

Replaces the value with one of the 8 values in `mx-discapacidad.txt` , chosen by a keyed hash.

Used by: `MX_DISCAPACIDAD`

##### **CONFIGURATION**

|                            |                                  |
|----------------------------|----------------------------------|
| lookupFile                 | <code>mx-discapacidad.txt</code> |
| hashMethod                 | SHA256                           |
| maskedValueCase            | PRESERVE_INPUT                   |
| inputCaseSensitive         | no                               |
| trimWhitespaceFromInput    | yes                              |
| trimWhitespaceInLookupFile | yes                              |

#### **MX\_EDAD** REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_EDAD`

PATTERNS, TRIED IN ORDER

|                    |                             |
|--------------------|-----------------------------|
| (\d{3,})           | replace with 90             |
| ([1-9])(\d)(\.\d+) | keep · MX_CM_ALFANUM · keep |
| ([1-9])(\d)        | keep · MX_CM_ALFANUM        |
| (\d)               | MX_CM_ALFANUM               |
| otherwise          | keep                        |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

Used by: MX\_L1\_EMAIL

PATTERNS, TRIED IN ORDER

|                                 |                                                   |
|---------------------------------|---------------------------------------------------|
| ([^@\s]+)@([^\s]+\.[^\s]{2,24}) | MX_CM_ALFANUM · MX_CM_ALFANUM · replace with test |
| otherwise                       | MX_CM_ALFANUM                                     |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 25 values in mx-empleadores.txt , chosen by a keyed hash.

Used by: MX\_L2\_EMPLEADOR

CONFIGURATION

|                            |                    |
|----------------------------|--------------------|
| lookupFile                 | mx-empleadores.txt |
| hashMethod                 | SHA256             |
| maskedValueCase            | PRESERVE_INPUT     |
| inputCaseSensitive         | no                 |
| trimWhitespaceFromInput    | yes                |
| trimWhitespaceInLookupFile | yes                |

MX\_ENTIDAD\_CURP SECURE LOOKUP

Replaces the value with one of the 33 values in mx-entidad-curp.txt , chosen by a keyed hash.

Used by: MX\_CURP\_CUERPO

CONFIGURATION

|                            |                      |
|----------------------------|----------------------|
| lookupFile                 | mx-entidad-curp.txt  |
| hashMethod                 | SHA256               |
| maskedValueCase            | PRESERVE_LOOKUP_FILE |
| inputCaseSensitive         | no                   |
| trimWhitespaceFromInput    | yes                  |
| trimWhitespaceInLookupFile | yes                  |

MX\_ENTIDAD\_NUMERO SECURE LOOKUP

Replaces the value with one of the 32 values in mx-entidad-numero.txt , chosen by a keyed hash.

Used by: `MX_CLAVE_ELECTOR`

#### CONFIGURATION

|                            |                       |
|----------------------------|-----------------------|
| lookupFile                 | mx-entidad-numero.txt |
| hashMethod                 | SHA256                |
| maskedValueCase            | PRESERVE_INPUT        |
| inputCaseSensitive         | no                    |
| trimWhitespaceFromInput    | yes                   |
| trimWhitespaceInLookupFile | yes                   |

#### MX\_ESCOLARIDAD SECURE LOOKUP

Replaces the value with one of the 12 values in `mx-escolaridad.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESCOLARIDAD`

#### CONFIGURATION

|                            |                    |
|----------------------------|--------------------|
| lookupFile                 | mx-escolaridad.txt |
| hashMethod                 | SHA256             |
| maskedValueCase            | PRESERVE_INPUT     |
| inputCaseSensitive         | no                 |
| trimWhitespaceFromInput    | yes                |
| trimWhitespaceInLookupFile | yes                |

#### MX\_ESCUELA SECURE LOOKUP

Replaces the value with one of the 15 values in `mx-escuelas.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESCUELA`

#### CONFIGURATION

|                            |                 |
|----------------------------|-----------------|
| lookupFile                 | mx-escuelas.txt |
| hashMethod                 | SHA256          |
| maskedValueCase            | PRESERVE_INPUT  |
| inputCaseSensitive         | no              |
| trimWhitespaceFromInput    | yes             |
| trimWhitespaceInLookupFile | yes             |

#### MX\_ESTADO\_CIVIL SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-estado-civil.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESTADO_CIVIL`

#### CONFIGURATION

|                            |                     |
|----------------------------|---------------------|
| lookupFile                 | mx-estado-civil.txt |
| hashMethod                 | SHA256              |
| maskedValueCase            | PRESERVE_INPUT      |
| inputCaseSensitive         | no                  |
| trimWhitespaceFromInput    | yes                 |
| trimWhitespaceInLookupFile | yes                 |

#### MX\_ESTADO\_CREDITICIO SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-estado-crediticio.txt`, chosen by a keyed hash.

Used by: `MX_BURO_CREDITO`

#### CONFIGURATION

|                            |                          |
|----------------------------|--------------------------|
| lookupFile                 | mx-estado-credificio.txt |
| hashMethod                 | SHA256                   |
| maskedValueCase            | PRESERVE_INPUT           |
| inputCaseSensitive         | no                       |
| trimWhitespaceFromInput    | yes                      |
| trimWhitespaceInLookupFile | yes                      |

#### MX\_FECHA\_AAMDD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

Used by: MX\_CURP\_CUERPO , MX\_RFC\_CUERPO\_FISICA , MX\_RFC\_CUERPO\_MORAL , MX\_RFC , MX\_CLAVE\_ELECTOR

#### PATTERNS, TRIED IN ORDER

|                                            |                                                      |
|--------------------------------------------|------------------------------------------------------|
| (\d)(\d)(0[1-9] 1[0-2])(0[1-9] 1\d 2[0-8]) | keep · MX_CM_ALFANUM · MX_MES · MX_DIA_1_28          |
| (\d)(\d)(0[13-9] 1[0-2])(29 30)            | keep · MX_CM_ALFANUM · MX_MES_30_DIAS · MX_DIA_29_30 |
| (\d)(\d)(0[13578] 1[02])(31)               | keep · MX_CM_ALFANUM · MX_MES_31_DIAS · keep         |
| (\d)(\d)(02)(29)                           | keep · MX_CM_ALFANUM · keep · replace with 28        |
| otherwise                                  | MX_CM_ALFANUM                                        |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### MX\_FECHA\_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: MX\_L2\_FECHA\_EVENTO

#### CONFIGURATION

|          |      |
|----------|------|
| minRange | -30  |
| maxRange | 30   |
| unit     | DAYS |
| roll     | no   |

#### MX\_FECHA\_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: MX\_L2\_FECHA\_NACIMIENTO

#### CONFIGURATION

|          |      |
|----------|------|
| minRange | -60  |
| maxRange | 60   |
| unit     | DAYS |
| roll     | no   |

#### MX\_GRUPO\_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in mx-grupo-sanguineo.txt , chosen by a keyed hash.

Used by: MX\_L3\_SALUD\_GRUPO\_SANGUINEO

#### CONFIGURATION

|            |                        |
|------------|------------------------|
| lookupFile | mx-grupo-sanguineo.txt |
|------------|------------------------|

|                            |                      |
|----------------------------|----------------------|
| hashMethod                 | SHA256               |
| maskedValueCase            | PRESERVE_LOOKUP_FILE |
| inputCaseSensitive         | no                   |
| trimWhitespaceFromInput    | yes                  |
| trimWhitespaceInLookupFile | yes                  |

**MX\_IDENTIDAD\_GENERO** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_IDENTIDAD\_GENERO\_LISTA .

Used by: MX\_L3\_IDENTIDAD\_GENERO

**PATTERNS, TRIED IN ORDER**

|                                   |                           |
|-----------------------------------|---------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA                |
| (\d{1,6})                         | MX_CM_ALFANUM             |
| otherwise                         | MX_IDENTIDAD_GENERO_LISTA |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_IDENTIDAD\_GENERO\_LISTA** SECURE LOOKUP

Replaces the value with one of the 8 values in mx-identidad-genero.txt , chosen by a keyed hash.

Used by: MX\_IDENTIDAD\_GENERO

**CONFIGURATION**

|                            |                         |
|----------------------------|-------------------------|
| lookupFile                 | mx-identidad-genero.txt |
| hashMethod                 | SHA256                  |
| maskedValueCase            | PRESERVE_INPUT          |
| inputCaseSensitive         | no                      |
| trimWhitespaceFromInput    | yes                     |
| trimWhitespaceInLookupFile | yes                     |

**MX\_INGRESO\_MENSUAL** NUMERIC MAPPING

Maps the number to another between 8,000 and 250,000.

Used by: MX\_FIN\_INGRESO\_MENSUAL

**CONFIGURATION**

|          |        |
|----------|--------|
| minValue | 8000   |
| maxValue | 250000 |

**MX\_IP** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX\_CM\_HEX .

Used by: MX\_L1\_IP

**PATTERNS, TRIED IN ORDER**

|                                            |                                               |
|--------------------------------------------|-----------------------------------------------|
| (\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}) | MX_OCTETO . MX_OCTETO . MX_OCTETO . MX_OCTETO |
| otherwise                                  | MX_CM_HEX                                     |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_LENGUA\_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_LENGUA\_INDIGENA\_LISTA .

Used by: MX\_L3\_LENGUA\_INDIGENA

PATTERNS, TRIED IN ORDER

|                                   |                          |
|-----------------------------------|--------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA               |
| (\d{1,6})                         | MX_CM_ALFANUM            |
| otherwise                         | MX_LENGUA_INDIGENA_LISTA |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_LENGUA\_INDIGENA\_LISTA SECURE LOOKUP

Replaces the value with one of the 27 values in mx-lenguas.txt , chosen by a keyed hash.

Used by: MX\_LENGUA\_INDIGENA

CONFIGURATION

|                            |                |
|----------------------------|----------------|
| lookupFile                 | mx-lenguas.txt |
| hashMethod                 | SHA256         |
| maskedValueCase            | PRESERVE_INPUT |
| inputCaseSensitive         | no             |
| trimWhitespaceFromInput    | yes            |
| trimWhitespaceInLookupFile | yes            |

MX\_LOCALIDAD SECURE LOOKUP

Replaces the value with one of the 229 values in mx-localidades.txt , chosen by a keyed hash.

Used by: MX\_L2\_LOCALIDAD

CONFIGURATION

|                            |                      |
|----------------------------|----------------------|
| lookupFile                 | mx-localidades.txt   |
| hashMethod                 | SHA256               |
| maskedValueCase            | PRESERVE_LOOKUP_FILE |
| inputCaseSensitive         | no                   |
| trimWhitespaceFromInput    | yes                  |
| trimWhitespaceInLookupFile | yes                  |

MX\_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_MEDICAMENTO\_LISTA .

Used by: MX\_L3\_SALUD\_MEDICAMENTO

PATTERNS, TRIED IN ORDER

|                                   |            |
|-----------------------------------|------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA |
|-----------------------------------|------------|

|           |                      |
|-----------|----------------------|
| (\d{1,6}) | MX_CM_ALFANUM        |
| otherwise | MX_MEDICAMENTO_LISTA |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### MX\_MEDICAMENTO\_LISTA SECURE LOOKUP

Replaces the value with one of the 26 values in `mx-medicamentos.txt`, chosen by a keyed hash.

Used by: `MX_MEDICAMENTO`

##### CONFIGURATION

|                            |                     |
|----------------------------|---------------------|
| lookupFile                 | mx-medicamentos.txt |
| hashMethod                 | SHA256              |
| maskedValueCase            | PRESERVE_INPUT      |
| inputCaseSensitive         | no                  |
| trimWhitespaceFromInput    | yes                 |
| trimWhitespaceInLookupFile | yes                 |

#### MX\_MES NUMERIC MAPPING

Maps the number to another between 1 and 12.

Used by: `MX_FECHA_AAMDD`

##### CONFIGURATION

|          |    |
|----------|----|
| minValue | 1  |
| maxValue | 12 |

#### MX\_MES\_30\_DIAS SECURE LOOKUP

Replaces the value with one of the 11 values in `mx-meses-30-dias.txt`, chosen by a keyed hash.

Used by: `MX_FECHA_AAMDD`

##### CONFIGURATION

|                            |                      |
|----------------------------|----------------------|
| lookupFile                 | mx-meses-30-dias.txt |
| hashMethod                 | SHA256               |
| maskedValueCase            | PRESERVE_INPUT       |
| inputCaseSensitive         | no                   |
| trimWhitespaceFromInput    | yes                  |
| trimWhitespaceInLookupFile | yes                  |

#### MX\_MES\_31\_DIAS SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-meses-31-dias.txt`, chosen by a keyed hash.

Used by: `MX_FECHA_AAMDD`

##### CONFIGURATION

|                         |                      |
|-------------------------|----------------------|
| lookupFile              | mx-meses-31-dias.txt |
| hashMethod              | SHA256               |
| maskedValueCase         | PRESERVE_INPUT       |
| inputCaseSensitive      | no                   |
| trimWhitespaceFromInput | yes                  |

|                            |     |
|----------------------------|-----|
| trimWhitespaceInLookupFile | yes |
|----------------------------|-----|

#### **MX\_MONTO\_DEUDA** NUMERIC MAPPING

Maps the number to another between 1,000 and 5,000,000.

Used by: **MX\_FIN\_MONTO\_DEUDA**

##### **CONFIGURATION**

|          |         |
|----------|---------|
| minValue | 1000    |
| maxValue | 5000000 |

#### **MX\_MOP** SECURE LOOKUP

Replaces the value with one of the 9 values in **mx-mop.txt** , chosen by a keyed hash.

Used by: **MX\_BURO\_CREDITO**

##### **CONFIGURATION**

|                            |                |
|----------------------------|----------------|
| lookupFile                 | mx-mop.txt     |
| hashMethod                 | SHA256         |
| maskedValueCase            | PRESERVE_INPUT |
| inputCaseSensitive         | no             |
| trimWhitespaceFromInput    | yes            |
| trimWhitespaceInLookupFile | yes            |

#### **MX\_MUNICIPIO** DATA CLEANSING

Replaces each value found in **mx-municipio-generalizado.txt** (6,547 pairs) by its counterpart; values not in the file stay as they are.

Used by: **MX\_L2\_MUNICIPIO**

##### **CONFIGURATION**

|                |                               |
|----------------|-------------------------------|
| lookupFile     | mx-municipio-generalizado.txt |
| delimiter      |                               |
| caseSensitive  | yes                           |
| trimWhitespace | yes                           |

#### **MX\_NACIONALIDAD** SECURE LOOKUP

Replaces the value with one of the 20 values in **mx-nacionalidades.txt** , chosen by a keyed hash.

Used by: **MX\_L2\_NACIONALIDAD**

##### **CONFIGURATION**

|                            |                       |
|----------------------------|-----------------------|
| lookupFile                 | mx-nacionalidades.txt |
| hashMethod                 | SHA256                |
| maskedValueCase            | PRESERVE_INPUT        |
| inputCaseSensitive         | no                    |
| trimWhitespaceFromInput    | yes                   |
| trimWhitespaceInLookupFile | yes                   |

#### **MX\_NIVEL\_SOCIOECONOMICO** REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: **MX\_NSE** .

Used by: **MX\_FIN\_NIVEL\_SOCIOECONOMICO**

PATTERNS, TRIED IN ORDER

|                         |                 |
|-------------------------|-----------------|
| ([1-5])                 | MX_QUINTIL      |
| ([6-9] 10)              | MX_DECIL_ALTO   |
| (?i)(decil\s*)(\d{1,2}) | keep · MX_DECIL |
| otherwise               | MX_NSE          |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_NOMBRE\_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

Used by: MX\_L1\_NOMBRE\_COMPLETO

PATTERNS, TRIED IN ORDER

|                                       |                                                                              |
|---------------------------------------|------------------------------------------------------------------------------|
| ([^\,]+),\s*(.+) )                    | MX_APELLIDOS · MX_NOMBRES                                                    |
| (\S+)                                 | MX_NOMBRE_PILA                                                               |
| (\S+)\s+(\S+)                         | MX_NOMBRE_PILA · MX_APELLIDO                                                 |
| (\S+)\s+(\S+)\s+(\S+)                 | MX_NOMBRE_PILA · MX_APELLIDO · MX_APELLIDO                                   |
| (\S+)\s+(\S+)\s+(\S+)\s+(\S+)         | MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_APELLIDO · MX_APELLIDO                  |
| (\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+) | MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_APELLIDO · MX_APELLIDO |
| otherwise                             | MX_CM_ALFANUM                                                                |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_NOMBRE\_PILA NAME

Replaces the name with one of the 255 names in mx-nombres.txt .

Used by: MX\_NOMBRES , MX\_NOMBRE\_COMPLETO

CONFIGURATION

|                    |                |
|--------------------|----------------|
| lookupFile         | mx-nombres.txt |
| maskedValueCase    | PRESERVE_INPUT |
| filterAccent       | yes            |
| inputCaseSensitive | no             |

MX\_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX\_CM\_ALFANUM .

Used by: MX\_L1\_NOMBRE , MX\_NOMBRE\_COMPLETO

PATTERNS, TRIED IN ORDER

|                       |                                                  |
|-----------------------|--------------------------------------------------|
| (\S+)                 | MX_NOMBRE_PILA                                   |
| (\S+)\s+(\S+)         | MX_NOMBRE_PILA · MX_NOMBRE_PILA                  |
| (\S+)\s+(\S+)\s+(\S+) | MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_NOMBRE_PILA |
| otherwise             | MX_CM_ALFANUM                                    |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### MX\_NSE SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-nse.txt` , chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

#### CONFIGURATION

|                            |                                   |
|----------------------------|-----------------------------------|
| lookupFile                 | <code>mx-nse.txt</code>           |
| hashMethod                 | <code>SHA256</code>               |
| maskedValueCase            | <code>PRESERVE_LOOKUP_FILE</code> |
| inputCaseSensitive         | no                                |
| trimWhitespaceFromInput    | yes                               |
| trimWhitespaceInLookupFile | yes                               |

#### MX\_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_NSS`

#### PATTERNS, TRIED IN ORDER

|                       |                            |
|-----------------------|----------------------------|
| <code>(\d{11})</code> | <code>MX_NSS_LUHN</code>   |
| otherwise             | <code>MX_CM_ALFANUM</code> |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### MX\_NSS\_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: `MX_NSS`

#### CONFIGURATION

|          |                |
|----------|----------------|
| preserve | <code>0</code> |
|----------|----------------|

#### MX\_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `MX_IP`

#### CONFIGURATION

|          |                  |
|----------|------------------|
| minValue | <code>1</code>   |
| maxValue | <code>254</code> |

#### MX\_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in `mx-ocupaciones.txt` , chosen by a keyed hash.

Used by: `MX_L2_OCUPACION`

#### CONFIGURATION

|            |                                 |
|------------|---------------------------------|
| lookupFile | <code>mx-ocupaciones.txt</code> |
| hashMethod | <code>SHA256</code>             |

|                            |                |
|----------------------------|----------------|
| maskedValueCase            | PRESERVE_INPUT |
| inputCaseSensitive         | no             |
| trimWhitespaceFromInput    | yes            |
| trimWhitespaceInLookupFile | yes            |

**MX\_OPINION\_POLITICA** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_OPINION\_POLITICA\_LISTA .

Used by: MX\_L3\_OPINION\_POLITICA

**PATTERNS, TRIED IN ORDER**

|                                   |                           |
|-----------------------------------|---------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA                |
| (\d{1,6})                         | MX_CM_ALFANUM             |
| otherwise                         | MX_OPINION_POLITICA_LISTA |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_OPINION\_POLITICA\_LISTA** SECURE LOOKUP

Replaces the value with one of the 7 values in mx-opiniones-politicas.txt , chosen by a keyed hash.

Used by: MX\_OPINION\_POLITICA

**CONFIGURATION**

|                            |                            |
|----------------------------|----------------------------|
| lookupFile                 | mx-opiniones-politicas.txt |
| hashMethod                 | SHA256                     |
| maskedValueCase            | PRESERVE_INPUT             |
| inputCaseSensitive         | no                         |
| trimWhitespaceFromInput    | yes                        |
| trimWhitespaceInLookupFile | yes                        |

**MX\_PARTIDO\_POLITICO** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_PARTIDO\_POLITICO\_LISTA .

Used by: MX\_L3\_AFILIACION\_POLITICA

**PATTERNS, TRIED IN ORDER**

|                                   |                           |
|-----------------------------------|---------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA                |
| (\d{1,6})                         | MX_CM_ALFANUM             |
| otherwise                         | MX_PARTIDO_POLITICO_LISTA |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_PARTIDO\_POLITICO\_LISTA** SECURE LOOKUP

Replaces the value with one of the 10 values in mx-partidos.txt , chosen by a keyed hash.

Used by: MX\_PARTIDO\_POLITICO

CONFIGURATION

|                            |                 |
|----------------------------|-----------------|
| lookupFile                 | mx-partidos.txt |
| hashMethod                 | SHA256          |
| maskedValueCase            | PRESERVE_INPUT  |
| inputCaseSensitive         | no              |
| trimWhitespaceFromInput    | yes             |
| trimWhitespaceInLookupFile | yes             |

MX\_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 200,000 and 30,000,000.

Used by: MX\_FIN\_PATRIMONIO

CONFIGURATION

|          |          |
|----------|----------|
| minValue | 200000   |
| maxValue | 30000000 |

MX\_PLACA CHARACTER MAPPING

Maps each character to another of its group (3 groups), keeping length and format.

Used by: MX\_L1\_PLACA

CONFIGURATION

|                 |                                                               |
|-----------------|---------------------------------------------------------------|
| characterGroups | ABCDEFGHIJKLMNPRSTUVWXYZ abcdefghijklmnpqrstuvwxyz 0123456789 |
| caseSensitive   | yes                                                           |

MX\_PREFERENCIA\_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_PREFERENCIA\_SEXUAL\_LISTA .

Used by: MX\_L3\_PREFERENCIA\_SEXUAL

PATTERNS, TRIED IN ORDER

|                                   |                             |
|-----------------------------------|-----------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA                  |
| (\d{1,6})                         | MX_CM_ALFANUM               |
| otherwise                         | MX_PREFERENCIA_SEXUAL_LISTA |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_PREFERENCIA\_SEXUAL\_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in mx-preferencia-sexual.txt , chosen by a keyed hash.

Used by: MX\_PREFERENCIA\_SEXUAL

CONFIGURATION

|                            |                           |
|----------------------------|---------------------------|
| lookupFile                 | mx-preferencia-sexual.txt |
| hashMethod                 | SHA256                    |
| maskedValueCase            | PRESERVE_INPUT            |
| inputCaseSensitive         | no                        |
| trimWhitespaceFromInput    | yes                       |
| trimWhitespaceInLookupFile | yes                       |

**MX\_PROGRAMA\_SOCIAL** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX\_PROGRAMA\_SOCIAL\_LISTA .

Used by: MX\_FIN\_PROGRAMA\_SOCIAL

PATTERNS, TRIED IN ORDER

|                                   |                          |
|-----------------------------------|--------------------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA               |
| (\d{1,6})                         | MX_CM_ALFANUM            |
| otherwise                         | MX_PROGRAMA_SOCIAL_LISTA |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_PROGRAMA\_SOCIAL\_LISTA** SECURE LOOKUP

Replaces the value with one of the 13 values in mx-programas-sociales.txt , chosen by a keyed hash.

Used by: MX\_PROGRAMA\_SOCIAL

CONFIGURATION

|                            |                           |
|----------------------------|---------------------------|
| lookupFile                 | mx-programas-sociales.txt |
| hashMethod                 | SHA256                    |
| maskedValueCase            | PRESERVE_INPUT            |
| inputCaseSensitive         | no                        |
| trimWhitespaceFromInput    | yes                       |
| trimWhitespaceInLookupFile | yes                       |

**MX\_PUEBLO** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_PUEBLO\_LISTA .

Used by: MX\_L3\_ETNIA

PATTERNS, TRIED IN ORDER

|                                   |                 |
|-----------------------------------|-----------------|
| (?i)(s[ií] no true false [sny01]) | MX_BANDERA      |
| (\d{1,6})                         | MX_CM_ALFANUM   |
| otherwise                         | MX_PUEBLO_LISTA |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_PUEBLO\_LISTA** SECURE LOOKUP

Replaces the value with one of the 31 values in mx-pueblos.txt , chosen by a keyed hash.

Used by: MX\_PUEBLO

CONFIGURATION

|                         |                |
|-------------------------|----------------|
| lookupFile              | mx-pueblos.txt |
| hashMethod              | SHA256         |
| maskedValueCase         | PRESERVE_INPUT |
| inputCaseSensitive      | no             |
| trimWhitespaceFromInput | yes            |

|                            |     |
|----------------------------|-----|
| trimWhitespaceInLookupFile | yes |
|----------------------------|-----|

#### MX\_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in `mx-quintil.txt`, chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

##### CONFIGURATION

|                            |                             |
|----------------------------|-----------------------------|
| lookupFile                 | <code>mx-quintil.txt</code> |
| hashMethod                 | <code>SHA256</code>         |
| maskedValueCase            | <code>PRESERVE_INPUT</code> |
| inputCaseSensitive         | <code>no</code>             |
| trimWhitespaceFromInput    | <code>yes</code>            |
| trimWhitespaceInLookupFile | <code>yes</code>            |

#### MX\_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_CREDENCIAL`, `MX_L3_BIOMETRICO`, `MX_L3_INFORMACION_GENETICA`

##### PATTERNS, TRIED IN ORDER

|                    |                                 |
|--------------------|---------------------------------|
| <code>(.+) </code> | each character → <code>X</code> |
| otherwise          | keep                            |

##### CONFIGURATION

|             |                  |
|-------------|------------------|
| trimInput   | <code>yes</code> |
| requireMask | <code>no</code>  |

#### MX\_REGIMEN\_FISCAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_REGIMEN_FISCAL_NOMBRE`.

Used by: `MX_FIN_REGIMEN_FISCAL`

##### PATTERNS, TRIED IN ORDER

|                                      |                                                                                     |
|--------------------------------------|-------------------------------------------------------------------------------------|
| <code>(6\d{2})</code>                | <code>MX_REGIMEN_FISCAL_CLAVE</code>                                                |
| <code>(6\d{2})(\s*[—]\s*)(.+)</code> | <code>MX_REGIMEN_FISCAL_CLAVE</code> · keep · <code>MX_REGIMEN_FISCAL_NOMBRE</code> |
| otherwise                            | <code>MX_REGIMEN_FISCAL_NOMBRE</code>                                               |

##### CONFIGURATION

|             |                  |
|-------------|------------------|
| trimInput   | <code>yes</code> |
| requireMask | <code>no</code>  |

#### MX\_REGIMEN\_FISCAL\_CLAVE SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-regimen-fiscal-clave.txt`, chosen by a keyed hash.

Used by: `MX_REGIMEN_FISCAL`

##### CONFIGURATION

|                    |                                          |
|--------------------|------------------------------------------|
| lookupFile         | <code>mx-regimen-fiscal-clave.txt</code> |
| hashMethod         | <code>SHA256</code>                      |
| maskedValueCase    | <code>PRESERVE_INPUT</code>              |
| inputCaseSensitive | <code>no</code>                          |

|                            |     |
|----------------------------|-----|
| trimWhitespaceFromInput    | yes |
| trimWhitespaceInLookupFile | yes |

**MX\_REGIMEN\_FISCAL\_NOMBRE** SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-regimen-fiscal-nombre.txt` , chosen by a keyed hash.

Used by: `MX_REGIMEN_FISCAL`

**CONFIGURATION**

|                            |                                           |
|----------------------------|-------------------------------------------|
| lookupFile                 | <code>mx-regimen-fiscal-nombre.txt</code> |
| hashMethod                 | SHA256                                    |
| maskedValueCase            | <code>PRESERVE_LOOKUP_FILE</code>         |
| inputCaseSensitive         | no                                        |
| trimWhitespaceFromInput    | yes                                       |
| trimWhitespaceInLookupFile | yes                                       |

**MX\_RELIGION** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_RELIGION_LISTA` .

Used by: `MX_L3_RELIGION`

**PATTERNS, TRIED IN ORDER**

|                                                |                                |
|------------------------------------------------|--------------------------------|
| <code>(?i)(s[ií] no true false [sny01])</code> | <code>MX_BANDERA</code>        |
| <code>(\d{1,6})</code>                         | <code>MX_CM_ALFANUM</code>     |
| otherwise                                      | <code>MX_RELIGION_LISTA</code> |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_RELIGION\_LISTA** SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-religiones.txt` , chosen by a keyed hash.

Used by: `MX_RELIGION`

**CONFIGURATION**

|                            |                                |
|----------------------------|--------------------------------|
| lookupFile                 | <code>mx-religiones.txt</code> |
| hashMethod                 | SHA256                         |
| maskedValueCase            | <code>PRESERVE_INPUT</code>    |
| inputCaseSensitive         | no                             |
| trimWhitespaceFromInput    | yes                            |
| trimWhitespaceInLookupFile | yes                            |

**MX\_RFC** REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_RFC`

**PATTERNS, TRIED IN ORDER**

|                                                                |                                                                              |
|----------------------------------------------------------------|------------------------------------------------------------------------------|
| <code>([A-ZÑ&amp;]{4}\d{6}[A-Z0-9]{2}[0-9A])</code>            | <code>MX_RFC_FISICA</code>                                                   |
| <code>([A-ZÑ&amp;]{3}\d{6}[A-Z0-9]{2}[0-9A])</code>            | <code>MX_RFC_MORAL</code>                                                    |
| <code>([A-ZÑ&amp;])([A-ZÑ&amp;])([A-ZÑ&amp;]{2})(\d{6})</code> | <code>MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD</code> |
| otherwise                                                      | <code>MX_CM_ALFANUM</code>                                                   |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_CUERPO\_FISICA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_FISICA

PATTERNS, TRIED IN ORDER

|                                                            |                                                                                                  |
|------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| ([A-ZÑ&])([A-ZÑ&])([A-ZÑ&]{2})(\d{6})([A-Z0-9]{2})([0-9A]) | MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_CM_ALFANUM · replace with 0 |
| otherwise                                                  | keep                                                                                             |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_CUERPO\_MORAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_MORAL

PATTERNS, TRIED IN ORDER

|                                          |                                                                  |
|------------------------------------------|------------------------------------------------------------------|
| ([A-ZÑ&]{3})(\d{6})([A-Z0-9]{2})([0-9A]) | MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_CM_ALFANUM · replace with 0 |
| otherwise                                | keep                                                             |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_DV STRING ALGORITHM CHAIN

Applies MX\_RFC\_DV\_P1 → MX\_RFC\_DV\_P2 → MX\_RFC\_DV\_P3 → MX\_RFC\_DV\_P4 → MX\_RFC\_DV\_P5 → MX\_RFC\_DV\_P6 , in this order.

Used by: MX\_RFC\_FISICA , MX\_RFC\_MORAL

CONFIGURATION

|                        |              |
|------------------------|--------------|
| algorithmReferences[1] | MX_RFC_DV_P1 |
| algorithmReferences[2] | MX_RFC_DV_P2 |
| algorithmReferences[3] | MX_RFC_DV_P3 |
| algorithmReferences[4] | MX_RFC_DV_P4 |
| algorithmReferences[5] | MX_RFC_DV_P5 |
| algorithmReferences[6] | MX_RFC_DV_P6 |

MX\_RFC\_DV\_P1 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_DV

PATTERNS, TRIED IN ORDER

|                  |                            |
|------------------|----------------------------|
| (.{0})(.{2})(.*) | keep · MX_RFC_DV_T1 · keep |
| otherwise        | keep                       |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_DV\_P2 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_DV

PATTERNS, TRIED IN ORDER

|                  |                            |
|------------------|----------------------------|
| (.{2})(.{3})(.*) | keep · MX_RFC_DV_T2 · keep |
| otherwise        | keep                       |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_DV\_P3 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_DV

PATTERNS, TRIED IN ORDER

|                  |                            |
|------------------|----------------------------|
| (.{4})(.{3})(.*) | keep · MX_RFC_DV_T3 · keep |
| otherwise        | keep                       |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_DV\_P4 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_DV

PATTERNS, TRIED IN ORDER

|                  |                            |
|------------------|----------------------------|
| (.{6})(.{3})(.*) | keep · MX_RFC_DV_T4 · keep |
| otherwise        | keep                       |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

MX\_RFC\_DV\_P5 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_DV

PATTERNS, TRIED IN ORDER

|                  |                            |
|------------------|----------------------------|
| (.{8})(.{3})(.*) | keep · MX_RFC_DV_T5 · keep |
| otherwise        | keep                       |

CONFIGURATION

|           |     |
|-----------|-----|
| trimInput | yes |
|-----------|-----|

|             |    |
|-------------|----|
| requireMask | no |
|-------------|----|

**MX\_RFC\_DV\_P6** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_DV

**PATTERNS, TRIED IN ORDER**

|                   |                            |
|-------------------|----------------------------|
| (.{10})(.{4})(.*) | keep · MX_RFC_DV_T6 · keep |
| otherwise         | keep                       |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_RFC\_DV\_T1** DATA CLEANSING

Replaces each value found in mx-rfc-dv-1.txt (812 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_RFC\_DV\_P1

**CONFIGURATION**

|                |                 |
|----------------|-----------------|
| lookupFile     | mx-rfc-dv-1.txt |
| delimiter      | ,               |
| caseSensitive  | yes             |
| trimWhitespace | yes             |

**MX\_RFC\_DV\_T2** DATA CLEANSING

Replaces each value found in mx-rfc-dv-2.txt (8,624 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_RFC\_DV\_P2

**CONFIGURATION**

|                |                 |
|----------------|-----------------|
| lookupFile     | mx-rfc-dv-2.txt |
| delimiter      | ,               |
| caseSensitive  | yes             |
| trimWhitespace | yes             |

**MX\_RFC\_DV\_T3** DATA CLEANSING

Replaces each value found in mx-rfc-dv-3.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_RFC\_DV\_P3

**CONFIGURATION**

|                |                 |
|----------------|-----------------|
| lookupFile     | mx-rfc-dv-3.txt |
| delimiter      | ,               |
| caseSensitive  | yes             |
| trimWhitespace | yes             |

**MX\_RFC\_DV\_T4** DATA CLEANSING

Replaces each value found in mx-rfc-dv-4.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_RFC\_DV\_P4

#### CONFIGURATION

|                |                 |
|----------------|-----------------|
| lookupFile     | mx-rfc-dv-4.txt |
| delimiter      | ,               |
| caseSensitive  | yes             |
| trimWhitespace | yes             |

#### MX\_RFC\_DV\_T5 DATA CLEANSING

Replaces each value found in mx-rfc-dv-5.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_RFC\_DV\_P5

#### CONFIGURATION

|                |                 |
|----------------|-----------------|
| lookupFile     | mx-rfc-dv-5.txt |
| delimiter      | ,               |
| caseSensitive  | yes             |
| trimWhitespace | yes             |

#### MX\_RFC\_DV\_T6 DATA CLEANSING

Replaces each value found in mx-rfc-dv-6.txt (14,256 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX\_RFC\_DV\_P6

#### CONFIGURATION

|                |                 |
|----------------|-----------------|
| lookupFile     | mx-rfc-dv-6.txt |
| delimiter      | ,               |
| caseSensitive  | yes             |
| trimWhitespace | yes             |

#### MX\_RFC\_FISICA STRING ALGORITHM CHAIN

Applies MX\_RFC\_CUERPO\_FISICA → MX\_RFC\_DV , in this order.

Used by: MX\_RFC

#### CONFIGURATION

|                        |                      |
|------------------------|----------------------|
| algorithmReferences[1] | MX_RFC_CUERPO_FISICA |
| algorithmReferences[2] | MX_RFC_DV            |

#### MX\_RFC\_MORAL STRING ALGORITHM CHAIN

Applies MX\_RFC\_CUERPO\_MORAL → MX\_RFC\_RELLENO → MX\_RFC\_DV → MX\_RFC\_SIN\_RELLENO , in this order.

Used by: MX\_RFC

#### CONFIGURATION

|                        |                     |
|------------------------|---------------------|
| algorithmReferences[1] | MX_RFC_CUERPO_MORAL |
| algorithmReferences[2] | MX_RFC_RELLENO      |
| algorithmReferences[3] | MX_RFC_DV           |
| algorithmReferences[4] | MX_RFC_SIN_RELLENO  |

#### MX\_RFC\_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX\_RFC\_MORAL

**PATTERNS, TRIED IN ORDER**

|                      |                                          |
|----------------------|------------------------------------------|
| <code>(.){11}</code> | <code>MX_RFC_RELLENO_TABLA</code> · keep |
| otherwise            | keep                                     |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_RFC\_RELLENO\_TABLA** DATA CLEANSING

Replaces each value found in `mx-rfc-relleno.txt` (38 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_RELLENO`

**CONFIGURATION**

|                |                                 |
|----------------|---------------------------------|
| lookupFile     | <code>mx-rfc-relleno.txt</code> |
| delimiter      | <code>,</code>                  |
| caseSensitive  | yes                             |
| trimWhitespace | yes                             |

**MX\_RFC\_SIN\_RELLENO** REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_MORAL`

**PATTERNS, TRIED IN ORDER**

|                      |               |
|----------------------|---------------|
| <code>(_){12}</code> | remove · keep |
| otherwise            | keep          |

**CONFIGURATION**

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_SALARIO\_DIARIO** NUMERIC MAPPING

Maps the number to another between 280 and 3,000.

Used by: `MX_FIN_SALARIO_DIARIO`

**CONFIGURATION**

|          |                   |
|----------|-------------------|
| minValue | <code>280</code>  |
| maxValue | <code>3000</code> |

**MX\_SALDO\_RETIRO** NUMERIC MAPPING

Maps the number to another between 5,000 and 5,000,000.

Used by: `MX_FIN_SALDO_RETIRO`

**CONFIGURATION**

|          |                      |
|----------|----------------------|
| minValue | <code>5000</code>    |
| maxValue | <code>5000000</code> |

**MX\_SEGURIDAD\_SOCIAL** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_SEGURIDAD_SOCIAL_LISTA` .

Used by: `MX_FIN_SEGURIDAD_SOCIAL`

#### PATTERNS, TRIED IN ORDER

|                                                |                                        |
|------------------------------------------------|----------------------------------------|
| <code>(?i)(s[ií] no true false [sny01])</code> | <code>MX_BANDERA</code>                |
| <code>(\d{1,2})</code>                         | <code>MX_CM_ALFANUM</code>             |
| otherwise                                      | <code>MX_SEGURIDAD_SOCIAL_LISTA</code> |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### `MX_SEGURIDAD_SOCIAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-seguridad-social.txt`, chosen by a keyed hash.

Used by: `MX_SEGURIDAD_SOCIAL`

#### CONFIGURATION

|                            |                                      |
|----------------------------|--------------------------------------|
| lookupFile                 | <code>mx-seguridad-social.txt</code> |
| hashMethod                 | <code>SHA256</code>                  |
| maskedValueCase            | <code>PRESERVE_LOOKUP_FILE</code>    |
| inputCaseSensitive         | no                                   |
| trimWhitespaceFromInput    | yes                                  |
| trimWhitespaceInLookupFile | yes                                  |

#### `MX_SEXO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_SEXO`

#### PATTERNS, TRIED IN ORDER

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <code>(?i)(femenino masculino)</code> | <code>MX_SEXO_PALABRA</code>      |
| <code>(?i)(mujer hombre)</code>       | <code>MX_SEXO_MUJER_HOMBRE</code> |
| <code>(?i)(female male)</code>        | <code>MX_SEXO_INGLES</code>       |
| <code>(?i)([hm])</code>               | <code>MX_SEXO_H_M</code>          |
| <code>(?i)(f)</code>                  | <code>MX_SEXO_F_M</code>          |
| otherwise                             | keep                              |

#### CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

#### `MX_SEXO_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `MX_SEXO`

#### CONFIGURATION

|                         |                              |
|-------------------------|------------------------------|
| lookupFile              | <code>mx-sexo-f-m.txt</code> |
| hashMethod              | <code>SHA256</code>          |
| maskedValueCase         | <code>PRESERVE_INPUT</code>  |
| inputCaseSensitive      | no                           |
| trimWhitespaceFromInput | yes                          |

|                            |     |
|----------------------------|-----|
| trimWhitespaceInLookupFile | yes |
|----------------------------|-----|

#### **MX\_SEXO\_H\_M** SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-h-m.txt` , chosen by a keyed hash.

Used by: `MX_CURP_CUERPO` , `MX_CLAVE_ELECTOR` , `MX_SEXO`

##### **CONFIGURATION**

|                            |                              |
|----------------------------|------------------------------|
| lookupFile                 | <code>mx-sexo-h-m.txt</code> |
| hashMethod                 | <code>SHA256</code>          |
| maskedValueCase            | <code>PRESERVE_INPUT</code>  |
| inputCaseSensitive         | <code>no</code>              |
| trimWhitespaceFromInput    | <code>yes</code>             |
| trimWhitespaceInLookupFile | <code>yes</code>             |

#### **MX\_SEXO\_INGLES** SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-ingles.txt` , chosen by a keyed hash.

Used by: `MX_SEXO`

##### **CONFIGURATION**

|                            |                                 |
|----------------------------|---------------------------------|
| lookupFile                 | <code>mx-sexo-ingles.txt</code> |
| hashMethod                 | <code>SHA256</code>             |
| maskedValueCase            | <code>PRESERVE_INPUT</code>     |
| inputCaseSensitive         | <code>no</code>                 |
| trimWhitespaceFromInput    | <code>yes</code>                |
| trimWhitespaceInLookupFile | <code>yes</code>                |

#### **MX\_SEXO\_MUJER\_HOMBRE** SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `MX_SEXO`

##### **CONFIGURATION**

|                            |                                       |
|----------------------------|---------------------------------------|
| lookupFile                 | <code>mx-sexo-mujer-hombre.txt</code> |
| hashMethod                 | <code>SHA256</code>                   |
| maskedValueCase            | <code>PRESERVE_INPUT</code>           |
| inputCaseSensitive         | <code>no</code>                       |
| trimWhitespaceFromInput    | <code>yes</code>                      |
| trimWhitespaceInLookupFile | <code>yes</code>                      |

#### **MX\_SEXO\_PALABRA** SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-palabra.txt` , chosen by a keyed hash.

Used by: `MX_SEXO`

##### **CONFIGURATION**

|                         |                                  |
|-------------------------|----------------------------------|
| lookupFile              | <code>mx-sexo-palabra.txt</code> |
| hashMethod              | <code>SHA256</code>              |
| maskedValueCase         | <code>PRESERVE_INPUT</code>      |
| inputCaseSensitive      | <code>no</code>                  |
| trimWhitespaceFromInput | <code>yes</code>                 |

|                                                                                                                            |                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| trimWhitespaceInLookupFile                                                                                                 | yes                                                                                 |
| <b>MX_SUPRIMIR</b> SECURE LOOKUP                                                                                           |                                                                                     |
| Replaces the value with one of the 1 values in <code>mx-sin-informacion.txt</code> , chosen by a keyed hash.               |                                                                                     |
| Used by: <code>MX_CATEGORIA_SUPRIMIDA</code>                                                                               |                                                                                     |
| <b>CONFIGURATION</b>                                                                                                       |                                                                                     |
| lookupFile                                                                                                                 | <code>mx-sin-informacion.txt</code>                                                 |
| hashMethod                                                                                                                 | SHA256                                                                              |
| maskedValueCase                                                                                                            | PRESERVE_LOOKUP_FILE                                                                |
| inputCaseSensitive                                                                                                         | no                                                                                  |
| trimWhitespaceFromInput                                                                                                    | yes                                                                                 |
| trimWhitespaceInLookupFile                                                                                                 | yes                                                                                 |
| <b>MX_TARJETA</b> REGEX DECOMPOSE                                                                                          |                                                                                     |
| Matches one pattern and gives each part of the value its own action; when none matches: keep.                              |                                                                                     |
| Used by: <code>MX_L1_TARJETA</code>                                                                                        |                                                                                     |
| <b>PATTERNS, TRIED IN ORDER</b>                                                                                            |                                                                                     |
| <code>(\d[\d\s-]{11,22}\d)</code>                                                                                          | <code>MX_TARJETA_LUHN</code>                                                        |
| otherwise                                                                                                                  | keep                                                                                |
| <b>CONFIGURATION</b>                                                                                                       |                                                                                     |
| trimInput                                                                                                                  | yes                                                                                 |
| requireMask                                                                                                                | no                                                                                  |
| <b>MX_TARJETA_LUHN</b> PAYMENT CARD                                                                                        |                                                                                     |
| Replaces the card number with another that passes the Luhn check.                                                          |                                                                                     |
| Used by: <code>MX_TARJETA</code>                                                                                           |                                                                                     |
| <b>CONFIGURATION</b>                                                                                                       |                                                                                     |
| minMaskedPositions                                                                                                         | 6                                                                                   |
| preserve                                                                                                                   | 0                                                                                   |
| <b>MX_TELEFONO</b> REGEX DECOMPOSE                                                                                         |                                                                                     |
| Tries 2 patterns in order and gives each part of the value its own action; when none matches: <code>MX_CM_ALFANUM</code> . |                                                                                     |
| Used by: <code>MX_L1_TELEFONO</code>                                                                                       |                                                                                     |
| <b>PATTERNS, TRIED IN ORDER</b>                                                                                            |                                                                                     |
| <code>(\+?52[\s-]?)?(1[\s-]?)?\((?<br/>(?:55 56 33 81)\)?[\s-]?)\(\d{4}\)([\s-]?)<br/>(\d{4})</code>                       | keep · keep · keep · <code>MX_CM_ALFANUM</code> · keep · <code>MX_CM_ALFANUM</code> |
| <code>(\+?52[\s-]?)?(1[\s-]?)?\((?<br/>[\s-]?)\(\d{3}\)([\s-]?)\(\d{4}\)</code>                                            | keep · keep · keep · <code>MX_CM_ALFANUM</code> · keep · <code>MX_CM_ALFANUM</code> |
| otherwise                                                                                                                  | <code>MX_CM_ALFANUM</code>                                                          |
| <b>CONFIGURATION</b>                                                                                                       |                                                                                     |
| trimInput                                                                                                                  | yes                                                                                 |
| requireMask                                                                                                                | no                                                                                  |

**MX\_TEXTO\_LIBRE** FREE TEXT REDACTION

Replaces the text matching 9 patterns with [DATO] , and the 1,436 terms of mx-texto-nombres.txt with [NOMBRE] .

Used by: MX\_L1\_TEXTO\_LIBRE , MX\_L3\_SALUD\_TEXTO\_CLINICO

PATTERNS, TRIED IN ORDER

|                                                                  |
|------------------------------------------------------------------|
| [A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d                             |
| [A-ZÑ&]{3,4}\d{6}[A-Z0-9]{2}[0-9A]                               |
| [A-Z]{6}\d{8}[HM]\d{3}                                           |
| [\w.+\\-]+@[\\w\\-]+(\\. [\\w\\-]+)+                             |
| (?<!\d)(\+?52)?1?\d{10}(?!\\d)                                   |
| (?<!\d)\d{11}(?!\\d)                                             |
| (?<!\d)\d{13,19}(?!\\d)                                          |
| (?<![A-Za-z])([A-HJ-NPR-Z]{3}-?\d{3}-?[A-HJ-NPR-Z](?! [A-Za-z])) |
| (?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\\d)                              |

CONFIGURATION

|                       |                      |
|-----------------------|----------------------|
| regExRedactValue      | [DATO]               |
| lookupFile            | mx-texto-nombres.txt |
| lookupFileRedactValue | [NOMBRE]             |
| isDenyList            | yes                  |

**MX\_VIVIENDA** REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX\_VIVIENDA\_LISTA .

Used by: MX\_FIN\_VIVIENDA

PATTERNS, TRIED IN ORDER

|                                   |                   |
|-----------------------------------|-------------------|
| (?i)(s[íí] no true false [sny01]) | MX_BANDERA        |
| (\d{1,6})                         | MX_CM_ALFANUM     |
| otherwise                         | MX_VIVIENDA_LISTA |

CONFIGURATION

|             |     |
|-------------|-----|
| trimInput   | yes |
| requireMask | no  |

**MX\_VIVIENDA\_LISTA** SECURE LOOKUP

Replaces the value with one of the 6 values in mx-vivienda.txt , chosen by a keyed hash.

Used by: MX\_VIVIENDA

CONFIGURATION

|                            |                 |
|----------------------------|-----------------|
| lookupFile                 | mx-vivienda.txt |
| hashMethod                 | SHA256          |
| maskedValueCase            | PRESERVE_INPUT  |
| inputCaseSensitive         | no              |
| trimWhitespaceFromInput    | yes             |
| trimWhitespaceInLookupFile | yes             |

## APPENDIX B

# Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

| FILE                                | LINES | USED BY                   | FIRST LINES                                                                      |
|-------------------------------------|-------|---------------------------|----------------------------------------------------------------------------------|
| mx-afores.txt                       | 11    | MX_AFORE_LISTA            | Afore Azteca · Afore Banamex · Afore Coppel · Afore Inbursa                      |
| mx-antecedentes.txt                 | 3     | MX_ANTECEDENTES_LISTA     | Sin antecedentes penales · Con antecedentes penales · Sin información            |
| mx-apellidos.txt                    | 337   | MX_APELLIDO               | Hernández · García · Martínez · López                                            |
| mx-bandera-0-1.txt                  | 2     | MX_BANDERA_0_1            | 0 · 1                                                                            |
| mx-bandera-s-n.txt                  | 2     | MX_BANDERA_S_N            | S · N                                                                            |
| mx-bandera-si-no.txt                | 2     | MX_BANDERA_SI_NO          | Sí · No                                                                          |
| mx-bandera-true-false.txt           | 2     | MX_BANDERA_TRUE_FALSE     | true · false                                                                     |
| mx-bandera-y-n.txt                  | 2     | MX_BANDERA_Y_N            | Y · N                                                                            |
| mx-cie10-decimal.txt                | 33    | MX_CIE10_DECIMAL          | E11.9 · E78.5 · J45.9 · J06.9                                                    |
| mx-cie10.txt                        | 37    | MX_CIE10                  | I10 · E11 · E78 · J45                                                            |
| mx-clave-municipio-generalizada.txt | 2,758 | MX_CLAVE_MUNICIPIO        | 01001,01001 · 1001,1001 · 01002,01002 · 1002,1002                                |
| mx-colonias.txt                     | 60    | MX_COLONIA                | Centro · Del Valle · San Miguel · Santa María                                    |
| mx-credito-vivienda.txt             | 6     | MX_CREDITO_VIVIENDA_LISTA | Crédito Infonavit · Crédito Fovissste · Cofinavit · Crédito hipotecario bancario |
| mx-curp-dv-1.txt                    | 676   | MX_CURP_DV_T1             | AA,AA0 · AB,AB7 · AC,AC4 · AD,AD1                                                |
| mx-curp-dv-2.txt                    | 6,760 | MX_CURP_DV_T2             | OAA,AA0 · OAB,AB5 · OAC,AC0 · OAD,AD5                                            |
| mx-curp-dv-3.txt                    | 1,000 | MX_CURP_DV_T3             | 000,000 · 001,013 · 002,026 · 003,039                                            |
| mx-curp-dv-4.txt                    | 1,000 | MX_CURP_DV_T4             | 000,000 · 001,011 · 002,022 · 003,033                                            |
| mx-curp-dv-5.txt                    | 1,000 | MX_CURP_DV_T5             | 000,000 · 001,019 · 002,028 · 003,037                                            |

| FILE                             | LINES  | USED BY                                               | FIRST LINES                                                                                                           |
|----------------------------------|--------|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| mx-curp-dv-6.txt                 | 20,280 | MX_CURP_DV_T6                                         | 0HAA,HAA6 · 0HAB,HAB2 · 0HAC,HAC8 · 0HAD,HAD4                                                                         |
| mx-curp-dv-7.txt                 | 6,760  | MX_CURP_DV_T7                                         | 0AA,AA0 · 0AB,AB4 · 0AC,AC8 · 0AD,AD2                                                                                 |
| mx-curp-dv-8.txt                 | 9,360  | MX_CURP_DV_T8                                         | 0A00,A00 · 0A10,A18 · 0A20,A26 · 0A30,A34                                                                             |
| mx-decil-alto.txt                | 5      | MX_DECIL_ALTO                                         | 6 · 7 · 8 · 9                                                                                                         |
| mx-decil.txt                     | 10     | MX_DECIL                                              | 1 · 2 · 3 · 4                                                                                                         |
| mx-detectar-afores.txt           | 27     | MX_FIN_AFORE – List                                   | Afore Azteca · Afore Banamex · Afore Coppel · Afore Inbursa                                                           |
| mx-detectar-apellidos.txt        | 423    | MX_L1_APELLIDO – List<br>MX_L1_NOMBRE_COMPLETO – List | Hernández · Hernandez · García · Garcia                                                                               |
| mx-detectar-bandera.txt          | 8      | MX_L3_ETNIA – List                                    | s · n · sí · si                                                                                                       |
| mx-detectar-clave-municipio.txt  | 2,758  | MX_L2_CLAVE_MUNICIPIO – List                          | 01001 · 1001 · 01002 · 1002                                                                                           |
| mx-detectar-credito-vivienda.txt | 20     | MX_FIN_CREDITO_VIVIENDA – List                        | Crédito Infonavit · Credito Infonavit · Crédito Fovissste · Credito Fovissste                                         |
| mx-detectar-discapacidad.txt     | 26     | MX_L3_SALUD_DISCAPACIDAD – List                       | Caminar, subir o bajar · Ver, aun usando lentes · Oír, aun usando aparato auditivo · Oír, aun usando aparato auditivo |
| mx-detectar-escolaridad.txt      | 27     | MX_L2_ESCOLARIDAD – List                              | Sin escolaridad · Preescolar · Primaria incompleta · Primaria completa                                                |
| mx-detectar-estado-civil.txt     | 19     | MX_L2_ESTADO_CIVIL – List                             | soltero · soltera · casado · casada                                                                                   |
| mx-detectar-grupo-sanguineo.txt  | 26     | MX_L3_SALUD_GRUPO_SANGUINEO – List                    | A+ · A- · B+ · B-                                                                                                     |
| mx-detectar-identidad-genero.txt | 19     | MX_L3_IDENTIDAD_GENERO – List                         | Mujer · Hombre · Mujer trans · Hombre trans                                                                           |
| mx-detectar-lenguas.txt          | 57     | MX_L3 LENGUA_INDIGENA – List                          | Náhuatl · Nahuatl · Maya · Tseltal                                                                                    |
| mx-detectar-medicamentos.txt     | 57     | MX_L3_SALUD_MEDICAMENTO – List                        | Paracetamol · Ibuprofeno · Naproxeno · Metamizol                                                                      |
| mx-detectar-municipios.txt       | 3,090  | MX_L2_MUNICIPIO – List                                | Aguascalientes · Asientos · Calvillo · Cosío                                                                          |

| FILE                                | LINES | USED BY                                             | FIRST LINES                                                                                                                                                                   |
|-------------------------------------|-------|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mx-detectar-nacionalidades.txt      | 64    | MX_L2_NACIONALIDAD – List                           | Mexicana · Estadounidense · Guatemalteca · Hondureña                                                                                                                          |
| mx-detectar-nombres.txt             | 301   | MX_L1_NOMBRE – List<br>MX_L1_NOMBRE_COMPLETO – List | María · Maria · José · Jose                                                                                                                                                   |
| mx-detectar-nse.txt                 | 13    | MX_FIN_NIVEL_SOCIOECONOMICO – List                  | a/b · ab · c+ · c                                                                                                                                                             |
| mx-detectar-opiniones-politicas.txt | 14    | MX_L3_OPINION_POLITICA – List                       | Izquierda · Centro izquierda · Centro · Centro derecha                                                                                                                        |
| mx-detectar-partidos.txt            | 35    | MX_L3_AFILIACION_POLITICA – List                    | Morena · Partido Acción Nacional · Partido Accion Nacional · Partido Revolucionario Institucional                                                                             |
| mx-detectar-preferencia-sexual.txt  | 17    | MX_L3_PREFERENCIA_SEXUAL – List                     | Heterosexual · Homosexual · Lesbiana · Gay                                                                                                                                    |
| mx-detectar-programas.txt           | 37    | MX_FIN_PROGRAMA_SOCIAL – List                       | Pensión para el Bienestar de las Personas Adultas Mayores · Pension para el Bienestar de las Personas Adultas Mayores · Pensión Mujeres Bienestar · Pension Mujeres Bienestar |
| mx-detectar-pueblos.txt             | 103   | MX_L3_ETNIA – List                                  | Nahua · Maya · Zapoteco · Mixteco                                                                                                                                             |
| mx-detectar-religiones.txt          | 56    | MX_L3_RELIGION – List                               | Católica · Catolica · Protestante o cristiana evangélica · Protestante o cristiana evangelica                                                                                 |
| mx-detectar-seguridad-social.txt    | 22    | MX_FIN_SEGURIDAD_SOCIAL – List                      | IMSS · ISSSTE · ISSSTE estatal · IMSS-Bienestar                                                                                                                               |
| mx-detectar-sexo.txt                | 12    | MX_L2_SEXO – List                                   | h · m · f · x                                                                                                                                                                 |
| mx-detectar-sindicatos.txt          | 16    | MX_L3_AFILIACION_SINDICAL – List                    | SNTE · CNTE · STPRM · SUTERM                                                                                                                                                  |
| mx-detectar-vivienda.txt            | 15    | MX_FIN_VIVIENDA – List                              | Propia · Propia en proceso de pago · Rentada o alquilada · Prestada                                                                                                           |
| mx-diagnosticos.txt                 | 30    | MX_DIAGNOSTICO_TEXT0                                | Hipertensión arterial sistémica · Diabetes mellitus tipo 2 · Asma · Lumbalgia                                                                                                 |
| mx-direcciones.txt                  | 3,000 | MX_DIRECCION                                        | Calle Belisario Domínguez 681 · Calle Coahuila 741 · Calle Marte 348 Int. 17 · Xicoténcatl 1448                                                                               |
| mx-discapacidad.txt                 | 8     | MX_DISCAPACIDAD_LISTA                               | Caminar, subir o bajar · Ver, aun usando lentes · Oír, aun usando aparato auditivo · Hablar o comunicarse                                                                     |
| mx-empleadores.txt                  | 25    | MX_EMPLEADOR                                        | Comercializadora del Bajío S.A. de C.V. · Servicios Integrales del Norte S.A. de C.V. · Constructora Sierra Madre S.A. de C.V. · Transportes Golfo Pacífico S.A. de C.V.      |
| mx-entidad-curp.txt                 | 33    | MX_ENTIDAD_CURP                                     | AS · BC · BS · CC                                                                                                                                                             |

| FILE                          | LINES | USED BY                   | FIRST LINES                                                                                                                                             |
|-------------------------------|-------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| mx-entidad-numero.txt         | 32    | MX_ENTIDAD_NUMERO         | 01 · 02 · 03 · 04                                                                                                                                       |
| mx-escolaridad.txt            | 12    | MX_ESCOLARIDAD            | Sin escolaridad · Preescolar · Primaria incompleta · Primaria completa                                                                                  |
| mx-escuelas.txt               | 15    | MX_ESCUELA                | Escuela Primaria Miguel Hidalgo · Escuela Primaria Rural Emiliano Zapata · Escuela Secundaria Técnica No. 14 · Telesecundaria Josefa Ortiz de Domínguez |
| mx-estado-civil.txt           | 6     | MX_ESTADO_CIVIL           | Soltero · Casado · Unión libre · Separado                                                                                                               |
| mx-estado-crediticio.txt      | 10    | MX_ESTADO_CREDITICIO      | Al corriente · Atraso de 1 a 29 días · Atraso de 30 a 59 días · Atraso de 60 a 89 días                                                                  |
| mx-grupo-sanguineo.txt        | 8     | MX_GRUPO_SANGUINEO        | A+ · A- · B+ · B-                                                                                                                                       |
| mx-identidad-genero.txt       | 8     | MX_IDENTIDAD_GENERO_LISTA | Mujer · Hombre · Mujer trans · Hombre trans                                                                                                             |
| mx-lenguas.txt                | 27    | MX LENGUA INDIGENA_LISTA  | Náhuatl · Maya · Tseltal · Tsotsil                                                                                                                      |
| mx-localidades.txt            | 229   | MX_LOCALIDAD              | Aguascalientes · Jesús María · Ensenada · Mexicali                                                                                                      |
| mx-medicamentos.txt           | 26    | MX_MEDICAMENTO_LISTA      | Paracetamol · Ibuprofeno · Naproxeno · Metamizol                                                                                                        |
| mx-meses-30-dias.txt          | 11    | MX_MES_30_DIAS            | 01 · 03 · 04 · 05                                                                                                                                       |
| mx-meses-31-dias.txt          | 7     | MX_MES_31_DIAS            | 01 · 03 · 05 · 07                                                                                                                                       |
| mx-mop.txt                    | 9     | MX_MOP                    | 01 · 02 · 03 · 04                                                                                                                                       |
| mx-municipio-generalizado.txt | 6,547 | MX_MUNICIPIO              | Aguascalientes Aguascalientes · AGUASCALIENTES AGUASCALIENTES · Asientos Asientos · ASIENTOS ASIENTOS                                                   |
| mx-nacionalidades.txt         | 20    | MX_NACIONALIDAD           | Mexicana · Estadounidense · Guatemalteca · Hondureña                                                                                                    |
| mx-nombres.txt                | 255   | MX_NOMBRE_PILA            | María · José · Juan · Luis                                                                                                                              |
| mx-nse.txt                    | 7     | MX_NSE                    | A/B · C+ · C · C-                                                                                                                                       |
| mx-ocupaciones.txt            | 40    | MX_OCUPACION              | Empleado administrativo · Comerciante · Vendedor · Obrero                                                                                               |
| mx-opiniones-politicas.txt    | 7     | MX_OPINION_POLITICA_LISTA | Izquierda · Centro izquierda · Centro · Centro derecha                                                                                                  |
| mx-partidos.txt               | 10    | MX_PARTIDO_POLITICO_LISTA | Morena · Partido Acción Nacional · Partido Revolucionario Institucional · Partido del Trabajo                                                           |

| FILE                         | LINES  | USED BY                     | FIRST LINES                                                                                                                                                                     |
|------------------------------|--------|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mx-preferencia-sexual.txt    | 9      | MX_PREFERENCIA_SEXUAL_LISTA | Heterosexual · Homosexual · Lesbiana · Gay                                                                                                                                      |
| mx-programas-sociales.txt    | 13     | MX_PROGRAMA_SOCIAL_LISTA    | Pensión para el Bienestar de las Personas Adultas Mayores · Pensión Mujeres Bienestar · Pensión para el Bienestar de las Personas con Discapacidad · Beca Universal Rita Cetina |
| mx-pueblos.txt               | 31     | MX_PUEBLO_LISTA             | Nahua · Maya · Zapoteco · Mixteco                                                                                                                                               |
| mx-quintil.txt               | 5      | MX_QUINTIL                  | 1 · 2 · 3 · 4                                                                                                                                                                   |
| mx-regimen-fiscal-clave.txt  | 13     | MX_REGIMEN_FISCAL_CLAVE     | 605 · 606 · 607 · 608                                                                                                                                                           |
| mx-regimen-fiscal-nombre.txt | 13     | MX_REGIMEN_FISCAL_NOMBRE    | Sueldos y Salarios e Ingresos Asimilados a Salarios · Arrendamiento · Régimen de Enajenación o Adquisición de Bienes · Demás ingresos                                           |
| mx-religiones.txt            | 13     | MX_RELIGION_LISTA           | Católica · Protestante o cristiana evangélica · Pentecostal · Testigo de Jehová                                                                                                 |
| mx-rfc-dv-1.txt              | 812    | MX_RFC_DV_T1                | AA,AA8 · AB,AB9 · AC,ACA · AD,AD0                                                                                                                                               |
| mx-rfc-dv-2.txt              | 8,624  | MX_RFC_DV_T2                | OAA,AA1 · OAB,AB0 · OAC,ACA · OAD,AD9                                                                                                                                           |
| mx-rfc-dv-3.txt              | 1,100  | MX_RFC_DV_T3                | 000,000 · 001,018 · 002,025 · 003,032                                                                                                                                           |
| mx-rfc-dv-4.txt              | 1,100  | MX_RFC_DV_T4                | 000,000 · 001,016 · 002,021 · 003,037                                                                                                                                           |
| mx-rfc-dv-5.txt              | 1,100  | MX_RFC_DV_T5                | 000,000 · 001,014 · 002,028 · 003,031                                                                                                                                           |
| mx-rfc-dv-6.txt              | 14,256 | MX_RFC_DV_T6                | 0000,000 · 0010,019 · 0020,027 · 0030,035                                                                                                                                       |
| mx-rfc-relleno.txt           | 38     | MX_RFC_RELLENO_TABLA        | 0,0 · 1,1 · 2,2 · 3,3                                                                                                                                                           |
| mx-seguridad-social.txt      | 10     | MX_SEGURIDAD_SOCIAL_LISTA   | IMSS · ISSSTE · ISSSTE estatal · IMSS-Bienestar                                                                                                                                 |
| mx-sexo-f-m.txt              | 2      | MX_SEXO_F_M                 | F · M                                                                                                                                                                           |
| mx-sexo-h-m.txt              | 2      | MX_SEXO_H_M                 | H · M                                                                                                                                                                           |
| mx-sexo-ingles.txt           | 2      | MX_SEXO_INGLES              | Female · Male                                                                                                                                                                   |
| mx-sexo-mujer-hombre.txt     | 2      | MX_SEXO_MUJER_HOMBRE        | Mujer · Hombre                                                                                                                                                                  |
| mx-sexo-palabra.txt          | 2      | MX_SEXO_PALABRA             | Femenino · Masculino                                                                                                                                                            |

| FILE                   | LINES | USED BY           | FIRST LINES                                                         |
|------------------------|-------|-------------------|---------------------------------------------------------------------|
| mx-sin-informacion.txt | 1     | MX_SUPRIMIR       | Sin información                                                     |
| mx-texto-nombres.txt   | 1,436 | MX_TEXTO_LIBRE    | María · MARÍA · Maria · MARIA                                       |
| mx-vivienda.txt        | 6     | MX_VIVIENDA_LISTA | Propia · Propia en proceso de pago · Rentada o alquilada · Prestada |

## Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

**E1** producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector cliente cte cli paciente pac trabajador trab empleado colaborador alumno estudiante afiliado asegurado derechohabiente beneficiario benef titular madre padre tutor conyuge pareja medico doctor profesional responsable contacto emergencia aval obligado coacreditado deudor acreditado remitente destinatario receptor firmante testigo representante apoderado propietario arrendatario contratante victima denunciante imputado socio donante heredero persona pers conductor chofer vendedor ejecutivo agente solicitante usuario\_?final ciudadano elector votante contribuyente jefe\_(de\_)?familia hijo hija familiar dependiente completos? y\_?apellidos? apellidos?

**E2** producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector cliente cte cli paciente pac trabajador trab empleado colaborador alumno estudiante afiliado asegurado derechohabiente beneficiario benef titular madre padre tutor conyuge pareja medico doctor profesional responsable contacto emergencia aval obligado coacreditado deudor acreditado remitente destinatario receptor firmante testigo representante apoderado propietario arrendatario contratante victima denunciante imputado socio donante heredero persona pers conductor chofer vendedor ejecutivo agente solicitante usuario\_?final ciudadano elector votante contribuyente jefe\_(de\_)?familia hijo hija familiar dependiente completo compl full y\_?apellidos? apellidos?

- 
- E3** producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector completo
- 
- E4** producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector
- 
- E5** ip mac web url correo mail electronica email
- 
- E6** producto prod serv prodserv articulo sucursal interna tipo registro primaria foranea elector electoral unica bancaria interbancaria municipio mun entidad ent localidad loc escuela centro cct clues sat producto servicio unidad plaza banco pais moneda regimen uso cfdi postal lada zona ageb area
- 
- E7** imss issste sat federal estatal regional administrativa
- 
- E8** fijo variable monto adicional servicio tarifa valor cuenta extra automatico recurrente domiciliado
- 
- E9** medicos patologicos personales\_?patologicos heredofamiliares gineco obstetricos familiares clinicos academicos laborales crediticios comerciales generales
-

APPENDIX D

# Profile set and classifiers

The profile set `MX – LFPDPPP – v2` runs these 153 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, datos sensibles (art. 2, VI) y datos financieros y patrimoniales (art. 7) de la LFPDPPP 2025.

| CLASSIFIER                         | KIND         | DOMAIN                      |
|------------------------------------|--------------|-----------------------------|
| MX_L1_CURP – Path                  | COLUMN NAME  | MX_L1_CURP                  |
| MX_L1_CURP – Type                  | DATA TYPE    | MX_L1_CURP                  |
| MX_L1_CURP – Regex                 | VALUE FORMAT | MX_L1_CURP                  |
| MX_L1_RFC – Path                   | COLUMN NAME  | MX_L1_RFC                   |
| MX_L1_RFC – Type                   | DATA TYPE    | MX_L1_RFC                   |
| MX_L1_RFC – Regex                  | VALUE FORMAT | MX_L1_RFC                   |
| MX_L1_NSS – Path                   | COLUMN NAME  | MX_L1_NSS                   |
| MX_L1_NSS – Type                   | DATA TYPE    | MX_L1_NSS                   |
| MX_L1_NSS – Regex                  | VALUE FORMAT | MX_L1_NSS                   |
| MX_L1_CLAVE_ELECTOR – Path         | COLUMN NAME  | MX_L1_CLAVE_ELECTOR         |
| MX_L1_CLAVE_ELECTOR – Type         | DATA TYPE    | MX_L1_CLAVE_ELECTOR         |
| MX_L1_CLAVE_ELECTOR – Regex        | VALUE FORMAT | MX_L1_CLAVE_ELECTOR         |
| MX_L1_CREDENCIAL_INE – Path        | COLUMN NAME  | MX_L1_CREDENCIAL_INE        |
| MX_L1_CREDENCIAL_INE – Regex       | VALUE FORMAT | MX_L1_CREDENCIAL_INE        |
| MX_L1_NOMBRE – Path                | COLUMN NAME  | MX_L1_NOMBRE                |
| MX_L1_NOMBRE – List                | KNOWN VALUES | MX_L1_NOMBRE                |
| MX_L1_APELLIDO – Path              | COLUMN NAME  | MX_L1_APELLIDO              |
| MX_L1_APELLIDO – List              | KNOWN VALUES | MX_L1_APELLIDO              |
| MX_L1_NOMBRE_COMPLETO – Path       | COLUMN NAME  | MX_L1_NOMBRE_COMPLETO       |
| MX_L1_NOMBRE_COMPLETO – List       | KNOWN VALUES | MX_L1_NOMBRE_COMPLETO       |
| MX_L1_EMAIL – Path                 | COLUMN NAME  | MX_L1_EMAIL                 |
| MX_L1_EMAIL – Type                 | DATA TYPE    | MX_L1_EMAIL                 |
| MX_L1_EMAIL – Regex                | VALUE FORMAT | MX_L1_EMAIL                 |
| MX_L1_TELEFONO – Path              | COLUMN NAME  | MX_L1_TELEFONO              |
| MX_L1_TELEFONO – Regex             | VALUE FORMAT | MX_L1_TELEFONO              |
| MX_L1_DIRECCION – Path             | COLUMN NAME  | MX_L1_DIRECCION             |
| MX_L1_DIRECCION – Type             | DATA TYPE    | MX_L1_DIRECCION             |
| MX_L1_DIRECCION – Regex            | VALUE FORMAT | MX_L1_DIRECCION             |
| MX_L1_DIRECCION_COMPLEMENTO – Path | COLUMN NAME  | MX_L1_DIRECCION_COMPLEMENTO |
| MX_L1_CLABE – Path                 | COLUMN NAME  | MX_L1_CLABE                 |
| MX_L1_CLABE – Type                 | DATA TYPE    | MX_L1_CLABE                 |

| CLASSIFIER                        | KIND         | DOMAIN                     |
|-----------------------------------|--------------|----------------------------|
| MX_L1_CLABE – Regex               | VALUE FORMAT | MX_L1_CLABE                |
| MX_L1_CUENTA_BANCARIA – Path      | COLUMN NAME  | MX_L1_CUENTA_BANCARIA      |
| MX_L1_TARJETA – Path              | COLUMN NAME  | MX_L1_TARJETA              |
| MX_L1_TARJETA – Regex             | VALUE FORMAT | MX_L1_TARJETA              |
| MX_L1_PASAPORTE – Path            | COLUMN NAME  | MX_L1_PASAPORTE            |
| MX_L1_PASAPORTE – Regex           | VALUE FORMAT | MX_L1_PASAPORTE            |
| MX_L1_DOCUMENTO_MIGRATORIO – Path | COLUMN NAME  | MX_L1_DOCUMENTO_MIGRATORIO |
| MX_L1_CEDULA_PROFESIONAL – Path   | COLUMN NAME  | MX_L1_CEDULA_PROFESIONAL   |
| MX_L1_CEDULA_PROFESIONAL – Regex  | VALUE FORMAT | MX_L1_CEDULA_PROFESIONAL   |
| MX_L1_LICENCIA_CONducIR – Path    | COLUMN NAME  | MX_L1_LICENCIA_CONducIR    |
| MX_L1_EFIRMA – Path               | COLUMN NAME  | MX_L1_EFIRMA               |
| MX_L1_EFIRMA – Regex              | VALUE FORMAT | MX_L1_EFIRMA               |
| MX_L1_IP – Path                   | COLUMN NAME  | MX_L1_IP                   |
| MX_L1_IP – Regex                  | VALUE FORMAT | MX_L1_IP                   |
| MX_L1_DISPOSITIVO – Path          | COLUMN NAME  | MX_L1_DISPOSITIVO          |
| MX_L1_DISPOSITIVO – Regex         | VALUE FORMAT | MX_L1_DISPOSITIVO          |
| MX_L1_PLACA – Path                | COLUMN NAME  | MX_L1_PLACA                |
| MX_L1_PLACA – Regex               | VALUE FORMAT | MX_L1_PLACA                |
| MX_L1_NIV – Path                  | COLUMN NAME  | MX_L1_NIV                  |
| MX_L1_NIV – Regex                 | VALUE FORMAT | MX_L1_NIV                  |
| MX_L1_NUMERO_CONTRATO – Path      | COLUMN NAME  | MX_L1_NUMERO_CONTRATO      |
| MX_L1_USUARIO_RRSS – Path         | COLUMN NAME  | MX_L1_USUARIO_RRSS         |
| MX_L1_CREDENCIAL – Path           | COLUMN NAME  | MX_L1_CREDENCIAL           |
| MX_L1_GEOLOCALIZACION – Path      | COLUMN NAME  | MX_L1_GEOLOCALIZACION      |
| MX_L1_GEOLOCALIZACION – Regex     | VALUE FORMAT | MX_L1_GEOLOCALIZACION      |
| MX_L1_TEXTO_LIBRE – Path          | COLUMN NAME  | MX_L1_TEXTO_LIBRE          |
| MX_L1_TEXTO_LIBRE – Type          | DATA TYPE    | MX_L1_TEXTO_LIBRE          |
| MX_L1_TEXTO_LIBRE – Regex         | VALUE FORMAT | MX_L1_TEXTO_LIBRE          |
| MX_L2_FECHA_NACIMIENTO – Path     | COLUMN NAME  | MX_L2_FECHA_NACIMIENTO     |
| MX_L2_FECHA_NACIMIENTO – Type     | DATA TYPE    | MX_L2_FECHA_NACIMIENTO     |
| MX_L2_ANIO_NACIMIENTO – Path      | COLUMN NAME  | MX_L2_ANIO_NACIMIENTO      |
| MX_L2_ANIO_NACIMIENTO – Type      | DATA TYPE    | MX_L2_ANIO_NACIMIENTO      |
| MX_L2_EDAD – Path                 | COLUMN NAME  | MX_L2_EDAD                 |
| MX_L2_EDAD – Type                 | DATA TYPE    | MX_L2_EDAD                 |
| MX_L2_FECHA_EVENTO – Path         | COLUMN NAME  | MX_L2_FECHA_EVENTO         |
| MX_L2_FECHA_EVENTO – Type         | DATA TYPE    | MX_L2_FECHA_EVENTO         |
| MX_L2_SEX0 – Path                 | COLUMN NAME  | MX_L2_SEX0                 |

| CLASSIFIER                          | KIND         | DOMAIN                       |
|-------------------------------------|--------------|------------------------------|
| MX_L2_SEX0 - List                   | KNOWN VALUES | MX_L2_SEX0                   |
| MX_L2_MUNICIPIO - Path              | COLUMN NAME  | MX_L2_MUNICIPIO              |
| MX_L2_MUNICIPIO - List              | KNOWN VALUES | MX_L2_MUNICIPIO              |
| MX_L2_CLAVE_MUNICIPIO - Path        | COLUMN NAME  | MX_L2_CLAVE_MUNICIPIO        |
| MX_L2_CLAVE_MUNICIPIO - Type        | DATA TYPE    | MX_L2_CLAVE_MUNICIPIO        |
| MX_L2_CLAVE_MUNICIPIO - List        | KNOWN VALUES | MX_L2_CLAVE_MUNICIPIO        |
| MX_L2_LOCALIDAD - Path              | COLUMN NAME  | MX_L2_LOCALIDAD              |
| MX_L2_COLONIA - Path                | COLUMN NAME  | MX_L2_COLONIA                |
| MX_L2_CODIGO_POSTAL - Path          | COLUMN NAME  | MX_L2_CODIGO_POSTAL          |
| MX_L2_CODIGO_POSTAL - Regex         | VALUE FORMAT | MX_L2_CODIGO_POSTAL          |
| MX_L2_NACIONALIDAD - Path           | COLUMN NAME  | MX_L2_NACIONALIDAD           |
| MX_L2_NACIONALIDAD - List           | KNOWN VALUES | MX_L2_NACIONALIDAD           |
| MX_L2_ESTADO_CIVIL - Path           | COLUMN NAME  | MX_L2_ESTADO_CIVIL           |
| MX_L2_ESTADO_CIVIL - List           | KNOWN VALUES | MX_L2_ESTADO_CIVIL           |
| MX_L2_OCUPACION - Path              | COLUMN NAME  | MX_L2_OCUPACION              |
| MX_L2_EMPLEADOR - Path              | COLUMN NAME  | MX_L2_EMPLEADOR              |
| MX_L2_ESCOLARIDAD - Path            | COLUMN NAME  | MX_L2_ESCOLARIDAD            |
| MX_L2_ESCOLARIDAD - List            | KNOWN VALUES | MX_L2_ESCOLARIDAD            |
| MX_L2_ESCUELA - Path                | COLUMN NAME  | MX_L2_ESCUELA                |
| MX_L2_CCT - Path                    | COLUMN NAME  | MX_L2_CCT                    |
| MX_L2_CCT - Regex                   | VALUE FORMAT | MX_L2_CCT                    |
| MX_L2_DEPENDIENTES - Path           | COLUMN NAME  | MX_L2_DEPENDIENTES           |
| MX_L2_DEPENDIENTES - Type           | DATA TYPE    | MX_L2_DEPENDIENTES           |
| MX_L3_ETNIA - Path                  | COLUMN NAME  | MX_L3_ETNIA                  |
| MX_L3_ETNIA - List                  | KNOWN VALUES | MX_L3_ETNIA                  |
| MX_L3 LENGUA_INDIGENA - Path        | COLUMN NAME  | MX_L3 LENGUA_INDIGENA        |
| MX_L3 LENGUA_INDIGENA - List        | KNOWN VALUES | MX_L3 LENGUA_INDIGENA        |
| MX_L3_SALUD_DIAGNOSTICO - Path      | COLUMN NAME  | MX_L3_SALUD_DIAGNOSTICO      |
| MX_L3_SALUD_DIAGNOSTICO - Regex     | VALUE FORMAT | MX_L3_SALUD_DIAGNOSTICO      |
| MX_L3_SALUD_MEDICAMENTO - Path      | COLUMN NAME  | MX_L3_SALUD_MEDICAMENTO      |
| MX_L3_SALUD_MEDICAMENTO - List      | KNOWN VALUES | MX_L3_SALUD_MEDICAMENTO      |
| MX_L3_SALUD_IDENTIFICADOR - Path    | COLUMN NAME  | MX_L3_SALUD_IDENTIFICADOR    |
| MX_L3_SALUD_TEXTO_CLINICO - Path    | COLUMN NAME  | MX_L3_SALUD_TEXTO_CLINICO    |
| MX_L3_SALUD_TEXTO_CLINICO - Type    | DATA TYPE    | MX_L3_SALUD_TEXTO_CLINICO    |
| MX_L3_SALUD_RESULTADO_EXAMEN - Path | COLUMN NAME  | MX_L3_SALUD_RESULTADO_EXAMEN |
| MX_L3_SALUD_GRUPO_SANGUINEO - Path  | COLUMN NAME  | MX_L3_SALUD_GRUPO_SANGUINEO  |
| MX_L3_SALUD_GRUPO_SANGUINEO - List  | KNOWN VALUES | MX_L3_SALUD_GRUPO_SANGUINEO  |

| CLASSIFIER                             | KIND         | DOMAIN                          |
|----------------------------------------|--------------|---------------------------------|
| MX_L3_SALUD_DISCAPACIDAD – Path        | COLUMN NAME  | MX_L3_SALUD_DISCAPACIDAD        |
| MX_L3_SALUD_DISCAPACIDAD – List        | KNOWN VALUES | MX_L3_SALUD_DISCAPACIDAD        |
| MX_L3_SALUD_SEXUAL_REPRODUCTIVA – Path | COLUMN NAME  | MX_L3_SALUD_SEXUAL_REPRODUCTIVA |
| MX_L3_SALUD_MENTAL_ADICCIONES – Path   | COLUMN NAME  | MX_L3_SALUD_MENTAL_ADICCIONES   |
| MX_L3_BIOMETRICO – Path                | COLUMN NAME  | MX_L3_BIOMETRICO                |
| MX_L3_BIOMETRICO – Type                | DATA TYPE    | MX_L3_BIOMETRICO                |
| MX_L3_INFORMACION_GENETICA – Path      | COLUMN NAME  | MX_L3_INFORMACION_GENETICA      |
| MX_L3_PREFERENCIA_SEXUAL – Path        | COLUMN NAME  | MX_L3_PREFERENCIA_SEXUAL        |
| MX_L3_PREFERENCIA_SEXUAL – List        | KNOWN VALUES | MX_L3_PREFERENCIA_SEXUAL        |
| MX_L3_IDENTIDAD_GENERO – Path          | COLUMN NAME  | MX_L3_IDENTIDAD_GENERO          |
| MX_L3_IDENTIDAD_GENERO – List          | KNOWN VALUES | MX_L3_IDENTIDAD_GENERO          |
| MX_L3_VIDA_SEXUAL – Path               | COLUMN NAME  | MX_L3_VIDA_SEXUAL               |
| MX_L3_RELIGION – Path                  | COLUMN NAME  | MX_L3_RELIGION                  |
| MX_L3_RELIGION – List                  | KNOWN VALUES | MX_L3_RELIGION                  |
| MX_L3_CREENCIA_FILOSOFICA_MORAL – Path | COLUMN NAME  | MX_L3_CREENCIA_FILOSOFICA_MORAL |
| MX_L3_OPINION_POLITICA – Path          | COLUMN NAME  | MX_L3_OPINION_POLITICA          |
| MX_L3_OPINION_POLITICA – List          | KNOWN VALUES | MX_L3_OPINION_POLITICA          |
| MX_L3_AFILIACION_POLITICA – Path       | COLUMN NAME  | MX_L3_AFILIACION_POLITICA       |
| MX_L3_AFILIACION_POLITICA – List       | KNOWN VALUES | MX_L3_AFILIACION_POLITICA       |
| MX_L3_AFILIACION_SINDICAL – Path       | COLUMN NAME  | MX_L3_AFILIACION_SINDICAL       |
| MX_L3_AFILIACION_SINDICAL – List       | KNOWN VALUES | MX_L3_AFILIACION_SINDICAL       |
| MX_FIN_BURO_CREDITO – Path             | COLUMN NAME  | MX_FIN_BURO_CREDITO             |
| MX_FIN_MONTO_DEUDA – Path              | COLUMN NAME  | MX_FIN_MONTO_DEUDA              |
| MX_FIN_MONTO_DEUDA – Type              | DATA TYPE    | MX_FIN_MONTO_DEUDA              |
| MX_FIN_INGRESO_MENSUAL – Path          | COLUMN NAME  | MX_FIN_INGRESO_MENSUAL          |
| MX_FIN_INGRESO_MENSUAL – Type          | DATA TYPE    | MX_FIN_INGRESO_MENSUAL          |
| MX_FIN_SALARIO_DIARIO – Path           | COLUMN NAME  | MX_FIN_SALARIO_DIARIO           |
| MX_FIN_SALARIO_DIARIO – Type           | DATA TYPE    | MX_FIN_SALARIO_DIARIO           |
| MX_FIN_PATRIMONIO – Path               | COLUMN NAME  | MX_FIN_PATRIMONIO               |
| MX_FIN_PATRIMONIO – Type               | DATA TYPE    | MX_FIN_PATRIMONIO               |
| MX_FIN_AFORE – Path                    | COLUMN NAME  | MX_FIN_AFORE                    |
| MX_FIN_AFORE – List                    | KNOWN VALUES | MX_FIN_AFORE                    |
| MX_FIN_SALDO_RETIRO – Path             | COLUMN NAME  | MX_FIN_SALDO_RETIRO             |
| MX_FIN_SALDO_RETIRO – Type             | DATA TYPE    | MX_FIN_SALDO_RETIRO             |
| MX_FIN_CREDITO_VIVIENDA – Path         | COLUMN NAME  | MX_FIN_CREDITO_VIVIENDA         |
| MX_FIN_CREDITO_VIVIENDA – List         | KNOWN VALUES | MX_FIN_CREDITO_VIVIENDA         |
| MX_FIN_SEGURIDAD_SOCIAL – Path         | COLUMN NAME  | MX_FIN_SEGURIDAD_SOCIAL         |

| CLASSIFIER                         | KIND         | DOMAIN                      |
|------------------------------------|--------------|-----------------------------|
| MX_FIN_SEGURIDAD_SOCIAL - List     | KNOWN VALUES | MX_FIN_SEGURIDAD_SOCIAL     |
| MX_FIN_PROGRAMA_SOCIAL - Path      | COLUMN NAME  | MX_FIN_PROGRAMA_SOCIAL      |
| MX_FIN_PROGRAMA_SOCIAL - List      | KNOWN VALUES | MX_FIN_PROGRAMA_SOCIAL      |
| MX_FIN_NIVEL_SOCIOECONOMICO - Path | COLUMN NAME  | MX_FIN_NIVEL_SOCIOECONOMICO |
| MX_FIN_NIVEL_SOCIOECONOMICO - List | KNOWN VALUES | MX_FIN_NIVEL_SOCIOECONOMICO |
| MX_FIN_VIVIENDA - Path             | COLUMN NAME  | MX_FIN_VIVIENDA             |
| MX_FIN_VIVIENDA - List             | KNOWN VALUES | MX_FIN_VIVIENDA             |
| MX_FIN_REGIMEN_FISCAL - Path       | COLUMN NAME  | MX_FIN_REGIMEN_FISCAL       |
| MX_PENAL_ANTECEDENTES - Path       | COLUMN NAME  | MX_PENAL_ANTECEDENTES       |
| MX_PENAL_CAUSA - Path              | COLUMN NAME  | MX_PENAL_CAUSA              |
| MX_PENAL_CAUSA - Regex             | VALUE FORMAT | MX_PENAL_CAUSA              |