

Spain — GDPR and Ley Orgánica 3/2018 (LOPDGDD)

Discovery and masking of Spanish personal data: DNI and NIE with a valid letter, the Seguridad Social number, the IBAN and the CCC, the referencia catastral and the CUPS with valid control characters, municipios and postal codes generalized below 20,000 inhabitants, the special categories of article 9, health, economic and tax data, and criminal records and administrative sanctions.

83

DOMAINS

147

CLASSIFIERS

347

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1 About this profile set

2 The law in Spain: the Regulation and the LOPDGDD

3 Pseudonymization, anonymization and non-production copies

4 How sensitive data is discovered

5 How data is masked

6 Essential and extended packs

7 Domains at a glance

PART 8 · DIRECT IDENTIFIERS

8.1	DNI and NIF of a natural person	ES_L1_DNI
8.2	NIE	ES_L1_NIE
8.3	Passport	ES_L1_PASAPORTE
8.4	Support number of the identity card	ES_L1_SOPORTE_DOCUMENTO
8.5	Seguridad Social number	ES_L1_NSS
8.6	Student number	ES_L1_CODIGO_ESTUDIANTE
8.7	Professional registration number	ES_L1_COLEGIADO
8.8	Given name	ES_L1_NOMBRE
8.9	Surname	ES_L1_APELLIDO
8.10	Full name	ES_L1_NOMBRE_COMPLETO
8.11	E-mail	ES_L1_EMAIL
8.12	Telephone	ES_L1_TELEFONO
8.13	Address	ES_L1_DIRECCION
8.14	Address complement	ES_L1_DIRECCION_COMPLEMENTO
8.15	Bank account (IBAN and CCC)	ES_L1_CUENTA_BANCARIA
8.16	Payment card	ES_L1_TARJETA
8.17	Digital wallet	ES_L1_BILLETERA
8.18	IP address	ES_L1_IP
8.19	Device identifier	ES_L1_DISPOSITIVO
8.20	Cookie and tracking identifier	ES_L1_COOKIE
8.21	Vehicle plate	ES_L1_MATRICULA
8.22	Vehicle identification	ES_L1_VEICULO
8.23	Referencia catastral	ES_L1_REFERENCIA_CATASTRAL
8.24	CUPS (supply point)	ES_L1_CUPS

8.25	Contract and customer number	ES_L1_CONTRATO
8.26	User name and social profile	ES_L1_USUARIO
8.27	Credential	ES_L1_CREDENCIAL
8.28	Image and voice	ES_L1_IMAGEN
8.29	Geolocation	ES_L1_GEOLOCALIZACION
8.30	Free text	ES_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	ES_L2_FECHA_NACIMIENTO
9.2	Year of birth	ES_L2_ANIO_NACIMIENTO
9.3	Age	ES_L2_EDAD
9.4	Date of a life event	ES_L2_FECHA_EVENTO
9.5	Sex	ES_L2_SEXO
9.6	Municipio	ES_L2_MUNICIPIO
9.7	INE code of the municipio	ES_L2_CODIGO_MUNICIPIO
9.8	Postal code	ES_L2_CODIGO_POSTAL
9.9	Nationality	ES_L2_NACIONALIDAD
9.10	Residence status	ES_L2_SITUACION_ADMINISTRATIVA
9.11	Marital status	ES_L2_ESTADO_CIVIL
9.12	Occupation	ES_L2_OCUPACION
9.13	Employer	ES_L2_EMPLEADOR
9.14	Level of education	ES_L2_NIVEL_EDUCATIVO
9.15	School or university	ES_L2_CENTRO_EDUCATIVO
9.16	Dependants	ES_L2_PERSONAS_A_CARGO

PART 10 · SPECIAL CATEGORIES (ART. 9 RGPD AND ART. 9 LOPDGGD)

10.1	Racial or ethnic origin	ES_L3_ORIGEN_ETNICO
10.2	Religion	ES_L3_RELIGION
10.3	Philosophical beliefs	ES_L3_CONVICCION_FILOSOFICA
10.4	Political opinion	ES_L3_OPINION_POLITICA
10.5	Party membership	ES_L3_AFILIACION_PARTIDARIA
10.6	Trade union membership	ES_L3_AFILIACION_SINDICAL
10.7	Biometric data	ES_L3_BIOMETRICO
10.8	Genetic data	ES_L3_GENETICO
10.9	Sexual orientation	ES_L3_ORIENTACION_SEXUAL
10.10	Sex life	ES_L3_VIDA_SEXUAL
10.11	Gender identity	ES_L3_IDENTIDAD_GENERO
10.12	Victims of gender and sexual violence	ES_L3_VICTIMA

PART 11 · HEALTH DATA (ART. 9 RGPD, LEY 41/2002 AND DA 17 LOPDGDD)

11.1	Health identifiers	ES_SALUD_IDENTIFICADOR
11.2	Health coverage	ES_SALUD_COBERTURA
11.3	Diagnosis	ES_SALUD_DIAGNOSTICO
11.4	Medical procedure	ES_SALUD_PROCEDIMIENTO
11.5	Medicine	ES_SALUD_MEDICAMENTO
11.6	Clinical text	ES_SALUD_TEXTO_CLINICO
11.7	Test result	ES_SALUD_RESULTADO_PRUEBA
11.8	HIV and sexually transmitted infections	ES_SALUD_VIH
11.9	Blood group	ES_SALUD_GRUPO_SANGUINEO
11.10	Disability	ES_SALUD_DISCAPACIDAD
11.11	Dependency	ES_SALUD_DEPENDENCIA
11.12	Occupational health	ES_SALUD_LABORAL
11.13	Reproductive health	ES_SALUD_REPRODUCTIVA
11.14	Mental health	ES_SALUD_MENTAL

PART 12 · ECONOMIC AND TAX DATA (ART. 20 LOPDGDD AND ART. 95 LGT)

12.1	Credit history	ES_FIN_HISTORIAL_CREDITICIO
12.2	Debt	ES_FIN_DEUDA
12.3	Income	ES_FIN_INGRESOS
12.4	Assets	ES_FIN_PATRIMONIO
12.5	Pension	ES_FIN_PENSION
12.6	Social benefits	ES_FIN_PRESTACION_SOCIAL
12.7	Tax data	ES_FIN_TRIBUTARIO

PART 13 · CRIMINAL AND ADMINISTRATIVE OFFENCES (ART. 10 RGPD, ARTS. 10 AND 27 LOPDGDD)

13.1	Criminal records	ES_PENAL_ANTECEDENTES
13.2	Certificate of the register of sex offenders	ES_PENAL_DELITOS_SEXUALES
13.3	Court case number	ES_PENAL_PROCEDIMIENTO
13.4	Administrative sanctions	ES_PENAL_SANCION_ADMINISTRATIVA
14	Check characters computed by lookup tables	
15	Where people live: municipios, INE codes and postal codes	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	

About this profile set

This profile set finds the personal data in a Spanish database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and DNIs alone is not enough: a birth date, a sex and one small municipio already point at a handful of people, and 7,700 of the 8,132 municipios of Spain have fewer than 20,000 inhabitants. The set works in the layers where the risk is:

- **Direct identifiers** — DNI, NIE and the NIF of a natural person, passport, the support number of the card, the Seguridad Social number, student and professional numbers, names, contact, address, bank accounts, cards, devices, cookies, plates, the referencia catastral of a property, the CUPS of an electricity or gas supply, photographs, free text.
- **Quasi-identifiers** — birth date, year of birth, age, sex, municipio, its INE code and the postal code, nationality and residence status, marital status, occupation, employer, education, dependants.
- **Special categories** — the data of article 9 of the Regulation: racial or ethnic origin, political opinions and party membership, religious or philosophical beliefs, trade union membership, genetic and biometric data, sex life and sexual orientation; with gender identity and the victims of gender violence, which Spanish law protects in their own right.
- **Health data** — the historia clínica, diagnoses, procedures, medicines, HIV, disability and dependency, occupational health, reproductive and mental health.
- **Economic data** — the files of defaulters and the risk centre of the Banco de España, debts, income, assets, pensions, social benefits, and the tax data the Ley General Tributaria calls reserved.
- **Criminal and administrative offences** — criminal records, the certificate of the register of sex offenders, court case numbers, and administrative sanctions such as fines and the points of a driving licence.

Each group below says what each domain is, how it is masked and why. The discovery is a profile set of 147 classifiers at a threshold of 60; the masking is 83 domains with their algorithms. Column names are recognized in Castilian, in English and, for the most common data, in Catalan, Galician and Basque.

The law in Spain: the Regulation and the LOPDGDD

Spain has no data protection law of its own in the way its neighbours across the Atlantic do: the law is the **General Data Protection Regulation**, Regulation (EU) 2016/679, which applies directly, and **Ley Orgánica 3/2018, de 5 de diciembre, de Protección de Datos Personales y garantía de los derechos digitales** (LOPDGDD), which adapts and completes it where the Regulation leaves room to the Member States. The fundamental right itself is in article 18.4 of the Constitution. The LOPDGDD has been amended several times — by Ley Orgánica 3/2020, Ley Orgánica 7/2021, Ley 2/2023, Ley 11/2023 and, last, by Ley 10/2025 of 26 December, which rewrote the advertising exclusion systems of article 23 — without touching the provisions this set rests on. The authority is the **Agencia Española de Protección de Datos** (AEPD), beside the authorities of Catalonia, the Basque Country and Andalusia for their own public sector.

The Regulation protects **natural persons** only: article 4.1 defines personal data as information relating to an identified or identifiable natural person, and recital 14 says it does not cover data concerning legal persons. So the NIF of a company passes through this set untouched, while the NIF of a self-employed person — which is their DNI — is masked like any other.

Four provisions of the LOPDGDD shape this set beyond the Regulation:

- **Article 9.1** — for ideology, trade union membership, religion, sexual orientation, beliefs and racial or ethnic origin, "el solo consentimiento del afectado no bastará para levantar la prohibición del tratamiento de datos cuya finalidad principal sea identificar" them. Consent, which the Regulation allows, is not enough in Spain.
- **Article 10** — data on criminal convictions and offences may be processed outside the authorities only where a law with the rank of law allows it; **article 27** extends the rule to administrative infringements and sanctions.
- **Article 32** — when data are rectified or erased they must be **blocked**: identified and reserved "para impedir su tratamiento, incluyendo su visualización", and article 32.3 forbids processing blocked data "para ninguna finalidad distinta" from making them available to courts and authorities.
- **Additional provision 17** — the laws under which health data are processed, and the conditions for pseudonymized health data in research, quoted below.

Infringements are graded by articles 72 to 74 of the LOPDGDD, and the fines are those of article 83 of the Regulation, up to 20 million euros or 4% of worldwide turnover. Among the very serious infringements, which prescribe after three years, are processing special categories outside article 9 (art. 72.1 e), processing criminal data outside article 10 (art. 72.1 f), breaching the duty of confidentiality (art. 72.1 i), failing to block data (art. 72.1 n) — and, the provision that speaks most directly to this set, **"la reversión deliberada de un procedimiento de anonimización a fin de permitir la reidentificación de los afectados"** (art. 72.1 p).

3

Pseudonymization, anonymization and non-production copies

The Regulation names the technique. Article 4.5 defines **pseudonymisation** as processing personal data so that they can no longer be attributed to a specific person without the use of additional information, "provided that such additional information is kept separately and is subject to technical and organisational measures". Recital 26 leaves anonymous information outside the Regulation altogether and measures identifiability by "all the means reasonably likely to be used". Article 25.1 names pseudonymisation as the first example of data protection by design, article 32.1 a) as the first example of a security measure, and article 6.4 e) as a safeguard that makes a further use compatible with the original one.

Masking with the engine is pseudonymization in exactly that sense: the result is deterministic for the engine's key, and whoever holds the key and the production data can reproduce the mapping. A masked copy is therefore still personal data **for whoever can reach the key**, and the key has to be kept apart from the copy. The Court of Justice drew the consequence on 4 September 2025, in **EDPS v SRB (C-413/23 P)**: pseudonymized data may not be personal data for a recipient who has no means reasonably likely to reidentify them, while they remain personal data for the one who holds the additional information. The EDPB said the same in its Guidelines 01/2025 on pseudonymisation, adopted on 16 January 2025. The European Commission proposed in November 2025, in the Digital Omnibus, to write that relative reading into the definition of personal data; the Council's compromise of 2026 dropped the change, and in October 2026 the definition stands as it was.

Spanish law adds three things of its own. The additional provision 17 of the LOPDGDD allows pseudonymized health data in research only with **"una separación técnica y funcional entre el equipo investigador y quienes realicen la seudonimización y conserven la información que posibilite la reidentificación"** — the rule this set asks for the engine key. Article 28.2 a) lists "reversión no autorizada de la seudonimización" among the risks a controller must weigh. And article 72.1 p) makes deliberately reversing an anonymization a very serious infringement.

On copies outside production the guidance is plain. The AEPD wrote on 18 April 2022, in "Brechas de datos personales en entornos de desarrollo y preproducción", that the use of personal data in development and pre-production environments should be avoided, that test data should be created artificially or derived from real data so that their structure is kept but no real personal data remain, and that where real data are strictly needed the decision must be documented with an analysis of necessity and proportionality. For the public sector and its suppliers it is a rule: the **Esquema Nacional de Seguridad** (Real Decreto 311/2022) requires in measure **mp.sw.1** that development be done on a system separate from production, "ni datos de producción en el de desarrollo", and in its reinforcement R4 that tests before a system is put in service "preferiblemente" not use real data — both for systems of medium and high category. A masked copy is how both are met.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	27	65	9
Extended	83	147	347	103

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- DNI and NIF of a natural person — ES_L1_DNI
- NIE — ES_L1_NIE
- Passport — ES_L1_PASAPORTE
- Seguridad Social number — ES_L1_NSS
- Given name — ES_L1_NOMBRE
- Surname — ES_L1_APELLIDO
- Full name — ES_L1_NOMBRE_COMPLETO
- E-mail — ES_L1_EMAIL
- Telephone — ES_L1_TELEFONO
- Address — ES_L1_DIRECCION
- Address complement — ES_L1_DIRECCION_COMPLEMENTO
- Birth date — ES_L2_FECHA_NACIMIENTO

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM	
DIRECT IDENTIFIERS					
DNI and NIF of a natural person	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	ES_DOCUMENTO
ES_L1_DNI					
NIE	ESSENTIAL	COLUMN NAME	VALUE FORMAT		ES_DOCUMENTO
ES_L1_NIE					
Passport	ESSENTIAL	COLUMN NAME	VALUE FORMAT		ES_CM_DIGITOS_LETRAS
ES_L1_PASAPORTE					
Support number of the identity card		COLUMN NAME	VALUE FORMAT		ES_CM_DIGITOS_LETRAS
ES_L1_SOPORTE_DOCUMENTO					
Seguridad Social number	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	ES_NSS
ES_L1_NSS					
Student number		COLUMN NAME			ES_CM_ALFANUM
ES_L1_CODIGO_ESTUDIANTE					
Professional registration number		COLUMN NAME			ES_CM_ALFANUM
ES_L1_COLEGIADO					
Given name	ESSENTIAL	COLUMN NAME	KNOWN VALUES		ES_NOMBRES
ES_L1_NOMBRE					
Surname	ESSENTIAL	COLUMN NAME	KNOWN VALUES		ES_APELLIDOS
ES_L1_APELLIDO					
Full name	ESSENTIAL	COLUMN NAME	KNOWN VALUES		ES_NOMBRE_COMPLETO
ES_L1_NOMBRE_COMPLETO					
E-mail	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	ES_EMAIL
ES_L1_EMAIL					
Telephone	ESSENTIAL	COLUMN NAME	VALUE FORMAT		ES_TELEFONO
ES_L1_TELEFONO					
Address	ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	ES_DIRECCION
ES_L1_DIRECCION					
Address complement	ESSENTIAL	COLUMN NAME			ES_CM_ALFANUM
ES_L1_DIRECCION_COMPLEMENTO					
Bank account (IBAN and CCC)		COLUMN NAME	VALUE FORMAT		ES_CUENTA
ES_L1_CUENTA_BANCARIA					
Payment card		COLUMN NAME	VALUE FORMAT		ES_TARJETA
ES_L1_TARJETA					
Digital wallet		COLUMN NAME	VALUE FORMAT		ES_CM_ALFANUM
ES_L1_BILLETERA					
IP address		COLUMN NAME	VALUE FORMAT		ES_IP
ES_L1_IP					
Device identifier		COLUMN NAME	VALUE FORMAT		ES_CM_HEX
ES_L1_DISPOSITIVO					

DOMAIN	FOUND BY			ALGORITHM
Cookie and tracking identifier ES_L1_COOKIE	COLUMN NAME			ES_CM_ALFANUM
Vehicle plate ES_L1_MATRICULA	COLUMN NAME	VALUE FORMAT		ES_MATRICULA
Vehicle identification ES_L1_VEHICULO	COLUMN NAME	VALUE FORMAT		ES_CM_ALFANUM
Referencia catastral ES_L1_REFERENCIA_CATASTRAL	COLUMN NAME	VALUE FORMAT		ES_REFERENCIA_CATASTRAL
CUPS (supply point) ES_L1_CUPS	COLUMN NAME	VALUE FORMAT		ES_CUPS
Contract and customer number ES_L1_CONTRATO	COLUMN NAME			ES_CM_ALFANUM
User name and social profile ES_L1_USUARIO	COLUMN NAME			ES_CM_ALFANUM
Credential ES_L1_CREDENCIAL	COLUMN NAME			ES_REDACTAR
Image and voice ES_L1_IMAGEN	COLUMN NAME			ES_REDACTAR
Geolocation ES_L1_GEOLOCALIZACION	COLUMN NAME	VALUE FORMAT		ES_COORDENADA
Free text ES_L1_TEXTO_LIBRE	COLUMN NAME	DATA TYPE	VALUE FORMAT	ES_TEXTO_LIBRE
QUASI-IDENTIFIERS				
Birth date ESSENTIAL ES_L2_FECHA_NACIMIENTO	COLUMN NAME	DATA TYPE		ES_FECHA_NACIMIENTO
Year of birth ES_L2_ANIO_NACIMIENTO	COLUMN NAME	DATA TYPE		ES_ANIO
Age ES_L2_EDAD	COLUMN NAME	DATA TYPE		ES_EDAD
Date of a life event ES_L2_FECHA_EVENTO	COLUMN NAME	DATA TYPE		ES_FECHA_EVENTO
Sex ES_L2_SEXO	COLUMN NAME	KNOWN VALUES		ES_SEXO
Municipio ES_L2_MUNICIPIO	COLUMN NAME	KNOWN VALUES		ES_MUNICIPIO
INE code of the municipio ES_L2_CODIGO_MUNICIPIO	COLUMN NAME	VALUE FORMAT		ES_CODIGO_MUNICIPIO
Postal code ES_L2_CODIGO_POSTAL	COLUMN NAME	VALUE FORMAT		ES_CODIGO_POSTAL
Nationality ES_L2_NACIONALIDAD	COLUMN NAME	KNOWN VALUES		ES_NACIONALIDAD
Residence status ES_L2_SITUACION_ADMINISTRATIVA	COLUMN NAME	KNOWN VALUES		ES_SITUACION_ADMINISTRATIVA
Marital status ES_L2_ESTADO_CIVIL	COLUMN NAME	KNOWN VALUES		ES_ESTADO_CIVIL

DOMAIN	FOUND BY		ALGORITHM
Occupation ES_L2_OCUPACION	COLUMN NAME		ES_OCUPACION_0_CODIGO
Employer ES_L2_EMPLEADOR	COLUMN NAME		ES_EMPLEADOR
Level of education ES_L2_NIVEL_EDUCATIVO	COLUMN NAME	KNOWN VALUES	ES_NIVEL_EDUCATIVO
School or university ES_L2_CENTRO_EDUCATIVO	COLUMN NAME		ES_CENTRO_EDUCATIVO
Dependants ES_L2_PERSONAS_A_CARGO	COLUMN NAME	DATA TYPE	ES_CONTEO_LIMITADO
SPECIAL CATEGORIES (ART. 9 RGPD AND ART. 9 LOPDGDD)			
Racial or ethnic origin ES_L3_ORIGEN_ETNICO	COLUMN NAME	KNOWN VALUES	ES_ORIGEN_ETNICO
Religion ES_L3_RELIGION	COLUMN NAME	KNOWN VALUES	ES_RELIGION
Philosophical beliefs ES_L3_CONVICCION_FILOSOFICA	COLUMN NAME		ES_CATEGORIA_SUPRIMIDA
Political opinion ES_L3_OPINION_POLITICA	COLUMN NAME	KNOWN VALUES	ES_OPINION_POLITICA
Party membership ES_L3_AFILIACION_PARTIDARIA	COLUMN NAME	KNOWN VALUES	ES_PARTIDO
Trade union membership ES_L3_AFILIACION_SINDICAL	COLUMN NAME	KNOWN VALUES	ES_CATEGORIA_SUPRIMIDA
Biometric data ES_L3_BIOMETRICO	COLUMN NAME	DATA TYPE	ES_REDACTAR
Genetic data ES_L3_GENETICO	COLUMN NAME		ES_REDACTAR
Sexual orientation ES_L3_ORIENTACION_SEXUAL	COLUMN NAME	KNOWN VALUES	ES_ORIENTACION_SEXUAL
Sex life ES_L3_VIDA_SEXUAL	COLUMN NAME		ES_CATEGORIA_SUPRIMIDA
Gender identity ES_L3_IDENTIDAD_GENERO	COLUMN NAME	KNOWN VALUES	ES_IDENTIDAD_GENERO
Victims of gender and sexual violence ES_L3_VICTIMA	COLUMN NAME		ES_CATEGORIA_SUPRIMIDA
HEALTH DATA (ART. 9 RGPD, LEY 41/2002 AND DA 17 LOPDGDD)			
Health identifiers ES_SALUD_IDENTIFICADOR	COLUMN NAME	VALUE FORMAT	ES_CM_ALFANUM
Health coverage ES_SALUD_COBERTURA	COLUMN NAME	KNOWN VALUES	ES_COBERTURA_SALUD
Diagnosis ES_SALUD_DIAGNOSTICO	COLUMN NAME	VALUE FORMAT	ES_DIAGNOSTICO
Medical procedure ES_SALUD_PROCEDIMIENTO	COLUMN NAME		ES_PROCEDIMIENTO

DOMAIN	FOUND BY	ALGORITHM
Medicine ES_SALUD_MEDICAMENTO	COLUMN NAME KNOWN VALUES	ES_MEDICAMENTO
Clinical text ES_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	ES_TEXTO_LIBRE
Test result ES_SALUD_RESULTADO_PRUEBA	COLUMN NAME	ES_CM_ALFANUM
HIV and sexually transmitted infections ES_SALUD_VIH	COLUMN NAME	ES_CATEGORIA_SUPRIMIDA
Blood group ES_SALUD_GRUPO_SANGUINEO	COLUMN NAME KNOWN VALUES	ES_GRUPO_SANGUINEO
Disability ES_SALUD_DISCAPACIDAD	COLUMN NAME KNOWN VALUES	ES_DISCAPACIDAD
Dependency ES_SALUD_DEPENDENCIA	COLUMN NAME KNOWN VALUES	ES_DEPENDENCIA
Occupational health ES_SALUD_LABORAL	COLUMN NAME KNOWN VALUES	ES_APTITUD_LABORAL
Reproductive health ES_SALUD_REPRODUCTIVA	COLUMN NAME	ES_CATEGORIA_SUPRIMIDA
Mental health ES_SALUD_MENTAL	COLUMN NAME	ES_CATEGORIA_SUPRIMIDA
ECONOMIC AND TAX DATA (ART. 20 LOPDGGD AND ART. 95 LGT)		
Credit history ES_FIN_HISTORIAL_CREDITICIO	COLUMN NAME	ES_HISTORIAL_CREDITICIO
Debt ES_FIN_DEUDA	COLUMN NAME DATA TYPE	ES_VALOR_DEUDA
Income ES_FIN_INGRESOS	COLUMN NAME DATA TYPE	ES_INGRESOS
Assets ES_FIN_PATRIMONIO	COLUMN NAME DATA TYPE	ES_PATRIMONIO
Pension ES_FIN_PENSION	COLUMN NAME DATA TYPE	ES_VALOR_PENSION
Social benefits ES_FIN_PRESTACION_SOCIAL	COLUMN NAME KNOWN VALUES	ES_PRESTACION_SOCIAL
Tax data ES_FIN_TRIBUTARIO	COLUMN NAME	ES_TRIBUTARIO
CRIMINAL AND ADMINISTRATIVE OFFENCES (ART. 10 RGPD, ARTS. 10 AND 27 LOPDGGD)		
Criminal records ES_PENAL_ANTECEDENTES	COLUMN NAME	ES_ANTECEDENTES
Certificate of the register of sex offenders ES_PENAL_DELITOS_SEXUALES	COLUMN NAME KNOWN VALUES	ES_DELITOS_SEXUALES
Court case number ES_PENAL_PROCEDIMIENTO	COLUMN NAME VALUE FORMAT	ES_PROCEDIMIENTO_JUDICIAL
Administrative sanctions ES_PENAL_SANCION_ADMINISTRATIVA	COLUMN NAME	ES_SANCION_ADMINISTRATIVA

Direct identifiers

Data that identifies a person on its own. Spanish identifiers carry check characters — the letter of the DNI, the control digits of the Seguridad Social number and of the bank account, the control letters of the referencia catastral and of the CUPS — and every Spanish system validates them, so the set recomputes each one from the masked digits. The NIF of a company is no one's personal data and passes through untouched.

8.1 DNI and NIF of a natural person

ES_L1_DNI

ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	REGEX DECOMPOSE
-----------	-------------	-----------	--------------	-----------------

WHAT IT IS

The Documento Nacional de Identidad: eight digits and a letter, 12345678Z , often written 12.345.678-Z . The letter is the number **modulo 23**, read in the table TRWAGMYFPDXBNJZSQVHLCKE , and every Spanish form checks it. The DNI is also the NIF of its holder before the tax administration, so a NIF column of a natural person is this column.

The same domain takes what a document column holds beside DNIs: a NIE, the NIF of a natural person without DNI or NIE — **K** for a Spaniard under fourteen, **L** for a Spaniard resident abroad, **M** for a foreigner without NIE, seven digits and the letter of the seven digits —, the NIF of a company, a DNI stored without its letter and a passport.

HOW IT IS FOUND

COLUMN NAME ES_L1_DNI - Path

90% dni d_n_i nif *(except when followed by list E1)* n_i_f n(o|ro|um|umero)?
(dni|nif|documento|doc|identificaci[oó]n|id(ent)?) doc_?identidad documento_?(nacional_?)?
(de_?)?identidad nro_?doc num_?doc identificaci[oó]n *(except when preceded by*
(tipo|tp|cod|codigo|desc|clase)_ ; except when followed by tipo , clase , fiscal_?empresa) nie_?nif
nif_?nie dni_?nie nie_?dni
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|
trabajador|funcionario|alumno|estudiante|deudor|avalista|fiador|garante|solicitante|propietari
o|arrendatario|inquilino|conductor|tomador|responsable|representante|apoderado|persona|ciudada
no|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|pensionista|jubilad
o|interesado|declarante|perceptor)_?(dni|nif|doc|documento) (dni|nif)?
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|t
rabajador|funcionario|alumno|estudiante|deudor|avalista|fiador|garante|solicitante|propietario
|arrendatario|inquilino|conductor|tomador|responsable|representante|apoderado|persona|ciudadan
o|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|pensionista|jubilado
|interesado|declarante|perceptor) carn[eé]_?(de_?)?conducir n(o|ro|um|umero)?permiso?
conducir driver_?licen[cs]e national_?id id_?number

60% documento doc identificador_?fiscal nif tax_?id

DATA TYPE ES_L1_DNI - Type

Accepts text (length 6 or more) or number (length 6 or more); any other type rules the domain out.

VALUE FORMAT ES_L1_DNI - Regex

PATTERN	STRENGTH	NOTES
\d{8}[\s-]?[TRWAGMYFPDXBNJZSQVHLCKE]	95%	
\d{1,2}\.\d{3}\.\d{3}[\s-]?[TRWAGMYFPDXBNJZSQVHLCKE]	95%	
[KLM]\d{7}[TRWAGMYFPDXBNJZSQVHLCKE]	90%	
\d{8}	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The digits change and **the letter is recomputed**, so the masked value is a valid DNI that belongs to nobody. No framework writes a letter modulo 23, so a state of two digits — the remainder so far — is put in front of the value and crosses it one character at a time; each step is a Data Cleansing over a table of 299 lines that answers "state + character" with "character + new state", stepping over the dots, hyphens and spaces of the written forms. At the end a table of 46 lines turns the remainder into the letter, upper-case or lower-case as it was.

A NIE keeps its prefix and a K, L or M NIF its letter, each recomputed in the same chain. The **NIF of a company** — a letter such as A or B, seven digits and a control character — passes through untouched: article 4.1 of the Regulation reaches natural persons only, and its recital 14 says so of legal persons.

ES_DOCUMENTO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_DNI STRING ALGORITHM CHAIN

Applies ES_DNI_1 → ES_DNI_2 → ES_DNI_RESTAURAR , in this order. It is made of 22 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
12345678Z	→ 46916122D
12.345.678-Z	→ 46.916.122-D
X1234567L	→ X5649285W
K1234567S	→ K5649285W
B12345674	→ B12345674

8.2

NIE

ES_L1_NIE

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The Número de Identidad de Extranjero the Policía assigns to every foreign national with interests in Spain: a prefix **X, Y or Z**, seven digits and a letter, X1234567L . The prefix counts as a digit — X is 0, Y is 1, Z is 2 — and the letter is that eight-digit number modulo 23, the same rule as the DNI. It is printed on the Tarjeta de Identidad de Extranjero and serves as NIF.

HOW IT IS FOUND

COLUMN NAME	ES_L1_NIE - Path
90%	<code>nie n_i_e n(o ro um umero)?(de_)?(identidad?(de_)?)?extranjero n(o ro um umero)?nie tie tarjeta?(de_)?(identidad?(de_)?)?extranjero tarjeta?(de_)?residencia (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado emp trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano elector contribuyente proveedor socio conyuge padre madre hijo familiar pensionista jubilado interesado declarante perceptor)?nie nie_? (cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado emp trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano elector contribuyente proveedor socio conyuge padre madre hijo familiar pensionista jubilado interesado declarante perceptor) foreigner_id</code>

VALUE FORMAT	ES_L1_NIE - Regex		
PATTERN	STRENGTH	NOTES	
[XYZ] [\s-]? \d{7} [\s-]? [TRWAGMYFPDXBNJZSQVHLCKE]	95%		
A value that matches none counts 30% against the domain.			

HOW IT IS MASKED

With the same chain as the DNI: the seven digits change, the prefix stays, and the letter is recomputed with the prefix counted in. A masked NIE is a valid NIE of the same series.

ES_DOCUMENTO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_DNI	STRING ALGORITHM CHAIN
Applies ES_DNI_1 → ES_DNI_2 → ES_DNI_RESTAURAR , in this order. It is made of 22 algorithms that repeat the same step position by position; each one is in Appendix A.	
ES_CM_DIGITOS_LETRAS	CHARACTER MAPPING
Maps each character to another of its group (2 groups), keeping length and format.	
ES_CM_ALFANUM	CHARACTER MAPPING
Maps each character to another of its group (9 groups), keeping length and format.	

EXAMPLES

VALUE	MASKED
X1234567L	→ X5649285W
Y-1234567-X	→ Y-5649285-Q

8.3 Passport

ES_L1_PASAPORTE

ESSENTIAL	COLUMN NAME	VALUE FORMAT	CHARACTER MAPPING
-----------	-------------	--------------	-------------------

WHAT IT IS

The number of a passport: since 2006 the Spanish one is three letters and six digits, PAA123456 ; foreign passports take any shape.

HOW IT IS FOUND

COLUMN NAME ES_L1_PASAPORTE – Path

90% `pasaporte[a-z0-9_]*` `n(o|ro|um|umero)?pasaporte` `passport` `pasaportea` `passport[a-z0-9_]*`

VALUE FORMAT ES_L1_PASAPORTE – Regex

PATTERN	STRENGTH	NOTES
<code>[A-Z]{3}\d{6}</code>		45%
<code>[A-Z]{2}\d{6}</code>		35%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character: letters to letters, digits to digits, so the number keeps its shape.

ES_CM_DIGITOS_LETRAS **CHARACTER MAPPING**

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
PAA123456	→ TEU036274

8.4 Support number of the identity card

ES_L1_SOPORTE_DOCUMENTO

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The number printed on the card itself rather than the person — the IDESP of the DNI, three letters and six digits, or the support number of the Tarjeta de Identidad de Extranjero, E12345678 . Banks, telecom operators and administrations ask for it to check that the holder has the document in hand, and it identifies the card as surely as the DNI identifies the person.

HOW IT IS FOUND

COLUMN NAME ES_L1_SOPORTE_DOCUMENTO – Path

90% `n(o|ro|um|umero)?(de_)?soporte(_?(dni|nie|tie|documento))?` `soporte_?`
`(dni|nie|tie|documento)` `idesp` `can_?(dni|nie)` `n(o|ro|um|umero)?can` `card_?access_?number`

VALUE FORMAT ES_L1_SOPORTE_DOCUMENTO – Regex

PATTERN	STRENGTH	NOTES
<code>[A-Z]{3}\d{6}</code>		40%
<code>E\d{8}</code>		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_DIGITOS_LETRAS **CHARACTER MAPPING**

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

BAA123456

→ APW622948

8.5 Seguridad Social number

ES_L1_NSS

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The number the Tesorería General de la Seguridad Social gives a person the first time it registers them, kept for life: twelve digits, 28 12345678 40 — two for the province of the first registration, eight for the number and two **control digits**, the first ten read as one number modulo 97. A number whose eight digits start with a zero is an older one, and then the zero does not count.

HOW IT IS FOUND

COLUMN NAME ES_L1_NSS – Path

90% n(o|ro|um|umero)?(de_?)(afiliaci[oó]n|seguridad_?social|ss|naf|nuss|nass) naf nuss
nass afiliaci[oó]n?(a_?la_?)(ss|seguridad_?social) seguridad_?social num_?ss nss
n_s_s social_?security(_?number)? ssn

DATA TYPE ES_L1_NSS – Type

Accepts text (length 11 or more) or number (length 11 or more); any other type rules the domain out.

VALUE FORMAT ES_L1_NSS – Regex

PATTERN	STRENGTH	NOTES
(0[1-9] [1-4]\d 5[0-3] 66) [\s/\-]? \d{8} [\s/\-]? \d{2}	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The province stays and the eight digits change. The two control digits are **recomputed** by a state that crosses the ten digits with a table of 1,358 lines — 97 remainders by each digit and separator — and becomes the control digits itself; a leading zero is marked, stepped over and put back. The masked number is valid under the Seguridad Social rule and keeps its written form.

ES_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_NSS_CADENA STRING ALGORITHM CHAIN

Applies ES_NSS_CADENA_1 → ES_NSS_CADENA_2 → ES_NSS_CADENA_3 , in this order. It is made of 27 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

281234567840

→ 284691612272

28/12345678/40

→ 28/46916122/72

8.6 Student number

ES_L1_CODIGO_ESTUDIANTE

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The NIA a comunidad autónoma gives every pupil, and the student or record number of a university.

HOW IT IS FOUND

COLUMN NAME ES_L1_CODIGO_ESTUDIANTE – Path

80% nia n(o|ro|um|umero)?(de_)?(identificaci[oó]n?(de_l_)?)?alumno n(o|ro|um|umero)?(de_)?(matr[ií]cula|expediente)?(alumno|acad[eé]mico|estudiante) expediente?acad[eé]mico c[oó]digo?(de_)?(estudiante|alumno) cod?(alumno|estudiante) id?(alumno|estudiante) nre carn[eé]?(de_)?estudiante

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
2012345678	→ 6415666886

8.7 Professional registration number

ES_L1_COLEGIADO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The number of a member of a colegio profesional — doctors, lawyers, architects, psychologists — printed on prescriptions, reports and filings, and searchable in each colegio's public register.

HOW IT IS FOUND

COLUMN NAME ES_L1_COLEGIADO – Path

85% n(o|ro|um|umero)?(de_)?colegiad[oa] colegiad[oa] n(o|ro|um|umero)?colegio?profesional c[oó]digo?(profesional|m[eé]dico|facultativo) n(o|ro|um|umero)?(de_)?(registro?profesional|habilitaci[oó]n) cias?profesional

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
2812345	→ 4719789

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

One or two given names — `María de los Ángeles`, `José Antonio`, `Jordi`, `Iñaki`.

HOW IT IS FOUND

COLUMN NAME

ES_L1_NOMBRE – Path

85%

`primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `nombre_?propio` `nombre_?1` `nombre_?`
`2` `first_?names?` `given_?names?` `fname` `middle_?names?` `izena` `nom_?(propi|de_?pila)`
`nombres` (except when followed by `completos?`, `y_?apellidos?`, `apellidos?`)

50%

`nombre` (except when followed by list E2) `nom` (except when followed by list E3) `name` (except when followed by list E4)

KNOWN VALUES

ES_L1_NOMBRE – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-nombres.txt	698	70%	Aarón, Aaron, Abdelaziz, Abdelkader, Abdellah, Abderrahim

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word from a list of the 600 given names the INE counts most often among the population of 1 January 2025 — Castilian, Catalan, Galician and Basque names alike —, with the case of the input. `de`, `la`, `los` and `y` stay where they are.

ES_NOMBRES

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `ES_CM_ALFANUM`.

ES_PALABRA_NOMBRE

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `ES_NOMBRE`.

ES_NOMBRE

NAME

Replaces the name with one of the 600 names in `es-nombres.txt`.

ES_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María de los Ángeles	→	Lía de los Eva
JOSÉ ANTONIO	→	ISABEL YASMINA
Jordi	→	Miquel

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

A Spaniard carries two surnames, the first and the second, in the order the parents chose since Ley 20/2011 on the Registro Civil. A column may hold one or both: `García`, `Fernández López`, `de la Fuente`.

HOW IT IS FOUND

COLUMN NAME

ES_L1_APELLIDO – Path

85%

apellidos? primer_?apellido segundo_?apellido apellido_?(1|2|paterno|materno) ape_?(1|2) apell?_?(1|2) cognoms? primer_?cognom segon_?cognom apelidos? abizen(a|ak) last_?names? surnames? family_?names? lname

KNOWN VALUES

ES_L1_APELLIDO – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-apellidos.txt	617	70%	Abad, Acevedo, Acosta, Aguado, Agudo, Aguilar

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word from the 500 first surnames the INE counts most often, with the case of the input; particles stay.

ES_APELLIDOS

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_PALABRA_APELLIDO

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_APELLIDO .

ES_APELLIDO

NAME

Replaces the name with one of the 500 names in es-apellidos.txt .

ES_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
García Fernández	→	Sola Criado
de la Fuente	→	de la Pacheco

8.10 Full name

ES_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Given names and both surnames in one column, in the Spanish order — José Antonio García Fernández — or with the surnames first and a comma, GARCÍA FERNÁNDEZ, JOSÉ ANTONIO , as registers and lists write them.

HOW IT IS FOUND

COLUMN NAME ES_L1_NOMBRE_COMPLETO – Path

90%	<code>nombres?_?(completos? y_apellidos? apellidos?)</code> <code>apellidos?_?(y_?)?nombres?</code> <code>nombre_(del_ de_la_?)?</code> <code>(cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante investigado testigo medico docente socio heredero donante tutor pensionista jubilado interesado customer patient employee member holder mother father spouse contact person student driver owner)</code> <code>(cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante investigado testigo medico docente socio heredero donante tutor pensionista jubilado interesado customer patient employee member holder mother father spouse contact person student driver owner)_?(nombre nom nom_?)</code> <code>(cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante investigado testigo medico docente socio heredero donante tutor pensionista jubilado interesado customer patient employee member holder mother father spouse contact person student driver owner)</code> <code>nombre_?</code> <code>(madre padre tutor conyuge contacto_?emergencia referencia)</code> <code>nom_?complet</code> <code>nom_?i_?cognoms</code> <code>izen_?abizenak</code> <code>full_?name</code> <code>person_?name</code> <code>razon_?social_?(persona autonomo)</code>
60%	<code>madre</code> <code>padre</code> <code>tutor</code> <code>tutora</code> <code>conyuge</code> <code>representante_?legal</code> <code>apoderado</code> <code>avalista</code> <code>fiador</code> <code>beneficiario</code> <code>heredero</code> <code>titular</code> <code>tomador</code> <code>referencia_?(personal familiar)</code>
50%	<code>nombre</code> <i>(except when followed by list E2)</i> <code>nom</code> <i>(except when followed by list E3)</i> <code>name</code> <i>(except when followed by list E4)</i>

KNOWN VALUES ES_L1_NOMBRE_COMPLETO – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-nombres.txt	698	65%	Aarón, Aaron, Abdelaziz, Abdelkader, Abdellah, Abderrahim
es-detectar-apellidos.txt	617	65%	Abad, Acevedo, Acosta, Aguado, Agudo, Aguilar

Values are split into words, and each word is looked up.
A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Two words are a given name and a surname; three, a given name and two surnames; four, two and two. Each word is replaced from its own list, and the form with a comma is read as surnames, then names.

ES_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `ES_APELLIDO`.

`ES_APELLIDO` **NAME**
Replaces the name with one of the 500 names in `es-apellidos.txt`.

`ES_CM_ALFANUM` **CHARACTER MAPPING**
Maps each character to another of its group (9 groups), keeping length and format.

`ES_NOMBRES` **REGEX DECOMPOSE**
Tries 4 patterns in order and gives each part of the value its own action; when none matches: `ES_CM_ALFANUM`.

`ES_PALABRA_NOMBRE` **REGEX DECOMPOSE**
Matches one pattern and gives each part of the value its own action; when none matches: `ES_NOMBRE`.

`ES_NOMBRE` **NAME**
Replaces the name with one of the 600 names in `es-nombres.txt`.

EXAMPLES

VALUE		MASKED
José Antonio García Fernández	→	Isabel Yasmina Sola Criado
Lucía García	→	Sonia Sola
GARCÍA FERNÁNDEZ, JOSÉ ANTONIO	→	SOLA CRIADO, ISABEL YASMINA

8.11 E-mail

ES_L1_EMAIL

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

An e-mail address.

HOW IT IS FOUND

COLUMN NAME

ES_L1_EMAIL - Path

85%

e_?mail[a-z0-9_]* mail[a-z0-9_]* correo(?:electr[oó]nico)?[a-z0-9_]* dir_?correo
direcci[oó]n?(de_)?correo direcci[oó]n?electr[oó]nica correu(?:electr[oò]nic)?
helbide_?elektronikoa enderezo_?electr[oó]nico

DATA TYPE

ES_L1_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT

ES_L1_EMAIL - Regex

PATTERN	STRENGTH	NOTES
[A-Za-z0-9._%+ '\-]+@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The name and the domain are mapped character by character, and the top-level domain becomes `.test`, reserved for tests: a masked address can never deliver a message.

`ES_EMAIL` **REGEX DECOMPOSE**
Matches one pattern and gives each part of the value its own action; when none matches: `ES_CM_ALFANUM`.

`ES_CM_ALFANUM` **CHARACTER MAPPING**
Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

lucia.garcia@gmail.com

→

nameu.suyvio@pgoeb.test

8.12 Telephone

ES_L1_TELEFONO

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

A Spanish number is nine digits: 6 and 7 for a mobile, 8 and 9 for a landline whose first digits are the province. With Bizum, a mobile number is a payment address as well.

HOW IT IS FOUND

COLUMN NAME

ES_L1_TELEFONO - Path

85%

```
tel tlf tfno telf tel[eé]fono[a-z0-9]* tel_?
(fijo|casa|domicilio|oficina|trabajo|contacto|m[ó]vil) m[ó]vil movil[a-z0-9]* celular
whats_?app bizum n(o|ro|um|umero)_?(tel|tel[eé]fono|m[ó]vil|contacto) tel[eè]fon
m[oò]bil telefonoa sakelako fax phone[a-z0-9]* mobile[a-z0-9]*
```

VALUE FORMAT

ES_L1_TELEFONO - Regex

PATTERN

STRENGTH

NOTES

((\+|00)34[\s-])?[67]\d{2}[\s-]?\d{2,3}[\s-]?\d{2,3}[\s-]?\d{0,2}

80%

((\+|00)34[\s-])?[89]\d{1,2}[\s-]?\d{2,3}[\s-]?\d{2}[\s-]?\d{2}

60%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The country code and the first digit stay, so a masked number still says mobile or landline; the other digits change, and spaces and hyphens stay where they were.

ES_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_DIGITOS .

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

+34 612 34 56 78

→

+34 646 91 61 22

612345678

→

646916122

91 123 45 67

→

96 865 00 60

8.13 Address

ES_L1_DIRECCION

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

SECURE LOOKUP

WHAT IT IS

A street address: type of street, name, number, floor and door — Calle Mayor, 12, 3º B, Avda. de la Constitución 45, bajo, Carrer de Sant Pere, 14.

HOW IT IS FOUND

COLUMN NAME ES_L1_DIRECCION - Path

80% direcci[oó]n[a-z0-9]* (except when preceded by mac , ip , e_?mail , web , url , correo ; except when followed by list E5) domicilio[a-z0-9]* dom_?(particular|fiscal|social_?persona) residencia(_?habitual)? lugar_?(de_?)?residencia nombre_?(de_?la_?)?(v[íi]a|calle) v[íi]a_?(p[úu]blica)? calle adre[çc]a domicili enderezo helbidea address[a-z0-9]* (except when preceded by mac , ip , e_?mail , web , url ; except when followed by list E6)

DATA TYPE ES_L1_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT ES_L1_DIRECCION - Regex

PATTERN	STRENGTH	NOTES
(?i)(calle c avenida avda\.\.? av\.\. plaza pza\.\.? paseo p[ºo]\.\.? camino carretera ctra\.\.? ronda traves[íi]a glorieta r[úu]a carrer avinguda pla[çc]a passeig kalea etorbidea)\s+.{2,60}\d.*	85%	
(?i).*\b\d{1,3}\s*,?\s*(\d{1,2}\s*[ºº] bajo entresuelo [aá]tico izda?\.? dcha?\.?)\b.*	70%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line becomes a fictitious one from a list of 4,000 — calle, avenida, plaza, paseo, and the carrer, rúa and kalea of the other official languages — always the same one for the same input. Municipio and postal code are separate columns and are generalized there.

ES_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in es-direcciones.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Calle Mayor, 12, 3º B	→	Calle Mayor, 150, bajo
Avda. de la Constitución 45, bajo	→	C/ del Pilar, 44, 8º A

8.14 Address complement

ES_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Floor, door, staircase, block, portal, the name of an urbanización, a post-office box: what narrows an address to one home.

HOW IT IS FOUND

COLUMN NAME ES_L1_DIRECCION_COMPLEMENTO - Path

70% piso planta puerta escalera esc portal bloque bl letra_?puerta n(o|ro|um|umero)_?(de_?)?(v[íi]a|calle|portal|casa) num_?via km kil[oó]metro urbanizaci[oó]n_?(nombre)? complemento(_?direcci[oó]n)? resto_?direcci[oó]n apartado(_?(de_?)?correos)? apdo pis porta escala solairua atea p_?o_?box

HOW IT IS MASKED

Character by character, keeping its shape: 3º B stays a floor and a letter.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3º B	→	4º G
Escalera 2	→	Unkocuwe 3

8.15 Bank account (IBAN and CCC)

ES_L1_CUENTA_BANCARIA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

A Spanish account is twenty digits, the Código Cuenta Cliente: four for the bank, four for the branch, **two control digits** and ten for the account, 2100 0418 45 0200051332. The first control digit checks bank and branch, the second the account, each a weighted sum modulo 11. The IBAN puts ES and **two more control digits** in front, those of ISO 13616, modulo 97: ES91 2100 0418 4502 0005 1332.

HOW IT IS FOUND

COLUMN NAME ES_L1_CUENTA_BANCARIA - Path

90%
cuenta_?(bancaria|banco|corriente|ahorros?
|cliente|n[oó]mina|abono|cargo|domiciliaci[oó]n|iban|ccc) n(o|ro|um|umero)_(de_)?
(cuenta|cta) nro_?cta num_?cta cta_?(cte|corriente|bancaria|cargo|abono) iban[a-z0-9_]*
ccc c_c_c c[oó]digo_?cuenta_?cliente compte(_?bancari)? kontu_?zenbakia conta_
banc[aá]ria account_?(no|num|number) bank_?account

VALUE FORMAT ES_L1_CUENTA_BANCARIA - Regex

PATTERN	STRENGTH	NOTES
ES\d{22}		95%
ES\d{2}(\d{4}){5}		95%
\d{4}[\s-]? \d{4}[\s-]? \d{2}[\s-]? \d{10}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The ten digits of the account change; bank, branch and the first control digit stay valid. In an IBAN the plugin's IBAN algorithm masks the account and recomputes the IBAN digits — but not the second control digit, which no foreign IBAN has. The set then recomputes that digit with a state that crosses the account from right to left, carries the old and the new digit to the front, and corrects the IBAN digits for the change from a table of 10,000 lines. Compact or printed in groups of four, the masked IBAN passes both checks; a CCC alone gets its second digit recomputed the same way.

ES_CUENTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_DIGITOS.

ES_IBAN_COMPACTO STRING ALGORITHM CHAIN

Applies ES_IBAN_COMPACTO_1 → ES_IBAN_COMPACTO_2 → ES_IBAN_COMPACTO_3 →

ES_IBAN_COMPACTO_4, in this order. It is made of 34 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_IBAN_IMPRESO STRING ALGORITHM CHAIN

Applies ES_IBAN_IMPRESO_1 → ES_IBAN_IMPRESO_2 → ES_IBAN_IMPRESO_3 → ES_IBAN_IMPRESO_4 , in this order. It is made of 39 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_CCC STRING ALGORITHM CHAIN

Applies ES_CCC_1 → ES_CCC_2 → ES_CCC_RESTAURAR , in this order. It is made of 22 algorithms that repeat the same step position by position; each one is in Appendix A.

EXAMPLES

VALUE		MASKED
ES9121000418450200051332	→	ES4921000418415725647875
ES91 2100 0418 4502 0005 1332	→	ES60 2100 0418 4537 6765 3302
2100 0418 45 0200051332	→	2100 0418 42 0051889034

8.16 Payment card

ES_L1_TARJETA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The number of a credit or debit card.

HOW IT IS FOUND

COLUMN NAME

ES_L1_TARJETA – Path

85%

tarjeta(?:cr[eé]dito|d[eé]bito|n(o|ro|um|umero))? n(o|ro|um|umero)?tarjeta pan
targeta txartela card?(no|num|number) credit?card

VALUE FORMAT

ES_L1_TARJETA – Regex

PATTERN

STRENGTH

NOTES

\d{13,19}

90%

LUHN check digit; after removing [\s\–]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another number that passes the Luhn check, keeping its length and separators.

ES_TARJETA

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

ES_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE		MASKED
4532 0000 0000 0001	→	1913 8236 1564 8970

8.17 Digital wallet

ES_L1_BILLETERA

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The identifier of an electronic or crypto wallet.

HOW IT IS FOUND

COLUMN NAME ES_L1_BILLETERA - Path

85% monedero(_?(digital|electr[oó]nica))? billetera(_?(digital|electr[oó]nica))? wallet(_?(id|address|direccion))? direcci[oó]n?(bitcoin|btc|wallet|cripto) btc?(address|direccion) cartera?(cripto|digital)

VALUE FORMAT ES_L1_BILLETERA - Regex

PATTERN	STRENGTH	NOTES
(bc1 [13])[a-zA-HJ-NP-Z0-9]{25,59}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
bc1qar0srrr7xfkvy5l643lydnw9re59gtzzwf5mdq	→ mh2wis8tsdm0pdjd8v511yqxqg4ze53qkjbvp7dgf

8.18 IP address

ES_L1_IP

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

An IPv4 or IPv6 address. The Court of Justice held in Breyer (C-582/14) that a dynamic IP address is personal data for a provider who can lawfully obtain the means to identify the subscriber.

HOW IT IS FOUND

COLUMN NAME ES_L1_IP - Path

85% ip ip?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica) direcci[oó]n?ip dir?ip adre[ç]a?ip ipv[46] remote?addr(ess)? client?ip host?ip

VALUE FORMAT ES_L1_IP - Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)		100%
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}		90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet becomes a number from 1 to 254; an IPv6 address is mapped character by character, staying hexadecimal.

ES_IP **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **ES_CM_HEX**.

ES_OCTETO **NUMERIC MAPPING**

Maps the number to another between 1 and 254.

ES_CM_HEX **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

83.45.120.12

MASKED

→ 75.51.254.94

8.19 Device identifier

ES_L1_DISPOSITIVO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

MAC address, IMEI, IMSI, advertising identifier, session identifier.

HOW IT IS FOUND

COLUMN NAME

ES_L1_DISPOSITIVO - Path

80%

imei imsi iccid mac mac_?address direcci[oó]n_?mac device_(id|uuid|serial) id_?
(dispositivo|equipo|terminal) serial_(equipo|terminal|dispositivo) advertising_?id idfa
gaid session_?id id_?sesi[oó]n

VALUE FORMAT

ES_L1_DISPOSITIVO - Regex

PATTERN

STRENGTH

NOTES

([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}

100%

\\d{15}

80% LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character with hexadecimal letters in their own group, so a MAC stays a MAC; digits stay digits.

ES_CM_HEX

CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

3c:22:fb:9a:10:e4

MASKED

→ 5e:83:bb:3c:31:f9

8.20 Cookie and tracking identifier

ES_L1_COOKIE

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The value of a cookie or a tracking identifier. Article 22.2 of the Ley 34/2002 de servicios de la sociedad de la información subjects them to consent, and the AEPD's guide on cookies treats them as personal data.

HOW IT IS FOUND

COLUMN NAME

ES_L1_COOKIE - Path

80%

cookie(_?(id|value|valor|nombre))? cookies _?ga _?gid fbp fbclid utm_
(source|medium|campaign|term|content) id_(navegador|browser|visitante) visitor_?id
tracking_?id client_?id

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
GA1.2.123456789.1700000000	→	ZE0.5.891552838.7889916184

8.21 Vehicle plate

ES_L1_MATRICULA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Since September 2000 a Spanish plate is four digits and three consonants, 1234 BCD — no vowels, and neither Ñ nor Q. The older provincial plates carry the province, M-1234-AB , and special plates a prefix, E for works vehicles, C for mopeds.

HOW IT IS FOUND

COLUMN NAME

ES_L1_MATRICULA – Path

85%

matr[ií]cula(_?(veh[ií]culo|coche|moto|turismo))?(*except when followed by alumno , estudiante , acad[eé]mica , universitaria , curso , profesional*) n(o|ro|um|umero)?matr[ií]cula placa(_?matr[ií]cula)? matr[ií]cula_?vehicle license_?plate plate(_?(no|number))?

VALUE FORMAT

ES_L1_MATRICULA – Regex

PATTERN	STRENGTH	NOTES
\d{4}[\s-]?[BCDFGHJKLMNPSTVWXYZ]{3}		90%
[A-Z]{1,2}[\s-]?[A-Z]{1,2}		60%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The digits change, and the letters of the current series change **inside the alphabet the Dirección General de Tráfico uses**, so a masked plate is still a plate. The province and the prefix stay.

ES_MATRICULA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

ES_CM_DIGITOS_LETRAS .

ES_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

ES_CM_MATRICULA

CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

ES_CM_DIGITOS_LETRAS

CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1234 BCD	→	9707 ZSB
M-1234-AB	→	M-9707-MX

8.22 Vehicle identification

ES_L1_VEHICULO

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The frame number (VIN, bastidor) and the numbers of the registration and inspection documents.

HOW IT IS FOUND

COLUMN NAME ES_L1_VEHICULO - Path

85% vin bastidor n(o|ro|um|umero)?(de_)?(bastidor|chasis|motor|serie|vin) motor_
n(o|ro|um|umero) itv n(o|ro|um|umero)?(de_)?itv permiso?(de_)?circulaci[oó]n ficha_
t[eé]cnica

VALUE FORMAT ES_L1_VEHICULO - Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NPR-Z0-9]{17}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
VSSZZZ6JZ9R123456	→ WSJHYJ5WR0X792843

8.23 Referencia catastral

ES_L1_REFERENCIA_CATASTRAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The twenty characters the Catastro gives every property: for an urban one, seven digits for the block and parcel and seven for the map sheet, 9872023 VH57975 ; for a rural one, the municipio, the sector, the polígono and the parcel; then four digits for the unit inside it and **two control letters**. Each letter is a weighted sum of eleven characters modulo 23. Article 51 of the Texto Refundido de la Ley del Catastro Inmobiliario makes the holder of a property a protected datum, and the reference beside a person's name is that link.

HOW IT IS FOUND

COLUMN NAME ES_L1_REFERENCIA_CATASTRAL - Path

90% ref(erencia)?_catastral rc?(inmueble|finca|catastral) n(o|ro|um|umero)?(de_)?
(finca|finca?registral|registral|inmueble) finca?registral catastro refer[eè]ncia_
cadastral erreferentzia?katastrala cadastral?reference

VALUE FORMAT ES_L1_REFERENCIA_CATASTRAL – Regex

PATTERN	STRENGTH	NOTES
<code>\d{7}[A-Z0-9]{7}\d{4}[A-Z]{2}</code>		90%
<code>\d{5}[A-Z]\d{12}[A-Z]{2}</code>		90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The digits that name the parcel change — the first seven of an urban reference, the five of the parcel of a rural one — and the map sheet or the polígono stay, which say where the property is no more precisely than a district. Only one control letter depends on what changed, and it is **recomputed** by a state that crosses the reference with the weight of each position, carried over the characters that do not count. A reference written in groups, or only the fourteen characters of the parcel, gets its parcel digits changed without the letters.

ES_REFERENCIA_CATASTRAL **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_RC_URBANA **STRING ALGORITHM CHAIN**

Applies ES_RC_URBANA_1 → ES_RC_URBANA_2 → ES_RC_URBANA_3 , in this order. It is made of 38 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_RC_RUSTICA **STRING ALGORITHM CHAIN**

Applies ES_RC_RUSTICA_1 → ES_RC_RUSTICA_2 , in this order. It is made of 31 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
9872023VH5797S0001WX	→	1064025VH5797S0001QX
8943507PB5284S0001KR	→	1690206PB5284S0001ZR

8.24 CUPS (supply point)

ES_L1_CUPS

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The Código Universal del Punto de Suministro of an electricity or gas supply: ES , four digits for the distributor, twelve for the point and **two control letters** — the sixteen digits modulo 529, divided by 23 and read in the table of the DNI — sometimes followed by 0F . A CUPS names a home: the bill, the consumption curve of the smart meter and the social bonus all hang from it.

HOW IT IS FOUND

COLUMN NAME ES_L1_CUPS – Path

95% cups c_u_p_s c[oó]digo?(universal_)?(del_)?punto?(de_)?suministro punto?(de_)?
suministro cups?(luz|gas|electricidad|electronico)

VALUE FORMAT ES_L1_CUPS – Regex

PATTERN	STRENGTH	NOTES
<code>ES\d{16}[A-Z]{2}(\d[A-Z])?</code>		95%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The distributor stays, the twelve digits change, and the two letters are **recomputed** by a state of three digits that crosses the value with a table of 6,877 lines. A suffix stays.

ES_CUPS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

ES_CUPS_CADENA STRING ALGORITHM CHAIN

Applies ES_CUPS_CADENA_1 → ES_CUPS_CADENA_2 → ES_CUPS_CADENA_3 → ES_CUPS_CADENA_4 , in this order. It is made of 34 algorithms that repeat the same step position by position; each one is in Appendix A.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
ES1234123456789012JY	→	ES1234110858563136HA
ES002100000000001JN0F	→	ES0021668892878974DQ0F

8.25 Contract and customer number

ES_L1_CONTRATO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Numbers of contract, policy, loan, customer, subscriber, claim or employee — each one a key to one person in its own system.

HOW IT IS FOUND

COLUMN NAME

ES_L1_CONTRATO - Path

70%

```
n(o|ro|um|umero)?(contrato|p[ó]liza|pr[eé]stamo|solicitud|expediente_?
(administrativo|interno)|tr[aá]mite|referencia|cliente|socio|abonado|suministro|servicio|caso|
ticket|siniestro|reclamaci[ó]n|incidencia) contrato?(n(o|ro|um|umero)) c[ó]digo_?
(cliente|socio|empleado|afiliado|abonado) id?(cliente|socio|empleado|afiliado) n(o|ro)?
(empleado|personal|registro_?personal) nrp matr[ií]cula?(empleado|personal)
```

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
CT-123456	→	NG-557411

8.26 User name and social profile

ES_L1_USUARIO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

A login, an alias, a profile on a social network.

HOW IT IS FOUND

COLUMN NAME ES_L1_USUARIO - Path

70% usuario user_?name username login alias apodo nick(_?name)? perfil_?
(instagram|facebook|twitter|tiktok|linkedin|x) instagram facebook twitter tiktok
linkedin red_?social handle usuari erabiltzailea

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

@lucia_garcia

→

@nameu_suyvio

8.27 Credential

ES_L1_CREDENCIAL

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Passwords and their hashes, PINs, security codes, tokens, API keys, the Cl@ve PIN, answers to security questions.

HOW IT IS FOUND

COLUMN NAME ES_L1_CREDENCIAL - Path

90% contrase[nñ]a clave *(except when followed by catastral, primaria, for[aá]nea, valor, producto, cuenta_?cotizacion)* password passwd pwd pass hash_?(clave|contrasena|password) pin
c[oó]digo_?(seguridad|verificaci[oó]n|acceso|otp) cvv cvc token(_?(acceso|refresh|api))?
access_?token refresh_?token api_?key llave_?(api|privada) secreto secret otp
cl@ve_?pin clave_?pin certificado_?(digital|electr[oó]nico)_?(clave|pin|password)
pregunta_?secreta respuesta_?secreta frase_?semilla seed_?phrase contrasenya
pasahitza

HOW IT IS MASKED

Every character becomes X. A credential is never useful in a copy, and a hash of a real password can be attacked offline.

ES_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

Clave#2024

→

XXXXXXXXXX

8.28 Image and voice

ES_L1_IMAGEN

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Photographs, the image of an identity document, video surveillance, recorded calls — or the path to them. The image of a person is a fundamental right in article 18.1 of the Constitution and Ley Orgánica 1/1982, and the LOPDGDD gives video surveillance its own article 22.

HOW IT IS FOUND

COLUMN NAME ES_L1_IMAGEN - Path

85% foto(graf[ií]a)?[a-z0-9]* imagen_?(persona|rostro|perfil|dni|documento) avatar selfie retrato video_?(persona|entrevista|vigilancia) videovigilancia grabaci[oó]n(_?(llamada|voz|c[aá]mara))? audio_?(voz|llamada) url_?foto ruta_?(foto|imagen) fotografia irudia photo[a-z0-9]* picture image_(url|path|person)

HOW IT IS MASKED

Every character becomes X, so a path or a reference no longer leads to the file.

ES_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
/fotos/persona_12.jpg	→ XXXXXXXXXXXXXXXXXXXXX

8.29 Geolocation

ES_L1_GEOLOCALIZACION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, alone or as a pair. Article 90 of the LOPDGDD regulates the geolocation of workers.

HOW IT IS FOUND

COLUMN NAME ES_L1_GEOLOCALIZACION - Path

85% lat latitud lon lng longitud coordenadas? coord_?[xy] utm_?[xy] geo_(lat|lon|lng|loc|localizacion|posicion) georreferenciaci[oó]n geolocalizaci[oó]n gps(_?(ubicaci[oó]n|posici[oó]n|coordenadas))? ubicaci[oó]n_?gps latitude longitude

50% long

VALUE FORMAT ES_L1_GEOLOCALIZACION - Regex

PATTERN	STRENGTH	NOTES
(2[7-9] 3\d 4[0-4])\.\d{3,}\s*,\s*~?(1[0-8] \d)\.\d{3,}	90%	
(3[5-9] 4[0-4])\.\d{4,}	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and the first decimal stay — about 11 km — and the other decimals change: the place is blurred, not moved to another region.

ES_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
40.416775,-3.703790	→ 40.436747,-3.707721

8.30 Free text

ES_L1_TEXTO_LIBRE

COLUMN NAME

DATA TYPE

VALUE FORMAT

FREE TEXT REDACTION

WHAT IT IS

Observations, comments, descriptions of a complaint or an incident: text where anything may have been typed.

HOW IT IS FOUND

COLUMN NAME

ES_L1_TEXTO_LIBRE - Path

60%

observaci[oó]n(es)? obs comentarios? notas? anotaci[oó]n(es)? descripci[oó]n?
(queja|reclamaci[oó]n|solicitud|caso|hechos|incidencia|atenci[oó]n|denuncia) detalle_
(reclamaci[oó]n|solicitud|caso|incidencia) hechos relato motivo_(de_?la_?)?
(reclamaci[oó]n|solicitud|llamada) justificaci[oó]n mensaje *(except when preceded by list E7; except when followed by list E8)* texto(_?libre)? resumen_(caso|atenci[oó]n) queja reclamaci[oó]n
observacions oharrrak remarks? comments? notes? free_?text memo

DATA TYPE

ES_L1_TEXTO_LIBRE - Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT

ES_L1_TEXTO_LIBRE - Regex

PATTERN

STRENGTH

NOTES

\d{8}-?[TRWAGMYFPDXBNJZSQVHLCKE]	80%	anywhere in the value
[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}	70%	anywhere in the value
[67]\\d{2}[\\s\\-]?\\d{3}[\\s\\-]?\\d{3}	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction replaces DNIs, NIEs, e-mails, phones, cards, IBANs and CCCs, Seguridad Social numbers and IP addresses with [DAT0], and the 1,100 given names and surnames of the set with [NOMBRE].

ES_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 10 patterns with [DAT0], and the 2,494 terms of es-texto-nombres.txt with [NOMBRE].

EXAMPLES

VALUE	MASKED
Cliente García, DNI 12345678Z, correo l.garcia@gmail.com, móvil 612345678.	→ Cliente [NOMBRE], DNI [DAT0], correo [DAT0], móvil [DAT0].

Quasi-identifiers

Data that identifies nobody alone and identifies almost anybody together. Recital 26 of the Regulation asks how identifiable a person is by "all the means reasonably likely to be used", singling out included — and a birth date, a sex and a small municipio are such means. These columns are not emptied — a test needs ages and places that behave — they are coarsened until a combination stops pointing at one person.

9.1 Birth date

ES_L2_FECHA_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The birth date — with sex and municipio, the combination that singles people out.

HOW IT IS FOUND

COLUMN NAME ES_L2_FECHA_NACIMIENTO – Path

90% (fecha|fec|fch|f)_?(de_?)?nac(imiento)? fnac fechanac(imiento)? cumplea[n]os data_? (de_?)?naixement data_?(de_?)?nacemento jaiotze_?data dob date_?of_?birth birth_?date birthday

DATA TYPE ES_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted by up to 60 days either way, the same shift for the same date: ages and generations stay, the link to a register goes.

ES_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

9.2 Year of birth

ES_L2_ANIO_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The year alone.

HOW IT IS FOUND

COLUMN NAME ES_L2_ANIO_NACIMIENTO – Path

90% a[n]o_?(de_?)?nac(imiento)? anio_?nac(imiento)? any_?(de_?)?naixement year_?of_?birth birth_?year yob

DATA TYPE ES_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit changes: 1985 becomes 198x.

ES_ANIO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

ES_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

9.3

Age

ES_L2_EDAD

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

An age in years.

HOW IT IS FOUND

COLUMN NAME ES_L2_EDAD – Path

85%

```
edad(_?(actual|a[nñ]os|paciente|afiliado|cliente|al_?  
(ingreso|diagn[ó]stico|fallecimiento)))? grupo_?(de_)?edad tramo_?(de_)?edad rango_?  
(de_)?edad edat adina age(_?(years|group))?
```

DATA TYPE ES_L2_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit changes; 100 and over becomes 90, because a centenarian is rare enough to be found.

ES_EDAD **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

9.4

Date of a life event

ES_L2_FECHA_EVENTO

COLUMN NAME **DATA TYPE** **DATE SHIFT**

WHAT IT IS

Dates of death, marriage, hiring and dismissal, admission and discharge, sick leave, arrest and sentence, issue and expiry of a document.

HOW IT IS FOUND

COLUMN NAME ES_L2_FECHA_EVENTO - Path

80% (fecha|fec|fch|f)?(de_)?
(defunci[oó]n|fallecimiento|matrimonio|divorcio|alta|baja|ingreso|cese|despido|jubilaci[oó]n|hospitalizaci[oó]n|diagn[oó]stico|atenci[oó]n|consulta|parto|detenci[oó]n|sentencia|condena|expedici[oó]n?(dni|documento)|caducidad_?
(dni|nie|documento)|vacunaci[oó]n|intervenci[oó]n|accidente|incapacidad|baja_?m[eé]dica)
fec?(exp|expedicion|defuncion|alta|baja) date_?of_
(death|marriage|hire|admission|discharge)

DATA TYPE ES_L2_FECHA_EVENTO - Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted by up to 30 days either way.

ES_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE

MASKED

2021-03-15

→

2021-03-05T00:00

9.5 Sex

ES_L2_SEX0

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Sex as registered: H/M, V/M, Hombre/Mujer, Femenino/Masculino, 1/2, and the Catalan Home/Dona.

HOW IT IS FOUND

COLUMN NAME ES_L2_SEX0 - Path

85% sexo(_?(biol[oó]gico|registrar|paciente|afiliado|cliente))? (tp|tipo|cod|cd|id)?sexo
g[eé]nero (except when followed by *identidad*, *sentido*) sexe sexua sex gender (except when followed by
identity)

KNOWN VALUES ES_L2_SEX0 - List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-sexo.txt	14	50%	h, m, v, f, hombre, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: an H/M column stays H/M. A single M is read as mujer, the convention of the Spanish administration; a column that codes sex F/M, as the machine-readable zone of the DNI does, should get an algorithm of its own.

ES_SEX0 REGEX DECOMPOSE

Tries 8 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_SEX0_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-femenino-masculino.txt, chosen by a keyed hash.

ES_SEX0_MUJER_HOMBRE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-mujer-hombre.txt`, chosen by a keyed hash.

ES_SEX0_DONA_HOME **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-dona-home.txt`, chosen by a keyed hash.

ES_SEX0_FEMALE_MALE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-female-male.txt`, chosen by a keyed hash.

ES_SEX0_H_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-h-m.txt`, chosen by a keyed hash.

ES_SEX0_V_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-v-m.txt`, chosen by a keyed hash.

ES_SEX0_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-f-m.txt`, chosen by a keyed hash.

ES_SEX0_1_2 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
H	→	H
Mujer	→	Hombre
Femenino	→	Femenino

9.6 Municipio

ES_L2_MUNICIPIO

COLUMN NAME

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

The municipio of residence, birth or registration — Valdelageve, Alacant, La Guijarrosa —, as the INE writes it, with the article in front or behind, in any official language, or with its province beside it.

HOW IT IS FOUND

COLUMN NAME ES_L2_MUNICIPIO – Path

85% `municipio(_?(residencia|nacimiento|domicilio|empadronamiento))?` (except when followed by `cod`, `codigo`, `id`, `ine`) `localidad(_?(residencia|nacimiento|domicilio))?` `poblaci[oó]n` (except when followed by `total`, `activa`, `objetivo`) `ciudad(_?(residencia|nacimiento|domicilio))?` `municipi` `poblaci[oó]` `concello` `udallerria` `herria` `(nom|nombre|desc)_?` `(municipio|localidad|poblacion|ciudad)` `lugar_?(de_)?nacimiento` `city` `town` `municipality`

KNOWN VALUES ES_L2_MUNICIPIO – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-municipios.txt	10,872	80%	Alegria-Dulantzi, Alegria-Dulantzi, Amurrio, Aramaio, Artziniega, Armiñón

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A municipio of fewer than 20,000 inhabitants becomes the **nearest municipio of at least 20,000 in the same province**; a larger one stays, and so do the province and the comunidad. A name is generalized only when every municipio that bears it is small; written with its province, the same rule applies inside it and the province stays.

ES_MUNICIPIO DATA CLEANSING

Replaces each value found in `es-municipios-generalizados.txt` (68,972 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Valdelageve	→	Salamanca
Valdelageve (Salamanca)	→	Salamanca (Salamanca)
La Guijarrosa	→	Montilla
Alacant	→	Alacant

9.7 INE code of the municipio

ES_L2_CODIGO_MUNICIPIO

COLUMN NAME

VALUE FORMAT

DATA CLEANSING

WHAT IT IS

The code of the Instituto Nacional de Estadística: two digits for the province and three for the municipio, 37334 , often followed by its check digit.

HOW IT IS FOUND

COLUMN NAME

ES_L2_CODIGO_MUNICIPIO - Path

90%

```
(cod|codigo|cd|id)?(ine_?)(municipio|mun|municipal|localidad|poblacion)(_?
(ine|residencia|nacimiento|domicilio))? c[0ó]digo_?ine cod_?ine ine_?(municipio|code)
cmun c_?mun codmun municipio_?ine municipality_?code
```

VALUE FORMAT

ES_L2_CODIGO_MUNICIPIO - Regex

PATTERN

STRENGTH

NOTES

```
(0[1-9] | [1-4]\d | 5[0-2])\d{3}\d?
```

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The code of a small municipio becomes the code of the municipio its name goes to, with that municipio's own check digit, so a masked code agrees with the masked name and never leaves its province.

ES_CODIGO_MUNICIPIO DATA CLEANSING

Replaces each value found in `es-codigos-municipio-generalizados.txt` (15,400 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
37334	→	37274
28079	→	28079

9.8 Postal code

ES_L2_CODIGO_POSTAL

COLUMN NAME

VALUE FORMAT

DATA CLEANSING

WHAT IT IS

Five digits, the first two the province. A postal code of a rural area may cover a single village of a few dozen people.

HOW IT IS FOUND

COLUMN NAME

ES_L2_CODIGO_POSTAL - Path

90%

c[oó]digo_?postal cod_?postal codpostal cp c_p cp_?

(residencia|domicilio|cliente|envio) dp codi_?postal posta_?kodea zip(_?code)? postal_?

code

VALUE FORMAT

ES_L2_CODIGO_POSTAL - Regex

PATTERN

STRENGTH

NOTES

(0[1-9] | [1-4]\d|5[0-2])\d{3}

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A postal code whose main municipio is small becomes the main postal code of the municipio it is generalized to; a code of a large municipio stays. The province digits never change.

ES_CODIGO_POSTAL

DATA CLEANSING

Replaces each value found in es-codigos-postales-generalizados.txt (8,638 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE

MASKED

37766

→

37001

28013

→

28013

9.9 Nationality

ES_L2_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. It is not a special category of article 9, but Ley 15/2022 forbids discrimination "con independencia de su nacionalidad", and in a small place a nationality points at a few families.

HOW IT IS FOUND

COLUMN NAME

ES_L2_NACIONALIDAD - Path

85%

nacionalidad(_?(origen|actual))? pa[ií]s_(de_)?

(nacimiento|origen|nacionalidad|procedencia) ciudadan[ií]a nacionalitat naziotasuna

nationality citizenship country_of_birth

KNOWN VALUES

ES_L2_NACIONALIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-nacionalidades.txt

75

70%

Española, Espanola, Marroquí, Marroqui, Rumana, Colombiana

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the 27 nationalities most frequent in Spain.

ES_NACIONALIDAD **SECURE LOOKUP**

Replaces the value with one of the 27 values in `es-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Georgiana

→

Colombiana

9.10 Residence status

ES_L2_SITUACION_ADMINISTRATIVA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The status of a foreign national under the Ley Orgánica 4/2000 de extranjería: temporary or long-term residence, a family member of an EU citizen, an applicant for international protection, a refugee, arraigo, irregular. Ley 15/2022 forbids discrimination whether a person "disfruta o no de residencia legal".

HOW IT IS FOUND

COLUMN NAME

ES_L2_SITUACION_ADMINISTRATIVA - Path

90%

situaci[oó]n?(administrativa|de?residencia|de?extranjer[ií]a|migratoria) tipo?(de?)?
(residencia|autorizaci[oó]n|permiso) autorizaci[oó]n?(de?)?(residencia|trabajo|estancia)
permiso?(de?)?(residencia|trabajo) estatuto?(de?)?(refugiado|ap[aá]trida)
protecci[oó]n?internacional solicitante?(de?)?asilo asilo arraigo extranjer[ií]a
migration?status immigration?status residence?permit

KNOWN VALUES

ES_L2_SITUACION_ADMINISTRATIVA - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-
situacion-
administrativa.tx
t

33

70%

Residencia temporal, Residencia de larga duración, Residencia de larga
duracion, Residencia de larga duración UE, Residencia de larga duracion UE,
Certificado de registro de ciudadano de la UE

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of statuses; yes/no flags stay flags.

ES_SITUACION_ADMINISTRATIVA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_SITUACION_ADMINISTRATIVA_LISTA

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt` , chosen by a keyed hash.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

ES_SITUACION_ADMINISTRATIVA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 13 values in `es-situacion-administrativa.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Residencia en trámite

→ **Tarjeta de familiar de ciudadano de la UE**

9.11 Marital status

ES_L2_ESTADO_CIVIL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Marital status, including the pareja de hecho of the regional registers.

HOW IT IS FOUND

COLUMN NAME

ES_L2_ESTADO_CIVIL - Path

85%

estado_?civil est_?civil (cod|tipo|id)_?estado_?civil pareja_?de_?hecho estat_?civil
egoera_?zibila marital_?status civil_?status

KNOWN VALUES

ES_L2_ESTADO_CIVIL - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-estado-civil.txt	17	70%	Soltero/a, Casado/a, Pareja de hecho, Separado/a, Divorciado/a, Viudo/a
------------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within its vocabulary; a numeric code by another code.

ES_ESTADO_CIVIL **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ESTADO_CIVIL_LISTA .

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-si-no.txt` , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-true-false.txt` , chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt` , chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_ESTADO_CIVIL_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 6 values in `es-estado-civil-codigos.txt`, chosen by a keyed hash.

ES_ESTADO_CIVIL_LISTA **SECURE LOOKUP**

Replaces the value with one of the 6 values in `es-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Unión de hecho	→	Soltero/a
2	→	4

9.12 Occupation

ES_L2_OCUPACION

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Profession, job title, occupational category, or its code in the Clasificación Nacional de Ocupaciones (CNO-11).

HOW IT IS FOUND

COLUMN NAME

ES_L2_OCUPACION - Path

80%

`ocupaci[oó]n profes[ió]n oficio cno(_?11)? (cod|codigo)?(ocupacion|profesion|cno) puesto?(de_)?trabajo categor[ií]a?profesional grupo?(de_)?cotizaci[oó]n cargo?(actual|empleado) professi[oó] lanbidea occupation profession job?title`

50%

`cargo puesto`

HOW IT IS MASKED

Replaced from a list of common occupations; a CNO code gets other digits.

ES_OCUPACION_0_CODIGO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `ES_OCUPACION`.

ES_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

ES_OCUPACION **SECURE LOOKUP**

Replaces the value with one of the 37 values in `es-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Director de operaciones	→	Electricista
2211	→	9068

9.13 Employer

ES_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The name of the company a person works for — in a small town, one employer may be enough to tell who someone is.

HOW IT IS FOUND

COLUMN NAME ES_L2_EMPLEADOR – Path

90% empleador(_?(nombre|raz[oó]n?social))?(nombre|nom)?(empleador|empresa?donde?trabaja) empresa?(donde?)?(trabaja|empleadora) lugar?(de?)?trabajo centro?(de?)?trabajo empresa?empleadora empresa?actual ocupador employer(_?name)? workplace

HOW IT IS MASKED

Replaced by a fictitious company.

ES_EMPLEADOR **SECURE LOOKUP**

Replaces the value with one of the 24 values in es-empleadores.txt, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Corporación Industrial del Atlántico S.A.	→	Laboratorios Vida Sana S.L.

9.14 Level of education

ES_L2_NIVEL_EDUCATIVO

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

The highest level of studies, from no studies to a doctorate, or its code.

HOW IT IS FOUND

COLUMN NAME ES_L2_NIVEL_EDUCATIVO – Path

80% nivel?(educativo|de?estudios|acad[eé]mico|formativo|de?formaci[oó]n) estudios(_?(terminados|finalizados|realizados|m[aá]ximos))? titulaci[oó]n(_?acad[eé]mica)? formaci[oó]n?acad[eé]mica m[aá]ximo?nivel cned nivell?(d_?)?estudis ikasketa?maila education(_?level)?

KNOWN VALUES ES_L2_NIVEL_EDUCATIVO – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-nivel-educativo.txt	32	60%	Sin estudios, Educación primaria incompleta, Educacion primaria incompleta, Educación primaria, Educacion primaria, Educación secundaria obligatoria (ESO)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within its vocabulary; a numeric code by another code.

ES_NIVEL_EDUCATIVO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_NIVEL_EDUCATIVO_LISTA .

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-si-no.txt, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-true-false.txt, chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_NIVEL_EDUCATIVO_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 10 values in `es-nivel-educativo-codigos.txt`, chosen by a keyed hash.

ES_NIVEL_EDUCATIVO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 10 values in `es-nivel-educativo.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Licenciatura en curso

→

Formación profesional de grado medio

9.15 School or university

ES_L2_CENTRO_EDUCATIVO

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The school, institute or university a person attends or attended.

HOW IT IS FOUND

COLUMN NAME

ES_L2_CENTRO_EDUCATIVO - Path

75%

centro?(educativo|escolar|de?estudios|docente) colegio instituto ies ceip escuela
universidad facultad escola ikastetxea (nombre|nom)?
(colegio|instituto|universidad|centro) c[oó]digo?(de?)?centro school(_?name)?
university

HOW IT IS MASKED

Replaced by one of a list of centres.

ES_CENTRO_EDUCATIVO **SECURE LOOKUP**

Replaces the value with one of the 14 values in `es-centros-educativos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Universidad de Salamanca

→

Universidad Nacional de Educación a Distancia

9.16 Dependants

ES_L2_PERSONAS_A_CARGO

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Number of children or dependants, members of the household. Three children make a familia numerosa, and a large count is rare.

HOW IT IS FOUND

COLUMN NAME

ES_L2_PERSONAS_A_CARGO – Path

80%

personas_?a_?cargo

n(o|ro|um|umero)_?(de_?)?(hijos|descendientes|dependientes|personas_?a_?cargo|miembros)

hijos

descendientes

miembros_?(de_?la_?)?(unidad_?familiar|hogar)

unidad_?familiar

personas_?(en_?el_?)?hogar

tama[n̄]o_?(de_l_?)?hogar

familia_?numerosa

fills

number_?of_?children

dependents

DATA TYPE

ES_L2_PERSONAS_A_CARGO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Counts from 0 to 5 stay; anything above becomes 5.

ES_CONTEO_LIMITADO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5
2	→	2

Special categories (art. 9 RGPD and art. 9 LOPDGDD)

Article 9.1 of the Regulation prohibits processing these data unless one of the exceptions of article 9.2 applies, and article 9.1 of the LOPDGDD adds that, for ideology, trade union membership, religion, sexual orientation, beliefs and racial or ethnic origin, consent alone does not lift the prohibition "a fin de evitar situaciones discriminatorias". A test copy is none of those exceptions, and processing these data outside them is a very serious infringement (art. 72.1 e). Gender identity and the victims of gender violence join them because Spanish law protects them in their own right: Ley 15/2022 names "identidad sexual" and "expresión de género" among the grounds of discrimination, and Ley Orgánica 1/2004 the intimacy of the victims. Categorical columns are replaced within their own vocabulary, or suppressed outright.

10.1 Racial or ethnic origin

ES_L3_ORIGEN_ETNICO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Self-identified ethnic origin, belonging to the pueblo gitano. Spain does not ask it in the census, but surveys, social services and equality plans do. Article 9.1 of the LOPDGDD makes consent alone insufficient to process data whose main purpose is to identify it.

HOW IT IS FOUND

COLUMN NAME

ES_L3_ORIGEN_ETNICO - Path

95%

etnia origen_?([eé]tnico|racial) grupo_?[eé]tnico pertenencia_?[eé]tnica
autoidenticaci[oó]n_?([eé]tnica|racial) (cod|codigo|tipo|id)_?etnia raza comunidad_
gitana pueblo_?gitano ethnicity race

KNOWN VALUES

ES_L3_ORIGEN_ETNICO - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-origen-etnico.txt	32	90%	Gitana, Blanca o europea, Magrebí o árabe, Magrebi o arabe, Africana subsahariana, Latinoamericana
es-detectar-codigos-banderas.txt	14	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of categories; a numeric code by another code; a yes/no flag stays a flag.

ES_ORIGEN_ETNICO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ORIGEN_ETNICO_LISTA .

ES_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt` , chosen by a keyed hash.

ES_ORIGEN_ETNICO_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 9 values in `es-origen-etnico-codigos.txt` , chosen by a keyed hash.

ES_ORIGEN_ETNICO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 9 values in `es-origen-etnico.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afrodescendiente	→	Blanca o europea
3	→	5

10.2 Religion

ES_L3_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Religious belief or denomination — including the choice of religion class at school and the assignment of tax to the Catholic Church in the income tax return.

HOW IT IS FOUND

COLUMN NAME ES_L3_RELIGION - Path

95% `religi[oó]n` `creencia_?(religiosa)?` `confesi[oó]n_?religiosa` `confesionalidad` `credo`
`culto` `iglesia` `(cod|codigo|tipo)_?religion` `clase_?de_?religi[oó]n` `ense[nñ]anza_?`
`religiosa` `asignatura_?religi[oó]n` `casilla_?iglesia` `asignaci[oó]n_?tributaria_?iglesia`
`religi[oó]` `erlijioa` `religion` `church`

KNOWN VALUES ES_L3_RELIGION - List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-religiones.txt	45	90%	Católica, Catolica, Evangélica o protestante, Evangelica o protestante, Musulmana, Testigo de Jehová

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of religions; a yes/no flag stays a flag.

ES_RELIGION **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_RELIGION_LISTA .

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-si-no.txt` , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-true-false.txt` , chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt` , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt` , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `es-religiones.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Anglicana

→

Testigo de Jehová

10.3 Philosophical beliefs

ES_L3_CONVICCION_FILOSOFICA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Philosophical or moral beliefs, conscientious objection — of a health professional to abortion or euthanasia, for instance, which Ley Orgánica 3/2021 records in a register of objectors.

HOW IT IS FOUND

COLUMN NAME

ES_L3_CONVICCION_FILOSOFICA - Path

90%

```
convicci[oó]n(es)?_?(filos[oó]ficas?|morales?|personales?|[eé]ticas?) creencias?_?
(filos[oó]ficas?|morales?|personales?) ideolog[ií]a (except when followed by pol[ií]tica)
objeci[oó]n?(de_)?conciencia objetor?(de_)?conciencia masoner[ií]a logia veganismo
philosophical_beliefs? beliefs?
```

HOW IT IS MASKED

Suppressed to Sin información : the values share no vocabulary that could be kept.

ES_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_SUPRIMIR .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt` , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt` , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt` , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt` , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `es-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Objetor a transfusiones

→ Sin información

10.4 Political opinion

ES_L3_OPINION_POLITICA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Ideology, self-placement on the left-right scale of 1 to 10 the CIS uses, voting intention or recall.

HOW IT IS FOUND

COLUMN NAME

ES_L3_OPINION_POLITICA - Path

95%

opini[oó]n?pol[ií]tica ideolog[ií]a?pol[ií]tica preferencias?_
(pol[ií]tica|partidista|electoral) autoubicaci[oó]n?ideol[oó]gica escala?ideol[oó]gica
orientaci[oó]n?pol[ií]tica tendencia?pol[ií]tica intenci[oó]n?(de_)?voto recuerdo?
(de_)?voto simpat[ií]a?pol[ií]tica political?(opinion|orientation|view|preference)
voting?intention

KNOWN VALUES

ES_L3_OPINION_POLITICA - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-opiniones-
politicas.txt

23

70%

Izquierda, Centroizquierda, Centro, Centroderecha, Derecha,
Ninguna

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of positions; a value of the scale by another value of the scale.

ES_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_OPINION_POLITICA_LISTA

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_OPINION_POLITICA_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 10 values in `es-opiniones-politicas-codigos.txt`, chosen by a keyed hash.

ES_OPINION_POLITICA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 7 values in `es-opiniones-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Progresista	→	Derecha
7	→	2

10.5 Party membership

ES_L3_AFILIACION_PARTIDARIA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Membership of a political party, a member's fee, militancy.

HOW IT IS FOUND

COLUMN NAME

ES_L3_AFILIACION_PARTIDARIA - Path

95%

```
partido(?:pol[í]tico)?(?:afiliaci[oó]n|nombre|militancia))? afiliaci[oó]n?(
pol[í]tica|partidista|partido) militancia(?:pol[í]tica)? militante cuota?(de_)?
(afiliado|militante) (cod|codigo|nombre|nom)_?partido partit alderdia political_?party
party_?membership
```

KNOWN VALUES

ES_L3_AFILIACION_PARTIDARIA - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-partidos.txt

34

80%

PP, PSOE, Vox, Sumar, Podemos, ERC

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another party of the Spanish parliamentary spectrum; a yes/no flag stays a flag.

ES_PARTIDO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `ES_PARTIDO_LISTA`.

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 16 values in `es-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ciudadanos	→	ERC
S	→	S

10.6 Trade union membership

ES_L3_AFILIACION_SINDICAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Membership of a union, the union dues the payroll deducts, union delegates and works councils, union time off.

HOW IT IS FOUND

COLUMN NAME

ES_L3_AFILIACION_SINDICAL - Path

95%

`sindicato(_?(nombre|afiliado|afiliaci[oó]n|c[oó]digo))?` `sindicad[oa]` `afiliado_?sindicato`
`afiliaci[oó]n_?sindical` `cuota_?sindical` `descuento_?sindical` `delegado_?sindical`
`representante_?(de_?los_?)?trabajadores` `comit[eé]_?(de_?)?empresa` `horas_?sindicales`
`cr[eé]dito_?horario` `sindicat` `sindikatua` `trade_?union` `union_?member(ship)?`

KNOWN VALUES

ES_L3_AFILIACION_SINDICAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

`es-detectar-`
`sindicatos.txt`

20

60%

CCOO, Comisiones Obreras, UGT, Unión General de Trabajadores, Union General de Trabajadores, CSIF

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Suppressed to `Sin información`; a yes/no flag stays a flag.

ES_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `ES_SUPRIMIR`.

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `es-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
CC00	→	Sin información
S	→	S

10.7 Biometric data

ES_L3_BIOMETRICO

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Fingerprint and face templates, voice prints, digitized handwritten signatures: "biometric data for the purpose of uniquely identifying a natural person", in the words of article 9.1.

HOW IT IS FOUND

COLUMN NAME

ES_L3_BIOMETRICO - Path

90%

```
biometr[ií]a[a-z]* biom[eé]trico[a-z]* huella(_?(dactilar|digital))?(_?(template|plantilla|imagen|hash))? huellas dactilar template?(facial|huella|biometrico)
plantilla?(facial|biom[eé]trica) rostro?(hash|template) reconocimiento?(facial|de_?
voz) firma?(biom[eé]trica|manuscrita?digitalizada) iris voz?(biom[eé]trica|template)
empremta fingerprints? face?(template|hash|encoding) biometric[a-z]*
```

DATA TYPE

ES_L3_BIOMETRICO - Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. A biometric template cannot be masked into another valid one, and a real one should never reach a copy.

ES_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

10.8 Genetic data

ES_L3_GENETICO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

DNA profiles, genetic tests, mutations such as BRCA, newborn screening.

HOW IT IS FOUND

COLUMN NAME ES_L3_GENETICO – Path

90% `adn` `dna` `gen[eé]tic[oa]s?` `datos?_?gen[eé]ticos?` `genoma` `genotip[a-z]*` `prueba_?`
`(gen[eé]tica|de_?adn|de_?paternidad)` `perfil_?gen[eé]tico` `mutaci[oó]n` `brca[12]?`
`cariotipo` `cribado_?neonatal` `prueba_?del_?tal[oó]n` `genetic[a-z]*`

HOW IT IS MASKED

Every character becomes X .

ES_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
BRCA1 positivo	→ XXXXXXXXXXXXX

10.9 Sexual orientation

ES_L3_ORIENTACION_SEXUAL

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Sexual orientation, as recorded in surveys, equality plans or health records.

HOW IT IS FOUND

COLUMN NAME ES_L3_ORIENTACION_SEXUAL – Path

95% `orientaci[oó]n_?sexual` `preferencias?_?sexuales?` `(cod|codigo|tipo)_?orientacion_?sexual`
`orientaci[oó]_?sexual` `sexual_?orientation`

KNOWN VALUES ES_L3_ORIENTACION_SEXUAL – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-orientaciones-sexuales.txt	14	80%	Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of orientations.

ES_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ORIENTACION_SEXUAL_LISTA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt` , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt` , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt` , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

ES_ORIENTACION_SEXUAL_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `es-orientaciones-sexuales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Homosexual

→ **Pansexual**

10.10 Sex life

ES_L3_VIDA_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Data concerning a person's sex life: activity, partners, practices.

HOW IT IS FOUND

COLUMN NAME

ES_L3_VIDA_SEXUAL - Path

90%

vida_?sexual actividad_?sexual conducta_?sexual pr[aá]cticas?_?sexuales? parejas?_?sexuales? n(o|ro|um|umero)_?parejas sexualmente_?activ[oa] relaciones_?sexuales sex(ual)?_?life sexual?(activity|behavio(u)?r|partners)

HOW IT IS MASKED

Suppressed to `Sin información`; a yes/no flag stays a flag.

ES_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `ES_SUPRIMIR`.

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

ES_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `es-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Activa → Sin información

10.11 Gender identity

ES_L3_IDENTIDAD_GENERO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Gender identity and expression, the name a person goes by, a registry rectification of sex. Ley 4/2023 lets a person rectify the sex registered in the Registro Civil by their own declaration, and Ley 15/2022 names "identidad sexual" and "expresión de género" among the grounds of discrimination.

HOW IT IS FOUND

COLUMN NAME

ES_L3_IDENTIDAD_GENERO - Path

95%

identidad?(de_)?g[eé]nero identidad?sexual (cod|codigo|tipo)?identidad?genero g[eé]nero?(sentido|autopercebido) expresi[oó]n?de?g[eé]nero transg[eé]nero persona? trans rectificaci[oó]n?(registral_)?(del_)?sexo nombre?sentido pronombres? gender? identity

KNOWN VALUES

ES_L3_IDENTIDAD_GENERO - List

LIST

VALUES

STRENGTH

FIRST VALUES

es-detectar-identidades-genero.txt	17	70%	Mujer cis, Hombre cis, Mujer trans, Hombre trans, Persona no binaria, Otra
------------------------------------	----	-----	--

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of identities.

ES_IDENTIDAD_GENERO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_IDENTIDAD_GENERO_LISTA .

ES_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_IDENTIDAD_GENERO_LISTA

SECURE LOOKUP

Replaces the value with one of the 7 values in `es-identidades-genero.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Transgénero

→

Hombre trans

10.12 Victims of gender and sexual violence

ES_L3_VICTIMA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Whether a person is a victim of gender violence, domestic or sexual violence or trafficking; protection orders; the VioGén and ATENPRO systems. Article 63 of Ley Orgánica 1/2004 protects the intimacy of the victims and their personal data, and Ley Orgánica 10/2022 extends the protection to the victims of sexual violence.

HOW IT IS FOUND

COLUMN NAME

ES_L3_VICTIMA - Path

90%

```
v[ií]ctima(_?(de_)?(violencia(_?(de_?g[eé]nero|dom[eé]stica|machista|sexual|vicaria))?  
|delito|trata|agresi[oó]n|acoso))? violencia_?(de_)?g[eé]nero violencia_  
(dom[eé]stica|machista|sexual|vicaria|intrafamiliar) tipo_?(de_)?violencia orden_?(de_)?  
protecci[oó]n orden_?(de_)?alejamiento viogen atenpro trata_?(de_)?(seres_  
humanos|personas)
```

HOW IT IS MASKED

Suppressed to `Sin información` ; a yes/no flag stays a flag.

ES_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `ES_SUPRIMIR` .

ES_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt` , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt` , chosen by a keyed hash.

ES_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt` , chosen by a keyed hash.

ES_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt` , chosen by a keyed hash.

ES_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_SUPRIMIR

SECURE LOOKUP

Replaces the value with one of the 1 values in `es-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Violencia de género

→

Sin información

S

→

S

Health data (art. 9 RGPD, Ley 41/2002 and DA 17 LOPDGDD)

Health is a special category of article 9, and the additional provision 17 of the LOPDGDD lists the laws under which it is processed — the Ley General de Sanidad, Ley 41/2002 on the autonomy of the patient, the laws on the National Health System, on biomedical research, on disability — none of them a test environment. Article 16.3 of Ley 41/2002 asks that any secondary access to the historia clínica keep the identifying data "separados de los de carácter clínicoasistencial, de manera que, como regla general, quede asegurado el anonimato". Ley 15/2022 adds "enfermedad o condición de salud" and "estado serológico" to the grounds of discrimination.

11.1 Health identifiers

ES_SALUD_IDENTIFICADOR

COLUMN NAME	VALUE FORMAT	CHARACTER MAPPING
-------------	--------------	-------------------

WHAT IT IS

The number of the historia clínica, of an episode or an appointment, and the personal code of the health card — the CIP-SNS of the Sistema Nacional de Salud, four letters and twelve digits, and the codes of each comunidad, such as the NUHSA of Andalusia.

HOW IT IS FOUND

COLUMN NAME	ES_SALUD_IDENTIFICADOR – Path
85%	n(o ro um umero)?(historia(?:cl[ií]nica)? hc nhc episodio ingreso atenci[oó]n consulta cita receta tarjeta_?sanitaria) historia_?cl[ií]nica nhc cip(?:sns autonomico auton[oó]mico)? c[oó]digo?(de_)? identificaci[oó]n_?personal tarjeta_?sanitaria(?:individual)? tsi nuhsa cipa tis id_?paciente c[oó]digo?(paciente historia episodio) hist[oò]ria_?cl[ií]nica osasun_?txartela
55%	historia episodio ingreso consulta

VALUE FORMAT	ES_SALUD_IDENTIFICADOR – Regex	
PATTERN	STRENGTH	NOTES
[A-Z]{4}\d{12}		70%
AN\d{10}		70%
A value that matches none does not count against the domain.		

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM	CHARACTER MAPPING
---------------	-------------------

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BBBB123456789012	→	JLSM149629954003
AN1234567890	→	OJ3261702518

11.2 Health coverage

ES_SALUD_COBERTURA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Who covers a person's health care: the Seguridad Social as holder or beneficiary, the civil-service mutual funds MUFACE, ISFAS and MUGEJU, a mutual insurer, a private insurer. A mutual fund says what a person works as.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_COBERTURA - Path

85% cobertura(_?(sanitaria|m[eé]dica|asistencial))? aseguramiento r[eé]gimen?(de_)?
(aseguramiento|asistencia) tipo?(de_)?(asegurado|aseguramiento|cobertura|beneficiario)
mutualidad mutua(_?(laboral|colaboradora))? muface isfas mugeju aseguradora?
(m[eé]dica|salud) seguro?(m[eé]dico|de_salud|privado) entidad?(de_)?seguro

KNOWN VALUES ES_SALUD_COBERTURA - List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-cobertura.txt	23	80%	Seguridad Social (titular), Seguridad Social (beneficiario), MUFACE, ISFAS, MUGEJU, Mutua colaboradora

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of coverages; a numeric code gets other digits.

ES_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_COBERTURA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

ES_COBERTURA SECURE LOOKUP

Replaces the value with one of the 9 values in es-cobertura-salud.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
MUFACE	→ Sin cobertura

11.3 Diagnosis

ES_SALUD_DIAGNOSTICO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Diagnosis, illness, allergy or cause of death, as text or coded in **CIE-10-ES**, the Spanish edition of ICD-10 in use since 2016: F33.1 , E11.9 .

HOW IT IS FOUND

COLUMN NAME

ES_SALUD_DIAGNOSTICO - Path

85%

```
diagn[oó]stico[a-z]* dx(_?(principal|secundario|ingreso|alta)[0-9]?)? cie_?10(_?es)?
cie(_?(9|10|11|principal))? (cod|codigo)_?(diagnostico|dx|cie) juicio_?
(cl[ií]nico|diagn[oó]stico) impresi[oó]n_?diagn[oó]stica enfermedad(es)?[a-z]*
patolog[ií]a comorbilidad(es)? antecedentes?_?
(m[eé]dicos|patol[oó]gicos|cl[ií]nicos|personales|familiares) causa_(de_)?
(muerte|defunci[oó]n|baja|ingreso) motivo_(de_)?(consulta|baja|ingreso) alergias?
diagnosis diagnos(is|es) icd_(10|11)?
```

VALUE FORMAT

ES_SALUD_DIAGNOSTICO - Regex

PATTERN

STRENGTH

NOTES

[A-TV-Za-tv-z]\d{2}(\. [\dA-Za-z]{1,4}|\d|X)?

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A code becomes another code of the same form from a list of common diagnoses; a text becomes another diagnosis; a flag stays a flag.

ES_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

ES_DIAGNOSTICO_TEXTO .

ES_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in es-cie10-decimal.txt , chosen by a keyed hash.

ES_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in es-cie10.txt , chosen by a keyed hash.

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in es-diagnosticos.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	K21.9
E119	→	J30
Depresión mayor	→	Tendinitis

11.4 Medical procedure

ES_SALUD_PROCEDIMIENTO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Procedure, test or surgery, as text or coded in CIE-10-ES Procedimientos — seven characters, 0DTJ4ZZ.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_PROCEDIMIENTO – Path

85% procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado|cie))? (cod|codigo)?
 (procedimiento|prestaci[oó]n|intervenci[oó]n) prestaci[oó]n?(sanitaria|asistencial)
 prueba?(diagn[oó]stica|realizada|solicitada) intervenci[oó]n?quir[uú]rgica cirug[ií]a(_?
 realizada)? t[eé]cnica?(diagn[oó]stica|quir[uú]rgica) medical?procedure

HOW IT IS MASKED

A seven-character code is mapped character by character, keeping its shape; a numeric code gets other digits; a text becomes another procedure.

ES_PROCEDIMIENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_PROCEDIMIENTO_TEXTO .

ES_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

ES_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in es-procedimientos.txt, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0DTJ4ZZ	→	6FUJ8JX
Determinación de carga viral de VIH	→	Análisis de orina

11.5 Medicine

ES_SALUD_MEDICAMENTO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

A prescribed or dispensed medicine. A medicine reveals the illness behind it: an antiretroviral, an antipsychotic, methadone.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_MEDICAMENTO – Path

85% medicamentos?(_(recetado|prescrito|dispensado|nombre|activo))? f[aá]rmacos? principio_
activo dci c[oó]digo_?nacional cn_?(medicamento|f[aá]rmaco) receta(_?
(electr[oó]nica|m[eé]dica))? prescripci[oó]n(_?medicamento)? posolog[ií]a tratamiento_
(farmacol[oó]gico|actual|cr[oó]nico) (cod|codigo)_?medicamento medicament botika
medications? drugs?_?prescribed

KNOWN VALUES ES_SALUD_MEDICAMENTO – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar- medicamentos.txt	56	70%	Paracetamol, Ibuprofeno, Metamizol, Omeprazol, Metformina, Enalapril

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine of no particular meaning – paracetamol, omeprazol, enalapril.

ES_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_MEDICAMENTO_LISTA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 23 values in es-medicamentos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Sertralina 50 mg	→ Enalapril

11.6 Clinical text

ES_SALUD_TEXTO_CLINICO

COLUMN NAME DATA TYPE FREE TEXT REDACTION

WHAT IT IS

Anamnesis, clinical course, discharge reports, nursing notes: the free text of the historia clínica.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_TEXTO_CLINICO – Path

85% anamnesis evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))? enfermedad_?actual
exploraci[oó]n_?f[ií]sica plan_?(de_)?(tratamiento|cuidados) tratamiento_?indicado
juicio_?cl[ií]nico_?texto informe_?(de_)?alta informe_
(m[eé]dico|cl[ií]nico|radiol[oó]gico|anatomopatol[oó]gico) epicrisis nota_?(m[eé]dica|de_?
enfermer[ií]a|cl[ií]nica) notas?_?(m[eé]dicas|cl[ií]nicas) triaje(_?texto)? curso_
cl[ií]nico clinical_?notes? discharge_?summary

DATA TYPE ES_SALUD_TEXTO_CLINICO – Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

Free Text Redaction, as for any free text: identifiers, contact and names are replaced. The clinical content stays – redact or replace the whole column where the content itself is the risk.

ES_TEXTO_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 10 patterns with [DATO] , and the 2,494 terms of es-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE

Paciente García, DNI 12345678Z, consulta por cefalea.

MASKED

→ Paciente [NOMBRE], DNI [DATO], consulta por cefalea.

11.7 Test result

ES_SALUD_RESULTADO_PRUEBA

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

The result of an analysis or a test: glucose, cholesterol, a PCR, a pregnancy test.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_RESULTADO_PRUEBA – Path

80% resultado_?(de_?la_)?
(prueba|an[aá]lisis|anal[ií]tica|laboratorio|pcr|serolog[ií]a|biopsia|citolog[ií]a)
(prueba|an[aá]lisis|anal[ií]tica)_?(resultado|laboratorio) glucemia glucosa
hemoglobina(_?glicada)? hba1c colesterol(_?(total|hdl|ldl))? imc tensi[oó]n_?arterial
test_?(de_)?embarazo espirometr[ií]a alcoholemia lab_?results? test_?results?

50% resultado prueba analisis analitica

HOW IT IS MASKED

Character by character, keeping its shape.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Positivo

→

Qucuruhe

11.8 HIV and sexually transmitted infections

ES_SALUD_VIH

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

HIV status, viral load, antiretroviral treatment and PrEP, other sexually transmitted infections, hepatitis and tuberculosis. Ley 15/2022 names the "estado serológico" among the grounds of discrimination.

HOW IT IS FOUND

COLUMN NAME

ES_SALUD_VIH - Path

90%

```
vih(?:estado|resultado|prueba|diagn[ó]stico|positivo))? hiv sida aids serolog[ií]a_?
(vih|hiv) estado?serol[ó]gico carga?viral cd4 tar tratamiento?antirretroviral
antirretroviral(es)? prep profilaxis?pre?exposici[ó]n its ets infecci[ó]n(es)?_?
(de?)?transmisi[ó]n?sexual s[ií]filis hepatitis?[bc] tuberculosis tbc
```

HOW IT IS MASKED

Suppressed to Sin información ; a yes/no flag stays a flag.

ES_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_SUPRIMIR .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in es-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Positivo

→

Sin información

S

→

S

11.9 Blood group

ES_SALUD_GRUPO_SANGUINEO

COLUMN NAME KNOWN VALUES SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_GRUPO_SANGUINEO - Path

90% grupo_?sangu[ií]neo tipo_?(de_)?sangre rh factor_?rh grupo_?rh abo(_?rh)? grup_? sanguini blood_?(type|group)

KNOWN VALUES ES_SALUD_GRUPO_SANGUINEO - List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-grupos-sanguineos.txt	20	90%	A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another of the eight groups.

ES_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in es-grupos-sanguineos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
O+	→ A-

11.10 Disability

ES_SALUD_DISCAPACIDAD

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Type and degree of disability. A degree of 33% opens the protection of the Real Decreto Legislativo 1/2013, under the scale of Real Decreto 888/2022.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_DISCAPACIDAD - Path

90% discapacidad[a-z]* minusval[ií]a (tipo|cod|codigo|grado|porcentaje)_?(de_)? (discapacidad|minusval[ií]a) persona_?con_?discapacidad certificado_?(de_)?discapacidad tarjeta_?(de_)?discapacidad movilidad_?reducida necesidades_?educativas_?especiales neae discapacitat desgaitasuna disabilit(y|ies)

KNOWN VALUES ES_SALUD_DISCAPACIDAD - List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-discapacidades.txt	30	60%	Física, Fisica, Orgánica, Organica, Visual, Auditiva

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced within a list of types; a degree gets other digits; a flag stays a flag.

ES_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_DISCAPACIDAD_LISTA .

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in **es-bandera-si-no.txt** , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in **es-bandera-true-false.txt** , chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in **es-bandera-yes-no.txt** , chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in **es-bandera-s-n.txt** , chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in **es-bandera-y-n.txt** , chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in **es-bandera-0-1.txt** , chosen by a keyed hash.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

ES_DISCAPACIDAD_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in **es-discapacidades.txt** , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno del espectro autista

→ Sin discapacidad reconocida

11.11 Dependency

ES_SALUD_DEPENDENCIA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The grade of dependency under Ley 39/2006 — I moderate, II severe, III great dependency —, the individual care programme and the benefits that follow from it.

HOW IT IS FOUND

COLUMN NAME

ES_SALUD_DEPENDENCIA - Path

90%

dependencia(_?(grado|reconocida|valoraci[ó]n))? grado?(de_)?dependencia gran?
dependencia ley?(de_)?dependencia pia programa?individual?(de_)?atenci[ó]n
cuidador?(no?profesional|familiar) prestaci[ó]n?(econ[ó]mica?)(vinculada?a_l?
servicio|cuidados?en?el?entorno?familiar) ayuda?a?domicilio teleasistencia
depend[eè]ncia mendekotasuna

KNOWN VALUES

ES_SALUD_DEPENDENCIA - List

LIST

VALUES STRENGTH FIRST VALUES

es-detectar- dependencia.txt	13	70%	Grado I - Dependencia moderada, Grado II - Dependencia severa, Grado III - Gran dependencia, Sin grado reconocido, En valoración, En valoracion
---------------------------------	----	-----	--

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced within the grades; a numeric grade by another grade.

ES_DEPENDENCIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_DEPENDENCIA_LISTA

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_DEPENDENCIA_CODIGO SECURE LOOKUP

Replaces the value with one of the 3 values in `es-dependencia-codigos.txt`, chosen by a keyed hash.

ES_DEPENDENCIA_LISTA SECURE LOOKUP

Replaces the value with one of the 5 values in `es-dependencia.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Grado II nivel 1

→

En valoración

2

→

1

11.12 Occupational health

ES_SALUD_LABORAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Fitness for work, the medical examinations of the company's health surveillance, sick leave, work accidents and occupational diseases. Article 22.4 of Ley 31/1995 de prevención de riesgos laborales keeps the results of that surveillance from the employer, except as fit or unfit.

HOW IT IS FOUND

COLUMN NAME

ES_SALUD_LABORAL - Path

85%

```
aptitud_?(laboral|m[eé]dica) certificado_?(de_?)?aptitud reconocimiento_?m[eé]dico
vigilancia_?(de_?la_?)?salud examen_?(de_?)?salud accidente_?(de_?)?trabajo enfermedad_?
(profesional|laboral) incapacidad_?(temporal|permanente) baja_?(m[eé]dica|laboral|por_?
enfermedad) it_?(d[ií]as|motivo|contingencia)? parte_?(de_?)?(baja|alta|confirmaci[óó]n)
d[ií]as_?(de_?)?baja absentismo contingencia_?(com[uú]n|profesional)
```

KNOWN VALUES ES_SALUD_LABORAL – List

LIST	VALUES	STRENGTH	FIRST VALUES
es-detectar-aptitud-laboral.txt	10	60%	apto, no apto, apto con restricciones, pendiente, contingencia común, contingencia comun
es-detectar-codigos-banderas.txt	14	30%	s, n, sí, si, no, 1

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced within a list of fitness results; a yes/no flag stays a flag.

ES_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_APTITUD_LABORAL_LISTA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in es-aptitud-laboral.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
No apto temporal	→	Apto
S	→	S

11.13 Reproductive health

ES_SALUD_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, childbirth, contraception, assisted reproduction and the voluntary interruption of pregnancy of Ley Orgánica 2/2010.

HOW IT IS FOUND

COLUMN NAME ES_SALUD_REPRODUCTIVA – Path

90% embarazo embarazada gestante gestaci[oó]n edad_?gestacional semanas_?(de_)?
gestaci[oó]n fur fecha_?[uú]ltima_?regla control_?(de_)?embarazo prenatal parto(_?
tipo)? ces[aá]rea ive interrupci[oó]n_?(voluntaria_)?(del_)?embarazo aborto
m[eé]todo_?anticonceptivo anticoncepci[oó]n planificaci[oó]n_?familiar reproducci[oó]n_
asistida fecundaci[oó]n_?in_?vitro fiv salud_?(sexual|reproductiva) pregnan(t|cy)
contracepti(on|ve)

HOW IT IS MASKED

Suppressed to Sin información ; a yes/no flag stays a flag.

ES_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_SUPRIMIR .

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (9 groups), keeping length and format.

ES_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in es-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

12 semanas de gestación

→ Sin información

11.14 Mental health

ES_SALUD_MENTAL

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Mental disorders, psychiatric care, suicidal behaviour, addictions and their treatment.

HOW IT IS FOUND

COLUMN NAME	ES_SALUD_MENTAL - Path
90%	salud_?mental trastorno[a-z]* psiqui[aá]tri[a-z]* psicol[oó]gi[a-z]* depresi[oó]n ansiedad suicid[a-z]* tentativa_?(de_)?suicidio autolesi[oó]n conducta_?suicida consumo_?(de_)?(sustancias alcohol drogas t[oó]xicos) adicci[oó]n(es)? drogodependencia alcoholismo tabaquismo ludopat[ií]a cad centro_?(de_)?atenci[oó]n_?(a_?las_)? (adicciones drogodependencias) mental_?health

HOW IT IS MASKED

Suppressed to Sin información .

ES_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_SUPRIMIR .

ES_BANDERA REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
ES_BANDERA_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.
ES_BANDERA_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.
ES_BANDERA_YES_NO SECURE LOOKUP
Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.
ES_BANDERA_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.
ES_BANDERA_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.
ES_BANDERA_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.
ES_CM_ALFANUM CHARACTER MAPPING
Maps each character to another of its group (9 groups), keeping length and format.
ES_SUPRIMIR SECURE LOOKUP
Replaces the value with one of the 1 values in es-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Trastorno bipolar	→ Sin información

Economic and tax data (art. 20 LOPDGDD and art. 95 LGT)

Article 20 of the LOPDGDD allows the common files of defaulters only for debts that are certain, due and payable, and only "mientras persista el incumplimiento, con el límite máximo de cinco años"; article 20.3 denies the presumption of lawfulness to any profile built by adding other sources. Article 95 of the **Ley General Tributaria** makes every datum the tax administration obtains "reservado". And Ley 15/2022 names the "situación socioeconómica" among the grounds of discrimination. Amounts keep their order of magnitude so that totals and ratios still behave; what they stop doing is naming a salary.

12.1 Credit history

ES_FIN_HISTORIAL_CREDITICIO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Being in a file of defaulters — ASNEF, Badexcug — or in the Central de Información de Riesgos of the Banco de España, a credit score, days past due. Article 20 of the LOPDGDD lets those files keep a debt for five years at most.

HOW IT IS FOUND

COLUMN NAME

ES_FIN_HISTORIAL_CREDITICIO – Path

90%

```
historial_?(crediticio|de_?cr[eé]dito) asnef badexcug experian equifax fichero_?
(de_?)(morosos|morosidad|solventia) cirbe central_?(de_?)(informaci[oó]n_?de_?)?riesgos
scoring(_?(crediticio|interno))? score(_?crediticio)? puntuaci[oó]n_?(de_?)?cr[eé]dito
calificaci[oó]n_?(de_?)(riesgo|cr[eé]dito|solventia) clasificaci[oó]n_?(de_?)?riesgo
d[ií]as_?(de_?)(impago|mora|atraso) morosidad moroso impagad[oa]s? situaci[oó]n_?
(de_?)(impago|deuda) credit_?score credit_?rating
```

HOW IT IS MASKED

Replaced within a list of credit situations; a score gets other digits; a flag stays a flag.

ES_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ESTADO_CREDITO .

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 11 values in `es-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Incluido en ASNEF	→	En reclamación
745	→	471

12.2 Debt

ES_FIN_DEUDA

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Outstanding balance, loan or mortgage amount, monthly instalment, credit limit, attachment.

HOW IT IS FOUND

COLUMN NAME ES_FIN_DEUDA – Path

85% saldo_?(deudor|deuda|pendiente|vivo|impagado|pr[eé]stamo|hipoteca) importe_?(de_?la_?)?
(deuda|cuota|pr[eé]stamo|hipoteca|impagado|embargo|financiado) deuda(_?total)? capital_
pendiente l[ií]mite_?(de_?)?(cr[eé]dito|tarjeta) cuota_?(mensual|hipoteca|pr[eé]stamo)
embargo(_?(importe|cantidad))? loan_?(amount|balance) outstanding_?balance debt

DATA TYPE ES_FIN_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Replaced by another amount between 100 and 600,000 euros.

ES_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 100 and 600,000.

EXAMPLES

VALUE		MASKED
18500	→	10882

12.3 Income

ES_FIN_INGRESOS

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Salary, payslip, income of the household, earnings from work or capital.

HOW IT IS FOUND

COLUMN NAME ES_FIN_INGRESOS – Path

85% sueldo(_?(bruto|neto|mensual|base|anual))? salario(_?(bruto|neto|mensual|base|anual))?
n[oó]mina(_?(bruta|neta|importe))? retribuci[ó]n(_?(bruta|anual|mensual))? ingresos?(_?
(mensuales?|anuales?|totales?|familiares?|netos?|brutos?|unidad_?familiar))? rendimientos_?
(del_?)?(trabajo|capital) renta(_?(bruta|neta|anual|disponible|per_?c[aá]pita))? salari
sou soldata salary income wages?

DATA TYPE ES_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Replaced by another amount between 1,000 and 120,000 euros.

ES_INGRESOS **NUMERIC MAPPING**

Maps the number to another between 1,000 and 120,000.

EXAMPLES

VALUE		MASKED
28500	→	55996

12.4 Assets

ES_FIN_PATRIMONIO

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Cadastral or appraised value of a property, account and investment balances, pension plans.

HOW IT IS FOUND

COLUMN NAME ES_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|total))?` `valor_?(catastral|de_?tasaci[oó]n|del_?inmueble|de_?la_?vivienda|de_?mercado|del_?veh[if]iculo)` `tasaci[oó]n` `saldo_?(cuenta|ahorro|dep[oó]sito|inversi[oó]n|fondo|medio)` `dep[oó]sitos?` `inversiones` `cartera_?(de_?)?valores` `fondos?_?(de_?)?(inversi[oó]n|pensiones)` `plan_?(de_?)?pensiones` `net_?worth` `account_?balance`

DATA TYPE ES_FIN_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Replaced by another amount between 1,000 and 3,000,000 euros.

ES_PATRIMONIO **NUMERIC MAPPING**

Maps the number to another between 1,000 and 3,000,000.

EXAMPLES

VALUE		MASKED
185000	→	477515

12.5 Pension

ES_FIN_PENSION

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

The amount of a retirement, widow's, orphan's, disability or non-contributory pension, or of maintenance.

HOW IT IS FOUND

COLUMN NAME ES_FIN_PENSION – Path

90% pensi[oó]n(_?
(importe|mensual|anual|jubilaci[oó]n|viudedad|orfandad|incapacidad|alimentos|compensatoria|no_
?contributiva))?) importe?(pensi[oó]n|prestaci[oó]n|subsidio) base?reguladora pensi[oó]?
(import)? pension?amount

DATA TYPE ES_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Replaced by another amount between 500 and 3,400 euros a month — the range of the public pensions.

ES_VALOR_PENSION **NUMERIC MAPPING**

Maps the number to another between 500 and 3,400.

EXAMPLES

VALUE	MASKED
1250	→ 1612

12.6 Social benefits

ES_FIN_PRESTACION_SOCIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The Ingreso Mínimo Vital, unemployment benefit and subsidy, the minimum income of each comunidad, non-contributory pensions, the social bonus for electricity, grants. Each one says a household is poor, and Ley 15/2022 names the "situación socioeconómica" among the grounds of discrimination.

HOW IT IS FOUND

COLUMN NAME ES_FIN_PRESTACION_SOCIAL – Path

90% prestaci[oó]n(_?(social|por?desempleo|econ[oó]mica))? subsidio(_?(desempleo|agrario))?
ingreso?m[ií]nimo?vital imv renta?(m[ií]nima|garantizada|de?inserci[oó]n|valenciana?
de?inclusi[oó]n|social) rmi rgi bono?sosocial beneficiario?
(imv|prestaci[oó]n|subsidiobono|beca) beca(_?(mec|general|comedor))? ayuda?(social|de?
emergencia|al?alquiler) vulnerabilidad riesgo?(de?)?exclusi[oó]n situaci[oó]n?
socioecon[oó]mica nivel?socioecon[oó]mico sepe social?benefit

KNOWN VALUES ES_FIN_PRESTACION_SOCIAL – List

LIST	VALUES	STRENGTH	FIRST VALUES
------	--------	----------	--------------

es-detectar- prestaciones- sociales.txt	33	80%	Ingreso Mínimo Vital, Ingreso Minimo Vital, Prestación por desempleo, Prestacion por desempleo, Subsidio por desempleo, Renta mínima autonómica
---	----	-----	---

es-detectar- codigos- banderas.txt	14	30%	s, n, sí, sí, no, 1
--	----	-----	---------------------

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced within a list of benefits; a yes/no flag stays a flag.

ES_PRESTACION_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_PRESTACION_SOCIAL_LISTA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_PRESTACION_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `es-prestaciones-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ayuda de emergencia social	→	Pensión no contributiva
S	→	S

12.7 Tax data

ES_FIN_TRIBUTARIO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Tax base, tax due, the result of an income tax return, withholdings, the wealth tax. Article 95 of the Ley General Tributaria makes every datum the tax administration obtains "reservado", to be used only to apply the taxes.

HOW IT IS FOUND

COLUMN NAME ES_FIN_TRIBUTARIO - Path

90% `irpf(_?(base|cuota|resultado|retenci[oó]n|importe))?` `base_?(imponible|liquidable)(_?(general|ahorro))?` `cuota_?([ií]ntegra|l[ií]quida|diferencial|tributaria)` `resultado_?(de_?la_?)?declaraci[oó]n` `declaraci[oó]n_?(de_?la_?)?renta` `renta_?(declarada|imponible)` `retenci[oó]n(es)?_?(irpf|practicadas)` `modelo_?(100|190|714)` `impuesto_?(sobre?el_?)?` `patrimonio` `deducci[oó]n(es)?_?(auton[oó]mica|estatal)` `tax_?(base|return|amount)`

HOW IT IS MASKED

Replaced by another amount up to 250,000 euros; the sign of a refund and the cents stay.

ES_TRIBUTARIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_IMPORTE_TRIBUTARIO NUMERIC MAPPING

Maps the number to another between 0 and 250,000.

EXAMPLES

VALUE

MASKED

-1240.55

→

-7247.55

24350

→

15057

Criminal and administrative offences (art. 10 RGPD, arts. 10 and 27 LOPDGDD)

Article 10 of the LOPDGDD allows data on criminal convictions and offences outside the authorities only where a law with the rank of law covers them, and article 27 does the same for administrative infringements and sanctions; processing either outside those rules is a very serious infringement (art. 72.1 f and g). Article 136 of the Código Penal cancels an entry in the Registro Central de Penados after a term that runs from six months to ten years, and article 136.4 says the entries "no serán públicas". A non-production copy keeps the entry for as long as the copy lives, which is longer than any of those terms.

13.1 Criminal records

ES_PENAL_ANTECEDENTES

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Criminal records, convictions, offences, procedural and penitentiary situation, precautionary measures.

HOW IT IS FOUND

COLUMN NAME ES_PENAL_ANTECEDENTES – Path

95% antecedentes?(_(penales|policiales|judiciales))? certificado?(de_)?antecedentes(_? penales)? registro?central?(de_)?penados reincidencia condena(_?(penal|tipo))? delito(_?(tipo|cometido))? tipo?(de_)?delito situaci[ó]n? (penal|procesal|penitenciaria) medida?cautelar prisi[ó]n?provisional privad[oa]? (de_)?libertad interno?penitenciario centro?penitenciario libertad?condicional antecedents?penals criminal?record

55% estado?(del_)?proceso sentencia fallo

HOW IT IS MASKED

Replaced within a list of situations; a yes/no flag stays a flag.

ES_ANTECEDENTES **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ANTECEDENTES_LISTA .

ES_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-si-no.txt` , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-true-false.txt` , chosen by a keyed hash.

ES_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt` , chosen by a keyed hash.

ES_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-s-n.txt` , chosen by a keyed hash.

ES_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-y-n.txt` , chosen by a keyed hash.

ES_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `es-bandera-0-1.txt` , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `es-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Condenado por hurto en 2019

→ Sin antecedentes penales

13.2 Certificate of the register of sex offenders

ES_PENAL_DELITOS_SEXUALES

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Article 57 of Ley Orgánica 8/2021 (LOPVI) requires anyone working with minors to present a negative certificate of the Registro Central de Delincuentes Sexuales y de Trata de Seres Humanos, so schools, clubs and companies keep a column for it — and its value is a criminal-record datum.

HOW IT IS FOUND

COLUMN NAME

ES_PENAL_DELITOS_SEXUALES – Path

95%

certificado?(negativo?)?(de_?)?(delitos?_(de_?naturaleza_?)?sexual(es)?|registro?
(central_?)?(de_?)?delincuentes?sexuales) delitos?_sexuales delincuentes?sexuales
rcds registro?delincuentes lopivi(_?certificado)? certificat?(de_?)?delictes?sexuals

KNOWN VALUES

ES_PENAL_DELITOS_SEXUALES – List

LIST

VALUES STRENGTH FIRST VALUES

es-detectar-certificado-delitos-sexuales.txt	8	60%	certificado negativo, negativo, positivo, aportado, no aportado, pendiente
--	---	-----	--

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced within a list of certificate states; a yes/no flag stays a flag.

ES_DELITOS_SEXUALES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_DELITOS_SEXUALES_LISTA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-si-no.txt`, chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-true-false.txt`, chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-yes-no.txt`, chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-s-n.txt`, chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-y-n.txt`, chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `es-bandera-0-1.txt`, chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_DELITOS_SEXUALES_LISTA SECURE LOOKUP

Replaces the value with one of the 5 values in `es-certificado-delitos-sexuales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Certificado positivo

→

No aportado

13.3 Court case number

ES_PENAL_PROCEDIMIENTO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The NIG — the general identification number of a procedure, printed in groups, `28079 43 2 2023 0012345` — and the number of the case in its court, `PA 123/2023`. Court decisions are published by the CENDOJ with the parties anonymized; the number is what links them back.

HOW IT IS FOUND

COLUMN NAME

ES_PENAL_PROCEDIMIENTO - Path

90%

```
nig n(o|ro|um|umero)?(de_)?identificaci[ó]n_general n(o|ro|um|umero)?(de_)?
(procedimiento|autos|diligencias|asunto|causa|sumario|ejecutoria|atestado|denuncia)(_?
(judicial|penal|previas))? procedimiento?(judicial|penal) diligencias?(previas|urgentes)
sumario atestado(_?policial)? ejecutoria
```

50%

```
procedimiento causa autos expediente_?judicial
```

VALUE FORMAT

ES_PENAL_PROCEDIMIENTO - Regex

PATTERN

STRENGTH

NOTES

```
\d{5}\s?\d{2}\s?\d\s?\d{4}\s?\d{7}
```

90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The correlative changes; the code of the court seat, the jurisdiction and the year stay.

ES_PROCEDIMIENTO_JUDICIAL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `ES_CM_ALFANUM`.

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

28079 43 2 2023 0012345

→

28079 43 2 2023 7824923

PA 123/2023

→

PA 957/2023

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Administrative infringements and sanctions — fines, sanctioning files, the points of a driving licence. Article 27 of the LOPDGDD reserves them to the authority that imposes them, and processing them outside that rule is a very serious infringement (art. 72.1 g).

HOW IT IS FOUND

COLUMN NAME ES_PENAL_SANCION_ADMINISTRATIVA - Path

90%

sanci[oó]n(es)?(_?(administrativa|tipo|grado))? infracci[oó]n(es)?(_?(administrativa|tr[aá]fico|tipo))? expediente_?sancionador multa(s)?(_?(tr[aá]fico|importe|tipo))? denuncia_?(de_?)?tr[aá]fico puntos_?(de_l_?)? (carn[eé]|permiso) saldo_?(de_?)?puntos p[éé]rdida_?(de_?)?puntos retirada_?(de_l_?)? (carn[eé]|permiso) administrative_?(sanction|penalty) traffic_?fine

HOW IT IS MASKED

Replaced within a list of sanction states; a number of points gets other digits; a flag stays a flag.

ES_SANCION_ADMINISTRATIVA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_SANCION_ADMINISTRATIVA_LISTA .

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

ES_SANCION_ADMINISTRATIVA_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in es-sanciones-administrativas.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Multa de tráfico por exceso de velocidad	→	Sanción grave
12	→	58

Check characters computed by lookup tables

Spain validates almost every identifier by arithmetic. The letter of the DNI and the NIE is the number modulo 23; the control digits of the Seguridad Social number are the number modulo 97; the bank account carries two control digits modulo 11 and the IBAN two more modulo 97; the referencia catastral carries two letters, each a weighted sum modulo 23; the CUPS carries two letters, the number modulo 529. A masked value whose check characters were not recomputed is rejected by every form, every bank and every utility that receives it — which is exactly what a test needs to avoid.

No masking framework writes a letter, or two digits, or a remainder modulo 23, 97 or 529. Check Digit writes one digit. So the set computes them with tables. A **state** — the remainder so far, written with as many digits as the modulus needs — is put in front of the value and travels through it one character at a time. Each step is a Regex Decompose that hands three or four characters, "state + next character", to a Data Cleansing whose table answers "next character + new state". Separators and characters that do not count are stepped over by lines that carry the state unchanged. At the end a last table turns the remainder into the check characters, upper-case or lower-case as the input was.

The tables are small — 299 lines for the DNI, 1,358 for the Seguridad Social, 6,877 for the CUPS, eleven of 230 lines for the weights of the referencia catastral —, and a step that finds no line for its window leaves the value as it is, so one chain serves every written form: a DNI with or without dots and hyphen, a Seguridad Social number with or without slashes, a CUPS with or without spaces.

The bank account takes a different route. The plugin's IBAN algorithm masks the last characters of an IBAN and recomputes its two ISO 13616 digits, but it does not know the second control digit of the Spanish account, which sits between the branch and the account. The set lets the IBAN algorithm mask the account, recomputes that control digit with a state that crosses the account from right to left, carries the old and the new digit to the front as a pair, and corrects the IBAN digits for the change with a table of 10,000 lines: the second digit weighs 10^{16} in the number the IBAN checks, so the correction is $(\text{new} - \text{old}) \cdot 10^{16}$ modulo 97. Bank, branch and first control digit stay, and the result passes both checks.

Where people live: municipios, INE codes and postal codes

Spain is divided into 17 comunidades autónomas and 2 ciudades autónomas, 50 provinces and **8,132 municipios**, and the municipios are small: on the Padrón of 1 January 2025, **7,700 of them had fewer than 20,000 inhabitants** — 14.5 million people, almost a third of the 49.1 million of the country — and more than half have fewer than 1,000. A birth date, a sex and one of those municipios point at a handful of neighbours.

The threshold of 20,000 is the INE's own: when it published the microdata of the 2011 census it recoded the province and municipio of every person living in a municipio of fewer than 20,000 inhabitants, "para preservar el secreto estadístico". The 2021 census, published as a 10% sample, recoded below 10,000; a masked copy holds every row of the database, not a sample, so the stricter figure is the one that fits.

So a municipio below the threshold becomes the **nearest municipio of at least 20,000 in the same province**, measured between their centres; every province has one — its capital at least — so a generalized value never leaves its province, and the province and the comunidad are never rewritten. The islands follow the rule too: a small municipio of La Gomera or El Hierro goes to the nearest large one of its province, on another island.

Spanish municipio names come in many spellings: the INE writes the article behind, Guíjarrosa, La , and gives the names of the bilingual comunidades in both languages, Alacant/Alicante , Donostia/San

Sebastián; systems write La Coruña for A Coruña or Gerona for Girona. The table carries every one of those spellings, in capitals and without accents as well, and the forms with the province beside them — Villanueva (Toledo), Villanueva, Toledo — 68,972 lines in all. A name is generalized only when **every** municipio, province or comunidad that bears it is small; written with its province, the same rule applies inside it.

The codes follow the names. The INE code of a small municipio — two digits for the province, three for the municipio, with or without its check digit — becomes the code of the municipio its name goes to, with that municipio's own check digit. The postal code follows the municipio it mostly serves, by the street segments of the INE's **Callejero del Censo Electoral** of July 2026: a code whose main municipio is small becomes the main code of the municipio it is generalized to — 8,638 of 10,790 codes — so a masked postal code agrees with the masked municipio beside it and keeps the two digits of its province.

Limits

- **Masking with a key is pseudonymization, not anonymization.** Whoever holds the key and the production data can reproduce the mapping, so the masked copy is still personal data for them and still needs the measures of article 32 of the Regulation. Keep the key apart from the copy — the separation the additional provision 17 of the LOPDGDD asks for research — and do not call the copy anonymous while the key exists.
- **Blocked data must not be copied.** Article 32 of the LOPDGDD forbids processing blocked data for any purpose other than making them available to courts and authorities, and failing to block is a very serious infringement. Masking a blocked row does not make copying it lawful: leave blocked rows out of the copy, or keep them out of the subset the job reads.
- **The populations are those of the Padrón of 1 January 2025.** A municipio within a few hundred inhabitants of 20,000 may cross the line with the next revision; rebuild the set when the INE publishes it.
- **A postal code can span more than one municipio.** The set follows the municipio with most street segments; a code of a large town that also serves small villages around it is kept, and with it the hint that a person lives in one of them.
- **Data Cleansing leaves unknown values as they are.** A municipio spelled in a way that is not in the table — an old name, a typo, the name of a hamlet instead of its municipio — passes unchanged. The entidades singulares de población below the municipio are not in the table.
- **Bank and branch are preserved.** They are not personal data, and keeping them keeps a test account inside a real bank; but the branch can tell a town. Mask the branch with its own rule where that matters.
- **The control letters of a referencia catastral are recomputed only in its compact form.** Written in groups, or cut to the fourteen characters of the parcel, the parcel digits change but the letters are left as they were.
- **A single M is read as mujer.** That is the convention of the Spanish administration (H/M, V/M); a column that codes sex F/M, as the machine-readable zone of the DNI does, would get H instead of M in some rows and should have an algorithm of its own.
- **Free text** is redacted word by word: Free Text Redaction splits on whitespace, so a phone written 612 34 56 78 is reached in pieces and not as one number. The patterns of the set are the compact forms.
- **Children:** a birth date moves at most 60 days, so few people cross their 14th birthday — the age of digital consent in Spain under article 7 of the LOPDGDD — or their 18th; but some do. Split the rule by age group with Multi-Column Condition where that matters.
- **Binary columns and attachments are out of reach.** A scanned DNI, a photograph, a PDF of a medical report keeps everything the columns beside it no longer say. Inventory them and report them as residual risk.

- **Discovery is a proposal, not a verdict.** The classifiers read column names and values; a column with a name nobody recognizes may be missed, and one named like a person may be caught by mistake. Review the inventory before running a masking job.
-

17

Verification

The set is checked on every build. Each chain that computes a check character is first run in the build itself with the masking taken as the identity, and must hand a valid example back unchanged — the DNI

12345678Z , the Seguridad Social number 28 12345678 40 , the IBAN ES91 2100 0418 4502 0005 1332 , the referencia catastral 9872023VH579750001WX and the CUPS ES1234123456789012JY .

The 147 classifier configurations are reviewed one by one, and a battery of 159 columns — well named, badly named, named in Catalan, Galician or Basque, and 31 that are not personal data at all, among them the NIF of a company — is profiled with the whole set at its threshold of 60 and again with the essential pack alone: every column lands where it should, and none of the 31 is claimed.

The generalization is audited offline: all 8,132 municipios, all 10,790 postal codes and all 52 provinces are checked against the rule, and every one of the 68,972 replacements the table writes names a municipio of at least 20,000 — in the same province whenever the province is written.

The masking is run for real, in the plugin: 797 values across every domain — samples, placeholders and each algorithm's own sample input — every one checked against what it should become. Then in bulk: 250 DNIs (50 of them written with dots), 100 NIEs, 200 Seguridad Social numbers, 200 IBANs — one hundred compact and one hundred printed in groups of four —, 100 CCCs, 150 referencias catastrales and 100 CUPS give as many distinct outputs, **every one valid under its own rule**, of the same shape, and keeping what it should keep: the prefix of a NIE, the province of a Seguridad Social number, bank and branch, the map sheet or the polígono, the distributor.

18

Sources

- Regulation (EU) 2016/679, General Data Protection Regulation: articles 4, 6, 9, 10, 25, 32, 83 and 89, and recitals 14, 26, 28 and 29.
- Ley Orgánica 3/2018, de 5 de diciembre, de Protección de Datos Personales y garantía de los derechos digitales, consolidated text of the BOE as last amended by Ley 10/2025 of 26 December: articles 7, 9, 10, 20, 22, 27, 28, 32, 72 to 76 and 90, and additional provision 17.
- Court of Justice of the European Union, judgment of 4 September 2025, EDPS v SRB, C-413/23 P; judgment of 19 October 2016, Breyer, C-582/14. European Data Protection Board, Guidelines 01/2025 on pseudonymisation, adopted 16 January 2025.
- Agencia Española de Protección de Datos: "Brechas de datos personales en entornos de desarrollo y preproducción" (18 April 2022); Orientaciones y garantías en los procedimientos de anonimización de datos personales; La K-anonimidad como medida de la privacidad; Introducción al hash como técnica de seudonimización de datos personales.
- Real Decreto 311/2022, Esquema Nacional de Seguridad: measure mp.sw.1 and its reinforcement R4; article 2.3.
- Ley 41/2002 de autonomía del paciente, article 16.3; Ley 31/1995 de prevención de riesgos laborales, article 22.4; Ley 39/2006 de dependencia; Real Decreto Legislativo 1/2013 and Real Decreto 888/2022 on

disability; Ley Orgánica 2/2010; Ley 15/2022 integral para la igualdad de trato y la no discriminación, article 2.1; Ley 4/2023; Ley Orgánica 1/2004, article 63; Ley Orgánica 10/2022; Ley Orgánica 3/2021.

- Ley 58/2003 General Tributaria, article 95; Código Penal, article 136; Ley Orgánica 8/2021 (LOPVI), article 57; Texto Refundido de la Ley del Catastro Inmobiliario, article 51.
- Instituto Nacional de Estadística: Cifras de población de la Revisión del Padrón municipal a 1 de enero de 2025; Relación de municipios y sus códigos a 1 de enero de 2026; Callejero del Censo Electoral of July 2026; frequencies of given names and surnames of the Censo de población a 1 de enero de 2025; Censos de Población y Viviendas 2011 and 2021, microdata. Municipio centres from GeoNames, by INE code.
- The rules of the check characters: the Ministerio del Interior for the letter of the DNI and NIE; the Tesorería General de la Seguridad Social for the Seguridad Social number; the Código Cuenta Cliente of the Spanish banks and ISO 13616 for the IBAN; the Dirección General del Catastro for the referencia catastral, checked against references published in the BOE; the CNMC for the CUPS.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

ES_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER

(\d{3})(\d)	keep · ES_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ANTECEDENTES_LISTA .

Used by: ES_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_ANTECEDENTES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in es-antecedentes.txt , chosen by a keyed hash.

Used by: ES_ANTECEDENTES

CONFIGURATION

lookupFile	es-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_APELLIDO NAME

Replaces the name with one of the 500 names in es-apellidos.txt .

Used by: ES_PALABRA_APELLIDO

CONFIGURATION

lookupFile	es-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

ES_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

Used by: ES_L1_APELLIDO , ES_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	ES_PALABRA_APELLIDO
(\S+)\s+(\S+)	ES_PALABRA_APELLIDO · ES_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	ES_PALABRA_APELLIDO · ES_PALABRA_APELLIDO · ES_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	ES_PALABRA_APELLIDO · ES_PALABRA_APELLIDO · ES_PALABRA_APELLIDO · ES_PALABRA_APELLIDO
otherwise	ES_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

ES_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_APTITUD_LABORAL_LISTA .

Used by: ES_SALUD_LABORAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [sn]yx01))	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_APTITUD_LABORAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in es-aptitud-laboral.txt , chosen by a keyed hash.

Used by: ES_APTITUD_LABORAL

CONFIGURATION

lookupFile	es-aptitud-laboral.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CATEGORIA_SUPRIMIDA , ES_SITUACION_ADMINISTRATIVA , ES_ESTADO_CIVIL , ES_NIVEL_EDUCATIVO , ES_ORIGEN_ETNICO , ES_RELIGION , ES_OPINION_POLITICA , ES_PARTIDO , ES_ORIENTACION_SEXUAL , ES_IDENTIDAD_GENERO , ES_COBERTURA_SALUD , ES_DIAGNOSTICO , ES_MEDICAMENTO , ES_DISCAPACIDAD , ES_DEPENDENCIA , ES_APTITUD_LABORAL , ES_HISTORIAL_CREDITICIO , ES_PRESTACION_SOCIAL , ES_ANTECEDENTES , ES_DELITOS_SEXUALES , ES_SANCION_ADMINISTRATIVA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	ES_BANDERA_SI_NO
(?i)(true false)	ES_BANDERA_TRUE_FALSE
(?i)(yes)	ES_BANDERA_YES_NO
(?i)([sn])	ES_BANDERA_S_N
(?i)([yx])	ES_BANDERA_Y_N
([01])	ES_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-0-1.txt , chosen by a keyed hash.

Used by: ES_BANDERA

CONFIGURATION

lookupFile	es-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-s-n.txt , chosen by a keyed hash.

Used by: ES_BANDERA

CONFIGURATION

lookupFile	es-bandera-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-si-no.txt , chosen by a keyed hash.

Used by: ES_BANDERA

CONFIGURATION

lookupFile	es-bandera-si-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-true-false.txt , chosen by a keyed hash.

Used by: ES_BANDERA

CONFIGURATION

lookupFile	es-bandera-true-false.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-y-n.txt , chosen by a keyed hash.

Used by: ES_BANDERA

CONFIGURATION

lookupFile	es-bandera-y-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in es-bandera-yes-no.txt , chosen by a keyed hash.

Used by: ES_BANDERA

CONFIGURATION

lookupFile	es-bandera-yes-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_SUPRIMIR .

Used by: ES_L3_CONVICCION_FILOSOFICA , ES_L3_AFILIACION_SINDICAL , ES_L3_VIDA_SEXUAL , ES_L3_VICTIMA , ES_SALUD_VIH , ES_SALUD_REPRODUCTIVA , ES_SALUD_MENTAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_SUPRIMIR

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC STRING ALGORITHM CHAIN

Applies ES_CCC_1 → ES_CCC_2 → ES_CCC_RESTAURAR , in this order.

Used by: ES_CUENTA

CONFIGURATION

algorithmReferences[1]	ES_CCC_1
algorithmReferences[2]	ES_CCC_2
algorithmReferences[3]	ES_CCC_RESTAURAR

ES_CCC_1 STRING ALGORITHM CHAIN

Applies ES_CCC_CUENTA → ES_CCC_MARCAR → ES_CCC_ANTERIOR → ES_CCC_ESTADO → ES_CCC_PASO_00 → ES_CCC_PASO_01 → ES_CCC_PASO_02 → ES_CCC_PASO_03 , in this order.

Used by: ES_CCC

CONFIGURATION

algorithmReferences[1]	ES_CCC_CUENTA
algorithmReferences[2]	ES_CCC_MARCAR
algorithmReferences[3]	ES_CCC_ANTERIOR
algorithmReferences[4]	ES_CCC_ESTADO
algorithmReferences[5]	ES_CCC_PASO_00
algorithmReferences[6]	ES_CCC_PASO_01
algorithmReferences[7]	ES_CCC_PASO_02
algorithmReferences[8]	ES_CCC_PASO_03

ES_CCC_2 STRING ALGORITHM CHAIN

Applies ES_CCC_PASO_04 → ES_CCC_PASO_05 → ES_CCC_PASO_06 → ES_CCC_PASO_07 → ES_CCC_PASO_08 → ES_CCC_PASO_09 → ES_CCC_PASO_10 → ES_CCC_CONTROL , in this order.

Used by: ES_CCC

CONFIGURATION

algorithmReferences[1]	ES_CCC_PASO_04
algorithmReferences[2]	ES_CCC_PASO_05
algorithmReferences[3]	ES_CCC_PASO_06
algorithmReferences[4]	ES_CCC_PASO_07
algorithmReferences[5]	ES_CCC_PASO_08
algorithmReferences[6]	ES_CCC_PASO_09
algorithmReferences[7]	ES_CCC_PASO_10
algorithmReferences[8]	ES_CCC_CONTROL

ES_CCC_ANTERIOR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(0)(.*)	keep · replace with a · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(1)(.*)	keep · replace with b · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(2)(.*)	keep · replace with c · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(3)(.*)	keep · replace with d · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(4)(.*)	keep · replace with e · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(5)(.*)	keep · replace with f · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(6)(.*)	keep · replace with g · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(7)(.*)	keep · replace with h · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(8)(.*)	keep · replace with i · keep
(\d{4}[\s\-_]? \d{4}[\s\-_]? \d)(9)(.*)	keep · replace with j · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_CONTROL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_2

PATTERNS, TRIED IN ORDER

(.*)([a-j]\d{2})(.*)	keep · ES_CCC_CONTROL_TABLA · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_CONTROL_TABLA DATA CLEANSING

Replaces each value found in es-ccc-control.txt (110 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_CCC_CONTROL

CONFIGURATION

lookupFile	es-ccc-control.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_CCC_CUENTA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

(\d{4}[\s-]??\d{4}[\s-]??\d{2}[\s-]?)(\d{10})	keep · ES_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_ESTADO REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

(.*) (0)	keep · replace with 000
(.*) (1)	keep · replace with 100
(.*) (2)	keep · replace with 200
(.*) (3)	keep · replace with 300
(.*) (4)	keep · replace with 400
(.*) (5)	keep · replace with 500
(.*) (6)	keep · replace with 600
(.*) (7)	keep · replace with 700
(.*) (8)	keep · replace with 800
(.*) (9)	keep · replace with 900
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

[illegible]

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_PASO DATA CLEANSING

Replaces each value found in `es-ccc-paso.txt` (132 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_CCC_PASO_00, ES_CCC_PASO_01, ES_CCC_PASO_02, ES_CCC_PASO_03, ES_CCC_PASO_04, ES_CCC_PASO_05, ES_CCC_PASO_06, ES_CCC_PASO_07, ES_CCC_PASO_08, ES_CCC_PASO_09, ES_CCC_PASO_10, ES_IBAN_COMPACTO_PASO_00, ES_IBAN_COMPACTO_PASO_01, ES_IBAN_COMPACTO_PASO_02, ES_IBAN_COMPACTO_PASO_03, ES_IBAN_COMPACTO_PASO_04, ES_IBAN_COMPACTO_PASO_05, ES_IBAN_COMPACTO_PASO_06, ES_IBAN_COMPACTO_PASO_07, ES_IBAN_COMPACTO_PASO_08, ES_IBAN_COMPACTO_PASO_09, ES_IBAN_IMPRESO_PASO_00, ES_IBAN_IMPRESO_PASO_01, ES_IBAN_IMPRESO_PASO_02, ES_IBAN_IMPRESO_PASO_03, ES_IBAN_IMPRESO_PASO_04, ES_IBAN_IMPRESO_PASO_05, ES_IBAN_IMPRESO_PASO_06, ES_IBAN_IMPRESO_PASO_07, ES_IBAN_IMPRESO_PASO_08, ES_IBAN_IMPRESO_PASO_09, ES_IBAN_IMPRESO_PASO_10, ES_IBAN_IMPRESO_PASO_11

CONFIGURATION

lookupFile	es-ccc-paso.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_CCC_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

<code>(.*)({3})({0})</code>	<code>keep · ES_CCC_PASO · keep</code>
<code>otherwise</code>	<code>keep</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_PAS0_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

```

(.*)(. {3})(. {1})      keep · ES_CCC_PASO · keep
otherwise                keep

```

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_PAS0_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_1

PATTERNS, TRIED IN ORDER

<code>(.*)({3}).{2}</code>	<code>keep · ES_CCC_PASO · keep</code>
<code>otherwise</code>	<code>keep</code>

CONFIGURATION

```
trimInput      yes
```

requireMask	no
ES_CCC_PASO_03 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CCC_1	
PATTERNS, TRIED IN ORDER	
(.*)(.{3}).{3})	keep · ES_CCC_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_CCC_PASO_04 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CCC_2	
PATTERNS, TRIED IN ORDER	
(.*)(.{3}).{4})	keep · ES_CCC_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_CCC_PASO_05 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CCC_2	
PATTERNS, TRIED IN ORDER	
(.*)(.{3}).{5})	keep · ES_CCC_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_CCC_PASO_06 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CCC_2	
PATTERNS, TRIED IN ORDER	
(.*)(.{3}).{6})	keep · ES_CCC_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_CCC_PASO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_2

PATTERNS, TRIED IN ORDER

(.*)({3})({7})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_PASO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_2

PATTERNS, TRIED IN ORDER

(.*)({3})({8})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_PASO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_2

PATTERNS, TRIED IN ORDER

(.*)({3})({9})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_PASO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC_2

PATTERNS, TRIED IN ORDER

(.*)({3})({10})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CCC_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CCC

PATTERNS, TRIED IN ORDER

$(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)$	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with
$(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)$	· keep · replace with · keep · replace with · keep
$(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)$	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with
$(\wedge_*)_(\wedge_*)$	· keep · replace with · keep
$(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)$	keep · replace with · keep · replace with · keep · replace with · keep · replace with
$(\wedge_*)$	· keep
$(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)_(\wedge_*)$	keep · replace with · keep · replace with · keep · replace with · keep
$(\wedge_*)_(\wedge_*)_(\wedge_*)$	keep · replace with · keep · replace with · keep
$(\wedge_*)_(\wedge_*)$	keep · replace with · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CENTRO_EDUCATIVO SECURE LOOKUP

Replaces the value with one of the 14 values in `es-centros-educativos.txt`, chosen by a keyed hash.

Used by: ES_L2_CENTRO0_EDUCATIVO

CONFIGURATION

lookupFile	es-centros-educativos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `es-cie10.txt`, chosen by a keyed hash.

Used by: ES_DIAGNOSTIC0

CONFIGURATION

lookupFile	es-cie10.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `es-cie10-decimal.txt`, chosen by a keyed hash.

Used by: ES_DIAGNOSTICO

CONFIGURATION

lookupFile	es-cie10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

Used by: ES_L1_CODIGO_ESTUDIANTE , ES_L1_COLEGIADO , ES_L1_DIRECCION_COMPLEMENTO , ES_L1_BILLETERA , ES_L1_COOKIE , ES_L1_VEHICULO , ES_L1_CONTRATO , ES_L1_USUARIO , ES_SALUD_IDENTIFICADOR , ES_SALUD_RESULTADO_PRUEBA , ES_CATEGORIA_SUPRIMIDA , ES_DOCUMENTO , ES_NSS , ES_NOMBRES , ES_APELLIDOS , ES_NOMBRE_COMPLETO , ES_EMAIL , ES_REFERENCIA_CATASTRAL , ES_CUPS , ES_SITUACION_ADMINISTRATIVA , ES_RELIGION , ES_PARTIDO , ES_ORIENTACION_SEXUAL , ES_IDENTIDAD_GENERO , ES_MEDICAMENTO , ES_DISCAPACIDAD , ES_APTITUD_LABORAL , ES_PRESTACION_SOCIAL , ES_ANTECEDENTES , ES_DELITOS_SEXUALES , ES_PROCEDIMIENTO_JUDICIAL , ES_SANCION_ADMINISTRATIVA

CONFIGURATION

characterGroups	0123456789 AEIOU BCDFGHJKLMNPQRSTUVWXYZ aeiou bcd fghjklmnpqrstvwxyz ÁÉÍÓÚÚ áéíóúú ÀÈÏ àèì
caseSensitive	yes
minMaskedPositions	0

ES_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: ES_DNI_CUERPO , ES_DOCUMENTO , ES_NSS_CUERPO , ES_TELEFONO , ES_CCC_CUENTA , ES_CUENTA , ES_MATRICULA , ES_RC_URBANA_PARCELA , ES_RC_RUSTICA_PARCELA , ES_REFERENCIA_CATASTRAL , ES_CUPS_PUNTO , ES_COORDENADA , ES_ANIO , ES_EDAD , ES_OCUPACION_O_CODIGO , ES_COBERTURA_SALUD , ES_PROCEDIMIENTO , ES_HISTORIAL_CREDITICIO , ES_PROCEDIMIENTO_JUDICIAL

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0

ES_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: ES_L1_PASAPORTE , ES_L1_SOPORTE_DOCUMENTO , ES_DOCUMENTO , ES_MATRICULA , ES_PROCEDIMIENTO

CONFIGURATION

characterGroups	0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

ES_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: ES_L1_DISPOSITIVO , ES_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

ES_CM_MATRICULA CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: ES_MATRICULA

CONFIGURATION

characterGroups	0123456789 BCDFGHJKLMNPRSTVWXYZ
caseSensitive	yes
minMaskedPositions	0

ES_COBERTURA SECURE LOOKUP

Replaces the value with one of the 9 values in es-cobertura-salud.txt , chosen by a keyed hash.

Used by: ES_COBERTURA_SALUD

CONFIGURATION

lookupFile	es-cobertura-salud.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_COBERTURA .

Used by: ES_SALUD_COBERTURA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,8})	ES_CM_DIGITOS
otherwise	ES_COBERTURA

CONFIGURATION

trimInput	yes
requireMask	no

ES_CODIGO_MUNICIPIO DATA CLEANSING

Replaces each value found in es-codigos-municipio-generalizados.txt (15,400 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_L2_CODIGO_MUNICIPIO

CONFIGURATION

lookupFile	es-codigos-municipio-generalizados.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_CODIGO_POSTAL DATA CLEANSING

Replaces each value found in es-codigos-postales-generalizados.txt (8,638 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_L2_CODIGO_POSTAL

CONFIGURATION

lookupFile	es-codigos-postales-generalizados.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_L2_PERSONAS_A_CARGO

PATTERNS, TRIED IN ORDER

([0-5])	keep
(\d+)	replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_L1_GEOLOCALIZACION

PATTERNS, TRIED IN ORDER

(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)	keep · ES_CM_DIGITOS · keep · keep · ES_CM_DIGITOS
(-?\d{1,3}[.,]\d)(\d+)	keep · ES_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUENTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_DIGITOS .

Used by: ES_L1_CUENTA_BANCARIA

PATTERNS, TRIED IN ORDER

(ES\d{22})	ES_IBAN_COMPACTO
(ES\d{2} \d{4} \d{4} \d{4} \d{4} \d{4})	ES_IBAN_IMPRESO
(\d{4}[\s-]? \d{4}[\s-]? \d{2}[\s-]? \d{10})	ES_CCC
otherwise	ES_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

Used by: ES_L1_CUPS

PATTERNS, TRIED IN ORDER

(ES\s?\d{4}\s?\d{4}\s?\d{4}\s?\d{4}\s?[A-Za-z]{2}(:\d[A-Za-z])?)	ES_CUPS_CADENA
otherwise	ES_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_CADENA STRING ALGORITHM CHAIN

Applies ES_CUPS_CADENA_1 → ES_CUPS_CADENA_2 → ES_CUPS_CADENA_3 → ES_CUPS_CADENA_4 , in this order.

Used by: ES_CUPS

CONFIGURATION

algorithmReferences[1]	ES_CUPS_CADENA_1
algorithmReferences[2]	ES_CUPS_CADENA_2
algorithmReferences[3]	ES_CUPS_CADENA_3
algorithmReferences[4]	ES_CUPS_CADENA_4

ES_CUPS_CADENA_1 STRING ALGORITHM CHAIN

Applies ES_CUPS_PUNTO → ES_CUPS_MARCAR → ES_CUPS_PREPARAR → ES_CUPS_PASO_00 → ES_CUPS_PASO_01 → ES_CUPS_PASO_02 → ES_CUPS_PASO_03 → ES_CUPS_PASO_04 , in this order.

Used by: ES_CUPS_CADENA

CONFIGURATION

algorithmReferences[1]	ES_CUPS_PUNTO
algorithmReferences[2]	ES_CUPS_MARCAR
algorithmReferences[3]	ES_CUPS_PREPARAR
algorithmReferences[4]	ES_CUPS_PASO_00
algorithmReferences[5]	ES_CUPS_PASO_01
algorithmReferences[6]	ES_CUPS_PASO_02
algorithmReferences[7]	ES_CUPS_PASO_03
algorithmReferences[8]	ES_CUPS_PASO_04

ES_CUPS_CADENA_2 STRING ALGORITHM CHAIN

Applies ES_CUPS_PASO_05 → ES_CUPS_PASO_06 → ES_CUPS_PASO_07 → ES_CUPS_PASO_08 → ES_CUPS_PASO_09 → ES_CUPS_PASO_10 → ES_CUPS_PASO_11 → ES_CUPS_PASO_12 , in this order.

Used by: ES_CUPS_CADENA

CONFIGURATION

algorithmReferences[1]	ES_CUPS_PASO_05
algorithmReferences[2]	ES_CUPS_PASO_06
algorithmReferences[3]	ES_CUPS_PASO_07
algorithmReferences[4]	ES_CUPS_PASO_08
algorithmReferences[5]	ES_CUPS_PASO_09
algorithmReferences[6]	ES_CUPS_PASO_10
algorithmReferences[7]	ES_CUPS_PASO_11
algorithmReferences[8]	ES_CUPS_PASO_12

ES_CUPS_CADENA_3 STRING ALGORITHM CHAIN

Applies ES_CUPS_PASO_13 → ES_CUPS_PASO_14 → ES_CUPS_PASO_15 → ES_CUPS_PASO_16 → ES_CUPS_PASO_17 → ES_CUPS_PASO_18 → ES_CUPS_PASO_19 → ES_CUPS_PASO_20 , in this order.

Used by: ES_CUPS_CADENA

CONFIGURATION

algorithmReferences[1]	ES_CUPS_PASO_13
algorithmReferences[2]	ES_CUPS_PASO_14
algorithmReferences[3]	ES_CUPS_PASO_15
algorithmReferences[4]	ES_CUPS_PASO_16
algorithmReferences[5]	ES_CUPS_PASO_17
algorithmReferences[6]	ES_CUPS_PASO_18
algorithmReferences[7]	ES_CUPS_PASO_19
algorithmReferences[8]	ES_CUPS_PASO_20

ES_CUPS_CADENA_4 STRING ALGORITHM CHAIN

Applies ES_CUPS_PASO_21 → ES_CUPS_LETRAS → ES_CUPS_RESTAURAR , in this order.

Used by: ES_CUPS_CADENA

CONFIGURATION

algorithmReferences[1]	ES_CUPS_PASO_21
algorithmReferences[2]	ES_CUPS_LETRAS
algorithmReferences[3]	ES_CUPS_RESTAURAR

ES_CUPS_LETRAS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_4

PATTERNS, TRIED IN ORDER

(.*) (\d{3}~) (.*)	keep · ES_CUPS_LETRAS_TABLA · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_LETRAS_TABLA DATA CLEANSING

Replaces each value found in es-cups-lettras.txt (529 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_CUPS_LETRAS

CONFIGURATION

lookupFile	es-cups-lettras.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_CUPS_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO DATA CLEANSING

Replaces each value found in es-cups-paso.txt (6,877 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_CUPS_PASO_00 , ES_CUPS_PASO_01 , ES_CUPS_PASO_02 , ES_CUPS_PASO_03 , ES_CUPS_PASO_04 , ES_CUPS_PASO_05 , ES_CUPS_PASO_06 , ES_CUPS_PASO_07 , ES_CUPS_PASO_08 , ES_CUPS_PASO_09 , ES_CUPS_PASO_10 , ES_CUPS_PASO_11 , ES_CUPS_PASO_12 , ES_CUPS_PASO_13 , ES_CUPS_PASO_14 , ES_CUPS_PASO_15 , ES_CUPS_PASO_16 , ES_CUPS_PASO_17 , ES_CUPS_PASO_18 , ES_CUPS_PASO_19 , ES_CUPS_PASO_20 , ES_CUPS_PASO_21

CONFIGURATION

lookupFile	es-cups-paso.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_CUPS_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

(.{0}).{4}(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

(.{1}).{4}(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

(.{2})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

(.{3})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

(.{4})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{5})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
ES_CUPS_PASO_06 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CUPS_CADENA_2	
PATTERNS, TRIED IN ORDER	
(.{6})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_CUPS_PASO_07 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CUPS_CADENA_2	
PATTERNS, TRIED IN ORDER	
(.{7})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_CUPS_PASO_08 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CUPS_CADENA_2	
PATTERNS, TRIED IN ORDER	
(.{8})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_CUPS_PASO_09 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_CUPS_CADENA_2	
PATTERNS, TRIED IN ORDER	
(.{9})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_CUPS_PASO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{10})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{11})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{12})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{13})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{14})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{15})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{16})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{17})(.{4})(.*)	keep · ES_CUPS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PASO_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{18})(.{4})(.*)	keep · ES_CUPS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PAS0_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{19})(.{4})(.*)	keep · ES_CUPS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PAS0_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_3

PATTERNS, TRIED IN ORDER

(.{20})(.{4})(.*)	keep · ES_CUPS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PAS0_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_4

PATTERNS, TRIED IN ORDER

(.{21})(.{4})(.*)	keep · ES_CUPS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_CUPS_PREPARAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_CUPS_CADENA_1

PATTERNS, TRIED IN ORDER

(E)(.*[\d_])([A-Za-z]{2})(\d[A-Za-z])	replace with 000E · keep · replace with ~ · keep
---------------------------------------	--

CONFIGURATION

trimInput	yes
requireMask	no

ES_DELITOS_SEXUALES_LISTA SECURE LOOKUP

Replaces the value with one of the 5 values in `es-certificado-delitos-sexuales.txt` , chosen by a keyed hash.

Used by: `ES_DELITOS_SEXUALES`

CONFIGURATION

lookupFile	<code>es-certificado-delitos-sexuales.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_DEPENDENCIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`ES_DEPENDENCIA_LISTA` .

Used by: `ES_SALUD_DEPENDENCIA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snx01])</code>	<code>ES_BANDERA</code>
<code>(\d{1,6})</code>	<code>ES_DEPENDENCIA_CODIGO</code>
otherwise	<code>ES_DEPENDENCIA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_DEPENDENCIA_CODIGO SECURE LOOKUP

Replaces the value with one of the 3 values in `es-dependencia-codigos.txt` , chosen by a keyed hash.

Used by: `ES_DEPENDENCIA`

CONFIGURATION

lookupFile	<code>es-dependencia-codigos.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_DEPENDENCIA_LISTA SECURE LOOKUP

Replaces the value with one of the 5 values in `es-dependencia.txt` , chosen by a keyed hash.

Used by: `ES_DEPENDENCIA`

CONFIGURATION

lookupFile	<code>es-dependencia.txt</code>
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

ES_DIAGNOSTICO_TEXT0 .

Used by: ES_SALUD_DIAGNOSTICO

PATTERNS, TRIED IN ORDER

([A-TV-Za-tv-z]\d{2}\. [\dA-Za-z]{1,4})	ES_CIE10_DECIMAL
([A-TV-Za-tv-z]\d{2,3}X?)	ES_CIE10
(?i)(s[ií] no true false yes [sn]yx01))	ES_BANDERA
otherwise	ES_DIAGNOSTICO_TEXT0

CONFIGURATION

trimInput	yes
requireMask	no

ES_DIAGNOSTICO_TEXT0 SECURE LOOKUP

Replaces the value with one of the 30 values in es-diagnostics.txt , chosen by a keyed hash.

Used by: ES_DIAGNOSTICO

CONFIGURATION

lookupFile	es-diagnostics.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in es-direcciones.txt , chosen by a keyed hash.

Used by: ES_L1_DIRECCION

CONFIGURATION

lookupFile	es-direcciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_DISCAPACIDAD_LISTA .

Used by: ES_SALUD_DISCAPACIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_DISCAPACIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `es-discapacidades.txt`, chosen by a keyed hash.

Used by: `ES_DISCAPACIDAD`

CONFIGURATION

lookupFile	es-discapacidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_DNI STRING ALGORITHM CHAIN

Applies `ES_DNI_1` → `ES_DNI_2` → `ES_DNI_RESTAURAR`, in this order.

Used by: `ES_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	ES_DNI_1
algorithmReferences[2]	ES_DNI_2
algorithmReferences[3]	ES_DNI_RESTAURAR

ES_DNI_1 STRING ALGORITHM CHAIN

Applies `ES_DNI_CUERPO` → `ES_DNI_MARCAR` → `ES_DNI_PREPARAR` → `ES_DNI_PASO_00` → `ES_DNI_PASO_01` → `ES_DNI_PASO_02` → `ES_DNI_PASO_03` → `ES_DNI_PASO_04`, in this order.

Used by: `ES_DNI`

CONFIGURATION

algorithmReferences[1]	ES_DNI_CUERPO
algorithmReferences[2]	ES_DNI_MARCAR
algorithmReferences[3]	ES_DNI_PREPARAR
algorithmReferences[4]	ES_DNI_PASO_00
algorithmReferences[5]	ES_DNI_PASO_01
algorithmReferences[6]	ES_DNI_PASO_02
algorithmReferences[7]	ES_DNI_PASO_03
algorithmReferences[8]	ES_DNI_PASO_04

ES_DNI_2 STRING ALGORITHM CHAIN

Applies `ES_DNI_PASO_05` → `ES_DNI_PASO_06` → `ES_DNI_PASO_07` → `ES_DNI_PASO_08` → `ES_DNI_PASO_09` → `ES_DNI_PASO_10` → `ES_DNI_PASO_11` → `ES_DNI_LETRA`, in this order.

Used by: `ES_DNI`

CONFIGURATION

algorithmReferences[1]	ES_DNI_PASO_05
algorithmReferences[2]	ES_DNI_PASO_06
algorithmReferences[3]	ES_DNI_PASO_07
algorithmReferences[4]	ES_DNI_PASO_08
algorithmReferences[5]	ES_DNI_PASO_09
algorithmReferences[6]	ES_DNI_PASO_10
algorithmReferences[7]	ES_DNI_PASO_11
algorithmReferences[8]	ES_DNI_LETRA

ES_DNI_CUERPO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_1

PATTERNS, TRIED IN ORDER

([XYZKLMxyzklm])([\s-]?)(\d{7})([\s-]?)([A-Za-z])	keep · keep · ES_CM_DIGITOS · keep · keep
(\d{1,2}\.\d{3}\.\d{3})([\s-]?)([A-Za-z])	ES_CM_DIGITOS · keep · keep
(\d{6,8})([\s-]?)([A-Za-z])	ES_CM_DIGITOS · keep · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_LETRA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.*) (\d{2} [~^])	keep · ES_DNI_LETRA_TABLA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_LETRA_TABLA DATA CLEANSING

Replaces each value found in es-dni-letra.txt (46 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_DNI_LETRA

CONFIGURATION

lookupFile	es-dni-letra.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_DNI_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_1

PATTERNS, TRIED IN ORDER

([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO DATA CLEANSING

Replaces each value found in es-dni-paso.txt (575 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_DNI_PASO_00 , ES_DNI_PASO_01 , ES_DNI_PASO_02 , ES_DNI_PASO_03 , ES_DNI_PASO_04 , ES_DNI_PASO_05 , ES_DNI_PASO_06 , ES_DNI_PASO_07 , ES_DNI_PASO_08 , ES_DNI_PASO_09 , ES_DNI_PASO_10 , ES_DNI_PASO_11

CONFIGURATION

lookupFile	es-dni-paso.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_DNI_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_1

PATTERNS, TRIED IN ORDER

(.{0})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_1

PATTERNS, TRIED IN ORDER

(.{1})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
ES_DNI_PASO_02 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_DNI_1	
PATTERNS, TRIED IN ORDER	
(.{2})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_DNI_PASO_03 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_DNI_1	
PATTERNS, TRIED IN ORDER	
(.{3})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_DNI_PASO_04 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_DNI_1	
PATTERNS, TRIED IN ORDER	
(.{4})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_DNI_PASO_05 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_DNI_2	
PATTERNS, TRIED IN ORDER	
(.{5})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_DNI_PASO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PASO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_2

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · ES_DNI_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_DNI_PREPARAR REGEX DECOMPOSE

Tries 44 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_DNI_1

PATTERNS, TRIED IN ORDER

(0)(.*)(([A-Z])	replace with 000 · keep · replace with ~
(0)(.*)(([a-z])	replace with 000 · keep · replace with ^
(1)(.*)(([A-Z])	replace with 001 · keep · replace with ~
(1)(.*)(([a-z])	replace with 001 · keep · replace with ^
(2)(.*)(([A-Z])	replace with 002 · keep · replace with ~
(2)(.*)(([a-z])	replace with 002 · keep · replace with ^
(3)(.*)(([A-Z])	replace with 003 · keep · replace with ~
(3)(.*)(([a-z])	replace with 003 · keep · replace with ^
(4)(.*)(([A-Z])	replace with 004 · keep · replace with ~
(4)(.*)(([a-z])	replace with 004 · keep · replace with ^
(5)(.*)(([A-Z])	replace with 005 · keep · replace with ~
(5)(.*)(([a-z])	replace with 005 · keep · replace with ^
(6)(.*)(([A-Z])	replace with 006 · keep · replace with ~
(6)(.*)(([a-z])	replace with 006 · keep · replace with ^
(7)(.*)(([A-Z])	replace with 007 · keep · replace with ~
(7)(.*)(([a-z])	replace with 007 · keep · replace with ^
(8)(.*)(([A-Z])	replace with 008 · keep · replace with ~
(8)(.*)(([a-z])	replace with 008 · keep · replace with ^
(9)(.*)(([A-Z])	replace with 009 · keep · replace with ~
(9)(.*)(([a-z])	replace with 009 · keep · replace with ^
(X)(.*)(([A-Z])	replace with 00X · keep · replace with ~

requireMask	no
-------------	----

ES_DOCUMENTO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

Used by: ES_L1_DNI , ES_L1_NIE

PATTERNS, TRIED IN ORDER

([XYZxyz] [\s\~]? \d{7} [\s\~]? [A-Za-z] [KLMk\lm] [\s\~]? \d{7} [\s\~]? [A-Za-z] \d{1,2} \. \d{3} \. \d{3} [\s\~]? [A-Za-z] \d{6,8} [\s\~]? [A-Za-z])	ES_DNI
([ABCDEFGHJNPQRSUVWabcde fghjnpqrsuvw] [\s\~]? \d{7} [\s\~]? [0-9A-Ja-j])	keep
(\d{1,2} \. ? \d{3} \. ? \d{3})	ES_CM_DIGITOS
([A-Za-z] {2,3} \d{6})	ES_CM_DIGITOS_LETRAS
otherwise	ES_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

ES_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_L2_EDAD

PATTERNS, TRIED IN ORDER

(\d{3,})	replace with 90
([1-9]) (\d) ([.,] \d+)	keep · ES_CM_DIGITOS · keep
([1-9]) (\d)	keep · ES_CM_DIGITOS
(\d)	ES_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

Used by: ES_L1_EMAIL

PATTERNS, TRIED IN ORDER

(([^@\\s]+) @ ([^@\\s]+) \. ([A-Za-z] {2,24} (? : \. [A-Za-z] {2}) ?))	ES_CM_ALFANUM · ES_CM_ALFANUM · replace with test
otherwise	ES_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

ES_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in es-empleadores.txt , chosen by a keyed hash.

Used by: ES_L2_EMPLEADOR

CONFIGURATION

lookupFile	es-empleadores.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ESTADO_CIVIL_LISTA .

Used by: ES_L2_ESTADO_CIVIL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_ESTADO_CIVIL_CODIGO
otherwise	ES_ESTADO_CIVIL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in es-estado-civil-codigos.txt , chosen by a keyed hash.

Used by: ES_ESTADO_CIVIL

CONFIGURATION

lookupFile	es-estado-civil-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in es-estado-civil.txt , chosen by a keyed hash.

Used by: ES_ESTADO_CIVIL

CONFIGURATION

lookupFile	es-estado-civil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 11 values in `es-estados-credito.txt` , chosen by a keyed hash.

Used by: `ES_HISTORIAL_CREDITICIO`

CONFIGURATION

lookupFile	es-estados-credito.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `ES_L2_FECHA_EVENTO`

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

ES_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `ES_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS
roll	no

ES_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in `es-grupos-sanguineos.txt` , chosen by a keyed hash.

Used by: `ES_SALUD_GRUPO_SANGUINEO`

CONFIGURATION

lookupFile	es-grupos-sanguineos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `ES_ESTADO_CREDITO` .

Used by: `ES_FIN_HISTORIAL_CREDITICIO`

PATTERNS, TRIED IN ORDER

(\d{1,4})	ES_CM_DIGITOS
(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
otherwise	ES_ESTADO_CREDITO

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_AJUSTE DATA CLEANSING

Replaces each value found in `es-iban-ajuste.txt` (10,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_IBAN_COMPACTO_AJUSTE` , `ES_IBAN_IMPRESO_AJUSTE`

CONFIGURATION

lookupFile	es-iban-ajuste.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_IBAN_COMPACTO STRING ALGORITHM CHAIN

Applies `ES_IBAN_COMPACTO_1` → `ES_IBAN_COMPACTO_2` → `ES_IBAN_COMPACTO_3` → `ES_IBAN_COMPACTO_4` , in this order.

Used by: `ES_CUENTA`

CONFIGURATION

algorithmReferences[1]	ES_IBAN_COMPACTO_1
algorithmReferences[2]	ES_IBAN_COMPACTO_2
algorithmReferences[3]	ES_IBAN_COMPACTO_3
algorithmReferences[4]	ES_IBAN_COMPACTO_4

ES_IBAN_COMPACTO_1 STRING ALGORITHM CHAIN

Applies `ES_IBAN_COMPACTO_MASCARA` → `ES_IBAN_COMPACTO_MARCAR` → `ES_IBAN_COMPACTO_ANTERIOR` → `ES_IBAN_COMPACTO_ESTADO` → `ES_IBAN_COMPACTO_PASO_00` → `ES_IBAN_COMPACTO_PASO_01` → `ES_IBAN_COMPACTO_PASO_02` → `ES_IBAN_COMPACTO_PASO_03` , in this order.

Used by: `ES_IBAN_COMPACTO`

CONFIGURATION

algorithmReferences[1]	ES_IBAN_COMPACTO_MASCARA
algorithmReferences[2]	ES_IBAN_COMPACTO_MARCAR
algorithmReferences[3]	ES_IBAN_COMPACTO_ANTERIOR
algorithmReferences[4]	ES_IBAN_COMPACTO_ESTADO
algorithmReferences[5]	ES_IBAN_COMPACTO_PASO_00
algorithmReferences[6]	ES_IBAN_COMPACTO_PASO_01
algorithmReferences[7]	ES_IBAN_COMPACTO_PASO_02
algorithmReferences[8]	ES_IBAN_COMPACTO_PASO_03

ES_IBAN_COMPACTO_2 STRING ALGORITHM CHAIN

Applies ES_IBAN_COMPACTO_PASO_04 → ES_IBAN_COMPACTO_PASO_05 → ES_IBAN_COMPACTO_PASO_06 → ES_IBAN_COMPACTO_PASO_07 → ES_IBAN_COMPACTO_PASO_08 → ES_IBAN_COMPACTO_PASO_09 → ES_IBAN_COMPACTO_CONTROL → ES_IBAN_COMPACTO TRASLADO_00 , in this order.

Used by: ES_IBAN_COMPACTO

CONFIGURATION

algorithmReferences[1]	ES_IBAN_COMPACTO_PASO_04
algorithmReferences[2]	ES_IBAN_COMPACTO_PASO_05
algorithmReferences[3]	ES_IBAN_COMPACTO_PASO_06
algorithmReferences[4]	ES_IBAN_COMPACTO_PASO_07
algorithmReferences[5]	ES_IBAN_COMPACTO_PASO_08
algorithmReferences[6]	ES_IBAN_COMPACTO_PASO_09
algorithmReferences[7]	ES_IBAN_COMPACTO_CONTROL
algorithmReferences[8]	ES_IBAN_COMPACTO TRASLADO_00

ES_IBAN_COMPACTO_3 STRING ALGORITHM CHAIN

Applies ES_IBAN_COMPACTO TRASLADO_01 → ES_IBAN_COMPACTO TRASLADO_02 → ES_IBAN_COMPACTO TRASLADO_03 → ES_IBAN_COMPACTO TRASLADO_04 → ES_IBAN_COMPACTO TRASLADO_05 → ES_IBAN_COMPACTO TRASLADO_06 → ES_IBAN_COMPACTO TRASLADO_07 → ES_IBAN_COMPACTO TRASLADO_08 , in this order.

Used by: ES_IBAN_COMPACTO

CONFIGURATION

algorithmReferences[1]	ES_IBAN_COMPACTO TRASLADO_01
algorithmReferences[2]	ES_IBAN_COMPACTO TRASLADO_02
algorithmReferences[3]	ES_IBAN_COMPACTO TRASLADO_03
algorithmReferences[4]	ES_IBAN_COMPACTO TRASLADO_04
algorithmReferences[5]	ES_IBAN_COMPACTO TRASLADO_05
algorithmReferences[6]	ES_IBAN_COMPACTO TRASLADO_06
algorithmReferences[7]	ES_IBAN_COMPACTO TRASLADO_07
algorithmReferences[8]	ES_IBAN_COMPACTO TRASLADO_08

ES_IBAN_COMPACTO_4 STRING ALGORITHM CHAIN

Applies ES_IBAN_COMPACTO_AJUSTE → ES_IBAN_COMPACTO RESTAURAR , in this order.

Used by: ES_IBAN_COMPACTO

CONFIGURATION

algorithmReferences[1]	ES_IBAN_COMPACTO_AJUSTE
algorithmReferences[2]	ES_IBAN_COMPACTO RESTAURAR

ES_IBAN_COMPACTO_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_4

PATTERNS, TRIED IN ORDER

(ES)(\d{4})(.*)	keep · ES_IBAN_AJUSTE · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_ANTERIOR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_1

PATTERNS, TRIED IN ORDER

(ES\d{11})(0)(.*)	keep · replace with a · keep
(ES\d{11})(1)(.*)	keep · replace with b · keep
(ES\d{11})(2)(.*)	keep · replace with c · keep
(ES\d{11})(3)(.*)	keep · replace with d · keep
(ES\d{11})(4)(.*)	keep · replace with e · keep
(ES\d{11})(5)(.*)	keep · replace with f · keep
(ES\d{11})(6)(.*)	keep · replace with g · keep
(ES\d{11})(7)(.*)	keep · replace with h · keep
(ES\d{11})(8)(.*)	keep · replace with i · keep
(ES\d{11})(9)(.*)	keep · replace with j · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_CONTROL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

(.*)([a-j]\d{2})(.{10})	keep · ES_IBAN_CONTROL_TABLA · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_ESTADO REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_1

PATTERNS, TRIED IN ORDER

(.*)(0)	keep · replace with 000
(.*)(1)	keep · replace with 100
(.*)(2)	keep · replace with 200
(.*)(3)	keep · replace with 300
(.*)(4)	keep · replace with 400
(.*)(5)	keep · replace with 500
(.*)(6)	keep · replace with 600

<code>(.*) (7)</code>	keep · replace with <code>700</code>
<code>(.*) (8)</code>	keep · replace with <code>800</code>
<code>(.*) (9)</code>	keep · replace with <code>900</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `ES_IBAN_COMPACTO_1`

PATTERNS, TRIED IN ORDER

<code>([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*)</code>	keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep
<code>([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*)</code>	keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep
<code>([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*)</code>	keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep
<code>([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*)</code>	keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep
<code>([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*)</code>	keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep
<code>([^\s]*) (\s) ([^\s]*) (\s) ([^\s]*)</code>	keep · replace with <code>_</code> · keep · replace with <code>_</code> · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_MASCARA IBAN

Masks the last 10 characters of the IBAN and recomputes its two ISO 13616 check digits; the country code and the characters before stay.

Used by: `ES_IBAN_COMPACTO_1`

CONFIGURATION

validateInput	no
numCharsToMask	<code>10</code>

ES_IBAN_COMPACTO_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `ES_IBAN_COMPACTO_1`

PATTERNS, TRIED IN ORDER

<code>(.*)(.{3})(.{0})</code>	keep · <code>ES_CCC_PAS0</code> · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_1

PATTERNS, TRIED IN ORDER

(.*)({3})({1})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_1

PATTERNS, TRIED IN ORDER

(.*)({3})({2})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_1

PATTERNS, TRIED IN ORDER

(.*)({3})({3})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({4})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({5})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({6})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({7})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({8})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_PASO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_2

PATTERNS, TRIED IN ORDER

<code>(.*)({3})({9})</code>	<code>keep · ES_CCC_PAS0 · keep</code>
<code>otherwise</code>	<code>keep</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACT0_4

PATTERNS, TRIED IN ORDER

$(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)$	keep · replace with	· keep · replace with	· keep · replace with	· keep · replace with
$(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)$	· keep · replace with	· keep · replace with	· keep	
$(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)$	keep · replace with	· keep · replace with	· keep · replace with	· keep · replace with
$(\wedge_)*(_)(\wedge_)*(_)$	· keep · replace with	· keep		
$(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)$	keep · replace with	· keep · replace with	· keep · replace with	· keep · replace with
$(\wedge_)*(_)$	· keep			
$(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)$	keep · replace with	· keep · replace with	· keep · replace with	· keep
$(\wedge_)*(_)(\wedge_)*(_)(\wedge_)*(_)$	keep · replace with	· keep · replace with	· keep	
$(\wedge_)*(_)(\wedge_)*(_)$	keep · replace with	· keep		
otherwise	keep			

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO TRASLADO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACT0_2

PATTERNS, TRIED IN ORDER

```

(.{12})(.{3})(.*) keep · ES_IBAN_TRASLADO · keep
otherwise keep

```

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO TRASLADO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACT0_3

PATTERNS, TRIED IN ORDER

```

(.{11})(.{3})(.*)      keep · ES_IBAN TRASLADO · keep
otherwise                keep

```

CONFIGURATION

```
trimInput      yes
```

requireMask	no
ES_IBAN_COMPACTO TRASLADO_02 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_IBAN_COMPACTO_3	
PATTERNS, TRIED IN ORDER	
(.{10})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_IBAN_COMPACTO TRASLADO_03 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_IBAN_COMPACTO_3	
PATTERNS, TRIED IN ORDER	
(.{9})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_IBAN_COMPACTO TRASLADO_04 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_IBAN_COMPACTO_3	
PATTERNS, TRIED IN ORDER	
(.{8})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_IBAN_COMPACTO TRASLADO_05 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_IBAN_COMPACTO_3	
PATTERNS, TRIED IN ORDER	
(.{7})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_COMPACTO TRASLADO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_3

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO TRASLADO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_3

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_COMPACTO TRASLADO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_COMPACTO_3

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_CONTROL TABLA DATA CLEANSING

Replaces each value found in es-iban-control.txt (110 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_IBAN_COMPACTO_CONTROL , ES_IBAN_IMPRESO_CONTROL

CONFIGURATION

lookupFile	es-iban-control.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_IBAN_IMPRESO STRING ALGORITHM CHAIN

Applies ES_IBAN_IMPRESO_1 → ES_IBAN_IMPRESO_2 → ES_IBAN_IMPRESO_3 → ES_IBAN_IMPRESO_4 , in this order.

Used by: `ES_CUENTA`

CONFIGURATION

<code>algorithmReferences[1]</code>	<code>ES_IBAN_IMPRESO_1</code>
<code>algorithmReferences[2]</code>	<code>ES_IBAN_IMPRESO_2</code>
<code>algorithmReferences[3]</code>	<code>ES_IBAN_IMPRESO_3</code>
<code>algorithmReferences[4]</code>	<code>ES_IBAN_IMPRESO_4</code>

ES_IBAN_IMPRESO_1 STRING ALGORITHM CHAIN

Applies `ES_IBAN_IMPRESO_MASCARA` → `ES_IBAN_IMPRESO_MARCAR` → `ES_IBAN_IMPRESO_ANTERIOR` → `ES_IBAN_IMPRESO_ESTADO` → `ES_IBAN_IMPRESO_PASO_00` → `ES_IBAN_IMPRESO_PASO_01` → `ES_IBAN_IMPRESO_PASO_02` → `ES_IBAN_IMPRESO_PASO_03` , in this order.

Used by: `ES_IBAN_IMPRESO`

CONFIGURATION

<code>algorithmReferences[1]</code>	<code>ES_IBAN_IMPRESO_MASCARA</code>
<code>algorithmReferences[2]</code>	<code>ES_IBAN_IMPRESO_MARCAR</code>
<code>algorithmReferences[3]</code>	<code>ES_IBAN_IMPRESO_ANTERIOR</code>
<code>algorithmReferences[4]</code>	<code>ES_IBAN_IMPRESO_ESTADO</code>
<code>algorithmReferences[5]</code>	<code>ES_IBAN_IMPRESO_PASO_00</code>
<code>algorithmReferences[6]</code>	<code>ES_IBAN_IMPRESO_PASO_01</code>
<code>algorithmReferences[7]</code>	<code>ES_IBAN_IMPRESO_PASO_02</code>
<code>algorithmReferences[8]</code>	<code>ES_IBAN_IMPRESO_PASO_03</code>

ES_IBAN_IMPRESO_2 STRING ALGORITHM CHAIN

Applies `ES_IBAN_IMPRESO_PASO_04` → `ES_IBAN_IMPRESO_PASO_05` → `ES_IBAN_IMPRESO_PASO_06` → `ES_IBAN_IMPRESO_PASO_07` → `ES_IBAN_IMPRESO_PASO_08` → `ES_IBAN_IMPRESO_PASO_09` → `ES_IBAN_IMPRESO_PASO_10` → `ES_IBAN_IMPRESO_PASO_11` , in this order.

Used by: `ES_IBAN_IMPRESO`

CONFIGURATION

<code>algorithmReferences[1]</code>	<code>ES_IBAN_IMPRESO_PASO_04</code>
<code>algorithmReferences[2]</code>	<code>ES_IBAN_IMPRESO_PASO_05</code>
<code>algorithmReferences[3]</code>	<code>ES_IBAN_IMPRESO_PASO_06</code>
<code>algorithmReferences[4]</code>	<code>ES_IBAN_IMPRESO_PASO_07</code>
<code>algorithmReferences[5]</code>	<code>ES_IBAN_IMPRESO_PASO_08</code>
<code>algorithmReferences[6]</code>	<code>ES_IBAN_IMPRESO_PASO_09</code>
<code>algorithmReferences[7]</code>	<code>ES_IBAN_IMPRESO_PASO_10</code>
<code>algorithmReferences[8]</code>	<code>ES_IBAN_IMPRESO_PASO_11</code>

ES_IBAN_IMPRESO_3 STRING ALGORITHM CHAIN

Applies `ES_IBAN_IMPRESO_CONTROL` → `ES_IBAN_IMPRESO TRASLADO_00` → `ES_IBAN_IMPRESO TRASLADO_01` → `ES_IBAN_IMPRESO TRASLADO_02` → `ES_IBAN_IMPRESO TRASLADO_03` → `ES_IBAN_IMPRESO TRASLADO_04` → `ES_IBAN_IMPRESO TRASLADO_05` → `ES_IBAN_IMPRESO TRASLADO_06` , in this order.

Used by: `ES_IBAN_IMPRESO`

CONFIGURATION

<code>algorithmReferences[1]</code>	<code>ES_IBAN_IMPRESO_CONTROL</code>
<code>algorithmReferences[2]</code>	<code>ES_IBAN_IMPRESO TRASLADO_00</code>

algorithmReferences[3]	ES_IBAN_IMPRESO TRASLADO_01
algorithmReferences[4]	ES_IBAN_IMPRESO TRASLADO_02
algorithmReferences[5]	ES_IBAN_IMPRESO TRASLADO_03
algorithmReferences[6]	ES_IBAN_IMPRESO TRASLADO_04
algorithmReferences[7]	ES_IBAN_IMPRESO TRASLADO_05
algorithmReferences[8]	ES_IBAN_IMPRESO TRASLADO_06

ES_IBAN_IMPRESO_4 STRING ALGORITHM CHAIN

Applies ES_IBAN_IMPRESO TRASLADO_07 → ES_IBAN_IMPRESO TRASLADO_08 → ES_IBAN_IMPRESO TRASLADO_09 → ES_IBAN_IMPRESO TRASLADO_10 → ES_IBAN_IMPRESO TRASLADO_11 → ES_IBAN_IMPRESO AJUSTE → ES_IBAN_IMPRESO RESTAURAR , in this order.

Used by: ES_IBAN_IMPRESO

CONFIGURATION

algorithmReferences[1]	ES_IBAN_IMPRESO TRASLADO_07
algorithmReferences[2]	ES_IBAN_IMPRESO TRASLADO_08
algorithmReferences[3]	ES_IBAN_IMPRESO TRASLADO_09
algorithmReferences[4]	ES_IBAN_IMPRESO TRASLADO_10
algorithmReferences[5]	ES_IBAN_IMPRESO TRASLADO_11
algorithmReferences[6]	ES_IBAN_IMPRESO AJUSTE
algorithmReferences[7]	ES_IBAN_IMPRESO RESTAURAR

ES_IBAN_IMPRESO_AJUSTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER

(ES)(\d{4})(.*)	keep · ES_IBAN_AJUSTE · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_ANTERIOR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_1

PATTERNS, TRIED IN ORDER

(ES\d{2}_\d{4}_\d{4}_\d)(0)(.*)	keep · replace with a · keep
(ES\d{2}_\d{4}_\d{4}_\d)(1)(.*)	keep · replace with b · keep
(ES\d{2}_\d{4}_\d{4}_\d)(2)(.*)	keep · replace with c · keep
(ES\d{2}_\d{4}_\d{4}_\d)(3)(.*)	keep · replace with d · keep
(ES\d{2}_\d{4}_\d{4}_\d)(4)(.*)	keep · replace with e · keep
(ES\d{2}_\d{4}_\d{4}_\d)(5)(.*)	keep · replace with f · keep
(ES\d{2}_\d{4}_\d{4}_\d)(6)(.*)	keep · replace with g · keep
(ES\d{2}_\d{4}_\d{4}_\d)(7)(.*)	keep · replace with h · keep
(ES\d{2}_\d{4}_\d{4}_\d)(8)(.*)	keep · replace with i · keep

([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)	keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)\s([^\s]*)\s([^\s]*)	keep · replace with _ · keep · replace with _ · keep
([^\s]*)\s([^\s]*)	keep · replace with _ · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_MASCARA IBAN

Masks the last 12 characters of the IBAN and recomputes its two ISO 13616 check digits; the country code and the characters before stay.

Used by: ES_IBAN_IMPRESO_1

CONFIGURATION

validateInput	no
numCharsToMask	12

ES_IBAN_IMPRESO_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_1

PATTERNS, TRIED IN ORDER

(.*)(.{3})(.{0})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_1

PATTERNS, TRIED IN ORDER

(.*)(.{3})(.{1})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_1

PATTERNS, TRIED IN ORDER

(.*)(.{3})(.{2})	keep · ES_CCC_PASO · keep
------------------	---------------------------

otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_1

PATTERNS, TRIED IN ORDER	
(.*)(.{3})(.{3})	keep · ES_CCC_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER	
(.*)(.{3})(.{4})	keep · ES_CCC_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER	
(.*)(.{3})(.{5})	keep · ES_CCC_PAS0 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER	
(.*)(.{3})(.{6})	keep · ES_CCC_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({7})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({8})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({9})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_PASO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER

(.*)({3})({10})	keep · ES_CCC_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

ES_IBAN_IMPRESO_PASO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_2

PATTERNS, TRIED IN ORDER

<code>(.*)({3})({11})</code>	<code>keep · ES_CCC_PAS0 · keep</code>
<code>otherwise</code>	<code>keep</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER

[illegible]

CONFIGURATION

trimInput	yes
requireMask	no

ES IBAN IMPRESO TRASLADO 00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER

```

(.{15})(.{3})(.*)      keep · ES_IBAN_TRASLADO · keep
otherwise               keep

```

CONFIGURATION

trimInput	yes
requireMask	no

ES IBAN IMPRESO TRASLADO 01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER

<code>(.{14})(.{3})(.*)</code>	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER

<code>(.{13})(.{3})(.*)</code>	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER

<code>(.{12})(.{3})(.*)</code>	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER

<code>(.{11})(.{3})(.*)</code>	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER

<code>(.{10})(.{3})(.*)</code>	keep · ES_IBAN TRASLADO · keep
--------------------------------	--------------------------------

otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_3

PATTERNS, TRIED IN ORDER	
(.{9})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER	
(.{8})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER	
(.{7})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER	
(.{6})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN_IMPRESO TRASLADO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_IBAN_IMPRESO_4

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · ES_IBAN TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_IBAN TRASLADO DATA CLEANSING

Replaces each value found in es-iban-traslado.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_IBAN_COMPACTO TRASLADO_00 , ES_IBAN_COMPACTO TRASLADO_01 , ES_IBAN_COMPACTO TRASLADO_02 , ES_IBAN_COMPACTO TRASLADO_03 , ES_IBAN_COMPACTO TRASLADO_04 , ES_IBAN_COMPACTO TRASLADO_05 , ES_IBAN_COMPACTO TRASLADO_06 , ES_IBAN_COMPACTO TRASLADO_07 , ES_IBAN_COMPACTO TRASLADO_08 , ES_IBAN_IMPRESO TRASLADO_00 , ES_IBAN_IMPRESO TRASLADO_01 , ES_IBAN_IMPRESO TRASLADO_02 , ES_IBAN_IMPRESO TRASLADO_03 , ES_IBAN_IMPRESO TRASLADO_04 , ES_IBAN_IMPRESO TRASLADO_05 , ES_IBAN_IMPRESO TRASLADO_06 , ES_IBAN_IMPRESO TRASLADO_07 , ES_IBAN_IMPRESO TRASLADO_08 , ES_IBAN_IMPRESO TRASLADO_09 , ES_IBAN_IMPRESO TRASLADO_10 , ES_IBAN_IMPRESO TRASLADO_11

CONFIGURATION

lookupFile	es-iban-traslado.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_IDENTIDAD_GENERO_LISTA .

Used by: ES_L3_IDENTIDAD_GENERO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
--	------------

(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `es-identidades-genero.txt`, chosen by a keyed hash.

Used by: `ES_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	<code>es-identidades-genero.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_IMPORTE_TRIBUTARIO NUMERIC MAPPING

Maps the number to another between 0 and 250,000.

Used by: `ES_TRIBUTARIO`

CONFIGURATION

minValue	0
maxValue	250000

ES_INGRESOS NUMERIC MAPPING

Maps the number to another between 1,000 and 120,000.

Used by: `ES_FIN_INGRESOS`

CONFIGURATION

minValue	1000
maxValue	120000

ES_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `ES_CM_HEX`.

Used by: `ES_L1_IP`

PATTERNS, TRIED IN ORDER

(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3})	ES_OCTETO · ES_OCTETO · ES_OCTETO · ES_OCTETO
otherwise	ES_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

ES_MATRICULA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

`ES_CM_DIGITOS_LETRAS`.

Used by: ES_L1_MATRICULA

PATTERNS, TRIED IN ORDER

(\d{4})([\s-]?)([BCDFGHJKLMNPSTVWXYZ]{3})	ES_CM_DIGITOS · keep · ES_CM_MATRICULA
([A-Z]{1,2})([\s-]?)(\d{4})([\s-]?)([A-Z]{1,2})	keep · keep · ES_CM_DIGITOS · keep · ES_CM_DIGITOS_LETRAS
([ERCH])([\s-]?)(\d{4})([\s-]?)([BCDFGHJKLMNPSTVWXYZ]{3})	keep · keep · ES_CM_DIGITOS · keep · ES_CM_MATRICULA
otherwise	ES_CM_DIGITOS_LETRAS

CONFIGURATION

trimInput	yes
requireMask	no

ES_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_MEDICAMENTO_LISTA .

Used by: ES_SALUD_MEDICAMENTO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_MEDICAMENTO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 23 values in es-medicamentos.txt , chosen by a keyed hash.

Used by: ES_MEDICAMENTO

CONFIGURATION

lookupFile	es-medicamentos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_MUNICIPIO DATA CLEANSING

Replaces each value found in es-municipios-generalizados.txt (68,972 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_L2_MUNICIPIO

CONFIGURATION

lookupFile	es-municipios-generalizados.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 27 values in `es-nacionalidades.txt` , chosen by a keyed hash.

Used by: `ES_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	es-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`ES_NIVEL_EDUCATIVO_LISTA` .

Used by: `ES_L2_NIVEL_EDUCATIVO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>ES_BANDERA</code>
<code>(\d{1,6})</code>	<code>ES_NIVEL_EDUCATIVO_CODIGO</code>
otherwise	<code>ES_NIVEL_EDUCATIVO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `es-nivel-educativo-codigos.txt` , chosen by a keyed hash.

Used by: `ES_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	es-nivel-educativo-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `es-nivel-educativo.txt` , chosen by a keyed hash.

Used by: `ES_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	es-nivel-educativo.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

ES_NOMBRE NAME

Replaces the name with one of the 600 names in `es-nombres.txt`.

Used by: `ES_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	<code>es-nombres.txt</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
filterAccent	yes
inputCaseSensitive	no

ES_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `ES_CM_ALFANUM`.

Used by: `ES_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

<code>([^\,]+),\s*(.+)</code>	<code>ES_APELLIDOS</code> · <code>ES_NOMBRES</code>
<code>(\S+)</code>	<code>ES_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_APELLIDO</code> · <code>ES_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_APELLIDO</code> · <code>ES_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_APELLIDO</code> · <code>ES_PALABRA_APELLIDO</code> · <code>ES_PALABRA_APELLIDO</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_APELLIDO</code> · <code>ES_PALABRA_APELLIDO</code> · <code>ES_PALABRA_APELLIDO</code>
otherwise	<code>ES_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `ES_CM_ALFANUM`.

Used by: `ES_L1_NOMBRE`, `ES_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

<code>(\S+)</code>	<code>ES_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code>
<code>(\S+)\s+(\S+)\s+(\S+)\s+(\S+)</code>	<code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code> · <code>ES_PALABRA_NOMBRE</code>
otherwise	<code>ES_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

Used by: ES_L1_NSS

PATTERNS, TRIED IN ORDER

(\d{2}[\s\/-]?[d{8}[\s\/-]?[d{2}])	ES_NSS_CADENA
otherwise	ES_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_CADENA STRING ALGORITHM CHAIN

Applies ES_NSS_CADENA_1 → ES_NSS_CADENA_2 → ES_NSS_CADENA_3 , in this order.

Used by: ES_NSS

CONFIGURATION

algorithmReferences[1]	ES_NSS_CADENA_1
algorithmReferences[2]	ES_NSS_CADENA_2
algorithmReferences[3]	ES_NSS_CADENA_3

ES_NSS_CADENA_1 STRING ALGORITHM CHAIN

Applies ES_NSS_CUERPO → ES_NSS_MARCAR → ES_NSS_CERO → ES_NSS_PREPARAR → ES_NSS_PASO_00 → ES_NSS_PASO_01 → ES_NSS_PASO_02 → ES_NSS_PASO_03 , in this order.

Used by: ES_NSS_CADENA

CONFIGURATION

algorithmReferences[1]	ES_NSS_CUERPO
algorithmReferences[2]	ES_NSS_MARCAR
algorithmReferences[3]	ES_NSS_CERO
algorithmReferences[4]	ES_NSS_PREPARAR
algorithmReferences[5]	ES_NSS_PASO_00
algorithmReferences[6]	ES_NSS_PASO_01
algorithmReferences[7]	ES_NSS_PASO_02
algorithmReferences[8]	ES_NSS_PASO_03

ES_NSS_CADENA_2 STRING ALGORITHM CHAIN

Applies ES_NSS_PASO_04 → ES_NSS_PASO_05 → ES_NSS_PASO_06 → ES_NSS_PASO_07 → ES_NSS_PASO_08 → ES_NSS_PASO_09 → ES_NSS_PASO_10 → ES_NSS_PASO_11 , in this order.

Used by: ES_NSS_CADENA

CONFIGURATION

algorithmReferences[1]	ES_NSS_PASO_04
algorithmReferences[2]	ES_NSS_PASO_05
algorithmReferences[3]	ES_NSS_PASO_06
algorithmReferences[4]	ES_NSS_PASO_07
algorithmReferences[5]	ES_NSS_PASO_08
algorithmReferences[6]	ES_NSS_PASO_09
algorithmReferences[7]	ES_NSS_PASO_10

algorithmReferences[8]	ES_NSS_PASO_11
ES_NSS_CADENA_3 STRING ALGORITHM CHAIN	
Applies ES_NSS_PASO_12 → ES_NSS_PASO_13 → ES_NSS_CONTROL → ES_NSS_RESTAURAR → ES_NSS_ESPACIOS , in this order.	
Used by: ES_NSS_CADENA	
CONFIGURATION	
algorithmReferences[1]	ES_NSS_PASO_12
algorithmReferences[2]	ES_NSS_PASO_13
algorithmReferences[3]	ES_NSS_CONTROL
algorithmReferences[4]	ES_NSS_RESTAURAR
algorithmReferences[5]	ES_NSS_ESPACIOS
ES_NSS_CERO REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_NSS_CADENA_1	
PATTERNS, TRIED IN ORDER	
(\d{2}[_/\-]?)(\d{7}.*)	keep · replace with ! · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_NSS_CONTROL REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_NSS_CADENA_3	
PATTERNS, TRIED IN ORDER	
(.*)(\d{2}~)	keep · ES_NSS_CONTROL_TABLA
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_NSS_CONTROL_TABLA DATA CLEANSING	
Replaces each value found in es-nss-control.txt (97 pairs) by its counterpart; values not in the file stay as they are.	
Used by: ES_NSS_CONTROL	
CONFIGURATION	
lookupFile	es-nss-control.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_NSS_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_1

PATTERNS, TRIED IN ORDER

(\d{2})([\\s/\\-]?)(\d{8})([\\s/\\-]?)(\d{2})	keep · keep · ES_CM_DIGITOS · keep · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_ESPACIOS REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_3

PATTERNS, TRIED IN ORDER

([^\s]*)([^\s]*)([^\s]*)([^\s]*)([^\s]*)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with
([^\s]*)([^\s]*)([^\s]*)([^\s]*)	· keep · replace with · keep · replace with · keep
([^\s]*)([^\s]*)([^\s]*)([^\s]*)([^\s]*)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with
([^\s]*)([^\s]*)([^\s]*)	· keep · replace with · keep
([^\s]*)([^\s]*)([^\s]*)([^\s]*)([^\s]*)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep
([^\s]*)([^\s]*)([^\s]*)([^\s]*)	keep · replace with · keep · replace with · keep
([^\s]*)([^\s]*)	keep · replace with · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_1

PATTERNS, TRIED IN ORDER

([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with
(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	with · keep · replace with · keep · replace with · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with
(\s)([^\s]*)(\s)([^\s]*)	with · keep · replace with · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with
(\s)([^\s]*)	with · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with · keep · replace with · keep · replace with · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with · keep · replace with · keep
([^\s]*)(\s)([^\s]*)	keep · replace with · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

ES_NSS_PASO

DATA CLEANSING

Replaces each value found in `es-nss-paso.txt` (1,358 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_NSS_PASO_00`, `ES_NSS_PASO_01`, `ES_NSS_PASO_02`, `ES_NSS_PASO_03`, `ES_NSS_PASO_04`, `ES_NSS_PASO_05`, `ES_NSS_PASO_06`, `ES_NSS_PASO_07`, `ES_NSS_PASO_08`, `ES_NSS_PASO_09`, `ES_NSS_PASO_10`, `ES_NSS_PASO_11`, `ES_NSS_PASO_12`, `ES_NSS_PASO_13`

CONFIGURATION

lookupFile	<code>es-nss-paso.txt</code>
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_NSS_PASO_00

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `ES_NSS_CADENA_1`

PATTERNS, TRIED IN ORDER

<code>(.{0})(.{3})(.*)</code>	keep · <code>ES_NSS_PASO</code> · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_01

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `ES_NSS_CADENA_1`

PATTERNS, TRIED IN ORDER

<code>(.{1})(.{3})(.*)</code>	keep · <code>ES_NSS_PASO</code> · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_02

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `ES_NSS_CADENA_1`

PATTERNS, TRIED IN ORDER

<code>(.{2})(.{3})(.*)</code>	keep · <code>ES_NSS_PASO</code> · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_1

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · ES_NSS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · ES_NSS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · ES_NSS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · ES_NSS_PASO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PASO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PAS0_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PAS0_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PAS0_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PAS0_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_2

PATTERNS, TRIED IN ORDER

<code>(.{11})(.{3})(.*)</code>	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PAS0_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_3

PATTERNS, TRIED IN ORDER

<code>(.{12})(.{3})(.*)</code>	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PAS0_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_3

PATTERNS, TRIED IN ORDER

<code>(.{13})(.{3})(.*)</code>	keep · ES_NSS_PAS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_1

PATTERNS, TRIED IN ORDER

<code>(0)(.*)(\d{2})</code>	replace with 000 · keep · replace with ~
<code>(1)(.*)(\d{2})</code>	replace with 001 · keep · replace with ~
<code>(2)(.*)(\d{2})</code>	replace with 002 · keep · replace with ~
<code>(3)(.*)(\d{2})</code>	replace with 003 · keep · replace with ~
<code>(4)(.*)(\d{2})</code>	replace with 004 · keep · replace with ~
<code>(5)(.*)(\d{2})</code>	replace with 005 · keep · replace with ~
<code>(6)(.*)(\d{2})</code>	replace with 006 · keep · replace with ~
<code>(7)(.*)(\d{2})</code>	replace with 007 · keep · replace with ~
<code>(8)(.*)(\d{2})</code>	replace with 008 · keep · replace with ~
<code>(9)(.*)(\d{2})</code>	replace with 009 · keep · replace with ~
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_NSS_RESTAURAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_NSS_CADENA_3

PATTERNS, TRIED IN ORDER

(.*)(!)(.*)	keep · replace with 0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: ES_IP

CONFIGURATION

minValue	1
maxValue	254

ES_OCUPACION SECURE LOOKUP

Replaces the value with one of the 37 values in es-ocupaciones.txt , chosen by a keyed hash.

Used by: ES_OCUPACION_0_CODIGO

CONFIGURATION

lookupFile	es-ocupaciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_OCUPACION_0_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_OCUPACION .

Used by: ES_L2_OCUPACION

PATTERNS, TRIED IN ORDER

(\d{2,5})	ES_CM_DIGITOS
otherwise	ES_OCUPACION

CONFIGURATION

trimInput	yes
requireMask	no

ES_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_OPINION_POLITICA_LISTA .

Used by: ES_L3_OPINION_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_OPINION_POLITICA_CODIGO
otherwise	ES_OPINION_POLITICA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_OPINION_POLITICA_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in es-opiniones-politicas-codigos.txt , chosen by a keyed hash.

Used by: ES_OPINION_POLITICA

CONFIGURATION

lookupFile	es-opiniones-politicas-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in es-opiniones-politicas.txt , chosen by a keyed hash.

Used by: ES_OPINION_POLITICA

CONFIGURATION

lookupFile	es-opiniones-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_ORIENTACION_SEXUAL_LISTA .

Used by: ES_L3_ORIENTACION_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_ORIENTACION_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `es-orientaciones-sexuales.txt` , chosen by a keyed hash.

Used by: `ES_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	<code>es-orientaciones-sexuales.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_ORIGEN_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`ES_ORIGEN_ETNICO_LISTA` .

Used by: `ES_L3_ORIGEN_ETNICO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>ES_BANDERA</code>
<code>(\d{1,6})</code>	<code>ES_ORIGEN_ETNICO_CODIGO</code>
otherwise	<code>ES_ORIGEN_ETNICO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

ES_ORIGEN_ETNICO_CODIGO SECURE LOOKUP

Replaces the value with one of the 9 values in `es-origen-etnico-codigos.txt` , chosen by a keyed hash.

Used by: `ES_ORIGEN_ETNICO`

CONFIGURATION

lookupFile	<code>es-origen-etnico-codigos.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_ORIGEN_ETNICO_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `es-origen-etnico.txt` , chosen by a keyed hash.

Used by: `ES_ORIGEN_ETNICO`

CONFIGURATION

lookupFile	<code>es-origen-etnico.txt</code>
hashMethod	<code>SHA256</code>

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_APELLIDO .

Used by: ES_APELLIDOS , ES_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i) (de del la las los y i e da do dos das san santa sant von van di le)	keep
otherwise	ES_APELLIDO

CONFIGURATION

trimInput	yes
requireMask	no

ES_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: ES_NOMBRE .

Used by: ES_NOMBRES , ES_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i) (de del la las los y i e da do dos das san santa sant von van di le)	keep
otherwise	ES_NOMBRE

CONFIGURATION

trimInput	yes
requireMask	no

ES_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_PARTIDO_LISTA .

Used by: ES_L3_AFILIACION_PARTIDARIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_PARTIDO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 16 values in es-partidos.txt , chosen by a keyed hash.

Used by: ES_PARTIDO

CONFIGURATION

lookupFile	es-partidos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 1,000 and 3,000,000.

Used by: ES_FIN_PATRIMONIO

CONFIGURATION

minValue	1000
maxValue	3000000

ES_PRESTACION_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_PRESTACION_SOCIAL_LISTA .

Used by: ES_FIN_PRESTACION_SOCIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_PRESTACION_SOCIAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_PRESTACION_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in es-prestaciones-sociales.txt , chosen by a keyed hash.

Used by: ES_PRESTACION_SOCIAL

CONFIGURATION

lookupFile	es-prestaciones-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_PROCEDIMIENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_PROCEDIMIENTO_TEXTO .

Used by: ES_SALUD_PROCEDIMIENTO

PATTERNS, TRIED IN ORDER

([0-9A-HJ-NP-Z]{7})	ES_CM_DIGITOS_LETRAS
---------------------	----------------------

(\d{4,6})	ES_CM_DIGITOS
otherwise	ES_PROCEDIMIENTO_TEXTO

CONFIGURATION

trimInput	yes
requireMask	no

ES_PROCEDIMIENTO_JUDICIAL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .

Used by: ES_PENAL_PROCEDIMIENTO

PATTERNS, TRIED IN ORDER

(\d{5}\s?\d{2}\s?\d\s?\d{4}\s?) (\d{7})	keep · ES_CM_DIGITOS
([A-Za-z]{1,6}\.?\s*)(\d{1,6})(\s*/\s*)(\d{2,4})	keep · ES_CM_DIGITOS · keep · keep
(\d{1,6})(\s*/\s*)(\d{2,4})	ES_CM_DIGITOS · keep · keep
otherwise	ES_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

ES_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in es-procedimientos.txt , chosen by a keyed hash.

Used by: ES_PROCEDIMIENTO

CONFIGURATION

lookupFile	es-procedimientos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_RC_LETRA_TABLA DATA CLEANSING

Replaces each value found in es-rc-letra.txt (529 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_LETRA , ES_RC_RUSTICA_LETRA

CONFIGURATION

lookupFile	es-rc-letra.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_01 DATA CLEANSING

Replaces each value found in es-rc-peso-01.txt (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_17 , ES_RC_RUSTICA_PASO_10

CONFIGURATION

lookupFile	es-rc-peso-01.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_03 DATA CLEANSING

Replaces each value found in es-rc-peso-03.txt (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_15 , ES_RC_RUSTICA_PASO_08

CONFIGURATION

lookupFile	es-rc-peso-03.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_04 DATA CLEANSING

Replaces each value found in es-rc-peso-04.txt (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_04 , ES_RC_RUSTICA_PASO_04

CONFIGURATION

lookupFile	es-rc-peso-04.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_05 DATA CLEANSING

Replaces each value found in es-rc-peso-05.txt (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_03 , ES_RC_RUSTICA_PASO_03

CONFIGURATION

lookupFile	es-rc-peso-05.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_07 DATA CLEANSING

Replaces each value found in es-rc-peso-07.txt (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_16 , ES_RC_RUSTICA_PASO_09

CONFIGURATION

lookupFile	es-rc-peso-07.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_09 DATA CLEANSING

Replaces each value found in `es-rc-peso-09.txt` (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_RC_URBANA_PASO_06` , `ES_RC_RUSTICA_PASO_06`

CONFIGURATION

lookupFile	es-rc-peso-09.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_12 DATA CLEANSING

Replaces each value found in `es-rc-peso-12.txt` (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_RC_URBANA_PASO_02` , `ES_RC_RUSTICA_PASO_02`

CONFIGURATION

lookupFile	es-rc-peso-12.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_13 DATA CLEANSING

Replaces each value found in `es-rc-peso-13.txt` (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_RC_URBANA_PASO_00` , `ES_RC_RUSTICA_PASO_00`

CONFIGURATION

lookupFile	es-rc-peso-13.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_15 DATA CLEANSING

Replaces each value found in `es-rc-peso-15.txt` (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_RC_URBANA_PASO_01` , `ES_RC_RUSTICA_PASO_01`

CONFIGURATION

lookupFile	es-rc-peso-15.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_17 DATA CLEANSING

Replaces each value found in `es-rc-peso-17.txt` (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: `ES_RC_URBANA_PASO_05` , `ES_RC_RUSTICA_PASO_05`

CONFIGURATION

lookupFile	es-rc-peso-17.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_PESO_21 DATA CLEANSING

Replaces each value found in es-rc-peso-21.txt (230 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_14 , ES_RC_RUSTICA_PASO_07

CONFIGURATION

lookupFile	es-rc-peso-21.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_RUSTICA STRING ALGORITHM CHAIN

Applies ES_RC_RUSTICA_1 → ES_RC_RUSTICA_2 , in this order.

Used by: ES_REFERENCIA_CATASTRAL

CONFIGURATION

algorithmReferences[1]	ES_RC_RUSTICA_1
algorithmReferences[2]	ES_RC_RUSTICA_2

ES_RC_RUSTICA_1 STRING ALGORITHM CHAIN

Applies ES_RC_RUSTICA_PARCELA → ES_RC_RUSTICA_PREPARAR → ES_RC_RUSTICA_PASO_00 → ES_RC_RUSTICA_PASO_01 → ES_RC_RUSTICA_PASO_02 → ES_RC_RUSTICA_PASO_03 → ES_RC_RUSTICA_PASO_04 → ES_RC_RUSTICA_PASO_05 , in this order.

Used by: ES_RC_RUSTICA

CONFIGURATION

algorithmReferences[1]	ES_RC_RUSTICA_PARCELA
algorithmReferences[2]	ES_RC_RUSTICA_PREPARAR
algorithmReferences[3]	ES_RC_RUSTICA_PASO_00
algorithmReferences[4]	ES_RC_RUSTICA_PASO_01
algorithmReferences[5]	ES_RC_RUSTICA_PASO_02
algorithmReferences[6]	ES_RC_RUSTICA_PASO_03
algorithmReferences[7]	ES_RC_RUSTICA_PASO_04
algorithmReferences[8]	ES_RC_RUSTICA_PASO_05

ES_RC_RUSTICA_2 STRING ALGORITHM CHAIN

Applies ES_RC_RUSTICA_PASO_06 → ES_RC_RUSTICA_PASO_07 → ES_RC_RUSTICA_PASO_08 → ES_RC_RUSTICA_PASO_09 → ES_RC_RUSTICA_PASO_10 → ES_RC_RUSTICA_PASO_11 → ES_RC_RUSTICA_LETRA , in this order.

Used by: ES_RC_RUSTICA

CONFIGURATION

algorithmReferences[1]	ES_RC_RUSTICA_PASO_06
------------------------	-----------------------

algorithmReferences[2]	ES_RC_RUSTICA_PASO_07
algorithmReferences[3]	ES_RC_RUSTICA_PASO_08
algorithmReferences[4]	ES_RC_RUSTICA_PASO_09
algorithmReferences[5]	ES_RC_RUSTICA_PASO_10
algorithmReferences[6]	ES_RC_RUSTICA_PASO_11
algorithmReferences[7]	ES_RC_RUSTICA_LETRA

ES_RC_RUSTICA_LETRA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_2

PATTERNS, TRIED IN ORDER

(.{19})(.{3})	keep · ES_RC_LETRA_TABLA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PARCELA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(\d{5}[A-Z]\d{3})(\d{5})(\d{4}[A-Z]{2})	keep · ES_CM_DIGITOS · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · ES_RC_PESO_13 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · ES_RC_PESO_15 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · ES_RC_PESO_12 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · ES_RC_PESO_05 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · ES_RC_PESO_04 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{12})(.{3})(.*)	keep · ES_RC_PESO_17 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
ES_RC_RUSTICA_PASO_06 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_RC_RUSTICA_2	
PATTERNS, TRIED IN ORDER	
(.{13})(.{3})(.*)	keep · ES_RC_PESO_09 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_RC_RUSTICA_PASO_07 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_RC_RUSTICA_2	
PATTERNS, TRIED IN ORDER	
(.{14})(.{3})(.*)	keep · ES_RC_PESO_21 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_RC_RUSTICA_PASO_08 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_RC_RUSTICA_2	
PATTERNS, TRIED IN ORDER	
(.{15})(.{3})(.*)	keep · ES_RC_PESO_03 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_RC_RUSTICA_PASO_09 REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_RC_RUSTICA_2	
PATTERNS, TRIED IN ORDER	
(.{16})(.{3})(.*)	keep · ES_RC_PESO_07 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_2

PATTERNS, TRIED IN ORDER

(.{17})(.{3})(.*)	keep · ES_RC_PESO_01 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PASO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_2

PATTERNS, TRIED IN ORDER

(.{18})(.{3})(.*)	keep · ES_RC TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_RUSTICA_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_RUSTICA_1

PATTERNS, TRIED IN ORDER

(.{7})(0)(.*)	keep · replace with 000 · keep
(.{7})(1)(.*)	keep · replace with 001 · keep
(.{7})(2)(.*)	keep · replace with 002 · keep
(.{7})(3)(.*)	keep · replace with 003 · keep
(.{7})(4)(.*)	keep · replace with 004 · keep
(.{7})(5)(.*)	keep · replace with 005 · keep
(.{7})(6)(.*)	keep · replace with 006 · keep
(.{7})(7)(.*)	keep · replace with 007 · keep
(.{7})(8)(.*)	keep · replace with 008 · keep
(.{7})(9)(.*)	keep · replace with 009 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC TRASLADO DATA CLEANSING

Replaces each value found in es-rc-traslado.txt (828 pairs) by its counterpart; values not in the file stay as they are.

Used by: ES_RC_URBANA_PASO_07 , ES_RC_URBANA_PASO_08 , ES_RC_URBANA_PASO_09 , ES_RC_URBANA_PASO_10 , ES_RC_URBANA_PASO_11 , ES_RC_URBANA_PASO_12 , ES_RC_URBANA_PASO_13 , ES_RC_RUSTICA_PASO_11

CONFIGURATION

lookupFile	es-rc-traslado.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

ES_RC_URBANA STRING ALGORITHM CHAIN

Applies ES_RC_URBANA_1 → ES_RC_URBANA_2 → ES_RC_URBANA_3 , in this order.

Used by: ES_REFERENCIA_CATASTRAL

CONFIGURATION

algorithmReferences[1]	ES_RC_URBANA_1
algorithmReferences[2]	ES_RC_URBANA_2
algorithmReferences[3]	ES_RC_URBANA_3

ES_RC_URBANA_1 STRING ALGORITHM CHAIN

Applies ES_RC_URBANA_PARCELA → ES_RC_URBANA_PREPARAR → ES_RC_URBANA_PASO_00 → ES_RC_URBANA_PASO_01 → ES_RC_URBANA_PASO_02 → ES_RC_URBANA_PASO_03 → ES_RC_URBANA_PASO_04 → ES_RC_URBANA_PASO_05 , in this order.

Used by: ES_RC_URBANA

CONFIGURATION

algorithmReferences[1]	ES_RC_URBANA_PARCELA
algorithmReferences[2]	ES_RC_URBANA_PREPARAR
algorithmReferences[3]	ES_RC_URBANA_PASO_00
algorithmReferences[4]	ES_RC_URBANA_PASO_01
algorithmReferences[5]	ES_RC_URBANA_PASO_02
algorithmReferences[6]	ES_RC_URBANA_PASO_03
algorithmReferences[7]	ES_RC_URBANA_PASO_04
algorithmReferences[8]	ES_RC_URBANA_PASO_05

ES_RC_URBANA_2 STRING ALGORITHM CHAIN

Applies ES_RC_URBANA_PASO_06 → ES_RC_URBANA_PASO_07 → ES_RC_URBANA_PASO_08 → ES_RC_URBANA_PASO_09 → ES_RC_URBANA_PASO_10 → ES_RC_URBANA_PASO_11 → ES_RC_URBANA_PASO_12 → ES_RC_URBANA_PASO_13 , in this order.

Used by: ES_RC_URBANA

CONFIGURATION

algorithmReferences[1]	ES_RC_URBANA_PASO_06
algorithmReferences[2]	ES_RC_URBANA_PASO_07
algorithmReferences[3]	ES_RC_URBANA_PASO_08
algorithmReferences[4]	ES_RC_URBANA_PASO_09
algorithmReferences[5]	ES_RC_URBANA_PASO_10
algorithmReferences[6]	ES_RC_URBANA_PASO_11
algorithmReferences[7]	ES_RC_URBANA_PASO_12
algorithmReferences[8]	ES_RC_URBANA_PASO_13

ES_RC_URBANA_3 STRING ALGORITHM CHAIN

Applies ES_RC_URBANA_PASO_14 → ES_RC_URBANA_PASO_15 → ES_RC_URBANA_PASO_16 → ES_RC_URBANA_PASO_17 → ES_RC_URBANA_LETRA , in this order.

Used by: ES_RC_URBANA

CONFIGURATION

algorithmReferences[1]	ES_RC_URBANA_PASO_14
algorithmReferences[2]	ES_RC_URBANA_PASO_15
algorithmReferences[3]	ES_RC_URBANA_PASO_16
algorithmReferences[4]	ES_RC_URBANA_PASO_17
algorithmReferences[5]	ES_RC_URBANA_LETRA

ES_RC_URBANA_LETRA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_3

PATTERNS, TRIED IN ORDER

(.{18})(.{3})(.)	keep · ES_RC_LETRA_TABLA · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PARCELA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(\d{7})([A-Z0-9]{7}\d{4}[A-Z]{2})	ES_CM_DIGITOS · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(.{0})(.{3})(.*)	keep · ES_RC_PESO_13 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(.{1})(.{3})(.*)	keep · ES_RC_PESO_15 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · ES_RC_PESO_12 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · ES_RC_PESO_05 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · ES_RC_PESO_04 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_1

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · ES_RC_PESO_17 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · ES_RC_PESO_09 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · ES_RC TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · ES_RC TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · ES_RC TRASLADO · keep
------------------	------------------------------

otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER	
<code>(.{10})(.{3})(.*)</code>	keep · ES_RC TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER	
<code>(.{11})(.{3})(.*)</code>	keep · ES_RC TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER	
<code>(.{12})(.{3})(.*)</code>	keep · ES_RC TRASLADO · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_2

PATTERNS, TRIED IN ORDER	
<code>(.{13})(.{3})(.*)</code>	keep · ES_RC TRASLADO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_3

PATTERNS, TRIED IN ORDER

(.{14})(.{3})(.*)	keep · ES_RC_PESO_21 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_3

PATTERNS, TRIED IN ORDER

(.{15})(.{3})(.*)	keep · ES_RC_PESO_03 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_3

PATTERNS, TRIED IN ORDER

(.{16})(.{3})(.*)	keep · ES_RC_PESO_07 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_RC_URBANA_PASO_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_RC_URBANA_3

PATTERNS, TRIED IN ORDER

(.{17})(.{3})(.*)	keep · ES_RC_PESO_01 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
ES_RC_URBANA_PREPARAR REGEX DECOMPOSE	
Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.	
Used by: ES_RC_URBANA_1	
PATTERNS, TRIED IN ORDER	
(0)(.*)	replace with 000 · keep
(1)(.*)	replace with 001 · keep
(2)(.*)	replace with 002 · keep
(3)(.*)	replace with 003 · keep
(4)(.*)	replace with 004 · keep
(5)(.*)	replace with 005 · keep
(6)(.*)	replace with 006 · keep
(7)(.*)	replace with 007 · keep
(8)(.*)	replace with 008 · keep
(9)(.*)	replace with 009 · keep
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_REDACTAR REGEX DECOMPOSE	
Matches one pattern and gives each part of the value its own action; when none matches: keep.	
Used by: ES_L1_CREDENCIAL , ES_L1_IMAGEN , ES_L3_BIOMETRICO , ES_L3_GENETICO	
PATTERNS, TRIED IN ORDER	
(.+)	each character → X
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no
ES_REFERENCIA_CATASTRAL REGEX DECOMPOSE	
Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_ALFANUM .	
Used by: ES_L1_REFERENCIA_CATASTRAL	
PATTERNS, TRIED IN ORDER	
(\d{7}[A-Z0-9]{7}\d{4}[A-Z]{2})	ES_RC_URBANA
(\d{5}[A-Z]\d{12}[A-Z]{2})	ES_RC_RUSTICA
(\d{7})(\s?[A-Z0-9]{7}.*)	ES_CM_DIGITOS · keep
otherwise	ES_CM_ALFANUM
CONFIGURATION	
trimInput	yes
requireMask	no

ES_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: ES_RELIGION_LISTA .

Used by: ES_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in es-religiones.txt , chosen by a keyed hash.

Used by: ES_RELIGION

CONFIGURATION

lookupFile	es-religiones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SANCION_ADMINISTRATIVA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_SANCION_ADMINISTRATIVA_LISTA .

Used by: ES_PENAL_SANCION_ADMINISTRATIVA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_SANCION_ADMINISTRATIVA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_SANCION_ADMINISTRATIVA_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in es-sanciones-administrativas.txt , chosen by a keyed hash.

Used by: ES_SANCION_ADMINISTRATIVA

CONFIGURATION

lookupFile	es-sanciones-administrativas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

ES_SEX0 REGEX DECOMPOSE

Tries 8 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_L2_SEX0

PATTERNS, TRIED IN ORDER

(?i)(femenino masculino)	ES_SEX0_FEMENINO_MASCULINO
(?i)(mujer hombre)	ES_SEX0_MUJER_HOMBRE
(?i)(dona home)	ES_SEX0_DONA_HOME
(?i)(female male)	ES_SEX0_FEMALE_MALE
(?i)([hm])	ES_SEX0_H_M
(?i)(v)	ES_SEX0_V_M
(?i)(f)	ES_SEX0_F_M
([12])	ES_SEX0_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_SEX0_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-1-2.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEX0_DONA_HOME SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-dona-home.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-dona-home.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEX0_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-f-m.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-female-male.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-female-male.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-femenino-masculino.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-femenino-masculino.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-h-m.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-h-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-mujer-hombre.txt , chosen by a keyed hash.

Used by: ES_SEX0

CONFIGURATION

lookupFile	es-sexo-mujer-hombre.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SEXO_V_M SECURE LOOKUP

Replaces the value with one of the 2 values in es-sexo-v-m.txt , chosen by a keyed hash.

Used by: ES_SEXO

CONFIGURATION

lookupFile	es-sexo-v-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SITUACION_ADMINISTRATIVA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

ES_SITUACION_ADMINISTRATIVA_LISTA .

Used by: ES_L2_SITUACION_ADMINISTRATIVA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	ES_BANDERA
(\d{1,6})	ES_CM_ALFANUM
otherwise	ES_SITUACION_ADMINISTRATIVA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

ES_SITUACION_ADMINISTRATIVA_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in es-situacion-administrativa.txt , chosen by a keyed hash.

Used by: ES_SITUACION_ADMINISTRATIVA

CONFIGURATION

lookupFile	es-situacion-administrativa.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in es-sin-informacion.txt , chosen by a keyed hash.

Used by: ES_CATEGORIA_SUPRIMIDA

CONFIGURATION

lookupFile	es-sin-informacion.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

ES_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: ES_L1_TARJETA

PATTERNS, TRIED IN ORDER

(\d[\d\s-]{11,22}\d)	ES_TARJETA_LUHN
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: ES_TARJETA

CONFIGURATION

minMaskedPositions	6
preserve	0

ES_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: ES_CM_DIGITOS .

Used by: ES_L1_TELEFONO

PATTERNS, TRIED IN ORDER

((?:\+ 00)34[\s-]?)([6789])([\d\s-]{8,13})	keep · keep · ES_CM_DIGITOS
(\((?:\+ 00)34\)?[\s-]?)([6789])([\d\s-]{8,13})	keep · keep · ES_CM_DIGITOS
([6789])([\d\s-]{8,13})	keep · ES_CM_DIGITOS
otherwise	ES_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

ES_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 10 patterns with [DATO] , and the 2,494 terms of es-texto-nombres.txt with [NOMBRE] .

Used by: ES_L1_TEXTO_LIBRE , ES_SALUD_TEXTO_CLINICO

PATTERNS, TRIED IN ORDER

(?![\dA-Za-z])\d{8}-?[A-Za-z](?![A-Za-z])

(?<![A-Za-z])[XYZxyz]-?\d{7}-?[A-Za-z](?![A-Za-z])

\d{1,2}\.\d{3}\.\d{3}-?[A-Za-z]

[\w.\+-]+@[\\w-]+(\. [\\w-]+)+

(?<![\d\-])((\+|00)34)?[6789]\d{8}(?![\d\-])

(?<!\d)\d{13,19}(?!\\d)

ES\d{22}

(?<!\d)\d{20}(?!\\d)

(?<!\d)\d{2}/?\d{8}/?\d{2}(?!\\d)

(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\\d)

CONFIGURATION

regExRedactValue	[DATO]
lookupFile	es-texto-nombres.txt
lookupFileRedactValue	[NOMBRE]
isDenyList	yes

ES_TRIBUTARIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: ES_FIN_TRIBUTARIO

PATTERNS, TRIED IN ORDER

(-?)(\d+)([.,]\d{1,2})	keep · ES_IMPORTE_TRIBUTARIO · keep
(-?)(\d+)	keep · ES_IMPORTE_TRIBUTARIO
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

ES_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 100 and 600,000.

Used by: ES_FIN_DEUDA

CONFIGURATION

minValue	100
maxValue	600000

ES_VALOR_PENSION NUMERIC MAPPING

Maps the number to another between 500 and 3,400.

Used by: ES_FIN_PENSION

CONFIGURATION

minValue	500
maxValue	3400

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
es- antecedentes.txt	8	ES_ANTECEDENTES_LISTA	Sin antecedentes penales · Con antecedentes penales · Antecedentes cancelados · Causa pendiente
es-apellidos.txt	500	ES_APELLIDO	Abad · Acevedo · Acosta · Aguado
es-aptitud- laboral.txt	4	ES_APTITUD_LABORAL_LISTA	Apto · Apto con restricciones · No apto · Pendiente de calificación
es-bandera-0- 1.txt	2	ES_BANDERA_0_1	0 · 1
es-bandera-s- n.txt	2	ES_BANDERA_S_N	S · N
es-bandera-si- no.txt	2	ES_BANDERA_SI_NO	Sí · No
es-bandera-true- false.txt	2	ES_BANDERA_TRUE_FALSE	true · false
es-bandera-y- n.txt	2	ES_BANDERA_Y_N	Y · N
es-bandera-yes- no.txt	2	ES_BANDERA_YES_NO	Yes · No
es-ccc- control.txt	110	ES_CCC_CONTROL_TABLA	a00 0 · a01 1 · a02 9 · a03 8
es-ccc-paso.txt	132	ES_CCC_PASO	000 000 · 100 011 · 200 022 · 300 033
es-centros- educativos.txt	14	ES_CENTRO_EDUCATIVO	CEIP Miguel de Cervantes · CEIP Antonio Machado · IES Ramiro de Maeztu · IES Luis Vives
es-certificado- delitos- sexuales.txt	5	ES_DELITOS_SEXUALES_LISTA	Certificado negativo aportado · Certificado pendiente · Certificado caducado · No aportado
es-cie10- decimal.txt	33	ES_CIE10_DECIMAL	E11.9 · E78.5 · J45.909 · J06.9
es-cie10.txt	37	ES_CIE10	I10 · E11 · E78 · J45
es-cobertura- salud.txt	9	ES_COBERTURA	Seguridad Social (titular) · Seguridad Social (beneficiario) · MUFACE · ISFAS
es-codigos- municipio- generalizados.txt	15,400	ES_CODIGO_MUNICIPIO	01001 01059 · 010014 010590 · 01002 01059 · 010029 010590
es-codigos- postales- generalizados.txt	8,638	ES_CODIGO_POSTAL	01110 01001 · 01117 01001 · 01118 01001 · 01120 01001
es-cups- letras.txt	529	ES_CUPS_LETRAS_TABLA	000~ TT · 001~ TR · 002~ TW · 003~ TA

FILE	LINES	USED BY	FIRST LINES
es-cups-paso.txt	6,877	ES_CUPS_PASO	0000 0000 · 0001 1001 · 0002 2002 · 0003 3003
es-dependencia-codigos.txt	3	ES_DEPENDENCIA_CODIGO	1 · 2 · 3
es-dependencia.txt	5	ES_DEPENDENCIA_LISTA	Grado I - Dependencia moderada · Grado II - Dependencia severa · Grado III - Gran dependencia · Sin grado reconocido
es-detectar-apellidos.txt	617	ES_L1_APELLIDO - List ES_L1_NOMBRE_COMPLETO - List	Abad · Acevedo · Acosta · Aguado
es-detectar-aptitud-laboral.txt	10	ES_SALUD_LABORAL - List	apto · no apto · apto con restricciones · pendiente
es-detectar-certificado-delitos-sexuales.txt	8	ES_PENAL_DELITOS_SEXUALES - List	certificado negativo · negativo · positivo · aportado
es-detectar-cobertura.txt	23	ES_SALUD_COBERTURA - List	Seguridad Social (titular) · Seguridad Social (beneficiario) · MUFACE · ISFAS
es-detectar-codigos-banderas.txt	14	ES_L3_ORIGEN_ETNICO - List ES_SALUD_LABORAL - List ES_FIN_PRESTACION_SOCIAL - List	s · n · sí · si
es-detectar-dependencia.txt	13	ES_SALUD_DEPENDENCIA - List	Grado I - Dependencia moderada · Grado II - Dependencia severa · Grado III - Gran dependencia · Sin grado reconocido
es-detectar-discapacidades.txt	30	ES_SALUD_DISCAPACIDAD - List	Física · Fisica · Orgánica · Organica
es-detectar-estado-civil.txt	17	ES_L2_ESTADO_CIVIL - List	Soltero/a · Casado/a · Pareja de hecho · Separado/a
es-detectar-grupos-sanguineos.txt	20	ES_SALUD_GRUPO_SANGUINEO - List	A+ · A- · B+ · B-
es-detectar-identidades-genero.txt	17	ES_L3_IDENTIDAD_GENERO - List	Mujer cis · Hombre cis · Mujer trans · Hombre trans
es-detectar-medicamentos.txt	56	ES_SALUD_MEDICAMENTO - List	Paracetamol · Ibuprofeno · Metamizol · Omeprazol
es-detectar-municipios.txt	10,872	ES_L2_MUNICIPIO - List	Alegría-Dulantzi · Alegria-Dulantzi · Amurrio · Aramaio
es-detectar-nacionalidades.txt	75	ES_L2_NACIONALIDAD - List	Española · Espanola · Marroquí · Marroqui
es-detectar-nivel-educativo.txt	32	ES_L2_NIVEL_EDUCATIVO - List	Sin estudios · Educación primaria incompleta · Educacion primaria incompleta · Educación primaria
es-detectar-nombres.txt	698	ES_L1_NOMBRE - List ES_L1_NOMBRE_COMPLETO - List	Aarón · Aaron · Abdelaziz · Abdelkader

FILE	LINES	USED BY	FIRST LINES
es-detectar-opiniones-politicas.txt	23	ES_L3_OPINION_POLITICA – List	Izquierda · Centroizquierda · Centro · Centroderecha
es-detectar-orientaciones-sexuales.txt	14	ES_L3_ORIENTACION_SEXUAL – List	Heterosexual · Gay · Lesbiana · Bisexual
es-detectar-origen-etnico.txt	32	ES_L3_ORIGEN_ETNICO – List	Gitana · Blanca o europea · Magrebí o árabe · Magrebi o arabe
es-detectar-partidos.txt	34	ES_L3_AFILIACION_PARTIDARIA – List	PP · PSOE · Vox · Sumar
es-detectar-prestaciones-sociales.txt	33	ES_FIN_PRESTACION_SOCIAL – List	Ingreso Mínimo Vital · Ingreso Mínimo Vital · Prestación por desempleo · Prestacion por desempleo
es-detectar-religiones.txt	45	ES_L3_RELIGION – List	Católica · Catolica · Evangélica o protestante · Evangelica o protestante
es-detectar-sexo.txt	14	ES_L2_SEX0 – List	h · m · v · f
es-detectar-sindicatos.txt	20	ES_L3_AFILIACION_SINDICAL – List	CCOO · Comisiones Obreras · UGT · Unión General de Trabajadores
es-detectar-situacion-administrativa.txt	33	ES_L2_SITUACION_ADMINISTRATIVA – List	Residencia temporal · Residencia de larga duración · Residencia de larga duracion · Residencia de larga duración UE
es-diagnosticos.txt	30	ES_DIAGNOSTICO_TEXTO	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
es-direcciones.txt	4,000	ES_DIRECCION	C/ de la Ermita, 89, ático · Calle Blasco Ibáñez, 58, entresuelo · Calle del Molino, 7, bajo B · Camino Clara Campoamor, 51, 2º
es-discapacidades.txt	8	ES_DISCAPACIDAD_LISTA	Física · Orgánica · Visual · Auditiva
es-dni-letra.txt	46	ES_DNI_LETRA_TABLA	00~ T · 00^ t · 01~ R · 01^ r
es-dni-paso.txt	575	ES_DNI_PASO	000 000 · 001 101 · 002 202 · 003 303
es-empleadores.txt	24	ES_EMPLEADOR	Distribuciones Levante S.L. · Construcciones del Norte S.A. · Transportes La Meseta S.L. · Supermercados El Ahorro S.A.
es-estado-civil-codigos.txt	6	ES_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
es-estado-civil.txt	6	ES_ESTADO_CIVIL_LISTA	Soltero/a · Casado/a · Pareja de hecho · Separado/a
es-estados-credito.txt	11	ES_ESTADO_CREDITO	Sin incidencias · Incluido en fichero de morosos · Deuda saldada · Deuda reclamada judicialmente
es-grupos-sanguineos.txt	8	ES_GRUPO_SANGUINEO	A+ · A- · B+ · B-
es-iban-ajuste.txt	10,000	ES_IBAN_AJUSTE	0000 97 · 0001 35 · 0002 70 · 0003 08
es-iban-control.txt	110	ES_IBAN_CONTROL_TABLA	a00 000 · a01 011 · a02 099 · a03 088

FILE	LINES	USED BY	FIRST LINES
es-iban-traslado.txt	1,100	ES_IBAN_TRASLADO	000 000 · 001 010 · 002 020 · 003 030
es-identidades-genero.txt	7	ES_IDENTIDAD_GENERO_LISTA	Mujer cis · Hombre cis · Mujer trans · Hombre trans
es-medicamentos.txt	23	ES_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Metamizol · Omeprazol
es-municipios-generalizados.txt	68,972	ES_MUNICIPIO	Alegría-Dulantzi Vitoria-Gasteiz · Alegría-Dulantzi (Álava) Vitoria-Gasteiz (Álava) · Alegría-Dulantzi, Álava Vitoria-Gasteiz, Álava · Amurrio Vitoria-Gasteiz
es-nacionalidades.txt	27	ES_NACIONALIDAD	Española · Marroquí · Rumana · Colombiana
es-nivel-educativo-codigos.txt	10	ES_NIVEL_EDUCATIVO_CODIGO	1 · 2 · 3 · 4
es-nivel-educativo.txt	10	ES_NIVEL_EDUCATIVO_LISTA	Sin estudios · Educación primaria incompleta · Educación primaria · Educación secundaria obligatoria (ESO)
es-nombres.txt	600	ES_NOMBRE	Aarón · Abdelaziz · Abdelkader · Abdellah
es-nss-control.txt	97	ES_NSS_CONTROL_TABLA	00~ 00 · 01~ 01 · 02~ 02 · 03~ 03
es-nss-paso.txt	1,358	ES_NSS_PASO	000 000 · 001 101 · 002 202 · 003 303
es-ocupaciones.txt	37	ES_OCUPACION	Empleado administrativo · Dependiente de comercio · Cajero · Conductor de camión
es-opiniones-politicas-codigos.txt	10	ES_OPINION_POLITICA_CODIGO	1 · 2 · 3 · 4
es-opiniones-politicas.txt	7	ES_OPINION_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
es-orientaciones-sexuales.txt	8	ES_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
es-origen-etnico-codigos.txt	9	ES_ORIGEN_ETNICO_CODIGO	1 · 2 · 3 · 4
es-origen-etnico.txt	9	ES_ORIGEN_ETNICO_LISTA	Gitana · Blanca o europea · Magrebí o árabe · Africana subsahariana
es-partidos.txt	16	ES_PARTIDO_LISTA	PP · PSOE · Vox · Sumar
es-prestaciones-sociales.txt	12	ES_PRESTACION_SOCIAL_LISTA	Ingreso Mínimo Vital · Prestación por desempleo · Subsidio por desempleo · Renta mínima autonómica
es-procedimientos.txt	10	ES_PROCEDIMIENTO_TEXTO	Consulta de medicina de familia · Consulta de urgencias · Hemograma completo · Glucemia basal
es-rc-letra.txt	529	ES_RC_LETRA_TABLA	00M M · 00Q M · 00W M · 00E M
es-rc-peso-01.txt	230	ES_RC_PESO_01	000 000 · 001 101 · 002 202 · 003 303
es-rc-peso-03.txt	230	ES_RC_PESO_03	000 000 · 001 103 · 002 206 · 003 309

FILE	LINES	USED BY	FIRST LINES
es-rc-peso-04.txt	230	ES_RC_PESO_04	000 000 · 001 104 · 002 208 · 003 312
es-rc-peso-05.txt	230	ES_RC_PESO_05	000 000 · 001 105 · 002 210 · 003 315
es-rc-peso-07.txt	230	ES_RC_PESO_07	000 000 · 001 107 · 002 214 · 003 321
es-rc-peso-09.txt	230	ES_RC_PESO_09	000 000 · 001 109 · 002 218 · 003 304
es-rc-peso-12.txt	230	ES_RC_PESO_12	000 000 · 001 112 · 002 201 · 003 313
es-rc-peso-13.txt	230	ES_RC_PESO_13	000 000 · 001 113 · 002 203 · 003 316
es-rc-peso-15.txt	230	ES_RC_PESO_15	000 000 · 001 115 · 002 207 · 003 322
es-rc-peso-17.txt	230	ES_RC_PESO_17	000 000 · 001 117 · 002 211 · 003 305
es-rc-peso-21.txt	230	ES_RC_PESO_21	000 000 · 001 121 · 002 219 · 003 317
es-rc-traslado.txt	828	ES_RC TRASLADO	000 000 · 001 100 · 002 200 · 003 300
es-religiones.txt	10	ES_RELIGION_LISTA	Católica · Evangélica o protestante · Musulmana · Testigo de Jehová
es-sanciones-administrativas.txt	8	ES_SANCION_ADMINISTRATIVA_LISTA	Sin sanciones · Sanción leve · Sanción grave · Sanción muy grave
es-sexo-1-2.txt	2	ES_SEXO_1_2	1 · 2
es-sexo-dona-home.txt	2	ES_SEXO_DONA_HOME	Dona · Home
es-sexo-f-m.txt	2	ES_SEXO_F_M	F · M
es-sexo-female-male.txt	2	ES_SEXO_FEMALE_MALE	Female · Male
es-sexo-femenino-masculino.txt	2	ES_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
es-sexo-h-m.txt	2	ES_SEXO_H_M	H · M
es-sexo-mujer-hombre.txt	2	ES_SEXO_MUJER_HOMBRE	Mujer · Hombre
es-sexo-v-m.txt	2	ES_SEXO_V_M	V · M
es-sin-informacion.txt	1	ES_SUPRIMIR	Sin información
es-situacion-administrativa.txt	13	ES_SITUACION_ADMINISTRATIVA_LISTA	Residencia temporal · Residencia de larga duración · Residencia de larga duración UE · Certificado de registro de ciudadano de la UE
es-texto-nombres.txt	2,494	ES_TEXTO_LIBRE	Aarón · AARÓN · Aaron · AARON

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 empresa entidad sociedad proveedor pagador emisor retenedor

E2 producto prod item articulo empresa emp razon social comercial fiscal_empresa archivo fichero calle via avenida camino carretera barrio municipio localidad poblacion provincia comunidad pais banco entidad sucursal oficina agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo centro colegio instituto universidad curso asignatura documento doc unidad clinica hospital ambulatorio seguro area departamento cargo sistema app aplicacion grupo lista informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa prestacion partido sindicato religion lengua idioma lugar sede local tienda almacen proveedor convenio contrato poliza aseguradora organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura pago forma zona linea actividad sector finca edificio file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante investigado testigo medico docente socio heredero donante tutor pensionista jubilado interesado customer patient employee member holder mother father spouse contact person student driver owner completo apellidos? usuario corto largo

E3 producto prod item articulo empresa emp razon social comercial fiscal_empresa archivo fichero calle via avenida camino carretera barrio municipio localidad poblacion provincia comunidad pais banco entidad sucursal oficina agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo centro colegio instituto universidad curso asignatura documento doc unidad clinica hospital ambulatorio seguro area departamento cargo sistema app aplicacion grupo lista informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa prestacion partido sindicato religion lengua idioma lugar sede local tienda almacen proveedor convenio contrato poliza aseguradora organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura pago forma zona linea actividad sector finca edificio file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante investigado testigo medico docente socio heredero donante tutor pensionista jubilado interesado customer patient employee member holder mother father spouse contact person student driver owner complet cognoms?

E4	producto prod item articulo empresa emp razon social comercial fiscal_?empresa archivo fichero calle via avenida camino carretera barrio municipio localidad poblacion provincia comunidad pais banco entidad sucursal oficina agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo centro colegio instituto universidad curso asignatura documento doc unidad clinica hospital ambulatorio seguro area departamento cargo sistema app aplicacion grupo lista informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa prestacion partido sindicato religion lengua idioma lugar sede local tienda almacen proveedor convenio contrato poliza aseguradora organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura pago forma zona linea actividad sector finca edificio file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador funcionario alumno estudiante deudor avalista fiador garante solicitante propietario arrendatario inquilino conductor tomador responsable representante apoderado persona ciudadano contribuyente madre padre conyuge contacto referencia victima denunciante investigado testigo medico docente socio heredero donante tutor pensionista jubilado interesado customer patient employee member holder mother father spouse contact person student driver owner full complete last first
E5	ip mac email e_?mail correo electr[oó]nica web url tipo id general provincial territorial
E6	ip mac email e_?mail web url type id
E7	id cd cod codigo tipo fecha estado num nro
E8	id tipo codigo fecha estado cola log

APPENDIX D

Profile set and classifiers

The profile set `ES - LOPDGDD - v1` runs these 147 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, categorías especiales de datos (art. 9 RGPD y art. 9 LOPDGDD), datos de salud, datos económicos y tributarios y datos penales y de infracciones administrativas (art. 10 RGPD, arts. 10 y 27 LOPDGDD), conforme al Reglamento (UE) 2016/679 y a la Ley Orgánica 3/2018 de Protección de Datos Personales y garantía de los derechos digitales.

CLASSIFIER	KIND	DOMAIN
ES_L1_DNI - Path	COLUMN NAME	ES_L1_DNI
ES_L1_DNI - Type	DATA TYPE	ES_L1_DNI
ES_L1_DNI - Regex	VALUE FORMAT	ES_L1_DNI
ES_L1_NIE - Path	COLUMN NAME	ES_L1_NIE
ES_L1_NIE - Regex	VALUE FORMAT	ES_L1_NIE
ES_L1_PASAPORTE - Path	COLUMN NAME	ES_L1_PASAPORTE
ES_L1_PASAPORTE - Regex	VALUE FORMAT	ES_L1_PASAPORTE
ES_L1_SOPORTE_DOCUMENTO - Path	COLUMN NAME	ES_L1_SOPORTE_DOCUMENTO
ES_L1_SOPORTE_DOCUMENTO - Regex	VALUE FORMAT	ES_L1_SOPORTE_DOCUMENTO
ES_L1_NSS - Path	COLUMN NAME	ES_L1_NSS
ES_L1_NSS - Type	DATA TYPE	ES_L1_NSS
ES_L1_NSS - Regex	VALUE FORMAT	ES_L1_NSS
ES_L1_CODIGO_ESTUDIANTE - Path	COLUMN NAME	ES_L1_CODIGO_ESTUDIANTE
ES_L1_COLEGIADO - Path	COLUMN NAME	ES_L1_COLEGIADO
ES_L1_NOMBRE - Path	COLUMN NAME	ES_L1_NOMBRE
ES_L1_NOMBRE - List	KNOWN VALUES	ES_L1_NOMBRE
ES_L1_APELLIDO - Path	COLUMN NAME	ES_L1_APELLIDO
ES_L1_APELLIDO - List	KNOWN VALUES	ES_L1_APELLIDO
ES_L1_NOMBRE_COMPLETO - Path	COLUMN NAME	ES_L1_NOMBRE_COMPLETO
ES_L1_NOMBRE_COMPLETO - List	KNOWN VALUES	ES_L1_NOMBRE_COMPLETO
ES_L1_EMAIL - Path	COLUMN NAME	ES_L1_EMAIL
ES_L1_EMAIL - Type	DATA TYPE	ES_L1_EMAIL
ES_L1_EMAIL - Regex	VALUE FORMAT	ES_L1_EMAIL
ES_L1_TELEFONO - Path	COLUMN NAME	ES_L1_TELEFONO
ES_L1_TELEFONO - Regex	VALUE FORMAT	ES_L1_TELEFONO
ES_L1_DIRECCION - Path	COLUMN NAME	ES_L1_DIRECCION
ES_L1_DIRECCION - Type	DATA TYPE	ES_L1_DIRECCION
ES_L1_DIRECCION - Regex	VALUE FORMAT	ES_L1_DIRECCION
ES_L1_DIRECCION_COMPLEMENTO - Path	COLUMN NAME	ES_L1_DIRECCION_COMPLEMENTO

CLASSIFIER	KIND	DOMAIN
ES_L1_CUENTA_BANCARIA – Path	COLUMN NAME	ES_L1_CUENTA_BANCARIA
ES_L1_CUENTA_BANCARIA – Regex	VALUE FORMAT	ES_L1_CUENTA_BANCARIA
ES_L1_TARJETA – Path	COLUMN NAME	ES_L1_TARJETA
ES_L1_TARJETA – Regex	VALUE FORMAT	ES_L1_TARJETA
ES_L1_BILLETERA – Path	COLUMN NAME	ES_L1_BILLETERA
ES_L1_BILLETERA – Regex	VALUE FORMAT	ES_L1_BILLETERA
ES_L1_IP – Path	COLUMN NAME	ES_L1_IP
ES_L1_IP – Regex	VALUE FORMAT	ES_L1_IP
ES_L1_DISPOSITIVO – Path	COLUMN NAME	ES_L1_DISPOSITIVO
ES_L1_DISPOSITIVO – Regex	VALUE FORMAT	ES_L1_DISPOSITIVO
ES_L1_COOKIE – Path	COLUMN NAME	ES_L1_COOKIE
ES_L1_MATRICULA – Path	COLUMN NAME	ES_L1_MATRICULA
ES_L1_MATRICULA – Regex	VALUE FORMAT	ES_L1_MATRICULA
ES_L1_VEHICULO – Path	COLUMN NAME	ES_L1_VEHICULO
ES_L1_VEHICULO – Regex	VALUE FORMAT	ES_L1_VEHICULO
ES_L1_REFERENCIA_CATASTRAL – Path	COLUMN NAME	ES_L1_REFERENCIA_CATASTRAL
ES_L1_REFERENCIA_CATASTRAL – Regex	VALUE FORMAT	ES_L1_REFERENCIA_CATASTRAL
ES_L1_CUPS – Path	COLUMN NAME	ES_L1_CUPS
ES_L1_CUPS – Regex	VALUE FORMAT	ES_L1_CUPS
ES_L1_CONTRATO – Path	COLUMN NAME	ES_L1_CONTRATO
ES_L1_USUARIO – Path	COLUMN NAME	ES_L1_USUARIO
ES_L1_CREDENCIAL – Path	COLUMN NAME	ES_L1_CREDENCIAL
ES_L1_IMAGEN – Path	COLUMN NAME	ES_L1_IMAGEN
ES_L1_GEOLOCALIZACION – Path	COLUMN NAME	ES_L1_GEOLOCALIZACION
ES_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	ES_L1_GEOLOCALIZACION
ES_L1_TEXTO_LIBRE – Path	COLUMN NAME	ES_L1_TEXTO_LIBRE
ES_L1_TEXTO_LIBRE – Type	DATA TYPE	ES_L1_TEXTO_LIBRE
ES_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	ES_L1_TEXTO_LIBRE
ES_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	ES_L2_FECHA_NACIMIENTO
ES_L2_FECHA_NACIMIENTO – Type	DATA TYPE	ES_L2_FECHA_NACIMIENTO
ES_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	ES_L2_ANIO_NACIMIENTO
ES_L2_ANIO_NACIMIENTO – Type	DATA TYPE	ES_L2_ANIO_NACIMIENTO
ES_L2_EDAD – Path	COLUMN NAME	ES_L2_EDAD
ES_L2_EDAD – Type	DATA TYPE	ES_L2_EDAD
ES_L2_FECHA_EVENTO – Path	COLUMN NAME	ES_L2_FECHA_EVENTO
ES_L2_FECHA_EVENTO – Type	DATA TYPE	ES_L2_FECHA_EVENTO
ES_L2_SEX0 – Path	COLUMN NAME	ES_L2_SEX0

CLASSIFIER	KIND	DOMAIN
ES_L2_SEX0 - List	KNOWN VALUES	ES_L2_SEX0
ES_L2_MUNICIPIO - Path	COLUMN NAME	ES_L2_MUNICIPIO
ES_L2_MUNICIPIO - List	KNOWN VALUES	ES_L2_MUNICIPIO
ES_L2_CODIGO_MUNICIPIO - Path	COLUMN NAME	ES_L2_CODIGO_MUNICIPIO
ES_L2_CODIGO_MUNICIPIO - Regex	VALUE FORMAT	ES_L2_CODIGO_MUNICIPIO
ES_L2_CODIGO_POSTAL - Path	COLUMN NAME	ES_L2_CODIGO_POSTAL
ES_L2_CODIGO_POSTAL - Regex	VALUE FORMAT	ES_L2_CODIGO_POSTAL
ES_L2_NACIONALIDAD - Path	COLUMN NAME	ES_L2_NACIONALIDAD
ES_L2_NACIONALIDAD - List	KNOWN VALUES	ES_L2_NACIONALIDAD
ES_L2_SITUACION_ADMINISTRATIVA - Path	COLUMN NAME	ES_L2_SITUACION_ADMINISTRATIVA
ES_L2_SITUACION_ADMINISTRATIVA - List	KNOWN VALUES	ES_L2_SITUACION_ADMINISTRATIVA
ES_L2_ESTADO_CIVIL - Path	COLUMN NAME	ES_L2_ESTADO_CIVIL
ES_L2_ESTADO_CIVIL - List	KNOWN VALUES	ES_L2_ESTADO_CIVIL
ES_L2_OCUPACION - Path	COLUMN NAME	ES_L2_OCUPACION
ES_L2_EMPLEADOR - Path	COLUMN NAME	ES_L2_EMPLEADOR
ES_L2_NIVEL_EDUCATIVO - Path	COLUMN NAME	ES_L2_NIVEL_EDUCATIVO
ES_L2_NIVEL_EDUCATIVO - List	KNOWN VALUES	ES_L2_NIVEL_EDUCATIVO
ES_L2_CENTRO_EDUCATIVO - Path	COLUMN NAME	ES_L2_CENTRO_EDUCATIVO
ES_L2_PERSONAS_A_CARGO - Path	COLUMN NAME	ES_L2_PERSONAS_A_CARGO
ES_L2_PERSONAS_A_CARGO - Type	DATA TYPE	ES_L2_PERSONAS_A_CARGO
ES_L3_ORIGEN_ETNICO - Path	COLUMN NAME	ES_L3_ORIGEN_ETNICO
ES_L3_ORIGEN_ETNICO - List	KNOWN VALUES	ES_L3_ORIGEN_ETNICO
ES_L3_RELIGION - Path	COLUMN NAME	ES_L3_RELIGION
ES_L3_RELIGION - List	KNOWN VALUES	ES_L3_RELIGION
ES_L3_CONVICCION_FILOSOFICA - Path	COLUMN NAME	ES_L3_CONVICCION_FILOSOFICA
ES_L3_OPINION_POLITICA - Path	COLUMN NAME	ES_L3_OPINION_POLITICA
ES_L3_OPINION_POLITICA - List	KNOWN VALUES	ES_L3_OPINION_POLITICA
ES_L3_AFILIACION_PARTIDARIA - Path	COLUMN NAME	ES_L3_AFILIACION_PARTIDARIA
ES_L3_AFILIACION_PARTIDARIA - List	KNOWN VALUES	ES_L3_AFILIACION_PARTIDARIA
ES_L3_AFILIACION_SINDICAL - Path	COLUMN NAME	ES_L3_AFILIACION_SINDICAL
ES_L3_AFILIACION_SINDICAL - List	KNOWN VALUES	ES_L3_AFILIACION_SINDICAL
ES_L3_BIOMETRICO - Path	COLUMN NAME	ES_L3_BIOMETRICO
ES_L3_BIOMETRICO - Type	DATA TYPE	ES_L3_BIOMETRICO
ES_L3_GENETICO - Path	COLUMN NAME	ES_L3_GENETICO
ES_L3_ORIENTACION_SEXUAL - Path	COLUMN NAME	ES_L3_ORIENTACION_SEXUAL
ES_L3_ORIENTACION_SEXUAL - List	KNOWN VALUES	ES_L3_ORIENTACION_SEXUAL
ES_L3_VIDA_SEXUAL - Path	COLUMN NAME	ES_L3_VIDA_SEXUAL

CLASSIFIER	KIND	DOMAIN
ES_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	ES_L3_IDENTIDAD_GENERO
ES_L3_IDENTIDAD_GENERO – List	KNOWN VALUES	ES_L3_IDENTIDAD_GENERO
ES_L3_VICTIMA – Path	COLUMN NAME	ES_L3_VICTIMA
ES_SALUD_IDENTIFICADOR – Path	COLUMN NAME	ES_SALUD_IDENTIFICADOR
ES_SALUD_IDENTIFICADOR – Regex	VALUE FORMAT	ES_SALUD_IDENTIFICADOR
ES_SALUD_COBERTURA – Path	COLUMN NAME	ES_SALUD_COBERTURA
ES_SALUD_COBERTURA – List	KNOWN VALUES	ES_SALUD_COBERTURA
ES_SALUD_DIAGNOSTICO – Path	COLUMN NAME	ES_SALUD_DIAGNOSTICO
ES_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	ES_SALUD_DIAGNOSTICO
ES_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	ES_SALUD_PROCEDIMIENTO
ES_SALUD_MEDICAMENTO – Path	COLUMN NAME	ES_SALUD_MEDICAMENTO
ES_SALUD_MEDICAMENTO – List	KNOWN VALUES	ES_SALUD_MEDICAMENTO
ES_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	ES_SALUD_TEXTO_CLINICO
ES_SALUD_TEXTO_CLINICO – Type	DATA TYPE	ES_SALUD_TEXTO_CLINICO
ES_SALUD_RESULTADO_PRUEBA – Path	COLUMN NAME	ES_SALUD_RESULTADO_PRUEBA
ES_SALUD_VIH – Path	COLUMN NAME	ES_SALUD_VIH
ES_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	ES_SALUD_GRUPO_SANGUINEO
ES_SALUD_GRUPO_SANGUINEO – List	KNOWN VALUES	ES_SALUD_GRUPO_SANGUINEO
ES_SALUD_DISCAPACIDAD – Path	COLUMN NAME	ES_SALUD_DISCAPACIDAD
ES_SALUD_DISCAPACIDAD – List	KNOWN VALUES	ES_SALUD_DISCAPACIDAD
ES_SALUD_DEPENDENCIA – Path	COLUMN NAME	ES_SALUD_DEPENDENCIA
ES_SALUD_DEPENDENCIA – List	KNOWN VALUES	ES_SALUD_DEPENDENCIA
ES_SALUD_LABORAL – Path	COLUMN NAME	ES_SALUD_LABORAL
ES_SALUD_LABORAL – List	KNOWN VALUES	ES_SALUD_LABORAL
ES_SALUD_REPRODUCTIVA – Path	COLUMN NAME	ES_SALUD_REPRODUCTIVA
ES_SALUD_MENTAL – Path	COLUMN NAME	ES_SALUD_MENTAL
ES_FIN_HISTORIAL_CREDITICIO – Path	COLUMN NAME	ES_FIN_HISTORIAL_CREDITICIO
ES_FIN_DEUDA – Path	COLUMN NAME	ES_FIN_DEUDA
ES_FIN_DEUDA – Type	DATA TYPE	ES_FIN_DEUDA
ES_FIN_INGRESOS – Path	COLUMN NAME	ES_FIN_INGRESOS
ES_FIN_INGRESOS – Type	DATA TYPE	ES_FIN_INGRESOS
ES_FIN_PATRIMONIO – Path	COLUMN NAME	ES_FIN_PATRIMONIO
ES_FIN_PATRIMONIO – Type	DATA TYPE	ES_FIN_PATRIMONIO
ES_FIN_PENSION – Path	COLUMN NAME	ES_FIN_PENSION
ES_FIN_PENSION – Type	DATA TYPE	ES_FIN_PENSION
ES_FIN_PRESTACION_SOCIAL – Path	COLUMN NAME	ES_FIN_PRESTACION_SOCIAL
ES_FIN_PRESTACION_SOCIAL – List	KNOWN VALUES	ES_FIN_PRESTACION_SOCIAL

CLASSIFIER	KIND	DOMAIN
ES_FIN_TRIBUTARIO – Path	COLUMN NAME	ES_FIN_TRIBUTARIO
ES_PENAL_ANTECEDENTES – Path	COLUMN NAME	ES_PENAL_ANTECEDENTES
ES_PENAL_DELITOS_SEXUALES – Path	COLUMN NAME	ES_PENAL_DELITOS_SEXUALES
ES_PENAL_DELITOS_SEXUALES – List	KNOWN VALUES	ES_PENAL_DELITOS_SEXUALES
ES_PENAL_PROCEDIMIENTO – Path	COLUMN NAME	ES_PENAL_PROCEDIMIENTO
ES_PENAL_PROCEDIMIENTO – Regex	VALUE FORMAT	ES_PENAL_PROCEDIMIENTO
ES_PENAL_SANCION_ADMINISTRATIVA – Path	COLUMN NAME	ES_PENAL_SANCION_ADMINISTRATIVA